

dedication (optional)

Summary

Write your summary here...

Preface

Write your preface here...

Table of Contents

Summary	i
Preface	ii
Table of Contents	iv
List of Tables	v
List of Figures	vii
Abbreviations	viii
1 Introduction	1
1.1 Background and motivation	1
1.2 Previous work	1
1.3 Goal of thesis	2
1.4 Layout of thesis	2
1.5 Figures	2
1.6 References	2
1.7 Tables	3
2 Background Theory	5
2.1 Path planing	5
2.1.1 Straight lines	5
2.1.2 Interpolation	5
2.1.3 Dubins path	5
2.2 GPS	5
2.2.1 RTKGPS	5
3 Real time kinematic GPS	7
3.1 Differential GPS	7
3.2 Interger Ambiguity Resolution	7
3.2.1 Search space minimization strategies	7
3.3 Error sources	7
3.3.1 Clock error	7
3.3.2 Ionospheric and Trophospheric Delays	7
3.3.3 Ephemeris Errors (maa leses om; se foiler?)	8
3.3.4 Multipath	8

4	System Components	9
4.1	Software	9
4.1.1	Dune	9
4.1.2	Netpus	9
4.1.3	Ardupilot	9
4.1.4	RTKGPS	9
4.2	Physical system	9
4.2.1	x8 with all components	9
5	Experimental testing	11
5.1	SIL testing	11
5.2	Physical testing	11
5.2.1	Fly test	11
5.2.2	GPS test	11
6	Conclusion and Discussion	13
	Bibliography	15
	Appendix	17

List of Tables

1.1 Table 1. 3

List of Figures

1.1 Pikachu. 3

Abbreviations

Symbol = definition

Introduction

1.1 Background and motivation

Unmanned aerial vehicles (UAVs) have long been used by the military, but is now becoming increasingly more popular in the civilian sector. UAVs is a cheaper alternative in some situation like . Today manned helicopters and aircraft in jobs like aerial photography, and large area inspections. That increase the cost of such operation, and have the limitation that aircraft and helicopter mostly needs an airport to operate from. UAVs do not have the same limitation. A fixed wing drone can be launched from a catapult, and can be design such that it do not need a runway to land.

UAVs are predicted to be more applied in the industry. In the maritime sector they can be used in iceberg management, monitoring of oil spills, search and rescue and maritime traffic monitoring.

UAV operations from ship is considered more challenging compared to land operation. Launching UAV from a maritime platform can be done with a catapult, witch is a common way to launch UAV even on land. However, landing the UAV poses several problems. A ship has usally limited space, and if it's not design as an aircraft carrier landing on the deck is not an option. Existing system today relay on a net placed somewhere on the ship that caches the UAV. The problem with this solution is that it requires a guiding system either on the ship or in the UAV to hit the net.

Talk some about GPS system. It is nesesity to enable the UAV to land

Today UAVs are mostly used on land, but the possibility to apply them in maritime sector is something that are being develop. Fixed wing UAVs has the advantages that they can cover huge areas, compared to unmanned helicopters. The drawback of fixed wing is the recovery phase. There exist landing system, but they are limited to a few UAVs, and expensive to install (need reference). UAVs can be used to track icebergs or applied in search and rescue.

What is the problem with flying from a ship

A automatic recovery system for UAV on a ship would over time remove the need of a pilot on-board the ship. (maybe in emergency) could ask about that.

How should this thesis help solve that problem

This project theises is about implement and test a nett landing system using RTK-GPS for position measurement.

1.2 Previous work

On the landing subject: The UAV lab community; direct link to Frlich work.

1.3 Goal of thesis

Implement a automatic landing system on a x8 fixed wing UAV, and safely land it in a net.

1.4 Layout of thesis

```
\begin{eqnarray}\label{eq1}  
F = m \times a  
\end{eqnarray}
```

This will produce

$$F = m \times a \quad (1.1)$$

To refer to the equation

```
\eqref{eq1}
```

This will produce (1.1).

1.5 Figures

To create a figure

```
\begin{figure}[h!]  
  \centering  
  \includegraphics[width=0.5\textwidth]{fig/pikachu}  
  \caption{Pikachu.}  
  \label{fig1}  
\end{figure}
```

To refer to the figure

```
\textbf{Fig. \ref{fig1}}
```

This will produce **Fig. 1.1**

1.6 References

To cite references

```
\cite{1,2,3}
```

or

```
\citep{1,2,3}
```

This will produce: Sarma and Chen (2008); Brouwer and Jansen (2004); Muskat (1937)
or (Sarma and Chen, 2008; Brouwer and Jansen, 2004; Muskat, 1937), respectively.



Figure 1.1: Pikachu.

1.7 Tables

To creat a table

```
\begin{table}[!h]
\begin{center}
\begin{tabular}{c|c|c|c|c}
\hline
\textbf{No.} & \textbf{Data 1} & \textbf{Data 2} & \textbf{Data 3} & \textbf{Data 4} \\
\hline
1 & a1 & b1 & c1 & d1 \\
2 & a2 & b2 & c2 & d2 \\
\hline
\end{tabular}
\end{center}
\caption{Table 1.}
\label{Tab1}
\end{table}
```

This will produce

No.	Data 1	Data 2
1	a1	b1
2	a2	b2

Table 1.1: Table 1.

To refer to the table

```
\textbf{Table. \ref{Tab1}}
```

This will produce **Table. 1.1.**

Background Theory

In this chapter outline path planing and position measurement.

2.1 Path planing

How to find a way, follow a path, geeing from A to B or simply hitting something. When a system is required to find a way, follow a path, moving from A to B or moving toward something it need to plan a path. The path can have different requirements such as limitation on deviation from path, speed requirement or time requirement. Also it might be that a straight line is not an option. This thiess will focus on the path following part of path planning. The path is given by several wayponits that represent a end of a straight line. En figur an WP hadde vrt fint her.

2.1.1 Straight lines

2.1.2 Interpolation

2.1.3 Dubins path

Include a figure that show dubins path. Might use plots from assignment 3 i Guidance and Control. Same in the two previous subsections.

2.2 GPS

Basic on how a GPS works. Also write about error sources and method to estimate position.

2.2.1 RTKGPS

Real time kinematic GPS

This chapter outline the basic on how RTKGPS works. It's assumed that the reader is familiar with how a single GPS receiver works. The first section give a brief summary on what differential GPS is, and how that principle is applied in RTK-GPS. The two following sections is directly used in RKT-GPS(maybe write some more). The last section give a quick overview over the error sources that effect the measurement.

3.1 Differential GPS

Differential GPS consist of at least two receivers, where one is called a base station and the rest rovers. The two receivers are within range of a communication channel over which they are communicating. There are two basic ways to implement DGPS. There is the position-space method and the range-space method. Only the latter will be covered in this thesis.

3.2 Interger Ambiguity Resolution

3.2.1 Search space minimization strategies

3.3 Error sources

Link the error source to where they originate

3.3.1 Clock error

There is drift in both the satellite clock and the receiver clock. The satellite clock drift is smaller, because the clock is an atomic clock. The receiver clock error can be relative large. The satellite clock error given in the satellite message.

3.3.2 Ionospheric and Trophospheric Delays

Effect of signals travelling through the atmosphere. Free electrons from ultraviolet rays ionize a portion of gas molecules. These influence electromagnetic wave propagation.

Trophospheric: clody weather, rain or sun

3.3.3 Ephemeris Errors (maa leses om; se foiler?)

3.3.4 Multipath

Chapter 4

System Components

4.1 Software

4.1.1 Dune

4.1.2 Netpus

4.1.3 Ardupilot

4.1.4 RTKGPS

4.2 Physical system

4.2.1 x8 with all components

Experimental testing

5.1 SIL testing

5.2 Physical testing

5.2.1 Fly test

5.2.2 GPS test

Chapter 6

Conclusion and Discussion

Bibliography

- Brouwer, D. R., Jansen, J. D., 2004. Dynamic optimization of waterflooding with smart wells using optimal control theory. *SPE Journal* 9 (4), 391–402.
- Muskat, M., 1937. *Flow of Homogeneous Fluids*. McGraw Hill.
- Sarma, P., Chen, W. H., 2008. Applications of optimal control theory for efficient production optimization of realistic reservoirs. In: *Proceedings of the International Petroleum Technology Conference*. Kuala Lumpur, Malaysia.

Appendix

Write your appendix here...