



Home Cameras Lenses Accessories Cables Monitors Recorder All Manufacturers Illumination
More Email Us



[View Larger Image \(in new window\)](#)

Point Grey : FL2-1453C-C

By: [Point Grey](#)



CCD and CMOS Cameras

[Wholesale Price Request](#)

[Large Quantities, OEM & Scheduled Orders](#)

[Current Customer Reordering](#)

[Please Send Product Specifications](#)

Contact us for lowest price (800) 284-2288, (858) 565-1101, sales@avsupply.com, or fax (858) 565-7845

Point Grey 1/2" CCD; color; 1384 x 1032; 15 fps; C-mount

Description

Specifications

Resources / Documents

Resolution	1384 x 1032
Frame Rate	15 FPS
Megapixels	1.4 MP
Chroma	Color
Sensor Name	Sony ICX267
Sensor Type	CCD
Readout Method	Global shutter
Sensor Format	1/2"
Pixel Size	4.65 µm
Lens Mount	C-mount
ADC	12-bit
Gain Range	0 dB to 24 dB
Exposure Range	0.02 ms to >10 seconds
Trigger Modes	Standard, bulb, skip frames, multi-exposure preset, overlapped, multi-shot
Partial Image Modes	Pixel binning, ROI
Image Processing	Gamma, lookup table, hue, saturation, and sharpness
User Sets	3 memory channels for custom camera settings
Opto-isolated I/O Ports	1 input, 1 output
Non-isolated I/O Ports	2 bi-directional
Serial Port	1 (over non-isolated I/O)
Auxiliary Output	3.3 V, 150 mA maximum
Interface	FireWire 1394b
Power Requirements	8 to 30 V
Power Consumption (Maximum)	<2.5 W
Dimensions	29 mm x 29 mm x 30 mm

Currently Offline

Mass	58 grams
Machine Vision Standard	IIDC v1.31
Compliance	CE, FCC, KCC, RoHS
Temperature (Operating)	0° to 45°C
Temperature (Storage)	-30° to 60°C
Humidity (Operating)	20 to 80% (no condensation)
Humidity (Storage)	20 to 95% (no condensation)
Warranty	3 years

© 1996 - 2019 | All Rights Reserved

Audio Video Supply Inc.

4575 Ruffner St

San Diego, CA 92111

[Privacy Policy](#)

Prices and specifications subject to change without notice.

Call Now **1-800-284-2288**
Email Us **Sales@ausupply** 
   

Currently Offline