Proposal for Master Thesis: One Two

Masters Thesis in Mechatronics Kristian Gonzalez, September 2019

A thesis submitted in partial fulfillment of the requirements for the degree of Master of Science (M.Sc.).

Supervisor: Prof. Dr. Wolfgang Ertel

Ravensburg-Weingarten University of Applied Sciences

Co-supervisor: Prof. Dr. Stefan Elser

Ravensburg-Weingarten University of Applied Sciences

1 Introduction

Computer vision is a field that has grown explosively in the last few years, very much in thanks to the utilization of Convolutional Neural Networks, or CNN's, to accurately identify different kinds of information from raw image data. This capability has led to many different subfields of research, including 3D localization of objects using a variety of sensor setups. To that end, a few questions naturally arise: how many sensors are needed to accurately locate objects, and what tradeoffs exist for using more or less sensors? To that end, a paper is proposed to seek out a comparison between two specific sensor setups. The first sensor setup would use only camera data, and a derived stereo disparity image, to detect and localize the desired object of interest, specifically cars. The second sensor setup would use a single camera and a single lidar to perform the same task. The nature of the detection required would be a 3D bounding box, expressed as a box with real-world distances to describe an object's relative x, y, and z coordinates as well as its height, width, and length. The dataset that would be used for this task is not yet confirmed, but is currently one out of several possibilities:

- The KITTI dataset (3D detection task)
- Oxford RobotCar dataset (3D detection task)
- ???
- ???-2

Each of these possible datasets will be expanded upon below, describing their merits and drawbacks.

2 Literature Search Questions

There are multiple questions to answer regarding what is possible in this project. To that end, a literature search is underway to answer:

- What is the state of the art in current stereo vision-based object detection?
- What is the state of the art in current camera/lidar-based object detection?

- What dataset meets the required criteria for usage in this project? A dataset must have rgb data, stereo data or the ability to generate it, lidar data, and 3D bounding boxes.
- How are 3D bounding boxes evaluated, and what standard is used to obtain a score, such as precision, recall, and average precision?

2.1 State of the Art: Stereo-Based Object Detection

TextHere

2.2 State of the Art: Camera/Lidar-Based Object Detection

TextHere

2.3 Valid Datasets, and the Most Qualified to be Used

TextHere

2.4 3D Bounding Box Evaluation

TextHere

3 Project Schedule / Timeline

In order to meet all requirements while also satisfying educational program requirements, a proposed timeline is provided below. Notable dates here include the official start of the thesis, the final date of the thesis, including presentation and document turn-in.




Figure 1: Proposed schedule of paper. Highlighted tasks are critical milestones. Numbers inside of gray cells indicate the number of weeks each individual task lasts.

3.1 Same Problem but Different Solution

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, At accusam aliquyam diam diam dolore dolores duo eirmod eos erat, et nonumy sed tempor et et invidunt justo labore Stet clita ea et gubergren, kasd magna no rebum. sanctus sea sed takimata ut vero voluptua. est

Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur

4 Conclusion

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Curabitur augue dui, lacinia quis gravida sit amet, dignissim at justo. Pellentesque posuere, tellus id facilisis iaculis, purus nisi convallis purus, in dignissim risus sapien porta velit. Vivamus mauris lorem, facilisis eget luctus eu, sagittis sed erat. Suspendisse pulvinar semper feugiat. Praesent interdum magna orci, molestie efficitur nisi finibus vel. Vestibulum ut porta nibh, non condimentum nisl.