t46

GOTPM-CPL

(PSC3)

Technical Reference Manual

Hybrid PM + Tree Cosmological
N-Body Simulation Code with
CPL Dark Energy Support

Juhan Kim

2026

Based on the GOTPM algorithm (Dubinski et al. 2004)

https://github.com/kjhan0606/GOTPM-CPL

Contents

I Getting Started

1 Introduction . . . 7
1.1 Key Features . . . 7
1.2 Algorithm Overview . . . 7

2 Quick Start Guide . . . 9
2.1 Prerequisites . . . 9
2.2 Building the Code . . . 9
2.3 Setting Up a Run . . . 9
2.3.1 Directory Structure . . . 9
2.3.2 Parameter File . . . 10
2.3.3 Input Power Spectrum . . . 10
2.3.4 Job Submission (SLURM) . . . 10

II Code Architecture

3 Parameter Reference . . . 13
3.1 Cosmological Parameters . . . 13
3.2 Simulation Control . . . 13
3.3 Grid and Particle Setup . . . 14
3.4 Power Spectrum and Normalization . . . 14
3.5 I/O Parameters . . . 14

4 Compile-Time Flags . . . 15
4.1 Required Flags . . . 15
4.2 Optional Flags . . . 15

5 Data Structures . . . 17
5.1 Particle Types . . . 17
5.1.1 PM Particle (`pmparticletype`) . . . 17
5.1.2 Tree Particle (`treeparticletype`) . . . 17
5.1.3 Position Reconstruction Macros . . . 18
5.2 Simulation Parameters (`SimParameters`) . . . 18
5.3 Memory Management . . . 18

6 Source File Reference . . . 21
6.1 Core Simulation Loop . . . 21

6.2 Initial Conditions 21
6.3 Force Calculation 22
6.4 Domain Decomposition and Migration 22
6.5 Cosmology and Analysis 22
6.6 I/O and Utilities 23
6.7 Header Files 23

III Algorithms

7 Initial Conditions 27
7.1 Zel'dovich Approximation (1st-Order LPT) 27
7.2 2nd-Order LPT 27

8 PM Force Calculation 29
8.1 TSC Mass Assignment 29
8.2 FFT-Based Poisson Solver 29
8.3 4th-Order FDA 29
8.4 Variable PM (VarPM) 30

9 Tree Force Correction 31
9.1 Cell-Linked-List Construction 31
9.2 Force Evaluation 31
9.3 Type Conversion 31

10 Time Integration 33
10.1 Leap-Frog Scheme 33
10.2 Half-Step Synchronization 33

11 Cosmology: CPL Dark Energy 35
11.1 CPL Parameterization 35
11.2 Expansion History 35
11.3 Growth Factor 35
11.4 Poisson Correction 35

12 Domain Decomposition and Migration 37
12.1 Slab Decomposition 37
12.2 Particle Migration 37
12.3 Load Balancing 37

IV Reference

13 Troubleshooting 41
13.1 Common Issues 41
13.1.1 Segfault in Tree Correction 41
13.1.2 Malloc Error (Extremely Large Allocation) 41
13.1.3 Power Spectrum File Not Found 41
13.2 Performance Tuning 41

14 Example: CPL Dark Energy Simulation 43
14.1 Parameter File 43
14.2 Compilation 44
14.3 Execution 44
14.4 Expected Output 44

ish

Getting Started

1 Introduction

GOTPM-CPL (Grid-of-Oct-Tree Particle Mesh), also referred to as PSC3 (Parallel Simulation Code 3), is a massively parallel cosmological N-body simulation code that computes the gravitational evolution of dark matter particles in an expanding universe. The code implements the hybrid TreePM algorithm: long-range forces are computed on a uniform mesh using FFT-based Poisson solvers (PM), while short-range corrections are applied through a Barnes–Hut-type tree walk.

1.1 Key Features

- **Hybrid TreePM force calculation** — PM for long-range + Tree for short-range correction
- **CPL dark energy models** — Full support for the Chevallier–Polarski–Linder parameterization $w(a) = w_0 + w_a(1-a)$, including Poisson correction factors
- **2LPT initial conditions** — Built-in 2nd-order Lagrangian perturbation theory for accurate IC generation
- **MPI + OpenMP parallelization** — Slab domain decomposition with hybrid parallelism
- **Variable PM grid (VarPM)** — Adaptive z-domain boundaries for load balancing
- **Index-based position encoding** — High-precision particle positions via displacement + Lagrangian index
- **Custom memory allocator** — Stack-based pool allocator for deterministic memory management
- **Friends-of-Friends (FoF)** — Built-in parallel group finder
- **Power spectrum measurement** — On-the-fly $P(k)$ computation with TSC deconvolution

1.2 Algorithm Overview

The simulation proceeds through the following steps at each time step:

1. **PM force** — Assign particle mass to grid via TSC, solve Poisson equation in Fourier space, interpolate forces back to particles (4th-order FDA).
2. **Tree correction** — Build cell-linked-list, compute short-range force corrections using spline-softened gravity with opening angle θ.
3. **Velocity kick** — Update velocities using leap-frog integration.
4. **Position drift** — Advance particle positions.
5. **Migration** — Exchange particles between MPI domains if they have crossed slab boundaries.
6. **Domain rebalancing** — Adjust slab boundaries if load imbalance exceeds threshold.

Important

The code uses a *split-step* (leap-frog) integrator where velocities and positions are offset by half a time step. The `halfstep` structure controls the synchronization of positions and velocities for output.

2 Quick Start Guide

This chapter provides a step-by-step guide to building and running the code.

2.1 Prerequisites

- **Intel C/Fortran Compilers** — `mpiicx` and `mpiifx` (or `mpiicc/mpiifort`)
- **FFTW3** — Single-precision with MPI and OpenMP thread support (`libfftw3f`, `libfftw3f_mpi`, `libfftw3f_omp`)
- **MPI** — Intel MPI or OpenMPI
- **OpenMP** — Enabled via `-qopenmp`

2.2 Building the Code

Build Commands

```
cd PSC3_CPL_mv_new
# Edit Rules.make for your system (compiler, FFTW path, NMEG)
make clean
make this
# Produces: namu.exe
```

The build system consists of two files:

- `Rules.make` — System-specific compiler settings, library paths, and compile flags.
- `Makefile` — Object file list and build targets.

> The primary target compiler is Intel `mpiicx/mpiifx`. For PGI or GCC compilers, use the corresponding `Rules.make.*` variant (e.g., `Rules.make.pgcc`).

2.3 Setting Up a Run

2.3.1 Directory Structure

Create a separate run directory:

Run Directory Setup

```
mkdir MV_0m0.31_-1.2_-2.4
cd MV_0m0.31_-1.2_-2.4
ln -s ../PSC3_CPL_mv_new/namu.exe .
```

```
cp ../PSC3_CPL_mv_new/params.dat .
# Edit params.dat for your cosmological model
```

2.3.2 Parameter File

Edit `params.dat` to specify cosmological parameters, grid resolution, and run settings. See Chapter 3 for the full parameter reference.

2.3.3 Input Power Spectrum

Prepare an ASCII power spectrum file (e.g., from CAMB) with two columns: k [h/Mpc] and $P(k)$ [$(\mathrm{Mpc}/h)^3$]. Set `Powerflag = 2` and provide the filename in `Ascii Powerfile`.

2.3.4 Job Submission (SLURM)

Example SLURM Job Script

```
#!/bin/bash
#SBATCH --job-name=MV311224
#SBATCH --ntasks=16
#SBATCH --cpus-per-task=4
#SBATCH --time=1000000:00
#SBATCH --output outfile.o%j.grammar
#SBATCH --error errfile.e%j.grammar
#SBATCH -p normal

export OMP_NUM_THREADS=$SLURM_CPUS_PER_TASK
srun ./namu.exe params.dat
```

Choosing MPI Ranks and Threads

The number of MPI ranks (`ntasks`) determines the z-slab decomposition. The FFTW3 domain decomposition requires that N_z is divisible by the number of MPI ranks. Each rank spawns `cpus-per-task` OpenMP threads for shared-memory parallelism within the tree correction and TSC assignment.

II

Code Architecture

3 Parameter Reference

The simulation is controlled by the ASCII parameter file `params.dat`, which is read by rank 0 and broadcast to all MPI processes.

3.1 Cosmological Parameters

Parameter	Default	Description
`OmegaMatter0`	—	Present-day matter density Ω_m
`OmegaBaryon0`	—	Present-day baryon density Ω_b
`OmegaLambda0`	—	Present-day dark energy density Ω_Λ
`Hubble`	—	Hubble parameter $h = H_0/(100\ \mathrm{km/s/Mpc})$
`nPS`	—	Scalar spectral index n_s
`w0 of DE (CPL)`	-1	CPL equation of state w_0
`wa of DE (CPL)`	0	CPL evolution parameter w_a
`Sound Speed of DE`	0	Dark energy sound speed ($c_s^2 = 0$: clustering, 1: smooth)
`fNL`	0	Local non-Gaussianity amplitude
`gNL`	0	Higher-order non-Gaussianity

3.2 Simulation Control

Parameter	Default	Description
`INITIAL CONDITION`	—	1 = Zeldovich approximation, 2 = 2LPT
`Amax`	—	Maximum scale factor $a_{\max}$ (typically 48 for $z_i = 47$)
`Anow`	1	Starting scale factor
`Astep`	—	Scale factor increment per time step Δa
`Nstep`	—	Total number of time steps
`Stepcount`	1	Starting step count (for restart)
`Stepnum`	1	Step number to begin integration
`Theta`	0.3	Tree opening angle (overridden adaptively)
`Iseed`	—	Random seed for IC generation

3.3 Grid and Particle Setup

Parameter	Default	Description
`Nx, Ny, Nz`	—	PM grid dimensions (must be equal: $N_x = N_y = N_z$)
`Nspace`	1	Grid spacing in index units
`Boxsize(Mpc/h)`	—	Comoving box size in Mpc/h

3.4 Power Spectrum and Normalization

Parameter	Default	Description
`Powerflag`	—	0: generate on run, 1: CAMB binary, 2: ASCII file
`Ascii Powerfile`	—	Filename of input power spectrum
`ampRescaling flag`	0	0: none, 1: rescale to σ_8 at $z = 0$, 2: at z_{CMB}
`bias8`	1	Inverse of σ_8 for $R = 8$ Mpc$/h$

3.5 I/O Parameters

Parameter	Default	Description
`rvfilename`	—	Input RV data filename (for restart)
`rvprefix`	—	Output file prefix

4 Compile-Time Flags

The code behavior is controlled by preprocessor flags set in `Rules.make`.

4.1 Required Flags

Flag	Description
`-DINTEL`	Select Intel compiler conventions (main function name). Required for `mpiicx`.
`-DINDEX`	Enable particle index tracking. Each particle stores its Lagrangian grid index for high-precision position reconstruction.
`-DXYZDBL`	Use double-precision position reconstruction via $X = \mathrm{fmod}(x_{\mathrm{disp}} + x_{\mathrm{index}}, N_x)$. Must be paired with `-DINDEX`.
`-DINCLUDE_TREE_FORCE`	Enable tree force corrections on top of PM forces.

4.2 Optional Flags

Flag	Description
`-DNMEG=`*N*`L`	Memory pool size per MPI rank in megabytes (default: 100). Example: `-DNMEG=8000L` allocates 8 GB per rank.
`-DWGROUPSIZE=`*N*	I/O write group size for parallel output (default: 80).
`-DVarPM`	Enable variable-width PM domain decomposition. Allows non-uniform z-slab widths for load balancing.
`-DSAVESLICE`	Save x-z density slices at each time step.
`-DPMSEEDFORCE`	Use PM seed force for initial force evaluation.
`-DMPI_SLOW`	Use slower but more reliable MPI communication patterns.
`-DDEMODEL=0`	Constant Poisson correction factor (default).
`-DDEMODEL=1`	Scale-dependent Poisson correction (for k-dependent DE).
`-DMULTIMASS`	Support for multi-mass particles (adds `mass` field).
`-DINDTIME`	Individual time-stepping support (adds `tflag` field).
`-D_LARGE_FILES`	Enable large file support for I/O.

Example 4.1 (Standard Compilation)

A typical compilation command (via `Rules.make`):

```
CDFLAGS = -DWGROUPSIZE=80 -DNMEG=8000L -DINCLUDE_TREE_FORCE
    \
          -D_LARGE_FILES -DSAVESLICE -DPMSEEDFORCE
COMFLAGS = -DINDEX -DVarPM -DXYZDBL -DMPI_SLOW
OPT = -DINTEL -O2 -qopenmp
```

5 Data Structures

5.1 Particle Types

The code uses two particle structures that share the same memory through pointer casting. This is the core of the hybrid PM+Tree design.

5.1.1 PM Particle (`pmparticletype`)

Definition 5.1 (pmparticletype — 32 bytes)

```
typedef struct pmparticletype {
    float x, y, z;          /* displacement from index
        position */
    float vx, vy, vz;       /* peculiar velocity */
    long long indx;         /* Lagrangian grid index */
} pmparticletype;
```

The PM particle stores only displacement and velocity. The true position is reconstructed via:

$$X = \mathrm{fmod}\Big(x_{\mathrm{disp}} + (\mathrm{indx} \bmod m_x) + N_x,\ N_x\Big)$$

where $m_x = N_x/N_{\mathrm{space}}$. This encoding preserves sub-grid precision even for $N \geq 1024^3$.

5.1.2 Tree Particle (`treeparticletype`)

Definition 5.2 (treeparticletype — 40 bytes)

```
typedef struct treeparticletype {
    float x, y, z;
    float vx, vy, vz;
    long long indx;
    struct treeparticletype *next;  /* linked-list pointer
        */
} treeparticletype;
```

Extends `pmparticletype` with a `next` pointer for the cell-linked-list tree structure. The conversion between the two types is done in-place via backward copy (`pm2treetype`) and forward copy (`tree2pmtype`).

Important

The in-place conversion between `pmparticletype` and `treeparticletype` requires careful handling because both pointers alias the same memory. The code uses `memmove` through `char*` pointers to avoid strict-aliasing violations that can cause data corruption at `-O2` optimization.

5.1.3 Position Reconstruction Macros

```
/* With -DXYZDBL -DINDEX: */
#define XofP(p) fmod((double)((p)->x) + (double)(((p)->indx %
    simpar.mx)) + simpar.nx, simpar.nx)
#define YofP(p) fmod((double)((p)->y) + (double)((((p)->indx %
     simpar.mxmy) / simpar.mx)) + simpar.ny, simpar.ny)
#define ZofP(p) fmod((double)((p)->z) + (double)(((p)->indx /
    simpar.mxmy)) + simpar.nz, simpar.nz)
```

5.2 Simulation Parameters (`SimParameters`)

Definition 5.3 (SimParameters struct)

The global `simpar` structure holds all runtime parameters:

- **MPI identity**: `myid`, `nid`
- **Cosmology**: `omep` (Ω_m), `omeplam` (Ω_Λ), `wlam0` (w_0), `wlam1` (w_a), `CsDE` (sound speed)
- **Grid**: `nx`, `ny`, `nz`, `mx`, `my`, `mz`, `mxmy`
- **Scale factors**: `amax`, `anow`, `astep`
- **Force**: `theta` (opening angle), `pcorr` (Poisson correction)
- **Domain**: `local_nz`, `local_z_start`, `zmin`, `zmax`

5.3 Memory Management

Definition 5.4 (Stack-Based Memory Pool)

The code allocates a single large memory block at startup (`NMEG` megabytes) and manages sub-allocations through a stack-based allocator defined in `Memory2.c`:

- `Malloc(size, PPTR(var))` — Push allocation onto stack
- `Free(ptr)` — Pop or compact stack
- `Realloc(ptr, size)` — Resize with automatic compaction of subsequent allocations
- `freespace()` — Query available memory

The allocator tracks each allocation's size, starting address, and a pointer-to-pointer back-reference, enabling automatic pointer updates when memory is compacted.

The header `Memory.h` defines:

```
#define Realloc(A,B) Realloc(A,B,PPTR(A))
```

> This macro automatically supplies the third argument (pointer-to-pointer), so user code simply calls `Realloc(ptr, newsize)`.

6 Source File Reference

6.1 Core Simulation Loop

File	Description
`main.c`	Entry point. Initializes MPI/FFTW, reads `params.dat`, dispatches to `Zeldovich()` or `SecondOrderLPT()`.
`namu.zeldovich.c`	Main simulation driver for Zeldovich IC. Defines global variables (`DEFINE_SIM_PARA`, `DEFINE_PM_COMMON`, etc.), time integration loop, and type conversion functions (`pm2treetype`, `tree2pmtype`).
`namu.2lpt.c`	Main simulation driver for 2LPT IC. Similar structure to `namu.zeldovich.c` with 2nd-order displacement fields.
`treemain.c`	Tree correction driver. Calls `pm2treetype`, `treecorrection`, `PreFoF`, then `tree2pmtype`.
`pmmain.c`	PM force driver. TSC density assignment, forward FFT, Poisson solve, backward FFT, 4th-order FDA force interpolation.
`dumpmain.c`	Output controller. Triggers snapshot writes when positions and velocities are synchronized.

6.2 Initial Conditions

File	Description
`TwoLPT.F`	2nd-order LPT potential computation in Fourier space. Computes the $\phi^{(2)}$ kernel terms.
`TwoOrderLPT.F`	Converts LPT potentials to particle displacements and velocities.
`addTwoOrderLPT.c`	Applies 2nd-order displacement to particle positions.
`ZeldovichInit.F`	1st-order (Zeldovich) displacement and velocity fields.
`addZeldovichInit.c`	Applies Zeldovich displacement to particles.
`FindSeed.F`	Parallel random number seed initialization.
`sub.lynx.camb.F`	CAMB power spectrum reader and interpolator. Handles fNL non-Gaussianity.

6.3 Force Calculation

File	Description
`tsc.c` / `tsc_omp2.c`	Triangular Shaped Cloud (TSC) mass assignment with OpenMP.
`fft.c`	FFTW3-MPI wrapper for forward/backward transforms. Thread-safe initialization.
`pm_main_sub_fftw3.F`	Low-level FFTW3 workspace management routines.
`p_solver.F`	Poisson solver in Fourier space. Applies $\tilde{\phi}(k) = -\tilde{\rho}(k)/k^2$.
`fda4.c`	4th-order Finite Difference Approximation for force interpolation from grid to particles.
`VarPM.c`	Variable-resolution PM: TSC and FDA with non-uniform z-slab widths.
`Treewalk.c`	Barnes–Hut tree construction and traversal. Builds linked-list octree with opening angle criterion.
`kjhtpm.mod1.gpu.omp.c`	Tree force correction with OpenMP. Cell-linked-list construction (`ParticleCellLinkedList`) and force evaluation (`treecorrection`).
`force_spline.c`	Spline-softened gravitational force kernel.
`pcorr.c`	Poisson correction factor for CPL dark energy models.

6.4 Domain Decomposition and Migration

File	Description
`pmigrate.kisti.omp.c`	MPI particle migration between z-slabs. Handles periodic boundaries and bulk transfer.
`mydomaindecomposition.omp.c`	Adaptive load balancing. Adjusts z-slab boundaries when load imbalance exceeds 1%.
`slicemigrate.c`	FFT data migration between non-uniform and uniform z-slab layouts.
`determine_mpi_misc_param.c`	Computes FFTW3 domain layout parameters (`local_nz`, `local_z_start`).

6.5 Cosmology and Analysis

File	Description
`FLRW.F`	Friedmann equation solver. Growth factors for ΛCDM, quintessence, and CPL models. Functions: `growth()`, `growthcpl()`, `cplOmegaMatter()`, `HofEz()`, `PoissonCor()`.

File	Description
NR.F	Numerical Recipes: Simpson integration (qsimp), Romberg integration (qromo), ODE solver (odeint).
correl.F	On-the-fly power spectrum measurement with TSC window deconvolution.
PreFoF.mod2.omp.c	Parallel Friends-of-Friends group finder preparation (ghost exchange).

6.6 I/O and Utilities

File	Description
kjhrw.c	Parallel binary I/O for particle snapshots (read/write).
header.c	ASCII parameter file reader/writer.
flagwriting.c	Output scheduling: determines when to trigger data writes based on scale factor, step count, and flag files.
Memory2.c	Stack-based memory pool allocator.
timerutil.c	Wall-clock timer utilities.
indexing.c	Particle-to-Lagrangian-grid index mapping.

6.7 Header Files

File	Description
pmheader.h	Particle structures (pmparticletype, treeparticletype), SimParameters, position macros (XofP, YofP, ZofP), timer macros.
pm_common.h	Global PM variables: np, pmparticles, treeparticles, den, work.
flow.h	Evolution factors (EvolFact), half-step structure, output flag function declarations.
Memory.h	Memory allocator API and the Realloc macro.
varpm.h	Variable PM function declarations and NZBound structure.
common_simparam.h	Legacy common-block-style simulation parameters.
fortran.h	C–Fortran interface macros and FFTW/MPI includes.
kjhtree.h	Tree structure definitions.
force_spline.h	Spline kernel function declarations.

III

Algorithms

7 Initial Conditions

7.1 Zel'dovich Approximation (1st-Order LPT)

The Zel'dovich approximation displaces particles from a uniform grid according to the linear displacement field:

$$\mathbf{x}(\mathbf{q},a) = \mathbf{q} - \frac{D_1(a)}{a}\nabla\phi^{(1)}(\mathbf{q}) \tag{7.1}$$

where $\mathbf{q}$ is the Lagrangian coordinate (stored as `indx`), $D_1(a)$ is the linear growth factor, and $\phi^{(1)}$ is the gravitational potential from the linear density field.

The velocity is:

$$\mathbf{v} = \dot{a}\mathbf{x} - a\dot{D}_1\nabla\phi^{(1)} \tag{7.2}$$

7.2 2nd-Order LPT

The 2LPT adds a second-order correction:

$$\mathbf{x}(\mathbf{q},a) = \mathbf{q} - D_1(a)\Psi^{(1)}(\mathbf{q}) + D_2(a)\Psi^{(2)}(\mathbf{q}) \tag{7.3}$$

where $D_2 \approx -\frac{3}{7}D_1^2$ for $\Omega_m = 1$, and

$$\nabla^2\phi^{(2)} = \sum_{i>j}\left(\phi^{(1)}_{,ii}\phi^{(1)}_{,jj} - (\phi^{(1)}_{,ij})^2\right) \tag{7.4}$$

The 2LPT initial conditions are significantly more accurate than Zel'dovich for moderate-to-high redshift starts ($z_i \sim 50$).

Algorithm 7.1 (IC Generation)

1. Generate Gaussian random field $\delta(\mathbf{k})$ using input $P(k)$ and random seed.
2. Compute 1st-order potential: $\tilde{\phi}^{(1)}(\mathbf{k}) = -\tilde{\delta}(\mathbf{k})/k^2$.
3. (2LPT only) Compute 2nd-order source and potential $\phi^{(2)}$.
4. Assign displacements and velocities to particles on a uniform grid.
5. Migrate particles to their correct MPI domains.

8 PM Force Calculation

8.1 TSC Mass Assignment

The Triangular Shaped Cloud scheme assigns particle mass to the $3^3 = 27$ nearest grid points using a quadratic spline window:

$$W_{\mathrm{TSC}}(x) = \begin{cases} \frac{3}{4} - x^2 & |x| \leq \frac{1}{2} \\ \frac{1}{2}\left(\frac{3}{2} - |x|\right)^2 & \frac{1}{2} < |x| \leq \frac{3}{2} \\ 0 & |x| > \frac{3}{2} \end{cases} \tag{8.1}$$

The density field is:

$$\rho(\mathbf{x}_g) = \frac{m_p}{\Delta x^3} \sum_p W_{\mathrm{TSC}}(\mathbf{x}_g - \mathbf{x}_p) \tag{8.2}$$

The implementation in `tsc_omp2.c` uses OpenMP parallelization with thread-local density arrays to avoid race conditions.

8.2 FFT-Based Poisson Solver

Algorithm 8.1 (PM Force Pipeline)

1. **Density field** $\rho(\mathbf{x})$ computed via TSC.
2. **Forward FFT**: $\tilde{\rho}(\mathbf{k}) = \quad [\rho]$ using FFTW3-MPI (`fft.c`).
3. **Poisson solve**: $\tilde{\phi}(\mathbf{k}) = -\tilde{\rho}(\mathbf{k})/k^2$ (`p_solver.F`).
4. **Dark energy correction**: $\tilde{\phi} \to p_{\mathrm{corr}}(a) \cdot \tilde{\phi}$ for CPL models.
5. **Backward FFT**: $\phi(\mathbf{x}) = \quad ^{-1}[\tilde{\phi}]$.
6. **Force interpolation**: 4th-order FDA gives $\mathbf{F} = -\nabla\phi$ at particle positions (`fda4.c`).

8.3 4th-Order FDA

The force at grid point i is:

$$F_i = \frac{1}{12\Delta x}\left(-\phi_{i+2} + 8\phi_{i+1} - 8\phi_{i-1} + \phi_{i-2}\right) \tag{8.3}$$

This requires padding the potential mesh by 3 slices below and 4 slices above the local domain, handled by `paddingpotentialmesh()` in `VarPM.c`.

8.4 Variable PM (VarPM)

With `-DVarPM` enabled, each MPI rank can own a non-uniform number of z-slabs. The z-domain boundaries (`zmin`, `zmax`) adapt to balance particle counts. The TSC and FDA routines accept variable z-boundaries and convert between the local variable-width domain and the global uniform FFTW layout via `tsc_fftw_mesh()` in `VarPM.c`.

9 Tree Force Correction

9.1 Cell-Linked-List Construction

The tree correction uses a cell-linked-list rather than a full octree. In `ParticleCellLinkedList()` (`kjhtpm.mod1.gpu.omp.c`):

1. Divide the local domain into cells of width ~ 4 grid spacings.
2. Assign each particle to its cell using integer truncation of position.
3. Build a linked list through the `next` pointer of `treeparticletype`.

Particle positions near domain boundaries can produce out-of-range cell indices. The code clamps indices to valid range:

```
if(ix < 0) ix = 0;   if(ix >= mxm1) ix = mxm1;
if(iy < 0) iy = 0;   if(iy >= mym1) iy = mym1;
if(iz < 0) iz = 0;   if(iz >= mzm1) iz = mzm1;
```

9.2 Force Evaluation

For each particle, the tree correction computes the short-range gravitational force from nearby particles using a spline-softened kernel. The opening angle criterion θ determines whether to use a cell's center of mass or open it:

$$\frac{\ell}{r} < \theta \quad \Rightarrow \quad \text{use cell monopole} \tag{9.1}$$

where ℓ is the cell size and r is the particle–cell distance. The opening angle is adaptively adjusted during the simulation:

```
if(stepcount < 10)        theta = 0.3;
else if(stepcount < 20)   theta = 0.35;
else if(stepcount < 60)   theta = 0.4;
else                      theta = 0.45;
```

9.3 Type Conversion

Before tree correction, particles are expanded in-place from 32-byte `pmparticletype` to 40-byte `treeparticletype` (`pm2treetype`), and shrunk back afterward (`tree2pmtype`).

Algorithm 9.1 (pm2treetype — In-Place Expansion)

1. `Realloc` the particle array to $N_p \times 40$ bytes.
2. Copy backwards (from last particle to first) using `memmove` to avoid overwriting:

```
for(i = nplong-1; i >= 0; i--) {
    memmove((char*)treeparticles + i*sizeof(
        treeparticletype),
            (char*)pmparticles + i*sizeof(pmparticletype
                ),
            sizeof(pmparticletype));
}
```

3. The `next` pointer (last 8 bytes) is left uninitialized and set during linked-list construction.

10 Time Integration

10.1 Leap-Frog Scheme

The code uses a kick-drift-kick leap-frog integrator where the scale factor a advances by a fixed step Δa:

$$v_{n+1/2} = v_n + \frac{\Delta a}{2}\dot{v}_n \quad \text{(kick)} \tag{10.1}$$

$$x_{n+1} = x_n + \Delta a\, v_{n+1/2} \quad \text{(drift)} \tag{10.2}$$

$$v_{n+1} = v_{n+1/2} + \frac{\Delta a}{2}\dot{v}_{n+1} \quad \text{(kick)} \tag{10.3}$$

The velocity factors `fact1` and `fact2` encode the cosmological dependence:

$$\ddot{a} = -\frac{4\pi}{3}\left(\frac{1}{a^2} + (1+3w)\frac{\Omega_\Lambda}{\Omega_m}\frac{f_{\mathrm{DE}}(a)}{a^3}\right) \tag{10.4}$$

computed by `appapsq()` in `FLRW.F`.

10.2 Half-Step Synchronization

The `halfstep` structure controls when positions and velocities are synchronized (both at the same time level) for output:

- `halfstep.first = 1, second = 0`: First half-step (velocity kick only).
- `halfstep.first = 1, second = 1`: Second half-step (complete the full step).

  This is triggered by output flags (`flagsyncpdata`) and the PreFoF group finder.

11 Cosmology: CPL Dark Energy

11.1 CPL Parameterization

The equation of state for dark energy is parameterized as:

$$w(a) = w_0 + w_a\,(1 - a/a_{\max}) \tag{11.1}$$

where $a_{\max}$ is the maximum scale factor. The standard ΛCDM model corresponds to $w_0 = -1$, $w_a = 0$.

11.2 Expansion History

The Hubble parameter $H(a)$ in a flat universe:

$$H^2(a) = H_0^2 \left[\Omega_m \left(\frac{a_{\max}}{a}\right)^3 + (1 - \Omega_m - \Omega_\Lambda) \left(\frac{a_{\max}}{a}\right)^2 + \Omega_\Lambda\, f_{\rm DE}(a) \right] \tag{11.2}$$

where

$$f_{\rm DE}(a) = \left(\frac{a}{a_{\max}}\right)^{-3(1+w_0+w_a)} \exp\left[-3w_a \left(1 - \frac{a}{a_{\max}}\right)\right] \tag{11.3}$$

is the dark energy scaling function, implemented as `scaleDE()` in `FLRW.F`.

11.3 Growth Factor

The matter growth factor $D_+(a)$ satisfies:

$$\ddot{D}_+ + 2H\dot{D}_+ = \frac{3}{2}\Omega_m(a)\,H^2\,C_w(a)\,D_+ \tag{11.4}$$

where $C_w(a) = 1 + (1+w)\,\Omega_{\rm DE}(a)/\Omega_m(a)$ encodes the dark energy clustering. This is solved numerically via the RK4 integrator in `growthcpl()` with the `odeint` driver from Numerical Recipes.

11.4 Poisson Correction

For dark energy models with clustering ($c_s = 0$), the Poisson equation is modified:

$$\nabla^2\phi = 4\pi G\,\bar{\rho}_m\,\delta_m\,p_{\rm corr}(a) \tag{11.5}$$

where

$$p_{\rm corr}(a) = 1 + \frac{\Omega_{\rm DE}(a)\, D_{\rm DE}(a)}{\Omega_m(a)\, D_m(a)} \tag{11.6}$$

This correction is computed at each time step by `PoissonCor()` in `FLRW.F` and applied in `pmmain.c`.

For smooth dark energy ($c_s = 1$), $p_{\rm corr} = 1$ (no clustering correction).

12 Domain Decomposition and Migration

12.1 Slab Decomposition

The simulation box is divided into N_{rank} slabs along the z-axis. Each MPI rank owns a contiguous range of z-coordinates $[z_{\min}, z_{\max})$. This aligns with the FFTW3-MPI data layout, which distributes the first (z) dimension across ranks.

12.2 Particle Migration

After positions are updated, particles that have moved outside their domain are exchanged via `migrate()` in `pmigrate.kisti.omp.c`:

Algorithm 12.1 (Particle Migration)

1. Scan all local particles; classify as staying, moving up, or moving down.
2. Send "up" particles to rank+1, receive from rank−1 (periodic).
3. Send "down" particles to rank−1, receive from rank+1 (periodic).
4. Compact local array and append received particles.
5. If multi-slab migration is needed, repeat for larger shifts.

12.3 Load Balancing

The domain rebalancer in `mydomaindecomposition.omp.c` monitors the particle count ratio:

$$R = \frac{N_{\max} - N_{\min}}{N_{\text{avg}}} \times 100\% \tag{12.1}$$

If $R > 1\%$ (the `MAXINHOMO` threshold), z-slab boundaries are adjusted so each rank holds approximately equal numbers of particles.

IV

Reference

13 Troubleshooting

13.1 Common Issues

13.1.1 Segfault in Tree Correction

Symptom: Crash in `treecorrection()` or `ParticleCellLinkedList()`.

Possible causes:

1. **Strict aliasing violation in** `pm2treetype`: At `-O2`, the compiler may reorder reads/writes of `pmparticles[i]` and `treeparticles[i]` because they are different types. The fix is to use `memmove` through `char*` pointers.
2. **Out-of-bounds cell index**: Particles near domain boundaries can produce negative or overly large cell indices. Ensure clamping is applied.
3. **Insufficient memory**: If `NMEG` is too small, the `Realloc` in `pm2treetype` fails.

13.1.2 Malloc Error (Extremely Large Allocation)

Symptom: "Error allocating memory N bytes in Malloc()" where N is petabytes.

Cause: OpenMP clamping bug. Check that the y and z index limits use `mym1`/`mzm1` (not `mxm1`) in `ParticleCellLinkedList()`.

13.1.3 Power Spectrum File Not Found

Ensure the `Ascii Powerfile` path in `params.dat` is relative to the run directory, not the source directory.

13.2 Performance Tuning

- **NMEG**: Set large enough to hold all particles plus FFT workspace. Rule of thumb: NMEG $\geq 40 \times N_p^{1/3}$ MB per rank for N_p total particles.
- **MPI vs OpenMP balance**: Use fewer MPI ranks with more threads per rank to reduce communication overhead. Typically 4–8 threads per rank.
- **Opening angle θ**: Larger values are faster but less accurate. The adaptive scheme (0.3–0.45) is a good default.

14 Example: CPL Dark Energy Simulation

This chapter walks through a complete simulation with CPL parameters $\Omega_m = 0.31$, $w_0 = -1.2$, $w_a = -2.4$.

14.1 Parameter File

params.dat

```
#Start of the Ascii Header of the GOTPM Simulation
define INITIAL CONDITION    = 2
define OmegaMatter0         = 0.31
define OmegaBaryon0         = 0.044
define OmegaLambda0         = 0.69
define Hubble               = 0.72
define nPS                  = 0.96
define Boxsize(Mpc/h)       = 1024
define w0 of DE (CPL)       = -1.2
define wa of DE (CPL)       = -2.4
define Sound Speed of DE    = 0
define Amax                 = 48
define Anow                 = 1
define Astep                = 0.025
define Nx                   = 1024
define Ny                   = 1024
define Nz                   = 1024
define Nspace               = 1
define Theta                = 0.3
define Nstep                = 1881
define Stepcount            = 1
define Stepnum              = 1
define Iseed                = -56
define Powerflag            = 2
define Ascii Powerfile      = camb.z=47_0.31_-1.2_-2.4.ascii
define rvfilename           = INITIAL
define rvprefix             = INITIAL
#End of Ascii Header
```

14.2 Compilation

Rules.make Settings

```
CC = mpiicx
FC = mpiifx
OPT = -DINTEL -O2 -qopenmp
CDFLAGS = -DWGROUPSIZE=80 -DNMEG=8000L -DINCLUDE_TREE_FORCE \
          -D_LARGE_FILES -DSAVESLICE -DPMSEEDFORCE
COMFLAGS = -DINDEX -DVarPM -DXYZDBL -DMPI_SLOW
FFTWDIR = /home/kjhan/local/
```

14.3 Execution

With 16 MPI ranks and 4 OpenMP threads per rank (64 cores total):

```
export OMP_NUM_THREADS=4
srun --ntasks=16 --cpus-per-task=4 ./namu.exe params.dat
```

14.4 Expected Output

The simulation starts at $z = 47$ ($a = 1$) and evolves to $z = 0$ ($a = 48$) in 1881 steps. Key output messages:

- `Poisson Correction factor X at anow = Y` — Dark energy correction at each step.
- `CPU(F-FFTW3)` and `CPU(B-FFTW3)` — Forward/backward FFT timing.
- `Treecorrectingtime CPU= X` — Tree force correction timing.
- `Step N CPU= X` — Total time per step.