





# Making Maps





**CHOROPLETHS**













# 2016 Electoral Vote




## Land Owned or Administered by the US Federal Government

Main Purpose or Type      National Park, Preserve or Wilderness Area      Public Domain Land      Military Use      Lake      Other




Kieran Healy / [kieranhealy.org](http://kieranhealy.org)  
Source: USGS Federal Lands map layer


## Land Owned or Administered by the US Federal Government







# Land Owned or Administered by the US Federal Government



## Primary Administrator

- Bureau of Land Management
- Forest Service
- Dept of Defense
- Park Service
- Bureau of Reclamation
- Dept of Energy
- Fish and Wildlife Service
- Other



# US STATE-LEVEL ELECTION DATA

```
election %>% select(state, total_vote,  
                      r_points, pct_trump, party, census) %>%  
sample_n(5)
```

```
## # A tibble: 5 x 6  
##       state total_vote r_points pct_trump      party    census  
##       <chr>     <dbl>     <dbl>      <dbl>      <chr>    <chr>  
## 1 New Jersey   3906723    -13.99     41.0 Democrat Northeast  
## 2 Nevada        1125385     -2.42     45.5 Democrat      West  
## 3 Virginia      3982752     -5.32     44.4 Democrat       South  
## 4 Pennsylvania   6166710      0.71     48.2 Republican Northeast  
## 5 Vermont        315067    -26.41     30.3 Democrat Northeast
```

```
## Hex color codes for Dem Blue and Rep Red
party_colors <- c("#2E74C0", "#CB454A")





p0 <- ggplot(data = subset(election, st %in% "DC"),
               mapping = aes(x = r_points,
                             y = reorder(state, r_points),
                             color = party))

p1 <- p0 + geom_vline(xintercept = 0, color = "gray30") +
  geom_point(size = 2)

p2 <- p1 + scale_color_manual(values = party_colors)

p3 <- p2 + scale_x_continuous(breaks = c(-30, -20, -10, 0, 10, 20, 30, 40),
                               labels = c("30\n(Clinton)", "20", "10", "0",
                                         "10", "20", "30", "40\n(Trump)"))

p4 <- p3 + facet_wrap(~ census, nrow=1, scales="free_y") +
  guides(color=FALSE) + labs(x = "Point Margin", y = "") +
  theme(axis.text=element_text(size=8))
```




Point Margin

```

library(ggforce)

p3 + facet_col(~ census,
               scales = "free_y",
               space = "free") +
guides(color=FALSE) +
labs(x = "Point Margin", y = "") +
theme(axis.text=element_text(size=8))

```



```
library(maps)
us_states <- map_data("state")
head(us_states)


##      long     lat group order   region subregion
## 1 -87.4620 30.3897     1     1 alabama       <NA>
## 2 -87.4849 30.3725     1     2 alabama       <NA>
## 3 -87.5250 30.3725     1     3 alabama       <NA>
## 4 -87.5308 30.3324     1     4 alabama       <NA>
## 5 -87.5709 30.3267     1     5 alabama       <NA>
## 6 -87.5881 30.3267     1     6 alabama       <NA>

dim(us_states)


## [1] 15537      6
```

```
p <- ggplot(data = us_states, aes(x = long, y = lat, group = group))
```


```
p + geom_polygon(fill = "white", color = "black")
```



```
p <- ggplot(data = us_states, aes(x = long, y = lat, group = group, fill = region))  
  
p + geom_polygon(color = "gray70", size = 0.2) + guides(fill = FALSE)
```



UTM Zone 11N  
EPSG:2955




Mercator  
EPSG:3857



U.S. National Atlas  
Equal Area  
EPSG:2163





```
p <- ggplot(data = us_states, aes(x = long, y = lat,  
                                    group = group, fill = region))  
  
p + geom_polygon(color = "gray70", size = 0.2) +  
  coord_map(projection = "albers", lat0 = 39, lat1 = 45) +  
  guides(fill = FALSE)
```

Many other projections  
are available

lat

50

45

40

35

30


25

-120

-100

-80

long



```
election$region <- tolower(election$state)  
us_states_elec <- left_join(us_states, election)
```


Don't do this part blindly.  
Be aware of the variables/  
keys you are merging/  
joining the data on and  
why you are doing it.

<https://github.com/kjhealy/fips-codes>

state.name	state.abbr	long.name	fips	sumlev	region	division	state	region.name	division.name
Alabama	AL	Alabama AL	1	40	3	6	1	South	East South Central
Alaska	AK	Alaska AK	2	40	4	9	2	West	Pacific
Arizona	AZ	Arizona AZ	4	40	4	8	4	West	Mountain
Arkansas	AR	Arkansas AR	5	40	3	7	5	South	West South Central
California	CA	California CA	6	40	4	9	6	West	Pacific

Some helper CSV files

```
p <- ggplot(data = us_states_elec,  
             aes(x = long, y = lat,  
                  group = group, fill = party))  
  
p + geom_polygon(color = "gray70", size = 0.2) +  
  coord_map(projection = "albers", lat0 = 39, lat1 = 45)
```



```
theme_map <- function(base_size=9, base_family="") {  
  require(grid)  
  theme_bw(base_size=base_size, base_family=base_family) %>replace%  
  theme(axis.line=element_blank(),  
        axis.text=element_blank(),  
        axis.ticks=element_blank(),  
        axis.title=element_blank(),  
        panel.background=element_blank(),  
        panel.border=element_blank(),  
        panel.grid=element_blank(),  
        panel.spacing=unit(0, "lines"),  
        plot.background=element_blank(),  
        legend.justification = c(0,0),  
        legend.position = c(0,0)  
  )  
}
```


```
p0 <- ggplot(data = us_states_elec, aes(x = long, y = lat,
                                         group = group, fill = party))

p1 <- p0 + geom_polygon(color = "gray70", size = 0.2) +
  coord_map(projection = "albers", lat0 = 39, lat1 = 45)

p2 <- p1 + scale_fill_manual(values = party_colors) +
  labs(title = "Election Results 2016", fill = NULL)


p2 + theme_map()
```

# Election Results 2016



```
p0 <- ggplot(data = us_states_elec, aes(x = long, y = lat,  
                                         group = group, fill = pct_trump))  
  
p1 <- p0 + geom_polygon(color = "gray70", size = 0.2) +  
      coord_map(projection = "albers", lat0 = 39, lat1 = 45)  
  
p2 <- p1 + labs(title = "Trump vote")  
  
p2 + theme_map() + labs(fill = "Percent")
```

# Trump vote




```
p0 <- ggplot(data = us_states_elec, aes(x = long, y = lat,
                                         group = group, fill = pct_trump))

p1 <- p0 + geom_polygon(color = "gray70", size = 0.2) +
  coord_map(projection = "albers", lat0 = 39, lat1 = 45)


p2 <- p1 + scale_fill_gradient(low = "white", high = "#CB454A") +
  labs(title = "Trump vote")
p2 + theme_map() + labs(fill = "Percent")
```

# Trump vote



```
p0 <- ggplot(data = us_states_elec, aes(x = long, y = lat,  
                                         group = group, fill = d_points))  
  
p1 <- p0 + geom_polygon(color = "gray70", size = 0.2) +  
      coord_map(projection = "albers", lat0 = 39, lat1 = 45)  
  
p2 <- p1 + scale_fill_gradient2() + labs(title = "Winning margins")  
p2 + theme_map() + labs(fill = "Percent")
```

# Winning margins




```
p0 <- ggplot(data = us_states_elec, aes(x = long, y = lat,
                                         group = group, fill = d_points))

p1 <- p0 + geom_polygon(color = "gray70", size = 0.2) +
  coord_map(projection = "albers", lat0 = 39, lat1 = 45)

p2 <- p1 + scale_fill_gradient2(low = "red",
                                 mid = scales::muted("purple"),
                                 high = "blue",
                                 breaks = c(-25, 0, 25, 50, 75)) +
  labs(title = "Winning margins")
p2 + theme_map() + labs(fill = "Percent")
```

## Winning margins




```
p0 <- ggplot(data = subset(us_states_elec,
                           region %nin% "district of columbia"),
               aes(x = long, y = lat, group = group, fill = d_points))

p1 <- p0 + geom_polygon(color = "gray70", size = 0.2) +
  coord_map(projection = "albers", lat0 = 39, lat1 = 45)

p2 <- p1 + scale_fill_gradient2(low = "red",
                                 mid = scales::muted("purple"),
                                 high = "blue") +
  labs(title = "Winning margins")
p2 + theme_map() + labs(fill = "Percent")
```

# Winning margins



**US COUNTIES**

<http://eric.clst.org/Stuff/USGeoJSON>

County choropleths are conceptually identical to state ones. The tables are just bigger, because there are way more lines to draw.

<http://eric.clst.org/Stuff/USGeoJSON>

**County files in USGeoJSON format, at  
varying resolutions**

# AMERICA'S UR-CHOROPLETHS

```
county_map %>% sample_n(10)
```

```
##          long      lat order  hole piece group     id
## 162407    602940 -1598728 162407 FALSE      1 0500000US48351.1 48351
## 128954    262762   138691 128954 FALSE      1 0500000US38077.1 38077
## 128454    -83454   255783 128454 FALSE      1 0500000US38065.1 38065
## 987       1150231 -1429721     987 FALSE      1 0500000US01025.1 01025
## 154248    902190 -1014238 154248 FALSE      1 0500000US47157.1 47157
## 4261     -1458767 -2381708    4261 FALSE      1 0500000US02013.1 02013
## 160533    571407 -1586804 160533 FALSE      1 0500000US48241.1 48241
## 180058   -1752450   400802 180058 FALSE      1 0500000US53069.1 53069
## 183904    1758330 -497820 183904 FALSE      1 0500000US54071.1 54071
## 71658     836958 -1549129    71658 FALSE      1 0500000US22037.1 22037
```

```
county_data %>%
  select(id, name, state, pop_dens, pct_black) %>%
  sample_n(10)
```

##	id	name	state	pop_dens	pct_black
## 954	20095	Kingman County	KS	[ 0, 10)	[ 0.0, 2.0)
## 1968	37085	Harnett County	NC	[ 100, 500)	[15.0,25.0)
## 356	12051	Hendry County	FL	[ 10, 50)	[10.0,15.0)
## 2674	48211	Hemphill County	TX	[ 0, 10)	[ 0.0, 2.0)
## 2821	48505	Zapata County	TX	[ 10, 50)	[ 0.0, 2.0)
## 2971	51580	Covington city	VA	[ 1000, 5000)	[10.0,15.0)
## 2248	41001	Baker County	OR	[ 0, 10)	[ 0.0, 2.0)
## 1644	30035	Glacier County	MT	[ 0, 10)	[ 0.0, 2.0)
## 2844	49041	Sevier County	UT	[ 10, 50)	[ 0.0, 2.0)
## 2932	51133	Northumberland County	VA	[ 50, 100)	[25.0,50.0)


```
county_full <- left_join(county_map, county_data, by = "id")

p <- ggplot(data = county_full,
             mapping = aes(x = long, y = lat,
                           fill = pop_dens,
                           group = group))

p1 <- p + geom_polygon(color = "gray70", size = 0.1) + coord_equal()

p2 <- p1 + scale_fill_brewer(palette="Blues",
                               labels = c("0-10", "10-50", "50-100",
                                             "100-500", "500-1,000",
                                             "1,000-5,000", ">5,000"))


p2 + labs(fill = "Population per\nsquare mile") + theme_map() +
  guides(fill = guide_legend(nrow = 1)) +
  theme(legend.position = "bottom")
```



Population per  
square mile

0-10	10-50	50-100	100-500	500-1,000	1,000-5,000	>5,000
------	-------	--------	---------	-----------	-------------	--------

```
p <- ggplot(data = county_full,  
             mapping = aes(x = long, y = lat,  
                           fill = pct_black,  
                           group = group))  
  
p1 <- p + geom_polygon(color = "gray70", size = 0.1) + coord_equal()  
  
p2 <- p1 + scale_fill_brewer(palette="Greens")  
  
p2 + labs(fill = "US Population, Percent Black") +  
  guides(fill = guide_legend(nrow = 1)) +  
  theme_map() + theme(legend.position = "bottom")
```



```
orange_pal <- RColorBrewer::brewer.pal(n = 6, name = "Oranges")
orange_pal
```


```
## [1] "#FEEDDE" "#FDD0A2" "#FDAE6B" "#FD8D3C" "#E6550D"
## [6] "#A63603"
```

```
orange_rev <- rev(orange_pal)
orange_rev
```

```
## [1] "#A63603" "#E6550D" "#FD8D3C" "#FDAE6B" "#FDD0A2"
## [6] "#FEEDDE"
```

```
gun_p <- ggplot(data = county_full,  
                  mapping = aes(x = long, y = lat,  
                                 fill = su_gun6,  
                                 group = group))  
  
gun_p1 <- gun_p + geom_polygon(color = "gray70", size = 0.1) + coord_equal()  
  
gun_p2 <- gun_p1 + scale_fill_manual(values = orange_pal)  
  
gun_p2 + labs(title = "Gun-Related Suicides, 1999-2015",  
               fill = "Rate per 100,000 pop.") +  
  theme_map() +  
  theme(legend.position = "bottom")
```

## Gun-Related Suicides, 1999-2015




Rate per 100,000 pop.


[0, 4)	[4, 7)	[7, 8)	[10, 12)
[8, 10)	[12, 54]		

```
pop_p <- ggplot(data = county_full,  
                  mapping = aes(x = long, y = lat,  
                                 fill = pop_dens6,  
                                 group = group))  
  
pop_p1 <- pop_p + geom_polygon(color = "gray70", size = 0.1) + coord_equal()  
  
pop_p2 <- pop_p1 + scale_fill_manual(values = orange_rev)  
  
pop_p2 + labs(title = "Reverse-coded Population Density",  
               fill = "People per square mile") +  
  theme_map() +  
  theme(legend.position = "bottom")
```

Reverse-coded Population Density




Gun-Related Suicides, 1999-2015



Rate per 100,000 pop.


[ 0, 4)	[ 7, 8)	[10,12)
[ 4, 7)	[ 8,10)	[12,54]

Reverse-coded Population Density



People per square mile

[ 0, 9)	[ 25, 45)	[ 82, 215)
[ 9, 25)	[ 45, 82)	[215,71672]



<http://kieranhealy.org/canada.r>

[http://kieranhealy.org/gcd\\_000b11a\\_e.zip](http://kieranhealy.org/gcd_000b11a_e.zip)

# SMALL MULTIPLES FOR MAPS

```
head(opiates)
```


```
## # A tibble: 6 x 10
##   Year     State FIPS Deaths Population Crude Adjusted
##   <int>    <chr> <int>  <int>      <int>  <dbl>    <dbl>
## 1 1999 Alabama     1      37  4430141  0.8     0.8
## 2 1999 Alaska      2      27  624779   4.3     4.0
## 3 1999 Arizona     4     229  5023823  4.6     4.7
## 4 1999 Arkansas    5      28  2651860  1.1     1.1
## 5 1999 California   6     1474 33499204  4.4     4.5
## 6 1999 Colorado     8      164 4226018   3.9     3.7
## # ... with 3 more variables: Adjusted.se <dbl>,
## #   Region <ord>, Abbr <chr>
```

```
opiates$region <- tolower(opiates$State)
```

```
opiates_map <- left_join(us_states, opiates)
```

```
p0 <- ggplot(data = opiates_map,  
              aes(x = long, y = lat,  
                  group = group,  
                  fill = cut_interval(Adjusted, n = 5)))  
  
p1 <- p0 + geom_polygon(color = "lightblue", size = 0.2) +  
      coord_map(projection = "albers", lat0 = 39, lat1 = 45)  
  
p2 <- p1 + scale_fill_brewer(type = "seq", palette = "Oranges")  
  
p2 + theme_map() + facet_wrap(~ Year, ncol = 3) +  
    guides(fill = guide_legend(nrow = 1)) +  
    theme(legend.position = "bottom",  
          strip.background = element_blank()) +  
    labs(fill = "Death rate per 100,000 population",  
         title = "Opiate Related Deaths by State, 1999-2014")
```

### Opiate Related Deaths by State, 1999-2014




Death rate per 100,000 population [0.76, 8.88] (8.88, 13.1] (13.1, 19.2] (19.2, 25.4] (25.4, 31.6] NA

**Is your data really spatial?**

```
p0 <- ggplot(data = opiates,  
               mapping = aes(x = Year, y = Adjusted))
```

```
p1 <- p0 + geom_line(color = "gray85",  
                      mapping = aes(group = State))
```




```
p2 <- p1 + geom_smooth(mapping = aes(group = Region),  
                      se = FALSE)
```

```
p3 <- p2 + geom_text_repel(data = subset(opiates,
                                         Year == max(Year) & Abbr != "DC"),
                           mapping = aes(x = Year, y = Adjusted, label = Abbr),
                           size = 1.8, segment.color = NA, nudge_x = 30) +
coord_cartesian(c(min(opiates$Year),
                  max(opiates$Year)))
```


```
p3 + labs(x = "", y = "Rate per 100,000 population",
           title = "State-Level Opiate Death Rates by Region, 1999-2014") +
  facet_wrap(~ reorder(Region, Adjusted, na.rm = TRUE), nrow = 1)
```

# State-Level Opiate Death Rates by Region, 1999-2014


Midwest




South



Northeast



West



# **SIMPLE FEATURES AND geom\_sf()**

r-spatial.org

r-spatial.github.io/sf/

walkerke.github.io/tidycensus

Tidy data +

Simple features spec +

Direct support in ggplot

```
install.packages("sf")
```

```
install.packages("drat")
```

```
drat::addRepo("kjhealy")
```

```
install.packages("nycdogs")
```


```
library(sf)
```

```
library(nycdogs)
```

```
devtools::install_github("kjhealy/nycdogs")
```

# nycdogs

The `nycdogs` package contains three datasets, `nyc_license`, `nyc_bites`, and `nyc_zips`. They contain, respectively, data on all licensed dogs in New York city, data on reported dog bites in New York city, and geographical data for New York city at the zip code level.



## Installation

`nycdogs` is a data package, bundling several datasets into a convenient format. The relatively large size of the data in the package means it is not suitable for hosting on CRAN, the core R package repository. There are two ways to install it.

### Install direct from GitHub

You can install the beta version of `nycdogs` from GitHub with:

```
devtools::install_github("kjhealy/nycdogs")
```

### Installation using `drat`

While using `install_github()` works just fine, it would be nicer to be able to just type `install.packages("nycdogs")` or `update.packages("nycdogs")` in the ordinary way. We can do this using Dirk Eddelbuettel's `drat` package. Drat provides a convenient way to make R aware of package repositories other than CRAN.

# Dogs of New York

`nyc_license`

```
#> # A tibble: 122,203 x 14
#>   animal_name animal_gender animal_birth_mo... breed_rc borough zip_code
#>   <chr>       <chr>           <date>          <chr>      <chr>      <int>
#> 1 Shadow       M              2000-01-01     Beagle    Brookl...  11236
#> 2 Rocco        M              2011-10-01     Boxer     Brookl...  11210
#> 3 Luigi         M              2005-09-01     Maltese   Bronx    10464
#> 4 Petunia      F              2013-08-01     Pug       Brookl...  11221
#> 5 Romeo         M              2008-10-01     Maltese   Bronx    10451
#> 6 Brandy        M              2004-01-01     Unknown   Brookl...  11225
#> 7 Sam            M              2011-05-01     Pug       Manhat...  10021
#> 8 May            F              2004-05-01     Unknown   Staten...  10305
#> 9 Ruby            F              2010-04-01     Boxer     Brookl...  11220
#> 10 Leo           M              2014-01-01    Beagle    Bronx    10468
#> # ... with 122,193 more rows, and 8 more variables:
#> #   community_district <dbl>, census_tract2010 <dbl>, nta <chr>,
#> #   city_council_district <dbl>, congressional_district <dbl>,
#> #   state_senatorial_district <dbl>, license_issued_date <date>,
#> #   license_expired_date <date>
```

# Zip Codes of New York

```
> nyc_zips
Simple feature collection with 262 features and 11 fields
geometry type:  POLYGON
dimension:      XY
bbox:           xmin: -74.25576 ymin: 40.49584 xmax: -73.6996 ymax: 40.91517
epsg (SRID):   4326
proj4string:    +proj=longlat +datum=WGS84 +no_defs
# A tibble: 262 x 12
  objectid zip_code po_name state borough st_fips cty_fips bld_gpostal_code
    <int>    <int> <chr>    <chr>    <chr>    <chr>          <int>
1       1     11372 Jackson... NY    Queens    36      081            0
2       2     11004 Glen O... NY    Queens    36      081            0
3       3     11040 New Hy... NY    Queens    36      081            0
4       4     11426 Beller... NY    Queens    36      081            0
5       5     11365 Fresh ... NY    Queens    36      081            0
6       6     11373 Elmhur... NY    Queens    36      081            0
7       7     11001 Floral... NY    Queens    36      081            0
8       8     11375 Forest... NY    Queens    36      081            0
9       9     11427 Queens... NY    Queens    36      081            0
10      10    11374 Rego P... NY    Queens    36      081            0
# ... with 252 more rows, and 4 more variables: shape_leng <dbl>,
#   shape_area <dbl>, id <chr>, geometry <POLYGON [°]>
```

# Zip Codes of New York

```
> nyc_zips
```

```
Simple feature collection with 262 features and 11 fields
geometry type:  POLYGON
dimension:      XY
bbox:           xmin: -74.25576  ymin: 40.49584  xmax: -73.6996  ymax: 40.91517
epsg (SRID):   4326
proj4string:    +proj=longlat +datum=WGS84 +no_defs
# A tibble: 262 x 12
```

```
#> # ... with 252 more rows, and 4 more variables: shape_leng <dbl>,
#> #   shape_area <dbl>, id <chr>, geometry <POLYGON [°]>
```

	object_id	zip_code	post_name	state	borough	lat	lon	lat2	lon2	special_code	id
1	1	11372	Jackson...	NY	Queens	36	081			0	
2	2	11004	Glen O...	NY	Queens	36	081			0	
3	3	11040	New Hy...	NY	Queens	36	081			0	
4	4	11426	Beller...	NY	Queens	36	081			0	
5	5	11365	Fresh ...	NY	Queens	36	081			0	
6	6	11373	Elmhur...	NY	Queens	36	081			0	
7	7	11001	Floral...	NY	Queens	36	081			0	
8	8	11375	Forest...	NY	Queens	36	081			0	
9	9	11427	Queens...	NY	Queens	36	081			0	
10	10	11374	Rego P...	NY	Queens	36	081			0	

```
nyc_fb <- nyc_license %>%
  group_by(zip_code, breed_rc) %>%
  tally() %>%
  mutate(freq = n / sum(n),
        pct = round(freq*100, 2)) %>%
  filter(breed_rc == "French Bulldog")

nyc_fb
#> # A tibble: 148 x 5
#> # Groups: zip_code [148]
#>   zip_code breed_rc      n   freq   pct
#>   <int> <chr>     <int> <dbl> <dbl>
#> 1 7030 French Bulldog 1 0.5 50
#> 2 10001 French Bulldog 32 0.0354 3.54
#> 3 10002 French Bulldog 18 0.0159 1.59
#> 4 10003 French Bulldog 40 0.0259 2.59
#> 5 10004 French Bulldog 8 0.0602 6.02
#> 6 10005 French Bulldog 12 0.0415 4.15
#> 7 10006 French Bulldog 3 0.0221 2.21
#> 8 10007 French Bulldog 9 0.0437 4.37
#> 9 10009 French Bulldog 37 0.0175 1.75
#> 10 10010 French Bulldog 22 0.0191 1.91
#> # â€¢ with 138 more rows
```

```
fb_map <- left_join(nyc_zips, nyc_fb)
#> Joining, by = "zip_code"
```


# The Relative Distribution of French Bulldogs in New York City, within Zip Code

## ## NYC map theme


```
theme_nymap <- function(base_size=9, base_family="") {  
  require(grid)  
  theme_bw(base_size=base_size, base_family=base_family) %>%  
    theme(axis.line=element_blank(),  
          axis.text=element_blank(),  
          axis.ticks=element_blank(),  
          axis.title=element_blank(),  
          panel.background=element_blank(),  
          panel.border=element_blank(),  
          panel.grid=element_blank(),  
          panel.spacing=unit(0, "lines"),  
          plot.background=element_blank(),  
          legend.justification = c(0, 0),  
          legend.position = c(0.1, 0.6),  
          legend.direction = "horizontal"  
    )  
}
```

# geom\_sf() automatically understands the spatial features of your data

```
fb_map %>% ggplot(mapping = aes(fill = pct)) +  
  geom_sf(color = "gray80", size = 0.1) +  
  scale_fill_viridis_c(option = "A") +  
  labs(fill = "Percent of All Licensed Dogs") +  
  annotate(geom = "text", x = -74.145 + 0.029, y = 40.82-0.012,  
    label = "New York City's French Bulldogs", size = 6) +  
  annotate(geom = "text", x = -74.1468 + 0.029, y = 40.8075-0.012,  
    label = "By Zip Code. Based on Licensing Data", size = 5) +  
  theme_nymap() +  
  guides(fill = guide_legend(title.position = "top",  
    label.position = "bottom",  
    keywidth = 1, nrow = 1))
```




New York City's French Bulldogs  
By Zip Code. Based on Licensing Data



```
library(colorspace)
```

```
fb_map %>% ggplot(mapping = aes(fill = pct)) +  
  geom_sf(color = "gray80", size = 0.1) +  
  scale_fill_continuous_sequential(palette = "Oranges") +  
  labs(fill = "Percent of All Licensed Dogs") +  
  annotate(geom = "text", x = -74.145 + 0.029, y = 40.82-0.012,  
          label = "New York City's French Bulldogs", size = 6) +  
  annotate(geom = "text", x = -74.1468 + 0.029, y = 40.7955,  
          label = "By Zip Code. Based on Licensing Data", size = 5) +  
  theme_nymap() +  
  guides(fill = guide_legend(title.position = "top",  
                             label.position = "bottom",  
                             keywidth = 1, nrow = 1))
```


New York City's French Bulldogs  
By Zip Code. Based on Licensing Data



# New York City's French Bulldogs

By Zip Code. Based on Licensing Data

Percent of All Licensed Dogs




```
nyc_fb <- nyc_license %>%
  group_by(zip_code, breed_rc) %>%
  tally() %>%
  mutate(freq = n / sum(n),
        pct = round(freq*100, 2)) %>%
  filter(breed_rc == "French Bulldog")
```

```
> nyc_fb
# A tibble: 148 x 5
# Groups:   zip_code [148]
  zip_code breed_rc     n   freq   pct
  <int> <chr>     <int>  <dbl> <dbl>
1    7030 French Bulldog     1  0.5    50
2   10001 French Bulldog    32  0.0354  3.54
3   10002 French Bulldog    18  0.0159  1.59
4   10003 French Bulldog    40  0.0259  2.59
5   10004 French Bulldog     8  0.0602  6.02
6   10005 French Bulldog    12  0.0415  4.15
7   10006 French Bulldog     3  0.0221  2.21
8   10007 French Bulldog     9  0.0437  4.37
9   10009 French Bulldog    37  0.0175  1.75
10  10010 French Bulldog    22  0.0191  1.91
# ... with 138 more rows
```

## New York City's French Bulldogs By Zip Code. Based on Licensing Data

Percent of All Licensed Dogs

Percent Range	Color
1%	Lightest Beige
2%	Very Light Orange
3%	Light Orange
4%	Medium Orange
5%	Dark Orange
6%	Dark Red



# The Relative Distribution of French Bulldogs in New York City, by Zip Code

```
library(colorspace)

nyc_fb <- nyc_license %>%
  group_by(zip_code, breed_rc) %>%
  tally() %>%
  ungroup() %>%
  complete(zip_code, breed_rc,
           fill = list(n = 0)) %>%
  mutate(freq = n / sum(n),
        pct = round(freq*100, 2)) %>%
  filter(breed_rc == "French Bulldog")
```

```
nyc_fb
#> # A tibble: 358 x 5
#>   zip_code breed_rc     n    freq    pct
#>   <int> <chr>     <dbl>    <dbl>   <dbl>
#> 1 121   French Bulldog 0 0      0
#> 2 1003  French Bulldog 0 0      0
#> 3 1175  French Bulldog 0 0      0
#> 4 7013  French Bulldog 0 0      0
#> 5 7030  French Bulldog 1 0.00000818 0
#> 6 7093  French Bulldog 0 0      0
#> 7 7302  French Bulldog 0 0      0
#> 8 7624  French Bulldog 0 0      0
#> 9 7675  French Bulldog 0 0      0
#> 10 8110 French Bulldog 0 0      0
#> # ... with 348 more rows
```


```
library(colorspace)
```

```
fb_map <- left_join(nyc_zips, nyc_fb)  
#> Joining, by = "zip_code"
```

```
fb_map %>% ggplot(mapping = aes(fill = pct)) +  
  geom_sf(color = "gray80", size = 0.1) +  
  scale_fill_continuous_sequential(palette = "Oranges") +  
  labs(fill = "Percent of All Licensed Dogs in the City") +  
  annotate(geom = "text", x = -74.145 + 0.029, y = 40.82-0.012,  
          label = "New York City's French Bulldogs", size = 6) +  
  annotate(geom = "text", x = -74.1468 + 0.029, y = 40.8075-0.012,  
          label = "By Zip Code. Based on Licensing Data", size = 5) +  
  theme_nymap() +  
  guides(fill = guide_legend(title.position = "top",  
                             label.position = "bottom",  
                             keywidth = 1, nrow = 1))
```

## New York City's French Bulldogs By Zip Code. Based on Licensing Data

Percent of All Licensed Dogs in the City





Percent Range	Color
0.00 - 0.01	Lightest Beige
0.01 - 0.02	Very Light Orange
0.02 - 0.03	Light Orange
0.03 - 0.04	Medium Orange
0.04 - 0.05	Dark Orange
0.05 - 0.06	Dark Red


0.00 0.01 0.02 0.03 0.04 0.05 0.06

# New York City's French Bulldogs


## By Zip Code. Based on Licensing Data



### Most Popular Names for Male Dogs in New York, by Borough




### Most Popular Names for Female Dogs in New York, by Borough




# Most Popular Names for Male Dogs in New York, by Borough

## Manhattan



## Brooklyn



Jack  
Milo  
Coco



## Staten Island

Max  
Rocky  
Charlie  
Buddy  
Bailey  
Buster  
Toby  
Cody  
Teddy  
Jake

## Bronx

Max  
Rocky  
Lucky  
Charlie  
Buddy  
Oreo  
King  
Toby  
Teddy  
Prince

Percent of All Licensed Male Dogs in Borough

