Centos7安装mysql详解

目录

安装前提: yum配置OK

参考安装教程:

https://www.cnblogs.com/shengChristine/p/9293996.html

https://www.cnblogs.com/xiaopotian/p/8196464.html

一、安装准备

1、查看是否有自带mysql

rpm -qa | grep mariadb

```
[root@yu ~]# rpm -qa | grep mysql
[root@yu ~]# _
```

2、删除语句

```
rpm -e --nodeps mariadb-libs-5.5.35-3.el7.x86_64
rpm -qa|grep -i mysql
yum -y remove mysql-community-client-5.6.38-2.el7.x86_64
```

二、开始安装

1、下载mysql的安装的包

进入到 cd /usr/local/src 目录

wget -i -c http://dev.mysql.com/get/mysql57-community-release-el7-10.noarch.rpm

2、报错: "dev.mysql.com" ,原因是解析不了这个域名,配置一下:

```
Iroot@yu /l# cat /etc/hosts
127.0.0.1 localhost localhost.localdomain localhost4 localhost4.localdomain4
192.168.121.110 yu
::1 localhost localhost.localdomain localhost6 localhost6.localdomain6
112.80.248.75 www.baidu.com
14.205.93.* mirrors.aliyun.com
137.254.60.11 dev.mysql.com
```

重新下载

```
wget -i -c http://dev.mysql.com/get/mysql57-community-release-el7-10.noarch.rpm
```

3、安装MySQL

输入以下语句:

```
yum -y install mysql57-community-release-el7-10.noarch.rpm
```

[root@yu src]# yum -y install mysql57-community-release-el7-11.noarch.rpm

杳看安装结果

yum repolist enabled | grep mysql.*

4、安装MySQL服务器

```
yum -y install mysql-community-server
```

5、启动服务器

```
systemctl start mysqld.service //启动
systemctl restart mysqld.service //重启
systemctl status mysqld.service //查看状态
```

6、查看默认密码:

```
| CrootOyu / | grep "password" /var/log/mysqld.log | 2019-12-21T01:10:32.144539Z 1 [Note] A temporary password is generated for rootOlocalhost: a0xu/zf9f 3Kp | CrootOyu / | |
```

三、登录

```
Iroot@yu /l# mysql -uroot -p
Enter password:
Welcome to the MySQL monitor. Commands end with ; or \g.
Your MySQL connection id is 6
Server version: 5.7.28
Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reservence is a registered trademark of Oracle Corporation and/or its
```

修改默认密码:

mysql> alter user 'root'@'localhost' identified by 'YUjinhua6!'; Query OK, 0 rows affected (0.00 sec)

```
mysql> show variables like 'zpasswordz';
                                          l Value
 Variable_name
 default_password_lifetime
                                         10
 disconnect_on_expired_password
                                           ON
 log_builtin_as_identified_by_password
                                           OFF
 mysql_native_password_proxy_users
                                         : OFF
                                           0
 old_passwords
 report_password
 sha256_password_auto_generate_rsa_keys | ON
 sha256_password_private_key_path
                                         | private_key.pem
 sha256_password_proxy_users
                                           OFF
 sha256_password_public_key_path
                                         l public_key.pem
| validate_password_check_user_name
                                         1 OFF
 validate_password_dictionary_file
 validate_password_length
                                         18
 validate_password_mixed_case_count
                                         1 1
 ∨alidate_password_number_count
                                         1 1
 validate_password_policy
                                         : MEDIUM
 Validate_password_special_char_count
17 rows in set (0.00 sec)
```

root用户外部ip能访问

```
mysql> flush privileges;
Query OK, 0 rows affected (0.00 sec)

mysql> create user 'root'Q'%' identified by 'YUjinhua6!';
Query OK, 0 rows affected (0.00 sec)

mysql> grant all *.* to 'root'Q'%' identified by "YUjinhua6!" with grant option;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corres
MySQL server version for the right syntax to use near '*.* to 'root'Q'%' identified by
with grant option' at line 1
mysql> grant all on *.* to 'root'Q'%' identified by "YUjinhua6!" with grant option;
Query OK, 0 rows affected, 1 warning (0.00 sec)
```