


# Power BI refreshes reinvented

Streamlining Power BI Refreshes Advanced Methods for Real-Time Refreshes

## After this session

Storage modes	Refresh operations	Partitioning	Orchestration
Understand the different storage modes in Power BI and how this relates to refreshes.	Understand which different options there are to refresh your Semantic Model manually as well as in an automated fashion.	Understand how different partitions in the data model are generated and can be triggered to refresh.	Understand how you can orchestrate your Power BI refresh and bind to other processes.



## Marc Lelijveld

Technical Evangelist | Solution Architect Macaw Netherlands









@MarcLelijveld



linkedin.com/in/MarcLelijveld



Data-Marc.com



DutchFabricUsergroup.com

**FAVORITE STUFF:** 












## What we cover today

- Refreshes?
- Incremental refresh
- High frequency refreshes & hybrid tables
- Refresh individual objects
- Orchestration & automation
- Wrap-up







Refreshes




## Understanding storage modes



Oh wait... we now also have DirectLake!





## Understanding Storage Modes

#### **Three storage modes**

- Import data cached in the model
- DirectQuery queries are submitted to the back-end data source
- Dual can act in both above storage modes, depending on query context

#### **Configuring storage modes**


- Storage modes are set on table level
- Setting storage mode to Import is an irreversible operation
- Data in DirectQuery mode cannot be displayed in the data tab



#### Caches and DirectQuery


#### **Risks of mixing storage modes**

- Avoid mismatch in results when query bits DirectQuery compared to Import
- Data cached (import) could be behind compared to DirectQuery data
- Make sure cached data is kept in sync regularly refresh!




#### Benefits to choose one or the other

- Improve query performance cache data for faster end-user performance
- Data refresh optimization no need to refresh for non-cached data
- Near-real time requirements reduce query latency when in DirectQuery mode
- Large Semantic Models choose to not import <u>certain</u> data by leveraging aggregations for example




## Different refresh operation types

Туре	What	Power BI Desktop	Power Bl Service (Interface)
Manual	Individual Table		×
	Full model		
Scheduled	Individual Table	×	×
	Full model	×	<b>✓</b>




#### Incremental refresh



## Considering incremental refresh

#### Why should you use it?

- Large data volumes
- Faster refreshes
- Resource consumption reduced (Both source & Power BI side)




#### Incremental refresh

Incremental refresh is supported for Power BI Premium, Premium per user, **Power BI Pro**, and Power BI Embedded Semantic Models.

Getting the latest data in **real time** with DirectQuery is **only supported for Power BI Premium\***, Premium per User, and Power BI Embedded Semantic Models.

\* Premium capacities = Fabric capacities



## Supported data sources


#### Data sources must be


- Structured
- Relational
- Allow query folding
- Typically SQL like sources




## Breaking up your data in partitions


- Each partition represents a time frame
- New partitions get added automatically
- Old partitions (in archive) get merged







## Configure Incremental Refresh









## Moving time frame







#### **Detect data changes**

- Even more selective refresh only that what has been changed
- Based date/time column used to identify and refresh only those days where the data has changed
- Typically, system generated dates like Modified Date Time
- Should never be the same column as your incremental periods
- The maximum value is evaluated for each partition in the incremental range to detect whether the partition should be refreshed or not





High frequency refreshes & hybrid tables




## What is high frequency?


#### Let's say real time?

- Hourly?
- Minutes?
- Seconds?

#### Or...


Just daily batches





## **Refresh limitations**


Frequency	Manual	Scheduled (via the service)
Free	Up to 8 times per day	
Pro	Up to 8 times per day	
Premium per User	Unlimited	48 times per day
Premium / Fabric Capacity	Unlimited	48 times per day



### Hybrid tables

- Live / Realtime data in Power BI
- Combines different storage modes on partition level in a single table
- Goes hand-in-hand with Incremental Refresh







## Hybrid tables

- Implementation with Incremental Refresh
- Customizable via 3rd party tooling like Tabular Editor (unsupported)

#### Limitation:


Only 1 DQ partition per table allowed.






## Hybrid tables – what challenge does it solve?


- Realtime scenarios without full tables on DQ mode
- No complex refresh mechanisms needed with partition refresh and queries over XMLA
- No more multiple tables and complex DAX to combine to achieve the same goal






### Hybrid tables – Keep in mind that...

- Premium feature
- DAX restrictions for DirectQuery apply
- Limited Power Query & DAX capabilities (due to DQ)
- Requires Large Semantic Model Format (storage) in workspace
- Performance hit on upstream data sources








Demo - configure hybrid tables and streaming data














## Can I change partition storage modes?

You cannot adjust tables with incremental refresh policies applied. However, there are other options to consider.


>	Options	
	Data View	Default
	Mode	DirectQuery
	Source Type	PolicyRange







## Refresh individual objects




## Effective refreshing

#### **Considerations**

- Refreshing the entire model takes too long with high load on sources
- Can we only refresh certain tables?
- Can we only refresh certain partitions?
- Can we use DQ tables/partitions (Hybrid Tables)

#### What do we need?

- Enhanced refresh API
- XMLA Endpoints



#### **Smaller increments**




Bind your refresh operations in Power BI to refresh operations in for example your data platform



Run smaller increments to speed up the end-to-end process




Trigger one (or multiple) selective table(s) or partition(s) at a time.



#### **Smaller increments**

Smaller increments can only be triggered to refresh via:


- Manual processing via Management Studio (or other tools)
- Power BI Enhanced Refresh API Previously known as Async refresh API
- XMLA endpoints



#### **Enhanced refresh API**

#### More granular controls

- type full / clearValues / calculate / dataonly / automatic / defragment
- Commitmode default is transactional
- maxParallism 10 max
- retryCount number of retries before failing
- objects which objects to refresh
- applyRefreshPolicy true/false whether you want to apply potential incremental refresh if configured
- effectiveDate in case of incremental refresh, this parameter overwrites the current date




#### **Enhanced refresh API**

Specify the objects to refresh

#### **POST**

https://api.powerbi.com/v1.0/myorg/groups/f089354e-8366-4e18-aea3-4cb4a3a50b48/datasets/cfafbeb1-8037-4d0c-896e-a46fb27ff229/refreshes

```
"type": "Full",
"commitMode": "transactional",
"maxParallelism": 2,
"retryCount": 2,
"objects": [
    "table": "DimCustomer",
    "partition": "DimCustomer"
    "table": "DimDate"
```




# Demo – Refresh one table or partition

#### More than refreshes


Enhanced refresh API also allows you to


- GET refresh history
- GET individual refresh details like progress or failures
- **DELETE** a running refresh




## Is the API the only option?

- Execute operations over XMLA endpoints
- Using Tabular Model Scripting Language
- More granular control using SQL Service Management Studio











## **Orchestration & Automation**

Binding refreshes to processes



#### Central E2E orchestration

- Combine pipelines from Data Platform with Power BI
- Lowest latency between source and report
- Incremental loading where possible
- Consider including backup operations for Power BI



## What to use to trigger and bind together?







## What is Semantic Link exactly?

Semantic Link is a feature in Microsoft
Fabric that allows you to connect from
Synapse Data Science Notebooks to Power
BI Semantic Models.

This feature **only** exists and works in Microsoft Fabric.







#### Semantic Link in Fabric notebooks!

Refresh your semantic models via a notebook and trigger dependent actions.

- Given Semantic Link uses the REST APIs, you can orchestrate not only your semantic model refresh, but also trigger upstream dataflows for example
- Refresh individual tables, partitions or reprocess partitions through enhanced refresh API
- Anything else what is possible with the REST API









# **Demo** – Fabric Notebooks for automation

#### Wrap up

LETS RECAP...

Refreshes can be manual or **automated** 

Incremental refresh makes your refresh more efficient


With detect data changes, further optimization can be done

Partitioning in incremental refresh should be based on functional dates

**Lower latency** by linking Power BI refreshes to other processes

Use the enhanced refresh API to trigger individual model objects

Use the toolkit of your preference for end-to-end orchestration & automation



#### Resources

#### **Setting up scheduled refreshes**

https://learn.microsoft.com/en-us/power-bi/connect-data/refresh-scheduled-refresh

#### **Configure incremental refresh**

https://learn.microsoft.com/en-us/power-bi/connect-data/incremental-refresh-configure

#### **Enhanced refresh API**

https://learn.microsoft.com/en-us/power-bi/connect-data/asynchronous-refresh

#### **Semantic Model connectivity with XMLA endpoints**


https://learn.microsoft.com/en-us/power-bi/enterprise/service-premium-connect-tools

#### **Tabular Model Scripting Language (TMSL)**

https://learn.microsoft.com/en-us/analysis-services/tmsl/tabular-model-scripting-language-tmsl-reference?view=asallproducts-allversions

#### These slides

https://github.com/marclelijveld/Slide-decks



# Thanks for attending!





#### **Marc Lelijveld**

Technical Evangelist | Architect Macaw Netherlands













@MarcLelijveld

linkedin.com/in/MarcLelijveld

Data-Marc.com



Feedback!

