Real Time Signal Processing with Symmetric and Asymmetric Support Intervals

Keven Joyce and Lia Harrington
University of Montana

May 14, 2015

Outline

Importance of Real Time Signal Processing

What is real time signal processing?

- Applications
  - Speech recognition
  - Audio signal processing
  - Video compression
  - Weather forecasting
  - Economic forecasting
  - Medical imagining (e.g., CAT, MRI)
  - And more...

Outline

What is the problem?

Goal: We wish to reconstruct some generated signal $\hat{x}$ that has been distorted by some error and convolution processes.

Solution: Take the convolution inverse of $\hat{x}$ to reconstruct the signal.

Outline

Problem Simulation

Specify the main ingredients of simulated measurement system:

- Finitely supported point spread function (influence function),
  - Symmetric case: $a_i = \frac{1}{10}$ for $|i| < 15$.
  - Asymmetric case: $a_i = \frac{2}{10} e^{-i/40}$ for $0 \leq i \leq 40$.
- The covariance function ϕ for the signal x is given by

$$\phi = \mathrm{Cov}\,(x) = b * b^*$$

  where $b_i = \frac{21}{100}(1 - |i|)$ for $|i| \leq 7$.
- Measurement noise is modeled with a zero mean Gaussian ν with a specified $\sigma^2 = \frac{1}{100}$.
- Finally, the data is given by

$$y = a * x + \nu$$

Reconstruction Operator R

- Following Lecture 13, we seek a reconstruction operator R that is given by convolution with r supported on a specified interval Δ, so that $\widehat{x} = r * x$.
- Further, it was shown that

$$H(r) = E(\widehat{x} - x)^2 = \langle P(r - P^{-1}q), r - P^{-1}q \rangle_\Delta + f_0 - \langle q, P^{-1}q \rangle_\Delta$$

  where P is the operator associated with convolution by $p = a * \phi * a^* + \sigma^2\delta$ and $q = a * \phi$.
- So, for a given Δ, the reconstruction kernel is uniquely determined by $r = P^{-1}q$, and

$$\operatorname{Var} \widehat{x} = H_{min} = f_0 - \langle q, r \rangle_\Delta .$$

Outline

Outline

References

[1] Golubtsov, P. (2015). Theoretical Big Data Analytics course notes.