

SE-MPPI: Coordinating Online Local-Minima Escape with Control-Barrier-Function Safety in a Nav2-Native Controller

Jungmo Kang¹

¹Independent Researcher, Seoul, Republic of Korea

Model Predictive Path Integral (MPPI) control, as shipped in the ROS 2 Nav2 stack, is among the strongest deployable local controllers for mobile robots, yet in narrow, cluttered and dynamic spaces it stalls in local minima and avoids collisions only through soft costs, without a formal safety guarantee. Prior work treats the two weaknesses separately, and none of it ships as a Nav2 controller. In this paper, we introduce *SE-MPPI* (Safe-Escape MPPI), a single Nav2-native controller that couples online local-minima detection-and-escape with a control-barrier-function (CBF) safety filter for dynamic obstacles. One entrapment signal switches escape costs into the MPPI rollouts and, through a coordinator, raises the barrier’s class- $\mathcal{K}$ gain; we show that forward invariance holds for any positive bounded gain schedule, so an escape admitted by a raised gain stays certified-safe. In a randomized, paired 1,200-trial 2D benchmark built from the controller’s primitives, the detection-and-escape layer lifts success from 0% to 88–90% on a static U-trap family and from 0% to 62–78% on a narrow-dynamic family (Holm-adjusted McNemar $p = 1.4 \times 10^{-9}$ and 1.1×10^{-6}), and disabling its free-space gap search returns both families to 0%. The escape–safety coordination, by contrast, is statistically indistinguishable from an independent escape+CBF stack; we report this null and claim the coordination as a certified-safe mechanism, not as an empirical gain. The controller also loads and runs in a live ROS 2 Jazzy, Nav2 and Gazebo stack, where it exposed three deployment faults that unit tests could not. Code, raw trials and regeneration scripts: <https://github.com/kjungmo/se-mppi-nav2>.

Keywords: model predictive path integral control, control barrier functions, local minima, collision avoidance, ROS 2 Nav2

1. Introduction

Autonomous mobile robots increasingly work in cluttered, dynamic indoor spaces such as warehouses, hospitals and service floors, where the local controller must be fast, non-conservative and safe at the same time. Within the ROS 2 Nav2 ecosystem (Macenski et al., 2020), the MPPI controller (`nav2_mppi_controller`) has become the high-performance default: it samples a batch of control rollouts, scores them with a bank of critic plugins, and fuses them with an information-theoretic softmax (Williams et al., 2018). With the defaults we build on, it plans over a horizon of $56 \times 0.05 \text{ s} \approx 2.8 \text{ s}$ with 1,000 rollouts per cycle.

Two weaknesses recur in exactly the environments that matter most. First, *local-minima entrapment*: a finite horizon and zero-mean Gaussian sampling make the robot stall or oscillate in front of non-convex obstacles, and Nav2’s mitigations (`PreferForwardCritic`, `TwirlingCritic`) are always-on cost shaping that neither detects entrapment nor promotes escape. Escape methods from the MPPI literature either reshape the sampling distribution all the time (Honda et al., 2024; Mohamed




Figure 1: Overview of SE-MPPI. The stock Nav2 MPPI optimizer produces a nominal command from sampled rollouts. A single entrapment signal e_t , computed from monotone progress along the global path (Section 3.2), switches the EscapeCritic’s repulsion and gap-attraction costs into the rollout scoring (Section 3.3) and tells the coordinator to raise the CBF gain α_t unless a tracked obstacle’s time-to-collision is imminent (Section 3.6). The CBF-QP filter then projects the nominal command onto the barrier-safe set for the tracked dynamic obstacles (Section 3.5); Nav2’s collision_monitor remains the last reactive layer.

et al., 2022; Sacks and Boots, 2022; Trevisan and Alonso-Mora, 2024; Wang et al., 2021) or detect entrapment and switch on a repulsive potential without any safety certificate (Fuke et al., 2025). Second, *no formal safety*: collision avoidance is encoded as soft costs, the costmap is a present-time snapshot with no prediction of obstacle motion, and collision_monitor is purely reactive. CBF-MPPI fusions supply safety (Borquez et al., 2025; Parwana et al., 2024, 2025; Rabiee and Hoagg, 2025; Yin et al., 2023), but none escapes local minima and none ships as a Nav2 controller. The two weaknesses also interact: conservatism for safety invites entrapment, and aggressive escape invites collision.

To overcome these limitations together, we introduce *SE-MPPI*, a Nav2 controller plugin that subclasses the stock MPPI controller and post-processes its command each cycle (Figure 1). A single entrapment detector, driven by monotone progress along the global path, is the one source of truth for the whole controller. When it fires, an EscapeCritic switches repulsion and free-space gap-attraction costs into the rollout scoring, and a coordinator raises the gain of a look-ahead-point CBF filter so that the escape manoeuvre is admitted, unless a tracked obstacle’s time-to-collision is imminent. Our contributions are:

- *Nav2-Native Safe-Escape Controller*: to our knowledge the first Nav2 local-controller plugin that combines online local-minima detection-and-escape with a CBF safety filter for tracked dynamic obstacles, packaged as a `nav2_core::Controller` plus a pluginlib MPPI critic over a plugin-free core, and released under Apache-2.0.
- *Certified-Safe Escape Coordination*: a gain-scheduling rule that raises the CBF class- $\mathcal{K}$ gain on detected entrapment and drops it back on an imminent time-to-collision, with a proof that forward invariance of the barrier’s safe set holds for every positive bounded gain schedule (Proposition 1). We claim this as a mechanism: in our benchmark it is empirically indistinguishable from an independent escape+CBF stack.
- *Paired Benchmark and Deployment Evidence*: a randomized, seed-deterministic 1,200-trial 2D benchmark with paired McNemar tests and Holm correction, every number regenerated from committed per-trial data, together with a live ROS 2 Jazzy, Nav2 and Gazebo integration that exposed three faults unreachable from unit tests.

We are deliberately conservative about novelty and about what we claim empirically. Fusing CBFs with MPPI is not new. The measured win is the online detection-and-escape layer: success rises from 0% to 88–90% on the static U-trap family and from 0% to 62–78% on the narrow-dynamic family, and the gap search is load-bearing, since without it both families stay at 0% (Sections 4.2 and 4.3). The coordination is certified-safe by construction yet produces no measurable outcome difference in the regimes we could test, and we delimit where it should matter (Section 5). The remaining claims are Nav2-native deployment and the faults a live stack exposes.

2. Related Work

MPPI and Deployable Local Controllers. Nav2 MPPI (Macenski et al., 2020; Williams et al., 2018), TEB (Rösmann et al., 2012), DWB, a Nav2 planner of the dynamic-window family (Fox et al., 1997), and Regulated Pure Pursuit (Macenski et al., 2023) are the standard deployable local controllers. MPPI’s critic interface (`mppi::critics::CriticFunction`) exposes the per-rollout trajectories, the reference path, the goal and the furthest-reached path index, which are exactly the signals needed for entrapment detection, so a custom critic can be inserted without forking the optimizer. SE-MPPI uses this interface for escape and adds an output-side safety filter, instead of replacing the optimizer.

Local-Minima Escape. Most escape methods are always-on changes of the sampling distribution: log-MPPI (Mohamed et al., 2022), Tsallis-divergence MPC (Wang et al., 2021), Stein-variational guidance (Honda et al., 2024), ancillary-controller biasing (Trevisan and Alonso-Mora, 2024), and learned sampling distributions (Sacks and Boots, 2022). The closest detect-and-switch method is DRPA-MPPI (Fuque et al., 2025), which detects entrapment from predicted trajectories and switches on a repulsive potential. It has no CBF or other formal safety, models no dynamic obstacles, and is not Nav2-integrated. SE-MPPI also detects and switches, but gates the escape through a safety certificate and adds a free-space gap subgoal that our ablation shows to be necessary.

CBF-MPPI Safety. Three fusion styles exist as research code: CBF terms in the rollout cost (Shield-MPPI (Yin et al., 2023), which adds a local repair step, and BR-MPPI (Parwana et al., 2025), which also steers sampling through a barrier-rate input), an output CBF-QP filter on the MPPI command (SCBF-MPPI (Parwana et al., 2024), built on the CBFKit toolbox (Black et al., 2024)), and per-rollout safety filtering that makes every sample provably safe (GS-MPPI (Rabiee and Hoagg, 2025), DualGuard (Borquez et al., 2025), which also filters the final command). For dynamic obstacles, DPCBF (Park et al., 2025) uses a parabolic safe set that is less conservative than collision-cone barriers but is QP-only and not embedded in MPPI. Our filter builds on the classical CBF-QP (Ames et al., 2017, 2019). None of these works ships as a Nav2 controller (CBFKit builds a standalone node), and none addresses entrapment; SE-MPPI couples the barrier to the escape layer through its gain.

Conformal Prediction for Safe Control. The released controller also carries an online conformal margin that inflates the barrier radius under prediction uncertainty, drawing on conformal prediction for safe planning and control (Dixit et al., 2023; Gonzales et al., 2025; Lindemann et al., 2023; Zhou et al., 2024) and on uncertainty-aware predictive barriers (Busellato et al., 2026). This margin is follow-up work and is *not* a contribution of this paper; every result reported here is isolated from it (Section 5).

Positioning. Table 1 places the named systems against four factors: shipping as a Nav2 plugin, online escape, a CBF-style safety layer, and escape–safety gain coordination. Each reviewed system holds exactly one; in particular, no Nav2-native controller carries a CBF. The gain coordination is the cleanest unoccupied element, although, as Section 4.3 shows, we could not measure an outcome benefit from it.

Table 1: Positioning. (a) ships as a Nav2 controller plugin; (b) online local-minima escape; (c) CBF-style safety layer (for DualGuard, Hamilton–Jacobi reachability); (d) escape–safety gain coordination. Each reviewed system holds one of the four; SE-MPPI is designed to hold all four. The review behind this table (June 2026) covered the Nav2 MPPI critic ecosystem, the CBF–MPPI papers cited here, and the public issue trackers of these projects.

System	Reference	(a)	(b)	(c)	(d)
DRPA-MPPI	Fuke et al. (2025)	–	✓	–	–
Shield-MPPI, BR-MPPI	Parwana et al. (2025); Yin et al. (2023)	–	–	✓	–
CBFKit	Black et al. (2024)	–	–	✓	–
SCBF-MPPI, DualGuard	Borquez et al. (2025); Parwana et al. (2024)	–	–	✓	–
GS-MPPI	Rabiee and Hoagg (2025)	–	–	✓	–
DPCBF	Park et al. (2025)	–	–	✓	–
SE-MPPI (ours)	this paper	✓	✓	✓	✓

3. SE-MPPI: Coordinated Escape and Barrier Safety in One Nav2 Controller

Problem Setup. Consider a differential-drive robot with pose $\mathbf{x}_t = (x_t, y_t, \theta_t)$, position $\mathbf{p}_t = (x_t, y_t)$ and control $\mathbf{u}_t = (v_t, \omega_t) \in \mathcal{U}$, where $\mathcal{U}$ is the box $v \in [v_{\min}, v_{\max}]$, $|\omega| \leq \omega_{\max}$, following the unicycle model $\dot{x} = v \cos \theta$, $\dot{y} = v \sin \theta$, $\dot{\theta} = \omega$. A Nav2 global planner supplies a path $\sigma = (\sigma_1, \dots, \sigma_M)$. Around the robot are static structure, seen only through the local costmap, and a set $\mathcal{O}_t$ of dynamic obstacles o with position $\mathbf{p}_o$, radius R_o and estimated velocity $\mathbf{v}_o$. Let r be the robot’s inscribed radius and m a safety margin. We seek a controller that (G1) keeps making progress along σ instead of stalling in a local minimum, (G2) keeps the robot collision-free with respect to $\mathcal{O}_t$ with a forward-invariance certificate, and (G3) runs as a Nav2 controller in real time on a CPU. Formally, each control cycle approximately solves

$$\mathbf{u}_{t:t+T-1}^* = \arg \min_{\mathbf{u}_{t:t+T-1} \in \mathcal{U}^T} \mathbb{E} \left[\sum_{\tau=t}^{t+T-1} c(\mathbf{x}_\tau, \mathbf{u}_\tau; \sigma) + e_t c_{\text{esc}}(\mathbf{x}_{t:t+T}) \right] \quad (1)$$

s.t. h_o satisfies the CBF condition (9) at $(\mathbf{x}_t, \mathbf{u}_t) \quad \forall o \in \mathcal{O}_t$,

where c is the stock Nav2 critic cost, $e_t \in \{0, 1\}$ is the entrapment flag, c_{esc} are the escape costs, and h_o is a control barrier function for obstacle o . The tension is that G1 may demand manoeuvres that approach obstacles to round a trap, whereas a fixed safety filter for G2 forbids exactly those manoeuvres. SE-MPPI splits (1): MPPI minimizes the expected cost, with escape costs switched in by e_t (Sections 3.1 to 3.3); a per-cycle QP enforces the barrier on the first control (Sections 3.4 and 3.5); and a coordinator couples the two through the barrier gain (Section 3.6). Algorithm 1 summarizes one cycle.

3.1. Sampling Nominal Commands: Reusing the Nav2 MPPI Optimizer

SE-MPPI subclasses the stock `MPPIController` and calls its optimizer unchanged. Given the previous control sequence $\bar{\mathbf{u}}_{0:T-1}$, the optimizer draws K perturbations $\epsilon_j^k \sim \mathcal{N}(\mathbf{0}, \Sigma)$, rolls out $\mathbf{u}_j^k = \text{clip}_{\mathcal{U}}(\bar{\mathbf{u}}_j + \epsilon_j^k)$ through the motion model, and scores each rollout $\mathbf{x}_{0:T}^k$ with the listed critics C_i , among which the

EscapeCritic (Section 3.3):

$$S^k = \sum_i C_i(\mathbf{x}_{0:T}^k) + e_t \left(C_{\text{apf}}(\mathbf{x}_{0:T}^k) + C_{\text{gap}}(\mathbf{x}_{0:T}^k) \right),$$

$$w^k = \frac{\exp(-(S^k - \min_{k'} S^{k'})/\lambda)}{\sum_{k''} \exp(-(S^{k''} - \min_{k'} S^{k'})/\lambda)}, \quad \bar{\mathbf{u}}_j \leftarrow \sum_k w^k \mathbf{u}_j^k. \quad (2)$$

The first element is the nominal command $\mathbf{u}_t^{\text{nom}} = (\bar{v}_0, \bar{\omega}_0)$ (Williams et al., 2018). (Nav2 additionally regularizes the control effort through a small weight γ ; we omit it for brevity.) With the released defaults, $T = 56$, $\Delta t = 0.05$ s, $K = 1000$, $\lambda = 0.3$ and $\Sigma^{1/2} = \text{diag}(0.2, 0.4)$ (Table 5).

3.2. Detecting Entrapment: A Single Monotone Progress Signal

The nearest-path index $k_t = \arg \min_i \|\mathbf{p}_t - \sigma_i\|$ is non-monotone: it jumps back when the robot backs off a wall. We therefore track the furthest index ever reached and count the cycles in which it fails to advance,

$$k_t^{\max} = \max(k_{t-1}^{\max}, k_t), \quad s_t = \begin{cases} 0 & k_t^{\max} > k_{t-1}^{\max}, \\ s_{t-1} + 1 & \text{otherwise,} \end{cases}$$

$$e_t = \begin{cases} 0 & k_t^{\max} > k_{t-1}^{\max} \text{ or } \|\mathbf{p}_t - \sigma_M\| \leq \epsilon_{\text{goal}}, \\ 1 & s_t \geq W, \\ e_{t-1} & \text{otherwise.} \end{cases} \quad (3)$$

Entrapment thus latches after W stalled cycles ($W = 30$ by default) and clears on the first real progress, so stop-and-go motion during an escape cannot leave the flag stuck; within ϵ_{goal} of the path end the detector is reset, so a robot finishing at the goal does not trigger a false escape. The controller is the *only* detector: the critic and the coordinator read the same atomic flag through a registry keyed by the controller name, so escape and safety always agree on whether the robot is trapped. (When the critic runs under a stock MPPI controller, it falls back to its own detector on MPPI’s furthest-reached index.)

3.3. Escaping Local Minima: Gated Repulsion and Gap Attraction

Only while $e_t = 1$, the EscapeCritic adds two terms to every rollout’s cost in (2); in free space the controller is therefore exactly stock MPPI (detect-and-switch rather than always-on). The first is a distance-field artificial potential. Let $d(\mathbf{q})$ be the 8-connected Dijkstra distance from costmap cell $\mathbf{q}$ to the nearest obstacle cell, where unknown cells are *not* obstacles so that unexplored space does not repel the escape. With $\mathcal{J}^k$ the on-map poses of rollout k and $d_{\min}$ half a cell,

$$U(d) = \begin{cases} \frac{1}{2} \eta \left(\frac{1}{\max(d, d_{\min})} - \frac{1}{d_0} \right)^2 & d < d_0, \\ 0 & d \geq d_0, \end{cases} \quad C_{\text{apf}}(\mathbf{x}_{0:T}^k) = \left(\frac{1}{|\mathcal{J}^k|} \sum_{j \in \mathcal{J}^k} U(d(\mathbf{p}_j^k)) \right)^p, \quad (4)$$

which pushes rollouts off the trapping surface. Repulsion alone does not route the robot *around* a non-convex trap, so the second term supplies a temporary subgoal. The critic casts N_r rays at bearings $\psi_i = -\pi + 2\pi i/N_r$ from the robot, measures each ray’s free length $\ell(\psi_i) \leq r_{\max}$ on the costmap, and selects the open bearing closest to the goal bearing ψ_{goal} ; rollouts whose endpoint heads toward it are rewarded:

$$\psi^* = \arg \min_{\psi_i: \ell(\psi_i) \geq r_{\min}} |\text{wrap}(\psi_i - \psi_{\text{goal}})|, \quad C_{\text{gap}}(\mathbf{x}_{0:T}^k) = w_g \left(1 - \cos \text{wrap}(\angle(\mathbf{p}_T^k - \mathbf{p}_t) - \psi^*) \right)^{p_g}. \quad (5)$$

The defaults are $d_0 = 0.6$ m, $\eta = 1$, $N_r = 36$, $r_{\max} = 2$ m, $r_{\min} = 0.6$ m and $w_g = 4$ (Table 5). Section 4.3 shows that this gap term is what makes escape succeed.

3.4. Tracking Dynamic Obstacles: Costmap Clusters with Gated Association

The tracker clusters local-costmap cells at or above the inscribed-inflation threshold, summarizing each cluster c by a centroid $\mathbf{c}$ and a radius. Each current cluster is associated with at most one previous track within a gate of 0.6 m, each track being consumable once, so a split or merge cannot manufacture a phantom velocity. The velocity is a clamped finite difference over the track history,

$$\mathbf{v}_o = \text{clamp}_{v_{\text{track}}}\left(\frac{\mathbf{c}_t - \mathbf{c}_{t'}}{t - t'}\right), \quad \mathcal{O}_t = \{o : \|\mathbf{v}_o\| \geq v_{\text{dyn}}, R_o \leq R_{\max}\}, \quad (6)$$

with t' the previous observation of the track and $v_{\text{track}} = 2$ m/s. Only obstacles that are moving and small enough to be a movable body enter $\mathcal{O}_t$, and hence the coordinator and the CBF. Static structure is deliberately excluded and left to the MPPI obstacle critic and costmap inflation; Section 4.4 shows why this scoping is essential on a real costmap. The constant-velocity model is a replaceable baseline (Section 5).

3.5. Filtering Commands: A Look-Ahead-Point CBF Quadratic Program

A distance barrier on the unicycle's centre has relative degree two in ω . We therefore enforce safety on the look-ahead point $\mathbf{P}_t = \mathbf{p}_t + L(\cos \theta_t, \sin \theta_t)$, which (v, ω) actuates fully:

$$\dot{\mathbf{P}}_t = G(\theta_t) \mathbf{u}_t, \quad G(\theta) = \begin{bmatrix} \cos \theta & -L \sin \theta \\ \sin \theta & L \cos \theta \end{bmatrix}. \quad (7)$$

For each $o \in \mathcal{O}_t$, with $\mathbf{d}_o = \mathbf{P}_t - \mathbf{p}_o$ and effective radius $R_o^{\text{eff}} = r + R_o + m$, the barrier and its derivative are

$$h_o = \|\mathbf{d}_o\|^2 - (R_o^{\text{eff}})^2, \quad \dot{h}_o = 2 \mathbf{d}_o^\top (G(\theta_t) \mathbf{u}_t - \mathbf{v}_o), \quad (8)$$

and the continuous-time CBF condition (Ames et al., 2017, 2019)

$$\dot{h}_o + \alpha_t h_o \geq 0 \quad (9)$$

is linear in $\mathbf{u}_t$. Once per control cycle we solve, with OSQP (Stellato et al., 2020),

$$\min_{v, \omega, \delta \geq 0} w_v (v - v_t^{\text{nom}})^2 + w_\omega (\omega - \omega_t^{\text{nom}})^2 + \rho \delta^2 \quad \text{s.t.} \quad 2 \mathbf{d}_o^\top G(\theta_t) \mathbf{u} + \delta \geq -\alpha_t h_o + 2 \mathbf{d}_o^\top \mathbf{v}_o \quad \forall o, \quad \mathbf{u} \in \mathcal{U}, \quad (10)$$

where the nominal command is first clamped to $\mathcal{U}$ and a single shared slack δ keeps the QP feasible. Obstacles are pruned to the N_{obs} nearest by *clearance* (surface gap) rather than centre distance, so a large obstacle is never dropped in favour of a smaller one whose centre is closer. If the QP can stay safe only by relaxing the barrier ($\delta > \epsilon_\delta = 10^{-3}$) or fails, the controller brakes, setting $v = 0$ while keeping the QP's turn (or, on solver failure, the clamped nominal turn): it stops rather than drive into an imminent collision.

Because (9) is imposed only at sampling instants, strict between-sample invariance would require tightening R_o^{eff} by a term of order $\dot{h}_{\max} \Delta t$. In practice the margin m absorbs this gap, and we report the empirical slack usage instead of claiming continuous-time invariance between samples.

3.6. Coordinating Escape and Safety: Gain Scheduling with Certified Invariance

The coordinator resolves the barrier gain from the entrapment flag and the minimum time-to-collision under the current command,

$$\alpha_t = \begin{cases} \alpha_{\text{escape}} & e_t = 1 \text{ and } \text{TTC}_t \geq \tau, \\ \alpha_{\text{base}} & \text{otherwise,} \end{cases} \quad \text{TTC}_t = \min_{o \in \mathcal{O}_t: \kappa_o > 0} \frac{\|\mathbf{r}_o\| - (r + R_o)}{\kappa_o}, \quad \kappa_o = -\frac{\mathbf{r}_o^\top (\mathbf{v}_o - v_t^{\text{nom}} \mathbf{h}_t)}{\|\mathbf{r}_o\|}, \quad (11)$$

where $\mathbf{r}_o = \mathbf{p}_o - \mathbf{p}_t$, $\mathbf{h}_t = (\cos \theta_t, \sin \theta_t)$, κ_o is the closing speed, $\text{TTC}_t = 0$ on contact and $+\infty$ if nothing approaches, and $\alpha_{\text{escape}} > \alpha_{\text{base}} > 0$ (defaults 6 and 2, $\tau = 1.5$ s).¹ Raising α_t relaxes the lower bound $\dot{h}_o \geq -\alpha_t h_o$, letting the robot approach an obstacle faster as an escape requires, while the TTC override snaps the gain back to α_{base} when a dynamic obstacle is imminent. The next result shows that this schedule never trades away the certificate.

Assumption 1 (Slack-free barrier between samples). For a fixed obstacle j and all $t \geq 0$ in the interval considered, the QP (10) is feasible with $\delta(t) = 0$, and the continuous-time inequality $\dot{h}_j(t) \geq -\alpha(t) h_j(t)$ holds for almost every t .

The second clause is an assumption, not a consequence: feasibility at discrete instants does not by itself imply the inequality between samples (the sampled-data caveat of Section 3.5).

Proposition 1 (Certified-safe escape). *Let $\alpha : [0, \infty) \rightarrow [\alpha_{\min}, \alpha_{\max}] \subset (0, \infty)$ be any measurable, positive, bounded gain schedule, in particular the piecewise-constant switching (11) with its TTC override. Under Assumption 1, if $h_j(0) \geq 0$ then $h_j(t) \geq 0$ for all $t \geq 0$: the look-ahead point never enters obstacle j 's inflated disc.*

Proof. Define $\varphi(t) = \exp(\int_0^t \alpha(s) ds)$, which is finite and strictly positive because $0 < \alpha \leq \alpha_{\max}$. Almost everywhere,

$$\frac{d}{dt} [\varphi(t) h_j(t)] = \varphi(t) [\dot{h}_j(t) + \alpha(t) h_j(t)] \geq 0, \quad (12)$$

so φh_j is non-decreasing and $\varphi(t) h_j(t) \geq \varphi(0) h_j(0) = h_j(0) \geq 0$. Since $\varphi(t) > 0$, $h_j(t) \geq 0$ for all $t \geq 0$. $\square$

Corollary 1. *Forward invariance of $C_j = \{h_j \geq 0\}$ holds for every positive bounded schedule, including the switch to α_{escape} and the TTC override back to α_{base} . When the QP returns $\delta = 0$, all rows satisfy the hypothesis simultaneously, so $C = \bigcap_j C_j$ is invariant; the argument is per obstacle and gain-agnostic, so sharing one α_t across rows does not affect it.*

Raising α therefore never permits $h_j < 0$; it only weakens the lower bound on $\dot{h}_j$, admitting bolder detours inside the same invariant set. Escape aggressiveness and the safety certificate are decoupled, and the gain is the single knob that trades caution for manoeuvrability inside the set. This is the reason we coordinate rather than stack the two layers, and it holds whether or not the barrier binds. The guarantee is conditional on $\delta = 0$ and on the obstacle model. Because the slack is shared, one imminent obstacle can momentarily loosen the margin on every other obstacle in the same solve, so we report slack usage empirically: in the benchmark of Section 4, the QP never uses slack on the mover-free families, and uses nonzero slack in 26–34 of 50 narrow-dynamic trials (maximum 0.47) and in 47–48 of 50 dynamic-family trials (maximum 0.015) per CBF-carrying configuration (Table 7). The $\delta > \epsilon_\delta$ brake is the fallback in those cycles.

¹The released controller also holds α_t at α_{base} while an online conformal bound on obstacle-prediction error exceeds a trust threshold, and that bound inflates R_o^{eff} . This is the follow-up conformal margin of Section 2, not claimed here; an implementation of (11) alone reproduces the benchmark configurations of Section 4, not the released defaults.

Algorithm 1: One SE-MPPI control cycle (computeVelocityCommands)

Input: pose $\mathbf{x}_t$, global path σ , local costmap, previous state $(k_{t-1}^{\max}, s_{t-1}, e_{t-1})$
Output: safe command $\mathbf{u}_t^{\text{safe}}$

- 1 $\mathbf{u}_t^{\text{nom}} \leftarrow$ stock MPPI optimizer, scoring rollouts with (2); the EscapeCritic adds $C_{\text{apf}} + C_{\text{gap}}$ iff the shared flag $e_{t-1} = 1$
- 2 $k_t \leftarrow \arg \min_i \|\mathbf{p}_t - \sigma_i\|$; update $k_t^{\max}, s_t, e_t$ by (3); publish e_t to the shared registry
- 3 $O_t \leftarrow$ tracked clusters that are moving and small (6)
- 4 $\alpha_t \leftarrow$ gain from e_t and TTC $_t$ by (11)
- 5 **if** $O_t = \emptyset$ **then**
- 6 $\mathbf{u}_t^{\text{safe}} \leftarrow \text{clip}_{\mathcal{U}}(\mathbf{u}_t^{\text{nom}})$
- 7 **else**
- 8 keep the N_{obs} obstacles of smallest clearance; solve the QP (10) with gain α_t
- 9 **if** *solver failed* **or** $\delta > \epsilon_\delta$ **then**
- 10 $v_t^{\text{safe}} \leftarrow 0$ // brake, keep the turn
- 11 **return** $\mathbf{u}_t^{\text{safe}}$

3.7. Packaging for Nav2: Two Plugins over a Plugin-Free Core

SE-MPPI is built on ROS 2 Jazzy and Nav2 (Macenski et al., 2020). The package `nav2_se_controller` ships three shared libraries: a plugin-free `se_mppi_core` (entrapment, CBF filter, coordinator, tracker, repulsion, gap search), the `escape_critic` MPPI critic, and the `safe_escape_controller`. Separating the core from the two plugin libraries resolves a `class_loader` factory conflict that otherwise prevents the critic and the controller from loading together. Two integration details are easy to get wrong. First, Nav2’s `CriticManager` resolves a critics-list entry NAME to the class `mppi::critics::NAME`; a critic in any other namespace passes a direct pluginlib unit test yet never loads from the critics list, so `EscapeCritic` lives in `mppi::critics`. Second, the Jazzy critic data are `xtensor` tensors, not the Eigen types of Nav2’s development branch, so the critic is written against the installed headers. The QP uses `osqp-eigen` (Stellato et al., 2020), and the build is reproducible through RoboStack (conda-forge) independently of the host OS. The modules this paper relies on (entrapment detector, CBF filter, coordinator, tracker, gap search, repulsion, path progress and plugin loading) carry 44 gtest cases; with the follow-up prediction and multi-robot modules and the live-injection regression of Section 4.4, the package holds 82 TEST cases in 13 files.

4. Experiments

We first check each mechanism in isolation, then measure the contribution of every layer on a randomized paired benchmark (Section 4.2), isolate the gap search, the coordination and the CBF by ablation (Section 4.3), and finally report what a live Nav2 deployment confirms and exposes (Section 4.4).

4.1. Experimental Setup

Evaluation Surface. The controlled quantitative comparison is a randomized 2D benchmark that reuses the controller’s primitives in NumPy and OSQP: the MPPI sampler, the APF repulsion, the gap raycast, the look-ahead-point CBF-QP, the α coordination with TTC override, and the monotone-progress entrapment detector. As in the released controller and the deployment lesson of Section 4.4,




Figure 2: Mechanism validation in the 2D mirror (seed-fixed single runs; Table 2). (a) Stock MPPI stalls at the mouth of a finite wall ($x \approx 1.2$ m) while the detection-and-escape layer rounds it to the goal. (b) Against a mover crossing the path, the no-CBF controller collides ($\times$) while the look-ahead-point CBF filter keeps the robot clear. (c, d) On the U-trap, the coordinated gain rises from $\alpha_{\text{base}}=2$ to $\alpha_{\text{escape}}=6$ while entrapped (shaded) and the QP slack stays below 2×10^{-6} throughout: the escape is admitted without relaxing the barrier, the situation covered by Proposition 1. Regenerated as vector graphics by `scripts/make_figures.py`.

the CBF and the TTC see only the dynamic obstacles, never static walls. The 2D mirror is not the live Nav2 controller: it drives a 2D unicycle, uses distance-to-goal progress and a free-space gap subgoal in place of a global path, and certifies the look-ahead point rather than the full body; Section C lists every difference. We use this surface instead of a live Gazebo matrix because on the only host available to us (a WSL2 workstation running at a real-time factor of about 0.3–0.6 under CPU contention, with transform smear adding phantom cells to the costmap) a live comparison measures the host rather than the algorithm.

Scenario Families. Four seed-deterministic families exercise the two weaknesses and their conjunction. *U-trap*: a finite U- or C-shaped pocket with the goal behind its back wall, a static local minimum. *Clutter*: a random field of 5–9 circular obstacles with a guaranteed footprint-clear path. *Dynamic*: one or two pedestrian-like movers timed to cross the robot’s path. *Narrow-dynamic*: the U-trap pocket plus movers sweeping its mouth during the escape window, the narrow-and-dynamic coincidence the coordination targets.

Configurations. Six ablation configurations toggle the mechanisms: **A** stock MPPI (no escape, no CBF); **C** escape only; **D** CBF only; **E** escape+CBF with $\alpha_{\text{escape}} = \alpha_{\text{base}}$, i.e. independent layers; **F** full SE-MPPI with $\alpha : 2 \rightarrow 6$ and TTC override, i.e. coordinated; and **F⁻** F with the gap search disabled. The deployable baselines of the specified full-scale protocol (DWB, RPP, TEB, a DRPA-style always-on escape and a Shield-style CBF-only controller) have not been run; we make no comparison to them.

Protocol and Metrics. Every scenario is a pure function of an integer seed, and the MPPI noise stream uses the same seed, so all configurations face byte-identical worlds and rollout noise, as the paired design requires. We run 4 families $\times$ 50 seeds $\times$ 6 configurations = 1,200 trials with a budget of 400 steps of 0.1 s. A trial is a success if it reaches the goal without a footprint collision, a collision if the footprint overlaps an obstacle, and a timeout otherwise. Success carries a Wilson 95% interval; the primary test is McNemar on paired outcomes; continuous metrics (time-to-goal, path length, clearance) use Mann–Whitney U with Cliff’s δ ; all p -values are Holm-corrected within each family (16 tests per family). The benchmark runs on CPU in Python; we report no per-cycle compute figures (Section 5). Parameters are in Table 5, and commands in Section A.

Table 2: Mechanism validation (single seed-fixed runs of the 2D mirror; 40 s budget). “Stalled” = budget exhausted without progress. Source: data/mechanism_validation.json, regenerated from experiments/prototype/run_validation.py.

Scenario	Configuration	Reached	Collided	Time (s)	Min. clear. (m)	$\max_t \alpha_t$
U-trap	stock MPPI (A)	no (stalled)	no	–	0.33	2
U-trap	escape (C)	yes	no	27.7	0.32	2
Crossing mover	escape, no CBF (C)	no	yes	–	–0.00	2
Crossing mover	SE-MPPI (F)	yes	no	18.6	0.01	6
U-trap	SE-MPPI (F)	yes	no	27.7	0.32	6
U-trap + mover	independent (E)	yes	no	27.7	0.32	2

Table 3: Main result: success rate in % with Wilson 95% confidence interval, $N = 50$ paired scenarios per cell (1,200 trials). Best per family in bold. On the two trap families the escape configurations (C, E, F) separate from stock (A), CBF only (D) and the no-gap ablation (F^-), which all stay at 0%. Source: experiments/results_2d/summary.csv.

Configuration	U-trap	Clutter	Dynamic	Narrow-dyn.
A stock MPPI	0 [0,7]	52 [39,65]	80 [67,89]	0 [0,7]
C escape only	90 [79,96]	62 [48,74]	76 [63,86]	78 [65,87]
D CBF only	0 [0,7]	52 [39,65]	82 [69,90]	0 [0,7]
E escape + CBF (indep.)	88 [76,94]	62 [48,74]	78 [65,87]	64 [50,76]
F SE-MPPI (coord.)	88 [76,94]	62 [48,74]	78 [65,87]	62 [48,74]
F^- F without gap search	0 [0,7]	52 [39,65]	84 [71,92]	0 [0,7]

4.2. Main Results

Mechanism Check. Before measuring rates, we verify that each mechanism does what it is designed to do on three hand-built scenes (Figure 2, Table 2). Stock MPPI stalls in front of a finite wall for the full 40 s budget, while the escape layer reaches the goal in 27.7 s; against a crossing mover the no-CBF controller collides after 4.7 s, while the CBF filter reaches the goal in 18.6 s with the minimum clearance never negative; and on the U-trap the coordinated gain rises from 2 to 6 while entrapped, with QP slack below 2×10^{-6} throughout, so the escape is admitted without relaxing the barrier (Proposition 1). In these benign scenes the coordinated and independent variants are both safe and equally fast (27.7 s, 0.32 m clearance), so they cannot separate the two; the randomized benchmark below is the quantitative test.

The Escape Layer Is the Measured Contribution. On both trap families the effect is decisive and survives Holm correction (Tables 3 and 4). Success rises from 0%, where stock A, CBF-only D and no-gap F^- all time out in the pocket, to 88–90% on U-trap (44 of 50 discordant pairs in F^- ’s favour, $p_{\text{adj}} = 1.4 \times 10^{-9}$) and to 62–78% on narrow-dynamic (31 of 50, $p_{\text{adj}} = 1.1 \times 10^{-6}$). On clutter the escape adds 10 percentage points (52% $\rightarrow$ 62%, not significant after correction) at the cost of about 2.4 s longer mean time-to-goal over successful trials (15.2 s $\rightarrow$ 17.7 s; Table 6). On the pure dynamic family, which contains no trap, it is appropriately neutral ($A \rightarrow F$: $b/c = 3/2$, $p_{\text{adj}} = 1$). Figure 3 shows the full per-family picture, including collision and timeout rates.

4.3. Ablation Studies

The Gap Search Is Load-Bearing. F^- , which keeps the entrapment detector, the APF repulsion and the gain modulation but drops the gap search, scores 0% on both trap families (Table 3), identical to

Table 4: Paired contrasts against F (McNemar on success, Holm-adjusted within each family of 16 tests). b = trials the baseline solves and F does not; c = the reverse. * marks $p_{\text{adj}} < 0.05$. The escape contrast ($A \rightarrow F$) is decisive on both trap families; the coordination contrast ($E \rightarrow F$) is null everywhere. Source: `experiments/results_2d/stats.json`.

Family	Escape ($A \rightarrow F$)		CBF cost ($C \rightarrow F$)		Coordination ($E \rightarrow F$)	
	b/c	p_{adj}	b/c	p_{adj}	b/c	p_{adj}
U-trap	0/44	$1.4 \times 10^{-9*}$	1/0	1	0/0	1
Clutter	0/5	1	0/0	1	0/0	1
Dynamic	3/2	1	1/2	1	0/0	1
Narrow-dyn.	0/31	$1.1 \times 10^{-6*}$	8/0	0.109	1/0	1




Figure 3: Outcome rates per family across configurations A – F^- ($N = 50$ each; Wilson 95% intervals on success). On the trap families (U-trap, narrow-dynamic) the escape configurations C , E and F separate from A , D and F^- , which time out at 0% success. Plotted directly from `experiments/results_2d/summary.csv`.

stock MPPI. Detection-and-switch escapes only *with* the free-space gap subgoal: repulsion and gain modulation without a routed opening do not escape.

Escape–Safety Coordination Is Null in This Regime. The contrast that bears on the coordination contribution is E (independent) versus F (coordinated): identical mechanisms that differ only in whether the CBF gain follows the escape phase. Across all 200 paired scenarios this contrast is null (Table 4, Figure 4): the discordant counts are 0/0, 0/0, 0/0 and 1/0, McNemar $p = 1$ in every family, and every continuous effect size (Cliff’s δ) satisfies $|\delta| \leq 0.032$. The gain does engage as designed ($\max_t \alpha_t = 6$ during escape, TTC override active). The per-trial slack telemetry (Table 7) locates where the barrier actually works. On the mover-free families the dynamic-obstacle CBF sees no obstacle at all: slack is zero in every trial, E and F issue identical commands, and the null there is structural. On narrow-dynamic the barrier *does* engage and even relaxes, with nonzero slack in 34 of 50 trials for E and F (26 for D and F^- , maximum 0.47), and on dynamic in 47–48 of 50 (maximum 0.015); yet E and F still do not differ. The correct reading is therefore not that the barrier never binds, but that the *outcomes are insensitive to the α schedule*: where the barrier is quiescent the two configurations coincide exactly, and where it is active both gains admit escapes whose outcomes are indistinguishable at $N = 50$. In this benchmark the coordination produces no measurable outcome difference over independent escape+CBF. This is consistent with, and delimits, Proposition 1: coordination is a certified-safe mechanism, not, in these scenarios, an outcome improvement.

What the CBF Changes. Against body-grazing crossers (dynamic) the look-ahead-point filter leaves the collision rate essentially unchanged (20% for A versus 16–18% with a CBF; descriptive, since the committed analysis carries no paired collision test). In the cramped narrow-dynamic pocket,




Figure 4: The coordination contrast is null. Independent escape+CBF (E) versus coordinated SE-MPPI (F) per family, with the paired McNemar discordant counts and raw p -values from experiments/results_2d/stats.json. The two are indistinguishable in every family.

the CBF configurations show a *higher* collision rate than their no-CBF counterparts (18% $\rightarrow$ 32%, descriptive) and lose about 16 points of success (C 78% versus F 62%; McNemar $b/c = 8/0$, raw $p = 0.008$, $p_{\text{adj}} = 0.109$), which is directionally consistent though not significant after correction at $N = 50$. We attribute both to the braking fallback and the point certificate and discuss them as limitations in Section 5.

4.4. Live Nav2 and Gazebo Integration

We deployed SE-MPPI in a complete live stack: ROS 2 Jazzy, Nav2 (AMCL, costmaps, NavFn, behaviour-tree navigator, recovery, collision monitor) and the Gazebo `tb3_sandbox` world. The committed launch logs and trial telemetry confirm that the controller and the `EscapeCritic` load and activate from the critics list, that the controller produces velocity commands of the same form as stock MPPI, and that the lifecycle reaches the active state and sustains multi-minute drives on a U-trap testbed without a crash or collision after the fix below. The goal was not reached: the committed telemetry records STUCK at 254.5 s and TIMEOUT at 299.8 s, both collision-free, under the host constraints of Section 4.1. The escape-injection path has also run live: its first live activation exposed the ABI fault below, and the tensor shapes captured from that event are committed as a regression test, while the controller and critic now log every detection and injection transition for auditability. A sustained live entrapment-and-escape demonstration remains confounded by the host artefacts and is deferred to a GPU workstation. Three faults surfaced that only a live stack reveals:

- *Static walls in the CBF.* Feeding every lethal cluster, walls included, into the CBF makes the barrier infeasible everywhere and freezes the robot; scoping the CBF to moving, body-sized obstacles (6) fixes it.
- *Compute budget.* The per-cycle budget must match the host (horizon preserved, rate and batch reduced), or the loop misses its rate and the optimizer diverges.
- *xtensor ABI mismatch.* The installed `libmppi_controller.so` is compiled with `XTENSOR_USE_XSIMD` and `AVX2` (an aligned-allocator element type), whereas our plugin used the default allocator. Because the critic tensors cross the pluginlib boundary by reference, the first `EscapeCritic` write to `data.costs` violated the one-definition rule and crashed the whole Nav2 process on the first live escape injection. Unit tests could not catch it, since they compile every translation unit with one flag set, and earlier live runs had never triggered entrapment. Compiling the critic with the installed headers' flags, per target because a global `AVX2` switch breaks the separately built OSQP-Eigen boundary, fixes it, and a regression test replays the

injection with the live tensor shapes.

This is the class of fault a Nav2-native deployment exposes and that a standalone node or a pure 2D study cannot.

5. Discussion and Limitations

Where Should Coordination Matter? The null E-versus-F result does not contradict the design; it bounds where the design can pay off. An outcome-level benefit requires a regime in which the choice of α changes *which* escape manoeuvres are admitted at outcome-deciding moments: faster or persistent movers, tighter margins, or a dynamic gap the escape route must thread while the barrier is active. Our generator’s pedestrian-like movers produce barrier engagement (Table 7) but not that sensitivity. Constructing and measuring such a regime is future work, and we claim no coordination benefit we have not measured.

Cost Analysis. We do not report per-cycle compute. The benchmark runs a Python mirror whose timings say nothing about the C++ plugin, and the compute telemetry of the committed live pilot trials is empty ($n = 0$ samples), so any figure would be unsupported. The QP adds one small solve per cycle whose size grows with the obstacle budget N_{obs} (capped by clearance pruning), and the escape terms are evaluated only while entrapped; measuring their cost on a real-time-capable host belongs to the full-scale benchmark.

Deployment Lessons. The three live faults of Section 4.4 share a pattern: each sits on an interface (costmap semantics, the compute budget, the binary interface across the pluginlib boundary) that unit tests with one consistent build configuration and synthetic inputs do not exercise. For controller plugins that write into another library’s tensors, we recommend compiling against the installed headers’ exact flags and committing a regression test that replays live-captured shapes.

Limitations. We state the limits of the evidence explicitly.

- *Full-scale physics benchmark not run.* The quantitative comparison is the 2D mirror, not the live controller. The specified full-scale protocol, an identical Nav2 stack and differential robot across BARN (Perille et al., 2020; Xiao et al., 2024), DynaBARN (Nair et al., 2022) and HuNavSim (Pérez-Higueras et al., 2023) against stock MPPI (Macenski et al., 2020; Williams et al., 2018), DWB (Fox et al., 1997), RPP (Macenski et al., 2023), TEB (Rösmann et al., 2012), a DRPA-style always-on escape (Fuke et al., 2025) and a Shield-style CBF-only controller (Yin et al., 2023), scored by success, collision, time-to-goal, path length, clearance and compute under the same statistics, needs a GPU workstation we did not have. The live entrapment-and-escape reproduction is deferred for the same reason.
- *Coordination benefit unmeasured.* The coordination is certified-safe by construction but produced no outcome difference over independent escape+CBF (Section 4.3).
- *Braking is not a safe fallback when cornered.* In the narrow-dynamic pocket the infeasible-QP fallback ($v = 0$) leaves the robot in the path of a sweeping mover, and the CBF configurations collide more often than their no-CBF counterparts (18% $\rightarrow$ 32%). A cornered robot needs an evasive fallback, not a stop.
- *Look-ahead point versus full body.* Proposition 1 certifies the look-ahead point $\mathbf{P}_t$, not the robot body. Body safety is approximate: $L \approx r$ places $\mathbf{P}_t$ at the leading edge, and the costmap critic and collision_monitor cover the residual. Full-body certification would inflate the margin by L , which we avoid because it over-constrains sub-metre gaps. The gap is visible in the data:

body-grazing crossers still collide at 16–18% with the filter.

- *Sampled-data and slack caveats.* Invariance between samples is assumed (Assumption 1), not proven, and the shared slack couples the rows of one solve; we report slack usage instead of an unconditional certificate.
- *Constant-velocity tracker.* The obstacle model evaluated here is a constant-velocity baseline that miscalculates turning or accelerating agents and does not quantify its uncertainty. The released controller has since added occupancy-persistence static/dynamic classification, least-squares horizon prediction and an online conformal radius; these belong to follow-up work, and none of them is present in the 2D mirror behind every quantitative result reported here.
- *Other approximations.* The TTC is a one-dimensional closing-speed estimate that can induce over-rotation in tight spaces, and localization jumps in symmetric or narrow maps can perturb the progress signal.

6. Conclusion

We presented SE-MPPI, which packages local-minima escape and control-barrier-function safety, usually studied apart, in a single deployable Nav2 controller: one entrapment signal drives both a sampling-time escape critic and an output-time CBF filter, and a coordinated gain lets the robot escape while a forward-invariance argument keeps the escape certified-safe. On a randomized, paired 1,200-trial 2D benchmark, the online detection-and-escape layer is the decisive contribution, raising success from 0% to 88–90% on the U-trap family and from 0% to 62–78% on the narrow-dynamic family, with the free-space gap search load-bearing, whereas the coordination is statistically indistinguishable from independent escape+CBF in the regimes we could test. The controller loads, activates and runs in a full ROS 2 Jazzy, Nav2 and Gazebo stack, where three integration faults surfaced that only a live deployment reveals. The remaining step is the full-scale physics benchmark on a real-time-capable GPU host.

References

- A. D. Ames, X. Xu, J. W. Grizzle, and P. Tabuada. Control Barrier Function Based Quadratic Programs for Safety Critical Systems. *IEEE Transactions on Automatic Control*, 62(8):3861–3876, 2017. doi: 10.1109/TAC.2016.2638961. URL <https://doi.org/10.1109/TAC.2016.2638961>.
- A. D. Ames, S. Coogan, M. Egerstedt, G. Notomista, K. Sreenath, and P. Tabuada. Control Barrier Functions: Theory and Applications. In *2019 18th European Control Conference (ECC)*, pages 3420–3431, 2019. doi: 10.23919/ECC.2019.8796030. URL <https://arxiv.org/abs/1903.11199>.
- M. Black, G. Fainekos, B. Hoxha, H. Okamoto, and D. Prokhorov. CBFkit: A Control Barrier Function Toolbox for Robotics Applications. In *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 12428–12434, 2024. doi: 10.1109/IROS58592.2024.10801431. URL <https://arxiv.org/abs/2404.07158>.
- J. Borquez, L. Raus, Y. U. Ciftci, and S. Bansal. DualGuard MPPI: Safe and Performant Optimal Control by Combining Sampling-Based MPC and Hamilton-Jacobi Reachability. *IEEE Robotics and Automation Letters*, 10(7):6944–6951, 2025. doi: 10.1109/LRA.2025.3568686. URL <https://arxiv.org/abs/2502.01924>.

- L. Busellato, F. Cunico, D. Dall’Alba, M. Emporio, A. Giachetti, R. Muradore, and M. Cristani. Uncertainty Aware-Predictive Control Barrier Functions: Safer Human–Robot Interaction through Probabilistic Motion Forecasting. *Robotics and Autonomous Systems*, 197:105291, 2026. doi: 10.1016/j.robot.2025.105291. URL <https://arxiv.org/abs/2508.20812>.
- A. Dixit, L. Lindemann, S. X. Wei, M. Cleaveland, G. J. Pappas, and J. W. Burdick. Adaptive Conformal Prediction for Motion Planning among Dynamic Agents. In *Proceedings of the 5th Annual Learning for Dynamics and Control Conference (L4DC)*, volume 211 of *Proceedings of Machine Learning Research*, pages 300–314, 2023. URL <https://proceedings.mlr.press/v211/dixit23a.html>.
- D. Fox, W. Burgard, and S. Thrun. The Dynamic Window Approach to Collision Avoidance. *IEEE Robotics & Automation Magazine*, 4(1):23–33, 1997. doi: 10.1109/100.580977.
- T. Fuke, M. Endo, K. Honda, and G. Ishigami. DRPA-MPPI: Dynamic Repulsive Potential Augmented MPPI for Reactive Navigation in Unstructured Environments. In *2025 IEEE 21st International Conference on Automation Science and Engineering (CASE)*, pages 961–968, 2025. doi: 10.1109/CASE58245.2025.11163902. URL <https://arxiv.org/abs/2503.20134>.
- J. Gonzales, K. Mizuta, K. Leung, and L. J. Ratliff. Safe Probabilistic Planning for Human-Robot Interaction using Conformal Risk Control. In *2025 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 18676–18683, 2025. doi: 10.1109/IROS60139.2025.11247339. URL <https://arxiv.org/abs/2603.10392>.
- K. Honda, N. Akai, K. Suzuki, M. Aoki, H. Hosogaya, H. Okuda, and T. Suzuki. Stein Variational Guided Model Predictive Path Integral Control: Proposal and Experiments with Fast Maneuvering Vehicles. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7020–7026, 2024. doi: 10.1109/ICRA57147.2024.10611021. URL <https://arxiv.org/abs/2309.11040>.
- L. Lindemann, M. Cleaveland, G. Shim, and G. J. Pappas. Safe Planning in Dynamic Environments Using Conformal Prediction. *IEEE Robotics and Automation Letters*, 8(8):5116–5123, 2023. doi: 10.1109/LRA.2023.3292071. URL <https://arxiv.org/abs/2210.10254>.
- S. Macenski, F. Martín, R. White, and J. Ginés Clavero. The Marathon 2: A Navigation System. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 2718–2725, 2020. doi: 10.1109/IROS45743.2020.9341207. URL <https://arxiv.org/abs/2003.00368>.
- S. Macenski, S. Singh, F. Martín, and J. Ginés. Regulated Pure Pursuit for Robot Path Tracking. *Autonomous Robots*, 47(6):685–694, 2023. doi: 10.1007/s10514-023-10097-6. URL <https://arxiv.org/abs/2305.20026>.
- I. S. Mohamed, K. Yin, and L. Liu. Autonomous Navigation of AGVs in Unknown Cluttered Environments: log-MPPI Control Strategy. *IEEE Robotics and Automation Letters*, 7(4):10240–10247, 2022. doi: 10.1109/LRA.2022.3192772. URL <https://arxiv.org/abs/2203.16599>.
- A. Nair, F. Jiang, K. Hou, Z. Xu, S. Li, X. Xiao, and P. Stone. DynaBARN: Benchmarking Metric Ground Navigation in Dynamic Environments. In *2022 IEEE International Symposium on Safety, Security, and Rescue Robotics (SSRR)*, pages 347–352. IEEE, 2022. doi: 10.1109/SSRR56537.2022.10018758.
- H. K. Park, T. Kim, and D. Panagou. Beyond Collision Cones: Dynamic Obstacle Avoidance for Nonholonomic Robots via Dynamic Parabolic Control Barrier Functions. arXiv preprint arXiv:2510.01402, 2025. URL <https://arxiv.org/abs/2510.01402>. Accepted to IEEE International Conference on Robotics and Automation (ICRA) 2026.

- H. Parwana, M. Black, G. Fainekos, B. Hoxha, H. Okamoto, and D. Prokhorov. Model Predictive Path Integral Methods with Reach-Avoid Tasks and Control Barrier Functions. arXiv preprint arXiv:2407.13693, 2024. URL <https://arxiv.org/abs/2407.13693>.
- H. Parwana, T. Kim, K. Long, B. Hoxha, H. Okamoto, G. Fainekos, and D. Panagou. BR-MPPI: Barrier Rate Guided MPPI for Enforcing Multiple Inequality Constraints with Learned Signed Distance Field. arXiv preprint arXiv:2506.07325, 2025. URL <https://arxiv.org/abs/2506.07325>.
- N. Pérez-Higueras, R. Otero, F. Caballero, and L. Merino. HuNavSim: A ROS 2 Human Navigation Simulator for Benchmarking Human-Aware Robot Navigation. *IEEE Robotics and Automation Letters*, 8(11):7130–7137, 2023. doi: 10.1109/LRA.2023.3316072. URL <https://arxiv.org/abs/2305.01303>.
- D. Perille, A. Truong, X. Xiao, and P. Stone. Benchmarking Metric Ground Navigation. In *2020 IEEE International Symposium on Safety, Security, and Rescue Robotics (SSRR)*, pages 116–121, 2020. doi: 10.1109/SSRR50563.2020.9292572. URL <https://arxiv.org/abs/2008.13315>.
- P. Rabiee and J. B. Hoagg. Guaranteed-Safe MPPI Through Composite Control Barrier Functions for Efficient Sampling in Multi-Constrained Robotic Systems. In *2025 IEEE 64th Conference on Decision and Control (CDC)*, pages 5515–5520, 2025. doi: 10.1109/CDC57313.2025.11312129. URL <https://arxiv.org/abs/2410.02154>.
- C. Rösmann, W. Feiten, T. Wösch, F. Hoffmann, and T. Bertram. Trajectory Modification Considering Dynamic Constraints of Autonomous Robots. In *Proceedings of ROBOTIK 2012; 7th German Conference on Robotics*, pages 74–79. VDE Verlag, 2012. URL <https://ieeexplore.ieee.org/document/6309484>.
- J. Sacks and B. Boots. Learning Sampling Distributions for Model Predictive Control. In *Proceedings of the 6th Conference on Robot Learning (CoRL)*, volume 205 of *Proceedings of Machine Learning Research*, pages 1733–1742, 2022. URL <https://proceedings.mlr.press/v205/sacks23a.html>.
- B. Stellato, G. Banjac, P. Goulart, A. Bemporad, and S. Boyd. OSQP: An Operator Splitting Solver for Quadratic Programs. *Mathematical Programming Computation*, 12(4):637–672, 2020. doi: 10.1007/s12532-020-00179-2. URL <https://arxiv.org/abs/1711.08013>.
- E. Trevisan and J. Alonso-Mora. Biased-MPPI: Informing Sampling-Based Model Predictive Control by Fusing Ancillary Controllers. *IEEE Robotics and Automation Letters*, 9(6):5871–5878, 2024. doi: 10.1109/LRA.2024.3397083. URL <https://arxiv.org/abs/2401.09241>.
- Z. Wang, O. So, J. Gibson, B. Vlahov, M. S. Gandhi, G.-H. Liu, and E. A. Theodorou. Variational Inference MPC using Tsallis Divergence. In *Robotics: Science and Systems XVII*, 2021. doi: 10.15607/RSS.2021.XVII.073. URL <https://arxiv.org/abs/2104.00241>.
- G. Williams, P. Drews, B. Goldfain, J. M. Rehg, and E. A. Theodorou. Information-Theoretic Model Predictive Control: Theory and Applications to Autonomous Driving. *IEEE Transactions on Robotics*, 34(6):1603–1622, 2018. doi: 10.1109/TRO.2018.2865891. URL <https://arxiv.org/abs/1707.02342>.
- X. Xiao, Z. Xu, A. Datar, G. Warnell, P. Stone, J. J. Damanik, J. Jung, C. A. Deresa, T. D. Huy, C. Jinyu, C. Yichen, J. A. Cahyono, J. Wu, L. Mo, M. Lv, B. Lan, Q. Meng, W. Tao, and L. Cheng. Autonomous Ground Navigation in Highly Constrained Spaces: Lessons Learned From the Third BARN Challenge at ICRA 2024. *IEEE Robotics & Automation Magazine*, 31(3):197–204, 2024. doi: 10.1109/MRA.2024.3427891. URL <https://arxiv.org/abs/2407.01862>.

- J. Yin, C. Dawson, C. Fan, and P. Tsiotras. Shield Model Predictive Path Integral: A Computationally Efficient Robust MPC Method Using Control Barrier Functions. *IEEE Robotics and Automation Letters*, 8(11):7106–7113, 2023. doi: 10.1109/LRA.2023.3315211. URL <https://arxiv.org/abs/2302.11719>.
- H. Zhou, Y. Zhang, and W. Luo. Safety-Critical Control with Uncertainty Quantification using Adaptive Conformal Prediction. In *2024 American Control Conference (ACC)*, pages 574–580, 2024. doi: 10.23919/ACC60939.2024.10644391. URL <https://arxiv.org/abs/2407.03569>.

A. Reproduction

All paths are relative to the code release (<https://github.com/kjungmo/se-mppi-nav2>, Apache-2.0).

Software. ROS 2 Jazzy, Nav2 and Gazebo are installed through RoboStack (conda channels `robostack-jazzy` and `conda-forge`) by `scripts/setup_ros2_env.sh`, which also installs `osqp-eigen` and `eigen` for the CBF-QP and a compiler toolchain, so the build does not depend on the host OS version.

Benchmark regeneration. Every benchmark number is generated from the committed per-trial file by committed scripts. The committed data use $N = 50$:

```
export MAMBA_ROOT_PREFIX=$HOME/micromamba
micromamba run -n ros2 python3 -m experiments.benchmark2d.runner \
    --families utrap clutter dynamic narrowdyn -n 50 --workers 6 --max-steps 400
micromamba run -n ros2 python3 -m experiments.benchmark2d.report
```

The figures and tables of this paper are regenerated from those outputs, and the mechanism runs of Table 2 are re-executed, by

```
micromamba run -n ros2 python3 docs/papers/arxiv_ref/scripts/make_figures.py
python3 docs/papers/arxiv_ref/scripts/make_tables.py
python3 scripts/check_paper_numbers.py --arxiv
```

Scenarios and seeds. Seeds 0–49 per family; the generators in `experiments/benchmark2d/scenarios.py` seed numpy generators with a per-family offset plus the trial seed (10^6 U-trap, 2×10^6 clutter, 3×10^6 dynamic, 4×10^6 narrow-dynamic), and the MPPI noise stream uses the same trial seed (`experiments/benchmark2d/runner.py`), so every configuration sees identical worlds and rollout noise. The six toggle sets are in `experiments/benchmark2d/configs.py`; the overlays for the deferred full-scale protocol are in `experiments/configs/ablations.yaml`.

Data. Raw per-trial data: `experiments/results_2d/trials.csv` (1,200 rows). Aggregates and statistics: `summary.csv`, `stats.json`, `tables.md` in the same directory. Live pilot telemetry and logs: `experiments/results_pilot/`. The claim-to-artifact map for this paper is `docs/papers/arxiv_ref/NUMBERS.md`.

B. Parameters

C. Differences Between the 2D Mirror and the Nav2 Controller

The 2D mirror (`experiments/prototype/se_mppi_proto.py`, driven by `experiments/benchmark2d/rollout.py`) reuses the controller’s formulas but differs in the following documented ways.

- *Progress signal.* Without a global path, entrapment is declared when the best distance-to-goal has not improved by 10^{-3} m for $W = 15$ cycles, instead of the stall of $k_t^{\max}$ in (3).
- *Gap use.* The selected gap bearing places a temporary subgoal 2.5 m along the opening, replacing the goal in the MPPI cost while entrapped, in lieu of Nav2’s global routing and the critic’s C_{gap} term; the gap choice carries a hysteresis term toward the previous bearing so that symmetric openings do not flip every cycle.

Table 5: Parameters. Released-controller defaults come from the package’s parameter file and parameter getters; 2D-mirror values from the prototype primitives and the benchmark rollout (Sections A and C).

Symbol	Meaning	Released controller	2D mirror
$T, \Delta t$	MPPI horizon steps, step (s)	56, 0.05	25, 0.1
K	rollouts per cycle	1000	600
λ	MPPI temperature	0.3	0.3
$\Sigma^{1/2}$	sampling std. of (ν, ω)	(0.2, 0.4)	(0.25, 0.6)
$\mathcal{U}$	$\nu \in [\nu_{\min}, \nu_{\max}]$, $ \omega \leq \omega_{\max}$	$[-0.35, 0.5]$, 1.9	$[-0.35, 0.5]$, 1.9
W	entrapment stall window (cycles)	30	15
ϵ_{goal}	entrapment suppression radius (m)	0.5	–
d_0, η	APF influence distance (m), gain	0.6, 1.0	0.8, 0.3
$N_r, r_{\max}, r_{\min}$	gap rays, ray range (m), min. clearance (m)	36, 2.0, 0.6	72, 3.0, 2.4
w_g	gap-attraction weight	4.0	subgoal (Section C)
L	look-ahead distance (m)	0.2	0.2
r, m	robot radius (m), safety margin (m)	0.225 (logged), 0.05	0.22, 0.05
ρ	QP slack weight	10^3	10^3
ϵ_δ	slack threshold for braking	10^{-3}	10^{-3}
N_{obs}	obstacles kept in the QP	20	all dynamic
$\alpha_{\text{base}}, \alpha_{\text{escape}}$	CBF class- $\mathcal{K}$ gains	2.0, 6.0	2.0, 6.0
τ	TTC override threshold (s)	1.5	1.5
$v_{\text{dyn}}, R_{\max}$	CBF admission: min. speed (m/s), max. radius (m)	0.1, 1.0	$\ \mathbf{v}_o\ > 0$

- *Geometry.* Obstacles, including walls built from chains of discs, are circles; APF distances and ray lengths are computed analytically against them rather than on a costmap distance field.
- *Obstacle knowledge.* The CBF and TTC receive the true positions and velocities of the moving obstacles, so the tracker of Section 3.4 is not exercised.
- *Costs.* The MPPI cost is a goal-distance, path-progress and obstacle-proximity cost rather than Nav2’s critic stack; parameters differ as listed in Table 5.
- *Mechanism scenes.* Table 2 comes from `run_validation.py`, whose CBF sees all obstacles, including the static wall discs; the benchmark mirror restricts the CBF to movers, as the Nav2 controller does.

D. Extended Results

Table 6 lists every configuration and family of the benchmark, and Table 7 the slack usage behind the discussion of Sections 3.6 and 4.3. Configurations E and F coincide exactly on U-trap and clutter because the CBF sees no obstacle in those mover-free families, so the gain schedule is irrelevant there.

E. Notation

Table 6: Full per-family results of the 2D benchmark ($N = 50$ per cell). Rates in %; time-to-goal and path length are means over successful trials only ($\pm 95\%$ CI half-width); minimum clearance is over all trials. Source: experiments/results_2d/summary.csv.

Family	Config	Succ.	Coll.	Timeout	Time-to-goal (s)	Path (m)	Min. clear. (m)
U-trap	A	0	0	100	–	–	0.33 $\pm$ 0.00
	C	90	0	10	31.34 $\pm$ 1.36	8.12 $\pm$ 0.33	0.32 $\pm$ 0.00
	D	0	0	100	–	–	0.33 $\pm$ 0.00
	E	88	0	12	31.20 $\pm$ 1.36	8.09 $\pm$ 0.32	0.32 $\pm$ 0.00
	F	88	0	12	31.20 $\pm$ 1.36	8.09 $\pm$ 0.32	0.32 $\pm$ 0.00
	F [–]	0	0	100	–	–	0.33 $\pm$ 0.00
Clutter	A	52	0	48	15.23 $\pm$ 0.49	5.81 $\pm$ 0.17	0.36 $\pm$ 0.02
	C	62	0	38	17.67 $\pm$ 2.11	6.14 $\pm$ 0.32	0.35 $\pm$ 0.02
	D	52	0	48	15.23 $\pm$ 0.49	5.81 $\pm$ 0.17	0.36 $\pm$ 0.02
	E	62	0	38	17.67 $\pm$ 2.11	6.14 $\pm$ 0.32	0.35 $\pm$ 0.02
	F	62	0	38	17.67 $\pm$ 2.11	6.14 $\pm$ 0.32	0.35 $\pm$ 0.02
	F [–]	52	0	48	15.23 $\pm$ 0.49	5.81 $\pm$ 0.17	0.36 $\pm$ 0.02
Dynamic	A	80	20	0	22.48 $\pm$ 1.44	7.99 $\pm$ 0.55	0.12 $\pm$ 0.03
	C	76	20	4	21.87 $\pm$ 1.36	7.75 $\pm$ 0.53	0.13 $\pm$ 0.03
	D	82	16	2	22.74 $\pm$ 1.52	8.02 $\pm$ 0.65	0.13 $\pm$ 0.03
	E	78	18	4	21.77 $\pm$ 1.25	7.56 $\pm$ 0.47	0.13 $\pm$ 0.03
	F	78	18	4	21.78 $\pm$ 1.25	7.57 $\pm$ 0.47	0.13 $\pm$ 0.03
	F [–]	84	16	0	23.01 $\pm$ 1.66	8.14 $\pm$ 0.68	0.13 $\pm$ 0.03
Narrow-dyn.	A	0	18	82	–	–	0.22 $\pm$ 0.04
	C	78	18	4	30.52 $\pm$ 1.30	8.33 $\pm$ 0.44	0.21 $\pm$ 0.04
	D	0	32	68	–	–	0.19 $\pm$ 0.04
	E	64	32	4	30.55 $\pm$ 1.50	8.24 $\pm$ 0.55	0.18 $\pm$ 0.04
	F	62	32	6	30.36 $\pm$ 1.51	8.11 $\pm$ 0.50	0.18 $\pm$ 0.04
	F [–]	0	32	68	–	–	0.19 $\pm$ 0.04

Table 7: CBF slack usage. Trials (of 50) in which the QP relaxed a barrier row at least once, and the largest per-trial slack_max. Configurations without a CBF (A, C) are zero by construction; on the mover-free families the CBF sees no obstacle. Source: experiments/results_2d/stats.json (slack_usage).

Family	A	C	D	E	F	F [–]
U-trap	0	0	0	0	0	0
Clutter	0	0	0	0	0	0
Dynamic	0	0	47 (0.015)	48 (0.015)	48 (0.015)	47 (0.015)
Narrow-dyn.	0	0	26 (0.469)	34 (0.469)	34 (0.469)	26 (0.469)

Table 8: Notation.

Symbol	Meaning
$\mathbf{x}_t = (x_t, y_t, \theta_t), \mathbf{p}_t$	robot pose, robot position
$\mathbf{u}_t = (v_t, \omega_t), \mathcal{U}$	control (linear, angular velocity), admissible box
$\sigma = (\sigma_1, \dots, \sigma_M)$	global path from the Nav2 planner
$k_t, k_t^{\max}$	nearest and furthest-reached path index
s_t, W, e_t	stall counter, stall window, entrapment flag
$O_t; \mathbf{p}_o, R_o, \mathbf{v}_o$	tracked dynamic obstacles; position, radius, velocity
$\mathbf{P}_t, L, G(\theta)$	look-ahead point, its offset, its Jacobian
h_o, R_o^{eff}	barrier for obstacle o , effective radius $r + R_o + m$
$\alpha_t; \alpha_{\text{base}}, \alpha_{\text{escape}}$	class- $\mathcal{K}$ gain; its two scheduled values
$\delta, \rho, \epsilon_\delta$	QP slack, slack weight, braking threshold
TTC_t, τ	minimum time-to-collision, override threshold
S^k, w^k, λ	rollout cost, softmax weight, temperature
$C_{\text{apf}}, C_{\text{gap}}$	escape costs (repulsion, gap attraction)
$\psi^\star$	bearing of the selected free-space gap