Aspect-Level Sentiment Analysis of Hotel Reviews

MAAI 902 Natural Language Processing & LLMs — Assessment Task 2: NLP Solution Design

Karthik Krishna (Student ID: 1697286)
Repository: `https://github.com/kk917/hotel-review-aspect-sentiment`

23 October 2026

1 Introduction and problem definition

A hotel manager cannot tell from a star rating what to fix. This project builds and tests an NLP pipeline that reports sentiment per aspect from free-text hotel reviews. The aspects are cleanliness, staff, location, room, food, value, noise and facilities. It targets the cases where simple methods fail: negation, contrast, and several aspects in one comment.

The problem. Hotel managers receive a steady stream of online reviews. Today they use the overall score and read comments by hand. Both fail at scale. A score is one number for a stay that went well in some ways and badly in others. Reading every comment takes time that grows with each review, so recurring problems are found late. Review-level sentiment does not help. One label per review hides the mixed opinions a manager needs. Here a review-level classifier reaches only macro F1 0.603, and a perfect one would still give one label per review.

Why the hard cases matter. Three comments from the data show the problem:

- "The room was excellent, but the staff were rude at check in." The room is praised and the staff criticised, so no single label is right.
- "The wifi didn't work." Negation reverses the meaning of "work".
- "Not a clean hotel at all." A positive word ("clean") sits inside a negative statement.

A manager needs each aspect scored separately, and negated and contrasted statements read correctly.

Why NLP. Ratings cannot say which aspect upset a guest. Keyword counts find "staff" but cannot separate "staff were lovely" from "staff were not lovely". A rule that flips polarity after "not" breaks on "not bad" and on "clean but noisy". Language models read the words around a keyword, and aspect-based models also take the aspect as input. The project tests whether this helps. It compares a simple baseline with two pretrained transformers on a hand-labelled set that over-represents the hard cases (Section 3).

Scope. The solution takes English hotel reviews. For each comment and each detected aspect it returns positive, negative or neutral. It then builds a per-aspect summary with the source sentences beside every count. It uses eight keyword-based aspects, so an aspect described in unusual words is missed. It does not detect sarcasm, handle other languages, rank hotels or judge staff, and it writes no free-text summaries. The evidence is about 20,000 Booking.com reviews of European hotels and 201 hand-labelled comment–aspect pairs. Results show how the approaches compare here, not how they perform on other platforms.

Related work. Early sentiment analysis predicted one overall polarity per text. Work then moved to the aspect level, because one review can express opposing opinions about different

aspects [1]. SemEval-2014 Task 4 provided shared benchmarks: manually annotated restaurant and laptop reviews, a common evaluation procedure, and 163 submissions from 32 teams [1]. A recent survey [2] organises ABSA by the sentiment elements involved (aspect term, aspect category, opinion term and polarity). It reports that pretrained language models such as BERT and RoBERTa raised performance, and that models usually assume training and test data come from the same distribution. A systematic review of 727 studies [3] finds that ABSA research relies on a narrow set of domains and datasets, which limits how far results generalise. Recent work moves towards instruction-tuned and large language models. InstructABSA [4] beats earlier methods on SemEval benchmarks, while a broad evaluation [5] finds that large language models do well with few examples but struggle with complex, structured sentiment tasks. In the survey's terms, this project does aspect sentiment classification for given aspect categories. A keyword lexicon supplies the aspect and a pretrained model predicts its polarity. The models are used as released, so the project tests how they transfer to hotel reviews without punctuation. This project does not fine-tune or prompt a large language model (Section 3). Its contribution is a practical comparison, not a new method, on this domain and text type, with an evaluation built around negation, contrast and multi-aspect comments.

2 Data considerations and pre-processing

The project uses a random sample of 20,000 reviews from the Kaggle dataset "515K Hotel Reviews Data in Europe" [6]. It holds about 515,000 reviews of 1,493 European hotels, scraped from Booking.com, and is published under the CC0: Public Domain licence. The reviews date from August 2015 to August 2017. Three columns are used: `Positive_Review`, `Negative_Review` and `Reviewer_Score`. After removing duplicates, 19,716 reviews remain.

Why this dataset. Booking.com asks reviewers to write in two boxes, one for what they liked and one for what they disliked. This gives a free but noisy sentiment label for each comment. The text also keeps capitals and words such as "not" and "but", which the hard cases depend on. An earlier candidate, a TripAdvisor corpus, was rejected after inspection. Its text was lower-cased and stripped of stop words, which removes negation cues.

Data quality and limits.

- All punctuation was stripped by the dataset creators, so sentence boundaries cannot be found. Each text box is treated as one short comment (33,236 comments from 19,716 reviews). Contractions such as "didn t" were restored to "didn't" by rules, so negations stay recognisable.
- Reviewers sort their own remarks into the two boxes. A model trained here may do worse on free-form reviews.
- The data covers European hotels only, comes from self-selected reviewers, is scraped, and is mostly English. Scores skew high: 64.6% of sampled reviews score 8 or higher and 36.3% score 10. Most reviews are short: the median is 22 words and 79.9% have fewer than 50.

Pre-processing. Cleaning is light. Whitespace and links are removed, the placeholders "No Positive" and "No Negative" become empty, and case and negations are kept. A keyword lexicon tags each comment with up to eight aspects. At least one aspect is found in 85.5% of comments. Three keyword flags mark hard cases: negation (29.5% of comments), contrast words such as "but" (13.5%) and several aspects in one comment (49.4%). The baseline uses TF-IDF with one- and two-word features. The transformers use their own sub-word representations.

Evaluation set. The box a comment came from is only a weak label. So a hand-checked set was built at aspect level. It has 201 (comment, aspect) pairs in four groups sampled at about 50 pairs each: contrast, negation, multi-aspect and plain. After labelling, group sizes range from 35

to 70. The originating box was hidden. Each pair has a sentiment toward its aspect (positive 94, negative 81, neutral 18, not applicable 8) and a difficulty type. "Not applicable" marks keyword false alarms, 4% of pairs. A language model drafted the labels, and the author then reviewed every row and changed one sentiment label. The draft is kept in frozen columns. The reviewer saw the draft, so the 99.5% agreement (kappa 0.992) is not independent inter-annotator agreement. The set is small and stratified by keyword flags, so it does not reflect the natural mix of comments.

3 Pipeline and architecture design

The pipeline turns raw reviews into a per-aspect summary. Reviews are cleaned and split into comments, tagged with aspects, scored for sentiment toward each aspect, and aggregated with their source sentences (Figure 1).




Figure 1: The pipeline. Step 5 (highlighted) is the only step that sees the aspect it is judging. Five models are compared at this step on the same 201 hand-labelled pairs.

Model choices. Five predictors are compared on the same labelled pairs. They test one question: does telling the model the aspect help with negation, contrast and multi-aspect comments?

- *Majority class* is the floor.
- *TF-IDF + logistic regression* is the standard baseline. It reads the whole comment and ignores the aspect. It is trained on 29,735 weak-labelled comments (labelled by their box), excluding every review in the evaluation set. Settings: one- and two-word features, minimum document frequency 2, sublinear term frequency, balanced class weights.
- *RoBERTa sentiment* [7] is a pretrained transformer that reads context, so it can in principle handle "not bad". It is aspect-blind and gives one label per comment.
- *DeBERTa ABSA* [8] is a pretrained aspect-based model. It reads the pair (comment, aspect), so "the room was excellent but the staff were rude" can score room and staff differently. It is the design's answer to multi-aspect and contrast cases.
- *Box label* returns the box a comment came from. A real system would not have this information, so it is a reference ceiling for weak labels, not a competitor.

A prompted large language model was considered but not evaluated. A comparison would be partly circular, because a language model drafted the labels.

Tuning. The transformers are used as released, with no fine-tuning or hyperparameter search. The evaluation set is too small (201 rows) to tune on without overfitting. Weak-label splits are made by review, so comments from one review never appear in both training and test sets.

Evaluation design. Models are scored on the 193 labelled pairs with a real sentiment (the 8 not-applicable pairs are excluded). Metrics are accuracy with a 95% bootstrap interval, three-class macro F1, and error counts per group. Macro F1 needs care. TF-IDF and the box label can only answer positive or negative, so they score zero on the 18 neutral pairs. That caps their macro F1

near 0.6. Accuracy is the fairer headline.

Results. Two earlier baselines frame the task. A review-level TF-IDF classifier reaches macro F1 0.603 but says nothing about aspects. A comment-level classifier predicting the box reaches 0.944, which measures how well it recovers the box, not whether it understands aspects. On the hand-labelled pairs, Table 1 gives overall results and Table 2 gives errors by group.

Table 1: Overall results on the 193 scored pairs.

Model	Accuracy (95% interval)	Macro F1 (3-class)
Majority class	0.42 to 0.55	0.218
Box label (reference)	0.82 to 0.91	0.604
TF-IDF + LogReg	0.80 to 0.90	0.594
RoBERTa (aspect-blind)	0.65 to 0.77	0.575
DeBERTa ABSA (aspect-aware)	0.76 to 0.87	0.627

Table 2: Error counts by difficulty group (lower is better).

Model	Contrast	Negation	Multi-aspect	Plain	Total of 193
TF-IDF + LogReg	20	4	2	3	29
RoBERTa (aspect-blind)	22	12	1	20	55
DeBERTa ABSA (aspect-aware)	15	9	3	8	35

Discussion. Five findings stand out.

First, the aspect-aware model beats the aspect-blind one. DeBERTa was right and RoBERTa wrong on 30 pairs, and the reverse on 10. Telling the model the aspect helps.

Second, a cheap model trained on about 30,000 weak-labelled in-domain comments matches DeBERTa overall (the intervals overlap, so this is a tie) and beats RoBERTa. It has learned this dataset's style.

Third, contrast is the hardest group for every model. Accuracy there is 0.41 to 0.59, against 0.66 to 0.99 elsewhere. DeBERTa is best (0.59, macro F1 0.52, against 0.36 for RoBERTa and 0.38 for TF-IDF). Many of these errors involve neutral labels. They are 12 of DeBERTa's 15 contrast errors, 13 of TF-IDF's 20 and 11 of RoBERTa's 22. The human called these pairs neutral, usually because the comment is mixed ("Rooms are small but typical for Paris They were very well appointed however"). The scheme has no mixed class, so a model that picks a side is marked wrong, and TF-IDF cannot answer neutral at all. Contrast difficulty is partly real and partly a limit of three-class labels.

Fourth, negation is the second weak spot. TF-IDF's four negation errors do not show that it understands negation. Most negation pairs are negative, and a bag of words that maps "not" to negative scores well without handling scope. The aspect-aware model does not solve scope either. All three models called the value of "Great location Club prices for not a club experience" positive. DeBERTa labelled "Pillows and bed are not comfortable at all" neutral. RoBERTa's main weakness is mild complaints. Of its 55 errors, 28 are negative pairs it called neutral, such as "the bedroom was a bit small" and "Tiny room for 150 EUR per night". This is probably because it was trained on tweets, not hotel complaints.

Fifth, multi-aspect pairs produced few errors for all models (1 to 3), and DeBERTa shows no advantage there. A text box holds either praise or complaint, so the aspects in one comment usually share a sentiment. The sample has few comments where aspects truly disagree. With 35

to 70 pairs per group, group-level differences are noisy and indicative only.

4 Tools, frameworks and platforms

The stack is small and open source, so the work can be rerun in a free Colab session.

Table 3: Tools and the reason each was chosen.

Tool	Role	Why chosen
Hugging Face Transformers	Runs the pretrained RoBERTa and DeBERTa models through one interface	Gives both models in a few lines; training from scratch is not feasible here
scikit-learn	TF-IDF, logistic regression, metrics, kappa, splits by review	Standard and fast; a simple baseline shows what transformers add
pandas	Loading, sampling and cleaning the CSV; holding comments and labels	The sample fits in memory, so no database is needed
spaCy	Rule-based sentence splitting when installed (regex fallback)	A light sentencizer suffices; the text has no punctuation
Gradio	The demo app: paste reviews, see the summary and evidence	One function gives a shareable interface; Streamlit or Flask need more code
Colab and Drive	Notebooks and free GPU inference	No local setup. The notebooks also run locally
GitHub	Version control and delivery of commented code and README	Required by the brief and records the history

LangChain was left out because the pipeline is a fixed sequence of functions. A hosted LLM API was left out so results can be reproduced without a key or cost.

5 Ethical and responsible AI considerations

The main risks come from the people behind the text and from over-trusting a small, partly automated evaluation. Each mitigation is marked as built or proposed.

1. **Reviewer privacy.** Reviews can contain names, phone numbers, emails or room numbers. *Built:* the demo masks emails, phone numbers and links before analysis or display, and the dataset is not redistributed. *Proposed:* a named-entity model to mask personal names, which patterns cannot find, and storing only masked text.
2. **Fake or incentivised reviews.** Scraped reviews may include paid or fabricated ones, which distort the scores a manager sees. *Built:* exact duplicates are removed. *Proposed:* detecting bursts of near-identical reviews, and showing review counts beside every score.
3. **Language and dialect bias.** The data is mostly English, from European hotels, written by reviewers who chose to write. Performance may be worse for non-native English, slang or very short comments. *Built:* results are reported by difficulty group with intervals that show how little 193 rows can prove. *Proposed:* accuracy by review length and language before any deployment.
4. **Hallucination and over-claiming.** A language model summary could invent complaints. *Built:* the demo writes no free text, and every count links to its source sentences, so a manager can verify it. The aspect tagger has a known false-alarm rate (4% of labelled pairs), which is why evidence is shown with every score.
5. **Unfair consequences for named staff.** A negative comment about a person could be used to discipline them on weak evidence. *Built:* results are aggregated by aspect (for

example "staff"), and nothing is grouped by person. Source sentences are shown, so a name in a comment would still appear until name masking (item 1) is added. *Proposed:* human review before any personnel decision, and wording that scores describe guest perception.

6. **Weak and AI-assisted labels.** Training labels come from the box a comment was written in, which is noisy. A language model drafted the evaluation labels before a human checked them. A reviewer who sees a draft may anchor on it, so the 99.5% agreement is not independent evidence of quality. *Built:* the draft is kept in frozen columns, the process is disclosed here, and no LLM is scored. *Proposed:* a second annotator working blind.
7. **Data provenance.** The data was scraped from a booking site and uploaded by a third party, so reviewers did not consent to this use. The Kaggle licence (CC0) comes from the uploader and cannot grant rights over the Booking.com content or the reviewers' text. *Built:* the data is used for coursework only, is not redistributed and is cited.

Overall, the system should be a triage tool that shows a manager where to look, with the evidence. It should never be an automatic judge of hotels or people.

6 Expected output, value proposition and conclusion

The prototype gives a manager a ranked list of aspects, worst first, with the sentences behind every number. Figure 2 comes from the demo run on four short example reviews. It illustrates the output and is not an evaluation.

The evidence table lets a manager check any count. The aspect-aware model also separates opinions that one label would merge. For "The room was excellent, but the staff were rude" it returns room positive and staff negative. The aspect-blind RoBERTa returns positive for both.

Value. The tool helps a manager decide where to look first. Instead of reading every comment, they see which aspects attract the most complaints and can open the exact sentences. Recurring problems such as noise or cleanliness show up as a pattern across reviews. Each score is traceable and nothing is generated as free text, so the output can be checked. This report did not measure time saved or business impact. Those remain hypotheses to test with real managers.

Limitations. The demo also shows the system's weaknesses. The model labelled "the breakfast was good" and "a lovely pool" as neutral, and "the wifi didn't work" as neutral in one test. The keyword tagger counted "Bathroom was dirty" under room as well as cleanliness. It missed cleanliness in "Not the cleanest hotel". These match Section 3: a DeBERTa accuracy interval of 0.76 to 0.87, a weak showing on contrast, and a lexicon that limits which aspects are found. The results come from one dataset, and one person checked the AI-drafted labels.

Future work. The most useful next steps are:

- fine-tune the aspect-aware model on this domain;
- replace the keyword tagger with a learned aspect extractor;
- mask personal names with a named-entity model;
- add a second, blind annotator and a "mixed" label;
- test a prompted language model and the tool with real managers.

Conclusion. Review-level scores hide what managers need to know. A pipeline that tags aspects and scores each one separately recovers more of it. In these experiments the aspect-aware transformer was more accurate than the aspect-blind one and made fewer errors on contrast, while a simple in-domain baseline stayed competitive overall. Aspect-level analysis is feasible and checkable with modest tools. Contrast and negation remain hard. A larger, independently labelled evaluation is needed before anyone relies on it.

Weakest aspect: **noise** (net score -1.0). Each row below links a sentiment to its source sentence.

Manager summary (per aspect, worst first)

aspect	positive	neutral	negative	mentions	net_score
noise	0	0	1	1	-1
staff	0	0	1	1	-1
cleanliness	0	0	2	2	-1
facilities	0	1	1	2	-0.5
food	0	1	0	1	0
room	2	0	1	3	0.33
location	1	0	0	1	1
value	1	0	0	1	1

Evidence: every sentence-aspect pair

review	sentence	aspect	sentiment
1	The room was excellent, but the staff were rude at check in.	staff	negative
1	The room was excellent, but the staff were rude at check in.	room	positive
2	Location was perfect and the breakfast was good.	location	positive
2	Location was perfect and the breakfast was good.	food	neutral
2	The wifi didn't work and the street was noisy at night.	noise	negative
2	The wifi didn't work and the street was noisy at night.	facilities	negative
3	Not a clean hotel at all.	cleanliness	negative
3	Bathroom was dirty and we were charged for things we didn't use.	cleanliness	negative
3	Bathroom was dirty and we were charged for things we didn't use.	room	negative
4	Great value for the price, very comfy beds and a lovely pool.	room	positive
4	Great value for the price, very comfy beds and a lovely pool.	value	positive
4	Great value for the price, very comfy beds and a lovely pool.	facilities	neutral

Figure 2: The Gradio demo on four example reviews. Top: the manager summary, worst aspect first (net score = (positive − negative) / mentions). Bottom: the evidence table linking every sentiment to its source sentence.

References

[1] Pontiki, M., Galanis, D., Pavlopoulos, J., Papageorgiou, H., Androutsopoulos, I. and Manandhar, S. (2014) 'SemEval-2014 Task 4: Aspect Based Sentiment Analysis', *Proceedings of the 8th International Workshop on Semantic Evaluation (SemEval 2014)*, Dublin, Ireland, pp. 27–35. Available at: `https://aclanthology.org/S14-2004/`

[2] Zhang, W., Li, X., Deng, Y., Bing, L. and Lam, W. (2022) 'A Survey on Aspect-Based Sentiment Analysis: Tasks, Methods, and Challenges', *arXiv preprint* arXiv:2203.01054. Available at: `https://arxiv.org/abs/2203.01054` (Accessed: 23 October 2026).

[3] Hua, Y. C., Denny, P., Wicker, J. and Taskova, K. (2024) 'A systematic review of aspect-based sentiment analysis: domains, methods, and trends', *Artificial Intelligence Review*, 57, article 296. Available at: `https://link.springer.com/article/10.1007/s10462-024-10906-z` (Accessed: 25 October 2026).

[4] Scaria, K., Gupta, H., Goyal, S., Sawant, S., Mishra, S. and Baral, C. (2024) 'InstructABSA: Instruction Learning for Aspect Based Sentiment Analysis', *Proceedings of NAACL 2024 (Short Papers)*, Mexico City, pp. 720–736. Available at: `https://aclanthology.org/2024.naacl-short.63` (Accessed: 25 October 2026).

[5] Zhang, W., Deng, Y., Liu, B., Pan, S. and Bing, L. (2024) 'Sentiment Analysis in the Era of Large Language Models: A Reality Check', *Findings of NAACL 2024*, pp. 3881–3906. Available at: `https://aclanthology.org/2024.findings-naacl.246` (Accessed: 25 October 2026).

[6] jiashenliu (n.d.) *515K Hotel Reviews Data in Europe* [Dataset]. Kaggle. Available at: `https://www.kaggle.com/datasets/jiashenliu/515k-hotel-reviews-data-in-europe` (Accessed: 23 October 2026).

[7] cardiffnlp (n.d.) *twitter-roberta-base-sentiment-latest* [Model]. Hugging Face. Available at: `https://huggingface.co/cardiffnlp/twitter-roberta-base-sentiment-latest` (Accessed: 23 October 2026).

[8] yangheng (n.d.) *deberta-v3-base-absa-v1.1* [Model]. Hugging Face. Available at: `https://huggingface.co/yangheng/deberta-v3-base-absa-v1.1` (Accessed: 23 October 2026).