

KT TrafficGenerator

Overview

Video: <https://drive.google.com/file/d/1aWtYc9R36u8INKzC7HbGY1hLKqg6hy7C/view?usp=sharing>

Passcode: kZM0z@e2

Slides walk thru

- background
- overall 'picture'

Code walk-thru

video: <https://drive.google.com/file/d/1qIFO1AOiJNomuBCM38KUSqQJ3yHwITcX/view?usp=sharing>

Passcode: Kd6a6&r%

All java code

Main java packages

Application 'flow'

- visitor
 - construct 'visitor' object for each visitor
 - signal to site handler, payload = visitor object
- site
 - read site config
 - reindex catalog
 - adjust product urls
 - if campaigns, adjust price/sale-price/...
 - Note for 'Shopify' store catalog via datahub
 - don't reindex (data hub does that automatically)
 - execute one of the three types of journeys
 - predefined journey
 - random journey
 - curated journey
 - very similar to 'predefined' journey
 - make discovery API calls (search, ...)
 - trigger events

Build/test/deploy steps

video: https://drive.google.com/file/d/18kPBKd0v2GaS9jb_TT-TpQ6QeDXbyiZh/view?usp=sharing

Passcode: 6t333n1.

maven for build

shell scripts to debug / testing

- debug 'environment' - 'local', "qa", "prod"

docker generation

- build docker to upload to GCP (google cloud)
- upload docker .tar to GCP (vm2)

on GCP/vm2:

- load docker .tar
- run docker script
- use crontab to configure all accounts' traffic

on GCP/vm2:

- log files help to see generator status / data / ...
 - output/generatorMessages.log —> debug/warn/err logs
 - api, pixel count logs —> count of api, pixel calls
 - generatorLog*tsv -> log message for each 'step' (search/suggest/...)
- log level (debug/warn/...) set via command line parameter (-l <debug|warn...)

also on GCP/vm2:

- file cleaner script (~/.sysop/rm_old_file.sh)
 - clean up files older than N days (N = 3)
 - keep disk space under control
 - run via crontab

setting up traffic generator for a new account "xyz" on vm2:

- create a folder ~/project/trafficgenerator/data/xyz
- inside data/xyz, create two sub-folders "input", "output"
- depending on which catalog to use (eg, home, apparel), copy that account's input/* to data/xyz/input (do recursive cp)
 - edit data/xyz/input/config/site.json for this acc's id, name, etc
 - also edit other config info (eg, RTS, RBS, widgets.json, ...)
- if needed, do a trial run of traffic generator for 'xyz' using one of the debug scripts (in scripts/deploy_*sh)
 - review logs created in data/xyz/output/*log files
- after verifying, update crontab to run traffic generator for 'xyz'
 - typically start each crontab entry slightly staggered from each other
 - eg, set the start time ~5min after the previous one. This is just to ensure there is no immediate load on the vm at the same time
- after 1~2 days, see the tools dashboard to verify pixels, pixel parameters etc