

Name: Kamlesh Kale

PRN No: 202501090146

Division: ME2

Batch: ME23

Codetantra practical 3

3.1.1 problem statement

Write a Python program to create a NumPy array based on user input and display the following:

- The created NumPy array.
- The number of dimensions of the array using `ndim`
- The shape of the array using `shape`
- The total number of elements in the array using `size`

Assume all input elements are valid integers.

Input Format:

- The first line contains two space-separated integers, `n` and `m`, representing the number of rows and the number of columns.
- The next `n` lines contain `m` space-separated integers representing the elements of the array, entered row by row.

Output Format:

- The created NumPy array (printed as a 2D array).
- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

Note: Use `reshape()` function to reshape the input array with the specified number of rows and columns.

Code:

```
import numpy as np
```

```
r,c = map(int,input().split())
elements = []
for _ in range(r):
    elements.extend(map(int,input().split()))
array = np.array(elements).reshape(r,c)

print(array)

print(array.ndim)

print(array.shape)

print(array.size)
```

Output:

Average time

0.010 s


9.83 ms



Maximum time

0.017 s

17.00 ms



✓ 2 out of 2 shown test case(s) passed

✓ 10 out of 10 hidden test case(s) passed

✓ Test case 1

17 ms



Expected output

Actual output

3 4

3 4

1 2 3 4

1 2 3 4

5 6 7 8

5 6 7 8

9 10 11 12

9 10 11 12

<code>[[·1··2··3··4]</code>	<code>[[·1··2··3··4]</code>
<code>·[·5··6··7··8]</code>	<code>·[·5··6··7··8]</code>
<code>·[·9·10·11·12]]</code>	<code>·[·9·10·11·12]]</code>
<code>2</code>	<code>2</code>
<code>(3,·4)</code>	<code>(3,·4)</code>
<code>12</code>	<code>12</code>

✓ Test case 2 3 ms 🛡️ ☰ 📄 ^	
Expected output	Actual output
<code>0 0</code>	<code>0 0</code>
<code>[]</code>	<code>[]</code>
<code>2</code>	<code>2</code>
<code>(0,·0)</code>	<code>(0,·0)</code>
<code>0</code>	<code>0</code>

Practical Lab Assignment

3.2.1 problem statement

The given code takes two 3×3

matrices, `matrix_a`, and `matrix_b`, as input from the user and converts them into NumPy arrays.

Task:

You are required to compute and display the results of the following matrix operations:

1. **Addition** ($\text{matrix_a} + \text{matrix_b}$)
2. **Subtraction** ($\text{matrix_a} - \text{matrix_b}$)
3. **Element-wise Multiplication** ($\text{matrix_a} * \text{matrix_b}$)
4. **Matrix Multiplication** ($\text{matrix_a} . \text{matrix_b}$)
5. **Transpose of Matrix A**

Input Format:

- The user will input 3 rows for , each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for , each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.

5. The Transpose of Matrix A.

Code:

```
import numpy as np
```

```
# Input matrices
```

```
print("Enter Matrix A:")
```

```
matrix_a = np.array([list(map(int, input().split()))  
for i in range(3)])
```

```
print("Enter Matrix B:")
```

```
matrix_b = np.array([list(map(int, input().split()))  
for i in range(3)])
```

```
# Addition
```

```
addition_result = matrix_a + matrix_b
```

```
print("Addition (A + B):")
```

```
print(addition_result)
```

```
# Subtraction
```

```
subtraction_result = matrix_a - matrix_b
print("Subtraction (A - B):")
print(subtraction_result)

# Multiplication (element-wise)
elementwise_multiplication_result = matrix_a *
matrix_b
print("Element-wise Multiplication (A * B):")
print(elementwise_multiplication_result)

# Matrix multiplication (dot product)
matrix_multiplication_result = np.dot(matrix_a,
matrix_b)
print("A dot B:")
print(matrix_multiplication_result)

# Transpose
transpose_a = matrix_a.T
print("Transpose of A:")
print(transpose_a)
```


Average time

0.019 s


19.50 ms



Maximum time

0.027 s

27.00 ms



✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1

27 ms



^

Expected output

Actual output

Enter Matrix A: ↵	Enter Matrix A: ↵
1 2 3	1 2 3
4 5 6	4 5 6
7 8 9	7 8 9
Enter Matrix B: ↵	Enter Matrix B: ↵
1 1 1	1 1 1
1 1 1	1 1 1
1 1 1	1 1 1
Addition (A + B): ↵	Addition (A + B): ↵
[[2 3 4] ↵	[[2 3 4] ↵
· [5 6 7] ↵	· [5 6 7] ↵
· [8 9 10]] ↵	· [8 9 10]] ↵
Subtraction (A - B): ↵	Subtraction (A - B): ↵
[[0 1 2] ↵	[[0 1 2] ↵
· [3 4 5] ↵	· [3 4 5] ↵
· [6 7 8]] ↵	· [6 7 8]] ↵
Element-wise Multiplication (A * B): ↵	Element-wise Multiplication (A * B): ↵
[[1 2 3] ↵	[[1 2 3] ↵
· [4 5 6] ↵	· [4 5 6] ↵
· [7 8 9]] ↵	· [7 8 9]] ↵
A dot B: ↵	A dot B: ↵
[[6 6 6] ↵	[[6 6 6] ↵
· [15 15 15] ↵	· [15 15 15] ↵

· [24·24·24]] ↵	· [24·24·24]] ↵
Transpose of A: ↵	Transpose of A: ↵
[[1·4·7] ↵	[[1·4·7] ↵
· [2·5·8] ↵	· [2·5·8] ↵
· [3·6·9]] ↵	· [3·6·9]] ↵

✓ Test case 2 18 ms 	
Expected output	Actual output
Enter Matrix A: ↵	Enter Matrix A: ↵
2 4 8	2 4 8
9 6 5	9 6 5
7 8 9	7 8 9
Enter Matrix B: ↵	Enter Matrix B: ↵
10 12 13	10 12 13
14 15 16	14 15 16
17 18 19	17 18 19
Addition (A++B): ↵	Addition (A++B): ↵
[[12·16·21] ↵	[[12·16·21] ↵
· [23·21·21] ↵	· [23·21·21] ↵
· [24·26·28]] ↵	· [24·26·28]] ↵
Subtraction (A--B): ↵	Subtraction (A--B): ↵
[[·-8·--8·-5] ↵	[[·-8·--8·-5] ↵
· [·-5·--9·-11] ↵	· [·-5·--9·-11] ↵

<code>· [-10 · -10 · -10]] ↗</code>	<code>· [-10 · -10 · -10]] ↗</code>
Element-wise Multiplication · (A · * · B): ↗	Element-wise Multiplication · (A · * · B): ↗
<code>[[· 20 · · 48 · 104] ↗</code>	<code>[[· 20 · · 48 · 104] ↗</code>
<code>· [126 · · 90 · · 80] ↗</code>	<code>· [126 · · 90 · · 80] ↗</code>
<code>· [119 · 144 · 171]] ↗</code>	<code>· [119 · 144 · 171]] ↗</code>
A · dot · B: ↗	A · dot · B: ↗
<code>[[212 · 228 · 242] ↗</code>	<code>[[212 · 228 · 242] ↗</code>
<code>· [259 · 288 · 308] ↗</code>	<code>· [259 · 288 · 308] ↗</code>
<code>· [335 · 366 · 390]] ↗</code>	<code>· [335 · 366 · 390]] ↗</code>
Transpose · of · A: ↗	Transpose · of · A: ↗
<code>[[2 · 9 · 7] ↗</code>	<code>[[2 · 9 · 7] ↗</code>
<code>· [4 · 6 · 8] ↗</code>	<code>· [4 · 6 · 8] ↗</code>
<code>· [8 · 5 · 9]] ↗</code>	<code>· [8 · 5 · 9]] ↗</code>

3.2.2problem statement

You are given two arrays arr1 and arr2. You need to perform horizontal and vertical stacking operations on them using NumPy.

- **Horizontal Stacking:** Stack the two matrices horizontally (side by side).
- **Vertical Stacking:** Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

Code:

```
import numpy as np
```

```
# Input matrices
```

```
print("Enter Array1:")
```

```
arr1 = np.array([list(map(int, input().split())) for i
in range(3)])

print("Enter Array2:")

arr2 = np.array([list(map(int, input().split())) for i
in range(3)])

# Perform horizontal stacking (hstack)

a = np.hstack((arr1, arr2))

print("Horizontal Stack:")

print(a)


# Perform vertical stacking (vstack)

b = np.vstack((arr1, arr2))

print("Vertical Stack:")

print(b)
```

Output:

Average time

0.013 s

12.50 ms



Maximum time

0.017 s

17.00 ms



✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1

17 ms



^

Expected output

Actual output

Enter Array1: ↵	Enter Array1: ↵
1 2 3	1 2 3
4 5 6	4 5 6
7 8 9	7 8 9
Enter Array2: ↵	Enter Array2: ↵
4 5 6	4 5 6
7 8 9	7 8 9
10 11 12	10 11 12
Horizontal Stack: ↵	Horizontal Stack: ↵
[[1 2 3 4 5 6] ↵	[[1 2 3 4 5 6] ↵
[4 5 6 7 8 9] ↵	[4 5 6 7 8 9] ↵
[7 8 9 10 11 12]] ↵	[7 8 9 10 11 12]] ↵
Vertical Stack: ↵	Vertical Stack: ↵
[[1 2 3] ↵	[[1 2 3] ↵
[4 5 6] ↵	[4 5 6] ↵
[7 8 9] ↵	[7 8 9] ↵
[4 5 6] ↵	[4 5 6] ↵
[7 8 9] ↵	[7 8 9] ↵
[10 11 12]] ↵	[10 11 12]] ↵

✓

Test case 2

12 ms

🐛

☰

📄

⤴

Expected output

Actual output

Enter Array1: ↵	Enter Array1: ↵
-1 -2 -3	-1 -2 -3
-4 -5 -6	-4 -5 -6
-7 -8 -9	-7 -8 -9
Enter Array2: ↵	Enter Array2: ↵
10 11 12	10 11 12
13 14 15	13 14 15
16 17 18	16 17 18
Horizontal Stack: ↵	Horizontal Stack: ↵
[[-1 -2 -3 10 11 12] ↵	[[-1 -2 -3 10 11 12] ↵
· [-4 -5 -6 13 14 15] ↵	· [-4 -5 -6 13 14 15] ↵
· [-7 -8 -9 16 17 18]] ↵	· [-7 -8 -9 16 17 18]] ↵
Vertical Stack: ↵	Vertical Stack: ↵
[[-1 -2 -3] ↵	[[-1 -2 -3] ↵
· [-4 -5 -6] ↵	· [-4 -5 -6] ↵
· [-7 -8 -9] ↵	· [-7 -8 -9] ↵
· [10 11 12] ↵	· [10 11 12] ↵
· [13 14 15] ↵	· [13 14 15] ↵
· [16 17 18]] ↵	· [16 17 18]] ↵

3.2.3 problem statement

Write a Python program that takes the following inputs from the user:

- Start value: The starting point of the sequence.

- Stop value: The sequence should end before this value.
- Step value: The increment between each number in the sequence.

The program should then generate a sequence using numpy based on these inputs and print the generated sequence.

Input Format:

- The user will input three integer values: start, stop, and step, each on a new line.

Output Format:

- The program should print the generated sequence based on the input values.

Code:

```
import numpy as np
```

```
# Take user input for the start, stop, and step of the  
sequence
```

```
start = int(input())
```

```
stop = int(input())
```

```
step = int(input())
```

```
# Generate the sequence using np.arange()
```

```
a=np.arange(start,stop,step)
```

```
print(a)
```

```
# Print the generated sequence
```

Output:

Average time
0.008 s
8.00 ms



Maximum time
0.013 s
13.00 ms




2 out of 2 shown test case(s) passed


2 out of 2 hidden test case(s) passed


Test case 1
13 ms






Expected output	Actual output
3	3
10	10
2	2
[3 · 5 · 7 · 9] ↗	[3 · 5 · 7 · 9] ↗


Test case 2
5 ms






Expected output	Actual output
10	10
20	20
30	30
[10] ↗	[10] ↗

3.2.4 problem statement

You are given two arrays A and B. Your task is to complete the function `array_operations`, which will

convert these lists into NumPy arrays and perform the following operations:

1. Arithmetic Operations:

- Compute the element-wise sum, difference, and product of the two arrays.

2. Statistical Operations:

- Calculate the mean, median, and standard deviation of array A.

3. Bitwise Operations:

- Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: $A_i \text{ OR } B_i$).

Input Format:

- The first line contains space-separated integers representing the elements of array A.
- The second line contains space-separated integers representing the elements of array B.

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

Code:

```
import numpy as np

def array_operations(A, B):

    # Convert A and B to NumPy arrays
    A = np.array(A)
    B = np.array(B)

    # Arithmetic Operations
    sum_result = A + B
    diff_result = A - B
    prod_result = A * B

    # Statistical Operations
    mean_A = np.mean(A)
```



```
median_A = np.median(A)
```

```
std_dev_A = np.std(A)
```

```
# Bitwise Operations
```

```
and_result = A & B
```

```
or_result = A | B
```

```
xor_result = A ^ B
```

```
# Output results with one space between each  
element
```

```
print("Element-wise Sum:", ''.join(map(str,  
sum_result)))
```

```
print("Element-wise Difference:", ''.join(map(str,  
diff_result)))
```

```
print("Element-wise Product:", ''.join(map(str,  
prod_result)))
```

```
print(f"Mean of A: {mean_A}")
```

```
print(f"Median of A: {median_A}")
```

```
print(f"Standard Deviation of A: {std_dev_A}")
```

```
print("Bitwise AND:", ''.join(map(str,
and_result)))

print("Bitwise OR:", ''.join(map(str, or_result)))

print("Bitwise XOR:", ''.join(map(str, xor_result)))

A = list(map(int, input().split())) # Elements of array A
B = list(map(int, input().split())) # Elements of array B
array_operations(A, B)
```

Output:

Average time	Maximum time
0.008 s	0.011 s
7.67 ms	11.00 ms

✓ 1 out of 1 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1

11 ms

Expected output Actual output

1 2 3 4	1 2 3 4
5 6 7 8	5 6 7 8
Element-wise Sum: 6 8 10 12	Element-wise Sum: 6 8 10 12
Element-wise Difference: -4 -4 -4 -4	Element-wise Difference: -4 -4 -4 -4
Element-wise Product: 5 12 21 32	Element-wise Product: 5 12 21 32
Mean of A: 2.5	Mean of A: 2.5
Median of A: 2.5	Median of A: 2.5
Standard Deviation of A: 1.118033988749895	Standard Deviation of A: 1.118033988749895
Bitwise AND: 1 2 3 0	Bitwise AND: 1 2 3 0
Bitwise OR: 5 6 7 12	Bitwise OR: 5 6 7 12
Bitwise XOR: 4 4 4 12	Bitwise XOR: 4 4 4 12

3.2.5 problem statement

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

- Creating a view of the original_array and assigning it to view_array.
- Creating a copy of the original_array and assigning it to copy_array.

After completing these steps, observe how modifying the view affects the `original_array`, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:

Original array after modifying view:<**original_array**>

View array:<**view_array**>

- After modifying the copy:

Original array after modifying copy:<**original_array**>

Copy array:<**copy_array**>

Code:

```
import numpy as np
```

```
inputlist = list(map(int,input().split(" ")))
```

```
# Original array
```

```
original_array = np.array(inputlist)
```

```
# Create a view
```

```
view_array = original_array.view()
```

```
# Create a copy
```

```
copy_array = original_array.copy()
```

```
# Modify the view
```

```
view_array[0] = 99
```

```
print("Original array after modifying view:",  
original_array)
```

```
print("View array:", view_array)
```

```
# Modify the copy
```

```
copy_array[1] = 88
```



```
print("Original array after modifying copy:",  
original_array)
```

```
print("Copy array:", copy_array)
```

Output:

Average time

0.005 s


4.75 ms



Maximum time

0.010 s

10.00 ms



2 out of 2 shown test case(s) passed



2 out of 2 hidden test case(s) passed



Test case 1

10 ms



Expected output

10 20 30 40 50 60
70 80

Actual output

10 20 30 40 50 60
70 80

Original array after
modifying view: [99
20 30 40 50 60 70 8
0]

Original array af
ter modifying vie
w: [99 20 30 40 5
0 60 70 80]

View array: [99 20 3
0 40 50 60 70 80]

View array: [99 2
0 30 40 50 60 70
80]

Original array after
modifying copy: [99
20 30 40 50 60 70 8
0]

Original array af
ter modifying cop
y: [99 20 30 40 5
0 60 70 80]

Copy array: [10 88 3
0 40 50 60 70 80]

Copy array: [10 8
8 30 40 50 60 70
80]



Test case 2

3 ms



Expected output	Actual output
99 2 3 4 5	99 2 3 4 5
Original array after modifying view: [99 2 3 4 5]	Original array af ter modifying vie w: [99 2 3 4 5]
View array: [99 2 3 4 5]	View array: [99 2 3 4 5]
Original array after modifying copy: [99 2 3 4 5]	Original array af ter modifying cop y: [99 2 3 4 5]
Copy array: [99 88 3 4 5]	Copy array: [99 8 8 3 4 5]

3.2.6 problem statement

The given code in the editor takes a single array, array1, as space-separated integers as input from the user.

Additionally, it takes the following inputs:

- search_value: The value to search for in the array.
- count_value: The value to count its occurrences in the array.
- broadcast_value: The value to add for broadcasting across the array.

You need to complete the code to perform the following operations:

1. Searching: Find the indices where `search_value` appears in `array1` and print these indices.

2. Counting: Count how many times `count_value` appears in `array1` and print the count.

3. Broadcasting: Add `broadcast_value` to each element of `array1` using broadcasting, and print the resulting array.

4. Sorting: Sort `array1` in ascending order and print the sorted array.

Input Format:

1. A single line containing space-separated integers representing `array1`.
2. An integer `search_value` represents the value to search for in the array.
3. An integer `count_value` represents the value to count in the array.

4. An integer `broadcast_value` represents the value to add to each element of the array.

Output Format:

1. The indices where `search_value` occurs in `array1`.
2. The count of occurrences of `count_value` in `array1`.
3. The array after adding the `broadcast_value` to each element.
4. The sorted array.

Code:

```
import numpy as np
```

```
# Input array from the user
```

```
array1 = np.array(list(map(int, input().split())))
```

```
# Searching
```



```
search_value = int(input("Value to search:"))
count_value = int(input("Value to count:"))
broadcast_value = int(input("Value to add:"))
# Find indices where value matches in array1
a = np.where(array1 == search_value)[0]
print(a)

# Count occurrences in array1
b = np.count_nonzero(array1 == count_value)
print(b)

# Broadcasting addition
c = array1 + broadcast_value
print(c)

# Sort the first array
d = np.sort(array1)
print(d)
```

Output:

Average time

0.009 s

9.25 ms



Maximum time

0.013 s

13.00 ms



✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1

13 ms



Expected output	Actual output
1 1 1 2 2 2	1 1 1 2 2 2
Value to search: 1	Value to search: 1

Value to count: 2	Value to count: 2
Value to add: 2	Value to add: 2
[0.1.2]	[0.1.2]
3	3
[3.3.3.4.4.4]	[3.3.3.4.4.4]
[1.1.1.2.2.2]	[1.1.1.2.2.2]

✓ Test case 2 7 ms 👤 ☰ 📄 ^	
Expected output	Actual output
1 2 3 4 5	1 2 3 4 5
Value to search: 6	Value to search: 6
Value to count: 6	Value to count: 6
Value to add: 6	Value to add: 6
[]	[]
0	0
[.7.8.9.10.11]	[.7.8.9.10.11]
[1.2.3.4.5]	[1.2.3.4.5]

3.2.7 problem statement

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- **Print all student details:** Display the complete details of all students, including roll numbers and marks for all subjects.
- **Find total students:** Determine the total number of students in the dataset.
- **Print all student roll numbers:** Extract and print the roll numbers of all students.
- **Print Subject 1 marks:** Extract and print the marks of all students in Subject 1.
- **Find minimum marks in Subject 2:** Identify the lowest marks in Subject 2.
- **Find maximum marks in Subject 3:** Identify the highest marks in Subject 3.
- **Print all subject marks:** Display the marks of all students for each subject.

Find total marks of students: Compute the total marks for each student across all subjects..

- **Find the average marks of each student:**
Compute the average marks for each student.
- **Find average marks of each subject:** Compute the average marks for all students in each subject.

- **Find average marks of Subject 1 and Subject 2:**
Compute the average marks for Subject 1 and Subject 2.
- **Find average marks of Subject 1 and Subject 3:**
Compute the average marks for Subject 1 and Subject 3.
- **Find the roll number of students who scored 24 marks in Subject 2:** Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.
- **Find the count of students who got less than 40 marks in Subject 1:** Count the number of students who scored less than 40 marks in Subject 1.
- **Find the count of students who got more than 90 marks in Subject 2:** Count the number of students who scored more than 90 marks in Subject 2.
- **Find the count of students who scored ≥ 90 in each subject:** Count the number of students who scored 90 or more marks in each subject.

- **Find the count of subjects in which each student scored ≥ 90 :** Determine how many subjects each student scored 90 or more marks in.
- **Print Subject 1 marks in ascending order:** Sort and print the marks of students in Subject 1 in ascending order.
- **Print students who scored between 50 and 90 in Subject 1:** Display students who scored marks between 50 and 90 in Subject 1.
- **Find index positions of students who scored 79 in subject 1:** Identify the index positions of students who scored exactly 79 marks in subject 1.

Code:

```
import numpy as np
```

```
a = np.loadtxt("Sample.csv", delimiter=',',  
skiprows=1)
```

```
# 1. Print all student details
```



```
print("All student Details:\n", a)

# 2. print total students
print("Total Students:", a.shape[0])

# 3. Print all student Roll numbers
print("All Student Roll Nos", a[:, 0])

# 4. Print subject 1 marks
print("Subject 1 Marks", a[:, 1])

# 5. print minimum marks of Subject 2
print("Min marks in Subject 2", np.min(a[:, 2]))

# 6. print maximum marks of Subject 3
print("Max marks in Subject 3", np.max(a[:, 3]))

# 7. Print All subject marks
print("All subject marks:", a[:, 1:])
total = np.sum(a[:, 1:], axis=1)

# 8. print Total marks of students
print("Total Marks", total)

#(no label in sample output)
print(np.round(np.mean(a[:, 1:], axis=1), 1))
```

9. print average marks of each student

10. print average marks of each subject

```
print("Average Marks of each subject",  
np.round(np.mean(a[:, 1:], axis=0), 1))
```

11. print average marks of S1 and S2

```
print("Average Marks of S1 and S2",  
np.round(np.mean(a[:, [1, 2]], axis=0), 1))
```

12. print average marks of S1 and S3

```
print("Average Marks of S1 and S3",  
np.round(np.mean(a[:, [1, 3]], axis=0), 1))
```

13. print Roll number who got maximum marks in Subject 3

```
print("Roll no who got maximum marks in Subject  
3", a[np.argmax(a[:, 3]), 0])
```

14. print Roll number who got minimum marks in Subject 2

```
print("Roll no who got minimum marks in Subject  
2", a[np.argmin(a[:, 2]), 0])
```


15. print Roll number who got 24 marks in Subject 2

```
print("Roll no who got 24 marks in Subject 2",  
a[a[:, 2] == 24, 0].reshape(-1,1))
```

16. print count of students who got marks in Subject 1 < 40

```
print("Count of students who got marks in Subject  
1 < 40", np.sum(a[:, 1] < 40))
```

17. print count of students who got marks in Subject 2 > 90

```
print("Count of students who got marks in Subject  
2 > 90:", np.sum(a[:, 2] > 90))
```

18. print count of students in each subject who got marks >= 90

```
print("Count of students in each subject who got  
marks >= 90:",
```

```
      np.sum(a[:, 1:] >= 90, axis=0))
```

19. print count of subjects in which each student got marks >= 90

```
print("Roll no:", a[:, 0])
```

```
print("Count of subjects in which student got  
marks >= 90:",  
np.sum(a[:, 1:] >= 90, axis=1))  
  
# 20. Print S1 marks in ascending order  
print(np.sort(a[:, 1]))  
  
# 21. Print S1 marks >= 50 and <= 90  
print(a[(a[:, 1] >= 50) & (a[:, 1] <= 90)])  
print(a)  
  
# 22. Print the index position of marks 79  
print(np.where(a[:, 1] == 79))
```

Output:

Average time

0.014 s

14.00 ms

Maximum time

0.014 s

14.00 ms

1 out of 1 shown test case(s) passed

Test case 1

14 ms

Expected output	Actual output
All·student·Details: 	All·student·Detail ls:
·[[301···67···77···8 8.]] 	·[[301···67···77.. ··88.]]
·[302···78···88···7 7.]] 	·[302···78···88.. ·77.]]
·[303···45···56···8 9.]] 	·[303···45···56.. ·89.]]
·[304···88···98···4 5.]] 	·[304···88···98.. ·45.]]

· [305. . . 78. . . 88. . . 99.] [↗]	· [305. . . 78. . . 88. . . 99.] [↗]
· [306. . . 68. . . 78. . . 36.] [↗]	· [306. . . 68. . . 78. . . 36.] [↗]
· [307. . . 79. . . 12. . . 45.] [↗]	· [307. . . 79. . . 12. . . 45.] [↗]
· [308. . . 46. . . 45. . . 77.] [↗]	· [308. . . 46. . . 45. . . 77.] [↗]
· [309. . . 89. . . 32. . . 88.] [↗]	· [309. . . 89. . . 32. . . 88.] [↗]
· [310. . . 79. . . 24. . . 33.]] [↗]	· [310. . . 79. . . 24. . . 33.]] [↗]
Total · Students: · 10 [↗]	Total · Students: · 10 [↗]
All · Student · Roll · Nos · [301. · 302. · 303. · 304. · 305. · 306. · 307. · 308. · 309. · 310.] [↗]	All · Student · Roll · Nos · [301. · 302. · 303. · 304. · 305. · 306. · 307. · 308. · 309. · 310.] [↗]
Subject · 1 · Marks · [67. · 78. · 45. · 88. · 78. · 68. · 79. · 46. · 89. · 79.] [↗]	Subject · 1 · Marks · [67. · 78. · 45. · 88. · 78. · 68. · 79. · 46. · 89. · 79.] [↗]
Min · marks · in · Subject · 2 · 12.0 [↗]	Min · marks · in · Subject · 2 · 12.0 [↗]
Max · marks · in · Subject · 3 · 99.0 [↗]	Max · marks · in · Subject · 3 · 99.0 [↗]
All · subject · marks: · [[67. · 77. · 88.] [↗]	All · subject · marks: · [[67. · 77. · 88.] [↗]

· [78. · 88. · 77.] ↗	· [78. · 88. · 77.] ↗
· [45. · 56. · 89.] ↗	· [45. · 56. · 89.] ↗
· [88. · 98. · 45.] ↗	· [88. · 98. · 45.] ↗
· [78. · 88. · 99.] ↗	· [78. · 88. · 99.] ↗
· [68. · 78. · 36.] ↗	· [68. · 78. · 36.] ↗
· [79. · 12. · 45.] ↗	· [79. · 12. · 45.] ↗
· [46. · 45. · 77.] ↗	· [46. · 45. · 77.] ↗
· [89. · 32. · 88.] ↗	· [89. · 32. · 88.] ↗
· [79. · 24. · 33.]] ↗	· [79. · 24. · 33.]] ↗
Total · Marks · [232. · 243. · 190. · 231. · 265. · 182. · 136. · 168. · 209. · 136.] ↗	Total · Marks · [232. · 243. · 190. · 231. · 265. · 182. · 136. · 168. · 209. · 136.] ↗
[77.3 · 81. · · 63.3 · 77. · · 88.3 · 60.7 · 45.3 · 56. · · 69.7 · 45.3] ↗	[77.3 · 81. · · 63.3 · 77. · · 88.3 · 60.7 · 45.3 · 56. · · 69.7 · 45.3] ↗
Average · Marks · of · each · subject · [71.7 · 59.8 · 67.7] ↗	Average · Marks · of · each · subject · [71.7 · 59.8 · 67.7] ↗
Average · Marks · of · S1 · and · S2 · [71.7 · 59.8] ↗	Average · Marks · of · S1 · and · S2 · [71.7 · 59.8] ↗
Average · Marks · of · S1 · and · S3 · [71.7 · 67.7] ↗	Average · Marks · of · S1 · and · S3 · [71.7 · 67.7] ↗
Roll · no · who · got · maximum · marks · in · Subject · 3 · 305.0 ↗	Roll · no · who · got · maximum · marks · in · Subject · 3 · 305.0 ↗

Roll·no·who·got·mini mum·marks·in·Subject ·2·307.0	Roll·no·who·got·m inimum·marks·in·S ubject·2·307.0
Roll·no·who·got·24·m arks·in·Subject·2· [[310.]]	Roll·no·who·got·2 4·marks·in·Subjec t·2·[[310.]]
Count·of·students·wh o·got·marks·in·Subje ct·1·<·40·0	Count·of·students ·who·got·marks·in ·Subject·1·<·40·0
Count·of·students·wh o·got·marks·in·Subje ct·2·>·90:·1	Count·of·students ·who·got·marks·in ·Subject·2·>·90:· 1
Count·of·students·in ·each·subject·who·go t·marks·>=·90:·[0·1· 1]	Count·of·students ·in·each·subject· who·got·marks·>=· 90:·[0·1·1]
Roll·no:·[301··302·· 303··304··305··306·· 307··308··309··310.]	Roll·no:·[301··30 2··303··304··305· ·306··307··308··3 09··310.]
Count·of·subjects·in ·which·student·got·m arks·>=·90:·[0·0·0·1 ·1·0·0·0·0·0]	Count·of·subjects ·in·which·student ·got·marks·>=·90: ·[0·0·0·1·1·0·0·0 ·0·0]
[45··46··67··68··78· ·78··79··79··88··8 9.]	[45··46··67··68·· 78··78··79··79··8 8··89.]
[[301···67···77···8 8.]	[[301···67···77·· ·88.]
·[302···78···88···7	·[302···78···88··

<code>9.]</code>	<code>99.]</code>
<code>·[306...68...78...36.]</code>	<code>·[306...68...78...36.]</code>
<code>·[307...79...12...45.]</code>	<code>·[307...79...12...45.]</code>
<code>·[309...89...32...88.]</code>	<code>·[309...89...32...88.]</code>
<code>·[310...79...24...33.]]</code>	<code>·[310...79...24...33.]]</code>
<code>[[301...67...77...88.]</code>	<code>[[301...67...77...88.]</code>
<code>·[302...78...88...77.]</code>	<code>·[302...78...88...77.]</code>
<code>·[303...45...56...89.]</code>	<code>·[303...45...56...89.]</code>
<code>·[304...88...98...45.]</code>	<code>·[304...88...98...45.]</code>
<code>·[305...78...88...99.]</code>	<code>·[305...78...88...99.]</code>
<code>·[306...68...78...36.]</code>	<code>·[306...68...78...36.]</code>
<code>·[307...79...12...45.]</code>	<code>·[307...79...12...45.]</code>
<code>·[308...46...45...77.]</code>	<code>·[308...46...45...77.]</code>
<code>·[309...89...32...88.]</code>	<code>·[309...89...32...88.]</code>
<code>·[310...79...24...33.]]</code>	<code>·[310...79...24...33.]]</code>
<code>(array([6, 9], dtype=int32),)</code>	<code>(array([6, 9], dtype=int32),)</code>

