

SQL Server: Advanced Corruption Recovery Techniques

Module 6: Advanced Repair Techniques

Paul S. Randal

<http://www.SQLskills.com/blogs/paul/>
Paul@SQLskills.com



pluralsight
hardcore developer training

Introduction

- The most advanced techniques involve editing system tables and manually changing page structures directly
- Although very challenging, success could save a business or your job
- In this module we'll cover:
 - System table corruption
 - When not to run repair
 - Reconstructing deleted data
 - Manually editing data files

Is Repair Guaranteed to Work?

- The simple answer is no
- There are an infinite number of combinations of possible corruptions and it's not possible to test them all
 - Some areas are not tested well at all, like system table corruption
 - Some repairs cannot be done, like rebuilding the boot page or a PFS page
- Story: testing the repair code while at Microsoft
- If you absolutely need to have zero data loss, you must have backups or a synchronously replicated copy of the database
 - Use database mirroring, availability groups, or SAN replication
- Usually you're going to use restore, if backups are available
 - Remember the Restore vs. Repair debate from the more basic course

Metadata Corruption

- Someone manually changed system tables in SQL Server 2000...
- Hidden system tables are accessible only when the Dedicated Admin Connection (DAC) is used
 - sqlcmd -A or prefix the SSMS connection string with "admin:"
 - 2012: Error message in SSMS can be ignored
 - 2012: TF7806 at startup plus running SQL Browser allows DAC connections under all circumstances, including named instances
 - SQL Performance blog post on this at <http://bit.ly/RKxGQV>
- These tables cannot be changed unless the server is booted with -m
- From SQL Server 2008 onward, if a system table is directly modified, it is noted in the database metadata
 - **This modification makes your database technically unsupported**
 - Check DBCC DBINFO
 - If you update a system catalog using 3-part naming, the dbi_updSysCatalog of the database you're in is erroneously updated

Rebuilding System Table Indexes

- Structurally corrupt system table clustered indexes cannot be repaired successfully
- Structurally corrupt system table nonclustered indexes sometimes can be rebuilt by repair
 - You may have to play around with DBCC CHECKTABLE to find which table is corrupt as DBCC CHECKDB may fail
 - This is not guaranteed to work...be careful as it may make things worse
- I would try to avoid running repair on system tables completely
 - Or at least test it on a copy of the database

Using Older Backups and Repair

- If you don't have valid, recent backups to recover with, you may be able to use older backups along with repair
- Steps to use:
 - Perform the repair operation
 - Determine what data is missing or damaged
 - Restore the old backup as a different database name
 - Determine if any of the missing data can be salvaged from the old database
- Of course, no guarantee that the salvaged data is up-to-date, but it may be better than nothing

Reconstructing Data From Nonclustered Indexes

- If repair is the only option and heap or clustered index structures are damaged, you may be able to recover data from nonclustered indexes
 - This may also be the case if repair is impossible because of corrupt metadata
- Create SELECT statements to figure out which table rows will be lost from running repair
- Create SELECT statements to force selection from non-damaged nonclustered indexes to salvage some of the column data
- Success rates will vary depending on the amount of column coverage in the nonclustered indexes
 - May need to use DBCC PAGE, as discussed later
- Do this BEFORE running repair, as the repair will rebuild nonclustered indexes based on the repaired heap or clustered index

Using DBCC PAGE To Walk Tables

- **If repair is the only option and heap or clustered index structures are damaged, you may be able to recover data using DBCC PAGE**
 - This may also be the case if repair is impossible because of corrupt metadata
- **Method 1: to assist in figuring out what key ranges will be lost, and will need to be reconstructed from nonclustered indexes**
 - Write code to programmatically walk through table structures using DBCC PAGE ... WITH TABLERESULTS
- **Method 2: manually examine corrupt pages to try to get data values from them**
 - After first determining what the corrupt pages are, from repair or using Method 1 above

The Ultimate Advanced Recovery

- **Manually editing data files using a hex editor or DBCC WRITEPAGE is the most advanced method of corruption recovery**
 - Usually requires very detailed knowledge of database structures
- **Always take a backup before manually editing a database**
 - If something goes wrong, you can still get back to the starting point
- **I usually do this once or twice a year for clients**
 - Some examples:
 - Fixing up broken off-row LOB links in SQL Server 2000 sysindexes
 - Recreating a file header page by copying from an older backup
 - Deallocating a broken page to allow data export when other metadata problems prevent DBCC CHECKDB repair from running
- **Always run DBCC CHECKDB to make sure you haven't made things worse and have fixed the original problem**
- **Always do it on a copy of the corrupt database**
 - If a backup/restore won't work, use a file system copy and hack attach

Any Other Ways to Salvage Data?

- **Possible other places to get data:**
 - Data warehouse
 - Test/dev systems
 - 3rd-parties that host/consume some of your data
 - Replication subscribers
 - Hard-copy printouts
- **I've heard some incredible stories of tenacity in the face of corruption**
 - "Unbelievable tale of disaster recovery" at <http://bit.ly/185Z2bl>

Course Summary

- **Now you know:**

- A lot more about how DBCC CHECKDB works and it can be tuned
- Undocumented DBCC commands that can help with corruption recovery
- Methods for dealing with transaction log problems
- Advanced restore techniques
- Advanced repair techniques

- **The most important takeaways from this course:**

- Basics will only get you so far, often more unconventional techniques are needed to recover from corruption
- The more you practice, the easier corruption recovery will be
- DBCC WRITEPAGE is a powerful, but dangerous command...use it carefully

- **Email me interesting corruption stories: Paul@SQLskills.com**

- **Thanks for watching!**