

Operators in a Query Plan



Erin Stellato

PRINCIPAL CONSULTANT

@erinstellato www.sqlskills.com/blogs/erin



Module Overview




Identify frequently-seen plan operators and understand their function

Review how altering a query can change the operator used

Review how a change in operator can change query performance



What Do You Look For in a Plan?



Scans






Table Scan




Clustered Index Scan

Seeks



Clustered Index Seek




Nonclustered Index Seek

Demo



Data Access Operators






Nested Loop

Uses each row from one input (outer data set) to find rows from a second input (inner data set) that meet the join predicate

Seen with smaller data sets and lookups

Watch for inflated I/O

Lookups



Key Lookup



RID Lookup


Demo



Nested Loops and Lookups



Merge Join



Data from two ordered inputs joined

- Matching rows returned

Ideally data is already ordered (e.g. index)

Worktables used when multiple values on both sides of the data set ('many-to-many')


Sort

Orders rows

Stop-and-go operation

Requires memory

Possible to spill to disk




Demo



Merge Joins and Sorts





Hash Join

Joins two unordered inputs

- Outputs the matching rows

Builds a hash table based on key value for each row in the outer data set, then for each row of the inner data set, calculates the hash and probe the table

Possible to spill to disk


Demo



Hash Join



Compute Scalar



Evaluates an expression

- Produces a scalar value (e.g. functions)

The estimated cost can be low

Plans do not always show objects accessed

Demo



Compute Scalar



What We Covered



Identify frequently-seen plan operators and understand their function

Review how altering a query or the schema can change the operator used

Review how a change in operator can change query performance

