

ALLIANCE UNIVERSITY | NAAC GRADE A+ ACCREDITED UNIVERSITY

ASSIGNMENT 7: SAMPLE DATA INSERTION

DATABASE MANAGEMENT SYSTEM

ALLIANCE UNIVERSITY

Department of Computer Applications

SUMMITED BY: KUNGUMA KEERTHANA M

REGISTER NO: 2511021240051

COURSE: BCA

YEAR: 2ND YEAR

PROJECT TITLE: Online Food Delivery System

1. Aim

To insert realistic sample data into all the tables of the Online Food Delivery System and ensure that the inserted records satisfy the defined constraints and relationships.

2. Software Requirements

- Database Management System: MySQL
- Tool: MySQL Workbench
- Language: SQL

3. Theory

Sample data insertion is the process of adding records to database tables using the SQL INSERT INTO command. It helps test the database structure, relationships, and constraints.

In a relational database, records must be inserted in the correct order. Parent table records must exist before related records are inserted into child tables. For example, customer details must be inserted before their addresses and orders.

4. SQL Program for Sample Data Insertion

The following program inserts sample records into all ten tables.


USE online_food_delivery;

1. Customer

Input:

```
213 •   INSERT INTO Customer
214     (Customer_ID, Name, Email, Phone, Password_Hash)
215     VALUES
216     (10, 'Keerthana', 'keerthana@example.com', '9876500001', 'sample_hash_1'),
217     (20, 'Ravi', 'ravi@example.com', '9876500002', 'sample_hash_2'),
218     (30, 'Priya', 'priya@example.com', '9876500003', 'sample_hash_3'),
219     (40, 'Arun', 'arun@example.com', '9876500004', 'sample_hash_4'),
220     (50, 'Divya', 'divya@example.com', '9876500005', 'sample_hash_5');
```

output:




2. Address

Input:

```
INSERT INTO Address
(Address_ID, Customer_ID, House_No, Street, City, Pincode)
VALUES
(10, 10, '12A', 'Anna Nagar', 'Chennai', '600040'),
(20, 20, '24B', 'MG Road', 'Bengaluru', '560001'),
(30, 30, '8', 'Gandhi Street', 'Chennai', '600001'),
(40, 40, '17C', 'Park Road', 'Hosur', '635109'),
(50, 50, '5A', 'Lake View Road', 'Coimbatore', '641001');
```

Output:




3. Restaurant

Input:

```
INSERT INTO Restaurant
(Restaurant_ID, Restaurant_Name, Phone, Location, Rating)
VALUES
(10, 'Spice Garden', '9000000001', 'Chennai', 4.5),
(20, 'Burger Hub', '9000000002', 'Bengaluru', 4.2),
(30, 'Pizza Corner', '9000000003', 'Chennai', 4.4),
(40, 'South Indian Meals', '9000000004', 'Hosur', 4.1),
(50, 'Sweet Treats', '9000000005', 'Coimbatore', 4.6);
```

Output:



4. Category

Input:

```
240 •   INSERT INTO Category
241     (Category_ID, Category_Name)
242     VALUES
243     (10, 'Indian'),
244     (20, 'Burger'),
245     (30, 'Pizza'),
246     (40, 'Chinese'),
247     (50, 'Desserts');
```

Output:

```
42  19:17:39  INSERT INTO Category (Category_ID, Category_Name) VALUES (10, 'Indian'), (20, 'Burger'), (30, 'Pi...  5 row(s) affected Records: 5  Duplicates: 0  Warnings: 0
```

5. Food_Item

Input:

```
249 •   INSERT INTO Food_Item
250     (Food_ID, Restaurant_ID, Category_ID, Food_Name, Price, Availability)
251     VALUES
252     (10, 10, 10, 'Veg Biryani', 180.00, TRUE),
253     (20, 10, 10, 'Paneer Butter Masala', 220.00, TRUE),
254     (30, 20, 20, 'Veg Burger', 120.00, TRUE),
255     (40, 30, 30, 'Margherita Pizza', 250.00, TRUE),
256     (50, 40, 10, 'South Indian Meals', 150.00, TRUE),
257     (60, 50, 50, 'Chocolate Cake', 100.00, TRUE),
258     (70, 10, 40, 'Veg Noodles', 160.00, FALSE),
259     (80, 30, 30, 'Farmhouse Pizza', 320.00, TRUE);
260
```

Output:

```
45  19:20:27  INSERT INTO Food_Item (Food_ID, Restaurant_ID, Category_ID, Food_Name, Price, Availability) V...  8 row(s) affected Records: 8  Duplicates: 0  Warnings: 0
```

6. Orders

Input:

```
261 •   INSERT INTO Orders
262     (Order_ID, Customer_ID, Address_ID, Order_Date, Total_Amount, Order_Status)
263     VALUES
264     (10, 10, 10, '2026-10-15 12:30:00', 360.00, 'Delivered'),
265     (20, 20, 20, '2026-10-15 13:00:00', 120.00, 'Delivered'),
266     (30, 30, 30, '2026-10-16 19:15:00', 250.00, 'Preparing'),
267     (40, 40, 40, '2026-10-17 20:00:00', 300.00, 'Out for Delivery'),
268     (50, 50, 50, '2026-10-18 16:30:00', 200.00, 'Placed');
```

Output:

```
47  19:22:29  INSERT INTO Orders (Order_ID, Customer_ID, Address_ID, Order_Date, Total_Amount, Order_Stat...  5 row(s) affected Records: 5  Duplicates: 0  Warnings: 0
```

7. Order_Item

Input:

```
270 •   INSERT INTO Order_Item
271     (Order_Item_ID, Order_ID, Food_ID, Quantity, Subtotal)
272     VALUES
273     (60, 10, 10, 2, 360.00),
274     (70, 20, 30, 1, 120.00),
275     (80, 30, 40, 1, 250.00),
276     (90, 40, 50, 2, 300.00),
277     (100, 50, 60, 2, 200.00);
```

Output:


```
55  19:28:27  INSERT INTO Order_Item (Order_Item_ID, Order_ID, Food_ID, Quantity, Subtotal) VALUES (60, 10,...  5 row(s) affected Records: 5  Duplicates: 0  Warnings: 0
```

8. Payment

Input:

```
279 •   INSERT INTO Payment
280     (Payment_ID, Order_ID, Payment_Method, Payment_Date, Amount, Payment_Status)
281     VALUES
282     (10, 10, 'UPI', '2026-10-15 12:35:00', 360.00, 'Completed'),
283     (20, 20, 'Card', '2026-10-15 13:05:00', 120.00, 'Completed'),
284     (30, 30, 'UPI', '2026-10-16 19:20:00', 250.00, 'Pending'),
285     (40, 40, 'Cash on Delivery', '2026-10-17 20:00:00', 300.00, 'Pending'),
286     (50, 50, 'Card', '2026-10-18 16:35:00', 200.00, 'Completed');
```

Output:




9. Delivery_Partner

Input:

```
288 •   INSERT INTO Delivery_Partner
289     (Partner_ID, Partner_Name, Phone, Vehicle_No, Status)
290     VALUES
291     (1, 'Karthik', '9100000001', 'TN01AB1234', 'Available'),
292     (2, 'Suresh', '9100000002', 'KA03CD5678', 'Busy'),
293     (3, 'Manoj', '9100000003', 'TN09EF9012', 'Busy'),
294     (4, 'Vijay', '9100000004', 'TN70GH3456', 'Busy'),
295     (5, 'Naveen', '9100000005', 'TN38JK7890', 'Available');
```

Output:



10. Delivery

Input:

```
298 •   INSERT INTO Delivery
299     (Delivery_ID, Order_ID, Partner_ID, Pickup_Time, Delivery_Time, Delivery_Status)
300     VALUES
301     (10, 10, 1, '2026-10-15 12:45:00', '2026-10-15 13:15:00', 'Delivered'),
302     (20, 20, 2, '2026-10-15 13:10:00', '2026-10-15 13:40:00', 'Delivered'),
303     (30, 30, 3, '2026-10-16 19:30:00', NULL, 'Preparing'),
304     (40, 40, 4, '2026-10-17 20:15:00', NULL, 'In Transit'),
305     (50, 50, 5, NULL, NULL, 'Assigned');
```

Output:

```
61  19:38:58  INSERT INTO Delivery (Delivery_ID, Order_ID, Partner_ID, Pickup_Time, Delivery_Time, Delivery_...  5 row(s) affected Records: 5  Duplicates: 0  Warnings: 0
```

5. Verification Queries

Verify records in every table

Input:

```
307 •   SELECT * FROM Customer;
308 •   SELECT * FROM Address;
309 •   SELECT * FROM Restaurant;
310 •   SELECT * FROM Category;
311 •   SELECT * FROM Food_Item;
312 •   SELECT * FROM Orders;
313 •   SELECT * FROM Order_Item;
314 •   SELECT * FROM Payment;
315 •   SELECT * FROM Delivery_Partner;
316 •   SELECT * FROM Delivery;
```

Output:

Delivery_ID	Order_ID	Partner_ID	Pickup_Time	Delivery_Time	Delivery_Status
10	10	1	2026-10-15 12:45:00	2026-10-15 13:15:00	Delivered
20	20	2	2026-10-15 13:10:00	2026-10-15 13:40:00	Delivered
30	30	3	2026-10-16 19:30:00	NULL	Preparing
40	40	4	2026-10-17 20:15:00	NULL	In Transit
50	50	5	NULL	NULL	Assigned
NULL	NULL	NULL	NULL	NULL	NULL

6. Verify Relationships Using JOIN

Input:

```
318 •   SELECT
319         o.Order_ID,
320         c.Name AS Customer_Name,
321         r.Restaurant_Name,
322         f.Food_Name,
323         oi.Quantity,
324         oi.Subtotal,
325         o.Order_Status
326     FROM Orders o
327     JOIN Customer c
328         ON o.Customer_ID = c.Customer_ID
329     JOIN Order_Item oi
330         ON o.Order_ID = oi.Order_ID
331     JOIN Food_Item f
332         ON oi.Food_ID = f.Food_ID
333     JOIN Restaurant r
334         ON f.Restaurant_ID = r.Restaurant_ID;
```

Output:

Order_ID	Customer_Name	Restaurant_Name	Food_Name	Quantity	Subtotal	Order_Status
10	Keerthana	Spice Garden	Veg Biryani	2	360.00	Delivered
10	Keerthana	Spice Garden	Veg Biryani	2	360.00	Delivered
20	Ravi	Burger Hub	Veg Burger	1	120.00	Delivered
20	Ravi	Burger Hub	Veg Burger	1	120.00	Delivered
30	Priya	Pizza Corner	Margherita Pizza	1	250.00	Preparing
30	Priya	Pizza Corner	Margherita Pizza	1	250.00	Preparing
40	Arun	South Indian Meals	South Indian Meals	2	300.00	Out for Delivery
40	Arun	South Indian Meals	South Indian Meals	2	300.00	Out for Delivery
50	Divya	Sweet Treats	Chocolate Cake	2	200.00	Placed
50	Divya	Sweet Treats	Chocolate Cake	2	200.00	Placed

This query displays the order ID, customer, restaurant, food item, quantity, subtotal, and order status by joining related tables.

7. Record Count Verification

Input:

```
336 •       SELECT 'Customer' AS Table_Name, COUNT(*) AS Total_Records FROM Customer
337     UNION ALL
338     SELECT 'Address', COUNT(*) FROM Address
339     UNION ALL
340     SELECT 'Restaurant', COUNT(*) FROM Restaurant
341     UNION ALL
342     SELECT 'Category', COUNT(*) FROM Category
343     UNION ALL
344     SELECT 'Food_Item', COUNT(*) FROM Food_Item
345     UNION ALL
346     SELECT 'Orders', COUNT(*) FROM Orders
347     UNION ALL
348     SELECT 'Order_Item', COUNT(*) FROM Order_Item
349     UNION ALL
350     SELECT 'Payment', COUNT(*) FROM Payment
351     UNION ALL
352     SELECT 'Delivery_Partner', COUNT(*) FROM Delivery_Partner
353     UNION ALL
354     SELECT 'Delivery', COUNT(*) FROM Delivery;
```

Output:

	Table_Name	Total_Records
▶	Customer	6
	Address	5
	Restaurant	5
	Category	5
	Food_Item	8
	Orders	5
	Order_Item	10
	Payment	5
	Delivery_Partner	5
	Delivery	5

8. Procedure

1. Open MySQL Workbench and connect to the database server.
2. Select the Online_Food_Delivery database.
3. Execute the INSERT statements in the order provided.
4. Check the output panel for errors.
5. Run the verification queries to display the records.
6. Run the record count query to confirm the number of records.
7. Execute the JOIN query to verify relationships between tables.
8. Capture screenshots of the successful execution and query results.

9. Result

Sample data was inserted into all ten tables of the Online Food Delivery System. Verification queries were used to check the stored records, count the records in each table, and retrieve related information through joins.

10. Conclusion

Sample data insertion helps test the structure and relationships of a database. By inserting realistic records in the correct order and verifying them through SQL queries, the Online Food Delivery System can be tested before developing further database operations.