### Outline

- Background
- MPLS: Fundamentals
- MPLS: Terminology
- GMPLS
- GMPLS: Recovery techniques
- Summary
- Resources

# Background

- What is MPLS?
  - Mechanism that directs data from one network node to the next based on on path labels rather than network addresses.
  - MPLS switches packets (IP packets) instead of routing packets to transport the data
- Why MPLS?
  - Provide a highly scalable mechanism that was topology driven rather than flow driven
  - Load balance traffic to utilize network bandwidth efficiently
  - Allow core routers/networking devices to switch packets based on a simplified header
  - Remove the complexity and overhead of network managements (Assemble and reassemble IP packets)

# MPLS was conceived, why?

- ▶ The shortest path routing protocols like IS-IS and OSPF
  - Did not take capacity characteristics into account while making the routing decisions
  - ► The outcome is, segmentation over the network which leads to congestion, while others remain under-utilized.
- MPLS reduces the complexity and redundancies by adding new network functionalities.

#### MPLS Fundamentals

- Main idea:
  - attach a short fixed-length label to packets at the ingress to an MPLS domain
  - the labels are used to make the forwarding decisions.
- MPLS consists of a forwarding and a control plane. Though they are decoupled and independent from each other.
- Supports explicit routed path.
- ▶ Provides Quality of Service (QoS) if it is implemented with Diff-Serv and Constraint-based routing.

# Diff-Serv and Constraint-based routing

- Differentiated Services
  - ► A network architecture for classifying and managing network traffic and provide QoS on modern IP networks.
  - it is used to provide low-latency to critical network traffic. (Media, VOIP).
- Constraint-based routing
  - ▶ It is a routing technique where resource availability and traffic characterization are taken into account.

### MPLS Fundamentals




Fig. 2. Conceptual view of MPLS control plane and forwarding plane.

# MPLS Fundamentals: Control Plane

# MPLS Fundamentals: Forwarding Plane

## MPLS architecture

# MPLS: Terminology

- ▶ FEC (Forwarding Equivalence Class)
  - Group of IP packets which are forwarded in the same manner (e.g. over the same path, with the same priority and the same label)
- Label
  - Short fixed length identifier which is used to identify a FEC
- Label Swapping
  - Looking up the oncoming label to determine the outgoing label, encapsulation and port
- Label switched path (LSP)
  - Path through one or more LSR for a particular FEC
- Label switching router (LSR)
  - an MPLS capable router



## FEC

Advantages?

# What is a Label?




Figure: This is the initial phase




Figure: Request a path to a specific node, send to the lowest cost possible router




Figure: Route the message to the destination node




Figure: A label table is initialized with information that when it receives the given label id, it is for this router 47.1




Figure: Map its label id to the router that sent request




Figure: The router that receives the mapping data, adds it ot its labeltable and generates a "in" label




Figure: When finished, the next router sends the mapping date of which label will be added




Figure: When it has reached the Ingress node, it will map the given label for the given destination IP




Figure: Send message with packet to 47.1, you have now a path to choose




Figure: When forwarded, you add label onto the packet, when it arrives to a node, it checks the label and replaces it to another one and forwards it




Figure: When reached to the egress node, it will then remove the label and deliver to the specific destination

# Disadvantages of MPLS

#### MPLS has performance issues in the network:

- constraint-based routing
  - Problem with computation of paths for LSPs subject to various types of constraints.
  - NP-complete problem
- traffic partitioning and assignment
  - This problem deals with the optimal partitioning and assignment of traffic to parallel LSPs between pairs of MPLS ingress and egress nodes.
- restoration
  - many proposals for restoration in ATM might be applicable to MPLS.

### **GMPLS**

#### What is GMPLS?

■ a protocol suite extending MPLS to manage further classes of interfaces and switching technologies other than packet interfaces and switching, such as time division multiplex, layer-2 switch, wavelength switch and fiber-switch.

### **GMPLS**

- GMPLS is an extended form of MPLS and some of these improvements are:
  - RSVP-TE
  - OSPF and IS-IS
  - New link-management protocol
  - Bi-directional LSP setup
    - Reduce latency
    - Less control overhead
    - Route selection is simpler
    - Cleaner interface
  - MPLS emphasizes the seperation of control plane and network plane
  - GMPLS extends this seperation and allows the control plane to be physically diverse from the associated data plane

# **GMPLS: Hierarchial LSP**

- •

# Summary

- ► MPLS
- ► GMPLS

#### Resources

- ► Generalized Multiprotocol Label Switching: An Overview of Signaling Enhancements and Recovery Techniques IEEE Communication Magazine, July 2001. A. Banerjee et. al.
- ▶ Internet Traffic Engineering Using Multi-Protocol Label Switching (MPLS). Computer Networks 40, Elsevier, 2002 D.O. Awduche and B. Jabbari.