# Train in Python, deploy anywhere and anyhow

Christian Bourjau

July 26, 2023

QuantCo PyData Zurich



### Outline

What makes deploying models difficult?

What is ONNX?

Expressing models in Spox

Summary

What makes deploying models

difficult?

Define pipeline with feature engineering: Python rocks!

### Training environment



- Define pipeline with feature engineering: Python rocks!
- Train: Python rocks!

# Source train Trained model Data

- Define pipeline with feature engineering: Python rocks!
- Train: Python rocks!
- Pickle the trained model: Python rocks?

# Source train Trained model pickle Artefact Data

- Define pipeline with feature engineering: Python rocks!
- Train: Python rocks!
- Pickle the trained model: Python rocks?
- Deploy ...

### **Training environment**



- Pickle makes it hard to:
  - Distribute models

- Pickle makes it hard to:
  - Distribute models
  - Archive models
  - Compose models from different sources
  - Keep training IP out of the distributed model

- Pickle makes it hard to:
  - Distribute models
  - Archive models
  - Compose models from different sources
  - Keep training IP out of the distributed model
- Insufficient performance:
  - Slow and single-threaded

- Pickle makes it hard to:
  - Distribute models
  - Archive models
  - Compose models from different sources
  - Keep training IP out of the distributed model
- Insufficient performance:
  - Slow and single-threaded
- No Python on deployment platform:
  - Deploy on the edge (e.g. mobile)

- Pickle makes it hard to:
  - Distribute models
  - Archive models
  - Compose models from different sources
  - Keep training IP out of the distributed model
- Insufficient performance:
  - Slow and single-threaded
- No Python on deployment platform:
  - Deploy on the edge (e.g. mobile)

Why is this so hard?

### Non-ML software

Compilation environment



### Non-ML software

# **Compilation environment**



### What we have


### **Training environment**



### Non-ML software




### What we want





### Non-ML software





### What we want











## **Deployment with ONNX**

```
import numpy as np
import onnxruntime
# Load the model into the runtime
session = onnxruntime.InferenceSession("model.onnx")
# Execute the model
def predict(**inputs: nd.ndarray) -> list[nd.ndarray]:
    return session.run(None, inputs)
```

# About that magical step...




Serialise inference logic and weights

**ONNX** is a standard


### **ONNX** is a standard

- Strongly typed computational DAG
  - Edges are Tensors
  - Nodes are operators
  - Nodes store state as attributes



### ONNX is a standard

- Strongly typed computational DAG
  - Edges are Tensors
  - Nodes are operators
  - Nodes store state as attributes
- Set of standardized operators ( $\sim$ 180)



# Creating ONNX graphs – with a beautiful abstraction

- ONNX is a tensor library API
- Spox<sup>1</sup>exposes that API as Python library

<sup>&</sup>lt;sup>1</sup>github.com/Quantco/spox

# Expressing models in Spox

# Linear regression in NumPy

```
from numpy import ndarray
import numpy as np

def lin_reg(X: ndarray, coef, intercept) -> np.ndarray:
    return coef @ X + intercept
```

# Linear regression in NumPy

```
from numpy import ndarray
import numpy as np
def lin_reg(X: ndarray, coef, intercept) -> np.ndarray:
    return coef @ X + intercept
def lin reg verbose(X: ndarray, coef, intercept) -> np.ndarray:
    return np.add(np.matmul(coef, X), intercept)
```

# Linear regression in Spox/ONNX

```
from spox import Var
import spox.opset.ai.onnx.v18 as op
```

# Linear regression in Spox/ONNX

```
from spox import Var
import spox.opset.ai.onnx.v18 as op
def lin_reg(X: Var, coef, intercept) -> Var:
    # Move state into constants
    coef = op.const(coef)
    intercept = op.const(intercept)
    return op.add(op.matmul(coef, X), intercept)
```



# **Expressing sklearn-like pipelines in Spox**

```
class SpoxLinearRegression:
    def __init__(self, state: LinearRegression):
        self.state = state

    def predict(self, X: Var) -> Var:
        return ...
```

# **Expressing sklearn-like pipelines in Spox**

```
class SpoxLinearRegression:
    def __init__(self, state: LinearRegression):
        self.state = state

def predict(self, X: Var) -> Var:
        coef = op.const(self.state.coef)
        intercept = op.const(self.state.intercept)
        return op.add(op.matmul(coef, X), intercept)
```

# Composing converters in a Pipeline

```
def converter(model):
    if isinstance(model, LinearRegression):
        return SpoxLinearRegression(model)
    ...
```

# Composing converters in a Pipeline

```
def converter(model):
    if isinstance(model, LinearRegression):
        return SpoxLinearRegression(model)
    . . .
class SpoxPipeline:
    . . .
    def predict(self, X: Var) -> Var:
        for step in self.model.steps[:-1]:
            X = converter(step).transform(X)
        last = self.model.steps[-1]
        return converter(last).predict(X)
```

# **Building the model**

# **Building the model**

```
pipe = Pipeline([("scaler", MinMaxScaler()),
                 ("linear", LinearRegression(...))])
pipe.fit(X train, v train)
. . .
import numpy as np
from spox import argument, build, Tensor
from your_converter_library import converter
X = argument(Tensor(np.float64, ("N",)))
y = converter(pipe).predict(X)
model = build({"X": X}, {"y": y})
onnx.save(model, "model.onnx")
```

Spox/ONNX is just another tensor library

Spox

<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy

<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy
- jax.numpy

<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy
- jax.numpy
- tf.experimental.numpy

<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy
- jax.numpy
- tf.experimental.numpy
- Dask

<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy
- jax.numpy
- tf.experimental.numpy
- Dask
- PyTorch

<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy
- jax.numpy
- tf.experimental.numpy
- Dask
- PyTorch
- CuPy

<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy
- jax.numpy
- tf.experimental.numpy
- Dask
- PyTorch
- CuPy
- · ...

<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy
- jax.numpy
- tf.experimental.numpy
- Dask
- PyTorch
- CuPy
- **-** ...



<sup>&</sup>lt;sup>1</sup>data-apis.org/

- Spox
- NumPy
- jax.numpy
- tf.experimental.numpy
- Dask
- PyTorch
- CuPy





<sup>&</sup>lt;sup>1</sup>data-apis.org/

# Spox ♥ ONNX:

Compile your trained model to a self-contained artefact

- Compile your trained model to a self-contained artefact
- Stable, very fast, and maintainable deployment

- Compile your trained model to a self-contained artefact
- Stable, very fast, and maintainable deployment
- Ready for production use!

- Compile your trained model to a self-contained artefact
- Stable, very fast, and maintainable deployment
- Ready for production use!
- ONNX has corporate backing by Microsoft and others

- Compile your trained model to a self-contained artefact
- Stable, very fast, and maintainable deployment
- Ready for production use!
- ONNX has corporate backing by Microsoft and others
- It is a key technology at QuantCo

# Spox ♥ ONNX:

- Compile your trained model to a self-contained artefact
- Stable, very fast, and maintainable deployment
- Ready for production use!
- ONNX has corporate backing by Microsoft and others
- It is a key technology at QuantCo

Tutorials and Docs: github.com/Quantco/spox

# **Appendix**

# Integrating existing converters

Spox also allows integration with existing converter libraries by way of inline.

```
class SpoxComplicatedRegressor:
    ...

def predict(X):
    onnx_model = skl2onnx.to_onnx(self.model, ...)
    (y,) = inline(onnx_model)(X)
    return y
```