

# PKT-300

## UHF FM TRANSCEIVER

### Enhanced Features in a Compact Radio

Introducing the PKT-300 portable radio, which comes with enhanced features that are perfect for those who need a lightweight, small, and powerful device. This radio is designed to be easy to use and can enhance work quality, efficiency, and worker well-being. It has a rugged, compact design, making it an ideal choice for fast-paced, customer service-focused retail, hospitality, warehousing, and entertainment venues. The integrated swivel belt clip makes it easy for employees to wear the radio and take advantage of one-touch, instant-on communications. With a robust 2 watts of transmit power, the PKT-300 provides loud and clear KENWOOD quality audio, even in high noise environments. The bright LCD display is easy to read in low light situations. The option to change frequencies or upgrade to 16 channels further extends the versatility of the PKT-300.

### General Features

#### COMPACT, LIGHTWEIGHT DESIGN & OPERATING EASE

Compact enough to carry anywhere with ease, the PKT-300 has a distinctively ergonomic form that's easy to hold and operate. It weighs 4.87oz (138 g) with the rechargeable Li-ion battery and control buttons, which are simple to use with PTT, MON, MENU, CALL, UP and DOWN operations.

#### 2 WATTS OF TRANSMIT POWER

Designed to be easy-to-use, the portable has a full 2 Watts of power for clear voice quality in noisy environments, yet it's extremely lightweight (4.87 oz).

#### PROGRAMMABLE CHANNELS

Users can modify each of the 6 or 16 preset channels to any of the 99 pre-stored frequencies.

#### 4-DIGIT 7-SEGMENT LCD WITH BACKLIGHTING

The large 4-digit 7-segment display makes it easy to check on both channel and signaling information. There is also a 3-level icon in the LCD to indicate how much battery power is left.

#### POWERFUL BATTERY

The 2200 mAh lithium-ion battery lasts through multiple shifts without recharging. Ready to use, right out of the box.

#### VERSATILITY

Customize your radio beyond the basic menu with programming software that allows full configuration of buttons and options. This enhances usability, compatibility, and reduces operator errors by restricting access.



Actual Size

### Other Features

- MIL-STD 810 C, D, E, F, G and H (refer to the chart on back page)
- Built-in VOX
- Key Lock/Super Lock
- Battery Saver
- Busy Channel Lockout
- Built-in Privacy Talk
- Compander
- 10-Call Alert Tone
- Wireless cloning and easy modifications

### Included Accessories

The PKT-300 comes with a battery, charger, AC adapter and swiveling belt clip holster. The two-pin connector works with popular accessories for additional versatility.

The PKT-300 Portable Radio comes with a standard 2-year warranty. All accessories and options carry a 1-year warranty.

## Accessories

All accessories may not be available in all markets.  
Contact an authorized KENWOOD dealer for details and complete list of all accessories.

### KNB-81L

Li-ion Battery Pack  
(3.6V/2,200mAh)  
(Same as supplied)



### KMC-21A

Lightweight Compact  
Speaker Microphone



### KHS-22A

Behind-the-Head  
Headset with Flexible  
Boom Mic and In-line  
PTT Single Ear Receiver



### KEP-2

2.5mm earphone kit  
for KMC-45 Speaker Mic



### KSC-50K

Single Unit Charger  
(Same as supplied)



### KMC-45D

MIL-SPEC, IP54/55  
Speaker Microphone



### KHS-26

Clip Mic w/ Earphone



### KBH-21

Belt Clip  
(Long 1.91 in / 50mm)



### KSC-44MLKS

AC Adapter  
(For KSC-50CR  
multi-unit use, up to 6 units)



### KHS-8BL

2-wire Palm  
Microphone w/ Earphone



### KHS-27A

D-Ring Ear Hanger  
w/PTT & Mic



### KBH-23K

Swivel Belt Clip Holster



KPG-208DK  
Programming Software

### KSC-506K

One Piece 6-Unit Charger



### KHS-9BL

3-wire Palm  
Microphone w/ Earphone



### KHS-31C

C-Ring Ear Hanger  
w/PTT & Mic



### KPG-22U

USB to 2-pin  
Programming Cable



## Specifications

| General                                                         | PKT-300                                                                         |
|-----------------------------------------------------------------|---------------------------------------------------------------------------------|
| Frequency Range                                                 | 450-470 MHz<br>Preset 99 Frequencies                                            |
| Number of Channels                                              | 6                                                                               |
| Channel Spacing                                                 | 25 / 12.5 kHz                                                                   |
| Antenna Impedance                                               | 50 Ω                                                                            |
| Battery Life (5-5-90 duty cycle)<br>with KNB-81L (3.6V/2200mAh) | Approx. 14 hours (Battery saver off)<br>Approx. 18 hours (Battery saver on)     |
| Operating Temperature Range*                                    | -22°F ~ +140°F (-30°C ~ +60°C)                                                  |
| Frequency Stability                                             | ±2.5ppm                                                                         |
| CH Frequency Spread                                             | 20 MHz                                                                          |
| Dimensions<br>Radio with KNB-81L                                | (W x H x D) Projections Not Included<br>1.97 x 3.86 x 1.06 in (50 x 98 x 27 mm) |
| Weight<br>Radio with KNB-81L                                    | 4.87 oz (138 g)                                                                 |
| FCC ID                                                          | K44523500                                                                       |

\*Operating temperature specification for a Li-ion battery is 14°F to +140°F (-10°C to +60°C)

Specifications shown are typical and subject to change without notice, due to advancements in technology.  
Details and timing of firmware and software updates are subject to change without notice.  
Analog measurements made per TIA603. Specifications are measured according to applicable standards.

| Receiver                                    | PKT-300                         |
|---------------------------------------------|---------------------------------|
| Sensitivity (12 dB SINAD)<br>Wide / Narrow  | 0.25 / 0.28 μV                  |
| Selectivity<br>Wide / Narrow                | 60 / 50 dB                      |
| Intermodulation Distortion<br>Wide / Narrow | 55 / 50 dB                      |
| Spurious Response                           | 55 dB                           |
| Audio Output Power                          | 100 mW / 8 Ω (External Speaker) |
| Transmitter                                 | PKT-300                         |
| RF Power Output<br>High / Low               | 2.0 / 0.5 W (ERP)               |
| Spurious Response                           | 55 dB                           |
| FM Hum & Noise<br>Wide / Narrow             | 40 / 34 dB                      |
| Audio Distortion                            | Less than 5%                    |
| Modulation<br>Wide / Narrow                 | 16K0F3E / 11K0F3E               |

ProTalk® is a registered trademark of JVC KENWOOD Corporation.  
All other trademarks are the property of their respective holders.

## MIL-STD & IP

| MIL Standard                      | MIL 810C<br>Methods/Procedures | MIL 810D<br>Methods/Procedures | MIL 810E<br>Methods/Procedures | MIL 810F<br>Methods/Procedures | MIL 810G<br>Methods/Procedures | MIL 810H<br>Methods/Procedures |
|-----------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Low Pressure                      | 500.1/Procedure I              | 500.2/Procedure I, II          | 500.3/Procedure I, II          | 500.4/Procedure I, II          | 500.5/Procedure I, II          | 500.6/Procedure I, II          |
| High Temperature                  | 501.1/Procedure I, II          | 501.2/Procedure I, II          | 501.3/Procedure I, II          | 501.4/Procedure I, II          | 501.5/Procedure I, II          | 501.7/Procedure I, II          |
| Low Temperature                   | 502.1/Procedure I              | 502.2/Procedure I, II          | 502.3/Procedure I, II          | 502.4/Procedure I, II          | 502.5/Procedure I, II          | 502.7/Procedure I, II          |
| Temperature Shock                 | 503.1/Procedure I              | 503.2/Procedure I              | 503.3/Procedure I              | 503.4/Procedure I, II          | 503.5/Procedure I              | 503.7/Procedure I              |
| Solar Radiation                   | 505.1/Procedure I              | 505.2/Procedure I              | 505.3/Procedure I              | 505.4/Procedure I              | 505.5/Procedure I              | 505.7/Procedure I              |
| Humidity                          | 507.1/Procedure I, II          | 507.2/Procedure II, III        | 507.3/Procedure II, III        | 507.4                          | 507.5/Procedure II             | 507.6/Procedure II             |
| Vibration                         | 514.2/Procedure VIII, X        | 514.3/Procedure I              | 514.4/Procedure I              | 514.5/Procedure I              | 514.6/Procedure I              | 514.8/Procedure I              |
| Shock                             | 516.2/Procedure I, II, V       | 516.3/Procedure I, IV          | 516.4/Procedure I, IV          | 516.5/Procedure I, IV          | 516.6/Procedure I, IV          | 516.8/Procedure I, IV          |
| International Protection Standard |                                |                                |                                |                                |                                |                                |
| Dust & Water Protection           | IP52                           |                                |                                |                                |                                |                                |

### JVC KENWOOD USA Corporation

Safety & Security Sector Headquarters  
1440 Corporate Drive | Irving, TX 75038

Order Administration/Distribution  
4001 Worsham Ave. | Long Beach, CA 90808

[www.kenwood.com/usa](http://www.kenwood.com/usa)

### JVC KENWOOD Canada Inc.

Canadian Headquarters and Distribution  
6685 Millcreek Drive, Unit 8, Mississauga, ON L5N 5M5

[www.kenwood.com/ca](http://www.kenwood.com/ca)



ISO9001 Registered  
Communications Systems Division  
JVC KENWOOD Corporation