

# State

# State

- behavioral design pattern that lets an object alter its behavior when its internal state changes
- a lot of applications have object that realizes some "logic states" (aka Finite State Machine)
- "orders", "machines", "buttons", car (engine), invoice, employee - we are living in a stateful world

```

public void InsertCard()
{
    switch (_currentState)
    {
        case MACHINE_STATE.INITIAL:
            _currentState = MACHINE_STATE.CARD_INSERTED;
            break;
        case MACHINE_STATE.CARD_INSERTED:
        case MACHINE_STATE.PIN_ENTERED:
        case MACHINE_STATE.CASH_WITHDRAWN:
            throw new InvalidOperationException("Card already inserted");
        default:
            throw new ArgumentOutOfRangeException();
    }
}

public void EnterPin(Pin pin)
{
    switch (_currentState)
    {
        case MACHINE_STATE.INITIAL:
            throw new InvalidOperationException("No card inserted");
        case MACHINE_STATE.CARD_INSERTED:
            if (pin != 1234) throw new InvalidOperationException("incorrect pin");
            _currentState = MACHINE_STATE.PIN_ENTERED;
            break;
        case MACHINE_STATE.PIN_ENTERED:
        case MACHINE_STATE.CASH_WITHDRAWN:
            throw new InvalidOperationException("Pin already entered");
        default:
            throw new ArgumentOutOfRangeException();
    }
}


```

# State

- this pattern **delegates** state handling to specific *State* types
- kind of "Strategy pattern" where "strategies" (states) know about each other and create transitions between them


# State

- this pattern **delegates** state handling to specific *State* types
- kind of "Strategy pattern" where "strategies" (states) know about each other and create transitions between them



# State


- this pattern **delegates** state handling to specific *State* types
- kind of "Strategy pattern" where "strategies" (states) know about each other and create transitions between them



- context - interface for clients, facade for operations, holds state
- who changes "state" - context or specific state?
- states created *ad-hoc* or at once (or maybe from a pool?).


# State

- this pattern **delegates** state handling to specific *State* types
- kind of "Strategy pattern" where "strategies" (states) know about each other and create transitions between them



# State

- this pattern **delegates** state handling to specific *State* types
- kind of "Strategy pattern" where "strategies" (states) know about each other and create transitions between them



- context (**Invoice**) - interface for client (**InvoiceProcessingService**), facade for operations, holds state
- who changes "state" - probably **InvoiceProcessingService**



# State - who changes "state"

- transitions rather fixed and unchanging - in context.
- transitions rather flexible - in specific states

# State

- use when:
  - you have an object that behaves differently depending on its current state
  - the number of states is **big**
  - and/or the state-specific code **changes** frequently

# **State - implementation details**

# State - implementation details

- what is *Context* in your code? That may be the easiest part.

# State - implementation details

- what is *Context* in your code? That may be the easiest part.
- what's *State interface*? Like in *Strategy*, it may be not trivial
  - what operations are "state-specific"?
  - how much we will violate "L"? ☹☹

# State - implementation details

- what is *Context* in your code? That may be the easiest part.
- what's *State interface*? Like in *Strategy*, it may be not trivial
  - what operations are "state-specific"?
  - how much we will violate "L"? 🙄
- how *States* access *Context* data? Again, similar to *Strategy pattern*, we can:
  - make such data/method public 😬
  - nest the state classes in the context class (or at least its base class) 🙄

# State - implementation details

- what is *Context* in your code? That may be the easiest part.
- what's *State interface*? Like in *Strategy*, it may be not trivial
  - what operations are "state-specific"?
  - how much we will violate "L"? 🙄
- how *States* access *Context* data? Again, similar to *Strategy pattern*, we can:
  - make such data/method public 😬
  - nest the state classes in the context class (or at least its base class) 🙄
- who implements **changeState** logic/validation?
  - "centralized" version - our big switch
  - "decentralized" version - *concrete state* objects:

# Przykłady:

- \_Intro - smutny switch



# Przykłady:

- \_Intro - smutny switch
- PreMain - wydzielony stan

# Przykłady:

- \_Intro - smutny switch
- PreMain - wydzielony stan
- Main - lepsza enkapsulacja (nested base state)

# Przykłady:

- \_Intro - smutny switch
- PreMain - wydzielony stan
- Main - lepsza enkapsulacja (nested base state)
- Decentralized - stany samodzielnie określają przejścia (dodana odpowiednia operacja w kontekście - **bookState** property)

# Przykłady:

- \_Intro - smutny switch
- PreMain - wydzielony stan
- Main - lepsza enkapsulacja (nested base state)
- Decentralized - stany samodzielnie określają przejścia (dodana odpowiednia operacja w kontekście - **bookState** property)

Ogólnie: stany mogą być statyczne/singletony (jeśli nie mają danych) i tylko operować na kontekście jako argumente