

SHANSEP TXT_S_POP analyse met 15% rek op TXT_SAFE_klei_licht_16_175

SHANSEP Parameters

Parameter	Waarde
Snijpunt y-as gemiddeld [kPa]	9.749
S gemiddeld [-]	0.324
m gemiddeld [-]	0.961
POP gemiddeld [kPa]	43.144
Snijpunt y-as karakteristiek [kPa]	5.907
S karakteristiek [-]	0.323
m karakteristiek [-]	0.931
POP karakteristiek [kPa]	62.727
Type verzameling: lokaal = 1.0; regionaal = 0.75	0.75
VGW nat gemiddeld [kN/m3]	16.724
Watergehalte gemiddeld	53.432

SHANSEP Resultaten

Resultaat type	Analyse methode	Snijpunt y-as gem [kPa]	S gemiddeld [-]	m gemiddeld [-]	POP gemiddeld [kPa]	Snijpunt y-as kar [kPa]	S
0	bepaling S en POP uit triaxiaal- of DSS proeven	9.749	0.324	nan	31.293	5.907	0.3
1	bepaling S en m uit triaxiaal- of DSS proeven	nan	0.306	0.961	31.293	nan	0.2
2	o.b.v. opgegeven POP bij triaxiaal- of DSS proeven	nan	nan	nan	43.144	nan	na
3	bepaling S uit triaxiaal- of DSS proeven OCR=1	nan	0.306	nan	nan	nan	0.2

Resultaat type	Analyse methode	Snijpunt y-as gem [kPa]	S gemiddeld [-]	m gemiddeld [-]	POP gemiddeld [kPa]	Snijpunt y-as kar [kPa]	S
4	gemiddelde handmatige keuze snijput, S en m	nan	nan	nan	nan	nan	na

Invoerselectie Informatie

ALG__BORING_MONSTERNR_ID	Groep	Positie	NAP Vanaf [m]	NAP Tot [m]	VGW nat	VGW droog	Watergehalte voor
1201.0_AW208.+124_B_BIK_M017-a	TXT_SAFE_klei_licht_16_175	KR	-3.82	-4.14	17.30	12.14	42.51
1224.0_AW215.+116_B_BIK_M011-a	TXT_SAFE_klei_licht_16_175	KR	-2.10	-2.40	16.53	11.05	49.57
1277.0_AW216.+198_B_BIK_M027-b	TXT_SAFE_klei_licht_16_175	KR	-10.03	-10.21	17.00	11.67	45.57
1400.0_AW299.+003_B_BIT_M012-a	TXT_SAFE_klei_licht_16_175	BIT	-5.17	-5.36	16.16	10.15	59.23
1502.0_VY021.+018_B_BUK_M018-a	TXT_SAFE_klei_licht_16_175	KR	-2.55	-2.80	17.41	12.21	42.57
1511.0_VY021.+018_B_BUK_M024-a	TXT_SAFE_klei_licht_16_175	KR	-5.55	-5.90	16.98	11.57	46.72
1574.0_AW298.+178_B_BIK_14-b	TXT_SAFE_klei_licht_16_175	KR	-1.02	-1.32	16.62	10.84	53.24
1623.0_VY010.+135_B_BIK_26	TXT_SAFE_klei_licht_16_175	KR	-6.51	-6.91	17.41	12.27	41.83
1624.0_VY010.+135_B_BIK_27	TXT_SAFE_klei_licht_16_175	KR	-7.01	-7.41	16.56	10.79	53.40
1688.0_VY021.+019_B_BIT_19	TXT_SAFE_klei_licht_16_175	BIT	-5.52	-5.80	16.54	10.79	53.32
1743.0_VY053.+108_B_BUK_21	TXT_SAFE_klei_licht_16_175	KR	-2.83	-3.23	16.72	11.51	45.30
1744.0_VY053.+108_B_BUK_22	TXT_SAFE_klei_licht_16_175	KR	-3.33	-3.68	17.50	12.12	44.37
1767.0_VY093.+135_B_BUK_17	TXT_SAFE_klei_licht_16_175	KR	-1.34	-1.74	17.82	12.70	40.32
1784.0_VY093.+142_B_AL_7	TXT_SAFE_klei_licht_16_175	AL	-1.83	-2.20	16.58	10.87	52.49
1787.0_VY093.+142_B_AL_9-b	TXT_SAFE_klei_licht_16_175	AL	-2.93	-3.23	16.67	10.37	60.77
2238.0_VY004.+186_B_MBIB_mo-14a	TXT_SAFE_klei_licht_16_175	BIT	-2.75	-3.10	16.69	10.90	[-]
2450.0_VY050.+179_B_BIK_mo-23a	TXT_SAFE_klei_licht_16_175	KR	-4.37	-4.73	16.64	10.68	[-]
2472.0_VY050.+179_B_BIT_mo-15a	TXT_SAFE_klei_licht_16_175	BIT	-4.21	-4.54	16.27	10.19	[-]

ALG__BORING_MONSTERNR_ID	Groep	Positie	NAP Vanaf [m]	NAP Tot [m]	VGW nat	VGW droog	Watergehalte voor
2529.0_VY050.+179_B_MBIB_mo-22a	TXT_SAFE_klei_licht_16_175	BIT	-6.78	-7.06	17.22	11.89	[-]
2537.0_VY059.+001_B_BIT_mo-07a	TXT_SAFE_klei_licht_16_175	BIT	0.03	-0.35	16.42	10.72	[-]
2555.0_VY059.+002_B_BIK_mo-18a	TXT_SAFE_klei_licht_16_175	KR	-0.75	-1.15	17.39	12.27	[-]
2690.0_VY079.+066_B_AL_mo-05a	TXT_SAFE_klei_licht_16_175	AL	-0.83	-1.20	16.21	10.33	[-]
2691.0_VY079.+066_B_AL_mo-06a	TXT_SAFE_klei_licht_16_175	AL	-1.33	-1.67	16.00	9.68	[-]
2746.0_VY079.+091_B_BIK_mo-18a	TXT_SAFE_klei_licht_16_175	KR	-1.94	-2.31	16.51	11.07	[-]
2756.0_VY079.+091_B_BIT_mo-03a	TXT_SAFE_klei_licht_16_175	BIT	-0.98	-1.32	16.03	9.88	[-]
2976.0_VY022.+188_B_BIT_M014-b	TXT_SAFE_klei_licht_16_175	BIT	-5.93	-6.19	16.16	9.73	66.04
2982.0_VY022.+188_B_BIT_M018-a	TXT_SAFE_klei_licht_16_175	BIT	-7.88	-8.19	17.35	11.57	49.95
3152.0_VY032.+004_B_BIT_M008-a	TXT_SAFE_klei_licht_16_175	BIT	-1.52	-1.86	16.46	11.40	44.43
3176.0_VY032.+003_B_AL_M007-a	TXT_SAFE_klei_licht_16_175	AL	-1.75	-2.04	16.29	10.34	57.61
3182.0_VY032.+003_B_AL_M012-a	TXT_SAFE_klei_licht_16_175	AL	-4.25	-4.65	16.44	10.52	56.43
3743.0_AW207.+162_B_BIK_mo-22	TXT_SAFE_klei_licht_16_175	KR	-4.50	-4.87	17.50	12.90	[-]
3824.0_AW213.+167_B_BIK_mo-32	TXT_SAFE_klei_licht_16_175	KR	-10.84	-11.23	16.60	11.40	[-]
3859.0_AW213.+167_B_BIT_mo-31	TXT_SAFE_klei_licht_16_175	BIT	-10.55	-10.95	17.30	11.70	[-]
3911.0_AW217.+083_B_AL_mo-22	TXT_SAFE_klei_licht_16_175	AL	-11.01	-11.40	17.00	11.60	[-]
3952.0_AW217.+084_B_BIK_mo-34	TXT_SAFE_klei_licht_16_175	KR	-11.05	-11.45	17.10	11.80	[-]
3978.0_AW217.+084_B_BIT_mo-21	TXT_SAFE_klei_licht_16_175	BIT	-4.69	-5.07	16.90	11.70	[-]
3991.0_AW217.+084_B_BIT_mo-34	TXT_SAFE_klei_licht_16_175	BIT	-11.19	-11.58	17.50	12.60	[-]
4004.0_AW230.+080_B_AL_mo-06	TXT_SAFE_klei_licht_16_175	AL	-1.80	-2.17	16.70	11.90	[-]
4072.0_AW230.+082_B_BIT_mo-13	TXT_SAFE_klei_licht_16_175	BIT	-2.81	-3.19	17.60	12.60	[-]
4199.0_AW240.+027_B_BIK_mo-15	TXT_SAFE_klei_licht_16_175	KR	-0.23	-0.60	17.30	12.80	[-]