

Chapter 4

Multi-scale modelling of dry granular flows

4.1 Introduction

In nature, instabilities of slopes or cliffs are dramatic events involving sudden release of a large mass of soil. However, the prediction of catastrophic events still represents challenge, one difficulty being our incomplete understanding of the dynamics of granular flows (Rondon et al., 2011). Understanding the mechanics is of particular importance for risks assessment. Small scale laboratory experiments are usually unable to properly capture the dynamics of geophysical events. However, they can be useful to precisely study physical mechanisms, which may play a role in real flows (Iverson, 1997).

Conventionally, granular materials such as soils are modelled as a continuum. On a macroscopic scale, granular materials exhibit many collective phenomena and the use of continuum mechanics to describe the macroscopic behaviour can be justified. However, on a grain scale, the granular materials exhibit complex solid-like and/or fluid-like behaviour depending on how the grains interact with each other. Numerical studies at grain scale allows a precise understanding of the internal flow structure. Recent works on granular materials suggest that a continuum law may be incapable of revealing in-homogeneities at the grain-scale level, such as orientation of force chains, which are purely due to micro-structural effects Rycroft et al. (2009). Discrete Element approaches are capable of simulating the granular material as a discontinuous system allowing one to probe into local variables such as position, velocities, contact forces, etc. The fundamental question is how to model granular materials which exhibit complex phenomenon. It is important to understand the mechanics of granular flows and the ability and limitations of continuum methods in capturing the flow dynamics.

¹ 4.2 Granular column collapse

² The collapse of a granular column, which mimics the collapse of a cliff, has been extensively
³ studied in the case of dry granular material (Hogg, 2007; Kerswell, 2005; Lajeunesse et al.,
⁴ 2004; Lo et al., 2009; Lube et al., 2005; Staron and Hinch, 2007; Zenit, 2005). The granular
⁵ column collapse experiment involves filling a rectangular channel of height H_0 and width L_0
⁶ with a granular material of mass ‘m’ (see figure 4.1). The granular column is then released
⁷ *en masse* by quickly removing the gate, thus allowing the granular material to collapse onto
⁸ the horizontal surface, forming a deposit having a final height H_f and length L_f . Despite the
⁹ complexity of the intermediate flow dynamics, experimental investigations have shown that the
¹⁰ flow evolution, the spreading velocity, the final extent of the deposit, and the energy dissipation
¹¹ can be scaled in a quantitative way independent of the substrate properties, grain size, density,
¹² and shape of the granular material and released mass (Lajeunesse et al., 2005; Lube et al., 2005;
¹³ Staron and Hinch, 2007). The granular collapse has also been studied using discrete element
¹⁴ method, which allows precise measurement of the internal flow structure (Lo et al., 2009;
¹⁵ Staron and Hinch, 2006, 2007; Utili et al., 2014). Power laws relating the final run-out and
¹⁶ height to the initial aspect ratio of the column were observed. These findings immediately pose
¹⁷ the question: are these simple scaling fortuitous, an oversimplification, or in fact indicative of a
¹⁸ simple dynamical balance?

¹⁹ Granular flows are conventionally modelled as a frictional dissipation process in continuum
²⁰ mechanics but the lack of influence of inter-particle friction on the energy dissipation and
²¹ spreading dynamics (Lube et al., 2005) is surprising. However, Kerswell (2005) showed the run-
²² out behaviour has a clear material dependence, which corroborates the conclusion of Lajeunesse
²³ et al. (2004) and softens that of Lube et al. (2005). The collapse of a granular column on a
²⁴ horizontal surface is a simple case of granular flow, however a proper model that describes
²⁵ the flow dynamics is still lacking. Simple mathematical models based on conservation of
²⁶ horizontal momentum capture the scaling laws of the final deposit, but fail to describe the initial
²⁷ transition regime. From a theoretical point of view, the spreading has been described using
²⁸ depth averaged equations (Kerswell, 2005; Larrieu et al., 2006). The depth-averaged and Saint-
²⁹ Venant equations struggle to recover the precise dynamic behaviour of the system (Warnett
³⁰ et al., 2013) and only succeeds in predicting the scaling observed for aspect ratio less than one.
³¹ However, describing larger aspect ratio and capturing the initial stage of the collapse, when
³² the grains experience a rapid change of direction from vertical to horizontal, remain an open
³³ challenge,

³⁴ In the present study, multi-scale numerical modelling, i.e. grain-scale modelling and
³⁵ continuum analyses, of the quasi-two dimensional collapse of granular columns are performed
³⁶ using Discrete Element (DEM) approach and Generalised Interpolation Material Point Method

4.2 Granular column collapse




Figure 4.1 Schematic of experimental configuration for 2-D collapse in a rectangular channel, ([Lajeunesse et al., 2004](#))

(GIMPM). GIMPM is a hybrid Eulerian – Lagrangian approach, is implemented with Mohr-Coulomb failure criterion to describe the continuum behaviour. While the micro-mechanics is captured using DEM simulations. Comparing grain scale behaviour with continuum simulations highlights the limitations of continuum approaches in modelling the dense granular flows and their ability (or lack thereof) in capturing the complex micro-scale rheology.

4.2.1 Numerical set-up

[Lajeunesse et al. \(2004\)](#) performed axis-symmetric and plane strain tests on granular column collapse. Granular materials when released suddenly on a horizontal surface exhibit transient flow. The mechanism of flow initiation, spreading dynamics and energy dissipation are studied. The experimental configuration used by [Lajeunesse et al. \(2004\)](#) is shown in figure 4.1. Granular material of mass ‘ M ’ was poured into a container to form a rectangular heap of length ‘ L_0 ’, height ‘ H_0 ’ and thickness ‘ W ’. The internal friction angle and the wall friction between the wall and the glass beads measured by [Lajeunesse et al. \(2004\)](#) are listed in Table 4.1. The gate was then quickly removed to release the granular mass that spreads in the horizontal channel until it comes to rest. The final run-out distance ‘ L_f ’ and the collapsed height ‘ H_f ’ were measured. The run-out distance and collapse height were found to exhibit power law relation with the initial aspect ratio ‘ a ’ ($= H_i/L_0$) of the column.

In this study, numerical simulations of the granular column collapse experiments are performed by varying the initial aspect ratio of the column. DEM simulations involve modelling the granular column as individual particles. The granular column is prepared by randomly

Table 4.1 Material properties of glass ballotini ([Lajeunesse et al., 2004](#))

Parameter	Value
Mean diameter	1.15 mm
Repose angle	$22 \pm 0.5^\circ$
Avalanche angle	$27.4 \pm 0.5^\circ$
Wall friction angle	$24.8 \pm 0.2^\circ$

¹ packing poly-disperse grains on a regular lattice and allowing them to undergo free fall due to
² gravity, forming a randomly packed granular column

³ The grains are allowed to reach a stable equilibrium after undergoing some elastic com-
⁴ pressions due to gravity. The overlaps between particles are determined by the stiffness k_n of
⁵ the spring in the normal direction. Typically, average overlaps in the range 0.1 to 1.0% are
⁶ desirable and the spring constant is chosen to produce particle overlaps in this range. The
⁷ stiffness is determined using the following equation:

$$k_n = \frac{2\pi G}{(1-\nu)[2\ln(\frac{2r}{A})-1]} \quad (4.1)$$

$$A = \left[\frac{2r(1-\nu)f_n}{\pi G} \right]^{\frac{1}{2}} \quad (4.2)$$

¹¹ where f_n is the normal contact force; G is the shear modulus; ν is the Poisson's ratio and r is
¹² the radius of the grain. A simpler form of stiffness for a spherical grain is defined as:

$$k_n = 4ER \quad (4.3)$$

¹⁵ where E is the Young's modulus of the material and R is the radius of the grain. The normal
¹⁶ damping coefficient C_n is chosen to give a required coefficient of restitution ϵ (defined as the
¹⁷ ratio of the post-collisional to pre-collisional normal component of the relative velocity) for the
¹⁸ materials involved:


$$C_n = 2\gamma\sqrt{m_{ij}k_n} \quad (4.4)$$

$$\text{where } \gamma = -\frac{\ln(\epsilon)}{\sqrt{\pi^2 + \ln^2(\epsilon)}}, \quad \text{and} \quad m_{ij} = \frac{m_i m_j}{m_i + m_j} \quad (4.5)$$

²² 10 DEM simulations were carried out with columns having different initial aspect ratio ' a ',
²³ varying from 0.2 to 10. In order to study the effect of crystallisation on the run-out distance,
²⁴ 10 more MD simulations were carried out on granular columns composed of grains arranged

4.2 Granular column collapse

5



(a) DEM sample prepared using ballistic deposition

(b) DEM grains generated using the cumulative β distribution

Figure 4.2 DEM sample characteristics

Table 4.2 Micromechanical parameters used in DEM simulations

Parameter	Value
Young's modulus of glass bead	$70 \times 10^9 \text{ N m}^{-2}$
Poisson's ratio	0.22 - 0.24
Diameter of glass beads	0.92 to 1.38 mm
Normal and shear stiffness of grains	$1.6 \times 10^8 \text{ N m}^{-1}$
Normal and shear stiffness of wall	$4 \times 10^8 \text{ N m}^{-1}$
Inter-particle friction coefficient, μ	0.53
Wall friction coefficient	0.466
Coefficient of restitution, Γ	0.6

on a hexagonal lattice. In order to maintain a threshold amount of grains, in all the cases the columns contain at least 1000 grains, which is the safe lower limit for DEM as suggested by Oda and Iwashita (1999). The micro-mechanical parameters used in this study are presented in Table 4.2. Due to the unsteady nature of the flow, the grains get dispersed on the horizontal plane as discrete bodies start to separate from the main mass, hence the run-out distance is calculated as the position of the farthest grain which has at least one contact with the main mass.

A plane strain collapse of granular column is simulated as a continuum using MPM. The effect of number of material points on the accuracy of the simulation was discussed in Chapter 4. Guilkey et al. (2003) suggests at least four particles per cell for problems involving large deformations. 10 MPM simulations of the granular column collapse were performed using Mohr-Coulomb constitutive law by varying the initial aspect ratio, to understand the difference between the particle and continuum scale description of granular flows. The parameters used for the continuum analyses are presented in Table 4.3. The Young's modulus of the granular assembly is determined by performing a uni-axial compression of the granular column in DEM.

4.2.2 Deposit morphology

The variation of the normalized final run-out distance, $\Delta L = (L_f - L_i)/L_i$, with the initial aspect ratio 'a' of the column is presented in figure 4.4. Similar to the experimental results, a power law relationship is observed between the normalized run-out distance and the initial aspect ratio of the column. However, the discrete element simulations with random packing of grains overestimate the run-out distance by a factor of 1.2. In the present study, the following scaling

4.2 Granular column collapse




Figure 4.3 Periodic shear test

Table 4.3 Parameters used in continuum simulations

Parameter	Value
Material point spacing	0.575 mm
Number of material points per cell	16
Young's Modulus, E	1.98×10^6 Pa
Poisson's ratio, ν	0.22 to 0.24
Friction angle, ϕ	$23.2 \pm 0.2^\circ$
Dilatancy angle, Φ	0°
Density, ρ	1800 kg m^{-3}
Wall friction	0.466
Time step increment	1.0×10^{-6} s

¹ law for the run-out is observed.

$$\frac{L_f - L_i}{L_i} \approx \begin{cases} 1.67a, & a \lesssim 2.3 \\ 2.5a^{2/3}, & a \gtrsim 2.3 \end{cases} \quad (4.6)$$

⁴ The run-out distance observed in the case of hexagonal packing of grains matches the experi-
⁵ mental run-out distance observed by [Lajeunesse et al. \(2004\)](#). However, the DEM simulations
⁶ performed with random packing predict longer run-out distances in comparison with the ex-
⁷ perimental data. The difference in the run-out distance can be attributed to the variation in
⁸ the packing of grains in the granular column. Although, experimental data corresponds to
⁹ granular column collapse in a rectangular channel, the collapse is not a pure two-dimensional
¹⁰ collapse as in the case of numerical simulations. This can cause some variation in the run-out
¹¹ distance. [Balmforth and Kerswell \(2005\)](#) observed that the material property affects the final
¹² run-out distance and included a pre-factor ‘ λ ’ in the scaling law, which is in contrast to the
¹³ observation made by [Lube et al. \(2005\)](#). The scaling law observed in the present study for the
¹⁴ random packing is identical to the scaling law observed by [Lajeunesse et al. \(2004\)](#), except for
¹⁵ the pre-factor in the scaling law, indicating a strong correlation between the run-out distance
¹⁶ and the material property. [Daerr and Douady \(1999\)](#) also observed the effect of initial packing
¹⁷ density and the internal structure on the behaviour of granular flows. The continuum description
¹⁸ of the granular column collapse using Material Point Method shows good agreement with the
¹⁹ experimental results for columns with lower aspect ratio (‘ a ’ $\lesssim 2.3$), however it exhibits a
²⁰ significant increase in the run-out distance beyond the aspect ratio of 2.3. [Bandara \(2013\)](#) also
²¹ observed a jump in the run-out distance at the initial aspect ratio of 2.

²² [Daerr and Douady \(1999\)](#) also proposed an interpretation in terms of active Coulomb
²³ yielding to account for their experimental observation of the transient granular surface flow
²⁴ occurring when a highly compacted cylindrical pile of granular media supported by a disc is
²⁵ suddenly released and crumbles to form a cone.

²⁶ [Staron and Hinch \(2006\)](#) observed influence of role of friction. We first observed that
²⁷ the coefficient of restitution e was dramatically changing the behaviour of the systems for
²⁸ $e \rightarrow 1$; in particular, this dramatic change is expected to become more important for increasing
²⁹ values of a . On the contrary, for $e \leq 0.8$, the influence of the coefficient of restitution becomes
³⁰ negligible.

³¹ For small aspect ratio, the spreading results from a Coulomb-like failure of the edges and
³² imply no free fall of the column. In this case, the effective friction properties of the flow can be
³³ simply predicted from the shape of the final deposit

³⁴ In order to understand the mechanism of the run-out in a granular column collapse, it
³⁵ is essential to study the relation between the final collapsed height of the granular column

and its initial aspect ratio. figure 4.5 shows the variation of the normalized final height with the initial aspect ratio of the column. The final height predicted by the DEM and the MPM simulations matches the experimental data for granular columns with aspect ratio below 0.7, which indicates that the initial density of the column has negligible effect on the final collapse height. The scaling of final height of the column with the initial aspect ratio of the column can be written as:

$$\frac{H_f}{L_i} \propto \begin{cases} a, & a \lesssim 0.7 \\ a^{2/3}, & a \gtrsim 0.7 \end{cases} \quad (4.7)$$

The Material Point Method predicts a higher final height of the column in comparison with the particular simulations that should result in shorter run-outs, however it is inconsistent with the observations. In case of granular columns with smaller aspect ratios, only a tiny portion of the total mass is mobilized and the rest remains static, thus predicting the final collapse height accurately. The final height of a column is controlled by the amount of static region in the granular column collapse, while the run-out distance is essentially a function of the flowing mass. Hence, it is essential to compare the evolution of flow and the internal flow structure in the Discrete Element Method and Material Point Method simulations to understand the limitations of both the continuum and discrete element approaches.

For large aspect ratios, in which we were mainly interested, the dissipation process is more complex due to the free-fall dynamics. Indeed the vertical acceleration of the grains induces a non-trivial mass distribution in the flow while propagating. This mass distribution plays a dominant role in the power-law scaling law obeyed by the run-out.

4.2.3 Flow evolution and internal flow structure

For a fixed granular material and substrate properties, the flow dynamics and the final deposit morphology do not depend on the volume of granular material released, but depend only on the aspect ratio ‘ a ’ of the column. A power law relationship is observed between the run-out distance and the initial aspect ratio of the column. A transition in the run-out behaviour at an aspect ratio of 2.3 indicates a change in the flow dynamics. For smaller aspect ratios, the granular mass fails through avalanching of flanks producing a truncated cone-like deposit ($‘a’ < 0.7$) or conical deposit ($‘a’ > 0.7$). At smaller values of aspect ratios, the flow is initiated by failure at the edge of the pile along a well-defined fracture surface. The grains located above the failure surface move “*en masse*” leaving a static region underneath the failure surface. After a transient time of order τ_c , defined as $\sqrt{H_i/g}$, the flow is fully developed. The velocity profile along the granular column at critical time τ_c is presented in figure 4.6. At critical time, the




Figure 4.4 Normalised final run-out distance for columns with different initial aspect ratio




Figure 4.5 Normalised final collapse height for columns with different initial aspect ratio

velocity field depends only on the position of the grain along the sliding mass. The maximum velocity is observed at the front of the flowing mass corresponding to that of a plug flow in horizontal direction. Particulate and continuum simulations yield similar run-out distance at critical time. Unlike particulate simulations, the Material point method predicts that the maximum horizontal velocity occurs at the top of the sliding mass. Behind the fast flowing front, the flow is localized in the mass above the failure surface and the velocity profiles are locally parallel to the failure plane. The flow is composed of upper linear part and a lower exponential tail in the static granular bed. The velocity profile is similar to steady granular surface flow as observed by Lajeunesse et al. (2004).

For columns with lower initial aspect ratios, the run-out distance is proportional to the mass flowing above the failure surface. To understand the amount of mass mobilized during a collapse, the angle of the failure surface has to be studied. figure 4.6 shows a distinct failure surface when the flow is fully developed at critical time τ_c . The angle of the failure surface is found to be about 55° . The failure surface begins from the toe of the column and protrudes inwards at an angle of 50 to 55° . For columns with lower aspect ratios, the formation of the “truncated conical deposit” or “conical deposit” depends only on the initial length of the column, as the angle of the failure surface is found to be independent of the aspect ratio. The failure angle is consistent with the interpretation in terms of *active Coulomb failure* (Lajeunesse

¹ et al., 2004), which leads to a predicted failure angle $\theta_y = 45^\circ + \delta/2$, where δ is the internal
² friction angle of the granular material. In the present study, the friction angle of the glass
³ beads is 22° , which leads to $\theta_y = 45^\circ + 22^\circ/2 = 56^\circ$, which is in good agreement with the
⁴ numerical simulations and experimental observations by Lajeunesse et al. (2004). Contrary to
⁵ the suggestion of Lajeunesse et al. (2004), the fracture angle is found to have no direct effect
⁶ on the transition between the truncated cone and the conical deposit occurring at an aspect ratio
⁷ of 0.7. Schaefer (1990) observed the onset of instabilities in a narrow wedges of 56 to 65° for
⁸ Cambridge type constitutive models that describes granular flows. This observation matches
⁹ well with the failure angle observed in the present study. The final profile of the collapsed
¹⁰ granular column with an initial aspect ratio of 0.4 is shown in figure 4.7. The failure surface is
¹¹ distinct and the hexagonal dense packing of grains has a steeper failure surface in comparison
¹² with the random packing. The variation observed in the angle of the failure surface causes a
¹³ difference in the amount of mobilized mass above the failure surface, and in turn in the run-out
¹⁴ distance. The lower value of run-out distance observed in the case of hexagonal packing of
¹⁵ grains can be attributed to the crystallisation effects. crystallisation is the formation of large-
¹⁶ scale lattice structures during the flow, resulting in non-generic flow patterns. crystallisation is
¹⁷ found to have a significant effect on the final state of the granular column. Lacaze and Kerswell
¹⁸ (2009) observed that poly-disperse grains have lesser tendency to crystallize especially in the
¹⁹ case of columns with larger aspect ratio.

²⁰ For larger aspect ratios, the flow is still initiated by a well defined failure surface as can be
²¹ seen in figure 4.8. However, in this case the initial granular column is much higher than the
²² top of the failure surface. Due to gravity most of the grains in the column fall in the vertical
²³ direction consuming the column along their way. When they reach the vicinity of the failure
²⁴ surface, the flow gets deviated along the horizontal direction releasing a huge amount of kinetic
²⁵ energy gained during the free fall. For larger aspect ratio ($a > 0.7$), the resulting static region is
²⁶ a cone, the final height of the cone, i.e, H_f lies above the summit of the failure surface. Hence,
²⁷ a different evolution is observed from that of the axis-symmetric geometry (Lube et al., 2005),
²⁸ where the final height coincides with the summit of the failure surface forming a truncated
²⁹ conical deposit. Lajeunesse et al. (2004) articulated the variation in the deposit morphology
³⁰ between the axis-symmetric case and the rectangular collapse to be a geometrical effect rather
³¹ than as an experimental artefact. The final profile of the collapsed granular column with an
³² initial aspect ratio of 6 is presented in Figure.4.9. An initial failure surface starting from the toe
³³ end of the column at an angle of about 55° can be observed at critical time τ_c . As the collapse of
³⁴ the granular collapse progresses, successive failure planes parallel to the initial failure surface
³⁵ are formed and shear failure occurs along these planes. The presence of several shear bands
³⁶ in the final profile of the collapsed granular column confirms the hypothesis. crystallisation




Figure 4.6 Velocity profile of a granular column collapse ($a' = 0.4$ & $t = \tau_c$)




Figure 4.7 Velocity profile of a granular column collapse ($a' = 0.4$ & $t = 3 \times \tau_c$)

in hexagonal packing causes a significant effect on the run-out distance by forming series of parallel shear bands. However, the Material Point Method fails to capture the formation of shear bands during the collapse. This observation throws light on the mechanics of propagation of shear bands in massive landslides such as the Storegga submarine landslide. The flow behaviour becomes similar to that of columns with lower aspect ratio as the flow starts descending along the failure plane. Regardless of the experimental configuration and the initial aspect ratio of the columns, the flow is initiated by a well-defined rupture surface, above which the material slides down leaving a static region underneath the failure plane. Depending on the aspect ratio of the column, two asymptotic behaviours are observed. For smaller aspect ratios, the flow is dominated by friction and by the pressure gradient for larger aspect ratio.

To study the flow dynamics of granular columns with different aspect ratios, the flow front $L(t)$ and the maximum height of column $H(t)$ are tracked. The evolution of scaled height (H_f/L_i) and the run-out distance $(L_f - L_i)/L_i$ with time for granular columns with an initial aspect ratio of 0.4 and 6 are presented in Figures. 4.10a and 4.10b. Time is scaled with respect to the critical time τ_c , defined as the time at which the flow is fully mobilized. Three distinct regions can be observed in the flow evolution of granular column collapse regardless of the initial aspect ratio of the column. An initial transient acceleration phase is observed for a time $0.8\tau_c$. This phase is followed by a heap movement of granular materials at the foot with a constant spreading velocity V for about $2\tau_c$. When time ' t ' > τ_c , the velocity varies linearly with depth in the flowing layer and decreases exponentially with depth near the static layer. This velocity profile is similar to those observed in steady granular surface flows (Lajeunesse et al., 2004). Most of the run-out happens during this phase. The final phase involves deceleration of the flow front and the flow comes to rest after $0.6\tau_c$. The spreading of the granular column ceases after a time in the order of $3\tau_c$ for all values of aspect ratios, however some motion still persists along the free surface behind the flow front for a much longer time due to internal rearrangement, the duration of which can last up to $t \approx 6\tau_c$. For smaller aspect ratios, the critical time is evaluated as the point of intersection of the scaled run-out and height. The critical time predicted for both hexagonal and random packing of grains matches the experimental observations. However, the Material Point Method overestimates the critical time by a factor of 1.25, which means that it takes longer for the flow to be fully mobilized. However, the actual run-out duration is short and the granular materials comes to rest abruptly at about $t = 3\tau_c$. For columns with larger aspect ratios, the continuum and particulate approaches simulate similar flow evolution behaviour for times up to $3\tau_c$, beyond which particulate simulations stabilise and come to rest, while the flow continues to evolve in MPM simulations resulting in larger run-outs than expected. The flow tends to come to rest at time $t = 6\tau_c$. The three phases in a granular flow can be distinctly observed in the flow evolution plot for a granular column with initial aspect ratio of 6 (see

Figure figure 4.10b). For larger aspect ratios, the flow evolution behaviour observed in the case of random packing matches the experimental observation by Lajeunesse et al. (2004). Hexagonal packing predicts longer time for the flow to evolve, which can be attributed to the increase in the internal resistance due to crystallisation of grains. MPM overestimates the critical time by 50%, however has the same value of run-out as the particulate simulations, at time $t = 3\tau_c$, beyond which the material continues to flow until it ceases at $6\tau_c$. In order to understand the flow dynamics in the case of Material Point Method it is important to study the effect of different parameters on the deposit morphology.




Figure 4.8 Velocity profile of a granular column collapse ($a' = 6$ & $t = \tau_c$)




Figure 4.9 Velocity profile of a granular column collapse ($a' = 6$ & $t = 3 \times \tau_c$)





Figure 4.10 Flow evolution of granular column collapse

4.2.4 Energy dissipation mechanism

The time evolution of the flow exhibited three distinct stages during the collapse of a granular column. Studying the energy dissipation mechanism provides useful insight into the flow dynamics. shows the time evolution of potential energy (E_p) and kinetic energy (E_k) normalized by the initial potential energy E_o .

$$E_p = \sum_{p=1}^{N_p} m_p g h_p \quad (4.8) \quad 6$$

$$E_{ki} = \frac{1}{2} \sum_{p=1}^{N_p} m_p v_p^2 \quad (4.9) \quad 7$$

where N_p is the total number of particles, m_p is the mass of a particle ‘ p ’, h_p is the height and v_p is the velocity of the particle ‘ p ’. It can be observed from the figure that the initial potential energy stored in the particle is converted to kinetic energy which is dissipated as the granular material flows down. Three successive stages can be identified in the granular column collapse. In the initial acceleration stage ($t < 0.8\tau_c$), the initial potential energy stored in the grains is converted into vertical motion. In the second stage, the grains undergo collisions with the bottom plane and/or with neighbouring grains, and the stored potential energy is converted into horizontal motion. In the third stage, the grains eventually leave the base area of the column and flow sideways. As the process involves collective dynamics of all the particles, it is difficult to predict the exact trajectory of a grain, however, the overall dynamics can be explained. To explain the dissipation of energy during the collapse, [Staron et al. \(2005\)](#) assumed that the total initial potential energy stored in the system is completely dissipated through friction over the entire run-out distance as:

$$\mu m_o g \times (L_f - L_i) = m_o g H_o \quad (4.10) \quad 22$$

where μ is the friction coefficient. The model predicts well the flow dynamics for columns with larger aspect ratios, as most of the initial potential energy is dissipated during the collapse involving the entire column. However, for columns with smaller aspect ratios, only a portion of the mass above the failure surface is involved in the flow. Hence, the energy dissipation should involve only the grains lying above the failure surface. A mathematical model, which considers the grains lying above the failure surface, will be derived to predict the flow dynamics of the granular column collapse for different aspect ratios.





(a) Energy evolution of a column with ' a' = 0.4(b) Energy evolution of a column with ' a' = 6

Figure 4.11 Energy evolution of granular column collapse

4.2 Granular column collapse

Figure 4.12 Flow evolution of granular column collapse using $\mu(I)$ rheology




Figure 4.13 Evolution of inertial number with time for columns with ' $a' = 0.4$ and ' $a' = 6$

4.2.5 Role of initial grain properties

It should be noted that the collapse experiment is highly transient and no clear stationary regime was observed. On the contrary, the acceleration and the deceleration phases cover nearly the whole duration of the spreading. This makes the analysis of the structure of the flow and its relation with other characteristic of the system uneasy. Considering this, we were able to show nevertheless how the initial condition was dominating the behaviour of the spreading through the mass distribution induced in the flow. This means that the knowledge of the final run-out is not a sufficient characterization of the deposit: one also needs to know how mass is distributed to understand the dynamics and the dissipation process. This is expected to be true in natural contexts as well as in experiments. While the inter-grain friction μ does not affect the early vertical dynamics, nor the power-law dependence, it controls the effective frictional properties of the flow, and its internal structure. It is interesting to note that the details of the structure of the flow do not influence the final run-out dependence, and thus seem to play a marginal role in the overall behaviour of the spreading. This could explain why simple shallow-water model with basic rheology but where the free-fall dynamics was accounted for could reproduce the run-out scalings.


At this stage, it appears that the collapse experiment for large aspect ratios mixes two very different dynamics: while the second stage consists of a “conventional” horizontal granular flows, the first stage implies a large vertical acceleration. It shows how the initial condition can influence the overall behaviour of a granular system, and suggests that triggering mechanisms play a crucial role in the case of natural flows. This stresses the necessity of accounting for vertical acceleration in continuum models in the perspective of producing realistic prediction of the behaviour of granular flows.


The numerical constants of proportionality, however, show clear material dependence. This corroborates the conclusion of [Balmforth and Kerswell \(2005\)](#); [Lajeunesse et al. \(2004\)](#) and softens that of [Lube et al. \(2005\)](#).


4.3 Slopes subjected to impact loading

Transient granular flows occur very often in nature. Well-known examples are rockfalls, debris flows, and aerial and submarine avalanches. They form a major element of landscape reshape and their high destructive potential is a substantial factor of risk. Natural granular flows may be triggered as a result of different processes such as gradual degradation, induced by weathering or chemical reactions, liquefaction and external forces such as earthquakes.

Granular flows have been studied in laboratory experiments in different geometries such as tilted piles leading to slope failure and surface avalanches ([Iverson, 1997](#); ?) or by considering

Figure 4.14 Effect of density on run-out evolution ‘ a' = 0.8

Figure 4.15 Effect of density on energy evolution $a = 0.8$

Figure 4.16 Evolution of local packing density ' a' = 0.8




Figure 4.17 Effect of density on run-out evolution ' a' = 0.8 (poly-dispersity ' r ' = 6)





Figure 4.18 Snapshots of granular column collapse $t = 6\tau_c$


1 vertical columns of grains collapsing and spreading under their own weight ([Lajeunesse et al., 2004, 2005](#)). The dynamics observed in the experiments is often nontrivial in the sense that
 2 the final configurations after the dissipation of the whole kinetic energy can not be readily
 3 predicted by means of simple laws based on the Mohr-Coulomb nature of the material. For
 4 example, in collapsing columns, the run-out distance is found to obey a power-law dependence
 5 upon the initial aspect ratio of the column.
 6

7 The observed nontrivial transient dynamics is often correctly reproduced by the DEM,
 8 which provides a powerful tool for the grain-scale analysis of the trigger and its subsequent
 9 dynamics ([Staron and Lajeunesse, 2009; Staron et al., 2005](#)). However, even in simplified
 10 geometries such as those investigated in the experiments, the DEM suffers from a serious
 11 short-coming in the number of particles that can be simulated in a reasonable time. This is a
 12 critical issue when more complex geometries or long-time granular processes are considered, or
 13 when particle size distributions are broad. For this reason, most numerical studies are performed
 14 in 2D or simple particles shapes and size distributions are considered.

15 It is also obvious that classical modelling strategies based on the finite element method
 16 (FEM) cannot be used for the simulation of very large deformations. In various application of
 17 FEM, this problem is treated by means of technical tools such as re-meshing. Such methods
 18 are, however, not robust and lead to round-off errors and mesh-sensitivity. In contrast, the
 19 so-called Material Point Method (MPM) is an alternative approach for continuum problems that




(a) Evolution of potential and kinetic energy




(b) Evolution of packing density

Figure 4.19 Effect of density on energy and packing fraction evolution ' a' = 0.8 (poly-dispersity ' r ' = 6)



(a) Effect of density on run-out evolution



(b) Effect of density on energy evolution

Figure 4.20 Effect of density on run-out behaviour and energy evolution ' a' = 0.6

allows for indefinitely large deformations without re-meshing ?. In this method, the material points carry the information on state variables and a background fixe grid is used to solve the governing equations. The information between the material points and the grid is exchanged via suitable shape functions. The MPM has been applied with success to a number of solid mechanics problems and its theoretical foundations have recently been investigated by several authors.

In this paper, we are concerned with the ability of the MPM, as a continuum approach, to reproduce the evolution of a granular pile under its own weight or when destabilized by energy input. In particular, a central issue is whether power-law dependence of the run-out distance and timew ith respect to the initial geometry or energy can be reproduced by a simple prescription of the Mohr-Coulomb plastic behaviour within a MPM code. We therefore perform extensive simulations by varying continuously different input parameters and compare the data with those obtained from DEM simulations of the same system. We compare in detail the evolution of the profile of the pile and its total kinetic energy between the two methods and for different initial states. As we shall see, the MPM can successfully simulate the transient evolution with a single input parameter, namely the internal angle of friction. This opens the way to the simulation of geological-scale flows on complex topographies.

4.3.1 Numerical procedures

The numerical samples are composed of ~ 13000 disks with a uniform distribution of diameters by volume fractions in the range $[d_{min}, d_{max}]$ with $d_{max} = 1.5d_{min}$. The mean particle diameter and mass are $d \simeq 0.0025$ m and $m \simeq 0.0123$ kg, respectively. The particles are first poured uniformly into a rectangular box of given width and then the right-hand side wall is shifted further to the right to allow the particles to spread. A half-pile is obtained when all particles come to rest; see Fig. ???. This procedure leads to a mean packing fraction $\simeq 0.83$.

Table 4.4 DEM simulation of simple shear test (?)


Parameter	Value
Mean grain diameter	≈ 2.455 mm
Grain diameter $[d_{min} : d_{max}]$	[2.0, 3.0] mm
Friction co-efficient	0.4
Grain density	2600kg m^{-3}
Restitution co-efficient	0
Number of grains	1174

1 The initial static pile is set into motion by applying a constant horizontal gradient $v_{0x}(y) =$
 2 $k(y_{max} - y)$ with $k > 0$. Such a configuration mimics the energy transfer mechanism of a
 3 horizontal quake along the bottom of the pile. We are interested in the evolution of the
 4 geometry of the pile and its total kinetic energy as a function of the initial input energy E_0 . The
 5 run-out distance R_f is the distance of the rightmost particles from the left wall when the pile
 6 comes to rest. It will be normalized by the initial extension R_0 of the pile, as in the experiments
 7 of collapsing columns. The total run-out duration t_f is the time that the pile takes to reach its
 8 final run-out distance R_f .

9 The initial static pile is set into motion by applying a horizontal velocity $v_{0x}(y)$ to all
 10 particles during a short interval of time. Different velocity fields were tested: 1) The same
 velocity $v_{0x}(y) = v_0$ applied to all particles, 2) The same velocity $v_{0x}(y) = v_0$ applied to a
 column of particles next to the left wall, 3) a constant velocity gradient $v_{0x}(y) = k(y_{max} - y)$
 with $k > 0$. The first two pushing modes mimic the case of a pile impacted from the left
 by a moving mass (tsunami, debris...) whereas the last mode represents energy transfer by
 horizontal quake of the bottom line. We will compare briefly below the effect of different
 pushing modes, but later we will mainly explore the third mode. We are interested in the
 evolution of the geometry of the pile and its total kinetic energy as a function of the initial
 energy input E_0 . The run-out distance R_f is the distance of the rightmost particles from the left
 wall when the pile comes to rest. It will be normalized by the initial extension R_0 of the pile, as
 in the experiments of collapsing columns. The total run-out duration t_f is the time that the pile
 takes to reach its final run-out distance R_f .

22 For grain scale simulations, classical DEM and Contact Dynamics approach is used. A
 23 detailed description of the Contact Dynamics method can be found in [Jean \(1999\)](#); [Radjai and Dubois \(2011\)](#); [Radjai and Richéfeu \(2009\)](#); ?. This method is based on implicit time
 24 integration of the equations of motion and a nonsmooth formulation of mutual exclusion and
 25 dry friction between particles. The CD method requires no elastic repulsive potential and no
 26 smoothing of the Coulomb friction law for the determination of forces. For this reason, the
 27 simulations can be performed with large time steps compared to discrete element simulations.
 28 The unknown variables are particle velocities and contact forces, which are calculated at each
 29 time step by taking into account the conservation of momenta and the constraints due to mutual
 30 exclusion between particles and the Coulomb friction. We use an iterative research algorithm
 31 based on a nonlinear Gauss-Seidel scheme. The only contact parameters within the CD method
 32 are the friction coefficient μ_s , the normal restitution coefficient e_n and the tangential restitution
 33 coefficient e_t between particles. We will investigate the effect of these parameters on the
 34 evolution of kinetic energy and the profile of the pile.
 35

The natural units of our system are the mean particle diameter d , mean particle mass m and gravity g . For this reason, in the following we normalize the lengths by d , the times by $(d/g)^{1/2}$, the velocities by $(gd)^{1/2}$ and the energies by mgd .



(a) Evaluating the critical state friction angle from periodic shear test.
(b) Evolution of Inertial number with friction μ

Figure 4.21 Periodic shear test using CD (?).

4.3.2 Evolution of pile geometry and run-out

In this section, we consider the spreading process following the initial energy input into the pile. Fig. ?? shows several snapshots of the pile for an initial input energy $E_0 = 61$ (in dimensionless units). The pile is sheared from the bottom to the top, thus leaving a cavity in the vicinity of the left wall. The cavity is partially filled while the pile continues to spread to the right.

In this section, we consider the spreading process following the initial energy input into the pile. Fig. ?? shows several snapshots of the pile for each pushing mode and for the same initial energy $E_0 = 61$ (in dimensionless units). In mode 1, where the same velocity is imparted to all particles, the whole pile moves away from the left wall over a short distance and then it spreads out and declines in slope. The spreading continues farther until the slope nearly declines to zero. In mode 2, where the velocity is applied to a column of particles next to the left wall, the particles belonging to the column are literally expelled from the pile. They fall back farther way on the pile after a ballistic travel above the pile. At the same time, the right side of the pile slightly spreads away while the left side is filled by the particles rolling down into the gap left by the column. In mode 3, the pile is sheared from the bottom to the top, leaving thus a cavity in the vicinity of the left wall. The cavity is partially filled while the pile continues to spread.

All pushing modes involve a transient with a sharp change of the geometry of the pile followed by continuous spreading to the right. In mode 2, most of the energy is carried away by the ejected particles. In mode 1, the pile has a rigid-body velocity component and moves away

from the left wall, but shows an efficient energy transfer leading to a long run-out distance. The transient is more energy consuming in mode 3 compared to mode 1. For this reason, the run-out distance in mode 3 is long but shorter than in mode 1. In the following, we analyze in more detail the evolution of the pile in mode 3, which mimics a horizontal quake from the bottom and, despite the creation of a cavity, remains always in contact with the left wall irrespective of the input energy.

Figure 4.4 shows the normalized run-out distance $(R_f - R_0)/R_0$ and total run-out time t_f as a function of the input energy E_0 . We observe two regimes both characterized by a power-law run-out distance and time as a function of E_0 . In the first regime, corresponding to the range of low input energies $E_0 < 40 \text{ mgd}$, the run-out distance varies as $R_f \propto (E_0)^\alpha$ with $\alpha \simeq 0.61 \pm 0.04$ over nearly one decade while the duration keeps a constant value $t_f \simeq 60 (d/g)^{0.5}$ irrespective of the value of E_0 ! The error on the value of the exponent represents the confidence interval of linear fits on the logarithmic scale. An average run-out speed can be defined from the ratio $v_s = (R_f - R_0)/t_f$. According to the data, we have $v_s \propto (E_0)^{0.61 \pm 0.04}$. Since the initial average velocity varies as $v_0 \propto (E_0)^{0.5}$, this difference between the values of the exponents suggests that the mobilized mass during run-out declines when the input energy is increased. As we shall see below, the constant run-out time reflects also the collapse of the particles into the cavity left behind the pile.

In the second regime, corresponding to the range of high input energies $E_0 > 40 \text{ mgd}$, the run-out distance varies as $R_f \propto (E_0)^{\alpha'}$ over one decade with $\alpha' \simeq 0.77 \pm 0.03$ while the duration increases as $t_f \propto (E_0)^{\beta'}$ with $\beta' \simeq 0.21 \pm 0.04$. Hence, in this regime the average run-out speed varies as $v_s \propto (E_0)^{0.56 \pm 0.07}$. This exponent is close to the value 0.5 in $v_0 \propto (E_0)^{0.5}$, and hence, within the confidence interval of the exponents, in the second regime we may assume $\beta' \simeq \alpha' - 0.5$ and $v_s \propto v_0$.

It is worth noting that a similar power-law dependence of the run-out distance and time were found in the case of collapsing columns of grains with respect to the initial aspect ratio Topin et al. (2012). In the column geometry, the particles spread away owing to the kinetic energy acquired during gravitational collapse of the column. Topin et al. found that the run-out distance varies as a power law of the available peak kinetic energy at the end of the free-fall stage with an exponent $\simeq 0.5$. This value is below those obtained here for both regimes. This is, however, physically plausible since the distribution of particle kinetic energies at the end of the collapse is more chaotic than in our simulations where the energy is supplied from the very beginning in a well-defined shear mode. As pointed out by Staron et al. (2005), the distribution of kinetic energies is an essential factor for the run-out distance.




Figure 4.22 Snapshots of MPM simulations of the evolution of granular pile subjected to a gradient impact energy.




Figure 4.23 Snapshots of CD simulations of the evolution of granular pile subjected to a gradient impact energy (?).

4.3 Slopes subjected to impact loading




Figure 4.24 Run-out behaviour of a pile subjected a gradient impact energy

¹ 4.3.3 Decay of kinetic energy

² The non-trivial evolution of the pile geometry in two regimes suggests that the energy supplied
³ to the pile is not simply dissipated by shear and friction with the bottom plane. We also need to
⁴ split the kinetic energy into its different components (x , y and rotation) of the velocity field.
⁵ The input energy is in the x component, but due to both the creation of a cavity next to the left
⁶ wall and the rolling of the particles down the free surface of the pile and between particles, a
⁷ fraction of the energy is first transferred to the y component of the velocity field and dissipated
⁸ during the transient. In this section, we analyse these features in order to arrive in a picture
⁹ consistent with the evolution of the pile shape.

¹⁰ The decay of the total kinetic energy E is displayed in Fig. ??(a) for values of the input
¹¹ energy E_0 . We observe an initial fast drop of E followed by a regular fall-off until the end of the
¹² run-out. This regular fall-off occurs clearly with two different functional forms, thus revealing
¹³ two stages in the evolution of the pile. Fig. ??(b) shows the same plots normalized by E_0 . We
¹⁴ see that all plots corresponding to the first regime (low energies) collapse nearly on to a single
¹⁵ time evolution. This is consistent with the fact that, as previously shown, in this regime the run-
¹⁶ out time t_f is independent of the input energy. In contrast, the plots corresponding to the second
¹⁷ regime (high energies) collapse only at the beginning of run-out, i.e. for $t < t_1 \simeq 7.5 (d/g)^{0.5}$.

¹⁸ ?? displays the evolution of kinetic energy in the translational (E_x and E_y) and rotational
¹⁹ (E_θ) degrees of freedom of the particles. E_x decays as the total energy, but E_y and E_θ increase
²⁰ and pass through a peak before decaying rapidly to a negligibly small level. The transient is
²¹ best observed for E_y , which has significant values only for $t < t_1$. This energy represents the
²² proportion of kinetic energy transferred to the y component of the velocity field due to the
²³ destabilization of the pile and collapse of particles in the cavity behind the pile. We note that
²⁴ the lower E_0 , the higher the peak value of E_y/E_0 . This means that, at low values of the input
²⁵ energy a larger fraction of input energy E_0 is consumed in the destabilization process whereas
²⁶ at a high level of input energy, most of it is dissipated in the spreading phase. For this reason,
²⁷ the total duration t_1 of this destabilization transient is nearly the same in both regimes and its
²⁸ value is controlled by the gravity rather than the input energy. The height of the pile being of
²⁹ the order of $80 d$, the total free-fall time for a particle located at this height is $\simeq 12 (d/g)^{0.5}$,
³⁰ which is of the same order as t_1 . As to the rotational energy, its contribution both to the transient
³¹ stage and spreading appears to be negligible.

³² To analyze the second phase in the second regime, we now consider only the kinetic energy
³³ E'_{x0} available at the end of the transient. This energy is responsible for most of the run-out and
³⁴ hence it is expected to control the run-out distance and time. Fig. ??(a) shows the evolution
³⁵ of E_x normalized by E'_{x0} as a function of time. The plots have seemingly the same aspect but
³⁶ they show different decay times. A decay time τ can be defined as the time required for E_x to

4.3 Slopes subjected to impact loading







Figure 4.25 Evolution of kinetic energy with time



(a) Evolution of normalised horizontal kinetic energy with time



(b) Evolution of normalised vertical kinetic energy with time

Figure 4.26 Evolution of vertical and horizontal kinetic energy with time

decline by a factor 1/2. Fig. ??(b) shows the same data in which the time t' elapsed since t_1 is normalized by τ . Interestingly, now all the data nicely collapse on the same curve. We checked that this curve can not be fitted by simple functional forms such as variants of exponential decay. This means that the spreading of the pile is not a self-similar process in agreement with the fact that the energy fades away in a finite time t'_f .




Figure 4.27 Evolution of kinetic energy in the x component of the velocity field normalized by the available kinetic energy at the end of the transient as a function of normalized time.

The scaling of the data with the decay time τ suggests also that the run-out time t'_f since the beginning of the second phase might be a simple function of τ . Figure 4.27 shows both t'_f and τ as a function of E'_{x0} , where we observe a power law for both times over nearly one decade. The run-out time $t'_f \propto (E'_{x0})^{\beta'}$ has the same exponent $\beta' \simeq 0.21 \pm 0.03$ as t_f as a function of E_0 (see Fig. 4.4). For the decay time we have $\tau \propto (E'_{x0})^{\beta''}$ with $\beta'' \simeq 0.28 \pm 0.03$. The relation between the two times can thus be expressed as

$$t'_f = k \tau (E'_{x0})^{\beta'' - \beta'}, \quad (4.11)$$

where $k \simeq 5 \pm 0.4$ and $\beta'' - \beta' \simeq -0.05 \pm 0.06$. This value is small enough to be neglected within the confidence interval of our data. It is therefore plausible to assume that the run-out time is a multiple of the decay time and the spreading process is controlled by a single time. We however note that a weak dependence on the energy E'_{x0} is consistent with the fact that the whole available energy at the beginning of the second phase is not dissipated in the spreading process (calculated from the position of the tip of the pile) since the pile keeps deforming by the movements of the particles at the free surface even when the tip comes to rest. This can explain the small difference between the two exponents as observed here.

4.3.4 Effect of friction

The run-out distance and time and the dissipation of kinetic energy are controlled by the input energy and collective dynamics of the whole pile, as it was analyzed in the previous sections. But they are expected to depend also on the friction. We performed a series of simulations with different values of base friction. The results are shown in Fig. ?? for the profiles of the pile and evolution of the kinetic energy in time. We see no difference in the results for different values of $e_n = e_t$. This is a consequence of the fact that, even at large input energies, the pile remains in a dense state so that multiple collisions inside the pile occur at small time scales compared to the deformation time. When the restitution coefficients are increased, more collisions occur during a longer time interval but the overall energy dissipation rate by collisions remains the same. This effect is a seminal example of collective effects which erase the influence of local parameters at the macroscopic scale. In contrast with the restitution coefficients, however, the effect of the friction coefficient is quite important for the run-out, as observed in Fig. ?? for both the energy decay and geometrical profile of the pile. Both the run-out distance and decay time decrease as the friction coefficient is increased. This effect is much more pronounced at low values of the friction coefficient. The run-out time, for example, is reduced by a factor 4 as μ_s is increased from 0.1 to 0.4 while the run-out times and profiles do not change much for $\mu_s = 0.7$. This “saturation effect” was evidenced in a systematic way in simple shear tests and explained by the observation that the dissipation rate may reach a saturation point where the dilation of the granular material and rolling of the particles change in response to the increase of the friction coefficient [Estrada et al. \(2008\)](#).

30

Mode of dissipation

The choice of this geometry was motivated by our main goal to focus on the effect of an input energy on the consecutive dynamics of a granular material. For the range of input energies

4.3 Slopes subjected to impact loading

43





(a) Power law evolution of t'_f and τ as a function of kinetic energy E_{kx0} .(b) Linear relationship between decay time and run-out time after the transient as a function of the normalized kinetic energy E_{kx0} .

Figure 4.28 Decay time and run-out time as a function of the normalised kinetic energy E_{kx0} .




(a) Effect of friction on the run-out distance




(b) Effect of friction on the duration of run-out.

Figure 4.29 Effect of friction on the run-out behaviour

4.3 Slopes subjected to impact loading



(a) Run-out distance as a function of normalised input kinetic energy



(b) Duration of run-out as a function of normalised input kinetic energy

Figure 4.30 Effect of input velocity distribution on the run-out behaviour

$t = 0 \text{ s}$



$t = 0.03 \text{ s}$



$t = 0.06 \text{ s}$



$t = 0.09 \text{ s}$



Figure 4.31 Snapshots of MPM simulations of the evolution of granular pile subjected to a gradient impact energy $E_0 = 61 \text{ mgd}$.




Figure 4.32 Snapshots of DEM simulations of the evolution of granular pile subjected to a gradient impact energy $E_0 = 61 \text{ mgd}$.

1 investigated in this pushing test by means of contact dynamics simulations, we observed a
2 power-law dependence of the run-out distance and time with non-trivial exponents. This is
3 a central result of this work as it reveals that the power-law behaviour is a generic feature of
4 granular dynamics. The values of the exponents are not simple functions of the geometry.

5 We also evidenced two regimes with different values of the exponents: a low-energy
6 regime and a high-energy regime. The first regime reflects mainly the destabilization of the
7 pile by the quake with a run-out time independent of the input energy whereas the second
8 regime is governed by the spreading dynamics induced by the higher value of the input energy.
9 We showed that the evolution of the pile in this high-energy regime can be described by a
10 characteristic decay time and the energy available at the end of the first stage where the pile is
11 destabilized by the quake.

12 This work may be pursued along two directions: 1) experimental realization of a similar
13 setup with different modes of energy injection and 2) investigating the effect of various particle
14 shapes or the presence of an ambient fluid. Although numerical simulations are generally
15 reliable with realistic results found in the past studies of steady flows, we believe that the
16 transients are more sensitive situations than steady states and the experiments are necessary
17 for checking the validation of the results suggested by the simulations. Provided a convenient
18 method is used for supplying kinetic energy homogeneously into a pile, our configuration is
19 also interesting for the investigation of the behavior of a pile immersed in a viscous fluid.

20 **4.3.5 Effect of material points**

21 **4.3.6 Comparison with granular column collapse**

22 **4.4 Summary**

23 Multi-scale simulation of granular column collapse was performed to understand the ability and
24 limitations of continuum models to capture the micro-mechanics of dense granular flows. The
25 run-out behaviour predicted by both continuum and DEM simulations matches for columns
26 with small aspect ratios, where the dissipation is predominantly frictional. However, MPM
27 predicts larger run-out distances for columns with higher aspect ratios. Energy evolution
28 studies using DEM simulations reveal that the run-out behaviour is independent of frictional
29 properties of the granular material and collision predominates the initial free-fall regime. The
30 lack of a collisional energy dissipation mechanism in MPM results in over prediction of run-out
31 distances.

4.4 Summary




Figure 4.33 Evolution of run-out with time for varying material points per cell.





Figure 4.34 Evolution of kinetic with time for varying material points per cell

4.4 Summary




Figure 4.35 Evolution of run-out and duration of flow for varying material points per cell.




Figure 4.36 Comparison of column collapse with slope subjected to impact loading.

References

- Balmforth, N. J. and Kerswell, R. R. (2005). Granular collapse in two dimensions. *Journal of Fluid Mechanics*, 538:399–428. 1
2
3
- Bandara, S. (2013). *Material Point Method to simulate Large Deformation Problems in Fluid-saturated Granular Medium*. PhD thesis, University of Cambridge. 4
5
- Daerr, A. and Douady, S. (1999). Two types of avalanche behaviour in granular media. *Nature*, 399(6733):241–243. 6
7
- Estrada, N., Taboada, A., and Radjai, F. (2008). Shear strength and force transmission in granular media with rolling resistance. *Physical Review E*, 78(2):021301. 8
9
- Guilkey, J., Harman, T., Xia, A., Kashiwa, B., and McMurtry, P. (2003). An Eulerian-Lagrangian approach for large deformation fluid structure interaction problems, Part 1: algorithm development. *Advances in Fluid Mechanics*, 36:143–156. 10
11
12
- Hogg, A. J. (2007). Two-dimensional granular slumps down slopes. *Physics of Fluids*, 19(9):9. 13
- Iverson, R. M. (1997). The physics of debris flows. *Rev. Geophys.*, 35(3):245–296. 14
- Jean, M. (1999). The non-smooth contact dynamics method. *Computer Methods in Applied Mechanics and Engineering*, 177(3-4):235–257. 15
16
- Kerswell, R. (2005). Dam break with Coulomb friction: A model for granular slumping? *Physics of Fluids*, 17:057101. 17
18
- Lacaze, L. and Kerswell, R. R. (2009). Axisymmetric Granular Collapse: A Transient 3D Flow Test of Viscoplasticity. *Physical Review Letters*, 102(10):108305. 19
20
- Lajeunesse, E., Mangeney-Castelnau, A., and Vilotte, J. P. (2004). Spreading of a granular mass on a horizontal plane. *Physics of Fluids*, 16(7):2371. 21
22
- Lajeunesse, E., Monnier, J. B., and Homsy, G. M. (2005). Granular slumping on a horizontal surface. *Physics of Fluids*, 17(10). 23
24
- Larrieu, E., Staron, L., and Hinch, E. J. (2006). Raining into shallow water as a description of the collapse of a column of grains. *Journal of Fluid Mechanics*, 554:259–270. 25
26
- Lo, C. Y., Bolton, M., and Cheng, Y. P. (2009). Discrete element simulation of granular column collapse. volume 1145 of *6th International Conference on Micromechanics of Granular Media, Powders and Grains 2009*, pages 627–630. 27
28
29

- ¹ Lube, G., Huppert, H. E., Sparks, R. S. J., and Freundt, A. (2005). Collapses of two-dimensional
² granular columns. *Physical Review E - Statistical, Nonlinear, and Soft Matter Physics*,
³ 72(4):1–10.
- ⁴ Oda, M. and Iwashita, K. (1999). *Mechanics of granular materials: an introduction*. Taylor &
⁵ Francis.
- ⁶ Radjai, F. and Dubois, F. (2011). *Discrete-element modeling of granular materials*. ISTE
⁷ Wiley, London; Hoboken, N.J.
- ⁸ Radjai, F. and Richéfeu, V. (2009). Contact dynamics as a nonsmooth discrete element method.
⁹ *Mechanics of Materials*, 41(6):715–728.
- ¹⁰ Rondon, L., Pouliquen, O., and Aussillous, P. (2011). Granular collapse in a fluid: Role of the
¹¹ initial volume fraction. *Physics of Fluids*, 23(7):073301–073301–7.
- ¹² Rycroft, C. H., Orpe, A. V., and Kudrolli, A. (2009). Physical test of a particle simulation
¹³ model in a sheared granular system. *Physical Review E*, 80(3):031305.
- ¹⁴ Schaefer, D. G. (1990). Instability and ill-posedness in the deformation of granular materials.
¹⁵ *International Journal for Numerical and Analytical Methods in Geomechanics*, 14(4):253–
¹⁶ 278.
- ¹⁷ Staron, L. and Hinch, E. J. (2006). The spreading of a granular mass: role of grain properties
¹⁸ and initial conditions. *Granular Matter*, 9(3-4):205–217.
- ¹⁹ Staron, L. and Hinch, E. J. (2007). The spreading of a granular mass: Role of grain properties
²⁰ and initial conditions. *Granular Matter*, 9(3-4):205–217.
- ²¹ Staron, L. and Lajeunesse, E. (2009). Understanding how volume affects the mobility of dry
²² debris flows. *Geophys. Res. Lett.*, 36(12):L12402.
- ²³ Staron, L., Radjai, F., and Vilotte, J. P. (2005). Multi-scale analysis of the stress state in
²⁴ a granular slope in transition to failure. *The European physical journal. E, Soft matter*,
²⁵ 18(3):311–20.
- ²⁶ Topin, V., Monerie, Y., Perales, F., and Radjaï, F. (2012). Collapse Dynamics and Runout of
²⁷ Dense Granular Materials in a Fluid. *Physical Review Letters*, 109(18):188001.
- ²⁸ Utili, S., Zhao, T., and Houslsby, G. (2014). 3D DEM investigation of granular column collapse:
²⁹ Evaluation of debris motion and its destructive power. *Engineering Geology*.
- ³⁰ Warnett, J. M., Denissenko, P., Thomas, P. J., Kiraci, E., and Williams, M. A. (2013). Scalings
³¹ of axisymmetric granular column collapse. *Granular Matter*, 16(1):115–124.
- ³² Zenit, R. (2005). Computer simulations of the collapse of a granular column. *Physics of Fluids*,
³³ 17(Compex):031703–1–031703–4.