


Name	Kinnari Shah
UID no.	2021700058
Experiment No.	1
Subject	DAA

AIM of 1A:	To implement the various functions e.g. linear, non-linear, quadratic, exponential etc
-------------------	--

Program 1

PROBLEM STATEMENT :





Bharatiya Vidya Bhavan's
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Autonomous Institute Affiliated to University of Mumbai)
Mumbai Nagar, Andheri (W), Mumbai - 400 058.

Experiment No. 0

Aim – To implement the various functions e.g. linear, non-linear, quadratic, exponential etc.

Details – A function is a relation between a set of inputs and a set of permissible outputs with the property that each input is related to exactly one output. Let A & B be any two non-empty sets; mapping from A to B will be a function only when every element in set A has one end, only one image in set B.

Problem Definition & Assumptions – For this experiment, you have to implement at least 10 functions from the following list.

$(\frac{1}{2})^n$	n^3	$\lg^2 n$	$\lg(n!)$	2^{2n}	$n^{1/\lg n}$
$\ln \ln n$	$\lg n$	$n \cdot 2^n$	$n^{1/\lg n}$	$\ln n$	$2^{\lg n}$
$2^{\lg n}$	$(\lg n)^{\lg n}$	e^n	$(\lg n)!$	$(\sqrt{2})^{\lg n}$	$\sqrt{\lg n}$
$\lg(\lg n)$	$2^{\sqrt{2} \lg n}$	n	2^n	$n \lg n$	2^{2n+1}

Note – \lg denotes for \log_2 and \ln denotes \log_e

The input (i.e. n) to all the above functions varies from 0 to 100 with increment of 1. Then add the function $n!$ in the list and execute the same for n from 0 to 20.

Important Links:

following list:

$(\frac{1}{2})^n$	n^3	$\lg^2 n$	$\lg(n!)$	2^{2n}	$n^{1/\lg n}$
$\ln \ln n$	$\lg n$	$n \cdot 2^n$	$n^{1/\lg n}$	$\ln n$	$2^{\lg n}$
$2^{\lg n}$	$(\lg n)^{\lg n}$	e^n	$(\lg n)!$	$(\sqrt{2})^{\lg n}$	$\sqrt{\lg n}$
$\lg(\lg n)$	$2^{\sqrt{2} \lg n}$	n	2^n	$n \lg n$	2^{2n+1}

Note – \lg denotes for \log_2 and \ln denotes \log_e

The input (i.e. n) to all the above functions varies from 0 to 100 with increment of 1. Then add the function $n!$ in the list and execute the same for n from 0 to 20.

Important Links:

- C/C++ Function Online library
<https://cplusplus.com/reference/cstdlib/rand/>
- Formal definition of Function
https://www.whitman.edu/mathematics/higher_math_online/section04.01.html
- Draw 2-D plot using OpenLibre/MS Excel
<https://support.microsoft.com/en-us/topic/present-your-data-in-a-scatter-chart-or-a-line-chart-4570a80f-599a-4c6b-a155-104a9018b86e>

Input –

1) Each student randomly chose any ten functions from the aforementioned list.

Output –

- Print the values of each function value for all n starting 0 to 100 in tabular format for both aforementioned cases
- Draw two 2D plot of all functions such that x-axis represents the values of n and y-axis represent the function value for different n values using LibreOffice Calc/MS Excel.

PROGRAM:

```
#include <stdio.h>
#include <math.h>

double f1(int arr[])
{
    printf("\nf1=3/2^n\n");
    for(int i=0;i<=10;i++)
    {
        double r=pow(3.0/2,arr[i]);
        printf("%.2lf \t",r);
    }
    printf("\n");
}

double f2(int arr[])
{
    printf("\nf2=n^3\n");
    for(int i=0;i<=10;i++)
    {
        double r=pow(arr[i],3);
        printf("%.2lf \t",r);
    }
    printf("\n");
}

double f3(int arr[])
{
    printf("\nf3=(logx)^2\n");
    for(int i=0;i<=10;i++)
    {
        double r=pow(log(arr[i]),2);
        printf("%.2lf \t",r);
    }
    printf("\n");
}
```

```

double f4(int arr[])
{
    printf("\nf4=2^n\n");
    for(int i=0;i<=10;i++)
    {
        double r=pow(2,arr[i]);
        printf("%.2lf \t",r);
    }
    printf("\n");
}

double f5(int arr[])
{
    printf("\nf5=n*(2^n)\n");
    for(int i=0;i<=10;i++)
    {
        double r=pow(2,arr[i]);
        printf("%.2lf \t",arr[i]*r);
    }
    printf("\n");
}

double f6(int arr[])
{
    printf("\nf6=n\n");
    for(int i=0;i<=10;i++)
    {
        printf("%d \t",arr[i]);
    }
    printf("\n");
}

double f7(int arr[])
{
    printf("\nf7=n*logn\n");
    for(int i=0;i<=10;i++)

```

```

    {
        double r=arr[i]*log(arr[i]);
        printf("%.2lf \t",r);
    }
    printf("\n");
}

double f8(int arr[])
{
    printf("\nf8=logn\n");
    for(int i=0;i<=10;i++)
    {
        double r=log(arr[i]);
        printf("%.2lf \t",r);
    }
    printf("\n");
}

double f9(int arr[])
{
    printf("\nf9=2^logn\n");
    for(int i=0;i<=10;i++)
    {
        double r=pow(2,log(arr[i]));
        printf("%.2lf \t",r);
    }
    printf("\n");
}

double f10(int arr[])
{
    printf("\nf10=2^(n+1)\n");
    for(int i=0;i<=10;i++)
    {
        double r=pow(2,(arr[i]+1));
        printf("(%.2lf) \t",r);
    }
}

```

```
    }
    printf("\n");
}

long fact(int n)
{
    if(n==0)
        return 1;

    else
        return (n*fact(n-1));
}

int main()
{
    int arr[11]={0,10,20,30,40,50,60,70,80,90,100};
    f1(arr);
    f2(arr);
    f3(arr);
    f4(arr);
    f5(arr);
    f6(arr);
    f7(arr);
    f8(arr);
    f9(arr);
    f10(arr);

    printf("\nf11=n!\n");
    for(int i=0;i<=20;i++)
    {
        fact(i);
        printf("%ld\t",fact(i));
    }
    printf("\n");

    return 0;
```

}

RESULT:

```
f1=3/2^n
1.00  57.67  3325.26      191751.06      11057332.32      637621500.21      36768468716.93      2120255184830.25      122264598055704.6
4      7050392822843069.00      406561177535215232.00

f2=n^3
0.00  1000.00      8000.00      27000.00      64000.00      125000.00      216000.00      343000.00      512000.00      729
000.00      1000000.00

f3=(logx)^2
inf  5.30  8.97  11.57  13.61  15.30  16.76  18.05  19.20  20.25  21.21

f4=2^n
1.00  1024.00      1048576.00      1073741824.00      1099511627776.00      1125899906842624.00      1152921504606846976.00      118059162
0717411303424.00      1208925819614629174706176.00      1237940039285380274899124224.00      1267650600228229401496703205376.00

f5=n*(2^n)
0.00  10240.00      20971520.00      32212254720.00      43980465111040.00      56294995342131200.00      69175290276410818560.00      826
41413450218791239680.00      96714065569170333976494080.00      111414603535684224740921180160.00      126765060022822940149670320537600.0
0

f6=n
0  10  20  30  40  50  60  70  80  90  100

f7=n*logn
-nan  23.03  59.91  102.04  147.56  195.60  245.66  297.39  350.56  404.98  460.52




f8=logn
-inf  2.30  3.00  3.40  3.69  3.91  4.09  4.25  4.38  4.50  4.61

f9=2^logn
0.00  4.93  7.98  10.56  12.90  15.05  17.08  19.01  20.85  22.62  24.34

f10=2^(n+1)
(2.00)  (2048.00)      (2097152.00)      (2147483648.00)      (2199023255552.00)      (2251799813685248.00)      (2305843009213693952.00)
(2361183241434822606848.00)      (2417851639229258349412352.00)      (2475880078570760549798248448.00)      (25353012004564588029934064
10752.00)

f11=n!
1  1  2  6  24  120  720  5040  40320  362880  3628800  39916800  479001600  6227020800  871
78291200  1307674368000  20922789888000  355687428096000  6402373705728000  121645100408832000  2432902008176640000

...Program finished with exit code 0
Press ENTER to exit console.
```



OBSERVATIONS:

- From these graphs we observe that some functions are increasing faster than others. For eg $2^{(x+1)}$ is increasing faster and is more steeper than $x \cdot \log x$. Also $2^{(x+1)}$ is steeper than $2^{\log x}$ and $\log x$.
- Also $x \cdot 2^x$ is steeper than x , 2^x , x^3 and $(\log x)^2$.
- All the graphs are increasing in nature from values 0 to 100.

Program 2**AIM of 1B:**

Experiment on finding the running time of an algorithm.

PROBLEM STATEMENT :

Details – The understanding of running time of algorithms is explored by implementing two basic sorting algorithms namely Insertion and Selection sorts. These algorithms work as follows.

Insertion sort– It works similar to the sorting of playing cards in hands. It is assumed that the first card is already sorted in the card game, and then we select an unsorted card. If the selected unsorted card is greater than the first card, it will be placed at the right side; otherwise, it will be placed at the left side. Similarly, all unsorted cards are taken and put in their exact place.

Selection sort– It first finds the smallest value among the unsorted elements of the array is selected in every pass and inserted to its appropriate position into the array. In this algorithm, the array is divided into two parts, first is sorted part, and another one is the unsorted part. Initially, the sorted part of the array is empty, and unsorted part is the given array. Sorted part is placed at the left, while the unsorted part is placed at the right. In selection sort, the first smallest element is selected from the unsorted array and placed at the first position. After that second smallest element is selected and placed in the second position. The process continues until the array is entirely sorted.

Problem Definition & Assumptions – For this experiment, you need to implement two sorting algorithms namely Insertion and Selection sort methods. Compare these algorithms based on time and space complexity. Time required to sorting algorithms can be performed using `high_resolution_clock::now()` under namespace `std::chrono`.

You have to generate 1,00,000 integer numbers using C/C++ Rand function and save them in a text file. Both the sorting algorithms use these 1,00,000 integer numbers as input as follows. Each sorting algorithm sorts a block of 100 integers numbers with array indexes numbers `A[0..99]`, `A[0..199]`, `A[0..299]`, ..., `A[0..99999]`. You need to use `high_resolution_clock::now()` function to find the time required for 100, 200, 300.... 100000 integer numbers. Finally, compare two algorithms namely Insertion and Selection by plotting the time required to sort 100000 integers using LibreOffice Calc/MS Excel. The x-axis of 2-D plot represents the block no. of 1000 blocks. The y-axis of 2-D plot represents the running time to sort 1000 blocks of 100,200,300,...,100000 integer numbers.

Note – You have to use C/C++ file processing functions for reading and writing randomly generated 100000 integer numbers.

Important Links:

1. C/C++ Rand function Online library
<https://cplusplus.com/reference/cstdlib/rand/>
2. Time required calculation Online library-
https://en.cppreference.com/w/cpp/chrono/high_resolution_clock/now
3. Draw 2-D plot using OpenLibre/MS Excel
<https://support.microsoft.com/en-us/topic/present-your-data-in-a-scatter-chart-or-a-line-chart-4570a80f-599a-4d6b-a155-104a9018b86e>

	<p>Input –</p> <ol style="list-style-type: none"> 1) Each student have to generate random 100000 numbers using rand() function and use this input as 1000 blocks of 100 integer numbers to Insertion and Selection sorting algorithms. <p>Output –</p> <ol style="list-style-type: none"> 1) Store the randomly generated 100000 integer numbers to a text file. 2) Draw two 2D plot of all functions such that the x-axis of 2-D plot represents the block no. of 1000 blocks. The y-axis of 2-D plot represents the running time to sort 1000 blocks of 100,200,300,...,100000 integer numbers. 3) Comment on Space complexity for two sorting algorithms.
ALGORITHM:	<p>To create a text file containing 100000 random numbers</p> <p>Step 1: Start. Include stdlib.h library to use the rand function.</p> <p>Step 2:Initialise an array of size 100000 number[100000]</p> <p>Step 3:Run a for loop from i=0 to 100000</p> <p>Step 4: Call the rand() function and store the value in number[i] array .</p> <p>Step 5:Create a input.txt file and save the 100000 randomly generated values which is in the range from 0 to 100000 .Stop.</p> <p>Selection Sort:</p> <p>Step 1: Start. Write a function to swap two numbers using a temporary variable.</p> <p>Step 2: Declare a function selectionSort(int arr[],n) which takes the array and given size of the array as argument.</p> <p>Step 3:Run for loop which runs from i=0 to n-1 and take the minimun element at first position of array by initialising minIndex=i</p> <p>Step 4:Run another for loop from j=i+1 to n which will keep checking the next two consecutive numbers in array.</p> <p>Step 5: Check if arr[j]<arr[minIndex] and find the smallest element</p> <p>Step 6: If smallest element is found update minIndex=j and call the swap function by swapping it with first element of array.</p> <p>Step 7:Now in main ,access the text file input.txt where the random numbers are stored using fopen</p> <p>Step 8:Initialise block =1 and size of data array as 100 i.e data[size]</p> <p>Start 9:Run a while loop while(block<=1000) to access 1000 blocks , in this loop</p> <ol style="list-style-type: none"> 1. Run a for loop from i=0 to i=size and start reading the random numbers in data[i] array. 2. Declare clock_t t to get starting time of program 3. Call selectionsort(data,size) to get the sorted array of first 100 numbers 4. Get the time elapsed by t=clock()-t 5. Calculate the time take for block by t/clocks_per_sec and print the runtime for first

	<p>block</p> <p>6. Update size=size+100 and block++</p> <p>7. Update the pointer by fseek to move the cursor to the start of the file.</p> <p>Step 10: Stop</p> <p>Insertion Sort :</p> <p>Step 1: Start. Declare insertionSort(int arr[],int n) function</p> <p>Step 2: Iterate from arr[1] to arr[n] over the array.</p> <p>Step 3: Compare the current element (key) to its predecessor. If the key element is smaller than its predecessor, compare it to the elements before. Move the greater elements one position up to make space for the swapped element.</p> <p>Step 4: Repeat the steps 7,8,9 as above in main function and call insertionSort(data,size) in main</p> <p>Step 5: Stop</p>
PROGRAM:	<p>Selection Sort</p> <pre> #include <stdio.h> #include<stdlib.h> #include<time.h> void swap(int *a, int *b) { int temp = *a; *a = *b; *b = temp; } void selectionSort(int arr[],int n) { for(int i=0;i<n-1;i++) { int minIndex=i; for(int j=i+1;j<n;j++) { if(arr[j]<arr[minIndex]) { minIndex=j; } } } } </pre>

```

swap(&arr[minIndex],&arr[i]);
}

}

int main()
{
//to generate 1000000 random numbers
/*int numbers[100000];
for(int i=0;i<100000;i++)
{
numbers[i]=rand()% 100000;
printf("%d \n",numbers[i]);

}*/
FILE* ptr;
// file in reading mode
ptr = fopen("input.txt", "r");
if (NULL == ptr)
{
printf("file can't be opened \n");
}
int block=1;
int size=100;
while(block<=1000)
{
int data[size];
for(int i=0;i<size;i++)
{
fscanf(ptr,"%d",&data[i]);
//printf("%d",data[i]);
}
clock_t t;
t = clock();
selectionSort(data,size);
if(block<3) //this prints sorted first 2 blocks only
{
printf("\n\nafter sorting block %d:\n",block);
for(int i=0;i<size;i++)
{
printf("%d \n",data[i]);

```

```

    }
}

t = clock() - t;
double time_taken = ((double)t)/CLOCKS_PER_SEC;
printf("\nRuntime for block number %d : %f\n",block,time_taken);
size=size+100;
block++;
fseek(ptr,0,SEEK_SET); //moving cursor again to start pointer of txt file
}
fclose(ptr);

}

```

Insertion Sort

```

#include <math.h>
#include <stdio.h>
#include<time.h>
void insertionSort(int arr[], int n)
{
    int i, key, j;
    for (i = 1; i < n; i++)
    {
        key = arr[i];
        j = i - 1;
        while (j >= 0 && arr[j] > key)
        {
            arr[j + 1] = arr[j];
            j = j - 1;
        }
        arr[j + 1] = key;
    }
}

int main()

```

```

{
FILE* ptr;
// file in reading mode
ptr = fopen("input.txt", "r");
if (NULL == ptr)
{
printf("file can't be opened \n");
}
int block=1;
int size=100;
while(block<=1000)
{
int data[size];
for(int i=0;i<size;i++)
{
fscanf(ptr,"%d",&data[i]);
//printf("%d",data[i]);
}


clock_t t;
t = clock();
insertionSort(data,size);
if(block<3) //this prints sorted first 2 blocks only
{
printf("\n\nafter sorting block %d:\n",block);
for(int i=0;i<size;i++)
{
printf("%d \n",data[i]);
}
}

t = clock() - t;
double time_taken = ((double)t)/CLOCKS_PER_SEC;
printf("\nRuntime for block number %d : %f\n",block,time_taken);
size=size+100;
block++;
fseek(ptr,0,SEEK_SET); //moving cursor again to start pointer of txt file
}
fclose(ptr);
}

```


RESULT:

Selection Sort

A terminal window titled "Terminal" with the date and time "Feb 13 06:59". The prompt is "kinnari@Kinnari: ~". The command executed is "./a.out". The output shows the numbers after sorting block 1: 545, 2305, 2362, 2567, 2651, 3135, 3526, 5211, 5403, 6862, 6996, 10012, 12399, 13750, 13784, 13926, 13929, 15434, 16124, 16649.


```
kinnari@Kinnari:~$ ./a.out
after sorting block 1:
545
2305
2362
2567
2651
3135
3526
5211
5403
6862
6996
10012
12399
13750
13784
13926
13929
15434
16124
16649
```

Insertion Sort

A terminal window titled "kinnari@Kinnari: ~" with the date and time "Feb 13 06:59". The prompt is "kinnari@Kinnari: ~". The commands executed are "gedit exp2.c", "gcc exp2.c", and "./a.out". The output shows the numbers after sorting block 1: 545, 2305, 2362, 2567, 2651, 3135, 3526, 5211, 5403, 6862, 6996, 10012, 12399, 13750, 13784, 13926, 13929, 15434, 16124, 16649, 17276.

```
kinnari@Kinnari:~$ gedit exp2.c
kinnari@Kinnari:~$ gcc exp2.c
kinnari@Kinnari:~$ ./a.out
after sorting block 1:
545
2305
2362
2567
2651
3135
3526
5211
5403
6862
6996
10012
12399
13750
13784
13926
13929
15434
16124
16649
17276
```

```
kinnari@Kinnari: ~  
after sorting block 2:  
545  
723  
1474  
2245  
2305  
2362  
2567  
2651  
3135  
3526  
4567  
5211  
5403  
5732  
5771  
6219  
6862  
6996  
8117  
8235  
9441  
9503  
9859  
10012
```



Observation:

From above graph, it is clearly visible that the running time for selection sort algorithm representing blue line is more than the running time for insertion sort algorithm.

The insertion sort inserts the values in a pre sorted file to sort a set of values. On the other hand, the

selection sort finds the minimum number from the list and sort it in some order which requires multiple scanning of the array and therefore more comparisons. As a result the best case time complexity of selection sort is $O(n^2)$. On the other hand in insertion sort the number of times an element is moved or swapped is greater than the comparisons made. Due to this time complexity in best case for insertion sort is $O(n)$.

Among both of the sorting algorithm, the insertion sort is fast, efficient, stable while selection sort only works efficiently when the small set of elements is involved or the list is partially previously sorted.

CONCLUSION:	In this experiment, we implemented 10 functions in C program and drew a graph for those functions in the values between 0 to 100 and also compared the run time for selection sort and insertion sort.
--------------------	--