# Deep Deterministic Policy Gradient (DDPG)

#### **Insoon Yang**

Department of Electrical and Computer Engineering Seoul National University



• Stochastic (randomized) policy:

$$\pi(a|s) = \operatorname{Prob}(a_t = a|s_t = s)$$

• Stochastic (randomized) policy:

$$\pi(a|s) = \operatorname{Prob}(a_t = a|s_t = s)$$

Probability that action a is selected given the current state is s

Stochastic (randomized) policy:

$$\pi(a|s) = \operatorname{Prob}(a_t = a|s_t = s)$$

Probability that action a is selected given the current state is s



Stochastic policy

Stochastic (randomized) policy:

$$\pi(a|s) = \operatorname{Prob}(a_t = a|s_t = s)$$

Probability that action a is selected given the current state is s



Stochastic policy

Deterministic policy:

$$a = \mu(s)$$

Stochastic (randomized) policy:

$$\pi(a|s) = \operatorname{Prob}(a_t = a|s_t = s)$$

Probability that action a is selected given the current state is s



Stochastic policy

Deterministic policy:

$$a = \mu(s)$$

Action that is selected given the current state is s

• Stochastic (randomized) policy:

$$\pi(a|s) = \operatorname{Prob}(a_t = a|s_t = s)$$

Probability that action a is selected given the current state is s



Stochastic policy

Deterministic policy:

$$a = \mu(s)$$

Action that is selected given the current state is s



#### So far we considered stochastic policy gradient

Stochastic policy gradient:

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i} \bigg( \sum_{t=0}^{T} \nabla_{\theta} \log \underbrace{\underline{\pi_{\theta}(a_{t}^{i}|s_{t}^{i})}}_{\text{stochastic policy}} \bigg) \bigg( \sum_{t=0}^{T} r(s_{t}^{i}, a_{t}^{i}) \bigg)$$

#### So far we considered stochastic policy gradient

Stochastic policy gradient:

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i} \bigg( \sum_{t=0}^{T} \nabla_{\theta} \log \underbrace{\pi_{\theta}(a_{t}^{i} | s_{t}^{i})}_{\text{stochastic policy}} \bigg) \bigg( \sum_{t=0}^{T} r(s_{t}^{i}, a_{t}^{i}) \bigg)$$

(Online) Actor-critic algorithm:

- **1** Take action  $a \sim \pi_{\theta}(a|s)$ , and observe (s, a, s', r);
- ② Fit  $v_{\phi}^{\pi}(s)$  using target  $r + \gamma v_{\phi}^{\pi}(s')$ ;
- Svaluate Advantage  $A^\pi(s,a) = r + \gamma v_\phi^\pi(s') - v_\phi^\pi(s);$
- Estimate SG  $\nabla_{\theta} J(\theta) \approx \nabla_{\theta} \log \pi_{\theta}(a|s) A^{\pi}(s,a)$ ;
- **5** Update  $\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta)$ ;

# But deterministic policy looks simpler

# But deterministic policy looks simpler

Q) Can we use deterministic policy?

#### But deterministic policy looks simpler

- Q) Can we use deterministic policy?
  - Yes, Deterministic policy gradient (DPG)

#### **Deterministic Policy Gradient Algorithms**

David Silver
DeepMind Technologies, London, UK
Guy Lever
University College London, UK
Nicolas Heess, Thomas Degris, Daan Wierstra, Martin Riedmiller
DeepMind Technologies, London, UK

DAVID@DEEPMIND.COM

GUY.LEVER@UCL.AC.UK

\*@DEEPMIND.COM

#### Towards deterministic policy gradient

ullet Parameterize deterministic policy  $\mu$  by parameter vector  $\theta$ :  $\mu_{ heta}$ 

#### Towards deterministic policy gradient

- ullet Parameterize deterministic policy  $\mu$  by parameter vector  $\theta$ :  $\mu_{ heta}$
- Idea: Move the policy in the direction of  $\nabla_{\theta}Q^{\mu^k}$  (Critic's Q-function)

#### Towards deterministic policy gradient

pi deterministic

- ullet Parameterize deterministic policy  $\mu$  by parameter vector  $\theta$ :  $\mu_{ heta}$
- ullet Idea: Move the policy in the direction of  $abla_{ heta}Q^{\mu^k}$  (Critic's Q-function)

$$\theta \leftarrow \theta + \alpha \mathbb{E}_{s \sim \rho^{\mu k}} \left[ \nabla_{\theta} Q^{\mu^k}(s, \mu_{\theta}(s)) \right],$$

where

$$\rho^{\mu}(s') := \int \sum_{t=1}^{\infty} \gamma^t p_0(s) p(s \to s', t, \mu) ds$$

denotes the discounted state visitation distribution

# Applying chain rule

$$\begin{split} \theta &\leftarrow \theta + \alpha \mathbb{E}_{s \sim \rho^{\mu^k}} \left[ \nabla_\theta Q^{\mu^k}(s, \underbrace{\mu_\theta(s)}) \right] \\ &= \theta + \alpha \mathbb{E}_{s \sim \rho^{\mu^k}} \left[ \underbrace{\nabla_\theta \mu_\theta(s) \nabla_a Q^{\mu^k}(s, a)|_{a = \mu_\theta(s)}}_{\text{chain rule}} \right] \end{split}$$

#### Applying chain rule

$$\begin{split} \theta &\leftarrow \theta + \alpha \mathbb{E}_{s \sim \rho^{\mu^k}} \left[ \nabla_\theta Q^{\mu^k}(s, \underbrace{\mu_\theta(s)}) \right] \\ &= \theta + \alpha \mathbb{E}_{s \sim \rho^{\mu^k}} \left[ \underbrace{\nabla_\theta \mu_\theta(s) \nabla_a Q^{\mu^k}(s, a)|_{a = \mu_\theta(s)}}_{\text{chain rule}} \right] \end{split}$$

Q) Does it work? Is it valid?

## Deterministic Policy Gradient Theorem

Yes, it's valid!

#### Deterministic Policy Gradient Theorem

Yes, it's valid!

• Performance objective:

$$J(\theta) := \mathbb{E}\bigg[\sum_{t=0}^{\infty} \gamma^t r(s_t, \underbrace{\mu_{\theta}(s_t)}_{\text{deterministic policy}})\bigg] = \mathbb{E}_{s \sim \rho^{\mu_{\theta}}}[r(s, \mu_{\theta}(s))]$$

#### Deterministic Policy Gradient Theorem

Yes, it's valid!

• Performance objective:

$$J(\theta) := \mathbb{E}\bigg[\sum_{t=0}^{\infty} \gamma^t r(s_t, \underbrace{\mu_{\theta}(s_t)}_{\text{deterministic policy}})\bigg] = \mathbb{E}_{s \sim \rho^{\mu_{\theta}}}[r(s, \mu_{\theta}(s))]$$

• Deterministic policy gradient:

$$\nabla_{\theta} J(\theta) = \mathbb{E}_{s \sim \rho^{\mu}} \left[ \nabla_{\theta} \mu_{\theta}(s) \nabla_{a} Q^{\mu}(s, a) |_{a = \mu_{\theta}(s)} \right]$$

#### Deterministic Actor-Critic algorithm

Initialize 
$$\underbrace{\theta}_{\text{actor net critic net}}$$
 ;

- **1** Take action  $a = \mu_{\theta}(s)$ , and observe  $\{(s, a, s', r)\}$ ;
- § Fit  $Q^{\mu}_{\phi}(s,a)$  using target  $r + \gamma Q^{\mu}_{\phi}(s',\mu_{\theta}(s'));$
- Stimate  $\nabla_{\theta}J(\theta) \approx \nabla_{\theta}\mu_{\theta}(s)\nabla_{a}Q_{\phi}^{\mu}(s,a)|_{a=\mu_{\theta}(s)};$
- Update  $\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta)$ ;

#### Deterministic Actor-Critic algorithm

Initialize 
$$\underbrace{\theta}_{\text{actor net critic net}}$$
 ;

- **1** Take action  $a = \mu_{\theta}(s)$ , and observe  $\{(s, a, s', r)\}$ ;
- § Fit  $Q^{\mu}_{\phi}(s,a)$  using target  $r + \gamma Q^{\mu}_{\phi}(s',\mu_{\theta}(s'))$ ;
- Stimate  $\nabla_{\theta} J(\theta) \approx \nabla_{\theta} \mu_{\theta}(s) \nabla_{a} Q_{\phi}^{\mu}(s,a)|_{a=\mu_{\theta}(s)};$
- Update  $\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta)$ ;
- Q) Any issue?

#### Deterministic Actor-Critic algorithm

Initialize 
$$\underbrace{\theta}_{\text{actor net critic net}}$$
 ;

- **1** Take action  $a = \mu_{\theta}(s)$ , and observe  $\{(s, a, s', r)\}$ ;
- § Fit  $Q^{\mu}_{\phi}(s,a)$  using target  $r + \gamma Q^{\mu}_{\phi}(s',\mu_{\theta}(s'));$
- Stimate  $\nabla_{\theta} J(\theta) \approx \nabla_{\theta} \mu_{\theta}(s) \nabla_{a} Q_{\phi}^{\mu}(s,a)|_{a=\mu_{\theta}(s)};$
- Update  $\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta)$ ;
- Q) Any issue?
  - On-policy: sample inefficient

And, Exploration

가

ullet Use any (behavior) policy: eta(s)

- Use any (behavior) policy:  $\beta(s)$
- Modified objective (value function of  $\mu_{\theta}$  averaged over  $\rho^{\beta}$ ):

$$J_{\beta}(\theta) = \int \rho^{\beta}(s)v^{\mu_{\theta}}(s)ds = \int \rho^{\beta}(s)Q^{\mu_{\theta}}(s,\mu_{\theta}(s))ds$$

- Use any (behavior) policy:  $\beta(s)$
- Modified objective (value function of  $\mu_{\theta}$  averaged over  $\rho^{\beta}$ ):

$$J_{\beta}(\theta) = \int \rho^{\beta}(s)v^{\mu_{\theta}}(s)ds = \int \rho^{\beta}(s)Q^{\mu_{\theta}}(s,\mu_{\theta}(s))ds$$

Modified policy gradient:

$$\nabla_{\theta} J_{\beta}(\theta) = \int \rho^{\beta}(s) \left[ \nabla_{\theta} \mu_{\theta}(s) \nabla_{a} Q^{\mu_{\theta}}(s, a) |_{a = \mu_{\theta}(s)} + \nabla_{\theta} Q^{\mu_{\theta}}(s, a) |_{a = \mu_{\theta}(s)} \right] ds$$

- Use any (behavior) policy:  $\beta(s)$
- Modified objective (value function of  $\mu_{\theta}$  averaged over  $\rho^{\beta}$ ):

$$J_{\beta}(\theta) = \int \rho^{\beta}(s)v^{\mu_{\theta}}(s)ds = \int \rho^{\beta}(s)Q^{\mu_{\theta}}(s,\mu_{\theta}(s))ds$$

Modified policy gradient:

$$\nabla_{\theta} J_{\beta}(\theta) = \int \rho^{\beta}(s) \left[ \nabla_{\theta} \mu_{\theta}(s) \nabla_{a} Q^{\mu_{\theta}}(s, a) |_{a = \mu_{\theta}(s)} + \nabla_{\theta} Q^{\mu_{\theta}}(s, a) |_{a = \mu_{\theta}(s)} \right] ds$$

Approximation (drop the second term):

$$\nabla_{\theta} J_{\beta}(\theta) \approx \int \rho^{\beta}(s) \nabla_{\theta} \mu_{\theta}(s) \nabla_{a} Q^{\mu_{\theta}}(s, a)|_{a = \mu_{\theta}(s)} ds$$
$$= \mathbb{E}_{s \sim \rho^{\beta}} \left[ \nabla_{\theta} \mu_{\theta}(s) \nabla_{a} Q^{\mu_{\theta}}(s, a)|_{a = \mu_{\theta}(s)} \right]$$

#### Off-Policy Deterministic Actor-Critic algorithm

Initialize  $\theta, \phi$ ;

- **1** Take action  $a = \beta(s)$ , and observe  $\{(s, a, s', r)\}$ ;
- ② Fit  $Q_{\phi}^{\mu}(s,a)$  using target  $r + \gamma Q_{\phi}^{\mu}(s',\mu_{\theta}(s'))$ ; (No problem?)
- $\textbf{ Stimate } \nabla_{\theta}J(\theta) \approx \nabla_{\theta}\mu_{\theta}(s)\nabla_{a}Q_{\phi}^{\mu}(s,a)|_{a=\mu_{\theta}(s)};$
- **9** Update  $\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta)$ ;

#### Off-Policy Deterministic Actor-Critic algorithm

#### Initialize $\theta, \phi$ ;

- **1** Take action  $a = \beta(s)$ , and observe  $\{(s, a, s', r)\}$ ;
- ② Fit  $Q_{\phi}^{\mu}(s,a)$  using target  $r + \gamma Q_{\phi}^{\mu}(s',\mu_{\theta}(s'))$ ; (No problem?)
- $\textbf{S Estimate } \nabla_{\theta}J(\theta) \approx \nabla_{\theta}\mu_{\theta}(s)\nabla_{a}Q_{\phi}^{\mu}(s,a)|_{a=\mu_{\theta}(s)};$
- **1** Update  $\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta)$ ;
  - Advantage: Sample efficiency
  - Disadvantage: Bias

# Can we combine it with DQN?

#### Can we combine it with DQN?

#### Why not? Deep deterministic policy gradient (DDPG)

Published as a conference paper at ICLR 2016

# CONTINUOUS CONTROL WITH DEEP REINFORCEMENT LEARNING

Timothy P. Lillicrap; Jonathan J. Hunt; Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver & Daan Wierstra Google Deepmind London, UK {countzero, jjhunt, apritzel, heess, etcm, tassa, davidsilver, wierstra} @ google.com

#### ABSTRACT

We adapt the ideas underlying the success of Deep Q-Learning to the continuous action domain. We present an actor-critic, model-free algorithm based on the deterministic policy gradient that can operate over continuous action spaces. Using the same learning algorithm, network architecture and hyper-parameters, our algorithm robustly solves more than 20 simulated physics tasks, including classic problems such as cartpole swing-up, dexterous manipulation, legged locomotion and car driving. Our algorithm is able to find policies whose performance is competitive with those found by a planning algorithm with full access to the dynamics of the domain and its derivatives. We further demonstrate that for many of the tasks the algorithm can learn policies "end-to-end": directly from raw pixel inputs.

#### Best of Both Worlds

- Actor: Deterministic policy gradient
  - Simple
  - 2 Continuous control

#### Best of Both Worlds

- Actor: Deterministic policy gradient
  - Simple
  - 2 Continuous control
- Critic: DQN
  - Off-policy (sample efficient)
  - Experience replay (minimize correlations between samples)
  - Target network (consistency)

#### Why not stochastic policy gradient + DQN?

• DQN is computationally inefficient to use with stochastic policies

## Why not stochastic policy gradient + DQN?

- DQN is computationally inefficient to use with stochastic policies
- Q) Why?

#### Why not stochastic policy gradient + DQN?

- DQN is computationally inefficient to use with stochastic policies
- Q) Why?

When computing target, it requires integral over action:

$$y_j^- := r_j + \gamma \int \pi_{\theta}(a|s_j') Q_{\phi^-}^{\pi}(s_j', a) da$$

Deterministic: gamma \* Q(s\*,a\*)

#### DDPG algorithm

- Initialize critic network  $Q_{\phi}$  and actor network  $\mu_{\theta}$  with  $\phi$  and  $\theta$ ;
- Initialize target networks  $Q_{\phi^-}$ ,  $\mu_{\theta^-}$  with  $\phi^- \leftarrow \phi$  and  $\theta^- \leftarrow \theta$ ;
- for episode = 1:M
  - Initialize a random process  $\mathcal N$  for exploration;
  - Receive initial state  $s_0$ ;
  - for t = 1 : T
    - ① Execute action  $a_t = \mu_{\theta}(s_t) + \mathcal{N}_t$  and store  $(s_t, a_t, s_{t+1}, r_t)$  in **Buffer**;
    - 2 Sample a minibatch  $\{(s_i, a_i, s_{i+1}, r_i)\}$  from **Buffer**;
    - **3** Set target  $y_i^- := r_i + \gamma Q_{\phi^-}(s_{i+1}, \mu_{\theta^-}(s_{i+1}));$
    - Update the critic network by minimizing  $L(\phi) := \frac{1}{N} \sum_{i} (Q_{\phi}(s_{i}, a_{i}) y_{i})^{2};$
    - **1** Update the actor network by using deterministic policy gradient:  $\nabla_{\theta}J(\theta) \approx \frac{1}{N}\sum_{i}\nabla_{\theta}\mu_{\theta}(s_{i})\nabla_{a}Q_{\phi}(s_{i},a)|_{a=\mu_{\theta}(s_{i})}$
    - **1** Update the target networks:  $\phi^- \leftarrow \tau \phi + (1-\tau)\phi^-$ , and  $\theta^- \leftarrow \tau \theta + (1-\tau)\theta^-$  with small  $\tau$ ;

# Advantages and Disadvantages

#### Advantages:

- Can handle continuous spaces (policy gradient)
- Sample efficiency (off-policy)
- Minimize correlations between samples (experience replay)
- Consistency (slowly changing target networks)

#### Advantages and Disadvantages

#### Advantages:

- Can handle continuous spaces (policy gradient)
- Sample efficiency (off-policy)
- Minimize correlations between samples (experience replay)
- Consistency (slowly changing target networks)

#### Disadvantages:

Exploration

#### DDPG results