

Actor-Critic Methods

Insoon Yang


Department of Electrical and Computer Engineering
Seoul National University



CORE

Control + Optimization Research Lab

Recap: Parameterizing Policy




Q) How can we find a good $\pi(a|s)$, which is a **function**?

Idea:

- Parameterize policy by a parameter vector $\theta \in \mathbb{R}^{\ell}$: $\pi_{\theta}(a|s)$
- Find an optimal θ

Recap: How to find optimal parameters θ ?



- Let $\tau := (s_0, a_0, \dots, s_T, a_T)$ denote the state-action trajectory
- By Markov property,

$$p_\theta(\tau) = p(s_0) \prod_{t=0}^T \pi_\theta(a_t | s_t) p(s_{t+1} | s_t, a_t)$$

- Approximate MDP problem:

$$\max_{\theta} \mathbb{E}_{\tau \sim p_\theta(\tau)} \left[\sum_t r(s_t, a_t) \right] =: J(\theta)$$

Recap: Policy Gradient Theorem & REINFORCE

$$\nabla_{\theta} J(\theta) = \mathbb{E}_{\tau \sim p_{\theta}(\tau)} \left[\left(\sum_{t=0}^T \nabla_{\theta} \log \pi_{\theta}(a_t | s_t) \right) \left(\sum_{t=0}^T r(s_t, a_t) \right) \right]$$

Initialize θ ;

- 1 Sample $\{\tau^i\}_{i=1}^N := \{(s_0^i, a_0^i, \dots, s_T^i, a_T^i)\}_{i=1}^N$ using the current policy $\pi_{\theta}(a_t | s_t)$
- 2 Estimate the gradient

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_{i=1}^N \left(\sum_{t=0}^T \nabla_{\theta} \log \pi_{\theta}(a_t^i | s_t^i) \right) \left(\sum_{t=0}^T r(s_t^i, a_t^i) \right)$$

- 3 Perform gradient ascent:

$$\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta);$$

Recap: Policy Gradient with Baselines

- Policy gradient

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_i \sum_{t=0}^T \nabla_{\theta} \log \pi_{\theta}(a_t^i | s_t^i) [Q^{\pi_{\theta}}(s_t^i, a_t^i) - b]$$

Recap: Policy Gradient with Baselines

- Policy gradient

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_i \sum_{t=0}^T \nabla_{\theta} \log \pi_{\theta}(a_t^i | s_t^i) [Q^{\pi_{\theta}}(s_t^i, a_t^i) - b]$$

- Good baseline: $b = v^{\pi_{\theta}}(s_t, a_t)$

$$\nabla_{\theta} J(\theta) \approx \frac{1}{N} \sum_i \sum_{t=0}^T \nabla_{\theta} \log \pi_{\theta}(a_t^i | s_t^i) A^{\pi_{\theta}}(s_t^i, a_t^i),$$

where $A^{\pi_{\theta}}(s_t^i, a_t^i) := Q^{\pi_{\theta}}(s_t^i, a_t^i) - v^{\pi_{\theta}}(s_t^i)$ is called the advantage function

How can we compute a good gradient?

Good gradient:

- ① Unbiased (Ok!)
- ② Low variance (How?)

How can we compute a good gradient?

Good gradient:

- ① Unbiased (Ok!)
- ② Low variance (How?)
 - Use baseline $b = v^{\pi_\theta}(s_t, a_t)$:

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_i \sum_{t=0}^T \nabla_\theta \log \pi_\theta(a_t^i | s_t^i) \underbrace{(Q^{\pi_\theta}(s_t^i, a_t^i) - v^{\pi_\theta}(s_t^i))}_{A^{\pi_\theta}(s_t^i, a_t^i)}$$

- Need to accurately estimate v^π , Q^π or A^π (**Policy evaluation**)

Policy evaluation

Q) How to evaluate $v^\pi(s_t)$?

Policy evaluation

Q) How to evaluate $v^\pi(s_t)$?

- Monte Carlo:

$$v^\pi(s_t) \approx \frac{1}{N} \sum_{i=1}^N \sum_{t'=t}^T r_{t'}^i$$

Policy evaluation with function approximation

Want to fit the value function by

$$v^{\pi}(s_t) \approx v_{\phi}^{\pi}(s_t) \quad \phi : \text{parameter vector}$$

Q) What are the training data?

Policy evaluation with function approximation

Want to fit the value function by

$$v^\pi(s_t) \approx v_\phi^\pi(s_t) \quad \phi : \text{parameter vector}$$

Q) What are the training data?

$$\bullet \left\{ \left(\underbrace{s_t^i}_{s^i}, \underbrace{\sum_{t'=t}^T r_{t'}^i}_{y^i} \right) \right\} =: \{(s^i, y^i)\}$$

Policy evaluation with function approximation

Want to fit the value function by

$$v^\pi(s_t) \approx v_\phi^\pi(s_t) \quad \phi : \text{parameter vector}$$

Q) What are the training data?

$$\bullet \left\{ \left(\underbrace{s_t^i}_{s^i}, \underbrace{\sum_{t'=t}^T r_{t'}^i}_{y^i} \right) \right\} =: \{(s^i, y^i)\}$$

Q) How can we find the best ϕ ?

Policy evaluation with function approximation

Want to fit the value function by

$$v^\pi(s_t) \approx v_\phi^\pi(s_t) \quad \phi : \text{parameter vector}$$


Q) What are the training data?

- $\left\{ \left(\underbrace{s_t^i}_{s^i}, \underbrace{\sum_{t'=t}^T r_{t'}^i}_{y^i} \right) \right\} =: \{(s^i, y^i)\}$

Q) How can we find the best ϕ ?

- (supervised) regression:

$$\min_{\phi} \mathcal{L}(\phi) := \frac{1}{2} \sum_i \|v_\phi^\pi(s_i) - y_i\|^2$$



Better version?

Recap) Monte Carlo target: $y_i := \sum_{t'=t}^T r_{t'}^i$

Q) Can we choose a better target?

Better version?

Recap) Monte Carlo target: $y_i := \sum_{t'=t}^T r_{t'}^i$

Q) Can we choose a better target?

- Use previous fitted value function:

$$y_i := r(s_t^i, a_t^i) + \underbrace{v_{\phi}^{\pi}(s_{t+1}^i)}_{\text{fitted value ftn}}$$

Better version?

Recap) Monte Carlo target: $y_i := \sum_{t'=t}^T r_{t'}^i$

Q) Can we choose a better target?

- Use previous fitted value function:

$$y_i := r(s_t^i, a_t^i) + \underbrace{v_\phi^\pi(s_{t+1}^i)}_{\text{fitted value ftn}}$$

- Training data:

$$\bullet \left\{ \left(\underbrace{s_t^i}_{s^i}, \underbrace{r_t^i + v_\phi^\pi(s_{t+1}^i)}_{y^i} \right) \right\} =: \{(s^i, y^i)\}$$

Better version?

Recap) Monte Carlo target: $y_i := \sum_{t'=t}^T r_{t'}^i$

Q) Can we choose a better target?

- Use previous fitted value function:


$$y_i := r(s_t^i, a_t^i) + \underbrace{v_\phi^\pi(s_{t+1}^i)}_{\text{fitted value ftn}}$$

- Training data:

- $\left\{ \left(\underbrace{s_t^i}_{s^i}, \underbrace{r_t^i + v_\phi^\pi(s_{t+1}^i)}_{y^i} \right) \right\} =: \{(s^i, y^i)\}$

- Regression:

$$\min_{\phi} \mathcal{L}(\phi) := \frac{1}{2} \sum_i \|v_\phi^\pi(s_i) - y_i\|^2$$



Actor-Critic algorithm



Batch version:

- 1 Sample $\{(s_t^i, a_t^i, s_{t+1}^i, r_t^i)\}$ using $\pi_\theta(a|s)$;
- 2 Fit $v_\phi^\pi(s)$ by solving the regression problem
$$\min_\phi \mathcal{L}(\phi) := \frac{1}{2} \sum_i \|v_\phi^\pi(s_i) - y_i\|^2;$$
- 3 Evaluate Advantage $A^\pi(s_t^i, a_t^i) = r_t^i + v_\phi^\pi(s_{t+1}^i) - v_\phi^\pi(s_t^i)$;
- 4 Estimate SG $\nabla_\theta J(\theta) \approx \sum_i \nabla_\theta \log \pi_\theta(a_t^i | s_t^i) A^\pi(s_t^i, a_t^i)$;
- 5 Update $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$;

Note:

- Critic: Step 2, 3
- Actor: Step 4, 5

Intuition behind actor-critic



Actor-Critic algorithm with discount factor

With discount factor γ :

- 1 Sample $\{(s_t^i, a_t^i, s_{t+1}^i, r_t^i)\}$ using $\pi_\theta(a|s)$;
- 2 Fit $v_\phi^\pi(s)$ by solving the regression problem
$$\min_\phi \mathcal{L}(\phi) := \frac{1}{2} \sum_i \|v_\phi^\pi(s_i) - y_i\|^2;$$
- 3 Evaluate Advantage $A^\pi(s_t^i, a_t^i) = r_t^i + \gamma v_\phi^\pi(s_{t+1}^i) - v_\phi^\pi(s_t^i)$;
- 4 Estimate SG $\nabla_\theta J(\theta) \approx \sum_i \nabla_\theta \log \pi_\theta(a_t^i | s_t^i) A^\pi(s_t^i, a_t^i)$;
- 5 Update $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$;

Online Actor-Critic algorithm

Fully incremental online version:

- 1 Take action $a \sim \pi_\theta(a|s)$, and observe (s, a, s', r) ;
- 2 Fit $v_\phi^\pi(s)$ using target $r + \gamma v_\phi^\pi(s')$;
- 3 Estimate Advantage $A^\pi(s, a) = r + \gamma v_\phi^\pi(s') - v_\phi^\pi(s)$;
- 4 Estimate SG $\nabla_\theta J(\theta) \approx \nabla_\theta \log \pi_\theta(a|s) A^\pi(s, a)$;
- 5 Update $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$;

Online Actor-Critic algorithm

Fully incremental online version:

- 1 Take action $a \sim \pi_\theta(a|s)$, and observe (s, a, s', r) ;
- 2 Fit $v_\phi^\pi(s)$ using target $r + \gamma v_\phi^\pi(s')$;
- 3 Estimate Advantage $A^\pi(s, a) = r + \gamma v_\phi^\pi(s') - v_\phi^\pi(s)$;
- 4 Estimate SG $\nabla_\theta J(\theta) \approx \nabla_\theta \log \pi_\theta(a|s) A^\pi(s, a)$;
- 5 Update $\theta \leftarrow \theta + \alpha \nabla_\theta J(\theta)$;

Q) What's an issue in actor-critic?

Online Actor-Critic algorithm

Fully incremental online version:

- 1 Take action $a \sim \pi_{\theta}(a|s)$, and observe (s, a, s', r) ;
- 2 Fit $v_{\phi}^{\pi}(s)$ using target $r + \gamma v_{\phi}^{\pi}(s')$;
- 3 Estimate Advantage $A^{\pi}(s, a) = r + \gamma v_{\phi}^{\pi}(s') - v_{\phi}^{\pi}(s)$;
- 4 Estimate SG $\nabla_{\theta} J(\theta) \approx \nabla_{\theta} \log \pi_{\theta}(a|s) A^{\pi}(s, a)$;
- 5 Update $\theta \leftarrow \theta + \alpha \nabla_{\theta} J(\theta)$;

Q) What's an issue in actor-critic?

- On-policy: sample inefficient

Off-Policy Actor-Critic

Off-Policy Actor-Critic

Thomas Degris

Flowers Team, INRIA, Talence, ENSTA-ParisTech, Paris, France

THOMAS.DEGRIS@INRIA.FR

Martha White

Richard S. Sutton

RLAI Laboratory, Department of Computing Science, University of Alberta, Edmonton, Canada

WHITEM@CS.UALBERTA.CA

SUTTON@CS.UALBERTA.CA

Key idea: Use behavior policy $\beta(a|s) \neq \pi_{\theta}(a|s)$

Off-Policy Actor-Critic

Off-Policy Actor-Critic

Thomas Degris

Flowers Team, INRIA, Talence, ENSTA-ParisTech, Paris, France

THOMAS.DEGRIS@INRIA.FR

Martha White

Richard S. Sutton

RLAI Laboratory, Department of Computing Science, University of Alberta, Edmonton, Canada

WHITEM@CS.UALBERTA.CA

SUTTON@CS.UALBERTA.CA

Key idea: Use behavior policy $\beta(a|s) \neq \pi_\theta(a|s)$

- Changes in objective: $J(\theta) \rightarrow J_\beta(\theta)$, where

$$J_\beta(\theta) := \mathbb{E}_{\tau \sim p^\beta} \left[\sum_t r(s_t, a_t) \right] = \int p^\beta(\tau) r(\tau) d\tau$$

Off-Policy Actor-Critic

Off-Policy Actor-Critic

Thomas Degris

Flowers Team, INRIA, Talence, ENSTA-ParisTech, Paris, France

THOMAS.DEGRIS@INRIA.FR

Martha White

Richard S. Sutton

RLAI Laboratory, Department of Computing Science, University of Alberta, Edmonton, Canada

WHITEM@CS.UALBERTA.CA

SUTTON@CS.UALBERTA.CA

Key idea: Use behavior policy $\beta(a|s) \neq \pi_\theta(a|s)$

- Changes in objective: $J(\theta) \rightarrow J_\beta(\theta)$, where

$$J_\beta(\theta) := \mathbb{E}_{\tau \sim p^\beta} \left[\sum_t r(s_t, a_t) \right] = \int p^\beta(\tau) r(\tau) d\tau$$

- Approximate gradient:

$$\nabla_\theta J_\beta(\theta) \approx \mathbb{E}_{\tau \sim p^\beta} \left[\frac{\pi_\theta(a|s)}{\beta(a|s)} \nabla_\theta \log \pi_\theta(a|s) r(\tau) \right]$$

Advantages and Disadvantages

Advantages:

- Lower variance (thanks to critic)
- (Often) Fast and stable convergence

Advantages and Disadvantages

Advantages:

- Lower variance (thanks to critic)
- (Often) Fast and stable convergence

Disadvantages:

- Not unbiased (because the critic is not perfect)
- Training two networks required (for actor and critic)

Will learn actor-critic deep RL methods

Published as a conference paper at ICLR 2016

HIGH-DIMENSIONAL CONTINUOUS CONTROL USING GENERALIZED ADVANTAGE ESTIMATION

John Schulman, Philipp Moritz, Sergey Levine, Michael I. Jordan and Pieter Abbeel

Department of Electrical Engineering and Computer Science

University of California, Berkeley

{joschu, pcmoritz, levine, jordan, pabbeel}@eecs.berkeley.edu