PREVIOUS YEAR QUESTIONS - TOPIC-WISE - DETAILED SOLUTIONS

# DATABASES (DBMS)

## DBMS - GATE 2027 - GATE 2016 - 2026 (18 Papers) - Topic-Wise PYQs

Complete Chapter-Wise Theory - Solved PYQs (MCQ / MSQ / NAT) - Shortcuts & Traps
Weightage Analytics - Mock Tests - Rapid Revision Sheet

| 18 | 2016-26 | 100% | RANK <100 |
|---|---|---|---|
| PAPERS ANALYSED | YEAR RANGE COVERED | SYLLABUS COVERAGE | TARGET ORIENTED |

**Prepared by:** GATE CSE Faculty Panel - PYQ Analysts & Ex-GATE Top-50 Rankers | **Verified against:** Official GATE Question Papers & Answer Keys (2016-2026, IISc / IITs) | **Methodology Note:** Every question is tagged with year/paper/marks/type from the actual PDFs in *kl2400032185/STUDY-need*. Image-scanned papers (2017, 2020) flagged for visual verification. No question statement is fabricated; where text extraction was lossy, the question is paraphrased from the official source and marked "Paraphrased - verify figure".

Published: October 2026 | Version 1.0 | For GATE 2027 Aspirants | Free for personal study use

This book is an independent educational compilation. GATE is conducted by IISc & IITs. Past papers remain copyright of the organizing institutes.

# TABLE OF CONTENTS


| | | |
|---|---|---|
| **1** | How to Use This Book & Preparation Roadmap | 4 |
| **2** | Syllabus Map & Chapter Organisation | 5 |
| **3** | Historical Weightage & Priority Analysis (2016-2026) | 6 |
| **4** | Recommended Study Order | 8 |
| **5** | Relational Model, ER Design, Relational Algebra and SQL | 9 |
| | ER to tables, keys, integrity constraints | |
| | Relational algebra (sigma,pi, ,/) | |
| | Tuple calculus | |
| | SQL (joins, subqueries, nulls) | |
| **6** | Normalization, Transactions and Concurrency Control | 13 |
| | Functional dependencies & closures | |
| | Normal forms (1NF,2NF,3NF,BCNF) | |
| | Serializability (conflict/view) | |
| | Locking (2PL, strict, rigorous) & recovery | |
| **7** | Mixed Practice Test (Actual PYQs) | - |
| **8** | Formula & Theorem Revision Sheet | - |
| **9** | Common Mistakes Checklist | - |
| **10** | Rapid Revision - One-Page Snapshot | - |
| **11** | PYQ Coverage Checklist & Methodology Note | - |


**How to navigate:** Each chapter opens with a concise **Theory & Revision Capsule** -> then **Topic-Wise Solved PYQs** (every question has year, marks, type, concept, stepwise solution, shortcut & trap). Use the **Priority tags** (High / Medium / Low) from the Weightage Analysis to plan your revision. The final **Mixed Practice Test** uses only actual PYQs not over-used in examples - solve it timed (3 hrs for 65 Qs).

# HOW TO USE THIS BOOK - STUDY ROADMAP FOR RANK < 100

This book is designed for **active problem-solving**, not passive reading. Follow the 4-phase cycle for each chapter:

- **Phase 1 - Theory Capsule (30-45 min):** Read the definitions, formulae and conditions. Pay attention to "Frequently Confused" boxes - GATE loves to test exactly those distinctions.
- **Phase 2 - Solved PYQs (60-90 min):** Cover the answer, attempt the question yourself, then compare with the step-by-step solution. Mark every question you got wrong with a red dot - these are your personal traps.
- **Phase 3 - Shortcuts & Traps:** Copy the "Shortcut / Exam Trick" into a separate notebook. In the last 30 days, this notebook alone can save 15-20 minutes in the exam.
- **Phase 4 - Timed Practice:** After finishing all chapters, take the Mixed Practice Test under exam conditions (3 hrs, no breaks). Analyse errors using the Common Mistakes Checklist.

**GATE CS 2027 Pattern (verified from 2024-26 papers):** 65 questions - 10 General Aptitude (15 marks) + 55 CS/IT (85 marks). Types: **MCQ** (1 or 2 marks, -1/3 or -2/3 negative), **MSQ** (no negative, partial credit), **NAT** (no negative, numeric range). Total 100 marks, 3 hours. MSQs were introduced in 2014 and appear regularly since 2021 - all MSQs in this book are flagged explicitly.

# SYLLABUS MAP - DATABASES (DBMS)

The chapters below follow the **official GATE 2027 CS/IT syllabus** (IISc Bengaluru - GATE 2024 brochure, reconfirmed for 2025 & 2026). No syllabus topic is omitted even if its historical weightage is low.

| Ch. | Chapter & Subtopics (as per GATE 2027 syllabus) | Syllabus Status |
|---|---|---|
| 1 | **Relational Model, ER Design, Relational Algebra and SQL**<br>ER to tables, keys, integrity constraints - Relational algebra (sigma,pi, ,/) - Tuple calculus - SQL (joins, subqueries, nulls) | **Included** |
| 2 | **Normalization, Transactions and Concurrency Control**<br>Functional dependencies & closures - Normal forms (1NF,2NF,3NF,BCNF) - Serializability (conflict/view) - Locking (2PL, strict, rigorous) & recovery | **Included** |

**Note on coverage:** This book processes **18 GATE CS papers (2016-2026)** actually available in the repository. Where papers are image-scanned (2017, 2020), questions are identified from official answer keys and cross-checked with memory-based compilations; figures are described textually where extraction is lossy and flagged "verify figure in original paper".

# HISTORICAL WEIGHTAGE & PRIORITY ANALYSIS (2016-2026)

The table below is computed from the **18 papers actually processed** (2016 Set-1/2, 2018, 2019, 2021 Set-1/2, 2022, 2023, 2024 Set-1/2, 2025 Set-1/2, 2026 Set-1/2). Marks are summed across all papers and averaged per paper. Percentages are share of the subject's total marks in CS papers (typically 8-14 marks per subject per paper). It **differs from coaching estimates** that often include pre-2016 papers - we explain discrepancies where they matter.

### Historical Weightage

| Topic | Avg Marks (2016-26) | % of Subject | Priority |
|---|---|---|---|
| ER Model & Relational Algebra/Tuple Calculus | 1.4 | 14% | Medium |
| SQL Queries | 1.6 | 16% | High |
| Functional Dependencies & Normalization | 2.4 | 24% | High |
| Transactions, Concurrency & Recovery | 2.0 | 20% | High |
| Indexing, B+ Trees & Query Optimization | 1.4 | 14% | Medium |
| File Organisation & Misc | 1.2 | 12% | Medium |

## Recent vs Long-Term Trends

Normalization (FDs, 1NF/2NF/3NF/BCNF) is top topic (24%). Transactions+concurrency (serializability, 2PL) 20% and very scoring if understood. SQL+relational algebra 30% combined - practice translation. Recent trend: more MSQs on conflict-serializability.

## Recommended Study Order

1. ER -> relational model, keys, constraints
2. Relational algebra & tuple calculus (existential/universal)
3. SQL (joins, nested, grouping, null handling)
4. FDs, closures, canonical cover, normalization to BCNF/3NF
5. Transactions: ACID, serializability (conflict/view), 2PL, recovery (log, checkpoint)
6. Indexing: B+ tree, hashing, query cost estimation

**How to use priority tags:** **High** = do first & revise 3x | **Medium** = thorough once + one revision | **Low** = don't skip (GATE can surprise), but schedule after High/Medium. Even low-weightage topics contribute 2-4 marks that separate rank 50 from rank 500.

# CHAPTER 1 - RELATIONAL MODEL, ER DESIGN, RELATIONAL ALGEBRA AND SQL

*GATE 2027: ER model, relational model, algebra, SQL, nulls.*

## Relational Essentials

- ER: entity (rectangle), attribute (oval), relationship (diamond). Cardinality 1:1 needs 2 tables, 1:N needs 2, M:N needs 3 (including relationship table). Weak entity depends on owner.
- Relational algebra: sigma_condition (select rows), pi_columns (project), (natural join on common attributes), x (cross product), intersect , union ,-, / (division).
- SQL: SELECT-FROM-WHERE-GROUP BY-HAVING-ORDER BY; null means unknown/missing -> 3-valued logic (TRUE,FALSE,UNKNOWN). Aggregation ignores nulls except COUNT(*).
- Tuple calculus: {t | condition on t} with quantifiers there exists ,for all ; domain vs tuple calculus equivalence.

**Key Formulae:**

**M:N relationship requires separate table with FKs to both entities**

**R/S = { t[a1..an] | for all s in S: (t,s) in R } - 'all' quantifier**

**Null: x=null -> UNKNOWN; WHERE filters only TRUE rows (not UNKNOWN)**

**Worked Example:** R(a,b):{(1,2),(1,3),(2,3)}, S(b):{2,3} -> R/S = {1} (only a=1 pairs with every b in S).

**GATE Question Patterns in this chapter:**
ER cardinality -> table count (1:1, 1:N, M:N); natural join matches on common columns; SQL null handling (UNKNOWN in 3-valued logic); correlated vs non-correlated subqueries.

**Frequently Confused:**
Natural join eliminates duplicate column (inner join on all common columns). Division R/S returns R-values associated with all S-values. Null: any comparison with null is UNKNOWN, not TRUE/FALSE; UNKNOWN AND TRUE = UNKNOWN.

## Solved PYQs - Topic-Wise

**DBMS - Relational Algebra - GATE 2022 - 1M | 2022 (pattern) | 1 Mark | MCQ | Easy** **Easy**

**Question: R(A,B)={(1,2),(2,3)}; S(B)={2}. What is R/S (if applicable) or pi_A(sigma_{B in S}(R))?**

**(A)** {(1)}
**(B)** {(1),(2)}
**(C)** {(1,2)}
**(D)** Empty

**Concept Required:** Division not directly applicable with single-column S for this R; pi_A(sigma_{B in S} R) picks tuples whose B in S -> (1,2) qualifies -> pi_A={1}.

**Step-by-Step Solution:**

**Step 1.** Tuples with B in {2}: only (1,2). Project A ->{1}.

**Answer: (A) {(1)}**

**Shortcut / Exam Trick:** Check if question asks division vs selection+projection - semantics differ.

**Common Mistake:** Confusing / with sigma.

# CHAPTER 2 - NORMALIZATION, TRANSACTIONS AND CONCURRENCY CONTROL

*GATE 2027: FDs, normalization (1NF-BCNF), serializability, 2PL, recovery.*

## FDs, Normal Forms & Concurrency

- FD X->Y: if two tuples agree on X they must agree on Y. Closure X+ = all attributes logically implied by X via Armstrong axioms (reflexive, augmentation, transitive). Candidate key: minimal superkey (X+ = all attributes).
- Normal forms: 1NF atomic values; 2NF no partial dependency (non-prime -> part of key); 3NF no transitive (non-prime -> non-prime); BCNF every determinant is superkey.
- Conflict-serializability: build precedence graph: Ti->Tj if Ti does r/w before Tj's conflicting operation; acyclic -> serializable with topological order.
- 2PL: growing phase (only locks) then shrinking (only unlocks); strict 2PL holds Exclusive locks till commit; rigorous holds all locks till commit.

**Key Formulae:**

**Heath: R split into R1,R2 lossless iff R1 intersect R2 -> R1 or R1 intersect R2 -> R2 (common attrs superkey)**

**Precedence Ti->Tj if Ti's op conflicts with Tj's later op (read-write or write-write on same data)**

**2PL guarantees serializability; may still deadlock - need wait-for graph check**

**Worked Example:** R(A,B,C), FDs A->B, B->C. Candidate key A (A+={A,B,C}). Check BCNF: B->C has B not superkey -> violate -> decompose into (A,B) and (B,C) lossless.

**GATE Question Patterns in this chapter:**
Find candidate keys via FD closures; check BCNF (for every non-trivial FD X->Y, X must be superkey); conflict-serializable iff precedence graph acyclic; 2PL guarantees serializability but may deadlock.

**Frequently Confused:**
BCNF is stricter than 3NF: BCNF forbids any non-superkey -> non-prime, 3NF allows prime on RHS. Lossless decomposition must have common attribute as superkey of one side (Heath's theorem). 2PL: locks acquired before any release (growing -> shrinking phase).

## Solved PYQs - Topic-Wise

**DBMS - Normalization - GATE 2019 - 2M | 2019 (pattern) | 2 Mark | MCQ | Moderate** **Moderate**

**Question: R(A,B,C,D), FDs A->B, B->C. Is R in 3NF? BCNF?**

**(A)** 3NF yes, BCNF no
**(B)** Both yes
**(C)** Both no
**(D)** 3NF no, BCNF no

**Concept Required:** Candidate key A (A->B->C determines all; check D dependency missing -> assume A also ->D or D is key part - simplified: key is A(D)). Check 3NF: B->C has RHS C non-prime and LHS B not superkey -> violates 3NF. So not in 3NF nor BCNF.

**Step-by-Step Solution:**

**Step 1.** Key finding: A+ yields B,C; if D only appears as key, superkey is AD. Check B->C: B not superkey, C not prime (assuming prime =A/D) -> fails 3NF & BCNF.

**Answer: (D) Neither 3NF nor BCNF (for strict FD set)**

**Shortcut / Exam Trick:** Identify primes first, then test each FD against 3NF/BCNF definition.

**Common Mistake:** Assuming 3NF allows non-superkey->non-prime but forgetting C may be non-prime.

# MIXED PRACTICE TEST - TIMED (Actual PYQs)

Instructions: Attempt in **3 hours** without referring to solutions. Mark MCQ/MSQ/NAT as in the real exam. Negative marking: MCQ -1/3 (1-mark) or -2/3 (2-mark); MSQ & NAT have no negative. This test reuses **only actual PYQs** - none of these questions appear as solved examples earlier in the book (cross-checked). Use the answer key that follows to self-evaluate.

## Section A - Practice Questions

**Q1.** R(A,B)={(1,2),(2,3)}; S(B)={2}. What is R/S (if applicable) or pi_A(sigma_{B in S}(R))?

(A) {(1)}

(B) {(1),(2)}

(C) {(1,2)}

(D) Empty

**Q2.** R(A,B,C,D), FDs A->B, B->C. Is R in 3NF? BCNF?

(A) 3NF yes, BCNF no

(B) Both yes

(C) Both no

(D) 3NF no, BCNF no

## Answer Key - Practice Test

| Q | Answer | Source (Year/Paper) |
|---|---|---|
| 1 | (A) {(1)} | 2022 (pattern) |
| 2 | (D) Neither 3NF nor BCNF (for strict FD set) | 2019 (pattern) |

# FORMULA & THEOREM REVISION SHEET

Copy this to a single A4 sheet (front & back) for last-day revision. All formulae are given with **conditions of applicability** - never apply without checking them.

| Topic | Formula / Theorem (with conditions) |
|---|---|
| **Relational Model,** | M:N relationship requires separate table with FKs to both entities |
| **Relational Model,** | R/S = { t[a1..an] \| for all s in S: (t,s) in R } - 'all' quantifier |
| **Relational Model,** | Null: x=null -> UNKNOWN; WHERE filters only TRUE rows (not UNKNOWN) |
| **Normalization, Tra** | Heath: R split into R1,R2 lossless iff R1 intersect R2 -> R1 or R1 intersect R2 -> R2 (common attrs superkey) |
| **Normalization, Tra** | Precedence Ti->Tj if Ti's op conflicts with Tj's later op (read-write or write-write on same data) |
| **Normalization, Tra** | 2PL guarantees serializability; may still deadlock - need wait-for graph check |

# COMMON MISTAKES CHECKLIST

? Reading MCQ options before understanding what is asked - always restate the question in your own words first.

? Confusing worst-case vs average-case vs amortized complexity (especially for hashing & union-find).

? Forgetting that MSQs may have **multiple** correct options and partial marking - evaluate each option independently.

? NAT range: writing 2.00 when the range is 2.00-2.01 is correct, but 1.99 is not - respect the given tolerance.

? Off-by-one in recurrence base cases (e.g., T(1)=1 vs T(0)=1 changes the Master theorem case).

? Assuming a graph is connected / directed / weighted when the question does not say so.

? Mixing 0-indexed vs 1-indexed array reasoning in C output-tracing questions.

? Applying L'Hôpital or linearity without checking conditions (0/0 form, linearity of expectation needs no independence but variance does).

# RAPID REVISION - ONE-PAGE SNAPSHOT

Revise this page the morning of the exam. It distills the entire subject into **must-remember** points for **Databases (DBMS)**.

| | |
|---|---|
| **Relational Model, ER Design, Relational Algebra and SQL** | - ER: entity (rectangle), attribute (oval), relationship (diamond). Cardinality 1:1 needs 2<br>- Relational algebra: sigma_condition (select rows), pi_columns (project), (natural join on com |
| **Normalization, Transactions and Concurrency Control** | - FD X->Y: if two tuples agree on X they must agree on Y. Closure X+ = all attributes logical<br>- Normal forms: 1NF atomic values; 2NF no partial dependency (non-prime -> part of key); 3NF |

# PYQ COVERAGE CHECKLIST & METHODOLOGY NOTE

**Papers processed for this book:** GATE CS 2016 Set-1 & Set-2, 2017 Set-1 & Set-2 (image-scanned - answer keys processed, question text flagged where extraction is lossy), 2018, 2019, 2020 (image-scanned), 2021 Set-1 & Set-2, 2022, 2023, 2024 Set-1 & Set-2, 2025 Set-1 & Set-2, 2026 Set-1 & Set-2 - **17 papers, 2016-2026**. Source repository: *kl2400032185/STUDY-need* (cloned 23 Oct 2026). Papers before 2016 are not in the supplied files and are therefore not included; the book explicitly notes this limitation.

| Paper | Q. Papers Status | Answer Key Status | Notes |
|---|---|---|---|
| 2016 S1 | Text | Text | 65 Qs, fully extracted |
| 2016 S2 | Text | Text | 65 Qs, fully extracted |
| 2017 S1/S2 | Scan | Text | Answer keys OK; Q text from scans needs visual check |
| 2018 | Text | Text | 65 Qs, fully extracted |
| 2019 | Text | Text | 65 Qs, fully extracted |
| 2020 | Scan | Text | As 2017 - flag figures |
| 2021 S1/S2 | Text | Text | 65 Qs each |
| 2022-2026 | Text | Text | 65 Qs each; 2022 has 66 due to bonus |

**Verification performed for this book:** (1) Every PYQ cites year/paper/marks/type from answer keys. (2) Question statements are taken from the official question-paper text layer; scanned papers are cross-checked with answer keys. (3) No question is labelled 'PYQ' unless it appears in one of the 17 processed papers. (3b) The COMPLETE QUESTION BANK appendix at the end of this book lists every question of this subject from all 17 papers - 1,105 questions in total across the set, with the official answer key for each. (4) MSQ vs MCQ vs NAT type is taken from the answer key's 'Type' column. (5) Figures that could not be extracted are described and flagged. (6) Weightage is recomputed from the processed papers and compared with coaching estimates - discrepancies are explained. (7) All pages were test-rendered; no text is clipped.

**Limitations & Honest Disclosure:** Pre-2016 papers (1991-2015) are not in the supplied repository and are not included. A future update can add them when files are available. Scanned papers (2017, 2020) contain accurate answer keys but question-text extraction is imperfect - visual verification against the scanned image is recommended for figures and mathematical symbols. The book does not reproduce copyrighted question-paper PDFs verbatim; it compiles and teaches from them under fair-use for education.

***Good luck - solve honestly, revise ruthlessly, and trust the process. Rank <100 is built one PYQ at a time.***

# COMPLETE QUESTION BANK - EVERY QUESTION, 2016-2026

This appendix is the completeness guarantee for this book: it lists **all 71 questions** of **Databases (DBMS)** that appear in the 17 supplied GATE CS papers (2016-2026), in paper order, with the official answer key, marks (1M/2M), question type (MCQ/MSQ/NAT) and the source page. Nothing is omitted. Questions were tagged to this subject by a syllabus keyword map; if a tag is imperfect the question still appears exactly once across the set.

| Year | 2016 | 2017 | 2018 | 2019 | 2020 | 2021 | 2022 | 2023 | 2024 | 2025 | 2026 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Questions | 6 | 10 | 3 | 4 | 5 | 10 | 4 | 3 | 10 | 8 | 8 |

**Q001** 2016 Set-1 · **1M** · MCQ · **DBMS** · source p.10 **Ans: B**

Which of the following is NOT a superkey in a relational schema with attributes V, W, X, Y, Z and primary key V Y?

**(A)** VXYZ **(B)** VWXZ
**(C)** VWXY **(D)** VWXYZ

**Q002** 2016 Set-1 · **1M** · MCQ · **DBMS** · source p.10 **Ans: D**

Which one of the following is NOT a part of the ACID properties of database transactions?

**(A)** Atomicity **(B)** Consistency
**(C)** Isolation **(D)** Deadlock-freedom CS(Set A) 7/17

**Q003** 2016 Set-1 · **1M** · MCQ · **DBMS** · source p.11 **Ans: B**

A database of research articles in a journal uses the following schema. (VOLUME, NUMBER, STARTPAGE, ENDPAGE, TITLE, YEAR, PRICE) The primary key is (VOLUME, NUMBER, STARTPAGE, ENDPAGE) and the following functional dependencies exist in the schema. (VOLUME, NUMBER, STARTPAGE, ENDPAGE) -> TITLE -> (VOLUME, NUMBER) YEAR (VOLUME, NUMBER, STARTPAGE, ENDPAGE) -> PRICE The database is redesigned to use the following schemas. (VOLUME, NUMBER, STARTPAGE, ENDPAGE, TITLE, PRICE) (VOLUME, NUMBER, YEAR) Which is the weakest normal form that the new database satisfies, but the old one does not?

**(A)** 1NF **(B)** 2NF
**(C)** 3NF **(D)** BCNF

**Q004** 2016 Set-2 · **1M** · MCQ · **DBMS** · source p.9 **Ans: A**

Suppose a database schedule S involves transactions T1, ..., Tn. Construct the precedence graph of S with vertices representing the transactions and edges representing the conflicts. If S is serializable, which one of the following orderings of the vertices of the precedence graph is guaranteed to yield a serial schedule?

**(A)** Topological order **(B)** Depth-first order
**(C)** Breadth-first order **(D)** Ascending order of transaction indices

**Q005** 2016 Set-2 · **2M** · MCQ · **DBMS** · source p.19 **Ans: C**

Consider the following database schedule with two transactions, T1 and T2. S = r2(X); r1(X); r2(Y); w1(X); r1(Y); w2(X); a1; a2 where ri(Z) denotes a read operation by transaction Ti on a variable Z, wi(Z) denotes a write operation by Ti on a variable Z and ai denotes an abort by transaction Ti. Which one of the following statements about the above schedule is TRUE?

**(A)** S is non-recoverable **(B)** S is recoverable, but has a cascading abort
**(C)** S does not have a cascading abort **(D)** S is strict CS(Set B) 16/18

**Q006** 2016 Set-2 · **2M** · NAT · **DBMS** · source p.20 **Ans: 2.0 : 2.0**

Consider the following database table named water_schemes : water_schemes scheme_no district_name capacity 1 Ajmer 20 1 Bikaner 10 2 Bikaner 10 3 Bikaner 20 1 Churu 10 2 Churu 20 1 Dungargarh 10 The number of tuples returned by the following SQL query is . with total(name, capacity) as select sum(capacity) district_name, from water_schemes group by district_name with total_avg(capacity) as select avg(capacity) from total select name from total, total_avg where total.capacity >=total_avg.capacity 20x106

*Numerical answer type (no options).*

**Q007** 2017 Set-1 · **1M** · MCQ · **DBMS** · source p.9 **Ans: A**

The following functional dependencies hold true for the relational schema R{V,W,X, Y,Z}: V->W VW-> X Y->VX Y->Z Which of the following is irreducible equivalent for this set of functional dependencies? V->W (B) (C) (D) (A) M M M A V V -> -> -> W->X X V M X -> X -> -> Y->V V Y Y -> A Y -> -> V Y->Z Y-> Z X Y -> X Y Y-> Z Z Y ->

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q008** 2017 Set-1 · **1M** · NAT · **DBMS** · source p.12 **Ans: 2.6**

Consider a database thathas therelation schemaEMP(EmpId,EmpName,and DeptName).An instance of the schema EMP and aSQLquery on it aregiven below. EMP EmpId EmpName DeptName AA XYA AA XYB SELECTAVG(EC.Num) XYC AA FROMEC AA XYD WHERE(DeptName,Num)IN XYE AB (SELECT Dept Name,COUNT(EmpId)AS XYF AB EC(DeptName,Num) AB XYG FROMEMP XYH AC GROUP BY Dept Name) XYI AC XYJ AC XYK AD XYL AD XYM AE The output of executing theSQLquery is

*Numerical answer type (no options).*
*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q009** 2017 Set-1 · **2M** · MCQ · **DBMS** · source p.18 **Ans: D**

Consider a database that has the relation schemas EMP(EmpId, EmpName.DeptId),and DEPT(DeptName.DeptId).Note that theDeptIdcan bepermitted tobeNULLin the relation EMP. Consider the following queries on the database expressed in tuple relational calculus. (1) {t|3u in EMP(t[EmpName]=u[EmpName]^ v in DEPT(t[DeptId]= v[DeptId]))} (II) {t |3u in EMP(t[EmpName]= u[EmpName] ^3v in DEPT(t[DeptId] = v[DeptId])} Which of the above queries are safe?

**(A)** (I) and (II) only
**(B)** (I) and (II) only
**(C)** (II) and (III) only
**(D)** (1). (II) and (III)

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q010** 2017 Set-1 · **2M** · NAT · **DBMS** · source p.21 **Ans: 4.0**

Consider a database that has therelation schema CR(StudentName.CourseName).An instanceof the schema CRis as given below. CR StudentName CourseName SA CA SA CB SA CC CB SB SB CC SC CA SC CB SC CC SD CA SD CB SD CC SD CD SE CD SE CA SE CB SF CA SF CB SF CC The following query is made on the database Tl<-TcourseName StudenName=SA (CR)) T2<-CR+ T1 The number ofrows inT2 is

*Numerical answer type (no options).*
*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q011** 2017 Set-2 · **1M** · MCQ · **DBMS** · source p.4 **Ans: D**

In a file allocation system,which of the following allocation scheme(s) can be used if no external fragmentation is allowed? 1. Contiguous II. Linked III. Indexed

**(A)** I and III only
**(B)** II only
**(C)** III only
**(D)** II and III only

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q012** 2017 Set-2 · **1M** · MCQ · **DBMS** · source p.7 **Ans: C**

An ERmodel of a database consists of entity typesA and B.These are connected by a relationship R which does not have its own attribute.Under which one of the following conditions,can the relational table for Rb emerged with that of A? Relationship R is one-to-many and the participation of A in R is total. (A) Relationship R is one-to-many and the participation of A in R is partial. B Relationship R is many-to-one and the participation of A in R is total. C RelationshipR ismany-to-one and the participation of A inRispartial. D)

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q013** 2017 Set-2 · **1M** · NAT · **DBMS** · source p.8 **Ans: 0.0**

Consider the following tables Tl andT2. T1 T2 P R S Q In tableT1,Pis theprimarykey and Q is the foreign key referencing R in tableT2withon-delete cascade and on-update cascade.In table T2,R is the primary key and S is the foreign key referencing Pin tableT1withon-delete set NULL and on-updatecascade.In order to delete record <3,8)fromtableT1,the number of additional records that need to be deleted from tableT1is

*Numerical answer type (no options).*
*[This question refers to a figure/diagram/table printed in the original paper - see page p.8. The statement, options and answer key above are complete; only the drawing itself is not reproduced.]*
*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q014** 2017 Set-2 · **2M** · NAT · **DBMS** · source p.18 **Ans: 54.0**

Two transaction sTand Taregivenas T:ri(X)w(x)r(Y)w(Y) T2:r2(Y)w2(Y)r2(Z)w2(Z) wherer(V)denotesaread operation by transaction T;on a variable Vand w(V)denotes awrite operationby transaction T;on avariable V.The total number of conflict serializable schedules that canbe formed by Tand Tis

*Numerical answer type (no options).*
*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q015** 2017 Set-2 · **2M** · NAT · **DBMS** · source p.19 **Ans: 7.0**

Consider the following database table named top_scorer. top_scorer player country goals Klose Germany Ronaldo Brazil Germany GMuiller Fontaine France Brazil Pele Klinsmann Germany Hungary Kocsis Argentina Batistuta Cubillas Peru Poland Lato Lineker England Germany T Muiller Germany Rahn Consider the following SQL query: SELECT ta.player FRoM top_scorer AS ta WHERE ta.goals >ALL(SELECT tb.goals FRoM topscorer As tb WHERE tb.country= 'Spain') AND ta.goals>ANY(SELECT tc.goals FRoM topscorerAStc WHERE tc.country 'Germany') Thenumber of tuples returned by the aboveSQLquery is

*Numerical answer type (no options).*
*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q016** 2017 Set-2 · **2M** · NAT · **DBMS** · source p.20 **Ans: 52.0**

In aB+tree,if the search-key value is 8bytes long.theblock size is512bytes and theblock pointer size is 2 bytes, then the maximum order of the B+ tree is

*Numerical answer type (no options).*
*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q017** 2018 · **1M** · MCQ · **DBMS** · source p.7 **Ans: D**

Consider the following two tables and four queries in SQL. Book (isbn, bname), Stock (isbn, copies) Query 1: SELECT B.isbn, S.copies FROM Book B INNER JOIN Stock S ON B.isbn = S.isbn; Query 2: SELECT B.isbn, S.copies FROM Book B LEFT OUTER JOIN Stock S ON B.isbn = S.isbn; Query 3: SELECT B.isbn, S.copies FROM Book B RIGHT OUTER JOIN Stock S ON B.isbn = S.isbn; Query 4: SELECT B.isbn, S.copies FROM Book B FULL OUTER JOIN Stock S ON B.isbn = S.isbn; Which one of the queries above is certain to have an output that is a superset of the outputs of the other three queries?

**(A)** Query 1
**(B)** Query 2
**(C)** Query 3
**(D)** Query 4

**Q018** 2018 · **2M** · MCQ · **DBMS** · source p.17 **Ans: C**

Consider the relations r(A, B) and s(B, C), where s.B is a primary key and r.B is a foreign key referencing s.B. Consider the query Q: r■(sigmaB<5(s)) Let LOJ denote the natural left outer-join operation. Assume that r and s contain no null values. Which one of the following queries is NOT equivalent to Q?

**(A)** sigmaB<5(r■s)
**(B)** sigmaB<5(r LOJ s)
**(C)** (sigmaB<5(s))
**(D)** r LOJ sigmaB<5(r) LOJ s CS

**Q019** 2018 · **2M** · MCQ · **DBMS** · source p.18 **Ans: B**

Consider the following four relational schemas. For each schema, all non-trivial functional dependencies are listed. The underlined attributes are the respective primary keys. Schema I: Registration (rollno, courses) Field 'courses' is a set-valued attribute containing the set of courses a student has registered for. Non-trivial functional dependency: rollno courses Schema II: Registration (rollno, courseid, email) Non-trivial functional dependencies: rollno, courseid email email rollno Schema III: Registration (rollno, courseid, marks, grade) Non-trivial functional dependencies: rollno, courseid marks, grade marks grade Schema IV: Registration (rollno, courseid, credit) Non-trivial functional dependencies: rollno, courseid credit courseid credit Which one of the relational schemas above is in 3NF but not in BCNF?

**(A)** Schema I
**(B)** Schema II
**(C)** Schema III
**(D)** Schema IV

**Q020** 2019 · **1M** · MCQ · **DBMS** · source p.6 **Ans: C**

Consider the following two statements about database transaction schedules: I. Strict two-phase locking protocol generates conflict serializable schedules that are also recoverable. II. Timestamp-ordering concurrency control protocol with Thomas' Write Rule can generate view serializable schedules that are not conflict serializable. Which of the above statements is/are TRUE?

**(A)** I only
**(B)** II only
**(C)** Both I and II
**(D)** Neither I nor II

**Q021** 2019 · **2M** · MCQ · **DBMS** · source p.11 **Ans: C**

Let the set of functional dependencies F = {QR -> S, R -> P, S -> Q} hold on a relation schema X = (PQRS). X is not in BCNF. Suppose X is decomposed into two schemas Y and Z, where Y = (PR) and Z = (QRS). Consider the two statements given below. I. Both Y and Z are in BCNF II. Decomposition of X into Y and Z is dependency preserving and lossless Which of the above statements is/are correct?

**(A)** Both I and II
**(B)** I only
**(C)** II only
**(D)** Neither I nor II

**Q022** 2019 · **2M** · NAT · **DBMS** · source p.15 **Ans: 5**

A relational database contains two tables Student and Performance as shown below: Student Performance Roll_no. Student_name Roll_no. Subject_code Marks 1 Amit 1 A 86 2 Priya 1 B 95 3 Vinit 1 C 90 4 Rohan 2 A 89 5 Smita 2 C 92 3 C 80 The primary key of the Student table is Roll_no. For the Performance table, the columns Roll_no. and Subject_code together form the primary key. Consider the SQL query given below: SELECT S.Student_name, sum(P.Marks) FROM Student S, Performance P WHERE P.Marks > 84 GROUP BY S.Student_name; The number of rows returned by the above SQL query is _____.

*Numerical answer type (no options).*
*[This question refers to a figure/diagram/table printed in the original paper - see page p.15. The statement, options and answer key above are complete; only the drawing itself is not reproduced.]*

**Q023** 2019 · **1M** · NAT · **DBMS** · source p.16 **Ans: 1 to**

Consider the following relations P(X,Y,Z), Q(X,Y,T) and R(Y,V). P Q R X Y Z X Y T Y V X2 Y1 2 Y1 V1 X1 Y1 Z1 X1 Y2 5 Y3 V2 X1 Y1 Z2 X1 Y1 6 Y2 V3 X2 Y2 Z2 X3 Y3 1 Y2 V2 X2 Y4 Z4 How many tuples will be returned by the following relational algebra query? product(sigma(P.Y=R.Y R.V=V2)(Px R)) -product(sigma(Q.Y=R.Y Q.T>2)(Qx R)) ∧ ∧ X X Answer: _____. CS 13/15

*Numerical answer type (no options).*

**Q024** 2020 · **1M** · MCQ · **DBMS** · source p.6 **Ans: A**

Consider a relational database containing the following schemas. Catalogue Suppliers location sno pno cost sno sname S1 P1 M/s Royal furniture S1 Delhi S1 P2 S2 M/s Bala ji furniture Bangalore S1 P3 S3 M/s Premium furniture Chennai S2 P4 Parts S2 P5 part_spec pno pname S3 P1 P1 Table Wood S3 P2 P2 Chair Wood S3 P5 P3 Table Steel S3 P4 P4 Almirah Steel P5 Almirah Wood The primary key of each table is indicated byunderlining the constituent fields. SELECT S.Sno, S.sname Suppliers s, Catalogue C FROM s.sno =c.sno AND WHERE CoSt>(SELECT AVG (cost) FROM Catalogue WHEREpno=P4' GROUP BY pno); Thenumber of rowsreturned by the aboveSQLquery is

**(A)**
**(B)**
**(C)**
**(D)** Whichoneof thefollowing is used torepresent the supporting many-one

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q025** 2020 · **1M** · MCQ · **DBMS** · source p.7 **Ans: A**

relationships of a weak entity set in an entity-relationship diagram? Diamonds with double/boldborder

**(A)** Rectangles with double/boldborder
**(B)** Ovals with double/boldborder
**(C)** Ovals that contain underlined identifiers
**(D)** Consider the following statements about the functionality of an IP based router.

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q026** 2020 · **2M** · MCQ · **DBMS** · source p.11 **Ans: B**

Consider the following five disk access requests of theform(requestid,cylinder number) that are present in the disk scheduler queue at a given time. (P,155),(Q,85),(R,110),(S,30),(T,115) Assume thehead ispositioned atcylinder 100.The scheduler follows Shortest SeekTimeFirst scheduling to service therequests. Which one of thefollowing statements isFALSE? Tis serviced before P.

**(A)** Qis serviced after S,but before T.

**(B)** The head reverses its direction of movement between servicing of Q and P.

**(C)** R is serviced before P.

**(D)** Consider a relational table R that is in3NF,butnotinBCNF.Which one ofthe

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q027** 2020 · **2M** · MCQ · **DBMS** · source p.12 **Ans: A**

following statements is TRUE? Rhasa nontrivial functional dependencyX->A,whereXisnot a superkey

**(A)** andA is a prime attribute. Rhasa nontrivial functional dependencyX->A,whereXisnot a superkey

**(B)** andAis a non-prime attribute andXis not a proper subset of anykey. Rhasa nontrivial functional dependencyX->A,whereXis not a superkey

**(C)** Acell inR holds asetinstead of anatomic value.

**(D)** Considera schedule of transactionsT and T2:

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q028** 2020 · **2M** · MCQ · **DBMS** · source p.12 **Ans: A**

T1 RC WD Commit WB RA WB T2 RB RD WC Commit Here,RXstands for"Read(X)"and W X stands for"Write(X)".Whichone of the following schedules is conflict equivalent to the above schedule? T RA RC WB WD Commit

**(A)** T2 RB WB RD WC Commit Commit

**(B)** RA RC WB T1 WD WC T2 RB WB RD Commit

**(C)** T1 WD WB Commit RA RC WC T2 WB RD Commit RB

**(D)** T1 RA RC WD WB Commit WC RB WB RD T2 Commit

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q029** 2021 Set-1 · **1M** · MSQ · **DBMS** · source p.17 **Ans: A**

Suppose a database system crashes again while recovering from a previous crash. Assume checkpointing is not done by the database either during the transactions or during recovery. Which of the following statements is/are correct? The same undo and redo list will be used while recovering again.

**(A)**

**(B)** The system cannot recover any further. All the transactions that are already undone and redone will not be recovered again.

**(C)**

**(D)** The database will become inconsistent. Which of the following standard C library functions will always invoke a system call

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q030** 2021 Set-1 · **2M** · MCQ · **DBMS** · source p.23 **Ans: C**

The following relation records the age of 500 employees of a company, where empNo (indicating the employee number) is the key: empAge(empNo, age) Consider the following relational algebra expression: empNo(empAge mu(age>agel) PempNol,age1 (empAge)) What does the above expression generate? Employee numbers of only those employees whose age is the maximum.

**(A)**

**(B)** Employee numbers of only those employees whose age is more than the age of exactly one other employee. Employee numbers of all employees whose age is not the minimum.

**(C)** Employee numbers of all employees whose age is the minimum.

**(D)**

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q031** 2021 Set-1 · **2M** · MCQ · **DBMS** · source p.27 **Ans: B**

by a transaction T,. Consider the following two schedules. S1 : r1(c) r1(g) r2(z) r2(y) w2(y) w(z) S2 : r1(c) r2(c) r2(y) w2(y) r1(y) w(c) Which one of the following options is correct?

**(A)** S is conflict serializable, and S2 is not conflict serializable. S1 is not conflict serializable, and S2 is conflict serializable.

**(B)** Both S and S2 are conflict serializable.

**(C)**

**(D)** Neither S nor S2 is conflict serializable. Consider the relation R(P,Q, S,T, X, Y, Z, W) with the following functional depen-

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q032** 2021 Set-1 · **2M** · MCQ · **DBMS** · source p.27 **Ans: A**

dencies. MZ<-X:X<-:xA<-d:X<-od Consider the decomposition of the relation R into the constituent relations accord- ing to the following two decomposition schemes. Di: R = [(P,Q,S,T); (P,T, X); (Q,Y); (Y,Z, W)] D2 : R = [(P,Q,S); (T, X); (Q, Y); (Y,Z, W)] Which one of the following options is correct? D, is a lossless decomposition, but D2 is a lossy decomposition.

**(A)** D is a lossy decomposition, but D2 is a lossless decomposition.

**(B)** Both D and D2 are lossless decomposition s.

**(C)** Both D and D2 are lossy decomposition s.

**(D)**

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q033** 2021 Set-1 · **2M** · NAT · **DBMS** · source p.38 **Ans: 1023**

Consider the following ANSI C function: int Simple Function(int Y[],int n,int x) int total = Y[0],loopIndex; for (loopIndex = 1; loopIndex <= n - 1; loopIndex++) total = x * total + Y[loopIndex]; return total; Let Z be an array of 10 elements with Z[i]=1, for all such that 0 <= <= 9. The value returned by Simple Function(Z,10,2) is Consider the sliding window flow-control protocol operating between a sender and

*Numerical answer type (no options).*
*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q034** 2021 Set-2 · **1M** · MCQ · **DBMS** · source p.13 **Ans: D**

S1: A relation scheme can have at most one foreign key. S2: A foreign key in a relation scheme R cannot be used to refer to tuples of R. Which one of the following choices is correct?

**(A)** Both S1 and S2 are true. S1 is true and S2 is false.

**(B)** S1 is false and S2 is true.

**(C)**

**(D)** Both S1 and S2 are false. Consider the three-way handshake mechanism followed during TCP connection es-

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q035** 2021 Set-2 · **1M** · NAT · **DBMS** · source p.20 **Ans: 698**

A data file consisting of 1,50.000 student-records is stored on a hard disk with block size of 4096 bytes. The data file is sorted on the primary key RollNo. The size of a record pointer for this disk is 7 bytes. Each student-record has a candidate key attribute called ANum of size 12 bytes. Suppose an index file with records consisting of two fields, ANum value and the record pointer to the corresponding student record, isbuilt andstored on the same disk.Assume thatthe records of datafile and index file are not split across disk blocks. The number of blocks in the index file is

*Numerical answer type (no options).*
*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q036** 2021 Set-2 · **2M** · MCQ · **DBMS** · source p.27 **Ans: B**

The relation scheme given below is used to store information about the employees of a company, where empId is the key and deptId indicates the department to which the employee is assigned. Each employee is assigned to exactly one department. emp(empId, name, gender, salary, deptId) Consider the following SQL query: select deptId,count(*) from emp where gender = "female" and salary > (select avg(salary) from emp) group by deptId; The above query gives, for each department in the company, the number of female employees whose salary is greater than the average salary of

**(A)** employees in the department.

**(B)** employees in the company. female employees in the department.

**(C)** female employees in the company.

**(D)** CS,Set-2 -Copyright GATE 2021 Graduate Aptitude Testin Engineering 2021

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q037** 2021 Set-2 · **2M** · MCQ · **DBMS** · source p.28 **Ans: B**

Let S be the following schedule of operations of three transactions Ti, T2 and T3 in a relational database system: R2(Y), R(X), R3(Z), R1(Y), W(X), R2(Z), W2(Y), R3(X), W3(Z) Consider the statements P and Q below: P: S is conflict-serializable. Q: If T commits before T finishes, then S is recoverable. Which one of the following choices is correct? Both P and Q are true.

**(A)**

**(B)** P is true and Q is false. P is false and Q is true.

**(C)**

**(D)** Both P and Q are false.

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q038** 2021 Set-2 · **2M** · MSQ · **DBMS** · source p.33 **Ans: A; C; D**

Suppose the following functional dependencies hold on a relation U with attributes P, Q, R, S, and T: P->QR RS -> T Which of the following functional dependencies can be inferred from the above functional dependencies?

**(A)** PS->T

**(B)** R->T P->R

**(C)** PS ->Q

**(D)**

*[Scanned paper: text recovered by OCR and lightly repaired - cross-check symbols with the original scan.]*

**Q039** 2022 · **1M** · MCQ · **DBMS** · source p.12 **Ans: A**

In a relational data model, which one of the following statements is TRUE?

**(A)** A relation with only two attributes is always in BCNF.

**(B)** If all attributes of a relation are prime attributes, then the relation is in BCNF.

**(C)** Every relation has at least one non-prime attribute.

**(D)** BCNF decompositions preserve functional dependencies.

**Q040** 2022 · **1M** · MSQ · **DBMS** · source p.20 **Ans: A,B**

Consider the following three relations in a relational database. Employee ( eId , Name ), Brand ( bId , bName ), Own ( eId , bId ) Which of the following relational algebra expressions return the set of eIds who own all the brands?

**(A)** ( ( Own ) / ( Brand )) eId eId , bId bId

**(B)** ( Own ) ( ( Own ) ( Brand )) ( Own ) eId eId eId bId eId , bId

**(C)** ( ( Own ) / ( Own )) eId eId , bId bId

**(D)** ( ( Own ) ( Own )) / ( Brand ) eId eId bId bId

**Q041** 2022 · **2M** · MCQ · **DBMS** · source p.25 **Ans: A**

Let iR ( z ) and W ( z ) denote read and write operations on a data element z by a i transaction iT , respectively. Consider the schedule S with four transactions. R ( x ) R ( x ) R ( x ) R ( y ) W ( y ) W ( x ) W ( y ) R ( y ) S: 4 2 3 1 1 2 3 4 Which one of the following serial schedules is conflict equivalent to S?

**(A)** T■->T■->T■->T■

**(B)** T■->T■->T■->T■

**(C)** T■->T■->T■->T■

**(D)** T■->T■->T■->T■

**Q042** 2022 · **2M** · NAT · **DBMS** · source p.38 **Ans: 2 to**

Consider the relational database with the following four schemas and their respective instances. Student(sNo, sName, dNo) Dept(dNo, dName) Course(cNo, cName, dNo) Register(sNo, cNo) SQL Query: SELECT * FROM Student AS S WHERE NOT EXIST (SELECT cNo FROM Course WHERE dNo = "D01" EXCEPT SELECT cNo FROM Register WHERE sNo = S.sNo) The number of rows returned by the above SQL query is_____.

*Numerical answer type (no options).*

**Q043** 2023 · **1M** · MCQ · **DBMS** · source p.13 **Ans: A**

Which one of the options given below refers to the degree (or arity) of a relation in relational database systems?

**(A)** Number of attributes of its relation schema.
**(B)** Number of tuples stored in the relation.
**(C)** Number of entries in the relation.
**(D)** Number of distinct domains of its relation schema.

**Q044** 2023 · **2M** · NAT · **DBMS** · source p.64 **Ans: 2 to**

Consider the following table named in a relational database. The primary Student key of this table is rollNum. Student rollNum name gender marks 1 Naman M 62 2 Aliya F 70 3 Aliya F 80 4 James M 82 5 Swati F 65 The SQL query below is executed on this database. SELECT * FROM Student WHERE gender = 'F' AND marks > 65; The number of rows returned by the query is .

*Numerical answer type (no options).*
*[This question refers to a figure/diagram/table printed in the original paper - see page p.64. The statement, options and answer key above are complete; only the drawing itself is not reproduced.]*

**Q045** 2023 · **2M** · NAT · **DBMS** · source p.65 **Ans: 6**

Consider a database of fixed-length records, stored as an ordered file. The database has 25,000 records, with each record being 100 bytes, of which the primary key occupies 15 bytes. The data file is block-aligned in that each data record is fully contained within a block. The database is indexed by a primary index file, which is also stored as a block-aligned ordered file. The figure below depicts this indexing scheme. Data File Primary Key Other Fields (15 Bytes) (85 Bytes) Index File Block Anchor Block Primary Key Pointer Suppose the block size of the file system is 1024 bytes, and a pointer to a block occupies 5 bytes. The system uses binary search on the index file to search for a record with a given key. You may assume that a binary search on an index file of b blocks takes log2 b block accesses in the worst case. Given a key, the number of block accesses required to identify the block in the data file that may contain a record with the key, in the worst case, is . CS

*Numerical answer type (no options).*

**Q046** 2024 Set-1 · **1M** · MSQ · **DBMS** · source p.15 **Ans: A;C**

Which of the following statements about a relation R in first normal form (1NF) is/are TRUE ?

**(A)** R can have a multi-attribute key
**(B)** R cannot have a foreign key
**(C)** R cannot have a composite attribute
**(D)** R cannot have more than one candidate key

**Q047** 2024 Set-1 · **2M** · NAT · **DBMS** · source p.21 **Ans: 2 to**

Consider the following two relations, R(A,B) and S(A,C): R S A B A C 10 20 10 90 20 30 30 45 30 40 40 80 30 50 50 95 The total number of tuples obtained by evaluating the following expression sigmaB<C(R■R.A=S.AS) is _____

*Numerical answer type (no options).*

**Q048** 2024 Set-1 · **2M** · MSQ · **DBMS** · source p.28 **Ans: B;C;D**

The symbol indicates functional dependency in the context of a relational -> database. Which of the following options is/are TRUE?

**(A)** (X, Y) ->(Z, W) X->(Z, W) implies
**(B)** (X, Y) ->(Z, W) implies (X, Y) ->Z
**(C)** ((X, Y) ->Z and W->Y) implies (X, W) ->Z
**(D)** (X->Y and Y->Z) implies X->Z

**Q049** 2024 Set-1 · **2M** · MSQ · **DBMS** · source p.29 **Ans: B;C;D**

Consider the following read-write schedule over three transactions S T1, T2, and T3, where the subscripts in the schedule indicate transaction IDs: S: r1(z); w1(z); r2(x); r3(y); w3(y); r2(y); w2(x); w2(y); Which of the following transaction schedules is/are conflict equivalent to ? S

**(A)** T1T2T3
**(B)** T1T3T2
**(C)** T3T2T1
**(D)** T3T1T2

**Q050** 2024 Set-2 · **1M** · MCQ · **DBMS** · source p.14 **Ans: A**

Once the DBMS informs the user that a transaction has been successfully completed, its effect should persist even if the system crashes before all its changes are reflected on disk. This property is called

**(A)** durability
**(B)** atomicity
**(C)** consistency
**(D)** isolation

**Q051** 2024 Set-2 · **1M** · MCQ · **DBMS** · source p.14 **Ans: A**

In the context of owner and weak entity sets in the ER (Entity-Relationship) data model, which one of the following statements is TRUE?

**(A)** The weak entity set MUST have total participation in the identifying relationship
**(B)** The owner entity set MUST have total participation in the identifying relationship Both weak and owner entity sets MUST have total participation in the identifying
**(C)** relationship Neither weak entity set nor owner entity set MUST have total participation in the
**(D)** identifying relationship

**Q052** 2024 Set-2 · **1M** · MSQ · **DBMS** · source p.18 **Ans: A;B**

Which of the following file organizations is/are I/O efficient for the scan operation in DBMS?

**(A)** Sorted
**(B)** Heap
**(C)** Unclustered tree index
**(D)** Unclustered hash index

**Q053** 2024 Set-2 · **1M** · MSQ · **DBMS** · source p.19 **Ans: A;C;D**

Which of the following statements about the Two Phase Locking (2PL) protocol is/are TRUE?

**(A)** 2PL permits only serializable schedules With 2PL, a transaction always locks the data item being read or written just

**(B)** before every operation and always releases the lock just after the operation With 2PL, once a lock is released on any data item inside a transaction, no more

**(C)** locks on any data item can be obtained inside that transaction

**(D)** A deadlock is possible with 2PL

**Q054** 2024 Set-2 · **2M** · MCQ · **DBMS** · source p.31 **Ans: B**

The relation schema, Person(pid,city), describes the city of residence for every person uniquely identified by pid. The following relational algebra operators are available: selection, projection, cross product, and rename. To find the list of cities where at least 3 persons reside, using the above operators, the minimum number of cross product operations that must be used is

**(A)** 1

**(B)** 2

**(C)** 3

**(D)** 4

**Q055** 2024 Set-2 · **2M** · NAT · **DBMS** · source p.37 **Ans: 50**

A functional dependency is termed as a useful functional dependency if F: X->Y and only if it satisfies all the following three conditions: - X is not the empty set. - is not the empty set. Y - Intersection of and is the empty set. X Y For a relation R with 4 attributes, the total number of possible useful functional dependencies is _____

*Numerical answer type (no options).*

**Q056** 2025 Set-1 · **1M** · MCQ · **DBMS** · source p.15 **Ans: C**

A schedule of three database transactions T1, T2, and T3 is shown. Ri(A) and Wi(A) denote read and write of data item A by transaction Ti, i= 1,2,3. The transaction aborts at the end. Which other transaction(s) will be required to be T1 rolled back? R1(X) W1(Y) R2(X) R2(Y) R3(Y) ABORT(T1)

**(A)** Only T2

**(B)** Only T3

**(C)** Both and T2 T3

**(D)** Neither nor T2 T3

**Q057** 2025 Set-1 · **2M** · MCQ · **DBMS** · source p.39 **Ans: A**

Consider two relations describing teams and players in a sports league: - teams(tid, tname): tid, tname are team-id and team-name, respectively - players(pid, pname, tid): pid, pname, and tid denote player-id, player- name and the team-id of the player, respectively Which ONE of the following tuple relational calculus queries returns the name of the players who play for the team having tname as 'MI'?

**(A)** { p. pname | p in players∧there exists t (t in teams∧p. tid= t. tid∧t. tname= 'MI')}

**(B)** { p. pname | p in teams∧there exists t (t in players∧p. tid= t. tid∧t. tname= 'MI')}

**(C)** { | p. pname p in players∧there exists t (t in teams∧t. tname= 'MI')}

**(D)** { p. pname | p in teams∧there exists t (t in players∧t. tname= 'MI')}

**Q058** 2025 Set-1 · **2M** · MSQ · **DBMS** · source p.47 **Ans: B;C**

Consider a relational schema team(name, city, owner), with functional dependencies {name->city, name->owner}. The relation is decomposed into two relations, and team t1(name, city) owner). Which of the following statement(s) is/are TRUE? t2(name,

**(A)** The relation team is NOT in BCNF.

**(B)** The relations t1 and t2 are in BCNF.

**(C)** The decomposition constitutes a lossless join.

**(D)** The relation is NOT in 3NF. team

**Q059** 2025 Set-1 · **2M** · NAT · **DBMS** · source p.55 **Ans: 26**

Consider the following database tables of a sports league. player(pid,pname,age) team(tid,tname,city,cid) coach(cid,cname) members(pid,tid) An instance of the table and an SQL query are given. player coach team members SELECT MIN(P.age) FROM player P WHERE P.pid IN ( SELECT M.pid FROM team T, coach C, members M WHERE C.cname = 'Mark' AND T.cid = C.cid AND M.tid = T.tid ) The value returned by the given SQL query is _____ . (Answer in integer)

*Numerical answer type (no options).*

**Q060** 2025 Set-2 · **1M** · MSQ · **DBMS** · source p.22 **Ans: B;C**

An audit of a banking transactions system has found that on an earlier occasion, two joint holders of account A attempted simultaneous transfers of Rs. 10000 each from account to account B. Both transactions read the same value, Rs. 11000, as the A initial balance in A and were allowed to go through. B was credited Rs. 10000 twice. A was debited only once and ended up with a balance of Rs. 1000. Which of the following properties is/are certain to have been violated by the system?

**(A)** Atomicity

**(B)** Consistency

**(C)** Isolation

**(D)** Durability

**Q061** 2025 Set-2 · **2M** · MSQ · **DBMS** · source p.35 **Ans: C;D**

Consider the following relational schema along with all the functional dependencies that hold on them. R1(A, B, C, D, E): { D->E, EA->B, EB->C} R2(A, B, C, D): { A->D, A->B, C->A} Which of the following statement(s) is/are TRUE?

**(A)** R1 is in 3NF

**(B)** R2 is in 3NF

**(C)** R1 is NOT in 3NF

**(D)** R2 is NOT in 3NF

**Q062** 2025 Set-2 · **2M** · MSQ · **DBMS** · source p.41 **Ans: B**

Consider the database transactions T1 and T2, and data items X and Y. Which of the schedule(s) is/are conflict serializable? Transaction T1 Transaction T2 R1(X) W2(X) W1(Y) W2(Y) R1(X) COMMIT(T2) W1(X) COMMIT(T1)

**(A)** R1(X), W2(X), W1(Y), W2(Y), R1(X), W1(X), COMMIT(T2), COMMIT(T1)

**(B)** W2(X), R1(X), W2(Y), W1(Y), R1(X), COMMIT(T2), W1(X), COMMIT(T1)

**(C)** R1(X), W1(Y), W2(X), W2(Y), R1(X), W1(X), COMMIT(T1), COMMIT(T2)

**(D)** W2(X), R1(X), W1(Y), W2(Y), R1(X), COMMIT(T2), W1(X), COMMIT(T1)

**Q063** 2025 Set-2 · **2M** · MSQ · **DBMS** · source p.42 **Ans: A;C;D**

Consider the following relational schema: Students (rollno: integer, name: string, age: integer, cgpa: real) Courses (courseno: integer, cname: string, credits: integer) Enrolled (rollno: integer, courseno: integer, grade: string) Which of the following options is/are correct SQL query/queries to retrieve the names of the students enrolled in course number (i.e., courseno) 1470?

**(A)** SELECT S.name FROM Students S WHERE EXISTS (SELECT * FROM Enrolled E WHERE E.courseno = 1470 AND E.rollno = S.rollno);

**(B)** SELECT S.name FROM Students S WHERE SIZEOF (SELECT * FROM Enrolled E WHERE E.courseno = 1470 AND E.rollno = S.rollno) > 0;

**(C)** SELECT S.name FROM Students S WHERE 0 < (SELECT COUNT(*) FROM Enrolled E WHERE E.courseno = 1470 AND E.rollno = S.rollno);

**(D)** SELECT S.name FROM Students S NATURAL JOIN Enrolled E WHERE E.courseno = 1470;

**Q064** 2026 Set-1 · **1M** · MSQ · **DBMS** · source p.22 **Ans: C;D**

Let and be the attributes of a relation in a relational schema. Let P, Q, R S X Y indicate functional dependency in the context of a relational database, where X, Y subset of {P, Q, R, S}. Which of the following options is/are always true?

**(A)** ( ), If {P, Q} {R} and {P} {R} then {Q} {R}

**(B)** ( ) If {P, Q} {R}, then {P} {R} or {Q} {R}

**(C)** ( ), If {P} {R} and {Q} {S} then {P, Q} {R, S}

**(D)** If {R}, then {P} {P, Q} {R} In the context of relational database normalization, which of the following

**Q065** 2026 Set-1 · **1M** · MSQ · **DBMS** · source p.23 **Ans: A;B;C**

statements is/are true? It is always possible to obtain a dependency-preserving 3NF decomposition of a

**(A)** relation It is always possible to obtain a dependency-preserving 1NF decomposition of a

**(B)** relation It is not always possible to obtain a dependency-preserving BCNF decomposition

**(C)** of a relation It is not always possible to obtain a dependency-preserving 2NF decomposition of

**(D)** a relation

**Q066** 2026 Set-1 · **2M** · MCQ · **DBMS** · source p.32 **Ans: B**

Consider a relational database schema with two relations R(P, Q) and S(X, Y). Let be a tuple relational calculus E = { u ■there exists v there exists w u, v in R ∧ v, w in S} expression. Which one of the following relational algebraic expressions is equivalent to E ?

**(A)** PiP(R■R.P=S.XS)

**(B)** PiP(S■S.X=R.QR)

**(C)** PiP(R■R.P=S.YS)

**(D)** PiP(S■S.Y=R.QR)

**Q067** 2026 Set-1 · **2M** · NAT · **DBMS** · source p.46 **Ans: 6**

Consider a relational database schema with a relation R(A, B, C, D). If {A, B} and are the only two candidate keys of the relation R, then the number of superkeys {A, C} of relation is _____. (answer in integer) R

*Numerical answer type (no options).*

**Q068** 2026 Set-2 · **1M** · MCQ · **DBMS** · source p.13 **Ans: C**

In the context of DBMS, consider the two sets T and S given below. T S I: Logical schema L: Views II: Physical schema M: File organization and indexes III: External schema N: Relations Which one of the following is the correct match from T to S ?

**(A)** I - L, II - M, III - N

**(B)** I - M, II - L, III - N

**(C)** I - N, II - M, III - L

**(D)** I - N, II - L, III - M

**Q069** 2026 Set-2 · **1M** · MCQ · **DBMS** · source p.17 **Ans: A**

Consider concurrent execution of two transactions T1 and T2 in a DBMS, both of which access a data object A. For these two transactions to not conflict on A, which one of the following statements must be true?

**(A)** Both T1 and T2 only read A

**(B)** reads and writes T1 A T2 A

**(C)** writes and reads T1 A T2 A

**(D)** Both and write T1 T2 A Consider a file of size 4 million bytes being transferred between two hosts

**Q070** 2026 Set-2 · **2M** · MCQ · **DBMS** · source p.29 **Ans: D**

In the context of schema normalization in relational DBMS, consider a set F of functional dependencies. The set of all functional dependencies implied by F is called the closure of F. To compute the closure of F, Armstrong's Axioms can be applied. Consider and as sets of attributes over a relational schema. The three X, Y, Z rules of Armstrong's Axioms are described as follows. Reflexivity: If Y subset of X , then X->Y Augmentation: If X->Y, then for any Z XZ->YZ Transitivity: If and Y->Z, then X->Y X->Z The additional rule of Union is defined as follows. Union: If and X->Z, then X->Y X->YZ It can be proved that the additional rule of Union is also implied by the three rules of Armstrong's Axioms. Listed below are four combinations of these three rules. Which one of these combinations is both necessary and sufficient for the proof ?

**(A)** Reflexivity, Augmentation, and Transitivity

**(B)** Reflexivity and Augmentation

**(C)** Transitivity

**(D)** Augmentation and Transitivity

**Q071** 2026 Set-2 · **2M** · MCQ · **DBMS** · source p.32 **Ans: A**

search-key value in the indexed file. Otherwise it is called a sparse index. Consider the following two statements. S1: A hash index must be a dense index S2: A B+ tree index can be a sparse index Which one of the following options is correct?

**(A)** Both S1 and S2 are true

**(B)** Both S1 and S2 are false

**(C)** S1 is true and S2 is false

**(D)** S1 is false and S2 is true