

GR5241 Spring 2022

Project Milestone 2: Deep Learning Part


Name: Kangshuo Li**UNI: kl3259**

Part 4: Deep Learning

3. (5 points) Train a single layer neural network with 100 hidden units (e.g. with architecture: $784 \rightarrow 100 \rightarrow 10$). You should use the initialization scheme discussed in class and choose a reasonable learning rate (i.e. 0.1). Train the network repeatedly (more than 5 times) using different random seeds, so that each time, you start with a slightly different initialization of the weights. Run the optimization for at least 150 epochs each time. If you observe underfitting, continue training the network for more epochs until you start seeing overfitting.

(a) Plot the average training cross-entropy error (sum of the cross-entropy error terms over the training dataset divided by the total number of training example) on the y-axis vs. the epoch number (x-axis). On the same figure, plot the average validation cross-entropy error function. Examine the plots of training error and validation/test error (generalization). How does the network's performance differ on the training set versus the validation set during learning? Use the plot of training and testing error curves to support your argument.

Cross_entropy_error




The learning curves with respect to cross-entropy error of all 6 random initializations are shown above.

In this question, we set the learning rate $\eta = 0.1$, and the number of epochs equals to 180 with batch size $N_{\text{batch}} = 64$. Since we used a setup that requires sufficient epochs

(b) We could implement an alternative performance measure to the cross entropy, the mean miss-classification error. We can consider the output correct if the correct label is given a higher probability than the incorrect label, then count up the total number of examples that are classified incorrectly (divided by the total number of examples) according to this criterion for training and validation respectively, and maintain this statistic at the end of each epoch. Plot the classification error (in percentage) vs. number of epochs, for both training and testing. Do you observe a different behavior compared to the behavior of the cross-entropy error function?

Misclassification_error



(c) Visualize your best results of the learned W as one hundred 28×28 images (plot all filters as one image, as we have seen in class). Do the learned features exhibit any structure?

(d) Try different values of the learning rate. You should start with a learning rate of 0.1. You should then reduce it to .01, and increase it to 0.2 and 0.5. What happens to the convergence properties of the algorithm (looking at both average cross entropy and % incorrect)? Try momentum of 0.0, 0.5, 0.9. How does momentum affect convergence rate? How would you choose the best value of these parameters?

4. (5 points) Redo part 3(a) - 3(d) with a CNN i.e. with one 2-D convolutional layers \rightarrow Relu activation \rightarrow Maxpooling with appropriate hyperparameters. Compare the best result from the single layer neural network and the CNN, what could you conclude?

5. (5 points) Redo part 3(a) - 3(d) with your favorite deep learning architecture (e.g., introducing batch normalization, introducing dropout in training) to beat the performance of SVM with Gaussian Kernel, i.e., to have a test error rate lower than 1.4%.

