

## Grid View

[GridView](#) is a [ViewGroup](#) that displays items in a two-dimensional, scrollable grid. The grid items are automatically inserted to the layout using a [ListAdapter](#).

In this tutorial, you'll create a grid of image thumbnails. When an item is selected, a toast message will display the position of the image.

1. Start a new project named *HelloGridView*.
2. Find some photos you'd like to use, or [download these sample images](#). Save the image files into the project's `res/drawable/` directory.
3. Open the `res/layout/main.xml` file and insert the following:

```
<?xml version="1.0" encoding="utf-8"?>
<GridView xmlns:android="http://schemas.android.com/apk/res/android"
    android:id="@+id/gridview"
    android:layout_width="fill_parent"
    android:layout_height="fill_parent"
    android:columnWidth="90dp"
    android:numColumns="auto_fit"
    android:verticalSpacing="10dp"
    android:horizontalSpacing="10dp"
    android:stretchMode="columnWidth"
    android:gravity="center"
/>
```

This [GridView](#) will fill the entire screen. The attributes are rather self explanatory. For more information about valid attributes, see the [GridView](#) reference.

4. Open `HelloGridView.java` and insert the following code for the [onCreate\(\)](#) method:

```
public void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.main);

    GridView gridview = (GridView) findViewById(R.id.gridview);
    gridview.setAdapter(new ImageAdapter(this));

    gridview.setOnItemClickListener(new OnItemClickListener() {
        public void onItemClick(AdapterView<?> parent, View v, int position,
        long id) {
            Toast.makeText>HelloGridView.this, "" + position,
            Toast.LENGTH_SHORT).show();
        }
    });
}
```

After the `main.xml` layout is set for the content view, the [GridView](#) is captured from the layout with [findViewById\(int\)](#). The [setAdapter\(\)](#) method then sets a custom adapter ([ImageAdapter](#)) as the source for all items to be displayed in the grid. The [ImageAdapter](#) is created in the next step.

To do something when an item in the grid is clicked, the [setOnItemClickListener\(\)](#) method is passed a new [AdapterView.OnItemClickListener](#). This anonymous instance defines the [onItemClick\(\)](#) callback method to show a [Toast](#) that displays the index position (zero-based) of the selected item (in a real world

scenario, the position could be used to get the full sized image for some other task).

5. Create a new class called `ImageAdapter` that extends `BaseAdapter`:

```
public class ImageAdapter extends BaseAdapter {
    private Context mContext;

    public ImageAdapter(Context c) {
        mContext = c;
    }

    public int getCount() {
        return mThumbIds.length;
    }

    public Object getItem(int position) {
        return null;
    }

    public long getItemId(int position) {
        return 0;
    }

    // create a new ImageView for each item referenced by the Adapter
    public View getView(int position, View convertView, ViewGroup parent) {
        ImageView imageView;
        if (convertView == null) { // if it's not recycled, initialize some
attributes
            imageView = new ImageView(mContext);
            imageView.setLayoutParams(new GridView.LayoutParams(85, 85));
            imageView.setScaleType(ImageView.ScaleType.CENTER_CROP);
            imageView.setPadding(8, 8, 8, 8);
        } else {
            imageView = (ImageView) convertView;
        }

        imageView.setImageResource(mThumbIds[position]);
        return imageView;
    }

    // references to our images
    private Integer[] mThumbIds = {
        R.drawable.sample_2, R.drawable.sample_3,
        R.drawable.sample_4, R.drawable.sample_5,
        R.drawable.sample_6, R.drawable.sample_7,
        R.drawable.sample_0, R.drawable.sample_1,
        R.drawable.sample_2, R.drawable.sample_3,
        R.drawable.sample_4, R.drawable.sample_5,
        R.drawable.sample_6, R.drawable.sample_7,
        R.drawable.sample_0, R.drawable.sample_1,
        R.drawable.sample_2, R.drawable.sample_3,
        R.drawable.sample_4, R.drawable.sample_5,
        R.drawable.sample_6, R.drawable.sample_7
    };
}
```

First, this implements some required methods inherited from `BaseAdapter`. The constructor and `getCount()` are self-explanatory. Normally, `getItem(int)` should return the actual object at the specified position in the adapter, but it's ignored for this example. Likewise, `getItemId(int)` should return the row id of the item, but it's not needed here.

The first method necessary is [getView\(\)](#). This method creates a new [View](#) for each image added to the [ImageAdapter](#). When this is called, a [View](#) is passed in, which is normally a recycled object (at least after this has been called once), so there's a check to see if the object is null. If it *is* null, an [ImageView](#) is instantiated and configured with desired properties for the image presentation:

- [setLayoutParams\(ViewGroup.LayoutParams\)](#) sets the height and width for the View—this ensures that, no matter the size of the drawable, each image is resized and cropped to fit in these dimensions, as appropriate.
- [setScaleType\(ImageView.ScaleType\)](#) declares that images should be cropped toward the center (if necessary).
- [setPadding\(int, int, int, int\)](#) defines the padding for all sides. (Note that, if the images have different aspect-ratios, then less padding will cause for more cropping of the image if it does not match the dimensions given to the [ImageView](#).)


If the [View](#) passed to [getView\(\)](#) is *not* null, then the local [ImageView](#) is initialized with the recycled [View](#) object.

At the end of the [getView\(\)](#) method, the [position](#) integer passed into the method is used to select an image from the [mThumbIds](#) array, which is set as the image resource for the [ImageView](#).

All that's left is to define the [mThumbIds](#) array of drawable resources.

6. Run the application.

Your grid layout should look something like this:



Try experimenting with the behaviors of the [GridView](#) and [ImageView](#) elements by adjusting their properties. For example, instead of using [setLayoutParams\(ViewGroup.LayoutParams\)](#), try using [setAdjustViewBounds\(boolean\)](#).

## References

- [GridView](#)
- [ImageView](#)
- [BaseAdapter](#)
- [AdapterView.OnItemClickListener](#)

[← Back to Hello, Views](#)

[↑ Go to top](#)

Except as noted, this content is licensed under [Creative Commons Attribution 2.5](#). For details and restrictions, see the [Content License](#).

[Site Terms of Service](#) - [Privacy Policy](#) - [Brand Guidelines](#)