

Hello Views >

List View

<u>ListView</u> is a <u>ViewGroup</u> that creates a list of scrollable items. The list items are automatically inserted to the list using a <u>ListAdapter</u>.

In this tutorial, you'll create a scrollable list of country names that are read from a string array. When a list item is selected, a toast message will display the position of the item in the list.

- 1. Start a new project named HelloListView.
- 2. Create an XML file named list_item.xml and save it inside the res/layout/ folder. Insert the following:

```
<?xml version="1.0" encoding="utf-8"?>
<TextView xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="fill_parent"
    android:layout_height="fill_parent"
    android:padding="10dp"
    android:textSize="16sp" >
</TextView>
```

This file defines the layout for each item that will be placed in the <u>ListView</u>.

3. Open the HelloListView.java and make the class extend ListActivity (instead of Activity):

```
public class HelloListView extends ListActivity {
```

4. Insert the following code for the onCreate() method:

Notice that this does not load a layout file for the Activity (which you usually do with setContentView(int). Instead, setListAdapter(ListAdapter) automatically adds a ListView to fill the entire screen of the ListActivity. This method takes an ArrayAdapter, which manages the array of list items that will be placed into the ListView. The ArrayAdapter constructor takes the application Context, the layout description for each list item (created in the previous step), and a ListView (defined next).

The <u>setTextFilterEnabled(boolean)</u> method turns on text filtering for the <u>ListView</u>, so that when the user

begins typing, the list will be filtered.

The <u>setOnItemClickListener(OnItemClickListener)</u> method defines the on-click listener for each item. When an item in the <u>ListView</u> is clicked, the <u>onItemClick()</u> method is called and a <u>Toast</u> message is displayed, using the text from the clicked item.

Tip: You can use list item designs provided by the platform instead of defining your own layout file for the ListAdapter. For example, try using android.R.layout.simple_list_item_1 instead of R.layout.list_item.

5. After the onCreate() method, add the string array:

```
static final String[] COUNTRIES = new String[] {
    "Afghanistan", "Albania", "Algeria", "American Samoa", "Andorra", "Angola", "Anguilla", "Antarctica", "Antigua and Barbuda", "Argentina",
    "Armenia", "Aruba", "Australia", "Austria", "Azerbaijan", "Bahrain", "Bangladesh", "Barbados", "Belarus", "Belgium",
    "Belize", "Benin", "Bermuda", "Bhutan", "Bolivia",
    "Bosnia and Herzegovina", "Botswana", "Bouvet Island", "Brazil", "British
Indian Ocean Territory",
    "British Virgin Islands", "Brunei", "Bulgaria", "Burkina Faso", "Burundi",
    "Cote d'Ivoire", "Cambodia", "Cameroon", "Canada", "Cape Verde",
    "Cayman Islands", "Central African Republic", "Chad", "Chile", "China",
    "Christmas Island", "Cocos (Keeling) Islands", "Colombia", "Comoros",
    "Cook Islands", "Costa Rica", "Croatia", "Cuba", "Cyprus", "Czech
Republic",
    "Democratic Republic of the Congo", "Denmark", "Djibouti", "Dominica",
"Dominican Republic",
    "East Timor", "Ecuador", "Egypt", "El Salvador", "Equatorial Guinea",
"Eritrea",
    "Estonia", "Ethiopia", "Faeroe Islands", "Falkland Islands", "Fiji",
"Finland",
    "Former Yugoslav Republic of Macedonia", "France", "French Guiana", "French
    "French Southern Territories", "Gabon", "Georgia", "Germany", "Ghana",
"Gibraltar"
    "Greece", "Greenland", "Grenada", "Guadeloupe", "Guam", "Guatemala",
"Guinea", "Guinea-Bissau",
    "Guyana", "Haiti", "Heard Island and McDonald Islands", "Honduras", "Hong
Kong", "Hungary",
    "Iceland", "India", "Indonesia", "Iran", "Iraq", "Ireland", "Israel",
"Italy", "Jamaica",
    "Japan", "Jordan", "Kazakhstan", "Kenya", "Kiribati", "Kuwait",
"Kyrgyzstan", "Laos",
    "Latvia", "Lebanon", "Lesotho", "Liberia", "Libya", "Liechtenstein",
             "Luxembourg",
"Lithuania", "Luxembourg",
"Macau", "Madagascar", "Malawi", "Malaysia", "Maldives", "Mali", "Malta",
"Marshall Islands",
    "Martinique", "Mauritania", "Mauritius", "Mayotte", "Mexico", "Micronesia",
"Moldova",
    "Monaco", "Mongolia", "Montserrat", "Morocco", "Mozambique", "Myanmar",
"Namibia",
    "Nauru", "Nepal", "Netherlands", "Netherlands Antilles", "New Caledonia",
"New Zealand",
    "Nicaragua", "Niger", "Nigeria", "Niue", "Norfolk Island", "North Korea",
"Northern Marianas",
    "Norway", "Oman", "Pakistan", "Palau", "Panama", "Papua New Guinea",
"Paraguay", "Peru",
    "Philippines", "Pitcairn Islands", "Poland", "Portugal", "Puerto Rico",
    "Reunion", "Romania", "Russia", "Rwanda", "Sqo Tome and Principe", "Saint
```

```
Helena",
    "Saint Kitts and Nevis", "Saint Lucia", "Saint Pierre and Miquelon",
    "Saint Vincent and the Grenadines", "Samoa", "San Marino", "Saudi Arabia",
"Senegal",
    "Seychelles", "Sierra Leone", "Singapore", "Slovakia", "Slovenia", "Solomon
Islands",
    "Somalia", "South Africa", "South Georgia and the South Sandwich Islands",
"South Korea",
    "Spain", "Sri Lanka", "Sudan", "Suriname", "Svalbard and Jan Mayen",
"Swaziland", "Sweden",
    "Switzerland", "Syria", "Taiwan", "Tajikistan", "Tanzania", "Thailand",
"The Bahamas",
    "The Gambia", "Togo", "Tokelau", "Tonga", "Trinidad and Tobago", "Tunisia",
"Turkey",
    "Turkmenistan", "Turks and Caicos Islands", "Tuvalu", "Virgin Islands",
"Uganda",
    "Ukraine", "United Arab Emirates", "United Kingdom",
    "United States", "United States Minor Outlying Islands", "Uruguay",
"Uzbekistan",
    "Vanuatu", "Vatican City", "Venezuela", "Vietnam", "Wallis and Futuna",
"Western Sahara",
    "Yemen", "Yugoslavia", "Zambia", "Zimbabwe"
```

This is the array of strings that will be placed into the <u>ListView</u>.

6. Run the application.

You can scroll the list, or type to filter it, then click an item to see a message. You should see something like this:



Note that using a hard-coded string array is not the best design practice. One is used in this tutorial for simplicity, in order to demonstrate the <u>ListView</u> widget. The better practice is to reference a string array defined by an external resource, such as with a <string-array> resource in your project res/values/strings.xml file. For example:

To use these resource strings for the <u>ArrayAdapter</u>, replace the original <u>setListAdapter(ListAdapter)</u> line with the following:

```
String[] countries = getResources().getStringArray(R.array.countries_array);
setListAdapter(new ArrayAdapter<String>(this, R.layout.list_item, countries));
```

References

- <u>ListView</u>
- <u>ListAdapter</u>

<u>← Back to Hello, Views</u> <u>↑ Go to top</u>

Except as noted, this content is licensed under <u>Creative Commons Attribution 2.5</u>. For details and restrictions, see the <u>Content License</u>.

Site Terms of Service - Privacy Policy - Brand Guidelines