

From Logistic Regression to Neural Networks (Part 1)

CS114B Lab 4

Kenneth Lai

February 26, 2021

Logistic Regression

- ▶ Documents are characterized by features

Logistic Regression

- ▶ Documents are characterized by features
 - ▶ No independence assumptions

Logistic Regression

- ▶ Documents are characterized by features
 - ▶ No independence assumptions
- ▶ For each feature j :
 - ▶ Value x_j
 - ▶ Weight w_j

Logistic Regression

- ▶ Documents are characterized by features
 - ▶ No independence assumptions
- ▶ For each feature j :
 - ▶ Value x_j
 - ▶ Weight w_j
- ▶ Bias term b

Logistic Regression

- ▶ Documents are characterized by features
 - ▶ No independence assumptions
- ▶ For each feature j :
 - ▶ Value x_j
 - ▶ Weight w_j
- ▶ Bias term b

▶ “Score” (log-odds) $z = \left(\sum_{j=1}^n w_j x_j \right) + b = \mathbf{w} \cdot \mathbf{x} + b$


Logistic Regression

- ▶ Documents are characterized by features
 - ▶ No independence assumptions
- ▶ For each feature j :
 - ▶ Value x_j
 - ▶ Weight w_j
- ▶ Bias term b

- ▶ “Score” (log-odds) $z = \left(\sum_{j=1}^n w_j x_j \right) + b = \mathbf{w} \cdot \mathbf{x} + b$


- ▶ Logistic function $\sigma(z) = \frac{1}{1 + e^{-z}} = \hat{y}$

Graphical Representation of Logistic Regression




Graphical Representation of Logistic Regression

- Inputs (and dummy feature 1)




Graphical Representation of Logistic Regression

- Weights (and bias term)




Graphical Representation of Logistic Regression

► Sum function Σ




Graphical Representation of Logistic Regression

► “Score”




Graphical Representation of Logistic Regression

- Logistic function σ




Graphical Representation of Logistic Regression


► Output




Graphical Representation of Logistic Regression



Graphical Representation of Logistic Regression




Graphical Representation of Logistic Regression




Graphical Representation of Logistic Regression

- ▶ Output
- ▶ Inputs




Graphical Representation of Logistic Regression

- ▶ Output
- ▶ Inputs
- ▶ $\hat{y} = \sigma(\mathbf{x} \cdot \theta)$




Graphical Representation of Logistic Regression

- ▶ Output
- ▶ Inputs
- ▶ $\hat{y} = \sigma(\mathbf{x} \cdot \theta)$
 - ▶ We will assume that the dummy feature 1 is part of \mathbf{x}



Graphical Representation of Logistic Regression



- ▶ **Output**
- ▶ **Inputs**
- ▶ $\hat{y} = \sigma(\mathbf{x} \cdot \theta)$
 - ▶ We will assume that the dummy feature 1 is part of \mathbf{x}
 - ▶ Why $\mathbf{x} \cdot \theta$ (rather than $\theta \cdot \mathbf{x}$)?

(Mini-)Batch Training

- ▶ Let \mathbf{x} consist of the feature vectors $\mathbf{x}^{(i)}$ for each document i in the (mini-)batch of size m , stacked on top of each other

(Mini-)Batch Training

- ▶ Let \mathbf{x} consist of the feature vectors $\mathbf{x}^{(i)}$ for each document i in the (mini-)batch of size m , stacked on top of each other

$$\mathbf{x} \cdot \theta = \begin{bmatrix} x_1^{(1)} & \dots & x_n^{(1)} & 1 \\ \vdots & \ddots & \vdots & \vdots \\ x_1^{(m)} & \dots & x_n^{(m)} & 1 \end{bmatrix} \cdot \begin{bmatrix} w_1 \\ \vdots \\ w_n \\ b \end{bmatrix} = \begin{bmatrix} \mathbf{x}^{(1)} \cdot \mathbf{w} + b \\ \vdots \\ \mathbf{x}^{(m)} \cdot \mathbf{w} + b \end{bmatrix}$$

(Mini-)Batch Training

- ▶ Let \mathbf{x} consist of the feature vectors $\mathbf{x}^{(i)}$ for each document i in the (mini-)batch of size m , stacked on top of each other

$$\mathbf{x} \cdot \theta = \begin{bmatrix} x_1^{(1)} & \dots & x_n^{(1)} & 1 \\ \vdots & \ddots & \vdots & \vdots \\ x_1^{(m)} & \dots & x_n^{(m)} & 1 \end{bmatrix} \cdot \begin{bmatrix} w_1 \\ \vdots \\ w_n \\ b \end{bmatrix} = \begin{bmatrix} \mathbf{x}^{(1)} \cdot \mathbf{w} + b \\ \vdots \\ \mathbf{x}^{(m)} \cdot \mathbf{w} + b \end{bmatrix}$$

$$\sigma(\mathbf{x} \cdot \theta) = \begin{bmatrix} \sigma(\mathbf{x}^{(1)} \cdot \mathbf{w} + b) \\ \vdots \\ \sigma(\mathbf{x}^{(m)} \cdot \mathbf{w} + b) \end{bmatrix} = \begin{bmatrix} \hat{y}^{(1)} \\ \vdots \\ \hat{y}^{(m)} \end{bmatrix}$$

Gradients in Logistic Regression

- ▶ Cross-entropy loss $L_{CE}(\hat{y}, y) = -[y \log \hat{y} + (1 - y) \log(1 - \hat{y})]$

Gradients in Logistic Regression

- ▶ Cross-entropy loss $L_{CE}(\hat{y}, y) = -[y \log \hat{y} + (1 - y) \log(1 - \hat{y})]$
- ▶ We want to compute $\frac{\partial L}{\partial w_j}$

Gradients in Logistic Regression

- ▶ Cross-entropy loss $L_{CE}(\hat{y}, y) = -[y \log \hat{y} + (1 - y) \log(1 - \hat{y})]$
- ▶ We want to compute $\frac{\partial L}{\partial w_j}$
- ▶ Chain Rule of calculus: $\frac{dy}{dx} = \frac{dy}{dz} \frac{dz}{dx}$

Gradients in Logistic Regression

- ▶ Cross-entropy loss $L_{CE}(\hat{y}, y) = -[y \log \hat{y} + (1 - y) \log(1 - \hat{y})]$
- ▶ We want to compute $\frac{\partial L}{\partial w_j}$
- ▶ Chain Rule of calculus: $\frac{dy}{dx} = \frac{dy}{dz} \frac{dz}{dx}$
- ▶ Looking at the graph: $\frac{\partial L}{\partial w_j} = \frac{\partial L}{\partial \hat{y}} \frac{\partial \hat{y}}{\partial z} \frac{\partial z}{\partial w_j}$

Gradients in Logistic Regression

$$\blacktriangleright \frac{\partial L}{\partial w_j} = \frac{\partial L}{\partial \hat{y}} \frac{\partial \hat{y}}{\partial z} \frac{\partial z}{\partial w_j}$$

Gradients in Logistic Regression

$$\begin{aligned} \blacktriangleright \frac{\partial L}{\partial w_j} &= \frac{\partial L}{\partial \hat{y}} \frac{\partial \hat{y}}{\partial z} x_j \\ \blacktriangleright \frac{\partial z}{\partial w_j} &= x_j \end{aligned}$$

Gradients in Logistic Regression

- ▶ $\frac{\partial L}{\partial w_j} = \frac{\partial L}{\partial \hat{y}} \hat{y}(1 - \hat{y}) x_j$
 - ▶ $\frac{\partial z}{\partial w_j} = x_j$
 - ▶ For the logistic function: $\frac{\partial \hat{y}}{\partial z} = \hat{y}(1 - \hat{y})$

Gradients in Logistic Regression

- ▶ $\frac{\partial L}{\partial w_j} = \frac{\hat{y} - y}{\hat{y}(1 - \hat{y})} \hat{y}(1 - \hat{y}) x_j$
 - ▶ $\frac{\partial z}{\partial w_j} = x_j$
 - ▶ For the logistic function: $\frac{\partial \hat{y}}{\partial z} = \hat{y}(1 - \hat{y})$
 - ▶ For the cross-entropy loss: $\frac{\partial L}{\partial \hat{y}} = \frac{\hat{y} - y}{\hat{y}(1 - \hat{y})}$

Gradients in Logistic Regression

- ▶ $\frac{\partial L}{\partial w_j} = \frac{\hat{y} - y}{\hat{y}(1 - \hat{y})} \hat{y}(1 - \hat{y}) x_j = (\hat{y} - y) x_j$
 - ▶ $\frac{\partial z}{\partial w_j} = x_j$
 - ▶ For the logistic function: $\frac{\partial \hat{y}}{\partial z} = \hat{y}(1 - \hat{y})$
 - ▶ For the cross-entropy loss: $\frac{\partial L}{\partial \hat{y}} = \frac{\hat{y} - y}{\hat{y}(1 - \hat{y})}$

Gradients in Logistic Regression

- ▶ $\frac{\partial L}{\partial w_j} = \frac{\hat{y} - y}{\hat{y}(1 - \hat{y})} \hat{y}(1 - \hat{y}) x_j = (\hat{y} - y) x_j$
 - ▶ $\frac{\partial z}{\partial w_j} = x_j$
 - ▶ For the logistic function: $\frac{\partial \hat{y}}{\partial z} = \hat{y}(1 - \hat{y})$
 - ▶ For the cross-entropy loss: $\frac{\partial L}{\partial \hat{y}} = \frac{\hat{y} - y}{\hat{y}(1 - \hat{y})}$
- ▶ $\frac{\partial L}{\partial b} = \frac{\hat{y} - y}{\hat{y}(1 - \hat{y})} \hat{y}(1 - \hat{y})(1) = \hat{y} - y$
 - ▶ $\frac{\partial z}{\partial b} = 1$
 - ▶ ...

Gradients in Logistic Regression

- ▶ Let m be the number of documents in the (mini-)batch

Gradients in Logistic Regression

- ▶ Let m be the number of documents in the (mini-)batch
- ▶ In vector form: $\nabla L = \frac{1}{m} \left(\mathbf{x}^T \cdot (\hat{\mathbf{y}} - \mathbf{y}) \right)$

Gradients in Logistic Regression

- ▶ Let m be the number of documents in the (mini-)batch
- ▶ In vector form: $\nabla L = \frac{1}{m} \left(\mathbf{x}^T \cdot (\hat{\mathbf{y}} - \mathbf{y}) \right)$
 - ▶ What is $\mathbf{x}^T \cdot (\hat{\mathbf{y}} - \mathbf{y})$?

Gradients in Logistic Regression

$$\begin{bmatrix} x_1^{(1)} & \dots & x_1^{(m)} \\ \vdots & \ddots & \vdots \\ x_n^{(1)} & \dots & x_n^{(m)} \\ 1 & 1 & 1 \end{bmatrix} \cdot \begin{bmatrix} \hat{y}^{(1)} - y^{(1)} \\ \vdots \\ \hat{y}^{(m)} - y^{(m)} \end{bmatrix} = \begin{bmatrix} \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) x_1^{(i)} \\ \vdots \\ \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) x_n^{(i)} \\ \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) \end{bmatrix}$$

Gradients in Logistic Regression

$$\begin{bmatrix} x_1^{(1)} & \dots & x_1^{(m)} \\ \vdots & \ddots & \vdots \\ x_n^{(1)} & \dots & x_n^{(m)} \\ 1 & 1 & 1 \end{bmatrix} \cdot \begin{bmatrix} \hat{y}^{(1)} - y^{(1)} \\ \vdots \\ \hat{y}^{(m)} - y^{(m)} \end{bmatrix} = \begin{bmatrix} \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) x_1^{(i)} \\ \vdots \\ \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) x_n^{(i)} \\ \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) \end{bmatrix}$$
$$= \begin{bmatrix} \sum_{i=1}^m \left(\frac{\partial L}{\partial w_1} \right)^{(i)} \\ \vdots \\ \sum_{i=1}^m \left(\frac{\partial L}{\partial w_n} \right)^{(i)} \\ \sum_{i=1}^m \left(\frac{\partial L}{\partial b} \right)^{(i)} \end{bmatrix}$$

Gradients in Logistic Regression

$$\begin{aligned} \begin{bmatrix} x_1^{(1)} & \dots & x_1^{(m)} \\ \vdots & \ddots & \vdots \\ x_n^{(1)} & \dots & x_n^{(m)} \\ 1 & 1 & 1 \end{bmatrix} \cdot \begin{bmatrix} \hat{y}^{(1)} - y^{(1)} \\ \vdots \\ \hat{y}^{(m)} - y^{(m)} \end{bmatrix} &= \begin{bmatrix} \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) x_1^{(i)} \\ \vdots \\ \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) x_n^{(i)} \\ \sum_{i=1}^m (\hat{y}^{(i)} - y^{(i)}) \end{bmatrix} \\ &= \begin{bmatrix} \sum_{i=1}^m \left(\frac{\partial L}{\partial w_1} \right)^{(i)} \\ \vdots \\ \sum_{i=1}^m \left(\frac{\partial L}{\partial w_n} \right)^{(i)} \\ \sum_{i=1}^m \left(\frac{\partial L}{\partial b} \right)^{(i)} \end{bmatrix} \\ &= \sum_{i=1}^m (\nabla L)^{(i)} \end{aligned}$$

Gradients in Logistic Regression

- ▶ Let m be the number of documents in the (mini-)batch
- ▶ In vector form: $\nabla L = \frac{1}{m} \left(\mathbf{x}^T \cdot (\hat{\mathbf{y}} - \mathbf{y}) \right)$
 - ▶ What is $\mathbf{x}^T \cdot (\hat{\mathbf{y}} - \mathbf{y})$?
 - ▶ It computes the sum of the gradients for each document i in the mini-batch!

Gradients in Logistic Regression

- ▶ Let m be the number of documents in the (mini-)batch
- ▶ In vector form: $\nabla L = \frac{1}{m} \left(\mathbf{x}^T \cdot (\hat{\mathbf{y}} - \mathbf{y}) \right)$
 - ▶ What is $\mathbf{x}^T \cdot (\hat{\mathbf{y}} - \mathbf{y})$?
 - ▶ It computes the sum of the gradients for each document i in the mini-batch!
 - ▶ Then to get the average gradient, we just divide by m

Gradient Descent

- ▶ Initialize parameters $\theta = \mathbf{w}, b$ (randomly or $\mathbf{0}$)

Gradient Descent

- ▶ Initialize parameters $\theta = \mathbf{w}, b$ (randomly or $\mathbf{0}$)
- ▶ At each time step t :

Gradient Descent

- ▶ Initialize parameters $\theta = \mathbf{w}, b$ (randomly or $\mathbf{0}$)
- ▶ At each time step t :
 - ▶ Compute gradient ∇L

Gradient Descent

- ▶ Initialize parameters $\theta = \mathbf{w}, b$ (randomly or $\mathbf{0}$)
- ▶ At each time step t :
 - ▶ Compute gradient ∇L
 - ▶ Move in direction of negative gradient

Gradient Descent

- ▶ Initialize parameters $\theta = \mathbf{w}, b$ (randomly or $\mathbf{0}$)
- ▶ At each time step t :
 - ▶ Compute gradient ∇L
 - ▶ Move in direction of negative gradient
- ▶ $\theta_{t+1} = \theta_t - \eta \nabla L$

Gradient Descent

- ▶ Initialize parameters $\theta = \mathbf{w}, b$ (randomly or $\mathbf{0}$)
- ▶ At each time step t :
 - ▶ Compute gradient ∇L
 - ▶ Move in direction of negative gradient
- ▶ $\theta_{t+1} = \theta_t - \eta \nabla L$
- ▶ Because L is convex, we eventually reach a global minimum