

(19)



(11)

**EP 2 920 405 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**17.06.2020 Bulletin 2020/25**

(51) Int Cl.:  
**E21B 23/14** <sup>(2006.01)</sup> **E21B 47/00** <sup>(2012.01)</sup>  
**F16L 55/00** <sup>(2006.01)</sup> **F16L 55/18** <sup>(2006.01)</sup>

(21) Application number: **13855569.3**

(86) International application number:  
**PCT/NZ2013/000210**

(22) Date of filing: **15.11.2013**

(87) International publication number:  
**WO 2014/077707 (22.05.2014 Gazette 2014/21)**

**(54) SENSOR TRANSPORTATION APPARATUS AND GUIDE DEVICE**

SENSORTRANSPORTVORRICHTUNG UND FÜHRUNGSVORRICHTUNG

APPAREIL DE TRANSPORT DE CAPTEUR ET DISPOSITIF DE GUIDAGE

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR**

(30) Priority: **16.11.2012 NZ 60366212**  
**16.11.2012 NZ 60366012**  
**06.08.2013 NZ 61398613**

(43) Date of publication of application:  
**23.09.2015 Bulletin 2015/39**

(73) Proprietor: **Petromac IP Limited**  
**Epsom, Auckland 1023 (NZ)**

(72) Inventor: **MCCORMICK, Stephen, Peter**  
**Beachlands, Auckland 2018 (NZ)**

(74) Representative: **Worthington, Richard Easton et al**  
**Withers & Rogers LLP**  
**4 More London Riverside**  
**London SE1 2AU (GB)**

(56) References cited:  
**WO-A1-01/40615 WO-A1-94/05941**  
**WO-A1-99/53172 WO-A1-2013/067255**  
**CN-Y- 2 864 066 FR-A1- 2 898 635**  
**US-A- 3 603 264 US-A- 5 111 891**  
**US-A- 5 111 891 US-A- 5 322 391**  
**US-A1- 2003 075 321 US-A1- 2009 145 596**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 2 920 405 B1**

## Description

### Technical Field

[0001] This invention relates to apparatus and methods for use in transporting sensor equipment, and in particular to apparatus and methods for use in wireline logging applications.

### Background art

[0002] Hydrocarbon exploration and development activities rely on information derived from sensors which capture data relating to the geological properties of an area under exploration. One approach used to acquire this data is through wireline logging. Wireline logging is typically performed in a wellbore immediately after a new section of hole has been drilled. These wellbores are drilled to a target depth covering a zone of interest, typically between 1000 - 5000 meters deep. A sensor package, also known as a "logging tool" or "tool-string" is then lowered into the wellbore and descends under gravity to the target depth of the wellbore well. The logging tool is lowered on a wireline - being a collection of electrical communication wires which are sheathed in a steel cable connected to the logging tool. Once the logging tool reaches the target depth it is then drawn back up through the wellbore at a controlled rate of ascent, with the sensors in the logging tool operating to generate and capture geological data.

[0003] There is a wide range of logging tools which are designed to measure various physical properties of the rocks and fluids contained within the rocks. The logging tools include transducers and sensors to measure properties such as electrical resistance, gamma-ray density, speed of sound and so forth. The individual logging tools are often combinable and are typically connected together to form a logging tool-string. These instruments are relatively specialised sensors, which in some cases need to be electrically isolated or located remote from metallic objects which are a source of noise in the data generated. Some sensors are designed to make close contact with the borehole wall during data acquisition whilst others are ideally centred in the wellbore for optimal results. These requirements need to be accommodated with any device that is attached to the tool-string.

[0004] The drilling of wells and the wireline logging operation is an expensive undertaking. This is primarily due to the capital costs of the drilling equipment and the specialised nature of the wireline logging systems. It is important for these activities to be undertaken and completed as promptly as possible to minimise these costs. Delays in deploying a wireline logging tool are to be avoided wherever possible.

[0005] One cause of such delays is the difficulties in lowering wireline logging tools down to the target depth of the wellbore. As the logging tool is lowered by cable down the wellbore by gravity alone, an operator at the

top of the well has very little control of the descent of the logging tool. Logging tools can become held up on ledges of rock formed inside a well - usually found at the boundaries of hard rock layers where the adjacent rock layer crumbles. An operator may not immediately identify that a logging tool has become stuck on a ledge, and may also spend a significant amount of time reeling the cable and tool-string back in and attempting to move it past the obstruction formed by a ledge.

[0006] The chances of a wireline logging tools getting stuck or being impeded is also significantly increased with deviated wells. Deviated wells do not run straight vertically downwards and instead extend downward at an angle. Multiple deviated wells are usually drilled from a single surface location to allow a large area of interest to be explored. As wireline logging tools are run down a wellbore with a cable under the action of gravity, the tool-string will traverse the low side or bottom of the wellbore wall and immediately encounter any obstructions on the wellbore wall as it travels downwards to the target depth. Furthermore, in deviated wells there is the potential for drilling cuttings to collect on the low side of the wellbore. Rock cuttings are more difficult to remove when the wellbore is deviated. The logging tool has to travel over or through these drilling cuttings, which can impede its progress and also collect in front of the logging tool. In some cases the logging tool may not be able to plough through the cuttings to reach the bottom of the wellbore. Furthermore, as hole deviation increases, the sliding friction can prevent the logging tool descending. The practical limit is around 50-60° from the vertical, and in these high angle wells any device that can reduce friction is very valuable. The running of the tool-string over the low side surface of the borehole also needs to be taken into account in the design of the tool-string, and in particular the housing and the containment of its sensitive sensors and transducers.

[0007] Attempts have been made to address these issues in the deployment of wireline logging tools, as disclosed in US patents 7866384, 7395881 and US patent application 20120061098. These patent specifications describe a number of different forms of in-line roller devices integrated into the logging tool-string. These devices aim to reduce the friction experienced by a tool-string as it is run along the low side slope of a deviated wellbore.

[0008] This in-line positioning of roller devices increases the potential to cause damage to the logging tools as there are additional O-rings connections required that could potentially leak. Furthermore, there are multiple additional electrical connections that need to be made between the individual logging tools making up the logging tool-string. The additional components and tool-string length means it takes longer to connect and disconnect the tool-string, which slows down the wireline logging operation and therefore increases well costs. Further, there is a lack of flexibility inherent in this approach as in-line roller devices can only be placed between logging tools, and as some of these tools are quite

long, in-line rollers may not keep the entire tool body off the borehole wall.

[0009] The rollers employed in these forms of prior art devices also have relatively small wheels with a minimal clearances. In deviated wellbores well drilling cuttings will collect on the low side of the well, and these small sets of rollers can struggle to make headway through piles of cuttings. In situations where large amounts of cuttings are encountered these small rollers can be of no assistance at all and simply add to the length and weight of an already unwieldy tool.

[0010] McNay patent US8011429 and Schumberger patent application US2013248208 describe roller assemblies which slip over the logging tool, and are mounted such that they are free to rotate about the longitudinal axis of the tool. These devices have relatively small wheels which do not rotate easily over rough surfaces. In addition, it is often the central or side part of the wheel which is in contact with the wellbore wall, rather than the circumferential or radially extreme edge. This means that the wheels are often skidding rather than rotating. Neither of these devices has an active lubrication system which can prevent contaminants from entering and jamming the bearings.

[0011] All of these existing prior art devices attempt to assist a tool-string in travelling down a deviated wellbore. However, the devices do not assist in maintaining a known orientation of the tool-string, or a specific clearance or "standoff" between the active part of the tool-string and the wellbore wall.

[0012] FR2898635 describes a shuttle or traction module for transporting a sensor down a cased well bore. The traction module has a radially deployable arm. The arm is deployable between a flattened position in which the arm and a roller at the distal end of the arm are retracted into a body of the traction module, and an extended position in which the roller is held against the wall of the well bore opposite to the point of contact between driven wheels of the traction module. The arm and roller ensure the driven wheels are pressed against the wellbore to remain in contact with the well bore.

[0013] US 684732 describes a sectional threading rod which is provided with wheels to reduce friction as the rod is pushed down a conduit. The wheels have an axle which is above the centre of the rod. However, the rod is not intended for use with a logging tool.

[0014] Other attempts to address the issues associated with deviated wellbores include a number of prior art "hole finding" devices. For example US patent US4474235, US patent application US 20120061098, PCT publication WO 2010/106312 and US patent application US20120222857 all describe systems for wireline hole finding devices which rely on one or more rollers located at the nose at the bottom of a tool-string. The nose is the leading end at the bottom of the tool-string during descent of the wellbore. These rollers are arranged to allow the nose of the tool-string to roll into, and then up and over, irregularities and obstructions in a well-

bore.

[0015] However due to the use of a number of metallic components these types of hole finding devices are not necessarily compatible with induction type resistivity tools which are generally the most commonly used sensor in such applications. Also, some logging tools are "bottom only", and have sensors which must be located at the lower extremity of the tool-string. The prior art hole finders are heavy and metallic and hence not compatible with such tools.

[0016] Furthermore, these systems are relatively complicated and must be appropriately designed and maintained to withstand the hostile environment experienced at depth in exploration wells. If the moving parts used in these systems cease to function the hole finder is ineffective. These designs are also relatively heavy and inflexible. Any impact forces or torque acting on the hole finder are transmitted into the tool-string, potentially causing damage to the sensors.

[0017] Another approach used in the design of hole finding devices is disclosed in US patent application US 20090145596. This patent specification describes an alternative hole finding system employed outside of wireline applications where a conduit, tubing or pipe is attached to the sensor tool in order to push it down the wellbore. This specification discloses a relatively complicated system which requires a surface operator to actively adjust the orientation of a nose assembly mounted at the bottom of the tool. The specification also discloses that this device requires a range of sensors that are used to detect sensor tool movement, and specifically if the sensor tool is held up. This form of hole finding system is again relatively heavy and complex. Furthermore, a dedicated operator is also required to monitor the progress of the sensor tool to actively adjust the orientation and angle of attack of the adjustable nose assembly when the sensors detect that the sensor device is held up as it moves down the wellbore. A similar design is described in US patent US7757782. This device is also an active system which requires manipulation from an operator at the surface to change the nose angle and azimuth in order in order to navigate past obstacles after the logging tool is obstructed.

[0018] It would therefore be of advantage to have an improved guide device which addressed any or all of the above issues. In particular, it would be of advantage to have an improved guide device which avoided obstacles - as opposed to having to negotiate obstacles. It would also be of advantage to have an improved guide device that did not require monitoring and active manipulation as the logging tool descends the wellbore. An improved guide device formed from a minimum number of metallic or conductive components, which includes no moving parts, which is easy to maintain and manufacture and which is lightweight and simple would be of advantage over the prior art. Furthermore it would also be of advantage to have an improved guide device which, if lost in an exploration well, could be drilled through to remove it

as an obstruction.

[0019] It would also be of advantage to have an improved sensor transportation apparatus which addressed any or all of the above issues or at least provided an alternative choice. In particular, a sensor transportation apparatus which reduced the friction experienced by a wireline logging tool during deployment down a deviated well would be of advantage. An improved sensor transportation apparatus which could also be used to orient a tool-string would also be of advantage. Furthermore it would also be of advantage to have improvements which coped with the build-up or collection of drilling cuttings in deviated wells and/or which addressed the problems inherent in prior art in-line roller systems.

#### Disclosure of Invention

[0020] According to one aspect of the present invention there is provided a sensor transportation apparatus according to claim 1.

[0021] According to a further aspect of the present invention there is provided a sensor transportation apparatus and a guide device according to claim 12.

[0022] According to a further aspect of the present invention, there is provided an elongate sensor assembly and a sensor transportation device according to claim 13.

[0023] According to a further aspect of the present invention, there is provided tool string according to claim 14.

[0024] Further aspects of the invention, which should be considered in all its novel aspects, will become apparent from the following description given by way of example of possible embodiments of the invention.

#### Brief description of the drawings

[0025] An example embodiment of the invention is now discussed with reference to the drawings in which:

Figure 1 shows a isometric view of a sensor transportation apparatus as configured in accordance with a preferred embodiment of the invention.

Figure 2 shows a side view of the transportation apparatus of figure 1

Figure 3 shows a top view of the transportation apparatus of figures 1 and 2.

Figure 4 shows a cross-section along plane A-A of the transportation apparatus of figures 1-3, and shows the integral lubrication delivery apparatus. The wellbore wall is shown in outline.

Figure 5 shows a cross-section of an alternative embodiment along plane A-A. The wellbore wall is shown in outline.

Figure 6a shows a front view of a transportation apparatus provided in accordance with an alternative configuration to that shown in figures 1 - 5, with the wellbore shown outline.

Figure 6b shows a perspective view of the transportation apparatus of Figure 6a.

Figure 7 shows a perspective view of a wireline tool-string engaged with both the transportation apparatus illustrated in respect to figure 6a and 6b in addition to the apparatus shown with respect to figures 1-4.

Figure 8 shows an isometric view of a further embodiment of the transportation apparatus.

Figure 9 shows a cross-section view of the embodiment shown in Figure 8.

Figure 10 shows a side view of a guide device.

Figure 11 shows a front perspective view of the guide device of Figure 10.

Figure 12 shows a rear perspective view of the guide device of Figure 10.

Figure 13 shows an exploded side view of another guide device.

Figure 14 shows an exploded perspective view of the guide device of Figure 13.

Figure 15 shows an isometric view of a base for a guide device.

Figure 16 shows a perspective view of an adjustable guide device set to a 3° angle.

Figure 17 shows the adjustable guide device of Figure 16 set to an 8° angle.

Figure 18 shows the adjustable guide device of Figure 16 set to a 15° angle.

Figure 19 shows exploded perspective view of another adjustable guide device.

Figure 20 shows an isometric view of an orientation structure which is provided with low friction skids.

Figure 21 shows an isometric view of another orientation structure which is provided with low friction skids.

Figure 22 shows an isometric view of another orientation structure which is provided with low friction

skids.

Figure 23 shows an isometric view of another orientation structure which is provided with low friction skids.

Figure 24 shows a transverse cross-section of another orientation structure which is provided with low friction skids.

Figure 25 shows a transverse cross-section of another orientation structure which is provided with low friction skids.

Figure 26 shows a transverse cross-section of another orientation structure which is provided with low friction skids.

Figure 27 shows a transverse cross-section of another orientation structure which is provided with low friction skids.

Figure 28 shows a perspective view of a guide device and orientation structure mounted to a wireline logging tool-string.

Figure 29 shows a perspective view of the guide device of Figure 28 in combination with an alternative orientation structure which is provided with low friction skids, mounted to a wireline logging tool-string.

Figure 30 a perspective view of the guide device of Figure 28 in combination with two orientation structures which are provided with low friction skids mounted to a wireline logging tool-string.

Figure 31 a perspective view of the guide device of Figure 28 in combination with transportation apparatus mounted to a wireline logging tool-string.

Figure 32 shows a perspective view of a weight bar attached to a guide device according to Figure 19 and three transport apparatus according to Figure 41.

Figure 33 shows a perspective view of a guide device according to Figure 19 attached to a wireline tool-string, with a bowspring orientation structure.

Figure 34 shows a perspective view of another guide device.

Figure 35 shows a perspective view of a lubrication delivery apparatus.

Figure 36 shows a side cross-section view of the lubrication delivery apparatus of Figure 35 prior to charging with lubricant.

Figure 37 shows a side cross-section view of the lubrication delivery apparatus of Figure 35 after charging with lubricant

Figure 38 illustrates the pressures experienced by the lubrication delivery apparatus of figures 35, 36 and 37 when used in a particular instance, and

Figure 39 shows a transverse cross-section of a transportation apparatus with an integral lubrication delivery apparatus, with one ball bearing assembly mounted wheel shown and the opposite wheel and bearing removed.

Figure 40 shows a perspective view of the transportation apparatus of Figure 39 with the opposite wheel and bearing shown in partially exploded form.

Figure 41 shows a perspective view of the transportation apparatus in another embodiment.

Figure 42 shows a transverse cross-section of the transportation apparatus of Figure 41 provided with a modified lubrication delivery system, plain bearings and separate stub axles.

Figure 43 shows an isometric view of a transport apparatus configured as a tractor unit, with the jockey wheel in a raised position.

Figure 44 shows a front view of the tractor unit of Figure 43 in use in a wellbore, with a lower portion of the jockey wheel shown in hidden detail.

Figure 45 shows a front view of the tractor unit of Figure 43 in use in a wellbore with the jockey wheel in a lowered position, and with a lower portion of the jockey wheel shown in hidden detail.

Figure 46 shows a perspective view of another orientation structure.

Figure 47 shows a transverse cross-section of the orientation structure of Figure 46, shown in use in a wellbore (wellbore shown in hidden detail).

Figure 48 shows a perspective view of a guide device and orientation structure mounted to a wireline logging tool-string which has a sampling tool on its upper surface.

Figure 49 shows the same wireline logging tool-string as Figure 48, but with wheeled transportation providing the orientation.

#### Best modes for carrying out the Invention

[0026] Figures 1 - 4 show a number of views of the

transportation apparatus 1 as provided. In this embodiment the transportation apparatus is arranged to connect over or on to the exterior surface of an elongate sensor assembly- shown in cross-section in Figure 4 as a tool-string 2 used in a wireline logging applications. Figure 4 also illustrates the position of the longitudinal axis 2a of the tool-string 2. As used herein the phrase "elongate sensor assembly" includes both the sensors themselves, and any equipment attached to the sensors such as weights, spacers, flexible couplings, positioning devices and the like.

[0027] Figure 4 illustrates the perimeter walls of a wellbore 3 which the tool-string 2 is to be conveyed down by the transportation apparatus 1. For the sake of convenience the wellbore 3 is shown with a substantially horizontal orientation, with its low side 3a shown at the bottom of the page. The transportation apparatus 1 includes the main body 4, used to mount and locate the remaining elements or components of the apparatus.

[0028] Figures 1 through 3 show details of a pair of engagement structures formed in this embodiment by integral locking collars 5. These locking collars 5 are located at either end of the apparatus 1. Each collar 5 is arranged to partially enclose the exterior side wall surface of the tool-string 2, allowing the transportation apparatus to be slid on and over the tool-string at any desired position along the length of the tool-string. Each collar includes a series of threaded holes 5a arranged to receive a screw which engages with a recess or blind hole in the exterior surface of the tool-string. These threaded holes 5a and an associated set of screws are used to lock the apparatus 1 to the tool-string 2 with a specific orientation. By arranging the collars 5 to only partially enclose the tool-string 2, the tool-string can be carried in a lower position than would be possible if the collars 5 were to completely encircle the circumference of the tool-string 2.

[0029] The main body of each of these collars also defines or forms a protection structure 14 which protects wheels deployed on either side of the body from impact and abrasion. These protection structures also serve to orientate the carriage and tool-string assembly in the wellbore. These protection structures can also prevent the space between the wheel and tool-string 2 catching on wellbore projections, such as the casing shoe, as the tool-string 2 is pulled up and out of the wellbore. As can be seen from at least Figure 1 these protection structures may incorporate an angled surface projection 13 which can act to position the sensor assembly and transportation apparatus in the wellbore and guide the tool down the wellbore.

[0030] Figures 1 through 4 also show the provision of a pair of wheels 6 which form part of the transportation apparatus 1. These wheels 6 are deployed laterally adjacent to one another on opposite sides of a tool-string. In the embodiment shown each wheel rotates on a stub axle 7. The wheels 6 have an axis of rotation which is perpendicular to a longitudinal axis of the elongate sensor assembly. In the embodiment shown, the wheels

have a common axis of rotation.

[0031] As can be seen from these figures each wheel 6 has a diameter substantially greater than one of the diameter, width or height of the tool-string 2. This allows each of the wheels 6 to make radial contact with the wall of the wellbore 3 (that is, the radial edge of the wheels makes contact with the wellbore wall). The large relative size of each wheel 6 lifts the tool-string 2 from the low side surface of the wellbore 3, allowing the transportation apparatus 1 to convey the tool-string 2 down the wellbore 3. These large wheels allow the transportation apparatus 1 to roll along rugose borehole walls, up and over obstructing ledges which would normally impede the progress of the wireline logging tool-string 2. The wheels are widely spaced in the wellbore with a broad wheel track which allows the wheels to bridge over obstructing wellbore cuttings which tend to sit on the low side of the hole 3a. In preferred embodiments the wheels 6 extend below the main body 4 and below the sensor engaged with the apparatus, and thereby create a minimum clear space of at least 10mm, more preferably at least 12.7 mm (1/2 inch), between the tool string 2 (and the body) and the bottom of the wellbore.

[0032] Figure 4 shows a cross-section view of the transportation apparatus of Figures 1 - 3 along the plane A-A shown in Figure 2 and 3. Figure 5 shows similar view to Figure 4 of a cross-section view of the transportation apparatus provided in a further embodiment. In the embodiment shown with respect to Figure 4 a double set of ball bearing assemblies 10 are used, whereas in Figure 5 the wheels rotate over a set of bushes 110.

[0033] Figures 4 and 5 show the positioning and arrangements of the axis of rotation of each wheel 6 as provided by stub axles 7. As can also be seen from these figures each of these stub axles 7 is located above the longitudinal axis 2a of the tool-string 2. The longitudinal axis is essentially the axial or longitudinal centre of mass of the tool-string. As the tool-string 2 is much heavier than the transportation apparatus 1 the tool-string 2 will tend to rotate into the orientation shown in Figure 4 where the transportation apparatus sits squarely on both wheels.

[0034] Identified on these figures is the rotational centre 15 of the transportation apparatus and the centroid 2a or centre of mass of the tool-string. In the embodiment shown each section of the tool-string has a centre of mass 2a approximately in the middle of the circular section of the tool-string. The rotational centre 15 of the transportation apparatus is located above the centroidal axis 2a of the tool-string. The centroidal axis of the tool-string, as that phrase is used herein, is formed by the line joining the centre of mass of each cross-section along the length of the tool-string. The axis of rotation of the wheels 6 preferably passes through the rotational centre 15.

[0035] The body 4 also mounts an orientation structure comprising at least one orientation projection 8. As can be seen from Figure 4 the orientation projection 8 assists in providing the tool-string 2 with a predictable orientation

within the wellbore 3. If the tool-string 2 were to rotate to place the orientation projection 8 in contact with the low side of the wellbore 3 this would make the position of the combined transportation apparatus and connected tool-string 2 unstable. The orientation projection 8 therefore assists in positioning and orientating the tool-string in the arrangement shown in respect of Figure 4. The radially extreme edges of the wheels 6 and the protection structure 14 also form part of the orientation structure and assist in orientating the tool-string in the orientation shown in respect of Figure 4.

[0036] Figure 4 and 5 also show the form provided through a cross-section of the transportation apparatus made through all of its orientation projections 8, protection structures 14 and wheels 6. This form has a transverse outline (that is an outline or silhouette when viewed along the longitudinal axis of the sensor assembly) which has a rotational centre 15. The position of this rotational centre is the point which experiences the minimum vertical displacement when the form is rolled over a flat horizontal surface. In preferred embodiments the extremities of the orientation structure lie on a substantially circular imaginary curve centred on the rotational centre 15. The rotational centre of the transportation apparatus is offset from the centroid or centre of mass of the tool-string 2a.

[0037] The offset between the rotational centre of the transportation device and centre of mass of the tool-string ensures the assembly is orientated in the most stable position with the tool-string centre of mass below the rotational centre of the transportation apparatus. In this stable position the tool-string descends down the wellbore carried on the wheels of the transportation apparatus.

[0038] Referring in particular to Figure 4, in this embodiment the rotation of each wheel 6 is lubricated by a pressurised lubrication system 9 as it rotates about a double set of ball bearing assemblies 10. Figure 5 shows an alternative arrangement of the transportation apparatus where the lubrication system 9 acts on a set of bushes 110. This lubrication system 9 includes a lubricant reservoir 11 and pressurising plunger linked to the bearings 10 or bushes 110 by a pair of channels 12. In other embodiments the plunger may be replaced by a set of elastomer bellows, or by an elastic diaphragm, as is described further below. The plunger is maintained at a higher pressure than the surrounding wellbore fluids thereby force feeding lubricant to the wheel bearing or bush surfaces via the channels 12. Pressurisation of lubricant at this point in the apparatus prevents the entry of exterior contaminants from the wellbore 3.

[0039] Figures 6a and 6b show cross-section and isometric views of a transportation apparatus. Figure 7 shows an isometric view of a wireline tool-string 2 engaged with both the transportation apparatus illustrated in respect of Figure 6a and 6b in addition to the apparatus shown with respect to Figures 1-4.

[0040] The apparatus shown in Figure 6b is arranged to engage with the bottom end or nose of a tool-string, thereby forming the leading component deployed down

a wellbore. The transportation apparatus 201 includes a single wheel 206 deployed as the leading component of the apparatus. This single wheel can act as a hole finding assembly which can encounter and then roll over the top of obstacles immediately in the path of the tool-string. As can also be seen from Figures 6a and 6b the wheel 206 has a scalloped or concave profile, allowing it to bridge cuttings and obstacles encountered in the middle of the low side of the wellbore. The wheel is scalloped to ensure that only the edges of the wheel contact the wellbore wall resulting in a wide wheel track width, lower rolling friction and greater stability in the operating position.

[0041] The axis of rotation of the wheel 206 is above the centreline or longitudinal mid-line axis 202a of the tool-string which defines the longitudinal or axial centre of mass of the tool-string. Furthermore, the apparatus 201 has an orientation structure which comprises multiple orientation projections 208 arranged to assist in maintaining this desired orientation of the tool-string. The orientation projections 208a also function as protection structures and protect the wheels. As can be seen in Figures 6a and 6b, one or more of the orientation projections 208a may also provide a mounting point for mounting the wheel 206 or wheel axle.

[0042] Figure 6a also shows the form provided through a cross-section view of the transportation apparatus 201 made through all of its orientation projections 208 and the end view of wheel 206. This form has a transverse outline with a rotational centre 207. The rotational centre is substantially parallel to and offset from a central axis of the elongate sensor assembly. The rotational centre of the transportation apparatus is offset from the centroid or centre of mass of the sensor assembly/tool-string 202a.

[0043] As described above, the offset between the rotational centre of the transportation device and centre of mass of the tool-string ensures the assembly is orientated in the most stable position with the tool-string centre of mass below the rotational centre of the transportation device. In this stable position the tool-string descends down the wellbore carried on the wheels of the transportation device.

[0044] Figure 7 shows how these two different transportation apparatuses can be deployed in conjunction with a single tool-string 2 to form a system for transporting the tool-string. The single wheeled apparatus 201 is used to lift the bottom end or nose of the tool-string while the paired wheels of the transportation apparatus 1 is used to carry the upper section of the tool-string 2. In another embodiment the transportation apparatus may be provided with a partial orientation structure, or no orientation structure at all. In these embodiments a separate component may carry some or all of the orientation structure. For example, a tool-string may be provided with a transportation apparatus and one or more of the orientation structures shown in Figures 20, 21 or 33. The relative positioning of the separate components of the orientation structure along the sensor assembly is not critical, pro-

vided the overall form has a transverse outline with a rotational centre.

**[0045]** Figures 8 and 9 show an alternative embodiment of the transportation apparatus 1a. This embodiment is configured for in-line connection to a sensor assembly, rather than mounting over the sensor or other sensor assembly component. As can be seen, the transportation apparatus 1a is provided with an orientation structure which includes a protection structure which includes removable orientation projections 8a which extend from in front of the wheels, around an exterior surface 6a of the wheels 6. These orientation projections 8a are shaped to assist in preventing material from clogging the space between the inside surface of the wheel 6b and the corresponding exterior surface of the main body 4a.

**[0046]** The width of the wheels 6 is preferably allows a clearance space between the inner surface of the wheel and the body, and between the outer surface of the wheel and the protection structure. In a preferred embodiment there is at least 4mm clearance between the operating surface of the wheels and the surrounding body and structure, as is described further below.

**[0047]** As is best seen in Figure 9, in this embodiment the orientation projections 8a also operate to support the outer ends of the stub axles 7 on which the wheels 6 are mounted. Those skilled in the art will appreciate that in an alternative embodiment (not shown) the stub axles 7 may be permanently connected to or integral with the removable orientation projections 8a, and may be engaged with and supported by the body 4a at their inner ends.

**[0048]** As shown in the cross-section view of Figure 9, the wheel 6 diameter is greater on the inner face 6b than the outer face 6a to fit to the circular wellbore profile. This variation in wheel diameter causes some skidding at the contact surface between the wheel and the wellbore wall as the wheel rotates. Preferably the wheel should be narrow in order to minimise skidding contact and provide the least friction between the wheel and the wellbore wall as the wheel rotates down the wellbore. As can be seen from these figures, the width of the wheels 6 is less than about 20mm, preferably less than 18mm. In one embodiment shown in figure 9 the wheel width is 10mm. In another preferred embodiment shown in fig 42 the wheel width is 15mm.

**[0049]** Figures 10 to 12 show a number of views of a guide device 21. The guide device 21 includes a nose assembly 22 formed from a nose section 23 and a base 27, as shown in Figures 10 and 11. Directly attached to the nose assembly 22 is an orientation structure 13, shown by an orientated stand-off 24.

**[0050]** The orientated stand-off 24 provides a sleeve like structure with a hollow interior cavity 29 arranged to receive the leading end of the wireline logging tool-string. The orientated stand-off 24 includes a pair of friction reducing elements, in this case travel skids 26, which are oriented to slide along the downside wall of the wellbore

through the action of a set of three orientation projections 8 provided by the orientated stand-off 24. The travel skids 26 are formed from a durable ceramic material which has low friction characteristics and resists abrasion, and the effects of high temperatures and high alkaline conditions found in a wellbore, for example alumina ceramic or poly-metallic oxide thermosetting ceramic. Suitable plastic or elastomer materials can also be used for this component. When provided with such friction reducing elements the orientated stand-off 24 can function as a transportation apparatus, although wheels may be necessary for high deviation angles.

**[0051]** The travel skids, when provided, may be designed for use in a specific wellbore diameter, and may be shaped to conform to the curvature of the wellbore wall. The leading and trailing edges of the travel skids are contoured to form a gentle entry to allow the skids to "ski" over mudcake and cuttings debris.

**[0052]** The travel skids are positioned on the orientated stand-off so that they do not travel over the lowermost section of the wellbore where cuttings are likely to accumulate. Rather, the skids straddle the cuttings and are positioned laterally in on the borehole wall, preferably between 30° and 45° from a vertical plane through the longitudinal axis of the sensor assembly.

**[0053]** As is described above with reference to Figures 1 to 4, the orientation projections 8 act to destabilise the position of the tool-string if placed in contact with the low side wall of a deviated wellbore. The substantial weight of the tool-string will ensure that if one of these projections is in contact with the down side wall, the tool-string will rotate back about it's longitudinal axis to an orientation placing the travel skids in contact with the downside wall.

**[0054]** As can be seen from Figures 10 to 12, the nose section 23 has a fixed offset angle relative to the longitudinal axis of any tool-string engaged with the interior cavity 29 of the orientated stand-off 24. This arrangement provides the nose section 23 with a permanent upward inclination as the combined guide device and tool-string is deployed down a deviated wellbore. The upward inclination of the nose section ensures that the nose section tip 36 is elevated above the low side of the wellbore by a height 37, and is offset from and above the longitudinal axis of the tool-string. Hence obstacles on the low side wall of the wellbore are avoided by the guide device with the tool-string following immediately after the nose assembly.

**[0055]** Figures 13 and 14 show an exploded view of a further preferred guide device. The guide device includes a nose section 23, a base 27 and an orientation structure 24. All three components may be partially or fully integrated (not shown) or provided as discrete components as in the arrangement shown. In the arrangement shown the base 27 has a fixed angle relative to the tool-string longitudinal axis and is attached directly to the leading end of the wireline logging tool-string. The nose section 23 is attached to the terminal end of the base 27. The orientation structure slides over and is attached to the



logging tool-string such that the orientation projections are aligned to orient the nose section 23 upwards as the tool-string descends down the wellbore.

[0056] The nose section 23 can be implemented in different lengths, thereby altering the height 37 from the bottom of the wellbore to the nose section tip 36. The offset of the nose section tip 36 is pre-set depending on the wellbore size and conditions.

[0057] An enlarged view of one arrangement of the base 27 is shown in Figure 15. The base 27 may be used with some nose sections of the prior art in order to provide improved performance, although those skilled in the art will appreciate that the tool-string will require some type of orientation structure, for example an orientated stand-off, bow spring excentraliser and/or transportation apparatus as described herein, in order to orientate the nose away from the base of the wellbore.

[0058] The base 27 has a first engagement portion 25a for engaging an end of a tool-string, and a second engagement portion 25b for engaging a nose assembly. The engagement portions have centrelines which are angularly offset, such that a nose assembly engaged, in use, with the second engagement portion 25b has a centreline which extends at an angle to the centreline of a tool-string engaged with the first engagement portion 25a, as can be seen in Figure 13. The offset angle may be any suitable angle, depending on the length of the nose assembly and the diameter of the wellbore, as is described further below.

[0059] The first engagement portion 25a is provided as a collar which fits over a standard boss provided at the end of a tool-string, and the second engagement portion 26b is provided as a hollow boss having standard outer dimensions for engaging a collar provided at the end of a prior art nose assembly. The base 27 is itself hollow, or at least has an aperture therethrough, to allow wiring to be passed through the base 27 if necessary.

[0060] Figures 16 to 18 show different configurations of angle nose assembly capable of being used in the arrangements shown in Figures 28-33. The nose assembly can rotate or pivot about an axle 38 which is engaged to the base 27, so that the angle of the nose assembly can be pre-set to a selected angle before the tool-string is lowered into the wellbore. The base 27 has a locking arm (not shown) extending inside the nose section 23. The nose section is set at a fixed pre-set angle from the longitudinal tool axis by a locking pin extending through one of three locking points 30 to connect with the locking arm. The nose section pivoting connection 38, combined with the locking point 30, secures the nose section to the base 27 at a fixed angle from the tool-string longitudinal axis. The selection of locking point 30 will determine the offset angle and hence the heights 37 of the nose section tip 36 above the low side of the wellbore.

[0061] As can be seen from Figures 16-18, each fixed angle setting of the nose assembly 22 provides the nose section 23 with a different offset angle. The offset angle implemented by each nose section 23 increases from 3°

in Figure 16, 8° in Figure 17 and 15° and Figure 18. Those skilled in the art will appreciate that the pre-set angle may be adjusted depending on the diameter of the wellbore, the required standoff of the tool-string in the wellbore, and the length of the nose assembly, to locate the end of the nose assembly in a suitable position in the wellbore. Longer nose assemblies will require shallower angles, and shorter nose assemblies will require larger angles, for a given wellbore diameter and standoff distance. The angle is selected such that the tip of the nose section is above the longitudinal axis of the tool-string.

[0062] Figure 19 shows an alternative adjustable nose assembly. The nose section 23 is provided with a locking member 31. A pin or axle 38 extends through apertures in the base 27 and the locking member 31. The base 27 has a vertically orientated longitudinal slot 33 to accommodate the locking member 31.

[0063] The end of the locking member 31 is provided with a plurality of locking pin apertures 34a which are parallel to the aperture for the axle 38. Locking pin apertures 34b are also provided in the base 27. The locking pin apertures 34a, 34b are arranged such that one of the apertures 34a in the locking member 31 is aligned with one of the apertures 34b in the base 27 when the nose section 23 is set to one of a predetermined number of angles. The nose section 23 is held at the required angle by inserting a locking pin 34 through apertures 34a, 34b. Preferably, the apertures 34a, 34b are arranged to allow the nose section to be set to angles of 3 degrees, 6 degrees or 9 degrees to the centreline of the tool-string, although may provide angles up to 60°, 45° or 20°. Angles as low as 1° may be used, although often this will require the use of an inconveniently long nose assembly.

[0064] Figures 20-23 show perspective views of two different types of orientation structures. These figures again illustrate the different forms of orientated stand-off 24 which are to be provided as orientation structures of a guide device.

[0065] These different orientated stand-offs cater for different sizes or diameters of wellbore size. These figures also illustrate different arrangements of orientation projections 8.

[0066] The stand-offs shown in Figure 20 and Figure 22 employ a set of four orientation projections 8, while the stand-offs 24 shown in Figures 21 and 23 employ three orientation projections only. The orientation projections 8 have tapered extremities 35 to assist in guiding the tool-string around or past obstacles encountered in a wellbore.

[0067] The oriented standoffs have a hole 29 passing through the body of the device. This hole is offset from the nominal centre of the standoff. The oriented standoff is designed to slip over a cylindrical wireline logging tool which is then fixed within the hole 29, and below the rotational centre of the stand-offs. The tool-string will therefore be conveyed with a predictable orientation, which in turn will impart an upward orientation or angle to the nose section of the nose assembly.

[0068] Figures 24-27 show a series of transverse or cross-section views of a number of different implementations of orientation structures. These orientation structures are capable of being used in the arrangements shown with respect to Figures 10-19 and 28-30. Identified on these figures is the rotational centre 15 of the orientation structure and the centroid 2a or centre of mass of the tool-string. Each section of the tool-string has a centre of mass 2a approximately in the middle of the circular section of the tool-string.

[0069] These figures also show the form provided through a transverse cross-section of each orientated stand-off made through all of its orientation projections 8 (which in these arrangements also corresponds to the transverse outline). The form provided by this cross section therefore has rotational centre 15. The rotational centre of the oriented stand-off is offset from the centroid or centre of mass of the tool-string 2a.

[0070] In a deviated wellbore the tool-string will naturally rotate about its longitudinal axis to seek the most stable position. The most stable position is where the tool-string and oriented stand-off assembly has the lowest centre of gravity. The lowest centre of gravity is where the tool centroid is below the centre of rotation. In this stable position, the guide device nose section is orientated upwards, the low-friction travel skids of the orientated stand-off are in contact with the low side of the wellbore and the logging tool sensors can be optimally orientated to measure the preferred side of the wellbore.

[0071] These views show various arrangements of orientated stand-offs with different numbers of orientation projections 8. As can be seen from these figures an orientated stand-off may be implemented with a number of different arrangements of orientation projection. These projections can also be formed with a variety of lengths to accommodate a range of different wellbore diameters.

[0072] As can also be seen from these figures, the extremities of each of the orientation projections 8 define sections of the perimeter of a substantially circular curve centred on a point above the centre of gravity of any tool-string engaged with the orientation structure. In the arrangements shown, each of the projections 8 is arrayed at an equal angle to that of its neighbouring projections. However, the travel skids 26 are preferably arranged to have a greater spacing between them than the spacing between the other orientation projections, in order to maximise the stability of the apparatus when it is in its preferred orientation.

[0073] Figures 28-31 demonstrate the use of the guide device. The figures show the guide device displayed in Figures 16-18 and an associated wireline logging tool-string. These figures show a variety of arrangements where an orientation structure 24 or structures are connected to a tool-string 2 at positions remote from a nose assembly 22.

[0074] Figure 28 illustrates the use of a single orientation structure, shown by an orientated stand-off 24 which is connected some distance away from a nose assembly

22.

Figure 29 illustrates a similar alternative arrangement of orientated stand-off 24 which is arranged to be deployed in a larger diameter wellbore than the stand-off shown with respect to Figure 28, and hence has the nose 23 set at a larger angle and uses a larger diameter orientation structure.

[0075] Figure 30 shows in a further arrangement which employs a pair of orientated stand-offs 24 located at two different positions along the length of a tool-string 2.

[0076] In Figure 31 a pair of transportation apparatus 1 are used to orientate the guide device 21. The transportation apparatus 1 again act to provide the tool-string 2 with a predictable orientation and to impart an upward inclination to the nose section 23 of the nose assembly 22, as is described above with reference to Figures 1-9.

[0077] Figure 32 shows a variation of the system shown in Figure 31. In this arrangement the transport apparatus 1 are attached to a weight bar 39. The weight bar 39 is attached to a tool-string 2, preferably by a flexible coupling. This allows the transport apparatus 1 and guide device 21 to be used with any type of tool-string, including those with sensors that must be touching the borehole wall, those with irregular profiles, and exceptionally large diameter tools relative to the wellbore diameter. Tools that require lateral movement in the wellbore during operation may also be used, for example sampling tools which move across wellbore when set, and imager tools that are run in hole collapsed and open out to be centralised when deployed.

[0078] Figure 33 shows another arrangement in which the orientation structure includes the use of a bowspring excentraliser as an orientation projection 8. Bowspring excentralisers are well known to those skilled in the art.

[0079] Referring next to Figure 34, a guide device 21 is shown which has a base 27b which has provision for mounting a temperature sensor 40 and/or other sensor means which require direct contact with the fluid in the wellbore. The base 27b has a guard structure 41 comprising two parallel ribs 42 arranged on either side of the sensor 40, the ribs 42 extending at least as far from the body of the base 27b as the sensor 40. This allows the temperature sensor probe to extend into the central area of the wellbore without risk of damage resulting from contact with the wellbore wall. In this position the temperature sensor assembly is well flushed by the movement of the tool through the wellbore fluids, and is not liable to be so covered with mudcake as to unduly affect response times. To ensure a fast response to temperature changes, preferentially the temperature sensor probe housing is made from a high thermal conductivity, low corrosion material such as low Beryllium Copper alloy, silver or gold. The temperature sensor probe is preferably thermally insulated from the base and body of the guide device 21.

[0080] By positioning the probe at the end of the nose of the tool-string the probe measures wellbore temperature before that temperature is influenced by the temper-

ate of the tool-string itself, and mixing of well fluids caused by the tool-string movement.

[0081] A pressure sensor may also be provided (additionally or alternatively to the temperature sensor). The provision of a pressure sensor which does not become clogged with mudcake or other debris allows the change of depth of the tool to be monitored. In this way the operator can ensure that the tool-string is proceeding into the wellbore at a rate which is consistent with the rate at which the cable feed is operating. Feeding cable at too high a rate can result in the cable becoming tangled and the tool-string becoming difficult to remove from the wellbore.

[0082] The sensor 40 is positioned so as to be behind the upwardly angled nose section 23. Because the orientation structures keep the nose section 23 angled upward, and the nose section 23 is held at a fixed angle when in use, the sensor 40 does not come into contact with the sides of the wellbore, and is shielded by the nose section 23 from any steps or shelves in the wellbore walls. In the arrangement shown the guide device 21 is provided with the pre-set angle adjustment system described above with reference to Figure 19, and shows the cover plate 43 which is used to retain the locking pin 34.

[0083] Referring next to Figures 35-37, a lubrication delivery apparatus which is suitable for use with the transportation apparatus 1 is generally referenced by arrow 300.

[0084] The apparatus 300 is formed from a base structure, provided in this arrangement by a block element 52. An inlet channel 53 is formed within the interior of the block element, as is an outlet channel 55. The inlet channel 53 terminates in an inlet port, formed in this arrangement by a grease nipple or valve 54. The outlet channel 55 leads to an outlet port 56 which allows for the free flow of lubricant, typically grease, from the apparatus 300.

[0085] The apparatus 300 has an elastic diaphragm 37 which covers most of the upper flat surface of the base structure 52. The diaphragm 57 is connected to and sealed against the base by a substantially rigid protective housing 58. The housing 58 also includes a port 59 to allow ambient pressure to act on the exterior side of the elastic diaphragm. The port also provides an opening for inspection of the diaphragm 57.

[0086] As can be seen from Figure 37, a reservoir 60 is formed between the interior surface of the diaphragm 57 and the surface of the base which it covers. Figure 36 shows the arrangement of the apparatus prior to this reservoir being filled with lubricant.

[0087] To charge or fill the reservoir 60, a suitable flowable lubricant, typically grease, is forced into the reservoir 60 through the grease nipple or valve 54 via a grease gun, oil pump or similar. The injected lubricant stretches the elastic diaphragm 57. The tension induced in the elastic diaphragm 57 due to this stretching, results in the lubricant in the reservoir 60 being maintained at a pressure higher than the ambient pressure acting on the exterior side of the elastic diaphragm 57.

[0088] Figure 37 shows the apparatus after the reservoir 60 is charged or filled with lubricant injected through the grease nipple or valve 54 and inlet channel 53. The lubricant is pressurised in the reservoir by the stretched elastic diaphragm 57. In this arrangement the elastic diaphragm has been stretched to twice its original area (elongation 100%). The lubricant is delivered from the pressurised reservoir 60 to the mechanical system via outlet channel 55 and outlet port 56.

[0089] In the arrangement shown the diaphragm 57 is formed from silicone rubber, allowing it to be deformed and expanded to accommodate the pressurised lubricant pumped into the reservoir 60. The elastic nature of the diaphragm allows it to store elastic potential energy imparted by the pressurised lubricant supply to maintain the pressure of lubricant held within the reservoir. This stored energy is slowly released by the diaphragm pushing lubricant out through the outlet channel 55 and outlet port 56 to lubricate a further mechanical system (not shown) to be deployed and an underground wellbore. One example of a mechanical system which can be lubricated is a bearing assembly, as is described further below.

[0090] The tension in the elastic diaphragm 57 maintains the lubricant at an incremental pressure over and above the ambient pressure acting on the exterior surface of the elastic diaphragm 57. This over pressurisation of lubricant by the apparatus 300 provides a supply of lubricant to the mechanical system being lubricated and also prevents the entry of contaminants from the wellbore into the mechanical system being lubricated.

[0091] In a variety of additional arrangements the flow of lubricant through the mechanical system may be controlled by a metering valve. The flow of lubricant may alternatively be limited by an oil or grease seal on the exit of the mechanical system. The mechanical system may also incorporate a bush bearing where flow of lubricant is limited by the close fit the bearing.

[0092] In the example shown in Figure 38 the ambient pressure (P) act on the exterior surface of the diaphragm 57 may be 101.3 kPa (14.7 psi). The additional pressure ( $\delta P$ ) exerted on the lubricant by the stretched elastomer diaphragm 57 may be 20.7 kPa (3 psi). Hence the lubricant reservoir pressure is 122.0 kPa (17.7 psi). Thus the pressure within the lubricated system is 20.7 kPa (3 psi), higher than its surroundings.

[0093] An imperfect seal between the mechanical system which is supplied with lubricant by the apparatus 300 and its surroundings will result in lubricant leaking out to the ambient surroundings. The constant flow of lubricant out of the mechanical system prevents contaminants from entering the mechanical system. When the device is operating in a wellbore at 4000m below surface, the ambient pressure may be in the order of 41.37 MPa (6000 psi). The stretched elastomer diaphragm 57 will still exert an additional 0.02 MPa (3 psi) pressure on the lubricant and hence the lubricant pressure is 41.39 MPa (6003 psi). Pressure within the mechanical system is now 41.39

MPa (6003 psi), 0.02 MPa (3 psi) above the surroundings, hence the mechanical system is protected from the entry of contaminants.

[0094] As the depth changes in the wellbore, so too does the ambient hydrostatic pressure. Unlike a spring/piston type system, the elastomer diaphragm has no sliding parts and is able to instantaneously adjust to small changes in ambient pressure, in this example, keeping lubricant pressure at 20.7 kPa (3 psi) above the surroundings. Because there are no sliding parts, and no friction inherent in the system, it will be effective at preventing contaminants entering the mechanical system even at very small differential pressure ( $\delta P$ ) from the stretched elastomer diaphragm.

[0095] Figures 39 to 41 show a transportation apparatus which is provided with an alternative implementation of the lubrication delivery apparatus 300. The lubrication apparatus shown in Figures 39-41 is equivalent to that discussed above with respect to Figures 35-38 other than for the inclusion of a pair of outlet channels and ports as discussed below, and performs the function of the pressurised lubrication system 9 described above with reference to Figures 4 and 5.

[0096] In Figures 39-41, the base structure of the lubrication delivery apparatus 300 is formed by a portion of the body of the transportation apparatus 1. As in the previously described arrangement, the base structure effectively forms a block like element which defines within its interior a pair of outlet channels 55 terminating in output ports 56. These outlet ports 56 are used to deliver lubricant to the bearings 61 of the transportation apparatus 1, as shown in Figures 39 and 40.

[0097] As best seen in Figure 39, each outlet port 56 feeds a chamber 62 formed between the end of the stub axle 7 and a cover 63 which is attached to the outer surface of the wheel 63. The chamber 62 extends to the open side of the bearing 61, thereby allowing pressurised lubricant to flow into the bearing 61.

[0098] A suitable lubricant seal 64 is provided on the inner side of the bearing 61. This arrangement allows the use of commercially available deep groove ball bearing assemblies 61 in the wellbore environment, the constant positive pressure on the inside of the oil/grease seal 64 ensuring that no water or other contaminants can penetrate the oil/grease seal 64.

[0099] The transportation apparatus shown in Figures 40 and 41 is provided with a protection structure in the form of removable orientation projections 8a which extend around an exterior surface 6a of the wheels 6, as described above with reference to Figures 8 and 9. These orientation projections 8a extend substantially longitudinally from in front of each wheel to behind the wheel, and are shaped to assist in preventing material from clogging the space between the inside surface of the wheel 6b and the exterior of the main body, and support the outer ends of the stub axles 7 on which the wheels 6 are mounted, as is described above. As can be seen in these figures, the wheels 6 extend above and below the longitudinally

extending orientation projection 8a. The longitudinally extending orientation projection 8a is preferably relatively slender, for example having a height which is greater than the diameter of the axle on which the wheel is mounted, but less than the radius of the wheel. As is best seen in Figure 41, a clearance space is provided between the radially extreme edge or surface 67 of the wheel (relative to the axis of rotation) and the longitudinal orientation projection 8a, although the profile of the wheel may mean that the clearance is reduced towards the centre of the wheel.

[0100] This clearance, along with the slender aspect of the protection structure, assists in preventing the area inside the protection structure from becoming clogged with debris from the wellbore surface. In a preferred embodiment there is a clearance of at least 4mm between radially extreme surface 67 of the wheel (that is, the surface of the wheel which is normally in contact with the wellbore wall) and the exterior of the main body, and at least 4mm clearance between the radially extreme edge of the wheel and the interior of the protection structure. In the embodiment shown the interior of the protection structure has a clearance of at least 15mm, more preferably at least 19mm.

[0101] The longitudinally orientated orientation projection preferably has a central axis which is substantially coincident with the rotational axis of the wheel.

[0102] Figure 42 shows another embodiment of a transportation apparatus 1 with a modified lubrication delivery apparatus. In the embodiment shown the transportation apparatus 1 uses plain bearings with a flanged bush bearing member 61a. The lubrication apparatus 300 has two outlet channels and at least four outlet ports 56. No lubricant seal is required for this embodiment.

[0103] In this embodiment the stub axles 7 are formed as separate components to the body (in contrast to the embodiments shown in Figures 4 and 5 wherein the stub axles are integrally formed with the body). However, the channels 55 still run through each stub axle.

[0104] In a preferred embodiment the arrangement of the bearings is such that some pressurised lubricant is able to escape past the bearings. This constant, but controlled, escape of lubricant acts to transport debris and contaminants away from the bearings.

[0105] The stub axles 7 are supported by the longitudinally extending orientation projections 8a.

[0106] Figures 43 to 45 show another transportation apparatus configured as a tractor unit.

[0107] The tractor unit 400 comprises a transportation apparatus with a plurality of main wheels 6, in this case four main wheels 6, and at least one jockey wheel 6c. The tractor unit preferably comprises an orientation structure having at least two orientation projections. Those skilled in the art will appreciate that the jockey wheel 6c also functions as an orientation projection.

[0108] The jockey wheel 6c is preferably mounted to an adjustable mounting means (not shown) for raising and lowering the jockey wheel relative to the main body

4a. One or more of the main wheels 6, and preferably each of the main wheels 6, are connectable to a drive means, typically one or more electric motors. In a preferred arrangement the main wheels 6 are provided with clutch means (not shown) which can disengage the main wheels 6 from the drive means to allow the main wheels 6 to freewheel when the borehole is sufficiently steep.

[0109] In use, one or more tractor units 400 are connected in line with the tool-string. The tool-string and tractor 400 can free-wheel down the wellbore until the tool-string can no longer descend under gravity alone. At this point the jockey wheel 6c is raised and extends upward to make contact with the top of the wellbore wall 3 (best seen in Figure 44) thereby increasing contact pressure on the driven wheels 6. The clutch is engaged and the main wheels 6 are driven by the drive means. In this way the tool-string can be transported along wellbores at very high deviation angles, up to and including substantially horizontal wellbores. The tractor unit is preferably provided with a guide device 21 as described above. One or more transportation means 1 may also be used as required to assist in transporting the tool-string.

[0110] Figures 46 and 47 show another orientation structure which is provided as an orientated standoff 24, similar to those shown in Figures 20 and 21. As shown in Figures 46 and 47, the engagement between the standoff 24 and the tool-string is similar to that used with the transportation apparatus described above with respect to Figures 1-3. The engagement structure 5 is in the form of a locking collar. The collar 5 is arranged to partially enclose the exterior side wall surface of the tool-string 2, allowing the standoff to be slid on and over the tool-string at any desired position along the length of the tool-string. Each collar includes a series of threaded holes 5a arranged to receive a screw which engages with a recess or blind hole in the exterior surface of the tool-string. These threaded holes 5a and an associated set of screws are used to lock the apparatus 1 to the tool-string 2 with a specific orientation. By arranging the collars 5 to only partially enclose the tool-string 2, the tool-string can be carried in a lower position than would be possible if the collars 5 were to completely encircle the circumference of the tool-string 2, and allows an increased clear space 65 (preferably at least 10mm, more preferably at least 12.7 mm (1/2 inch)) between the lower orientation projections 8, which in this arrangement comprise low friction skids. This clear space allows the cutting debris which has collected on the bottom surface of the bore to pass under the tool-string 2. As with the other orientation structures described above, the structures shown in Figures 46 and 47 have a centre of rotation which is offset from the centroid of the tool-string 2.

[0111] Figures 48 and 49 show a variant of the system shown in Figure 32. In this arrangement the tool-string is provided with a prior art sampling tool 66 for taking samples and pressure measurements. Because the tool-string 2 is connected to at least one orientation structure, whether an orientated standoff 24 or a transportation ap-

paratus 1, the sampling tool can be orientated to take its sample from the high side of the wellbore. This has the advantage that the high side of the wellbore tends to be less damaged by the grinding action of the drillpipe as it rotates and reciprocates during the drilling operation. This damage can affect the porosity and permeability of the wellbore wall in particular, and can lead to unrepresentative measurements, or at least delays in obtaining representative measurements. By using the apparatus shown, this sampling process is improved.

[0112] Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise", "comprising", and the like, are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense, that is to say, in the sense of "including, but not limited to".

## Claims

1. A sensor transportation apparatus to convey an elongate sensor assembly through a wellbore, the sensor transportation (1, 1a) apparatus comprising:

a main body comprising at least one engagement structure (5) adapted to connect the sensor transportation apparatus (1, 1a) to an elongate sensor assembly, and

two wheels (6) each arranged to rotate about an axis of rotation substantially perpendicular to a longitudinal axis of the elongate sensor assembly when the transportation apparatus (1, 1a) is connected to the elongate sensor assembly, and

an orientation structure (6, 8, 8a, 14) comprising the wheels (6) and at least one laterally extending orientation projection (8, 8a, 14), to define a form having a transverse outline which has a rotational centre (15), wherein lateral extremities of the orientation structure (6, 8, 8a, 14) substantially lie on a substantially circular curve centred on the rotational centre (15), wherein, in use, relative rotation between the sensor transportation apparatus and the elongate sensor assembly is prevented and the rotational centre is offset from a centre of mass (2a) of the elongate sensor assembly, **characterised in that:**

the orientation projection (8, 8a, 14) is configured so that in use the elongate sensor assembly (2) has an unstable position when the orientation projection (8) is in contact with the low side of the wellbore and the elongate sensor assembly is configured to naturally rotate from this unstable position so that the sensor transportation apparatus is oriented in a most stable position with the elongate sensor assembly centre of mass below the rotational centre of the sensor transportation apparatus and with the elongate

sensor assembly carried on the wheels of the transportation apparatus in contact with the low side of the well bore.

2. The sensor transportation apparatus of claim 1, wherein, in use, a rotational axis of each said wheel (6) is above the centre of mass (2a) of the elongate sensor assembly when the sensor transportation apparatus (1, 1a) is substantially horizontal.
3. The sensor transportation apparatus of any one of the preceding claims, wherein the orientation structure (6, 8, 8a, 14) comprises multiple orientation projections (8, 8a, 14).
4. The sensor transportation apparatus of claim 3, wherein the orientation projections (8a, 14) also function as protection structures to protect the wheels.
5. The sensor transportation apparatus of any one of the preceding claims, wherein the wheels (6) run on bearings (10, 110, 61, 61a) and the apparatus (1) further comprises a lubrication delivery apparatus (300) which provides a lubricant to the bearings (10, 110, 61, 61a) at a pressure which is greater than an ambient pressure within the wellbore.
6. The sensor transportation apparatus of claim 1, wherein the engagement structure (5) is adapted to partially enclose the exterior surface of the elongate sensor assembly without completely encircling the elongate sensor assembly.
7. The sensor transportation apparatus of any one of the preceding claims, wherein the rotational axes of the two wheels are substantially parallel and coplanar.
8. The sensor transportation apparatus of any one of the preceding claims wherein said orientation structure comprises at least one protection structure (8a) which extends longitudinally around the wheel (6), to thereby substantially prevent a side (6a) of the wheel from contacting the wellbore wall, wherein the wheel (6) extends above and below the protection structure (8a).
9. The sensor transportation apparatus of claim 8 wherein the protection structure (8a) has a height which is less than a radius of the wheel (6).
10. The sensor transportation apparatus of claim 8 or 9 wherein there is a clearance space of at least 4mm between:

a surface (6b) of the wheel (6) and both of a surrounding body of the apparatus (1) and the

orientation structure, or  
a surface (6b) of the wheel (6) and the elongate sensor assembly, and/or  
a surface of the wheel (6a) which is at the radial extremity of the wheel (6), relative to the axis of rotation, and an inner surface of the protection structure (8a).

11. The sensor transportation apparatus of any one of claims 8 to 10, wherein the protection structure (8a) comprises removable orientation projections (8a) which extend from in front of the wheels (6) around an exterior surface (6a) of the wheels (6).

12. The sensor transportation apparatus of any one of the preceding claims and a guide device (21) comprising a base (27) adapted to engage an end of the elongate sensor assembly and a nose section (22, 23) having a tip (36) which is offset from the longitudinal axis of the elongate sensor assembly when the guide device (21) is engaged with said sensor assembly, in use the orientation structure (6, 8, 8a, 14) orientating the guide device (21) in the wellbore so that an upward inclination of the nose section (22, 23) ensures that the tip (36) of the nose section (22, 23) is elevated above a low side (3a) of the wellbore by a height and offset from and above the longitudinal axis of the elongate sensor assembly (2).

13. An elongate sensor assembly (2) for use in wireline logging applications through a wellbore and a sensor transportation apparatus (1, 1a) as claimed in any one of claims 1 to 11 connected to the elongate sensor assembly (2), wherein the elongate sensor assembly (2) comprises a sampling tool (66) for taking samples and pressure measurements, oriented to take a sample from a high-side of the wellbore with the sensor transportation apparatus (1, 1a) in the stable orientation.

14. A tool string for use in wireline logging applications through a wellbore, comprising:

an elongate sensor assembly (2),  
the sensor transportation apparatus (1, 1a) as claimed in any one of claims 1 to 11, and  
a guide device (21) for guiding the elongate sensor assembly (2) in a wellbore, the guide device (21) comprising a base (27) engaged to an end of the elongate sensor assembly (2) and a nose section (23) having a tip (36) which is offset from the longitudinal axis of the elongate sensor assembly (2), in use the orientation structure (6, 8, 8a, 14, 208) orientating the guide device (21) in the wellbore so that an upward inclination of the nose section (23) ensures that the tip (36) of the nose section (23) is elevated above a low side (3a) of the wellbore by a height and offset

from and above the longitudinal axis of the elongate sensor assembly (2).

15. The tool string of Claim 13 wherein the nose section (23) with said tip (36) is arranged to project away from the base (27) at a fixed angle which is offset to a longitudinal axis of the tool-string when the guide device (21) is engaged with said elongate sensor assembly (2).
16. The tool string of claim 14 wherein the guide device (21) comprises a locking member (31) provided with a plurality of locking pin apertures (34a) and the base (27) comprises a plurality of locking pin apertures (34b) to lock the nose section (23) at a preselected angular setting with locking pins (34).

#### Patentansprüche

1. Sensortransportvorrichtung zur Förderung einer langgestreckten Sensoranordnung durch ein Bohrloch, die Sensortransportvorrichtung (1, 1a) umfassend

einen Grundkörper umfassend zumindest eine Eingriffsstruktur (5), die ausgebildet ist, die Sensortransportvorrichtung (1, 1a) mit einer langgestreckten Sensoranordnung zu verbinden, und zwei Räder (6), die jeweils angeordnet sind zum Rotieren um eine im Wesentlichen senkrecht zu einer Längsachse der langgestreckten Sensoranordnung verlaufende Rotationsachse, wenn die Sensortransportvorrichtung (1, 1a) mit der langgestreckten Sensoranordnung verbunden ist, und

eine Orientierungsstruktur (6, 8, 8a, 14) umfassend die Räder (6) und zumindest einen sich seitlich erstreckenden Orientierungsvorsprung (8, 8a, 14), der eine Form, die eine Transversalkontur mit einem Rotationsmittelpunkt (15) aufweist, definiert, wobei seitliche Enden der Orientierungsstruktur (6, 8, 8a, 14) im Wesentlichen auf einer im Wesentlichen kreisförmigen Kurve liegen, die im Rotationsmittelpunkt (15) zentriert ist, wobei im Einsatz eine relative Rotation zwischen der Sensortransportvorrichtung und der langgestreckten Sensoranordnung verhindert ist und der Rotationsmittelpunkt vom Massenmittelpunkt (2a) der langgestreckten Sensoranordnung versetzt ist,

**dadurch gekennzeichnet, dass**

der Orientierungsvorsprung (8, 8a, 14) dergestalt eingerichtet ist, dass im Einsatz, wenn der Orientierungsvorsprung (8) in Kontakt mit der unteren Seite des Bohrlochs ist, die langgestreckte Sensoranordnung (2) in einer instabilen Lage ist, und dass die langgestreckte Sensoran-

ordnung eingerichtet ist, sich natürlicherweise von dieser instabilen Lage wegzudrehen, so dass die Sensortransportvorrichtung in einer möglichst stabilen Lage ausgerichtet ist, in welcher der Massenmittelpunkt der langgestreckten Sensoranordnung unterhalb des Rotationsmittelpunkts der Sensortransportvorrichtung liegt und in welcher die langgestreckte Sensoranordnung auf den Rädern der Transportvorrichtung, welche die untere Seite des Bohrlochs berühren, getragen ist.

2. Sensortransportvorrichtung nach Anspruch 1, wobei eine Rotationsachse jedes der Räder (6) oberhalb des Massenmittelpunktes (2a) der langgestreckten Sensoranordnung ist, wenn die Sensortransportvorrichtung (1, 1a) im Einsatz und im Wesentlichen horizontal ist.

3. Sensortransportvorrichtung nach einem der vorhergehenden Ansprüche, wobei die Orientierungsstruktur (6, 8, 8a, 14) mehrere Orientierungsvorsprünge (8, 8a, 14) umfasst.

4. Sensortransportvorrichtung nach Anspruch 3, wobei die Orientierungsvorsprünge (8a, 14) außerdem als Schutzstruktur zum Schutz der Räder wirken.

5. Sensortransportvorrichtung nach einem der vorhergehenden Ansprüche, wobei die Räder (6) auf Lagern (10, 110, 61, 61a) laufen und die Vorrichtung (1) zudem eine Schmiermittelzufuhrvorrichtung (300) umfasst, die den Lagern (10, 110, 61, 61a) ein Schmiermittel mit einem Druck bereitstellt, der größer ist als der Umgebungsdruck innerhalb des Bohrlochs.

6. Sensortransportvorrichtung nach Anspruch 1, wobei die Eingriffsstruktur (5) ausgebildet ist, die Außenfläche der langgestreckten Sensoranordnung teilweise zu umschließen, ohne diese vollständig zu umgeben.

7. Sensortransportvorrichtung nach einem der vorhergehenden Ansprüche, wobei die Rotationsachsen der beiden Räder im Wesentlichen parallel und komplanar sind.

8. Sensortransportvorrichtung nach einem der vorhergehenden Ansprüche, wobei die Orientierungsstruktur zumindest eine Schutzstruktur (8a) umfasst, die sich längsverlaufend um das Rad (6) erstreckt, um dadurch ein Berühren einer Seite (6a) des Rades mit der Bohrlochwand im Wesentlichen zu verhindern, wobei das Rad (6) ober- und unterhalb der Schutzstruktur (8a) vorsteht.

9. Sensortransportvorrichtung nach Anspruch 8, wobei

die Schutzstruktur (8a) eine Höhe aufweist, die geringer ist als ein Radius des Rades (6).

10. Sensortransportvorrichtung nach Anspruch 8 oder 9, wobei ein Freiraumabstand von zumindest 4 mm zwischen  
5  
einer Oberfläche (6b) des Rades (6) und sowohl einen dieses umgebenden Körpers der Vorrichtung (1), als auch der Orientierungsstruktur, oder  
10  
einer Oberfläche (6b) des Rades (6) und der langgestreckten Sensoranordnung, und/oder einer Oberfläche des Rades (6a), die relativ zu der Rotationsachse an dem Radialende des Rades (6) liegt, und einer Innenfläche der Schutzstruktur (8a), vorgesehen ist.  
15
11. Sensortransportvorrichtung nach einem der vorhergehenden Ansprüche 8 bis 10, wobei die Schutzstruktur (8a) entfernbare Orientierungsvorsprünge (8a) umfasst, die sich von einer Vorderseite der Räder (6) um eine Außenfläche (6a) der Räder (6) erstrecken.  
20
12. Sensortransportvorrichtung nach einem der vorhergehenden Ansprüche und eine Führungsvorrichtung (21) umfassend eine Basis (27), die ausgebildet ist, mit einem Ende der langgestreckten Sensoranordnung im Eingriff zu sein, und einen Nasenabschnitt (22, 23), der eine Spitze (36) aufweist, die, wenn die Führungsvorrichtung (21) im Eingriff mit der Sensoranordnung ist, von der Längsachse der langgestreckten Sensoranordnung versetzt ist, wobei die Orientierungsstruktur (6, 8, 8a, 14) die Führungsvorrichtung (21) im Einsatz in dem Bohrloch dergestalt ausrichtet, dass eine Aufwärtsneigung des Nasenabschnitts (22, 23) sicherstellt, dass die Spitze (36) des Nasenabschnitts (22, 23) oberhalb einer unteren Seite (3a) des Bohrlochs um eine Höhe angehoben sowie von und über der Längsachse der langgestreckten Sensoranordnung (2) versetzt ist.  
25  
30  
35  
40
13. Langgestreckte Sensoranordnung (2) zur Verwendung in Bohrlochmessungsanwendungen in einem Bohrloch und eine Sensortransportvorrichtung (1, 1a) nach einem der Ansprüche 1 bis 11, die mit der langgestreckten Sensoranordnung (2) verbunden ist, wobei die langgestreckte Sensoranordnung (2) ein Messwerkzeug (66) zur Probenentnahme und zur Druckmessung umfasst, die mit der Sensortransportvorrichtung (1, 1a) in stabiler Lage ausgerichtet ist, eine Probe von einer oberen Seite des Bohrlochs zu nehmen.  
45  
50
14. Werkzeugstrang zur Verwendung in Bohrlochmessungsanwendungen, umfassend  
55

eine langgestreckte Sensoranordnung (2), die Sensortransportvorrichtung (1, 1a) nach einem der Ansprüche 1 bis 11 und eine Führungsvorrichtung (21) zur Führung der langgestreckten Sensoranordnung (2) in einem Bohrloch, die Führungsvorrichtung (21) umfassend eine Basis (27), die mit einem Ende der langgestreckten Sensoranordnung in Eingriff ist, und einen Nasenabschnitt (22, 23), der eine Spitze (36) aufweist, die von der Längsachse der langgestreckten Sensoranordnung (2) versetzt ist, und wobei die Orientierungsstruktur (6, 8, 8a, 14, 208) die Führungsvorrichtung (21) im Einsatz in dem Bohrloch dergestalt ausrichtet, dass eine Aufwärtsneigung des Nasenabschnitts (22, 23) sicherstellt, dass die Spitze (36) des Nasenabschnitts (22, 23) oberhalb einer unteren Seite (3a) des Bohrlochs um eine Höhe angehoben ist sowie von und über der Längsachse der langgestreckten Sensoranordnung (2) versetzt ist.

15. Werkzeugstrang nach Anspruch 14, wobei der Nasenabschnitt (23) mit der Spitze (36) angeordnet ist, wenn die Führungsvorrichtung (21) im Eingriff mit der langgestreckten Sensoranordnung (2) ist, in einen festen Winkel, der von einer Längsachse des Werkzeugstrangs versetzt ist, von der Basis (27) weg zu ragen.  
25
16. Werkzeugstrang nach Anspruch 15, wobei die Führungsvorrichtung (21) ein Verriegelungsglied (31) umfasst, das mit einer Mehrzahl an Verriegelungsstiftöffnungen (34a) ausgestattet ist, und die Basis (27) mehrere Verriegelungsstiftöffnungen (34b) umfasst, um den Nasenabschnitt (23) mittels Verriegelungsstiften (34) in einer vorausgewählten Winkelseinstellung zu verriegeln.  
30  
35  
40

## Revendications

1. Appareil de transport de capteur pour transporter un assemblage allongé de capteur dans un forage, l'appareil de transport (1, 1a) comprenant :  
45  
- un corps principal ayant au moins une structure d'engagement (5) pour relier l'appareil de transport de capteur (1, 1a) à un assemblage allongé de capteur et  
50  
- deux roues (6) montées chacune pour tourner autour d'un axe de rotation pratiquement perpendiculaire à l'axe longitudinal de l'assemblage allongé de capteur lorsque l'appareil de transport (1, 1a) est relié à l'assemblage allongé de capteur et,  
55  
- une structure d'orientation (6, 8, 8a, 14) comportant les roues (6) et au moins un relief d'orien-



lation (8, 8a, 14) s'étendant latéralement pour définir une forme ayant un contour transversal avec un centre de rotation (15), les extrémités latérales de la structure d'orientation (6, 8, 8a, 14) étant pratiquement situées sur une courbe essentiellement circulaire centrée sur le centre de rotation (15), et en utilisation, la rotation relative entre l'appareil de transport de capteur et l'assemblage allongé de capteur est bloqué en utilisation et le centre de rotation est décalé par rapport au centre de masse (2a) de l'assemblage allongé de capteur,

**appareil caractérisé en ce que**

le relief de rotation (8, 8a, 14) est configuré de façon qu'en utilisation, l'assemblage allongé de capteur (2) soit dans une position instable lorsque le relief de rotation (8) est en contact avec le côté inférieur du forage et l'assemblage allongé de capteur est configuré pour tourner naturellement à partir de cette position instable pour que l'appareil de transport de capteur s'oriente dans la position la plus stable, le centre de masse de l'assemblage allongé de capteur étant en dessous du centre de rotation de l'appareil de transport de capteur et l'assemblage allongé de capteur est porté par les roues de l'assemblage de transport, en contact avec le côté inférieur du forage.

2. Appareil de transport de capteur selon la revendication 1, dans lequel, en utilisation, l'axe de rotation de chacune des roues (6) est au-dessus du centre de masse (2a) de l'assemblage allongé de capteur lorsque l'appareil de transport de capteur (1a) est pratiquement horizontal.
3. Appareil de transport de capteur selon l'une quelconque des revendications précédentes, dans lequel la structure d'orientation (6, 8, 8a, 14) comporte plusieurs reliefs d'orientation (8, 8a, 14).
4. Appareil de transport de capteur selon la revendication 3, dans lequel les reliefs d'orientation (8a, 14) fonctionnent également comme structure de protection pour protéger les roues.
5. Appareil de transport de capteur selon l'une quelconque des revendications précédentes, dans lequel les roues (6) sont montées sur des paliers (10, 110, 61, 61a) et l'appareil (1) comporte en outre un distributeur de lubrifiant (300) qui alimente en lubrifiant les paliers (10, 110, 61, 61a) à une pression supérieure à la pression ambiante dans le forage.

6. Appareil de transport de capteur selon la revendication 1, dans lequel la structure d'engagement (5) entoure partiellement la surface extérieure de l'assemblage allongé de capteur sans entourer complètement cet assemblage allongé de capteur.
7. Appareil de transport de capteur selon l'une quelconque des revendications précédentes, dans lequel des axes de rotation des deux roues sont pratiquement parallèles et coplanaires.
8. Appareil de transport de capteur selon l'une quelconque des revendications précédentes, dans lequel la structure d'orientation comporte au moins une structure de protection (8a) qui s'étend longitudinalement autour de la roue (6) pour ainsi éviter pratiquement qu'un côté (6a) de la roue n'entre en contact avec la paroi du forage, la roue (6) dépassant la structure de protection (8a) par le dessus et le dessous.
9. Appareil de transport de capteur selon la revendication 8, dans lequel la structure de protection (8a) a une hauteur inférieure au rayon de roue (6).
10. Appareil de transport de capteur selon la revendication 8 ou 9, dans lequel il y a du jeu d'au moins 4 mm entre :
  - une surface (6b) de la roue (6) et à la fois le corps entourant l'appareil (1) et la structure d'orientation ou
  - une surface (6b) de la roue (6) et l'assemblage allongé de capteur et/ou
  - une surface de roue (6a) qui est à l'extrémité radiale de la roue (6) par rapport à l'axe de rotation et une surface intérieure de la structure de protection (8a).
11. Appareil de transport de capteur selon l'une revendication 8 à 10, dans lequel la structure de protection (8a) comporte des reliefs d'orientation (8a) amovibles qui s'étendent à partir de l'avant des roues (6) autour de la surface extérieure (6a) des roues (6).
12. Appareil de transport de capteur selon l'une quelconque des revendications précédentes et un dispositif de guidage (21) comportant une base (27) pour s'engager à l'extrémité de l'assemblage allongé

de capteur et une partie de bec (22, 23) ayant une extrémité (36) décalée par rapport à l'axe longitudinal de l'assemblage allongé de capteur lorsque le dispositif de guidage (21) coopère avec l'assemblage de capteur, et en utilisation, la structure d'orientation (6, 8, 8a, 14) orientant le dispositif de guidage (21) dans le forage est telle que l'inclinaison relevée de la partie de bec (22, 23) garantit que l'extrémité (36) de la partie de bec (22, 23) soit relevée au-dessus du côté inférieur (3a) du forage, d'une hauteur et d'un décalage à partir de l'axe longitudinal et au-dessus de celui-ci de l'assemblage allongé de capteur (2).


13. Assemblage allongé de capteur (2) utilisé pour la mise en place d'un câble dans le forage et un appareil de transport de capteur (1, la) selon l'une quelconque des revendications 1 à 11, relié à l'assemblage allongé de capteur (2), l'assemblage allongé de capteur (2) comportant un outil d'échantillonnage (66) pour prendre des échantillons et faire des mesures de pression, en étant orienté pour prendre un échantillon du côté haut du forage, l'appareil de transport de capteur (1, la) étant dans une orientation stable.

14. Segment d'outil pour être utilisé dans une application de mise en place de câbles dans un forage comprenant


- un assemblage allongé de capteur (2),
- l'appareil de transport de capteur (1, la) selon l'une quelconque des revendications 1 à 11 et
- un dispositif de guidage (21) pour guider l'assemblage allongé de capteur (2) dans le forage, dispositif de guidage (21) comprenant une base (27) reliée à une extrémité de l'assemblage allongé de capteur (2) et une partie de bec (23) ayant une extrémité (36) décalée par rapport à l'axe longitudinal de l'assemblage allongé de capteur (2) et, en utilisation, la structure d'orientation (6, 8, 8a, 14, 208) oriente le dispositif de guidage (21) dans le forage pour que l'inclinaison relevée de la partie de bec (23) assure que l'extrémité (36) de la partie de bec (23) soit relevée au-dessus du côté bas (3a) du forage, d'une hauteur et d'un décalage par rapport et au-dessus de l'axe longitudinal de l'assemblage allongé de capteur (2).

15. Segment d'outil selon la revendication 13, dans lequel la partie de bec (23) avec son extrémité (36) est en saillie par rapport à la base (27) suivant un angle fixe qui est décalé par rapport à l'axe longitudinal du segment d'outil lorsque le dispositif de guidage (21) est relié à l'assemblage allongé de capteur (2).

16. Segment d'outil selon la revendication 14, dans lequel le dispositif de guidage (21) comporte un organe de verrouillage (31) muni d'un ensemble d'orifices de broches de verrouillage (34a) et la base (27) comporte un ensemble d'orifices de broche de verrouillage (34b) pour verrouiller la partie de bec (23) selon un réglage angulaire présélectionné avec les broches de verrouillage (34).



**Figure 1**







Figure 3



### Figure 4

### Section A-A




Figure 5

Section A-A




Figure 6a






Figure 6b





**Figure 7**



**Figure 8**





Figure 9






Figure 11




Figure 12






Figure 14



**Figure 15**




Figure 16




Figure 17






Figure 18







**Figure 19**




**Figure 20**







**Figure 21**



**Figure 22**



**Figure 23**






Figure 28




Figure 29







Figure 30





**Figure 32**





**Figure 33**







Figure 34



**Figure 35**






Figure 38





Figure 39



**Figure 40**




Figure 41






Figure 42






**Figure 43**



**Figure 44**



**Figure 45**




Figure 46




Figure 47




Figure 48




Figure 49

REFERENCES CITED IN THE DESCRIPTION

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

Patent documents cited in the description

- US 7866384 B [0007]
- US 7395881 B [0007]
- US 20120061098 A [0007] [0014]
- US 8011429 B [0010]
- US 2013248208 A [0010]
- FR 2898635 [0012]
- US 684732 A [0013]
- US 4474235 A [0014]
- WO 2010106312 PCT [0014]
- US 20120222857 A [0014]
- US 20090145596 A [0017]
- US 7757782 B [0017]