HCCA for Token-Efficient Repository Repair

HCCA Project

https://github.com/klarisaka/HCCA-Official

November 12, 2026

Abstract

Repeated code inspection, test output, and execution recovery can make the input history of a coding agent expensive. HCCA assigns reading and execution work to independent worker contexts backed by shared role prompts, with planning and integration handled by a parent agent. We report a frozen direct-executor configuration on all 50 tasks in a community-selected SWE-bench Verified Mini dataset. HCCA v7 resolves 36 tasks, while a reused DeepSeek Harness minimal baseline resolves 35. One HCCA task is unfinished and receives zero credit in the 50-task denominator. HCCA uses 1,301 model requests, 36.811 million input tokens and 0.654 million output tokens, with 97.3906% of input reported as cached. At common off-peak token prices, its normalized cost is $0.644212152, compared with a baseline known-complete cost of at least $3.062054268. Both runs use the GXWTF endpoint, the `deepseek-v4.1-flash` model alias and two concurrent tasks. HCCA's role policy configures thinking/planning and analysts at high effort and execution/reading at low. This direct-executor run records 1,301 low and zero high requests. The baseline uses high. The observations support an economical configuration on this manifest. They leave the separate contributions of context design, prompts, tools and reasoning effort unresolved.

1 Introduction

Repository repair requires a coding agent to connect an issue description to source code, make a change and test the resulting behavior. Each stage produces material that may enter later model requests. A failed command can add a second command, an explanation, and another output block. If every later request contains this history, input consumption grows even when the final patch is small. Provider-side prompt caching can reduce the price of repeated input, while the total token volume and cache-miss volume remain important accounting quantities.

HCCA organizes this work around reusable reader, executor and analyst roles. A parent selects a bounded assignment and receives a compact result with evidence references. The worker retains the detailed interaction needed for its assignment. Shared role instructions provide a stable initial prompt segment, and task details enter the subsequent conversation. This design is intended to reduce the amount of execution history that must return to a planning context.

The present experiment concerns the direct-executor path through that runtime. The local Root dispatcher invokes a low-effort executor immediately for each repository issue, using the frozen configuration described in Section 3.

We examine task resolution, complete token accounting, cache reuse, output composition and normalized monetary cost. We compare HCCA v7 with an already completed minimal DeepSeek Harness (DSH) run on the same 50-task manifest. Both systems use the same provider and model alias, with separate run dates and different reasoning-effort settings. We retain the unfinished task in all aggregate denominators and include its consumed tokens in cost.

2 Runtime design

2.1 Shared roles and independent task contexts

HCCA stores reusable reader and executor role configurations in a global agent configuration directory. A newly delegated task receives the role instructions and an assignment envelope. The worker then accumulates its own assistant and tool messages. These role configurations can be reused across projects, while each assignment starts a fresh conversation.

Readers inspect source and other necessary files. Executors inspect code, modify the workspace, run commands and adapt to observed failures. Analysts support reasoning and further delegation. Root and analysts can each invoke an executor and receive its result in their own task context. The caller inspects the evidence and chooses subsequent

assignments. Readers follow the same parent-return relationship. Available execution modes and write tools follow the task's permissions. User guidance enters the parent, which determines the affected children and forwards relevant instructions. These are runtime capabilities. User-guided intervention and hierarchical decomposition were outside the measured direct-executor protocol.

The current distribution offers a standalone Root and a DSH integration in which the DSH conversation acts as Root. The benchmark uses the frozen standalone code path. The versioned results identify that source separately from the repackaged HCCA Official 0.2.1 distribution.

2.2 Executor interaction

The executor has native file listing, reading and search tools, a command tool, and a structured report tool. Inspection outputs are bounded by the tool implementation. Command results expose exit status and selected output, giving the executor evidence for correction. Multiple tools can be requested in one model response, reducing the number of model turns needed to obtain independent observations. The frozen implementation executes those tool calls sequentially.

A worker can revise a command or approach after failure within the same task context. Completion checks inspect execution evidence, outstanding tool errors, workspace changes and the submitted result. Official SWE-bench evaluation provides the task-resolution outcome after generation. The runtime's internal completion status and the official result therefore serve distinct purposes.

The soft executor context budget is a local estimate. When the estimated conversation size exceeds the budget, the implementation removes oldest complete exchanges while retaining the initial instructions. The estimator approximates non-CJK text at four characters per token and counts CJK characters separately. Provider-reported token usage is used for all empirical accounting.




Figure 1: Runtime delegation and return loops. Each executor assignment has its own context and returns evidence to its requesting parent. This benchmark uses the direct Root-to-executor route with local Root dispatch and low execution effort.

3 Experimental protocol

3.1 Tasks and outcome definition

SWE-bench evaluates issue resolution in real repositories through executable tests [1]. We use every entry, in original order, from `MariusHobbhahn/swe-bench-verified-mini`, a community-selected dataset containing 50 tasks drawn from SWE-bench Verified [2]. The fixed manifest hash is published with the result summary. The scope of the reported 72% HCCA resolution rate is these 50 selected tasks.

Each task starts from its specified base commit and issue text. Agent access is restricted to the provided repository, issue and preinstalled dependencies. The agent container has networking disabled. Host-side infrastructure relays model requests, keeping model credentials outside the task container. Agents receive no historical answers or patches. Official evaluation uses the generated prediction against the SWE-bench task tests.

Let $r_i = 1$ for an official resolved result and $r_i = 0$ otherwise. An unfinished task also receives $r_i = 0$. The reported score is

$$R = \frac{1}{50} \sum_{i=1}^{50} r_i. \tag{1}$$

HCCA has 49 official reports and one unfinished task. Its official reports contain 36 resolved and 13 unresolved outcomes. The unfinished task has no official result and contributes zero credit. Its 17 model requests and all associated token usage remain in the HCCA aggregate.

3.2 Configurations and provenance

The HCCA run uses a frozen v7 runtime and a run-local provider and scheduling adapter. The source inventory contains 41 runtime files and 10 original operations files, all checked against the frozen manifest. The adapter selects GXWTF and the recorded model alias, uses two concurrent task slots and routes requests through a dedicated relay. Each task has at most one outstanding model request. Generation and evaluation share the two task slots. The dedicated relay uses a process-local certificate-validation compatibility setting for the gateway's expired certificate, recorded in the configuration.

The DSH comparator is the completed minimal-profile baseline [3]. It is reused without additional baseline generation. Both arms use GXWTF and `deepseek-v4.1-flash`, with two tasks concurrently. This is a sequential comparison of two configurations run on separate dates. The public records retain each arm's timing and source identities.

Setting	HCCA frozen v7	DSH minimal baseline
Provider and model alias	GXWTF, `deepseek-v4.1-flash`	
Concurrent tasks	2	2
Configured reasoning policy	Mixed by role	Single high-effort agent
Thinking/planning and analyst effort	high	—
Executor/reader effort	low	—
Observed benchmark request effort	1,301 low, 0 high	baseline high
Initial model-planning stage	omitted	native minimal loop
Run date, UTC	November 12, 2026	November 11, 2026
Active task time budget	4,800 seconds	4,800 seconds
Requested output token ceiling	omitted	omitted
Temperature and seed	omitted	server defaults

Table 1: Recorded experiment settings. The HCCA mixed role policy includes high thinking/planning and analyst roles and low executor/reader roles. The direct execution path produced 1,301 low requests and zero high requests. DSH uses one high-effort agent. The context budget is a local estimate.

The HCCA soft executor context budget is 524,288 estimated tokens. The executor starts directly, with no fixed planning-model call. Unlimited executor rounds and shared calls remain subject to a 4,800-second active-runner deadline. Preparation and official evaluation occur outside this budget. Both arms omit client-specified model-output token caps. For this HCCA run, the request adapter also omits temperature and seed.

3.3 Accounting

We reconcile HCCA runtime transport-attempt records with per-task request exports and the dedicated relay, and obtain resolution from explicit official report booleans. Each actual request belongs to the current frozen run, including requests from failed or unfinished tasks. Earlier development runs are outside these totals.

HCCA has 1,301 requests with complete usage. The baseline has 2,014 actual requests, including 2,013 complete usage records and one partial record. Baseline token aggregates below sum the complete records. The unobserved usage of the partial record remains unknown. Exact baseline token totals and cost therefore remain unknown.

We use common off-peak normalization at the experiment's archived rates, in USD per million tokens, of 0.003 for cached input, 0.15 for uncached input and 0.60 for output [4]. For counts I_c, I_u and O, the normalized cost is

$$C = \frac{0.003I_c + 0.15I_u + 0.60O}{10^6}. \tag{2}$$

Provider-reported reasoning tokens are included in O once. The normalized cost is an accounting comparison at fixed prices. Actual GXWTF billing is a separate quantity. Because the baseline has one partial record, we report its known-complete cost as a lower bound.

4 Results

HCCA resolves 72% of the fixed manifest and DSH resolves 70%. The one-task difference is small. The paired task outcomes are provided in the public per-task accounting file. Both systems resolve 33 tasks, HCCA alone resolves 3, DSH alone resolves 2, and neither resolves 12.

The HCCA phase runs from 11:58:43 to 12:58:53 UTC on November 12, 2026, approximately 60 minutes 9.6 seconds including generation and evaluation. The reused baseline's model-request window is 04:13:28 to 09:00:27 UTC on

Metric	HCCA v7	DSH minimal high
Resolved / all tasks	36 / 50	35 / 50
Officially evaluated	49	50
Unfinished	1	0
Actual model requests	1,301	2,014
Complete / partial usage records	1,301 / 0	2,013 / 1
Input tokens	36,810,516	106,265,446
Cached input tokens	35,849,984	104,137,856
Uncached input tokens	960,532	2,127,590
Cached share of recorded input	97.3906%	97.9979%
Output tokens, including reasoning	654,304	4,050,837
Reasoning tokens within output	408,903	3,690,753
Other output tokens	245,401	360,084
Normalized cost, USD	0.644212152	≥3.062054268

Table 2: Full-manifest outcomes and usage. DSH token counts and cache share refer to its 2,013 complete records. Its remaining partial record is excluded from these sums and retains unknown usage. All HCCA usage, including the unfinished task, is included.

November 11. Preparation, evaluation and host conditions affect elapsed time, so these windows carry their recorded timing scope.

HCCA's 0.644212152 USD normalized cost is at most 21.1% of the baseline's known-complete cost. This establishes at least a 78.9% normalized-cost reduction for the observed configurations, with baseline missing usage increasing the baseline total if recovered. HCCA's normalized cost per resolved task is $0.017895, while the baseline's known-complete cost per resolved task is at least $0.087487.

Relative to the baseline's complete usage records, HCCA consumes approximately 65.4% fewer input tokens and 83.8% fewer output tokens. It makes 35.4% fewer actual requests. Both systems obtain substantial provider-reported cache reuse. The cached share of recorded input is 97.3906% for HCCA and 97.9979% for DSH.




Figure 2: Input, output and normalized-cost composition. DSH bars show the known-complete usage minimum. Reasoning is already part of output. Input categories and output are priced separately using Equation 2.

5 Interpreting token consumption

5.1 Request count and input size

Total input is the sum of prompt sizes over requests. Consequently, both the number of requests and the average input per request affect token consumption. Across its complete records, HCCA averages approximately 28,294 input tokens per request. DSH's 2,013 complete records average approximately 52,790 input tokens per request. These are request-weighted averages over repeated conversation histories. They do not measure unique repository text or the number of bytes a user supplied.

The observed input reduction combines fewer requests with smaller average requests. Shared worker prefixes and local execution history provide a mechanism for limiting what must enter a parent context. The direct-executor route also avoids a fixed planning pass. This experiment changes several properties together, so it does not identify a separate numerical contribution for either mechanism.

5.2 Cache reuse and monetary contribution

Provider-reported cache counters quantify the portion of input charged at the cached rate. Both arms have a high cached share, with the baseline's recorded share higher than HCCA's. HCCA has lower cached and uncached input totals in absolute terms. This combination explains how a configuration can consume less input while having a slightly lower cache-hit fraction.

A shared prompt is an implementation property, whereas a provider cache hit is an observation about serving behavior. Cache counters alone cannot reveal the exact prefix that was reused or attribute hits to a particular instruction. The source and configuration record establishes the intended stable-prefix layout. The experiment establishes aggregate cache reuse reported by GXWTF. Direct byte-level prefix and cache-placement measurements would be needed to estimate a causal caching benefit.

At the normalization rates, HCCA's cost divides into approximately $0.107550 for cached input, $0.144080 for uncached input and $0.392582 for output. Output therefore represents about 60.9% of its normalized cost. The same rates make output about 79.4% of the baseline's known-complete cost. The relative weights depend on the chosen common prices.

5.3 Reasoning and other output

HCCA's 654,304 output tokens include 408,903 reasoning tokens. The baseline's complete records contain 4,050,837 output tokens, including 3,690,753 reasoning tokens. The corresponding other-output counts are 245,401 and 360,084. We derive these counts by subtraction from provider usage, and the category can include tool-call arguments as well as visible text.

Approximately 96.6% of the output-token difference between the recorded aggregates is in the provider's reasoning field. Reasoning represents 62.5% of HCCA output and 91.1% of baseline output. This arithmetic makes the low-versus-high reasoning-effort difference a material interpretation issue. Prompts, tools, number of turns and repair trajectories also differ. An equal-effort ablation would be needed to estimate the portion caused by context organization alone.

6 Limitations and reproducibility

6.1 Scope of inference

This is one run per configuration on a fixed community-selected 50-task dataset. The tasks and their repository distribution can influence both accuracy and cost. A one-task resolution advantage on this manifest offers limited evidence about the ordering of the systems on other tasks. Paired outcomes are reported to make the comparison inspectable. Repeated trials and a larger independently specified task set would quantify variability.

Earlier runtime versions were iteratively developed and evaluated on this same manifest. The present comparison is a development-benchmark measurement.

The configurations share an endpoint, model alias and task-concurrency setting. They differ in reasoning effort, prompts, tool interfaces, history management and execution policy, and were run on different dates. A model alias does not establish identical underlying serving weights across dates. The baseline is reused, so provider state and host conditions were not synchronized.

The current run exercises direct execution. It leaves reader isolation, multi-level decomposition, multiple collaborating workers and interactive user guidance without benchmark-specific efficacy estimates. HCCA Official 0.2.1 also includes packaging and Windows/DSH integration work beyond the frozen snapshot. Those distribution features require their own evaluation.

The unfinished task receives zero score credit, and all observed usage is included. Its missing official result is retained as null in the public data, alongside a zero score contribution. Baseline partial usage remains unknown. These choices preserve the fixed denominator and observed expenditure.

6.2 Published artifacts

The repository publishes a versioned summary, one accounting row per task, this paper and its XeLaTeX source [5]. The records include task identifiers, explicit outcomes, complete-usage counts, request totals, normalized-cost components and provenance hashes. The source inventory hash identifies the frozen runtime independently of subsequent distribution releases. Historical v6 results retain their own filenames and configurations.

Raw task data, repository images, API credentials and full model traces are maintained separately from the lightweight public distribution. Public hashes provide provenance anchors. Re-execution additionally requires the exact task data, prepared repositories, provider access and a matching runtime snapshot. Preparation, generation, official evaluation and usage aggregation are distinct steps in the recorded workflow.

The machine-readable summary links the verified source inventory and task manifest to per-task results and run timestamps. Terminal accounting closes the run as 49 evaluated tasks and one unfinished task.

7 Conclusion

On the fixed 50-task community Verified Mini manifest, frozen HCCA v7 resolves 36 tasks at $0.644212152 normalized cost, including one unfinished task in the denominator and all consumed usage. The reused DSH minimal high baseline resolves 35 tasks with known-complete normalized cost of at least $3.062054268. HCCA uses fewer requests, smaller average input requests and less reported reasoning output in this comparison. Both configurations obtain high provider-reported input-cache reuse.

References

[1] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press and Karthik R. Narasimhan. *SWE-bench: Can Language Models Resolve Real-World GitHub Issues?* ICLR, 2024. https://openreview.net/forum?id=VTF8yNQM66.

[2] Marius Hobbhahn. *swe-bench-verified-mini*. Dataset repository. https://huggingface.co/datasets/MariusHobbhahn/swe-bench-verified-mini. Fixed task manifest and data hashes accompany this report.

[3] DeepSeek-AI. *DeepSeek Harness*. 2026. https://github.com/deepseek-ai/deepseek-harness. The experiment reuses the project's recorded minimal high-effort baseline.

[4] DeepSeek. *Models and Pricing*. https://api-docs.deepseek.com/quick_start/pricing/. Common off-peak rates are frozen in the experiment's published accounting.

[5] HCCA Project. *Frozen-v7 Verified Mini results and accounting*. November 12, 2026. https://github.com/klarisaka/HCCA-Official/blob/main/reports/verified50-hcca-v7-vs-dsh-2026-11-12-summary.json. Runtime distribution at https://github.com/klarisaka/HCCA-Official.