## NAME

SLogPAtomTypes

## **SYNOPSIS**

```
use AtomTypes::SLogPAtomTypes;
use AtomTypes::SLogPAtomTypes qw(:all);
```

## DESCRIPTION

SLogPAtomTypes class provides the following methods:

new, AssignAtomTypes, GetAllPossibleSLogPAtomTypes, GetAllPossibleSLogPNonHydrogenAtomTypes, GetSLogPAtomTypesData, StringifySLogPAtomTypes

The following functions are available:

 $Get All Possible SLog PA tom Types, \ Get All Possible SLog PN on Hydrogen Atom Types, \ Get SLog PA tom Types Data and the property of the$ 

SLogPAtomTypes is derived from AtomTypes class which in turn is derived from ObjectProperty base class that provides methods not explicitly defined in SLogPAtomTypes, AtomTypes or ObjectProperty classes using Perl's AUTOLOAD functionality. These methods are generated on-the-fly for a specified object property:

```
Set<PropertyName>(<PropertyValue>);
$PropertyValue = Get<PropertyName>();
Delete<PropertyName>();
```

The data file SLogPAomTypes.csv distributed with MayaChemTools release contains all possible SLogP [ Ref 89 ] atom types.

Examples of SLogP atom types:

```
C1, C2, C3, N1, N2, O1, O2 and so on
```

# **METHODS**

new

```
\verb§NewSLogPAtomTypes = new AtomTypes::SLogPAtomTypes(\$NamesAndValues);
```

Using specified *SLogPAtomTypes* property names and values hash, new method creates a new object and returns a reference to newly created SLogPAtomTypes object. By default, the following properties are initialized:

```
Molecule = ''
Type = 'SLogP'
IgnoreHydrogens = 0
```

## Examples:

# AssignAtomTypes

```
$SLogPAtomTypes->AssignAtomTypes();
```

Assigns SLogP atom types to all the atoms in a molecule and returns SLogPAtomTypes.

# ${\sf GetAIIPossibleSLogPAtomTypes}$

Returns all possible SLogP atom types corresponding to hydrogen and non-hydrogen atoms as an array reference.

GetAllPossibleSLogPNonHydrogenAtomTypes

```
$AtomTypesDataRef = $SLogPAtomTypes->
```

Returns all possible SLogP atom types corresponding to non-hydrogen atoms as an array reference.

## GetSLogPAtomTypesData

```
$AtomTypesDataMapRef = $SLogPAtomTypes->GetSLogPAtomTypesData();
$AtomTypesDataMapRef = AtomTypes::SLogPAtomTypes::GetSLogPAtomTypesData();
```

Returns SLogP atom types and associated data loaded from SLogP data file as a reference to hash with the following hash data format:

# ${\it Stringify SLogPAtom Types}$

```
$String = $SLogPAtomTypes->StringifySLogPAtomTypes();
```

Returns a string containing information about SLogPAtomTypes object.

#### **AUTHOR**

Manish Sud <msud@san.rr.com>

# **SEE ALSO**

AtomTypes.pm, AtomicInvariantsAtomTypes.pm, DREIDINGAtomTypes.pm, EStateAtomTypes.pm, FunctionalClassAtomTypes.pm, MMFF94AtomTypes.pm, SYBYLAtomTypes.pm, TPSAAtomTypes.pm, UFFAtomTypes.pm

## **COPYRIGHT**

Copyright (C) 2020 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.