



Tool Order : O.1032523.107-85-4-1-FDP, Partially Rejected, PETROBRAS BRASIL, WEST CARINA, 8-BUZ-108DA-RJS

Header

GENERAL INFORMATION

Client: PETROBRAS BRASIL
Rig: WEST CARINA
Well: 8-BUZ-108DA-RJS
Version no.: 3C-5T-0D

SERVICE QUALITY GROUP

FSM DD: IBalderrama **Sales rep:**
FSM VSilverio **Drill**
MWD: **Engg:**
SDM **COR:**
Cell
Name:
Created By: VSilverio on 20 Nov 2025 09:05 AM
Updated By: FReis4 on 29 Jan 2026 02:33 PM

SHIPPING INFORMATION

TCO Priority:	Confirmed	Shipping Instructions:	Ship to PDOCAS - Boats days ending on 01 and 06	Truck Company:
Dock Name:		Dock Phone:		County:
Planned Ship Date:	09 Feb 2026	Field:		Country/Region:
State/Province:		Basin/Project:		Well Latitude/Longitude:

WELL PARAMETERS

Hole Size:	215.899 (mm)	BHA To Go:	true	Bore Hole:	4
Bit Type:		Sea Depth:	(m)	Start Depth MD:	(m)
End Depth MD:	6507 (m)	End Depth TVD:	6355 (m)	Inclination:	0 (Degree)
Azimuth:	(Degree)	Min Planned Flow Rate:	90.849 (m3/hr)	Max Planned Flow Rate:	131.732 (m3/hr)
Min BH Circ Temp:	303.15 (K)	Max BH Circ Temp:	372.15 (K)	Max BH Static Temp:	382.15 (K)
Max Surface Temp:	(K)	Max BH Pressure:	340.313 (ATM)	Max StandPipe Pressure:	(ATM)
Max DLS:	3 (deg/30m)	Mud Type:	Water Based Mud (WBM)	Mud Density:	9.699 (lb/gal)
Mud Viscosity:	0 (CP)	Mud PV:	0 (CP)	Mud PV Temp:	(K)
High Temperature:	false	High Pressure:	false	High Mud Density:	false
High Dogleg:	false	High Shock:	false	Corrosive Environment:	true
Max Magnetic Spacing:		Maxwell Version:		HSPM Version:	

ToolScope Version:	RX 5/6 Version:	Connect BHA (Heisenberg) Version:
Connect BHA Version:		

INSPECTION PARAMETERS					
Inspection Company:	Drilco	Monitoring Company:	Not Required	Inspection Level:	DS-1 Cat 3-5 Edition 4
Inspection Paperwork:	YES				

ADDITIONAL INFORMATION		
Comments:	Basket test required:	true

Tools					
		Status	Redirect	Transport Type	Assigned Toolset
O.1032523.107-85-4-1-FDP		Partially Rejected			
Batteries					
Field Replaceable Batteries					
Quantity : 1 (StethoScope 6/8 Battery)					
StethoScope 6/8 Battery		Accepted			
Additional Tool Specific Instructions (PLEASE READ) comments	N/A		Battery Status	New	
	N/A		FMP Comment	N/A	
Submitted by VSilverio on 20-Nov-2025 09:28					
Quantity : 1 (StethoScope 6/8 Battery)					
StethoScope 6/8 Battery		Accepted			
Additional Tool Specific Instructions (PLEASE READ) comments	N/A		Battery Status	New	
	N/A		FMP Comment	N/A	
Submitted by VSilverio on 20-Nov-2025 09:28					
DT Equipment					
Hydra AP Drilling Jars					
Quantity : 1 (DJR-DRLG-HYDRA-0650)					
DJR-DRLG-HYDRA-0650		Redirected	BRMEA2-DTSS	Ship To Job	
Application	Standard environment – Regular Make Up Torque Required		Latch Reqd	NO	
Lift Subs Reqd	NO		Stand Off Reqd	NO	
Third Party Insp Reqd	NO		Additional Tool Specific Instructions (PLEASE READ)	Disparando para cima e para baixo	
DH Connection Type	PIN		DH Connection Size	NC50	
UH Connection Type	BOX		UH Connection Size	NC50	

comments	N/A	FMP Comment	TLM check SN
Submitted by VSilverio on 20-Nov-2025 09:23			
Quantity : 1 (DJR-DRLG-HYDRA-0650)			
DJR-DRLG-HYDRA-0650	Redirected	BRMEA2-DTSS	Ship To Job
Application	Standard environment – Regular Make Up Torque Required	Latch Req'd	NO
Lift Subs Req'd	NO	Stand Off Req'd	NO
Third Party Insp Req'd	NO	Additional Tool Specific Instructions (PLEASE READ)	Disparando para cima e para baixo
DH Connection Type	PIN	DH Connection Size	NC50
UH Connection Type	BOX	UH Connection Size	NC50
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:23			

Directional Drilling			
Motor			
Quantity : 1 (S700M)			
S700M	Accepted	S700M FS70DS0766	
Rotor Nozzle Size	N/A	DH Connection Size	4 1/2 REG
DH Connection Type	BOX	Lift Sub Required	NO
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
If No Select Sleeve Type	N/A	If Yes Stabilizer Size OD	8.375
If Yes Stabilizer Type	IB	Is Stabilization Required	YES
Additional Tool Specific Instructions (PLEASE READ)	S700M 7:8 4.8 GT (c/ Cam. 8 3/8" Espiral • BH=0° • Ported FV)	Bit Type	N/A
Compatibility elastomer-mud tested	YES	Proposed Run Length	100
Bend Angle	0	Fixed/Adjustable Motor Size	Adjustable 700
Lobe Configuration	78_4.8	Rubber Type	DynaPower HR (NBR-HR)
Motor Type	DynaForce	Rotor Nozzle	false
Rotor Coating	Chrome	FMP Comment	N/A
comments	N/A		
Submitted by VSilverio on 20-Nov-2025 09:33			

Rotary Steerable			
Quantity : 1 (PD675 Flow restrictor kit)			
PD675 Flow restrictor kit	Accepted	EQ-A1973 FRK-QSH01647	
Number of Restrictor bodies	1	Restrictor Kit Required	Not Required
Additional Tool Specific Instructions (PLEASE READ)	Enviar somente o Corpo do FR. O restante do Kit será transbordado do NS-29.	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 09:31			

Quantity : 1 (PD675 RT Receiver)			
PD675 RT Receiver	Accepted	PD6SRC-AA SN786816	
Receiver Stabilizer Type	TSP (High Abrasion)	RT Flex Required	NO
UH Connection Size	5 1/2 FH	UH Connection Type	BOX

Additional Tool Specific Instructions (PLEASE READ)	8 3/8" Power Drive Stabilized Receiver	DH Connection Size	4 1/2 IF
DH Connection Type	PIN	Receiver Collar Type	Sleeve Stabilizer
Receiver Float Valve Required	5R GA-Flapper Ported	Receiver Stabilizer Size	8 3/8
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:30			
Quantity : 1 (PD675 RT Receiver)			
PD675 RT Receiver		Accepted	
Receiver Stabilizer Type	TSP (High Abrasion)	RT Flex Required	NO
UH Connection Size	5 1/2 FH	UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	8 3/8" Power Drive Stabilized Receiver	DH Connection Size	4 1/2 IF
DH Connection Type	PIN	Receiver Collar Type	Sleeve Stabilizer
Receiver Float Valve Required	5R GA-Flapper Ported	Receiver Stabilizer Size	8 3/8
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 03-Dec-2025 16:34			
Quantity : 1 (PDX6 675)			
PDX6 675		Accepted	
Vortex Job	NO	Mud Motor Fluid Loss	0 (%)
Reamer/Hole Opener above the PowerDrive	NO	Reamer/hole openner fluid loss	0 (%)
Planned Max Flow Rate	124.905 (m3/hr)	Planned Min Flow Rate	90.84 (m3/hr)
Software Version	V4.6b03	Initial Toolface Setting	Neutral
Other (TF / % / MTF or GTF)	0 deg / 0% / GTF	Gamma Ray Type	Average (PDCU-GA)
D-Point Type	Extended (Current Commercial)	Downlink Configuration	18 & 60sec (FDL)
Transmitter Board Type	iLink Board	RT Transmission Method	Short Hop
X Hop Extension Module	Long Extension Module	RT Receiver Attachment	Shop Torqued
Receiver Collar Type	Sleeve Stabilizer	Receiver Stabilizer Size	8 3/8 - TC
Flex Collar Required	No	Flex Collar Connections	None
UH Connection Type	BOX	UH Connection Size	4 1/2 IF
DH Connection Type	BOX	DH Connection Size	4 1/2 REG
BHA Filter Sub Required	NO	Ditch Magnets Required	None
Float Valve Style	Flapper Ported	Additional Tool Specific Instructions (PLEASE READ)	PD X6 675 AB 8 1/2" Slick CC c/Ported Float // PADIII // Kit Medium Flow // DIP: -44 // DLK Map: Multipage
Bias Unit Size	215.899 (mm)	Bit Made Up In Base	NO
Bias Unit Pad Type	Type III (High Abrasion)	Bias Unit Material	P550
Bias Unit Flow Restrictor	Not Required	Bias Unit Restrictor Kit Required	Yes (for 4 1/2 in API Reg Bit Box)
PowerDrive Dump Kit	NO	Control Collar Type	Slick
Control Collar Connection	NC50 (UH) - NC50 (DH)	Control Collar Material	Standard
Control Collar			

Stabilizer Size	Slick - Hardfaced	PD Control Unit	MF-8B Medium Flow - 8 Blade
Mud Density	9.2 (lb/gal)	Flow Kit	
FMP Comment	N/A	comments	N/A

Submitted by VSilverio on 20-Nov-2025 09:30

Quantity : 1 (PDX6 675)

PDX6 675 Accepted

Vortex Job	NO	Mud Motor Fluid Loss	0 (%)
Reamer/Hole Opener above the PowerDrive	NO	Reamer/hole opener fluid loss	0 (%)
Planned Max Flow Rate	131.718 (m3/hr)	Planned Min Flow Rate	90.84 (m3/hr)
Software Version	V4.6b03	Initial Toolface Setting	Neutral
Other (TF / % / MTF or GTF)	0 deg / 0% / GTF	Gamma Ray Type	Average (PDCU-GA)
D-Point Type	Extended (Current Commercial)	Downlink Configuration	18 & 60sec (FDL)
Transmitter Board Type	iLink Board	RT Transmission Method	Short Hop
X Hop Extension Module	Long Extension Module	RT Receiver Attachment	Shop Torqued
Receiver Collar Type	Sleeve Stabilizer	Receiver Stabilizer Size	8 3/8 - TC
Flex Collar Required	No	Flex Collar Connections	None
UH Connection Type	BOX	UH Connection Size	4 1/2 IF
DH Connection Type	BOX	DH Connection Size	4 1/2 REG
BHA Filter Sub Required	NO	Ditch Magnets Required	None
Float Valve Style	Flapper Ported	Additional Tool Specific Instructions (PLEASE READ)	PD X6 675 AB 8 1/2" Slick CC c/Ported Float // PADIII // Kit Medium Flow // DIP: -44 // DLK Map: Multipage
Bias Unit Size	215.899 (mm)	Bit Made Up In Base	NO
Bias Unit Pad Type	Type III (High Abrasion)	Bias Unit Material	P550
Bias Unit Flow Restrictor	Not Required	Bias Unit Restrictor Kit Required	Yes (for 4 1/2 in API Reg Bit Box)
PowerDrive Dump Kit	NO	Control Collar Type	Slick
Control Collar Connection	NC50 (UH) - NC50 (DH)	Control Collar Material	Standard
Control Collar Stabilizer Size	Slick - Hardfaced	PD Control Unit	MF-8B Medium Flow - 8 Blade
Mud Density	9.7 (lb/gal)	Flow Kit	
FMP Comment	N/A	comments	N/A

Submitted by VSilverio on 03-Dec-2025 16:34

Drilling Tools and Services

Collar

Quantity : 1 (Non-Mag Drill Collar 6)

Non-Mag Drill Collar 6 Accepted

Vendor	N/A	Additional Tool Specific Instructions (PLEASE READ)	NMDC
Collar ID	N/A	Collar OD	171.45 (mm)
Collar Type	Slick	DH Connection Size	4 1/2 IF
DH Connection Type	PIN	Length	9 (m)
Length Tolerance	No Length Sensitive	Material	Monel
Other Length	N/A	UH Connection	

Size	4 1/2 IF	UH Connection Type	BOX
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:28			
Quantity : 1 (Non-Mag Pony DC)			
Non-Mag Pony DC		Accepted	
Collar OD	171.45 (mm)	Collar Type	Slick
DH Connection Size	4 1/2 IF	DH Connection Type	PIN
Material	Monel	Nominal Length	3
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	Non-Mag Pony Collat	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 09:28			
Drilling Equipment			
Quantity : 1 (MudGard Filter)			
MudGard Filter	Redirected	BRMEA2-DTSS	Ship To Job
DH Connection Size	4 1/2 IF	DH Connection Type	PIN
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
Length	2 (m)	Length Tolerance	No Length Sensitive
Sub OD	171.45 (mm)	Downhole Filter Required	YES
Material	Steel	Additional Tool Specific Instructions (PLEASE READ)	6.75" Mud Gard (Filtro de Fundo)
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:21			
Quantity : 1 (MudGard Filter)			
MudGard Filter	Redirected	BRMEA2-DTSS	Ship To Job
DH Connection Size	4 1/2 IF	DH Connection Type	PIN
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
Length	2 (m)	Length Tolerance	No Length Sensitive
Sub OD	171.45 (mm)	Downhole Filter Required	YES
Material	Steel	Additional Tool Specific Instructions (PLEASE READ)	6.75" Mud Gard (Filtro de Fundo)
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:21			
Specialized Tools - WCD-WBPE			
Quantity : 1 (Well Defender 675)			
Well Defender 675	Redirected	BRMEA2-DTSS	Ship To Job
DH Connection Size	NC50	DH Connection Type	PIN
Ball Catcher	YES	Ball Catcher Trapper	NO
Ball Catcher Capacity	30	Ball Bypass Required	NO
UH Connection Size	NC50	UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	6 3/4" Well Defender	comments	N/A

FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:22	

Quantity : 1 (Well Defender 675)

Well Defender 675		Redirected	BRMEA2-DTSS	Ship To Job
DH Connection Size	NC50		DH Connection Type	PIN
Ball Catcher	YES		Ball Catcher Trapper	NO
Ball Catcher Capacity	30		Ball Bypass Required	NO
UH Connection Size	NC50		UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	6 3/4" Well Defender		comments	N/A
FMP Comment	N/A			

Submitted by VSilverio on 20-Nov-2025 09:22

Stabilizers

Quantity : 1 (NB Stabilizer)

NB Stabilizer		Accepted		
Blade Type	Integral Spiral Blade		Bored for Float	YES
DH Connection Size	4 1/2 REG		DH Connection Type	BOX
Float Valve Size	4R		Float Valve Style	GA-Flapper Ported
Length	2 (m)		Length Tolerance	No Length Sensitive
Material	Steel		Other Length	N/A
Stabilizer Body OD	6 3/4		Stabilizer OD	8 3/8
Stabilizer Supplier	SLB		UH Connection Size	4 1/2 IF
UH Connection Type	BOX		Additional Tool Specific Instructions (PLEASE READ)	8 3/8" Near-Bit Stabilizer (Espiral • Ported FV)
comments	N/A		FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 08:40

Quantity : 1 (NB Stabilizer)

NB Stabilizer		Accepted		
Blade Type	Integral Spiral Blade		Bored for Float	YES
DH Connection Size	4 1/2 REG		DH Connection Type	BOX
Float Valve Size	4R		Float Valve Style	GA-Flapper Ported
Length	2 (m)		Length Tolerance	No Length Sensitive
Material	Steel		Other Length	N/A
Stabilizer Body OD	6 3/4		Stabilizer OD	8 3/8
Stabilizer Supplier	SLB		UH Connection Size	4 1/2 IF
UH Connection Type	BOX		Additional Tool Specific Instructions (PLEASE READ)	8 3/8" Near-Bit Stabilizer (Espiral • Ported FV)
comments	N/A		FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 08:40

Quantity : 1 (String Stabilizers)

String Stabilizers		Accepted		
Length	2 (m)		Length Tolerance	No Length Sensitive
Material	Steel		Other Length	N/A
Stabilizer Body OD	6 3/4		Stabilizer OD	8 3/8
Stabilizer Supplier	SLB		Stabilizer Type	Standard Stabilizer
UH Connection Size	4 1/2 IF		UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	8 3/8" String Stabilizer (Espiral)		Blade Type	Integral Spiral Blade

Bored for Float	NO	DH Connection Size	4 1/2 IF
DH Connection Type	PIN	Float Valve Size	Not required
Float Valve Style	Not Required	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 08:41			

Quantity : 1 (String Stabilizers)			
String Stabilizers		Accepted	
Length	2 (m)	Length Tolerance	No Length Sensitive
Material	Steel	Other Length	N/A
Stabilizer Body OD	6 3/4	Stabilizer OD	8 3/8
Stabilizer Supplier	SLB	Stabilizer Type	Standard Stabilizer
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	8 3/8" String Stabilizer (Espiral)	Blade Type	Integral Spiral Blade
Bored for Float	NO	DH Connection Size	4 1/2 IF
DH Connection Type	PIN	Float Valve Size	Not required
Float Valve Style	Not Required	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 08:41			

Quantity : 1 (String Stabilizers)			
String Stabilizers		Accepted	
Length	2 (m)	Length Tolerance	No Length Sensitive
Material	Steel	Other Length	N/A
Stabilizer Body OD	6 3/4	Stabilizer OD	8 3/8
Stabilizer Supplier	SLB	Stabilizer Type	Standard Stabilizer
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	8 3/8" String Stabilizer (Espiral)	Blade Type	Integral Spiral Blade
Bored for Float	NO	DH Connection Size	4 1/2 IF
DH Connection Type	PIN	Float Valve Size	Not required
Float Valve Style	Not Required	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 09:20			

Subs			
Quantity : 1 (Ball Catcher Sub)			
Ball Catcher Sub	Redirected	BRMEA2-DTSS	Ship To Job
Collar ID	69.85 (mm)	DH Connection Size	4 1/2 IF
DH Connection Type	PIN	Material	Steel
Nominal Length	N/A	Tool OD	7
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	BBC para well defender de 7"	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 09:22			

Quantity : 1 (Ball Catcher Sub)			
Ball Catcher Sub	Redirected	BRMEA2-DTSS	Ship To Job
Collar ID	69.85 (mm)	DH Connection Size	4 1/2 IF

DH Connection Type	PIN	Material	Steel
Nominal Length	N/A	Tool OD	7
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
Additional Tool Specific Instructions (PLEASE READ)	BBC para well defender de 7"	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 09:22			

Quantity : 1 (Float Sub)			
Float Sub		Accepted	
DH Connection Size	4 1/2 IF	DH Connection Type	PIN
Float Valve Required	YES	Sub OD	171.45 (mm)
Float Valve Size	5R	Float Valve Style	G-Flapper Non Ported
Length	1 (m)	Length Tolerance	No Length Sensitive
Material	Steel	UH Connection Size	4 1/2 IF
UH Connection Type	BOX	Vendor	SLB
Pressure Test Required	Yes	Minimum Pressure/Time for Test	300psi/5min
Maximum Pressure/Time for Test	2000psi/5min	Additional Tool Specific Instructions (PLEASE READ)	6.75" Float Vlave Non-Ported-Flapper ** Antes do envio para a sonda, deverão passar por testes de estanqueidade, com registro de pressão e tempo, por 5 (cinco) minutos com 300 psi e 5 (cinco) minutos com 2000 psi
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:23			

Quantity : 1 (Float Sub)			
Float Sub		Accepted	
DH Connection Size	4 1/2 IF	DH Connection Type	PIN
Float Valve Required	YES	Sub OD	171.45 (mm)
Float Valve Size	5R	Float Valve Style	G-Flapper Non Ported
Length	1 (m)	Length Tolerance	No Length Sensitive
Material	Steel	UH Connection Size	4 1/2 IF
UH Connection Type	BOX	Vendor	SLB
Pressure Test Required	Yes	Minimum Pressure/Time for Test	300psi/5min
Maximum Pressure/Time for Test	2000psi/5min	Additional Tool Specific Instructions (PLEASE READ)	6.75" Float Vlave Non-Ported-Flapper ** Antes do envio para a sonda, deverão passar por testes de estanqueidade, com registro de pressão e tempo, por 5 (cinco) minutos com 300 psi e 5 (cinco) minutos com 2000 psi
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:23			

Quantity : 1 (Float Sub)			
Float Sub		Accepted	
DH Connection Size	4 1/2 IF	DH Connection Type	PIN
Float Valve Required	YES	Sub OD	171.45 (mm)
Float Valve Size	5R	Float Valve Style	G-Flapper Non Ported
Length	1 (m)	Length Tolerance	No Length Sensitive
Material	Steel	UH Connection	

Size	4 1/2 IF	UH Connection Type	BOX
Vendor	SLB	Pressure Test Required	Yes
Minimum Pressure/Time for Test	300psi/5min	Maximum Pressure/Time for Test	2000psi/5min
Additional Tool Specific Instructions (PLEASE READ)	6.75" Float Valve Non-Ported-Flapper ** Antes do envio para a sonda, deverão passar por testes de estanqueidade, com registro de pressão e tempo, por 5 (cinco) minutos com 300 psi e 5 (cinco) minutos com 2000 psi	comments	N/A
FMP Comment	N/A		

Submitted by VSilverio on 20-Nov-2025 09:23

Quantity : 2 (LWD Crossover Subs)

LWD Crossover Subs #1	Accepted	MSSA-EC 4582063490-6
-----------------------	----------	----------------------

LWD Crossover Subs #2 Accepted

DH Connection Size	5 1/2 FH	DH Connection Type	PIN
Length	0.3 (m)	Length Tolerance	No Length Sensitive
Material	Monel	Sub OD	171.45 (mm)
UH Connection Size	5 1/2 FH	UH Connection Type	PIN
Vendor	SLB	Additional Tool Specific Instructions (PLEASE READ)	Crossover para modificar TerraSphere sem comunicação DH
comments	N/A	FMP Comment [LWD Crossover Subs #1]	N/A
FMP Comment [LWD Crossover Subs #2]	N/A		

Submitted by VSilverio on 20-Nov-2025 09:31

Quantity : 1 (MWD Crossover Subs)

MWD Crossover Subs Accepted

DH Connection Size	4 1/2 IF	DH Connection Type	PIN
Length	0.3 (m)	Length Tolerance	No Length Sensitive
Material	Monel	Sub OD	171.45 (mm)
UH Connection Size	5 1/2 FH	UH Connection Type	PIN
Vendor	SLB	Additional Tool Specific Instructions (PLEASE READ)	DH XO for TeleScope standalone
comments	N/A	FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 09:31

Quantity : 1 (MWD Crossover Subs)

MWD Crossover Subs Accepted

DH Connection Size	5 1/2 FH	DH Connection Type	PIN
Length	0.3 (m)	Length Tolerance	No Length Sensitive
Material	Monel	Sub OD	171.45 (mm)
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
Vendor	SLB	Additional Tool Specific Instructions (PLEASE READ)	UH MWD Crossover for TeleScope standalone
comments	N/A	FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 09:31

Formation Pressure			
Quantity : 1 (TST 675)			
TST 675		Accepted	
Collar Type	Standard	Stabilizer Size	209.549 (mm)
High Drawdown	NO	Packer Material	HNBR90, TST6, PN 100036137
Shock requirement	Non Shock Reduction E-chassis	Software Version	8.7B03
StethoScope 6/8 Batteries	YES	TST Support Kit	TST6 Field Kit
Additional Tool Specific Instructions (PLEASE READ)	StethoScope 675 (c/ camisa 8 1/4") (Pre-testes)	BHA To Go Tool	true
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
DH Connection Size	5 1/2 FH	DH Connection Type	PIN
Extenders	Downhole only	Pressure Rating	0 - 20000 (PSI)
Primary Gauge Type	ACQG (<20K psi)	Backup Gauge Type	Strain Gauge (<25K psi)
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:19			
Quantity : 1 (TST 675)			
TST 675		Accepted	
Collar Type	Standard	Stabilizer Size	209.549 (mm)
High Drawdown	NO	Packer Material	HNBR90, TST6, PN 100036137
Shock requirement	Non Shock Reduction E-chassis	Software Version	8.7B03
StethoScope 6/8 Batteries	YES	TST Support Kit	TST6 Field Kit
Additional Tool Specific Instructions (PLEASE READ)	StethoScope 675 (c/ camisa 8 1/4") (Pre-testes)	BHA To Go Tool	true
UH Connection Size	4 1/2 IF	UH Connection Type	BOX
DH Connection Size	5 1/2 FH	DH Connection Type	PIN
Extenders	Downhole only	Pressure Rating	0 - 20000 (PSI)
Primary Gauge Type	ACQG (<20K psi)	Backup Gauge Type	Strain Gauge (<25K psi)
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:19			
Nuclear			
Quantity : 1 (EcoScope 675)			
EcoScope 675		Accepted	DV6MC-AA 3332
BHA To Go Tool	true	DH Connection Size	5 1/2 FH
DH Connection Type	PIN	EcoScope Nuclear Support Kit Required	YES
Extenders	Downhole & Uphole	NBI (Near Bit Inclination)	NO
Radioactive Source Required	YES	Sigma	YES
Software Version	Queen 8.1	Sourceless Operation	NO
Spectroscopy	YES	Stabilizer OD	8 1/4
UH Connection Size	5 1/2 FH	UH Connection Type	BOX
BHA with Clink	No Clink	Additional Tool Specific Instructions (PLEASE READ)	EcoScope 675 - w/ 8 1/4" Stabilizer
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:07			
Quantity : 1 (EcoScope 675)			
EcoScope 675		Accepted	

BHA To Go Tool	true	DH Connection Size	5 1/2 FH
DH Connection Type	PIN	EcoScope Nuclear Support Kit Required	YES
Extenders	Downhole & Uphole	NBI (Near Bit Inclination) Sigma	NO
Radioactive Source Required	YES		YES
Software Version	Queen 8.1	Sourceless Operation	NO
Spectroscopy	YES	Stabilizer OD	8 1/4
UH Connection Size	5 1/2 FH	UH Connection Type	BOX
BHA with Clink	No Clink	Additional Tool Specific Instructions (PLEASE READ)	EcoScope 675 - w/ 8 1/4" Stabilizer
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:07			
Quantity : 2 (EcoScope FNP)			
EcoScope FNP #1		Released	FNP-BA 5176
EcoScope FNP #2		Released	FNP-BA UD10
Additional Tool Specific Instructions (PLEASE READ)	N/A	comments	N/A
FMP Comment [EcoScope FNP #1]	N/A	FMP Comment [EcoScope FNP #2]	N/A
Submitted by VSilverio on 20-Nov-2025 09:31			
Quantity : 1 (proVISION 675)			
proVISION 675		Accepted	MRT6D-AD V8727
Software Version	3.2	DH Connection Size	5 1/2 FH
DH Connection Type	PIN	Extenders	Downhole & Uphole
proVISION Support kit required	NO	Stabilizer Size	212.725 (mm)
Turbine Configuration	400 - 800	UH Connection Size	5 1/2 FH
UH Connection Type	BOX	Additional Tool Specific Instructions (PLEASE READ)	ProVISION 675 (c/ Cam. 8 3/8" // Flot Kit 400-800 gpm)
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:05			
Quantity : 1 (proVISION 675)			
proVISION 675		Accepted	
Software Version	3.2	DH Connection Size	5 1/2 FH
DH Connection Type	PIN	Extenders	Downhole & Uphole
proVISION Support kit required	NO	Stabilizer Size	212.725 (mm)
Turbine Configuration	400 - 800	UH Connection Size	5 1/2 FH
UH Connection Type	BOX	Additional Tool Specific Instructions (PLEASE READ)	ProVISION 675 (c/ Cam. 8 3/8" // Flot Kit 400-800 gpm)
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:05			
Resistivity			

Quantity : 1 (MicroScope HD 675)			
MicroScope HD 675		Accepted	MI6C-BA 796
Button Measurement Required	YES	DH Connection Size	5 1/2 FH
DH Connection Type	PIN	Extenders	Downhole & Uphole
Lower Stabilizer OD	8.375	Optimal Button Stabilizer OD for Hi Resolution	8.375
Software Version	Egeon 4.1	UH Connection Size	5 1/2 FH
UH Connection Type	BOX	Additional Tool Specific Instructions (PLEASE READ)	MicroScope HD 675 - DHS: 4.1B12
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 08:51			

Quantity : 1 (MicroScope HD 675)			
MicroScope HD 675		Accepted	
Button Measurement Required	YES	DH Connection Size	5 1/2 FH
DH Connection Type	PIN	Extenders	Downhole & Uphole
Lower Stabilizer OD	8.375	Optimal Button Stabilizer OD for Hi Resolution	8.375
Software Version	Egeon 4.1	UH Connection Size	5 1/2 FH
UH Connection Type	BOX	Additional Tool Specific Instructions (PLEASE READ)	MicroScope HD 675 - DHS: 4.1B12
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 08:51			

Quantity : 1 (TerraSphere 675)			
TerraSphere 675		Accepted	KAI6DC-BA 58494311
Mud Type	WBM	Mud Density	9.2 (lb/gal)
Downhole Stabilizer Size	8 3/8	TerraSphere Support Kit Needed	YES
UH Connection Type	BOX	UH Connection Size	5 1/2 FH
DH Connection Type	PIN	DH Connection Size	4 1/2 IF
Extenders	Uphole Only	US Sensor Configurations	US-PE SENSOR, K4, KAI6 (Regular)
EM Sensor Configurations	KAI6 EM ELECTRODE, DUMMY 30 ksi	Software Version	6.0
Additional Tool Specific Instructions (PLEASE READ)	TerraSphere 675 - BHA primário com Near Bit - Sem comunicação DH	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 08:51			

Quantity : 1 (TerraSphere 675)			
TerraSphere 675		Accepted	
Mud Type	WBM	Mud Density	9.2 (lb/gal)
Downhole Stabilizer Size	8 3/8	TerraSphere Support Kit Needed	YES
UH Connection Type	BOX	UH Connection Size	5 1/2 FH
DH Connection Type	PIN	DH Connection Size	4 1/2 IF

Extenders	Uphole Only	US Sensor Configurations	US-PE SENSOR, K4, KAI6 (Regular)
EM Sensor Configurations	KAI6 EM ELECTRODE, DUMMY 30 ksi	Software Version	6.0
Additional Tool Specific Instructions (PLEASE READ)	TerraSphere 675 - BHA primário com Near Bit - Sem comunicação DH	comments	N/A
FMP Comment	N/A		
Submitted by VSilverio on 20-Nov-2025 08:51			

Sonic			
Quantity : 1 (SonicScope 675)			
SonicScope 675		Accepted	MP6DC-BA V7212
Mud Density	9.3 (lb/gal)	AcqStopDelay	N/A
Downlink Enabled	N/A	CFG_Main	N/A
CFG_Slow	N/A	CFG_Medium	N/A
CFG_Fast	N/A	CFG_Salt	N/A
CFG_CE RM	N/A	CFG_PO	N/A
CFG_ADV	N/A	Software Version	8.7
DH Connection Size	5 1/2 FH	DH Connection Type	PIN
Extenders	Downhole & Uphole	Lower Stabilizer OD	8 1/4
LWD Batteries	NO	SonicScope Support Kit Required	NO
UH Connection Size	5 1/2 FH	UH Connection Type	BOX
Upper Stabilizer OD	8 1/4	Additional Tool Specific Instructions (PLEASE READ)	SonicScope 675 (c/ Cam. 8 1/4")
BHA To Go Tool	true	Basket test required?	true
Fishing Diagrams required?	true	Battery loading required?	false
Bit size (in)	215.899 (mm)	SCLP (mud slowness)	N/A
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:17			

Quantity : 1 (SonicScope 675)			
SonicScope 675		Accepted	
Mud Density	9.3 (lb/gal)	AcqStopDelay	N/A
Downlink Enabled	N/A	CFG_Main	N/A
CFG_Slow	N/A	CFG_Medium	N/A
CFG_Fast	N/A	CFG_Salt	N/A
CFG_CE RM	N/A	CFG_PO	N/A
CFG_ADV	N/A	Software Version	8.7
DH Connection Size	5 1/2 FH	DH Connection Type	PIN
Extenders	Downhole & Uphole	Lower Stabilizer OD	8 1/4
LWD Batteries	NO	SonicScope Support Kit Required	NO
UH Connection Size	5 1/2 FH	UH Connection Type	BOX
Upper Stabilizer OD	8 1/4	Additional Tool Specific Instructions (PLEASE READ)	SonicScope 675 (c/ Cam. 8 1/4")
BHA To Go Tool	true	Basket test required?	true
Fishing Diagrams required?	true	Battery loading required?	false
Bit size (in)	215.899 (mm)	SCLP (mud slowness)	N/A
comments	N/A	FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 09:17

Sources

Quantity : 1 (Radioactive Source)

Radioactive Source **Accepted** **GGLS-DA|A3660**

Source type	ECOSCOPE	Rig and Client have valid licenses / authorizations to store and use nuclear Sources	YES
Additional Tool Specific Instructions (PLEASE READ)	N/A	comments	N/A
FMP Comment	N/A		

Submitted by VSilverio on 20-Nov-2025 09:20

Measurements While Drilling

Extenders

Quantity : 1 (Extender)

Extender **Accepted**

Extender Type	Dummy	Additional Tool Specific Instructions (PLEASE READ)	Dummy extender to run TeleScope standalone
comments	N/A	FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 09:31

Quantity : 2 (Extender)

Extender #1 **Accepted** **MEXD-EB|07/016**

Extender #2 **Accepted**

Extender Type	MEXD	Additional Tool Specific Instructions (PLEASE READ)	Extender para modificar TerraSphere que estão sem comunicação DH
comments	N/A	FMP Comment [Extender #1]	N/A
FMP Comment [Extender #2]	N/A		

Submitted by VSilverio on 20-Nov-2025 09:31

Mud Pulse

Quantity : 1 (TeleScope 675)

TeleScope 675 **Accepted**

BHA To Go Tool	true	Reamer/hole opener above theTeleScope	NO
Reamer/hole opener fluid loss	0 (%)	Planned Min Flow Rate	90.84 (m3/hr)
Planned Max Flow Rate	131.718 (m3/hr)	Mud Density	9.7 (lb/gal)
MMA Rotor Type	5.1 Standard (200-1000GPM)	MMA Gap	0.08 (in)
MTA Flow Range	400 - 800 (GPM)	MWD WOB / TOR	YES
MWD PWD	NO	Services	D&I - 4 Axis Shock
High Temperature	false	PMEA modified for 180W capability	NO
Software Version	V14.0C04	Telemetry Mode	QPSK 4 Hz / 8 bps
Total G	N/A	Total H	N/A
Dip Angle	-43 (Degree)	Delayed Survey	NO
Survey on CRPM	NO	TF Switch	Low Inclination (2.5 < incl. < 3.5)
Cessasion			
Extenders	Uphole & Downhole	DH Filter Sub	NO
Collar Type	Non-ROP Collar preferred	DH Connection Size	5 1/2 FH
UH Connection Size	5 1/2 FH	DH Connection Type	PIN

UH Connection Type	BOX	Additional DH Sub for String Connection	NO
Additional UH Sub for String Connection	NO	Stab Saver Sub required	NO
Stabilizer Type	Not Required	Stabilizer Size	N/A
Stabilizer Made Up	NO	Agitator / Agitator Plus (BHA Oscillation System)	NO
High Telemetry Frequency	NO	Zero Gap MMA	NO
Silicate Mud	NO	Special Mud (non-Silicate)	NO
MOC #	N/A	Rotary Switch Enabled	YES
Additional Tool Specific Instructions (PLEASE READ)	TeleScope 675. Flow Kit: 400-800. Gap = 0.08	BR2GO_FSL	N/A
BR2GO_No CRPM check	N/A	BR2GO_Health MODF from run beginning	N/A
BR2GO_Latitude	N/A	BR2GO_Downlink bit time period (sec)	N/A
BR2GO_Send utility frame after	N/A	BR2GO_Magnetic declination	N/A
BR2GO_Collar RPM	N/A	BR2GO_Enable CRPM at start	N/A
BR2GO_Primary configuration	N/A	BR2GO_Send survey after (min)	N/A
BR2GO_Auto survey mode	N/A	BR2GO_TS Marker recording	N/A
BR2GO_BHA	N/A	BR2GO_Health MODF	N/A
Power sharing comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:14			
Quantity : 1 (TeleScope 675)			
TeleScope 675		Accepted	
BHA To Go Tool	true	Reamer/hole opener above theTeleScope	NO
Reamer/hole opener fluid loss	0 (%)	Planned Min Flow Rate	90.84 (m3/hr)
Planned Max Flow Rate	131.718 (m3/hr)	Mud Density	9.7 (lb/gal)
MMA Rotor Type	5.1 Standard (200-1000GPM)	MMA Gap	0.08 (in)
MTA Flow Range	400 - 800 (GPM)	MWD WOB / TOR	YES
MWD PWD	NO	Services	D&I - 4 Axis Shock
High Temperature	false	PMEA modified for 180W capability	NO
Software Version	V14.0C04	Telemetry Mode	QPSK 4 Hz / 8 bps
Total G	N/A	Total H	N/A
Dip Angle	-43 (Degree)	Delayed Survey	NO
Survey on CRPM	NO	TF Switch	Low Inclination (2.5 < incl. < 3.5)
Cessasion			
Extenders	Uphole & Downhole	DH Filter Sub	NO
Collar Type	Non-ROP Collar preferred	DH Connection Size	5 1/2 FH
UH Connection Size	5 1/2 FH	DH Connection Type	PIN
UH Connection Type	BOX	Additional DH Sub for String Connection	NO
Additional UH Sub for String Connection	NO	Stab Saver Sub required	NO
Stabilizer Type	Not Required	Stabilizer Size	N/A

Stabilizer Made Up	NO	Agitator / Agitator Plus (BHA Oscillation System)	NO
High Telemetry Frequency	NO	Zero Gap MMA	NO
Silicate Mud	NO	Special Mud (non-Silicate)	NO
MOC #	N/A	Rotary Switch Enabled	YES
Additional Tool Specific Instructions (PLEASE READ)	TeleScope 675. Flow Kit: 400-800. Gap = 0.08	BR2GO_FSL	N/A
BR2GO_No CRPM check	N/A	BR2GO_Health MODF from run beginning	N/A
BR2GO_Latitude	N/A	BR2GO_Downlink bit time period (sec)	N/A
BR2GO_Send utility frame after	N/A	BR2GO_Magnetic declination	N/A
BR2GO_Collar RPM	N/A	BR2GO_Enable CRPM at start	N/A
BR2GO_Primary configuration	N/A	BR2GO_Send survey after (min)	N/A
BR2GO_Auto survey mode	N/A	BR2GO_TS Marker recording	N/A
BR2GO_BHA Power sharing comments	N/A	BR2GO_Health MODF	N/A
		FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 09:14

Surface

Lifting Equipment

Quantity : 1 (Lifting Subs)

Lifting Subs Accepted

DH Connection Size	5 1/2 FH	DH Connection Type	PIN
Lift Sub Type	Lifting Nubbin	Sub Neck OD	127 (mm)
UH Connection Size	N/A	UH Connection Type	N/A
Vendor	N/A	Additional Tool Specific Instructions (PLEASE READ)	Lifting Sub para ferramentas 5 1/2" FH BOX **ALTERADO PARA 5" a pedido de TLM
comments	N/A	FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 09:28

Quantity : 1 (Lifting Subs)

Lifting Subs Accepted

DH Connection Size	5 1/2 FH	DH Connection Type	PIN
Lift Sub Type	Lifting Nubbin	Sub Neck OD	127 (mm)
UH Connection Size	N/A	UH Connection Type	N/A
Vendor	N/A	Additional Tool Specific Instructions (PLEASE READ)	Lifting Sub para ferramentas 5 1/2" FH BOX **ALTERADO PARA 5" a pedido de TLM
comments	N/A	FMP Comment	N/A

Submitted by VSilverio on 20-Nov-2025 09:28

Support Equipment

Quantity : 1 (EcoScope Source Shield)

EcoScope Source Shield Rejected

comments	N/A	FMP Comment	Not necessary.
----------	-----	-------------	----------------

Submitted by VSilverio on 20-Nov-2025 09:31

Quantity : 1 (OFFSHORE CONTAINER)			
OFFSHORE CONTAINER		Accepted	
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:31			
Quantity : 1 (Overpack)			
Overpack		Accepted GCOB-A 09-05	
comments	N/A	FMP Comment	N/A
Submitted by VSilverio on 20-Nov-2025 09:31			
Quantity : 5 (TRANSPORTATION BASKET)			
TRANSPORTATION BASKET #1		Accepted	
TRANSPORTATION BASKET #2		Accepted	
TRANSPORTATION BASKET #3		Accepted	
TRANSPORTATION BASKET #4		Accepted	
TRANSPORTATION BASKET #5		Accepted	
Additional Tool Specific Instructions (PLEASE READ)	N/A	comments	N/A
FMP Comment [TRANSPORTATION BASKET #1]	N/A	FMP Comment [TRANSPORTATION BASKET #2]	N/A
FMP Comment [TRANSPORTATION BASKET #3]	N/A	FMP Comment [TRANSPORTATION BASKET #4]	N/A
FMP Comment [TRANSPORTATION BASKET #5]	N/A		
Submitted by VSilverio on 20-Nov-2025 09:31			
Tool Op Sup Kits			
Quantity : 1 (EcoScope Support Kit)			
EcoScope Support Kit		Rejected	
Activation Blanket	1	Collar Clamps	1
Collar Shield	1	Flooded EcoScope Kit	1
FNP Handling Tool	2	Green Leaf Key	1
Hazmat Key	1	Hole Cover	1
Radiation Mud Monitor	Not Required	Radiation Survey Meter	2
Remote Handling Tong	1	Source Handling Tool	2
Source Plug removal tool	1	Transfer Shield	1
1 (Qty / Item / Part #)	N/A	10 (Qty / Item / Part #)	N/A
2 (Qty / Item / Part #)	N/A	3 (Qty / Item / Part #)	N/A
4 (Qty / Item / Part #)	N/A	5 (Qty / Item / Part #)	N/A
6 (Qty / Item / Part #)	N/A	7 (Qty / Item / Part #)	N/A
8 (Qty / Item / Part #)	N/A	9 (Qty / Item / Part #)	N/A
Additional Tool Specific Instructions (PLEASE READ)	N/A	comments	N/A
FMP Comment	Not necessary.		
Submitted by VSilverio on 20-Nov-2025 09:31			
Quantity : 1 (TST Support Kit)			
TST Support Kit		Accepted	
COMPLETE			
StethoScope KIT			

BOX (As Per Location Specifications - Additional Items may be added below)	YES	Tool OD	6 3/4
1 (Qty / Item / Part #)	N/A	2 (Qty / Item / Part #)	N/A
3 (Qty / Item / Part #)	N/A	4 (Qty / Item / Part #)	N/A
5 (Qty / Item / Part #)	N/A	6 (Qty / Item / Part #)	N/A
7 (Qty / Item / Part #)	N/A	8 (Qty / Item / Part #)	N/A
9 (Qty / Item / Part #)	N/A	10 (Qty / Item / Part #)	N/A
Additional Tool Specific Instructions (PLEASE READ)	N/A	comments	N/A
FMP Comment	N/A		

Submitted by VSilverio on 20-Nov-2025 09:31

Quantity : 1 (TerraSphere Support Kit)

TerraSphere Support Kit Accepted

TerraSphere Support Kit Needed	XSIM and XRAD	COMPLETE TERRASPHERE KIT BOX (As Per Location Specifications - Additional items may be added below)	YES
1 (Qty / Item / Part #)	N/A	10 (Qty / Item / Part #)	N/A
2 (Qty / Item / Part #)	N/A	3 (Qty / Item / Part #)	N/A
4 (Qty / Item / Part #)	N/A	5 (Qty / Item / Part #)	N/A
6 (Qty / Item / Part #)	N/A	7 (Qty / Item / Part #)	N/A
8 (Qty / Item / Part #)	N/A	9 (Qty / Item / Part #)	N/A
Additional Tool Specific Instructions (PLEASE READ)	N/A	comments	N/A
FMP Comment	N/A		

Submitted by VSilverio on 20-Nov-2025 09:31