

general_ledger

Generated by Doxygen 1.8.1.2

Thu Jun 19 2014 20:57:09

Contents

1	General Ledger.	1
2	Todo List	3
3	Bug List	5
4	Module Index	7
4.1	Modules	7
5	Class Index	9
5.1	Class Hierarchy	9
6	Class Index	11
6.1	Class List	11
7	File Index	13
7.1	File List	13
8	Module Documentation	15
8.1	Program configuration module	15
8.1.1	Detailed Description	15
8.2	Database interaction module	16
8.2.1	Detailed Description	17
8.2.2	Function Documentation	17
8.2.2.1	get_connection	17
8.2.2.2	get_database_type	17
8.2.2.3	get_field_names	17
8.2.2.4	get_row	17
8.3	SQL statements module	19
8.3.1	Detailed Description	19
8.4	General Ledger database module.	20
8.4.1	Detailed Description	20
8.5	General purpose utilities.	21
8.5.1	Detailed Description	21

8.5.2	Function Documentation	21
8.5.2.1	content_lines	21
8.5.2.2	join	21
8.5.2.3	next_content_line	22
8.5.2.4	replace	22
8.5.2.5	split	22
8.5.2.6	split	23
8.5.2.7	split_lines	23
8.5.2.8	trim	23
8.5.2.9	trim_back	23
8.5.2.10	trim_front	24
8.6	Database program.	25
8.6.1	Detailed Description	25
8.6.2	Function Documentation	25
8.6.2.1	check_db_parameters	25
8.6.2.2	check_help_and_version	25
8.6.2.3	login	26
8.6.2.4	main	26
8.6.2.5	set_configuration	26
8.7	Reporting program.	27
8.7.1	Detailed Description	27
8.7.2	Function Documentation	27
8.7.2.1	login	27
8.7.2.2	main	27
8.7.2.3	set_configuration	28
8.8	User administration program.	29
8.8.1	Detailed Description	29
8.8.2	Function Documentation	29
8.8.2.1	check_db_parameters	29
8.8.2.2	check_help_and_version	30
8.8.2.3	check_user_password	30
8.8.2.4	enable_user	30
8.8.2.5	get_user	30
8.8.2.6	login	30
8.8.2.7	main	31
8.8.2.8	set_configuration	31
8.8.2.9	set_user_password	31
8.8.2.10	show_user_details	31

9.1	genleg::Config Class Reference	33
9.1.1	Detailed Description	33
9.1.2	Constructor & Destructor Documentation	33
9.1.2.1	Config	33
9.1.2.2	~Config	34
9.1.3	Member Function Documentation	34
9.1.3.1	add_cmdline_option	34
9.1.3.2	is_set	34
9.1.3.3	operator[]	34
9.1.3.4	populate_from_cmdline	34
9.1.3.5	populate_from_file	35
9.1.4	Member Data Documentation	35
9.1.4.1	m_opts_set	35
9.1.4.2	m_opts_supp	35
9.2	genleg::ConfigBadConfigFile Class Reference	35
9.2.1	Detailed Description	36
9.2.2	Constructor & Destructor Documentation	36
9.2.2.1	ConfigBadConfigFile	36
9.3	genleg::ConfigBadOption Class Reference	37
9.3.1	Detailed Description	37
9.3.2	Constructor & Destructor Documentation	37
9.3.2.1	ConfigBadOption	38
9.4	genleg::ConfigCouldNotOpenFile Class Reference	38
9.4.1	Detailed Description	39
9.4.2	Constructor & Destructor Documentation	39
9.4.2.1	ConfigCouldNotOpenFile	39
9.5	genleg::ConfigException Class Reference	39
9.5.1	Detailed Description	39
9.5.2	Constructor & Destructor Documentation	40
9.5.2.1	ConfigException	40
9.6	genleg::ConfigOptionNotSet Class Reference	40
9.6.1	Detailed Description	41
9.6.2	Constructor & Destructor Documentation	41
9.6.2.1	ConfigOptionNotSet	41
9.7	gldb::DBConn Class Reference	41
9.7.1	Detailed Description	42
9.7.2	Constructor & Destructor Documentation	42
9.7.2.1	DBConn	42
9.7.2.2	DBConn	42
9.7.2.3	DBConn	42

9.7.3	Member Function Documentation	42
9.7.3.1	operator=	42
9.7.3.2	operator=	42
9.7.3.3	query	42
9.7.3.4	select	43
9.7.4	Member Data Documentation	43
9.7.4.1	m_imp	43
9.8	gldb::DBConnCouldNotConnect Class Reference	43
9.8.1	Detailed Description	44
9.8.2	Constructor & Destructor Documentation	44
9.8.2.1	DBConnCouldNotConnect	44
9.9	gldb::DBConnCouldNotQuery Class Reference	44
9.9.1	Detailed Description	45
9.9.2	Constructor & Destructor Documentation	45
9.9.2.1	DBConnCouldNotQuery	45
9.10	gldb::DBConnDummy Class Reference	46
9.10.1	Detailed Description	47
9.10.2	Constructor & Destructor Documentation	47
9.10.2.1	DBConnDummy	47
9.10.2.2	DBConnDummy	47
9.10.2.3	~DBConnDummy	47
9.10.3	Member Function Documentation	47
9.10.3.1	operator=	47
9.10.3.2	query	47
9.10.3.3	select	47
9.11	gldb::DBConnException Class Reference	48
9.11.1	Detailed Description	48
9.11.2	Constructor & Destructor Documentation	48
9.11.2.1	DBConnException	48
9.12	gldb::DBConnImp Class Reference	49
9.12.1	Detailed Description	49
9.12.2	Constructor & Destructor Documentation	49
9.12.2.1	DBConnImp	49
9.12.2.2	~DBConnImp	49
9.12.3	Member Function Documentation	50
9.12.3.1	query	50
9.12.3.2	select	50
9.13	gldb::DBConnMySQL Class Reference	50
9.13.1	Detailed Description	51
9.13.2	Constructor & Destructor Documentation	51

9.13.2.1	DBConnMySQL	51
9.13.2.2	DBConnMySQL	52
9.13.2.3	DBConnMySQL	52
9.13.2.4	~DBConnMySQL	52
9.13.3	Member Function Documentation	52
9.13.3.1	operator=	52
9.13.3.2	operator=	52
9.13.3.3	query	52
9.13.3.4	select	52
9.13.4	Member Data Documentation	53
9.13.4.1	m_conn	53
9.14	genleg::DBSQLDummy Class Reference	53
9.14.1	Detailed Description	54
9.15	genleg::DBSQLMySQL Class Reference	54
9.15.1	Detailed Description	54
9.16	genleg::DBSQLStatements Class Reference	55
9.16.1	Detailed Description	56
9.16.2	Constructor & Destructor Documentation	56
9.16.2.1	DBSQLStatements	56
9.16.2.2	~DBSQLStatements	56
9.16.3	Member Function Documentation	56
9.16.3.1	create_table	56
9.16.3.2	create_view	56
9.16.3.3	drop_table	56
9.16.3.4	drop_view	57
9.16.3.5	get_perms	57
9.16.3.6	grant	57
9.16.3.7	revoke	57
9.16.3.8	update_user	58
9.16.3.9	user_by_id	58
9.16.3.10	user_by_username	58
9.17	genleg::GLDatabase Class Reference	58
9.17.1	Detailed Description	60
9.17.2	Constructor & Destructor Documentation	60
9.17.2.1	GLDatabase	60
9.17.2.2	~GLDatabase	60
9.17.3	Member Function Documentation	60
9.17.3.1	backend	60
9.17.3.2	create_structure	61
9.17.3.3	create_user	61

9.17.3.4	destroy_structure	61
9.17.3.5	get_user_by_id	61
9.17.3.6	get_user_by_username	61
9.17.3.7	grant	62
9.17.3.8	load_sample_data	62
9.17.3.9	revoke	62
9.17.3.10	update_user	62
9.17.4	Member Data Documentation	62
9.17.4.1	m_dbc	63
9.17.4.2	m_sql	63
9.17.4.3	m_tables	63
9.17.4.4	m_views	63
9.18	genleg::GLDBException Class Reference	63
9.18.1	Detailed Description	63
9.18.2	Constructor & Destructor Documentation	63
9.18.2.1	GLDBException	63
9.19	genleg::GLUser Class Reference	64
9.19.1	Detailed Description	65
9.19.2	Constructor & Destructor Documentation	65
9.19.2.1	GLUser	65
9.19.2.2	~GLUser	65
9.19.3	Member Function Documentation	65
9.19.3.1	check_password	66
9.19.3.2	enabled	66
9.19.3.3	firstname	66
9.19.3.4	id	66
9.19.3.5	lastname	66
9.19.3.6	pass_hash	66
9.19.3.7	pass_salt	67
9.19.3.8	permissions	67
9.19.3.9	set_enabled	67
9.19.3.10	set_firstname	67
9.19.3.11	set_lastname	67
9.19.3.12	set_password	67
9.19.3.13	set_username	67
9.19.3.14	username	68
9.19.4	Member Data Documentation	68
9.19.4.1	m_enabled	68
9.19.4.2	m_firstname	68
9.19.4.3	m_id	68

9.19.4.4	m_lastname	68
9.19.4.5	m_pass_hash	68
9.19.4.6	m_pass_salt	68
9.19.4.7	m_perms	68
9.19.4.8	m_username	68
9.20	gldb::MySQLResult Class Reference	69
9.20.1	Detailed Description	69
9.20.2	Constructor & Destructor Documentation	69
9.20.2.1	MySQLResult	69
9.20.2.2	~MySQLResult	69
9.20.2.3	MySQLResult	69
9.20.2.4	MySQLResult	70
9.20.3	Member Function Documentation	70
9.20.3.1	num_fields	70
9.20.3.2	operator=	70
9.20.3.3	operator=	70
9.20.3.4	result	70
9.20.4	Member Data Documentation	70
9.20.4.1	m_num_fields	70
9.20.4.2	m_result	70
9.21	gldb::Table Class Reference	70
9.21.1	Detailed Description	72
9.21.2	Constructor & Destructor Documentation	72
9.21.2.1	Table	72
9.21.2.2	Table	72
9.21.2.3	Table	72
9.21.2.4	Table	72
9.21.2.5	~Table	73
9.21.3	Member Function Documentation	73
9.21.3.1	append_record	73
9.21.3.2	append_record	73
9.21.3.3	create_from_file	73
9.21.3.4	get_field	73
9.21.3.5	get_headers	74
9.21.3.6	insert_query	74
9.21.3.7	num_fields	74
9.21.3.8	num_records	74
9.21.3.9	operator=	74
9.21.3.10	operator=	75
9.21.3.11	operator[]	75

9.21.3.12	set_quoted	75
9.21.3.13	set_quoted	75
9.21.4	Member Data Documentation	75
9.21.4.1	m_headers	75
9.21.4.2	m_quoted	76
9.21.4.3	m_records	76
9.22	gldb::TableBadInputFile Class Reference	76
9.22.1	Detailed Description	77
9.22.2	Constructor & Destructor Documentation	77
9.22.2.1	TableBadInputFile	77
9.23	gldb::TableCouldNotOpenInputFile Class Reference	77
9.23.1	Detailed Description	78
9.23.2	Constructor & Destructor Documentation	78
9.23.2.1	TableCouldNotOpenInputFile	78
9.24	gldb::TableException Class Reference	78
9.24.1	Detailed Description	79
9.24.2	Constructor & Destructor Documentation	79
9.24.2.1	TableException	79
9.25	gldb::TableField Class Reference	79
9.25.1	Detailed Description	81
9.25.2	Constructor & Destructor Documentation	81
9.25.2.1	TableField	81
9.25.2.2	TableField	81
9.25.2.3	TableField	81
9.25.2.4	TableField	81
9.25.2.5	TableField	81
9.25.2.6	~TableField	82
9.25.3	Member Function Documentation	82
9.25.3.1	length	82
9.25.3.2	operator std::string	82
9.25.3.3	operator+=	82
9.25.3.4	operator+=	82
9.25.3.5	operator=	82
9.25.3.6	operator=	83
9.25.3.7	operator=	83
9.25.3.8	operator=	83
9.25.3.9	operator=	83
9.25.3.10	operator[]	84
9.25.3.11	operator[]	84
9.25.4	Friends And Related Function Documentation	84

9.25.4.1	operator<<	84
9.25.5	Member Data Documentation	84
9.25.5.1	m_data	84
9.26	gldb::TableMismatchedRecordLength Class Reference	85
9.26.1	Detailed Description	85
9.26.2	Constructor & Destructor Documentation	85
9.26.2.1	TableMismatchedRecordLength	86
9.27	gldb::TableNoSuchField Class Reference	86
9.27.1	Detailed Description	87
9.27.2	Constructor & Destructor Documentation	87
9.27.2.1	TableNoSuchField	87
9.28	gldb::TableNoSuchRecord Class Reference	87
9.28.1	Detailed Description	88
9.28.2	Constructor & Destructor Documentation	88
9.28.2.1	TableNoSuchRecord	88
9.29	gldb::TableRow Class Reference	88
9.29.1	Detailed Description	89
9.29.2	Constructor & Destructor Documentation	89
9.29.2.1	TableRow	89
9.29.2.2	TableRow	89
9.29.2.3	TableRow	90
9.29.2.4	TableRow	90
9.29.2.5	TableRow	90
9.29.2.6	TableRow	90
9.29.2.7	TableRow	90
9.29.2.8	~TableRow	90
9.29.3	Member Function Documentation	90
9.29.3.1	append_field	90
9.29.3.2	append_field	91
9.29.3.3	append_field	91
9.29.3.4	append_field	91
9.29.3.5	append_field	91
9.29.3.6	begin	91
9.29.3.7	begin	91
9.29.3.8	end	92
9.29.3.9	end	92
9.29.3.10	operator=	92
9.29.3.11	operator=	92
9.29.3.12	operator[]	92
9.29.3.13	operator[]	93

9.29.3.14 print	93
9.29.3.15 record_string	93
9.29.3.16 record_string	93
9.29.3.17 size	93
9.29.4 Member Data Documentation	93
9.29.4.1 m_fields	93
10 File Documentation	95
10.1 lib/config/config.cpp File Reference	95
10.1.1 Detailed Description	95
10.2 lib/config/config.h File Reference	96
10.2.1 Detailed Description	97
10.3 lib/config/config_getopt.cpp File Reference	97
10.3.1 Detailed Description	97
10.3.2 Macro Definition Documentation	98
10.3.2.1 _XOPEN_SOURCE	98
10.4 lib/database/data_structures.h File Reference	98
10.4.1 Detailed Description	99
10.5 lib/database/database.h File Reference	99
10.5.1 Detailed Description	100
10.6 lib/database/dbconn.cpp File Reference	101
10.6.1 Detailed Description	101
10.7 lib/database/dbconn.h File Reference	102
10.7.1 Detailed Description	103
10.8 lib/database/dbconnimp.h File Reference	103
10.8.1 Detailed Description	105
10.9 lib/database/table.cpp File Reference	105
10.9.1 Detailed Description	105
10.10 lib/database/table.h File Reference	106
10.10.1 Detailed Description	107
10.11 lib/database/tablefield.cpp File Reference	107
10.11.1 Detailed Description	108
10.12 lib/database/tablefield.h File Reference	108
10.12.1 Detailed Description	109
10.13 lib/database/ablerow.cpp File Reference	109
10.13.1 Detailed Description	110
10.14 lib/database/ablerow.h File Reference	110
10.14.1 Detailed Description	111
10.15 lib/database_imp/database_imp.h File Reference	112
10.15.1 Detailed Description	113

10.16lib/database_imp/dummy/dbconn_dummy_imp.cpp File Reference	114
10.16.1 Detailed Description	114
10.17lib/database_imp/dummy/dbconn_dummy_imp.h File Reference	115
10.17.1 Detailed Description	116
10.18lib/database_imp/mysql/dbconn_mysql_functions.cpp File Reference	117
10.18.1 Detailed Description	117
10.19lib/database_imp/mysql/dbconn_mysql_imp.cpp File Reference	118
10.19.1 Detailed Description	118
10.20lib/database_imp/mysql/dbconn_mysql_imp.h File Reference	119
10.20.1 Detailed Description	120
10.21lib/database_imp/mysql/dbconn_mysql_result.cpp File Reference	121
10.21.1 Detailed Description	121
10.22lib/database_imp/mysql/dbconn_mysql_result.h File Reference	122
10.22.1 Detailed Description	122
10.23lib/dbsql/dbsql.h File Reference	123
10.23.1 Detailed Description	124
10.24lib/dbsql/dbsql_dummy.h File Reference	124
10.24.1 Detailed Description	125
10.25lib/dbsql/dbsql_implementations.h File Reference	126
10.25.1 Detailed Description	126
10.26lib/dbsql/dbsql_mysql.h File Reference	127
10.26.1 Detailed Description	128
10.27lib/dbsql/dbsqlstatements.cpp File Reference	128
10.27.1 Detailed Description	128
10.28lib/dbsql/dbsqlstatements.h File Reference	129
10.28.1 Detailed Description	130
10.29lib/gldb/gldatabase.cpp File Reference	130
10.29.1 Detailed Description	131
10.29.2 Function Documentation	131
10.29.2.1 boolstring_to_bool	131
10.30lib/gldb/gldatabase.h File Reference	131
10.30.1 Detailed Description	133
10.31lib/gldb/gldb.h File Reference	133
10.31.1 Detailed Description	134
10.32lib/gldb/glexception.h File Reference	134
10.32.1 Detailed Description	135
10.33lib/gldb/gluser.cpp File Reference	136
10.33.1 Detailed Description	136
10.34lib/gldb/gluser.h File Reference	136
10.34.1 Detailed Description	137

10.35lib/gldb/gluser_pass.cpp File Reference	137
10.35.1 Detailed Description	138
10.35.2 Macro Definition Documentation	138
10.35.2.1 _XOPEN_SOURCE	138
10.35.3 Function Documentation	139
10.35.3.1 generate_salt	139
10.36lib/pgutils/pgutils.h File Reference	139
10.36.1 Detailed Description	139
10.37lib/pgutils/stringhelp.cpp File Reference	140
10.37.1 Detailed Description	140
10.38lib/pgutils/stringhelp.h File Reference	140
10.38.1 Detailed Description	142
10.39progs/gl_db/gl_db_main.cpp File Reference	142
10.39.1 Detailed Description	143
10.40progs/gl_report/gl_report_main.cpp File Reference	143
10.40.1 Detailed Description	145
10.41progs/gl_user/gl_user_main.cpp File Reference	145
10.41.1 Detailed Description	146

Chapter 1

General Ledger.

General Ledger will be a fully-featured, multi-user, open-source general ledger system. The project is in the early stages of development.

Chapter 2

Todo List

File [gluser_pass.cpp](#)

Implement a better form of password encryption. In particular, these functions are not re-entrant, and only use the first 8 characters of the password.

Chapter 3

Bug List

Member `gldb::Table::Table` (`const Table &table`)

'explicit' removed from here after failure to compile at end of MySQL query function.

Chapter 4

Module Index

4.1 Modules

Here is a list of all modules:

Program configuration module	15
Database interaction module	16
SQL statements module	19
General Ledger database module.	20
General purpose utilities.	21
Database program.	25
Reporting program.	27
User administration program.	29

Chapter 5

Class Index

5.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

genleg::Config	33
genleg::ConfigException	39
genleg::ConfigBadConfigFile	35
genleg::ConfigBadOption	37
genleg::ConfigCouldNotOpenFile	38
genleg::ConfigOptionNotSet	40
gldb::DBConn	41
gldb::DBConnException	48
gldb::DBConnCouldNotConnect	43
gldb::DBConnCouldNotQuery	44
gldb::DBConnImp	49
gldb::DBConnDummy	46
gldb::DBConnMySQL	50
genleg::DBSQLStatements	55
genleg::DBSQLDummy	53
genleg::DBSQLMySQL	54
genleg::GLDatabase	58
genleg::GLDBException	63
genleg::GLUser	64
gldb::MySQLResult	69
gldb::Table	70
gldb::TableException	78
gldb::TableBadInputFile	76
gldb::TableCouldNotOpenInputFile	77
gldb::TableMismatchedRecordLength	85
gldb::TableNoSuchField	86
gldb::TableNoSuchRecord	87
gldb::TableField	79
gldb::TableRow	88

Chapter 6

Class Index

6.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

genleg::Config	Configuration options class	33
genleg::ConfigBadConfigFile	Exception class for badly formed configuration file	35
genleg::ConfigBadOption	Exception class for bad provided option	37
genleg::ConfigCouldNotOpenFile	Exception class for when conf file cannot be opened	38
genleg::ConfigException	Configuration module exception base class	39
genleg::ConfigOptionNotSet	Exception class for option not set	40
gldb::DBConn	Database connection class	41
gldb::DBConnCouldNotConnect	Could not connect to database exception class	43
gldb::DBConnCouldNotQuery	Could not execute database query exception class	44
gldb::DBConnDummy	Dummy database implementation class	46
gldb::DBConnException	Base database connection exception class	48
gldb::DBConnImp	Abstract database implementation base class	49
gldb::DBConnMySQL	MySQL database implementation class	50
genleg::DBSQLDummy	Dummy SQL statements class	53
genleg::DBSQLMySQL	MySQL SQL statements class	54
genleg::DBSQLStatements	SQL statements class	55
genleg::GLDatabase	General ledger database class	58
genleg::GLDBException	Base general ledger database exceptionc class	63
genleg::GLUser	General ledger user class	64

gldb::MySQLResult	
MySQL result structure class	69
gldb::Table	
Database table class	70
gldb::TableBadInputFile	
Could not connect to database exception class	76
gldb::TableCouldNotOpenInputFile	
Could not connect to database exception class	77
gldb::TableException	
Base database connection exception class	78
gldb::TableField	
Database table field class	79
gldb::TableMismatchedRecordLength	
Mismatched record length exception class	85
gldb::TableNoSuchField	
No such field exception class	86
gldb::TableNoSuchRecord	
No such record exception class	87
gldb::TableRow	
Database table row class	88

Chapter 7

File Index

7.1 File List

Here is a list of all documented files with brief descriptions:

lib/config/ config.cpp	
Implementation of program configurations class	95
lib/config/ config.h	
Interface to program configurations class	96
lib/config/ config_getopt.cpp	
Implementation of command line functionality	97
lib/database/ data_structures.h	
Main interface to database data structures	98
lib/database/ database.h	
User interface to database functionality	99
lib/database/ dbconn.cpp	
Implementation of database connection class	101
lib/database/ dbconn.h	
Interface to database connection base class	102
lib/database/ dbconnimp.h	
Interface to abstract database implementation base class	103
lib/database/ table.cpp	
Implementation of database table data structure	105
lib/database/ table.h	
Interface to database table data structure	106
lib/database/ tablefield.cpp	
Implementation of database table field class	107
lib/database/ tablefield.h	
Interface to database table field class	108
lib/database/ tablerow.cpp	
Implementation of database table row data structure	109
lib/database/ tablerow.h	
Interface to database table row data structure	110
lib/database_imp/ database_imp.h	
Interface to database implementation factory function	112
lib/database_imp/dummy/ dbconn_dummy_imp.cpp	
Implementation of Dummy database connection implementation class	114
lib/database_imp/dummy/ dbconn_dummy_imp.h	
Interface to dummy database connection implementation class	115
lib/database_imp/mysql/ dbconn_mysql_functions.cpp	
Implementation of MySQL implementation factory function	117
lib/database_imp/mysql/ dbconn_mysql_imp.cpp	
Implementation of MySQL database connection implementation class	118

lib/database_imp/mysql/dbconn_mysql_imp.h	
Interface to MySQL database connection implementation class	119
lib/database_imp/mysql/dbconn_mysql_result.cpp	
Implementation of MySQL result structure resource handle class	121
lib/database_imp/mysql/dbconn_mysql_result.h	
Interface to MySQL result structure resource handle class	122
lib/dbsql/dbsql.h	
User interface to DBSQL module	123
lib/dbsql/dbsql_dummy.h	
Interface to dummy SQL statement class	124
lib/dbsql/dbsql_functions.h	??
lib/dbsql/dbsql_implementations.h	
Aggregation header for DBSQLStatements implementations	126
lib/dbsql/dbsql_mysql.h	
Interface to MySQL SQL statement class	127
lib/dbsql/dbsqlstatements.cpp	
Implementation of SQL statement class	128
lib/dbsql/dbsqlstatements.h	
Implementation of SQL module standalone functions	129
lib/gldb/gldatabase.cpp	
Implementation of General Ledger database class	130
lib/gldb/gldatabase.h	
Interface to General Ledger database class	131
lib/gldb/gldb.h	
User interface to General Ledger database module	133
lib/gldb/glexception.h	
Interface to General Ledger base exception class	134
lib/gldb/gluser.cpp	
Implementation of user class	136
lib/gldb/gluser.h	
Interface to user class	136
lib/gldb/gluser_pass.cpp	
Implementation of password functions for user class	137
lib/pgutils/pgutils.h	
Aggregate interface to general utility functions	139
lib/pgutils/stringhelp.cpp	
Implementation of string helper functions	140
lib/pgutils/stringhelp.h	
Interface to string helper functions	140
progs/gl_db/gl_db_main.cpp	
Main functionality for gl_db program	142
progs/gl_report/gl_report_main.cpp	
Main functionality for gl_report program	143
progs/gl_user/gl_user_main.cpp	
Main functionality for gl_user program	145

Chapter 8

Module Documentation

8.1 Program configuration module

Classes

- class [genleg::ConfigException](#)
Configuration module exception base class.
- class [genleg::ConfigOptionNotSet](#)
Exception class for option not set.
- class [genleg::ConfigBadOption](#)
Exception class for bad provided option.
- class [genleg::ConfigCouldNotOpenFile](#)
Exception class for when conf file cannot be opened.
- class [genleg::ConfigBadConfigFile](#)
Exception class for badly formed configuration file.
- class [genleg::Config](#)
Configuration options class.

Enumerations

- enum [genleg::Argument](#)
Enumeration class for option argument specifications.

8.1.1 Detailed Description

Module for getting options from the command line and configuration files.

8.2 Database interaction module

Classes

- class [gldb::DBConnException](#)
Base database connection exception class.
- class [gldb::DBConnCouldNotConnect](#)
Could not connect to database exception class.
- class [gldb::DBConnCouldNotQuery](#)
Could not execute database query exception class.
- class [gldb::DBConn](#)
Database connection class.
- class [gldb::DBConnImp](#)
Abstract database implementation base class.
- class [gldb::TableException](#)
Base database connection exception class.
- class [gldb::TableNoSuchField](#)
No such field exception class.
- class [gldb::TableNoSuchRecord](#)
No such record exception class.
- class [gldb::TableMismatchedRecordLength](#)
Mismatched record length exception class.
- class [gldb::TableBadInputFile](#)
Could not connect to database exception class.
- class [gldb::TableCouldNotOpenInputFile](#)
Could not connect to database exception class.
- class [gldb::Table](#)
Database table class.
- class [gldb::TableField](#)
Database table field class.
- class [gldb::TableRow](#)
Database table row class.
- class [gldb::DBConnDummy](#)
Dummy database implementation class.
- class [gldb::DBConnMySQL](#)
MySQL database implementation class.
- class [gldb::MySQLResult](#)
MySQL result structure class.

Functions

- [DBConnImp * gldb::get_connection](#) (const std::string &database, const std::string &hostname, const std::string &username, const std::string &password)
Creates and returns a pointer to a database implementation.
- std::string [gldb::get_database_type](#) ()
Returns the name of the compiled-in database type.
- static [TableRow get_field_names](#) (MySQLResult &result)
Gets field names from a MySQL result structure.
- static [TableRow get_row](#) (MySQLResult &result, MYSQL_ROW row)
Creates a TableRow from a MySQL result row.

8.2.1 Detailed Description

Module for interacting with the database.

8.2.2 Function Documentation

8.2.2.1 DBConnImp * glldb::get_connection (const std::string & *database*, const std::string & *hostname*, const std::string & *username*, const std::string & *password*)

Creates and returns a pointer to a database implementation.

The implementation of this function is provided by the individual database implementations. One database implementation is compiled into the program at any one time. Multiple database systems are, or will be, supported, and not every system will possess the libraries and headers to compile every implementation. Therefore, only one implementation is compiled in at a time. The fact that each database implementation will implement this function to return the correct derived class prevents any attempt to compile unsupported library code. This would not be feasible if we were to simply provide each implementation as a subclass.

Parameters

<i>database</i>	The name of the database to which to connect.
<i>hostname</i>	The hostname of the computer running the database.
<i>username</i>	The username with which to log into the database.
<i>password</i>	The password with which to log into the database.

Returns

A pointer to the database implementation.

8.2.2.2 std::string glldb::get_database_type ()

Returns the name of the compiled-in database type.

Returns

The name of the compiled-in database type.

8.2.2.3 static TableRow get_field_names (MySQLResult & *result*) [static]

Gets field names from a MySQL result structure.

Parameters

<i>result</i>	The MySQL result structure.
---------------	-----------------------------

Returns

A TableRow containing the field names.

8.2.2.4 static TableRow get_row (MySQLResult & *result*, MYSQL_ROW *row*) [static]

Creates a TableRow from a MySQL result row.

Parameters

<i>result</i>	The MySQL result structure.
<i>row</i>	The MySQL row structure.

Returns

A TableRow containing the row data.

8.3 SQL statements module

Classes

- class [genleg::DBSQLDummy](#)
Dummy SQL statements class.
- class [genleg::DBSQLMySQL](#)
MySQL SQL statements class.
- class [genleg::DBSQLStatements](#)
SQL statements class.

8.3.1 Detailed Description

Module for producing SQL statements used by program.

8.4 General Ledger database module.

Classes

- class [genleg::GLDatabase](#)
General ledger database class.
- class [genleg::GLDBException](#)
Base general ledger database exceptionc class.
- class [genleg::GLUser](#)
General ledger user class.

8.4.1 Detailed Description

Module for interacting with the general ledger database model.

8.5 General purpose utilities.

Functions

- `std::string & pgutils::trim_front (std::string &s)`
Trims leading whitespace from a string.
- `std::string & pgutils::trim_back (std::string &s)`
Trims trailing whitespace from a string.
- `std::string & pgutils::trim (std::string &s)`
Trims leading and trailing whitespace from a string.
- `std::vector< std::string > pgutils::split (const std::string &s, const char delim)`
Splits a delimited string into tokens.
- `std::vector< std::string > & pgutils::split (std::vector< std::string > &vec, const std::string &s, const char delim)`
Splits a delimited string into tokens.
- `bool pgutils::next_content_line (std::istream &ifs, std::string &s)`
Gets the next content line from a stream.
- `std::vector< std::string > & pgutils::content_lines (std::vector< std::string > &vec, std::istream &ifs)`
Populates a vector of content lines from a stream.
- `std::vector< std::vector< std::string > > & pgutils::split_lines (std::vector< std::vector< std::string > > &vec, std::istream &ifs, const char delim)`
Populates a vector of vectors of fields from a stream.
- `std::string & pgutils::join (const std::vector< std::string > &vec, std::string &s, const char delim)`
Joins a vector of strings into a delimited line.
- `bool pgutils::replace (std::string &str, const std::string &from, const std::string &to)`
Replaces a substring with another string.

8.5.1 Detailed Description

General purpose utility classes and functions.

8.5.2 Function Documentation

8.5.2.1 `std::vector< std::string > & pgutils::content_lines (std::vector< std::string > & vec, std::istream & ifs)`

Populates a vector of content lines from a stream.

Parameters

<code>vec</code>	The vector to populate.
<code>ifs</code>	The input stream.

Returns

A reference to `vec`.

8.5.2.2 `std::string & pgutils::join (const std::vector< std::string > & vec, std::string & s, const char delim)`

Joins a vector of strings into a delimited line.

The function is the opposite of `split`.

Parameters

<i>vec</i>	The vector containing the strings.
<i>s</i>	The string in which to store the line.
<i>delim</i>	The delimiter character to be used to delimit the fields.

Returns

A reference to *s*.

8.5.2.3 bool pgutils::next_content_line (std::istream & ifs, std::string & s)

Gets the next content line from a stream.

A "content line" is defined as a line which, after being trimmed of trailing and leading whitespace, is not empty, and does not start with a '#' character (indicating a comment line).

Parameters

<i>ifs</i>	The input stream.
<i>s</i>	The string in which to store the line.

Returns

`true` if there is a next content line, `false` otherwise.

8.5.2.4 bool pgutils::replace (std::string & str, const std::string & from, const std::string & to)

Replaces a substring with another string.

Parameters

<i>str</i>	The string containing the substring to replace.
<i>from</i>	The substring to replace.
<i>to</i>	The string with which to replace the substring.

Returns

`true` if a replacement was made, `false` otherwise.

8.5.2.5 std::vector< std::string > pgutils::split (const std::string & s, const char delim)

Splits a delimited string into tokens.

Parameters

<i>s</i>	The string to split.
<i>delim</i>	The delimiter character on which to split.

Returns

A vector of tokens.

8.5.2.6 `std::vector< std::string > & pgutils::split (std::vector< std::string > & vec, const std::string & s, const char delim)`

Splits a delimited string into tokens.

Parameters

<i>vec</i>	The vector into which to add the tokens.
<i>s</i>	The string to split.
<i>delim</i>	The delimiter character on which to split.

Returns

A reference to `vec`.

8.5.2.7 `std::vector< std::vector< std::string > > & pgutils::split_lines (std::vector< std::vector< std::string > > & vec, std::istream & ifs, const char delim)`

Populates a vector of vectors of fields from a stream.

Parameters

<i>vec</i>	The vector to populate.
<i>ifs</i>	The input stream.
<i>delim</i>	The delimiter character to split each content line.

Returns

A reference to `vec`.

8.5.2.8 `std::string & pgutils::trim (std::string & s)`

Trims leading and trailing whitespace from a string.

Parameters

<i>s</i>	The string to trim.
----------	---------------------

Returns

The trimmed string.

8.5.2.9 `std::string & pgutils::trim_back (std::string & s)`

Trims trailing whitespace from a string.

Parameters

<i>s</i>	The string to trim.
----------	---------------------

Returns

The trimmed string.

8.5.2.10 `std::string & pgutils::trim_front (std::string & s)`

Trims leading whitespace from a string.

Parameters

<code>s</code>	The string to trim.
----------------	---------------------

Returns

The trimmed string.

8.6 Database program.

Functions

- static void `set_configuration` (`Config` &config, int argc, char *argv[])
Sets program configuration options.
- static bool `check_help_and_version` (const `Config` &config)
Prints help or version messages if requested.
- static bool `check_db_parameters` (const `Config` &config)
Checks if database, hostname and username were provided.
- static void `print_usage_message` ()
Prints a program usage message.
- static void `print_version_message` ()
Prints a program version message.
- static void `print_help_message` ()
Prints a program help message.
- static std::string `login` (void)
Gets a password from the terminal.
- int `main` (int argc, char *argv[])
Main function.

Variables

- static const char * `progrname` = "gl_db"
Static variable for program name.

8.6.1 Detailed Description

Administrative database management program.

8.6.2 Function Documentation

8.6.2.1 static bool `check_db_parameters` (const `Config` & *config*) [static]

Checks if database, hostname and username were provided.

Parameters

<i>config</i>	Reference to a Config object.
---------------	-------------------------------

Returns

`true` if the information was provided, `false` otherwise.

8.6.2.2 static bool `check_help_and_version` (const `Config` & *config*) [static]

Prints help or version messages if requested.

Parameters

<i>config</i>	Reference to a Config object.
---------------	-------------------------------

Returns

`true` if the help or version message was requested, `false` otherwise.

8.6.2.3 static std::string login (void) [static]

Gets a password from the terminal.

Returns

The password.

8.6.2.4 int main (int argc, char * argv[])

Main function.

Parameters

<i>argc</i>	Number of command line arguments.
<i>argv</i>	Command line arguments.

Returns

Exit status code.

8.6.2.5 static void set_configuration (Config & config, int argc, char * argv[]) [static]

Sets program configuration options.

Parameters

<i>config</i>	Reference to a Config object.
<i>argc</i>	<code>argc</code> passed to <code>main()</code> .
<i>argv</i>	<code>argv</code> passed to <code>main()</code> .

8.7 Reporting program.

Functions

- static void `set_configuration` (`genleg::Config` &config, int argc, char *argv[])
Sets program configuration options.
- static void `print_usage_message` ()
Prints a program usage message.
- static void `print_version_message` ()
Prints a program version message.
- static void `print_help_message` ()
Prints a program help message.
- static std::string `login` (void)
Gets a password from the terminal.
- int `main` (int argc, char *argv[])
Main function.

Variables

- static const char * `progrname` = "gl_report"
Static variable for program name.

8.7.1 Detailed Description

Administrative reporting program.

8.7.2 Function Documentation

8.7.2.1 static std::string login (void) [static]

Gets a password from the terminal.

Returns

The password.

8.7.2.2 int main (int argc, char * argv[])

Main function.

Parameters

<code>argc</code>	Number of command line arguments.
<code>argv</code>	Command line arguments.

Returns

Exit status code.

8.7.2.3 `static void set_configuration (genleg::Config & config, int argc, char * argv[])` [static]

Sets program configuration options.

Parameters

<i>config</i>	Reference to a Config object.
<i>argc</i>	argc passed to <code>main()</code> .
<i>argv</i>	argv passed to <code>main()</code> .

8.8 User administration program.

Functions

- static void `set_configuration` (`Config` &config, int argc, char *argv[])
Sets program configuration options.
- static bool `check_help_and_version` (const `Config` &config)
Prints help or version messages if requested.
- static bool `check_db_parameters` (const `Config` &config)
Checks if database, hostname and username were provided.
- `GLUser` `get_user` (`Config` &config, `GLDatabase` &gdb)
Returns a user from either an ID or a name.
- static void `show_user_details` (const `GLUser` &user)
Outputs details for a user.
- static void `enable_user` (`GLUser` &user, `Config` &config, `GLDatabase` &gdb)
Enables or disables a user.
- static void `set_user_password` (`GLUser` &user, `Config` &config, `GLDatabase` &gdb)
Sets a user's password.
- static void `check_user_password` (`GLUser` &user, `Config` &config)
Checks a user's password.
- static void `print_usage_message` ()
Prints a program usage message.
- static void `print_version_message` ()
Prints a program version message.
- static void `print_help_message` ()
Prints a program help message.
- static std::string `login` (void)
Gets a password from the terminal.
- int `main` (int argc, char *argv[])
Main function.

Variables

- static const char * `progrname` = "gl_user"
Static variable for program name.

8.8.1 Detailed Description

User administration program.

8.8.2 Function Documentation

8.8.2.1 static bool `check_db_parameters` (const `Config` & *config*) [static]

Checks if database, hostname and username were provided.

Parameters

<i>config</i>	Reference to a Config object.
---------------	-------------------------------

Returns

`true` if the information was provided, `false` otherwise.

8.8.2.2 `static bool check_help_and_version (const Config & config) [static]`

Prints help or version messages if requested.

Parameters

<i>config</i>	Reference to a Config object.
---------------	-------------------------------

Returns

`true` if the help or version message was requested, `false` otherwise.

8.8.2.3 `static void check_user_password (GLUser & user, Config & config) [static]`

Checks a user's password.

Parameters

<i>user</i>	Reference to user.
<i>config</i>	Reference to program configuration options.

8.8.2.4 `static void enable_user (GLUser & user, Config & config, GLDatabase & gdb) [static]`

Enables or disables a user.

Parameters

<i>user</i>	Reference to user.
<i>config</i>	Reference to program configuration.
<i>gdb</i>	Reference to database object.

8.8.2.5 `GLUser get_user (Config & config, GLDatabase & gdb)`

Returns a user from either an ID or a name.

Parameters

<i>config</i>	Program configurations object.
<i>gdb</i>	Database object.

Returns

The user.

8.8.2.6 `static std::string login (void) [static]`

Gets a password from the terminal.

Returns

The password.

8.8.2.7 `int main (int argc, char * argv[])`

Main function.

Parameters

<i>argc</i>	Number of command line arguments.
<i>argv</i>	Command line arguments.

Returns

Exit status code.

8.8.2.8 `static void set_configuration (Config & config, int argc, char * argv[]) [static]`

Sets program configuration options.

Parameters

<i>config</i>	Reference to a Config object.
<i>argc</i>	argc passed to <code>main()</code> .
<i>argv</i>	argv passed to <code>main()</code> .

8.8.2.9 `static void set_user_password (GLUser & user, Config & config, GLDatabase & gdb) [static]`

Sets a user's password.

Parameters

<i>user</i>	Reference to user.
<i>config</i>	Reference to program configuration.
<i>gdb</i>	Reference to database object.

8.8.2.10 `static void show_user_details (const GLUser & user) [static]`

Outputs details for a user.

Parameters

<i>user</i>	Reference to user.
-------------	--------------------

Chapter 9

Class Documentation

9.1 genleg::Config Class Reference

Configuration options class.

```
#include <config.h>
```

Public Member Functions

- [Config](#) ()
- [~Config](#) ()
- void [add_cmdline_option](#) (const std::string option, const enum [Argument](#) arg)
Adds a supported command line option.
- void [populate_from_cmdline](#) (const int argc, char *const *argv)
Populates options from the command line.
- void [populate_from_file](#) (const std::string filename)
Populates options from a configuration file.
- bool [is_set](#) (const std::string option) const
Checks if an option is set.
- const std::string & [operator\[\]](#) (const std::string &option) const
operator[] overload.

Private Attributes

- std::map< std::string,
std::string > [m_opts_set](#)
- std::list< std::pair
< std::string, enum [Argument](#) > > [m_opts_supp](#)

9.1.1 Detailed Description

Configuration options class.

9.1.2 Constructor & Destructor Documentation

9.1.2.1 Config::Config ()

Constructor

9.1.2.2 Config::~Config ()

Destructor

9.1.3 Member Function Documentation

9.1.3.1 void Config::add_cmdline_option (const std::string *option*, const enum Argument *arg*)

Adds a supported command line option.

Parameters

<i>option</i>	The name of the option.
<i>arg</i>	The argument specification for the option.

9.1.3.2 bool Config::is_set (const std::string *option*) const

Checks is an option is set.

Parameters

<i>option</i>	The name of the option to check.
---------------	----------------------------------

Returns

`true` if the option has been set, `false` if it has not.

9.1.3.3 const std::string & Config::operator[] (const std::string & *option*) const

operator[] overload.

Retrieves the value of a set option.

Parameters

<i>option</i>	The name of the option.
---------------	-------------------------

Returns

The value of the option.

Exceptions

<i>ConfigOptionNotSet</i>	If the named option has not been set.
---	---------------------------------------

9.1.3.4 void Config::populate_from_cmdline (const int *argc*, char *const * *argv*)

Populates options from the command line.

Parameters

<i>argc</i>	<i>argc</i> supplied to <code>main()</code> .
<i>argv</i>	<i>argv</i> supplied to <code>main()</code> .

Exceptions

<i>ConfigBadOption</i>	If an unsupported option is specified, or if a required argument is missing, or if an unexpected argument is found.
--	---

9.1.3.5 void Config::populate_from_file (const std::string filename)

Populates options from a configuration file.

Parameters

<i>filename</i>	The name of the configuration file.
-----------------	-------------------------------------

Exceptions

<i>ConfigCouldNotOpenFile</i>	If the configuration file cannot be opened.
<i>ConfigBadConfigFile</i>	If the configuration file is badly formed.

9.1.4 Member Data Documentation

9.1.4.1 std::map<std::string, std::string> genleg::Config::m_opts_set [private]

Map of options which have been set

9.1.4.2 std::list<std::pair<std::string, enum Argument> > genleg::Config::m_opts_supp [private]

List of options which are supported

The documentation for this class was generated from the following files:


- lib/config/[config.h](#)
- lib/config/[config.cpp](#)
- lib/config/[config_getopt.cpp](#)

9.2 genleg::ConfigBadConfigFile Class Reference


Exception class for badly formed configuration file.

```
#include <config.h>
```

Inheritance diagram for `genleg::ConfigBadConfigFile`:



Collaboration diagram for `genleg::ConfigBadConfigFile`:



Public Member Functions

- [ConfigBadConfigFile](#) (const std::string &msg)
Constructor.

9.2.1 Detailed Description

Exception class for badly formed configuration file.

9.2.2 Constructor & Destructor Documentation

9.2.2.1 `genleg::ConfigBadConfigFile::ConfigBadConfigFile (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- [lib/config/config.h](#)

9.3 genleg::ConfigBadOption Class Reference


Exception class for bad provided option.

```
#include <config.h>
```

Inheritance diagram for genleg::ConfigBadOption:



Collaboration diagram for genleg::ConfigBadOption:



Public Member Functions

- [ConfigBadOption](#) (const std::string &msg)
Constructor.

9.3.1 Detailed Description

Exception class for bad provided option.

9.3.2 Constructor & Destructor Documentation

9.3.2.1 `genleg::ConfigBadOption::ConfigBadOption (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- `lib/config/config.h`

9.4 `genleg::ConfigCouldNotOpenFile` Class Reference


Exception class for when conf file cannot be opened.

```
#include <config.h>
```

Inheritance diagram for `genleg::ConfigCouldNotOpenFile`:



Collaboration diagram for `genleg::ConfigCouldNotOpenFile`:



Public Member Functions

- `ConfigCouldNotOpenFile (const std::string &msg)`
Constructor.

9.4.1 Detailed Description

Exception class for when conf file cannot be opened.

9.4.2 Constructor & Destructor Documentation

9.4.2.1 `genleg::ConfigCouldNotOpenFile::ConfigCouldNotOpenFile (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- [lib/config/config.h](#)

9.5 genleg::ConfigException Class Reference

Configuration module exception base class.

```
#include <config.h>
```

Inheritance diagram for genleg::ConfigException:



Public Member Functions

- [ConfigException](#) (const std::string &msg)
Constructor.

9.5.1 Detailed Description

Configuration module exception base class.

9.5.2 Constructor & Destructor Documentation

9.5.2.1 `genleg::ConfigException::ConfigException (const std::string & msg)` `[inline]`, `[explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- `lib/config/config.h`

9.6 `genleg::ConfigOptionNotSet` Class Reference


Exception class for option not set.

```
#include <config.h>
```

Inheritance diagram for `genleg::ConfigOptionNotSet`:



Collaboration diagram for `genleg::ConfigOptionNotSet`:



Public Member Functions

- [`ConfigOptionNotSet`](#) (`const std::string &msg`)

Constructor.

9.6.1 Detailed Description

Exception class for option not set.

9.6.2 Constructor & Destructor Documentation

9.6.2.1 genleg::ConfigOptionNotSet::ConfigOptionNotSet (const std::string & msg) [inline], [explicit]

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- lib/config/[config.h](#)

9.7 glldb::DBConn Class Reference

Database connection class.

```
#include <dbconn.h>
```

Collaboration diagram for glldb::DBConn:



Public Member Functions

- [DBConn](#) ([DBConnImp](#) *imp)
Constructor.
- [~DBConn](#) ()
Destructor..
- void [query](#) (const std::string &sql_query)
Runs an SQL query.
- [Table select](#) (const std::string &query)

Runs an SQL SELECT query.

- [DBConn](#) (const [DBConn](#) &)
- [DBConn](#) (const [DBConn](#) &&)
- [DBConn](#) & [operator=](#) (const [DBConn](#) &)
- [DBConn](#) & [operator=](#) (const [DBConn](#) &&)

Private Attributes

- [DBConnImp](#) * [m_imp](#)

9.7.1 Detailed Description

Database connection class.

9.7.2 Constructor & Destructor Documentation

9.7.2.1 [DBConn::DBConn \(\[DBConnImp\]\(#\) * *imp* \)](#) `[explicit]`

Constructor.

Parameters

<i>imp</i>	Pointer to database implementation object.
------------	--

9.7.2.2 [gldb::DBConn::DBConn \(const \[DBConn\]\(#\) & \)](#)

Deleted copy constructor

9.7.2.3 [gldb::DBConn::DBConn \(const \[DBConn\]\(#\) && \)](#)

Deleted move constructor

9.7.3 Member Function Documentation

9.7.3.1 [DBConn& gldb::DBConn::operator= \(const \[DBConn\]\(#\) & \)](#)

Deleted copy assignment operator

9.7.3.2 [DBConn& gldb::DBConn::operator= \(const \[DBConn\]\(#\) && \)](#)

Deleted move assignment operator

9.7.3.3 [void DBConn::query \(const std::string & *sql_query* \)](#)

Runs an SQL query.

Parameters

<i>sql_query</i>	The query.
------------------	------------

Returns

A [Table](#) object containing the results.

9.7.3.4 Table DBConn::select (const std::string & *query*)

Runs an SQL SELECT query.

Parameters

<i>query</i>	The query.
--------------	------------

Returns

A [Table](#) object containing the results.

9.7.4 Member Data Documentation

9.7.4.1 DBConnImp* glldb::DBConn::m_imp [private]

Pointer to database implementation object.

The documentation for this class was generated from the following files:


- lib/database/[dbconn.h](#)
- lib/database/[dbconn.cpp](#)

9.8 glldb::DBConnCouldNotConnect Class Reference


Could not connect to database exception class.

```
#include <dbconn.h>
```

Inheritance diagram for glldb::DBConnCouldNotConnect:



Collaboration diagram for `gldb::DBConnCouldNotConnect`:



Public Member Functions

- [DBConnCouldNotConnect](#) (const std::string &msg)
Constructor.

9.8.1 Detailed Description

Could not connect to database exception class.

9.8.2 Constructor & Destructor Documentation

9.8.2.1 `gldb::DBConnCouldNotConnect::DBConnCouldNotConnect (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- lib/database/[dbconn.h](#)

9.9 gldb::DBConnCouldNotQuery Class Reference


Could not execute database query exception class.

```
#include <dbconn.h>
```

Inheritance diagram for glldb::DBConnCouldNotQuery:



Collaboration diagram for glldb::DBConnCouldNotQuery:



Public Member Functions

- [`DBConnCouldNotQuery`](#) (const std::string &msg)
Constructor.

9.9.1 Detailed Description

Could not execute database query exception class.

9.9.2 Constructor & Destructor Documentation

9.9.2.1 `glldb::DBConnCouldNotQuery::DBConnCouldNotQuery (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- [lib/database/dbconn.h](#)

9.10 gldb::DBConnDummy Class Reference


Dummy database implementation class.

```
#include <dbconn_dummy_imp.h>
```

Inheritance diagram for gldb::DBConnDummy:



Collaboration diagram for gldb::DBConnDummy:



Public Member Functions

- [DBConnDummy](#) (const std::string database, const std::string hostname, const std::string username, const std::string password)
Constructor.
- [DBConnDummy](#) (const [DBConnDummy](#) &)
- virtual [~DBConnDummy](#) ()
- [DBConnDummy](#) & [operator=](#) (const [DBConnDummy](#) &)
- virtual void [query](#) (const std::string &sql_query)
Runs an SQL query.
- [Table select](#) (const std::string &[query](#))
Fakes running of an SQL SELECT query.

9.10.1 Detailed Description

Dummy database implementation class.

9.10.2 Constructor & Destructor Documentation

9.10.2.1 DBConnDummy::DBConnDummy (const std::string *database*, const std::string *hostname*, const std::string *username*, const std::string *password*)

Constructor.

Parameters

<i>database</i>	The name of the Dummy database.
<i>hostname</i>	The hostname of the server.
<i>username</i>	The username to log into the database.
<i>password</i>	The password to log into the database.

9.10.2.2 glldb::DBConnDummy::DBConnDummy (const DBConnDummy &)

Deleted copy constructor

9.10.2.3 DBConnDummy::~DBConnDummy () [virtual]

Destructor

9.10.3 Member Function Documentation

9.10.3.1 DBConnDummy& glldb::DBConnDummy::operator= (const DBConnDummy &)

Deleted assignment operator

9.10.3.2 void DBConnDummy::query (const std::string & *sql_query*) [virtual]

Runs an SQL query.

Parameters

<i>sql_query</i>	The query.
------------------	------------

Exceptions

<i>DBConnCouldNotQuery</i>	If could not successfully execute query.
--	--

Implements [`glldb::DBConnImp`](#).

9.10.3.3 Table DBConnDummy::select (const std::string & *query*) [virtual]

Fakes running of an SQL SELECT query.

Parameters

<i>query</i>	Any query.
--------------	------------

Returns

A [Table](#) object containing dummy results.

Implements [gldb::DBConnImp](#).

The documentation for this class was generated from the following files:


- [lib/database_imp/dummy/dbconn_dummy_imp.h](#)
- [lib/database_imp/dummy/dbconn_dummy_imp.cpp](#)

9.11 gldb::DBConnException Class Reference

Base database connection exception class.

```
#include <dbconn.h>
```

Inheritance diagram for gldb::DBConnException:



Public Member Functions

- [DBConnException](#) (const std::string &msg)
Constructor.

9.11.1 Detailed Description

Base database connection exception class.

9.11.2 Constructor & Destructor Documentation

9.11.2.1 `gldb::DBConnException::DBConnException (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- [lib/database/dbconn.h](#)

9.12 glldb::DBConnImp Class Reference

Abstract database implementation base class.

```
#include <dbconnimp.h>
```

Inheritance diagram for glldb::DBConnImp:



Public Member Functions

- [DBConnImp](#) ()
- virtual [~DBConnImp](#) ()
- virtual void [query](#) (const std::string &sql_query)=0
Runs an SQL query.
- virtual [Table select](#) (const std::string &query)=0
Runs an SQL SELECT query.

9.12.1 Detailed Description

Abstract database implementation base class.

9.12.2 Constructor & Destructor Documentation

9.12.2.1 glldb::DBConnImp::DBConnImp () [inline]

Constructor

9.12.2.2 virtual glldb::DBConnImp::~~DBConnImp () [inline], [virtual]

Destructor

9.12.3 Member Function Documentation

9.12.3.1 `virtual void gldb::DBConnImp::query (const std::string & sql_query)` [pure virtual]

Runs an SQL query.

Parameters

<i>sql_query</i>	The query.
------------------	------------

Implemented in [gldb::DBConnMySQL](#), and [gldb::DBConnDummy](#).

9.12.3.2 `virtual Table gldb::DBConnImp::select (const std::string & query)` [pure virtual]

Runs an SQL SELECT query.

Parameters

<i>query</i>	The query.
--------------	------------

Returns

A [Table](#) object containing the results.

Implemented in [gldb::DBConnMySQL](#), and [gldb::DBConnDummy](#).

The documentation for this class was generated from the following file:


- `lib/database/dbconnimp.h`

9.13 gldb::DBConnMySQL Class Reference


MySQL database implementation class.

```
#include <dbconn_mysql_imp.h>
```

Inheritance diagram for `gldb::DBConnMySQL`:



Collaboration diagram for glldb::DBConnMySQL:



Public Member Functions

- [DBConnMySQL](#) (const std::string &database, const std::string &hostname, const std::string &username, const std::string &password)
Constructor.
- [DBConnMySQL](#) (const [DBConnMySQL](#) &)
- [DBConnMySQL](#) (const [DBConnMySQL](#) &&)
- virtual [~DBConnMySQL](#) ()
- [DBConnMySQL](#) & [operator=](#) (const [DBConnMySQL](#) &)
- [DBConnMySQL](#) & [operator=](#) (const [DBConnMySQL](#) &&)
- virtual void [query](#) (const std::string &sql_query)
Runs an SQL query.
- virtual [Table select](#) (const std::string &sql_query)
Runs an SQL SELECT query.

Private Attributes

- MYSQL * [m_conn](#)

9.13.1 Detailed Description

MySQL database implementation class.

9.13.2 Constructor & Destructor Documentation

9.13.2.1 DBConnMySQL::DBConnMySQL (const std::string & database, const std::string & hostname, const std::string & username, const std::string & password)

Constructor.

Parameters

<i>database</i>	The name of the MySQL database.
<i>hostname</i>	The hostname of the server.
<i>username</i>	The username to log into the database.
<i>password</i>	The password to log into the database.

Exceptions

<i>DBConnCouldNotConnect</i>	If could not connect to database.
--	-----------------------------------

9.13.2.2 `gldb::DBConnMySQL::DBConnMySQL (const DBConnMySQL &)`

Deleted copy constructor

9.13.2.3 `gldb::DBConnMySQL::DBConnMySQL (const DBConnMySQL &&)`

Delete move constructor

9.13.2.4 `virtual gldb::DBConnMySQL::~DBConnMySQL () [virtual]`

Destructor

9.13.3 Member Function Documentation

9.13.3.1 `DBConnMySQL& gldb::DBConnMySQL::operator= (const DBConnMySQL &)`

Deleted assignment operator

9.13.3.2 `DBConnMySQL& gldb::DBConnMySQL::operator= (const DBConnMySQL &&)`

Deleted move assignment operator

9.13.3.3 `virtual void gldb::DBConnMySQL::query (const std::string & sql_query) [virtual]`

Runs an SQL query.

Parameters

<i>sql_query</i>	The SQL query.
------------------	----------------

Exceptions

<i>DBConnCouldNotQuery</i>	If could not successfully execute query.
--	--

Implements [`gldb::DBConnImp`](#).

9.13.3.4 `virtual Table gldb::DBConnMySQL::select (const std::string & sql_query) [virtual]`

Runs an SQL SELECT query.

Parameters

<i>sql_query</i>	The SQL query.
------------------	----------------

Returns

A [`Table`](#) object containing the results.

Exceptions

DBConnCouldNotQuery	If could not successfully execute query.
-------------------------------------	--

Implements [gldb::DBConnImp](#).

9.13.4 Member Data Documentation

9.13.4.1 MySQL* gldb::DBConnMySQL::m_conn [private]

The initialized MySQL handle.

The documentation for this class was generated from the following files:


- lib/database_imp/mysql/[dbconn_mysql_imp.h](#)
- lib/database_imp/mysql/[dbconn_mysql_imp.cpp](#)

9.14 genleg::DBSQLDummy Class Reference


Dummy SQL statements class.

```
#include <dbsql_dummy.h>
```

Inheritance diagram for genleg::DBSQLDummy:



Collaboration diagram for genleg::DBSQLDummy:



Additional Inherited Members

9.14.1 Detailed Description

Dummy SQL statements class.

The documentation for this class was generated from the following file:


- lib/dbsql/dbsql_dummy.h

9.15 genleg::DBSQLMySQL Class Reference


MySQL SQL statements class.

```
#include <dbsql_mysql.h>
```

Inheritance diagram for genleg::DBSQLMySQL:



Collaboration diagram for genleg::DBSQLMySQL:



Additional Inherited Members

9.15.1 Detailed Description

MySQL SQL statements class.

The documentation for this class was generated from the following file:


- lib/dbsql/dbsql_mysql.h

9.16 genleg::DBSQLStatements Class Reference

SQL statements class.

```
#include <dbsqlstatements.h>
```

Inheritance diagram for genleg::DBSQLStatements:



Public Member Functions

- [DBSQLStatements](#) ()
- virtual [~DBSQLStatements](#) ()
- virtual std::string [create_table](#) (const std::string &table_name) const
Returns a SQL statement for creating a table.
- virtual std::string [drop_table](#) (const std::string &table_name) const
Returns a SQL statement for dropping a table.
- virtual std::string [create_view](#) (const std::string &view_name) const
Returns a SQL statement for creating a view.
- virtual std::string [drop_view](#) (const std::string &view_name) const
Returns a SQL statement for dropping a view.
- virtual std::string [user_by_id](#) (const std::string &user_id) const
Returns a SQL statement to select a user by ID.
- virtual std::string [user_by_username](#) (const std::string &user_name) const
Returns a SQL statement to select a user by username.
- virtual std::string [update_user](#) (const [GLUser](#) &user) const
Returns a SQL UPDATE statement to update a user.
- virtual std::string [grant](#) (const std::string &user_id, const std::string &perm) const
Returns a SQL statement to grant a user a permission.
- virtual std::string [revoke](#) (const std::string &user_id, const std::string &perm) const
Returns a SQL UPDATE statement to revoke a permission from a user.
- virtual std::string [get_perms](#) (const std::string &user_id) const
Returns a SQL UPDATE statement to list a user's permissions.

9.16.1 Detailed Description

SQL statements class.

9.16.2 Constructor & Destructor Documentation

9.16.2.1 DBSQLStatements::DBSQLStatements ()

Constructor

9.16.2.2 DBSQLStatements::~~DBSQLStatements () [virtual]

Destructor

9.16.3 Member Function Documentation

9.16.3.1 std::string DBSQLStatements::create_table (const std::string & *table_name*) const [virtual]

Returns a SQL statement for creating a table.

Parameters

<i>table_name</i>	The table to create.
-------------------	----------------------

Returns

The SQL statement to create the table.

9.16.3.2 std::string DBSQLStatements::create_view (const std::string & *view_name*) const [virtual]

Returns a SQL statement for creating a view.

Parameters

<i>view_name</i>	The view to create.
------------------	---------------------

Returns

The SQL statement to create the view.

9.16.3.3 std::string DBSQLStatements::drop_table (const std::string & *table_name*) const [virtual]

Returns a SQL statement for dropping a table.

Parameters

<i>table_name</i>	The table to drop.
-------------------	--------------------

Returns

The SQL statement to drop the table.

9.16.3.4 std::string DBSQLStatements::drop_view (const std::string & *view_name*) const [virtual]

Returns a SQL statement for dropping a view.

Parameters

<i>view_name</i>	The view to drop.
------------------	-------------------

Returns

The SQL statement to drop the view.

9.16.3.5 std::string DBSQLStatements::get_perms (const std::string & *user_id*) const [virtual]

Returns a SQL UPDATE statement to list a user's permissions.

Parameters

<i>user_id</i>	The user ID for which to list.
----------------	--------------------------------

Returns

The SQL statement.

9.16.3.6 std::string DBSQLStatements::grant (const std::string & *user_id*, const std::string & *perm*) const [virtual]

Returns a SQL statement to grant a user a permission.

Attention

This function always sets the user granting the permission to user 1. This will need to be updated to support the recording of which user has granted the permission, when support for others to be able to do so is implemented.

Parameters

<i>user_id</i>	The user ID for which to grant the permission.
<i>perm</i>	A string containing the name of the permission.

Returns

The SQL statement.

9.16.3.7 std::string DBSQLStatements::revoke (const std::string & *user_id*, const std::string & *perm*) const [virtual]

Returns a SQL UPDATE statement to revoke a permission from a user.

Parameters

<i>user_id</i>	The user ID from which to revoke.
<i>perm</i>	The permission to revoke.

Returns

The SQL statement.

9.16.3.8 `std::string DBSQLStatements::update_user (const GLUser & user) const` `[virtual]`

Returns a SQL UPDATE statement to update a user.

Parameters

<i>user</i>	A user object.
-------------	----------------

Returns

The SQL statement.

9.16.3.9 `std::string DBSQLStatements::user_by_id (const std::string & user_id) const` `[virtual]`

Returns a SQL statement to select a user by ID.

Parameters

<i>user_id</i>	The user_id
----------------	-------------

Returns

The SQL statement.

9.16.3.10 `std::string DBSQLStatements::user_by_username (const std::string & user_name) const` `[virtual]`

Returns a SQL statement to select a user by username.

Parameters

<i>user_name</i>	The username.
------------------	---------------

Returns

The SQL statement.

The documentation for this class was generated from the following files:


- [lib/dbsql/dbsqlstatements.h](#)
- [lib/dbsql/dbsqlstatements.cpp](#)

9.17 genleg::GLDatabase Class Reference

General ledger database class.

```
#include <glatabase.h>
```


Collaboration diagram for genleg::GLDatabase:



Public Member Functions

- `GLDatabase` (const std::string &database, const std::string &hostname, const std::string &username, const std::string &password)
Constructor.
- `~GLDatabase` ()
- void `create_structure` ()
Creates the database structure.
- void `destroy_structure` ()
Destroys the database structure.
- void `load_sample_data` (const std::string &dir)
Loads sample data into the database.
- `GLUser get_user_by_id` (const std::string &user_id)
Returns a user from an ID.
- `GLUser get_user_by_username` (const std::string &user_name)
Returns a user from a user name.
- void `update_user` (const `GLUser` &user)
Updates a user's details.
- void `grant` (const `GLUser` &user, const std::string &perm)
Grants a user a permission.
- void `revoke` (const `GLUser` &user, const std::string &perm)
Revokes a permission from a user.

Static Public Member Functions

- static std::string `backend` ()
Returns the backend database implementation.

Private Member Functions

- [GLUser create_user](#) ([gldb::Table](#) &table)
Creates a user from a query table.

Private Attributes

- [gldb::DBConn m_dbc](#)
- `const std::shared_ptr< const DBSQLStatements > m_sql`
- `const std::vector< std::string > m_tables`
- `const std::vector< std::string > m_views`

9.17.1 Detailed Description

General ledger database class.

9.17.2 Constructor & Destructor Documentation

- 9.17.2.1 `GLDatabase::GLDatabase (const std::string & database, const std::string & hostname, const std::string & username, const std::string & password)`

Constructor.

Parameters

<i>database</i>	Database name.
<i>hostname</i>	Hostname of database machine.
<i>username</i>	Username to log into database.
<i>password</i>	Password to log into database.

Exceptions

GLDBException	on error.
-------------------------------	-----------

- 9.17.2.2 `GLDatabase::~~GLDatabase ()`

Destructor

9.17.3 Member Function Documentation

- 9.17.3.1 `std::string GLDatabase::backend () [static]`

Returns the backend database implementation.

This may be called to discover which database platform support has been compiled into the application.

Returns

A string containing the database platform name.

9.17.3.2 void GLDatabase::create_structure ()

Creates the database structure.

Exceptions

GLDBException	on error.
-------------------------------	-----------

9.17.3.3 GLUser GLDatabase::create_user (gldb::Table & table) [private]

Creates a user from a query table.

Provided because the public functions can get a user either from an ID or a name, this function contains the common functionality.

Parameters

<i>table</i>	A table from the appropriate query.
--------------	-------------------------------------

Returns

The new user.

9.17.3.4 void GLDatabase::destroy_structure ()

Destroys the database structure.

Exceptions

GLDBException	on error.
-------------------------------	-----------

9.17.3.5 GLUser GLDatabase::get_user_by_id (const std::string & user_id)

Returns a user from an ID.

Parameters

<i>user_id</i>	The user ID.
----------------	--------------

Returns

The user.

Exceptions

GLDBException	if the user cannot be found.
-------------------------------	------------------------------

9.17.3.6 GLUser GLDatabase::get_user_by_username (const std::string & user_name)

Returns a user from a user name.

Parameters

<i>user_name</i>	The user name.
------------------	----------------

Returns

The user.

Exceptions

<i>GLDBException</i>	if the user cannot be found.
--------------------------------------	------------------------------

9.17.3.7 void GLDatabase::grant (const GLUser & *user*, const std::string & *perm*)

Grants a user a permission.

Parameters

<i>user</i>	The user for which to grant.
<i>perm</i>	A string containing the permission to grant.

9.17.3.8 void GLDatabase::load_sample_data (const std::string & *dir*)

Loads sample data into the database.

Parameters

<i>dir</i>	The directory containing the sample data. Individual files in that directory should be named after the table they are intended to populate.
------------	---

Exceptions

<i>GLDBException</i>	on error.
--------------------------------------	-----------

9.17.3.9 void GLDatabase::revoke (const GLUser & *user*, const std::string & *perm*)

Revokes a permission from a user.

Parameters

<i>user</i>	The user for which to revoke.
<i>perm</i>	A string containing the permission to revoke.

9.17.3.10 void GLDatabase::update_user (const GLUser & *user*)

Updates a user's details.

Parameters

<i>user</i>	The user object.
-------------	------------------

9.17.4 Member Data Documentation

9.17.4.1 `gldb::DBConn genleg::GLDatabase::m_dbc` `[private]`

Database connection

9.17.4.2 `const std::shared_ptr<const DBSQLStatements> genleg::GLDatabase::m_sql` `[private]`

SQL statements object

9.17.4.3 `const std::vector<std::string> genleg::GLDatabase::m_tables` `[private]`

Vector containing database table names

9.17.4.4 `const std::vector<std::string> genleg::GLDatabase::m_views` `[private]`

Vector containing database view names

The documentation for this class was generated from the following files:

- [lib/gldb/gldatabase.h](#)
- [lib/gldb/gldatabase.cpp](#)

9.18 genleg::GLDBException Class Reference

Base general ledger database exceptionc class.

```
#include <glexception.h>
```

Public Member Functions

- [GLDBException](#) (const std::string &msg)
Constructor.

9.18.1 Detailed Description

Base general ledger database exceptionc class.

9.18.2 Constructor & Destructor Documentation

9.18.2.1 `genleg::GLDBException::GLDBException (const std::string & msg)` `[inline],[explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- [lib/gldb/glexception.h](#)

9.19 genleg::GLUser Class Reference

General ledger user class.

```
#include <gluser.h>
```

Collaboration diagram for genleg::GLUser:



Public Member Functions

- [GLUser](#) (const std::string &[id](#), const std::string &[username](#), const std::string &[firstname](#), const std::string &[lastname](#), const std::string &[pass_hash](#), const std::string &[pass_salt](#), std::vector< std::string > &&[perms](#), const bool [enabled](#))
Constructor.
- [~GLUser](#) ()
- const std::string & [id](#) () const
Returns the user ID.
- const std::string & [username](#) () const
Returns the username.
- const std::string & [firstname](#) () const
Returns the user's first name.
- const std::string & [lastname](#) () const
Returns the user's last name.
- const std::string & [pass_hash](#) () const
Returns the user's hashed password.
- const std::string & [pass_salt](#) () const
Returns the user's password salt.
- const std::vector< std::string > & [permissions](#) () const
Returns the permissions for a user.
- bool [enabled](#) () const
Returns the user's enabled status.
- void [set_username](#) (const std::string &[new_username](#))
Sets a user's username.
- void [set_firstname](#) (const std::string &[new_firstname](#))

- Sets a user's first name.*
- void [set_lastname](#) (const std::string &new_lastname)
- Sets a user's last name.*
- void [set_enabled](#) (const bool new_enabled)
- Sets a user's enabled status.*
- void [set_password](#) (const std::string &new_pass)
- Sets a user's password hash and salt.*
- bool [check_password](#) (const std::string &check_pass)
- Checks a password against the user's hash.*

Private Attributes

- const std::string [m_id](#)
- std::string [m_username](#)
- std::string [m_firstname](#)
- std::string [m_lastname](#)
- std::string [m_pass_hash](#)
- std::string [m_pass_salt](#)
- const std::vector< std::string > [m_perms](#)
- bool [m_enabled](#)

9.19.1 Detailed Description

General ledger user class.

9.19.2 Constructor & Destructor Documentation

- 9.19.2.1 **GLUser::GLUser (const std::string & *id*, const std::string & *username*, const std::string & *firstname*, const std::string & *lastname*, const std::string & *pass_hash*, const std::string & *pass_salt*, std::vector< std::string > && *perms*, const bool *enabled*)**

Constructor.

Parameters

<i>id</i>	User ID
<i>username</i>	Username
<i>firstname</i>	First name
<i>lastname</i>	Last name
<i>pass_hash</i>	The hashed password
<i>pass_salt</i>	The salt for the hashed password
<i>perms</i>	Vector of user permissions
<i>enabled</i>	true if user is enabled, false otherwise.

9.19.2.2 GLUser::~GLUser ()

Destructor

9.19.3 Member Function Documentation

9.19.3.1 `bool GLUser::check_password (const std::string & check_pass)`

Checks a password against the user's hash.

Parameters

<i>check_pass</i>	The password to check, must be > 8 characters.
-------------------	--

Returns

`true` is the password matches, `false` otherwise.

9.19.3.2 `bool GLUser::enabled () const`

Returns the user's enabled status.

Returns

The user's enabled status.

9.19.3.3 `const std::string & GLUser::firstname () const`

Returns the user's first name.

Returns

The user's first name.

9.19.3.4 `const std::string & GLUser::id () const`

Returns the user ID.

Returns

The user ID.

9.19.3.5 `const std::string & GLUser::lastname () const`

Returns the user's last name.

Returns

The user's last name.

9.19.3.6 `const std::string & GLUser::pass_hash () const`

Returns the user's hashed password.

Returns

The user's hashed password.

9.19.3.7 `const std::string & GLUser::pass_salt () const`

Returns the user's password salt.

Returns

The user's password salt.

9.19.3.8 `const std::vector< std::string > & GLUser::permissions () const`

Returns the permissions for a user.

Returns

A vector of strings containing the names of the permissions held by the user.

9.19.3.9 `void GLUser::set_enabled (const bool new_enabled)`

Sets a user's enabled status.

Parameters

<i>new_enabled</i>	The user's new enabled status.
--------------------	--------------------------------

9.19.3.10 `void GLUser::set_firstname (const std::string & new_firstname)`

Sets a user's first name.

Parameters

<i>new_firstname</i>	The user's new first name.
----------------------	----------------------------

9.19.3.11 `void GLUser::set_lastname (const std::string & new_lastname)`

Sets a user's last name.

Parameters

<i>new_lastname</i>	The user's new last name.
---------------------	---------------------------

9.19.3.12 `void GLUser::set_password (const std::string & new_pass)`

Sets a user's password hash and salt.

Parameters

<i>new_pass</i>	The new password, must be > 8 characters.
-----------------	---

9.19.3.13 `void GLUser::set_username (const std::string & new_username)`

Sets a user's username.

Parameters

<code>new_username</code>	The user's new username.
---------------------------	--------------------------

9.19.3.14 `const std::string & GLUser::username () const`

Returns the username.

Returns

The username.

9.19.4 Member Data Documentation

9.19.4.1 `bool genleg::GLUser::m_enabled [private]`

User's enabled status

9.19.4.2 `std::string genleg::GLUser::m_firstname [private]`

User's first name

9.19.4.3 `const std::string genleg::GLUser::m_id [private]`

User ID

9.19.4.4 `std::string genleg::GLUser::m_lastname [private]`

User's last name

9.19.4.5 `std::string genleg::GLUser::m_pass_hash [private]`

User's hashed password

9.19.4.6 `std::string genleg::GLUser::m_pass_salt [private]`

User's password salt

9.19.4.7 `const std::vector<std::string> genleg::GLUser::m_perms [private]`

List of permissions

9.19.4.8 `std::string genleg::GLUser::m_username [private]`

Username

The documentation for this class was generated from the following files:

- [lib/gldb/gluser.h](#)
- [lib/gldb/gluser.cpp](#)
- [lib/gldb/gluser_pass.cpp](#)

9.20 gldb::MySQLResult Class Reference

MySQL result structure class.

```
#include <dbconn_mysql_result.h>
```

Public Member Functions

- [MySQLResult](#) (MySQL *conn)
Constructor.
- [~MySQLResult](#) ()
- [MySQLResult](#) (const [MySQLResult](#) &result)
- [MySQLResult](#) ([MySQLResult](#) &&result)
- [MySQLResult](#) & operator= (const [MySQLResult](#) &result)
- [MySQLResult](#) & operator= ([MySQLResult](#) &&result)
- MySQL_RES * [result](#) ()
Returns the MYSQL_RES pointer.
- unsigned int [num_fields](#) () const
Returns the number of fields in the result set.

Private Attributes

- MySQL_RES * [m_result](#)
- unsigned int [m_num_fields](#)

9.20.1 Detailed Description

MySQL result structure class.

9.20.2 Constructor & Destructor Documentation

9.20.2.1 MySQLResult::MySQLResult (MySQL * conn) [explicit]

Constructor.

Parameters

<i>conn</i>	MySQL connection
-------------	------------------

Exceptions

DBConnCouldNotQuery	on failure
-------------------------------------	------------

9.20.2.2 gldb::MySQLResult::~~MySQLResult ()

Destructor

9.20.2.3 gldb::MySQLResult::MySQLResult (const MySQLResult & result)

Deleted copy constructor

9.20.2.4 `gldb::MySQLResult::MySQLResult (MySQLResult && result)`

Deleted move constructor

9.20.3 Member Function Documentation

9.20.3.1 `unsigned int glldb::MySQLResult::num_fields () const [inline]`

Returns the number of fields in the result set.

Returns

The number of fields in the result set.

9.20.3.2 `MySQLResult& glldb::MySQLResult::operator= (const MySQLResult & result)`

Deleted copy assignment operator

9.20.3.3 `MySQLResult& glldb::MySQLResult::operator= (MySQLResult && result)`

Deleted move assignment operator

9.20.3.4 `MYSQL_RES* glldb::MySQLResult::result () [inline]`

Returns the MYSQL_RES pointer.

Returns

The MYSQL_RES pointer.

9.20.4 Member Data Documentation

9.20.4.1 `unsigned int glldb::MySQLResult::m_num_fields [private]`

The number of fields in the result set

9.20.4.2 `MYSQL_RES* glldb::MySQLResult::m_result [private]`

The MYSQL_RES pointer

The documentation for this class was generated from the following files:


- [lib/database_imp/mysql/dbconn_mysql_result.h](#)
- [lib/database_imp/mysql/dbconn_mysql_result.cpp](#)

9.21 `gldb::Table` Class Reference

Database table class.

```
#include <table.h>
```

Collaboration diagram for glldb::Table:



Public Member Functions

- [Table](#) (const [TableRow](#) &headers)
Constructor.
- [Table](#) ([TableRow](#) &&headers)
Constructor with move semantics.
- [Table](#) (const [Table](#) &table)
Copy constructor.
- [Table](#) ([Table](#) &&table)
Move constructor.
- [Table](#) & [operator=](#) (const [Table](#) &table)
Copy assignment operator.
- [Table](#) & [operator=](#) ([Table](#) &&table)
Move assignment operator.
- [~Table](#) ()
- size_t [num_fields](#) () const
Returns the number of fields in each row.
- size_t [num_records](#) () const
Returns the number of record in the table.
- void [set_quoted](#) (const std::vector< bool > &vec)
Sets the quote flags for the records.
- void [set_quoted](#) (std::vector< bool > &&vec)
Sets the quote flags for the records with move semantics.
- const [TableRow](#) & [get_headers](#) () const
Returns the field names.
- const [TableRow](#) & [operator\[\]](#) (const size_t idx) const
Overloaded index operator.
- void [append_record](#) (const [TableRow](#) &new_record)
Appends a record to the table.
- void [append_record](#) ([TableRow](#) &&new_record)
Appends a record to the table with move semantics.
- std::string [insert_query](#) (const std::string &table_name, const size_t idx)
Creates an SQL INSERT query from a table record.
- std::string [get_field](#) (const std::string &field_name, const size_t row_index)
Gets a field from a record by field name.

Static Public Member Functions

- static [Table create_from_file](#) (const std::string &filename, const char delim)
Creates a table from an input file.

Private Attributes

- [TableRow m_headers](#)
- std::vector< [TableRow](#) > [m_records](#)
- std::vector< bool > [m_quoted](#)

9.21.1 Detailed Description

Database table class.

9.21.2 Constructor & Destructor Documentation

9.21.2.1 `Table::Table (const TableRow & headers) [explicit]`

Constructor.

Parameters

<i>headers</i>	Table row containing field names.
----------------	---

9.21.2.2 `Table::Table (TableRow && headers) [explicit]`

Constructor with move semantics.

Parameters

<i>headers</i>	Table row containing field names.
----------------	---

9.21.2.3 `Table::Table (const Table & table)`

Copy constructor.

Bug 'explicit' removed from here after failure to compile at end of MySQL query function.

Parameters

<i>table</i>	Table to copy.
--------------	--------------------------------

9.21.2.4 `Table::Table (Table && table)`

Move constructor.

Parameters

<i>table</i>	Table to move.
--------------	--------------------------------

9.21.2.5 Table::~~Table ()

Destructor

9.21.3 Member Function Documentation

9.21.3.1 void Table::append_record (const TableRow & new_record)

Appends a record to the table.

Parameters

<i>new_record</i>	The record to append.
-------------------	-----------------------

9.21.3.2 void Table::append_record (TableRow && new_record)

Appends a record to the table with move semantics.

Parameters

<i>new_record</i>	The record to append.
-------------------	-----------------------

9.21.3.3 Table Table::create_from_file (const std::string & filename, const char delim) [static]

Creates a table from an input file.

Parameters

<i>filename</i>	The name of the input file.
<i>delim</i>	The delimiting character.

Returns

The table.

Exceptions

<i>TableBadInputFile</i>	on badly formed input file.
<i>TableCouldNotOpenInputFile</i>	on bad filename.

9.21.3.4 std::string Table::get_field (const std::string & field_name, const size_t row_index)

Gets a field from a record by field name.

Parameters

<i>field_name</i>	The name of the field.
<i>row_index</i>	The index of the row.

Returns

The contents of the field.

Exceptions

<i>TableNoSuchField</i>	if <code>field_name</code> is not a valid field name.
<i>TableNoSuchRecord</i>	if there is no record at index <code>row_index</code> .

9.21.3.5 `const TableRow& glldb::Table::get_headers () const` `[inline]`

Returns the field names.

Returns

The field names.

9.21.3.6 `std::string Table::insert_query (const std::string & table_name, const size_t idx)`

Creates an SQL INSERT query from a table record.

Parameters

<i>table_name</i>	The name of the table into which to INSERT.
<i>idx</i>	The index of the record.

Returns

A string containing the query.

9.21.3.7 `size_t glldb::Table::num_fields () const` `[inline]`

Returns the number of fields in each row.

Returns

The number of fields in each row.

9.21.3.8 `size_t glldb::Table::num_records () const` `[inline]`

Returns the number of record in the table.

Returns

The number of records in the table.

9.21.3.9 `Table & Table::operator= (const Table & table)`

Copy assignment operator.

Parameters

<i>table</i>	<i>Table</i> to copy.
--------------	---------------------------------------

Returns

Reference to the assigned-to table.

9.21.3.10 `Table & Table::operator= (Table && table)`

Move assignment operator.

Parameters

<i>table</i>	Table to move.
--------------	--------------------------------

Returns

Reference to the assigned-to table.

9.21.3.11 `const TableRow & Table::operator[] (const size_t idx) const`

Overloaded index operator.

Parameters

<i>idx</i>	The zero-based index of the record.
------------	-------------------------------------

Returns

The selected record.

9.21.3.12 `void Table::set_quoted (const std::vector< bool > & vec)`

Sets the quote flags for the records.

Parameters

<i>vec</i>	A vector of bools. The size must match the size of the records.
------------	---

9.21.3.13 `void Table::set_quoted (std::vector< bool > && vec)`

Sets the quote flags for the records with move semantics.

Parameters

<i>vec</i>	A vector of bools. The size must match the size of the records.
------------	---

9.21.4 Member Data Documentation

9.21.4.1 `TableRow gldb::Table::m_headers` `[private]`

The names of the fields

9.21.4.2 `std::vector<bool> gldb::Table::m_quoted` [private]

A vector to show if fields should be quoted for INSERT

9.21.4.3 `std::vector<TableRow> gldb::Table::m_records` [private]

A vector of the records

The documentation for this class was generated from the following files:


- [lib/database/table.h](#)
- [lib/database/table.cpp](#)

9.22 `gldb::TableBadInputFile` Class Reference


Could not connect to database exception class.

```
#include <table.h>
```

Inheritance diagram for `gldb::TableBadInputFile`:



Collaboration diagram for `gldb::TableBadInputFile`:



Public Member Functions

- [TableBadInputFile](#) (const std::string &msg)

Constructor.

9.22.1 Detailed Description

Could not connect to database exception class.

9.22.2 Constructor & Destructor Documentation

9.22.2.1 glldb::TableBadInputFile::TableBadInputFile (const std::string & *msg*) [inline],[explicit]

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- lib/database/[table.h](#)

9.23 glldb::TableCouldNotOpenInputFile Class Reference


Could not connect to database exception class.

```
#include <table.h>
```

Inheritance diagram for glldb::TableCouldNotOpenInputFile:



Collaboration diagram for `gldb::TableCouldNotOpenInputFile`:



Public Member Functions

- [TableCouldNotOpenInputFile](#) (const std::string &msg)
Constructor.

9.23.1 Detailed Description

Could not connect to database exception class.

9.23.2 Constructor & Destructor Documentation

9.23.2.1 `gldb::TableCouldNotOpenInputFile::TableCouldNotOpenInputFile (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- `lib/database/table.h`

9.24 gldb::TableException Class Reference

Base database connection exception class.

```
#include <table.h>
```

Inheritance diagram for glldb::TableException:



Public Member Functions

- [TableException](#) (const std::string &msg)
Constructor.

9.24.1 Detailed Description

Base database connection exception class.

9.24.2 Constructor & Destructor Documentation

9.24.2.1 `glldb::TableException::TableException (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- lib/database/[table.h](#)

9.25 glldb::TableField Class Reference

Database table field class.

```
#include <tablefield.h>
```

Collaboration diagram for `gldb::TableField`:



Public Member Functions

- [TableField](#) (const char *data)
*Constructor accepting `const char *` data.*
- [TableField](#) (const std::string &data)
Constructor accepting `std::string` data.
- [TableField](#) (std::string &&data)
Constructor accepting `std::string` data with move semantics.
- [TableField](#) (const [TableField](#) &field)
Copy constructor.
- [TableField](#) ([TableField](#) &&field)
Move constructor.
- [~TableField](#) ()
- `size_t` [length](#) () const
Returns the length of the field.
- `operator std::string` () const
Overridden conversion operator.
- [TableField](#) & [operator=](#) (const char *data)
*Overridden assignment operator for `const char *`.*
- [TableField](#) & [operator=](#) (const std::string &data)
Overridden assignment operator for `std::string`.
- [TableField](#) & [operator=](#) (std::string &&data)
Overridden assignment operator for `std::string` with move semantics.
- [TableField](#) & [operator=](#) (const [TableField](#) &field)
Overridden copy assignment operator.
- [TableField](#) & [operator=](#) ([TableField](#) &&field)
Overridden move assignment operator.
- char & [operator\[\]](#) (const size_t idx)
Overridden index operator.
- const char & [operator\[\]](#) (const size_t idx) const
Overridden index operator.
- [TableField](#) & [operator+=](#) (const char c)
Overridden compound assignment operator.
- [TableField](#) & [operator+=](#) (const std::string &data)
Overridden compound assignment operator.

Private Attributes

- `std::string m_data`

Friends

- `std::ostream & operator<< (std::ostream &out, const TableField &field)`
Overridden << operator for printing a field.

9.25.1 Detailed Description

Database table field class.

9.25.2 Constructor & Destructor Documentation

9.25.2.1 TableField::TableField (const char * data) [explicit]

Constructor accepting `const char * data`.

Parameters

<i>data</i>	The initial contents of the field.
-------------	------------------------------------

9.25.2.2 TableField::TableField (const std::string & data)

Constructor accepting `std::string data`.

Parameters

<i>data</i>	The initial contents of the field.
-------------	------------------------------------

9.25.2.3 TableField::TableField (std::string && data)

Constructor accepting `std::string data` with move semantics.

Parameters

<i>data</i>	The initial contents of the field.
-------------	------------------------------------

9.25.2.4 TableField::TableField (const TableField & field)

Copy constructor.

Parameters

<i>field</i>	The field from which to copy.
--------------	-------------------------------

9.25.2.5 TableField::TableField (TableField && field)

Move constructor.

Parameters

<i>field</i>	The field from which to move.
--------------	-------------------------------

9.25.2.6 `TableField::~~TableField ()`

Destructor

9.25.3 Member Function Documentation

9.25.3.1 `size_t glDb::TableField::length () const [inline]`

Returns the length of the field.

Returns

The length of the field.

9.25.3.2 `glDb::TableField::operator std::string () const [inline]`

Overridden conversion operator.

Returns the field contents as a string.

9.25.3.3 `TableField & TableField::operator+= (const char c)`

Overridden compound assignment operator.

Parameters

<i>c</i>	The character to append to the field.
----------	---------------------------------------

Returns

A reference to the same field.

9.25.3.4 `TableField & TableField::operator+= (const std::string & data)`

Overridden compound assignment operator.

Parameters

<i>data</i>	The string to append to the field.
-------------	------------------------------------

Returns

A reference to the same field.

9.25.3.5 `TableField & TableField::operator= (const char * data)`

Overridden assignment operator for `const char *`.

Parameters

<i>data</i>	The new contents of the field.
-------------	--------------------------------

Returns

A reference to the same field.

9.25.3.6 TableField & TableField::operator= (const std::string & *data*)

Overridden assignment operator for `std::string`.

Parameters

<i>data</i>	The new contents of the field.
-------------	--------------------------------

Returns

A reference to the same field.

9.25.3.7 TableField & TableField::operator= (std::string && *data*)

Overridden assignment operator for `std::string` with move semantics.

Parameters

<i>data</i>	The new contents of the field.
-------------	--------------------------------

Returns

A reference to the same field.

9.25.3.8 TableField & TableField::operator= (const TableField & *field*)

Overridden copy assignment operator.

Parameters

<i>field</i>	The field to copy.
--------------	--------------------

Returns

A reference to the same field.

9.25.3.9 TableField & TableField::operator= (TableField && *field*)

Overridden move assignment operator.

Parameters

<i>field</i>	The field to move.
--------------	--------------------

Returns

A reference to the same field.

9.25.3.10 `char& glldb::TableField::operator[] (const size_t idx)` `[inline]`

Overridden index operator.

Parameters

<i>idx</i>	The desired index.
------------	--------------------

Returns

A reference to the character at the specified index.

9.25.3.11 `const char& glldb::TableField::operator[] (const size_t idx) const` `[inline]`

Overridden index operator.

Parameters

<i>idx</i>	The desired index.
------------	--------------------

Returns

A const reference to the character at the specified index.

9.25.4 Friends And Related Function Documentation

9.25.4.1 `std::ostream& operator<< (std::ostream & out, const TableField & field)` `[friend]`

Overridden << operator for printing a field.

Parameters

<i>out</i>	The ostream to which to print.
<i>field</i>	A reference to the field.

Returns

A reference to `out`.

9.25.5 Member Data Documentation

9.25.5.1 `std::string glldb::TableField::m_data` `[private]`

The field contents

The documentation for this class was generated from the following files:


- lib/database/[tablefield.h](#)
- lib/database/[tablefield.cpp](#)

9.26 glldb::TableMismatchedRecordLength Class Reference


Mismatched record length exception class.

```
#include <table.h>
```

Inheritance diagram for glldb::TableMismatchedRecordLength:



Collaboration diagram for glldb::TableMismatchedRecordLength:



Public Member Functions

- [TableMismatchedRecordLength](#) (const std::string &msg)
Constructor.

9.26.1 Detailed Description

Mismatched record length exception class.

9.26.2 Constructor & Destructor Documentation

9.26.2.1 `gldb::TableMismatchedRecordLength::TableMismatchedRecordLength (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- [lib/database/table.h](#)

9.27 gldb::TableNoSuchField Class Reference


No such field exception class.

```
#include <table.h>
```

Inheritance diagram for `gldb::TableNoSuchField`:



Collaboration diagram for `gldb::TableNoSuchField`:



Public Member Functions

- [TableNoSuchField](#) (const std::string &msg)
Constructor.

9.27.1 Detailed Description

No such field exception class.

9.27.2 Constructor & Destructor Documentation

9.27.2.1 `glDb::TableNoSuchField::TableNoSuchField (const std::string & msg) [inline], [explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:


- lib/database/[table.h](#)

9.28 glDb::TableNoSuchRecord Class Reference


No such record exception class.

```
#include <table.h>
```

Inheritance diagram for `glDb::TableNoSuchRecord`:



Collaboration diagram for `glDb::TableNoSuchRecord`:



Public Member Functions

- [TableNoSuchRecord](#) (const std::string &msg)
Constructor.

9.28.1 Detailed Description

No such record exception class.

9.28.2 Constructor & Destructor Documentation

9.28.2.1 `gldb::TableNoSuchRecord::TableNoSuchRecord (const std::string & msg) [inline],[explicit]`

Constructor.

Parameters

<i>msg</i>	Database error message
------------	------------------------

The documentation for this class was generated from the following file:

- lib/database/[table.h](#)

9.29 glldb::TableRow Class Reference

Database table row class.

```
#include <tablerow.h>
```

Public Member Functions

- [TableRow](#) ()
Constructor with initial number of fields.
- [TableRow](#) (const size_t size)
Constructor with string vector.
- [TableRow](#) (const std::vector< std::string > &vec)
Constructor with string vector and move semantics.
- [TableRow](#) (std::vector< std::string > &&vec)
Constructor with std::string initializer list.
- [TableRow](#) (std::initializer_list< std::string > i)
Copy constructor.
- [TableRow](#) (const [TableRow](#) &row)
Move constructor.
- [TableRow](#) ([TableRow](#) &&row)
Copy assignment operator.
- [TableRow](#) & operator= ([TableRow](#) &&row)
Move assignment operator.
- [~TableRow](#) ()
- size_t size () const
Returns the number of fields.

- iterator [begin](#) ()
Returns iterator for beginning.
- iterator [end](#) ()
Returns iterator for end plus one.
- const_iterator [begin](#) () const
Returns const iterator for beginning.
- const_iterator [end](#) () const
Returns const iterator for end plus one.
- [TableField](#) & [operator](#)[] (const size_t idx)
Overridden index operator.
- const [TableField](#) & [operator](#)[] (const size_t idx) const
Overridden index operator.
- void [append_field](#) (const char *new_field)
Appends a field to the row.
- void [append_field](#) (const std::string &new_field)
Appends a field to the row.
- void [append_field](#) (std::string &&new_field)
Appends a field to the row with move semantics.
- void [append_field](#) (const [TableField](#) &new_field)
Appends a field to the row.
- void [append_field](#) ([TableField](#) &&new_field)
Appends a field to the row with move semantics.
- void [print](#) (std::ostream &stream) const
Prints a row.
- std::string [record_string](#) (const std::vector< bool > "ed) const
Creates a comma separated string of fields.
- std::string [record_string](#) () const
Creates an unquoted comma separated string of fields.

Private Attributes

- std::vector< [TableField](#) > [m_fields](#)

9.29.1 Detailed Description

Database table row class.

9.29.2 Constructor & Destructor Documentation

9.29.2.1 TableRow::TableRow ()

Default constructor

9.29.2.2 TableRow::TableRow (const size_t size) `[explicit]`

Constructor with initial number of fields.

Parameters

<i>size</i>	The initial number of fields.
-------------	-------------------------------

9.29.2.3 TableRow::TableRow (const std::vector< std::string > & vec) [explicit]

Constructor with string vector.

Parameters

<i>vec</i>	The vector.
------------	-------------

9.29.2.4 TableRow::TableRow (std::vector< std::string > && vec) [explicit]

Constructor with string vector and move semantics.

Parameters

<i>vec</i>	The vector.
------------	-------------

9.29.2.5 TableRow::TableRow (std::initializer_list< std::string > i) [explicit]

Constructor with std::string initializer list.

Parameters

<i>i</i>	The initializer list.
----------	-----------------------

9.29.2.6 TableRow::TableRow (const TableRow & row)

Copy constructor.

Parameters

<i>row</i>	The row to copy.
------------	------------------

9.29.2.7 TableRow::TableRow (TableRow && row)

Move constructor.

Parameters

<i>row</i>	The row to move.
------------	------------------

9.29.2.8 TableRow::~~TableRow ()

Destructor

9.29.3 Member Function Documentation

9.29.3.1 void TableRow::append_field (const char * new_field)

Appends a field to the row.

Parameters

<i>new_field</i>	The contents of the new field.
------------------	--------------------------------

9.29.3.2 void TableRow::append_field (const std::string & *new_field*)

Appends a field to the row.

Parameters

<i>new_field</i>	The contents of the new field.
------------------	--------------------------------

9.29.3.3 void TableRow::append_field (std::string && *new_field*)

Appends a field to the row with move semantics.

Parameters

<i>new_field</i>	The contents of the new field.
------------------	--------------------------------

9.29.3.4 void TableRow::append_field (const TableField & *new_field*)

Appends a field to the row.

Parameters

<i>new_field</i>	A field from which to copy.
------------------	-----------------------------

9.29.3.5 void TableRow::append_field (TableField && *new_field*)

Appends a field to the row with move semantics.

Parameters

<i>new_field</i>	A field from which to copy.
------------------	-----------------------------

9.29.3.6 iterator glldb::TableRow::begin () [inline]

Returns iterator for beginning.

Returns

Iterator for beginning.

9.29.3.7 const_iterator glldb::TableRow::begin () const [inline]

Returns const iterator for beginning.

Returns

Const iterator for beginning.

9.29.3.8 iterator glldb::TableRow::end () [inline]

Returns iterator for end plus one.

Returns

Iterator for end plus one.

9.29.3.9 const_iterator glldb::TableRow::end () const [inline]

Returns const iterator for end plus one.

Returns

Const iterator for end plus one.

9.29.3.10 TableRow & TableRow::operator= (const TableRow & row)

Copy assignment operator.

Parameters

<i>row</i>	The row to copy.
------------	------------------

Returns

A reference to the assigned-to row.

9.29.3.11 TableRow & TableRow::operator= (TableRow && row)

Move assignment operator.

Parameters

<i>row</i>	The row to move.
------------	------------------

Returns

A reference to the assigned-to row.

9.29.3.12 TableField& glldb::TableRow::operator[] (const size_t idx) [inline]

Overridden index operator.

Parameters

<i>idx</i>	The zero-based index of the field.
------------	------------------------------------

Returns

A reference to the field at the specified index.

9.29.3.13 `const TableField& glldb::TableRow::operator[] (const size_t idx) const` `[inline]`

Overridden index operator.

Parameters

<i>idx</i>	The zero-based index of the field.
------------	------------------------------------

Returns

A const reference to the field at the specified index.

9.29.3.14 `void TableRow::print (std::ostream & stream) const`

Prints a row.

Parameters

<i>stream</i>	The ostream to which to print.
---------------	--------------------------------

9.29.3.15 `std::string TableRow::record_string (const std::vector< bool > & quoted) const`

Creates a comma separated string of fields.

Parameters

<i>quoted</i>	A vector of <code>bool</code> , for each field <code>true</code> means that field will be enclosed in single quotes in the comma separated string, <code>false</code> means it will not be.
---------------	---

Returns

The comma separated string.

9.29.3.16 `std::string TableRow::record_string () const`

Creates an unquoted comma separated string of fields.

Returns

The unquoted comma separated string.

9.29.3.17 `size_t glldb::TableRow::size () const` `[inline]`

Returns the number of fields.

Returns

The number of fields.

9.29.4 Member Data Documentation

9.29.4.1 `std::vector<TableField> glldb::TableRow::m_fields` `[private]`

A vector of fields

The documentation for this class was generated from the following files:

- lib/database/[tablerow.h](#)
- lib/database/[tablerow.cpp](#)


Chapter 10

File Documentation

10.1 lib/config/config.cpp File Reference

Implementation of program configurations class.

```
#include <fstream>
#include "config.h"
#include "pgutils/pgutils.h"
Include dependency graph for config.cpp:
```



10.1.1 Detailed Description

Implementation of program configurations class.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.2 lib/config/config.h File Reference

Interface to program configurations class.

```
#include <map>
#include <list>
#include <string>
#include <stdexcept>
Include dependency graph for config.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class `genleg::ConfigException`
Configuration module exception base class.
- class `genleg::ConfigOptionNotSet`
Exception class for option not set.
- class `genleg::ConfigBadOption`
Exception class for bad provided option.
- class `genleg::ConfigCouldNotOpenFile`
Exception class for when conf file cannot be opened.
- class `genleg::ConfigBadConfigFile`
Exception class for badly formed configuration file.
- class `genleg::Config`
Configuration options class.

Enumerations

- enum [genleg::Argument](#)

Enumeration class for option argument specifications.

10.2.1 Detailed Description

Interface to program configurations class.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.3 lib/config/config_getopt.cpp File Reference

Implementation of command line functionality.

```
#include <memory>
#include <getopt.h>
#include "config.h"
```

Include dependency graph for config_getopt.cpp:



Macros

- `#define _XOPEN_SOURCE 600`

10.3.1 Detailed Description

Implementation of command line functionality. Included in separate file to isolate usage of non-standard getopt library.

Author

Paul Griffiths

Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.3.2 Macro Definition Documentation**10.3.2.1 #define _XOPEN_SOURCE 600**

UNIX feature test macro for getopt library

10.4 lib/database/data_structures.h File Reference


Main interface to database data structures.

```
#include "tablefield.h"
```

```
#include "tablerow.h"
```

```
#include "table.h"
```

Include dependency graph for data_structures.h:




```

graph BT
    data_structures_h[lib/database/data_structures.h]
    dbconnimp_h[lib/database/dbconnimp.h]
    dbconn_h[lib/database/dbconn.h]
    dbconn_cpp[lib/database/dbconn.cpp]
    database_h[lib/database/database.h]
    dbconn_mysql_imp_h[lib/database_imp/mysql/dbconn_mysql_imp.h]
    database_imp_h[lib/database_imp/database_imp.h]
    glib_gldatabase_h[lib/glib/gldatabase.h]
    dummy_dbconn_imp_h[lib/database_imp/dummy/dbconn_dummy_imp.h]
    mysql_result_cpp[lib/database_imp/mysql/dbconn_mysql_result.cpp]
    dbconn_mysql_functions_cpp[lib/database_imp/mysql/dbconn_mysql_functions.cpp]
    gl_report_main_cpp[progs/gl_report/gl_report_main.cpp]
    glib_h[lib/glib/glib.h]
    gl_db_main_cpp[progs/gl_db/gl_db_main.cpp]
    gl_user_main_cpp[progs/gl_user/gl_user_main.cpp]
    dummy_dbconn_imp_cpp[lib/database_imp/dummy/dbconn_dummy_imp.cpp]

    data_structures_h --> dbconnimp_h
    data_structures_h --> dbconn_h
    dbconnimp_h --> dbconn_h
    dbconn_h --> dbconn_cpp
    database_h --> data_structures_h
    database_h --> dbconnimp_h
    database_h --> dbconn_h
    database_h --> dbconn_cpp
    database_h --> dbconn_mysql_imp_h
    database_h --> database_imp_h
    database_h --> glib_gldatabase_h
    database_h --> dummy_dbconn_imp_h
    database_h --> mysql_result_cpp
    dbconn_mysql_imp_h --> database_imp_h
    database_imp_h --> gl_report_main_cpp
    database_imp_h --> glib_gldatabase_h
    glib_gldatabase_h --> glib_h
    glib_h --> gl_db_main_cpp
    glib_h --> gl_user_main_cpp
    dummy_dbconn_imp_h --> dummy_dbconn_imp_cpp
  
```

Main interface to database data structures.

Paul Griffiths


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.5 lib/database/database.h File Reference


```
User interface to database functionality.
#include "data_structures.h"
#include "dbconnimp.h"
#include "dbconn.h"
```

```
#include "data_structures.h"
#include "dbconnimp.h"
#include "dbconn.h"
```

Include dependency graph for database.h:



This graph shows which files directly or indirectly include this file:



10.5.1 Detailed Description

User interface to database functionality.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.6 lib/database/dbconn.cpp File Reference

Implementation of database connection class.

```
#include "dbconn.h"
```

Include dependency graph for dbconn.cpp:



10.6.1 Detailed Description

Implementation of database connection class.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.7 lib/database/dbconn.h File Reference

Interface to database connection base class.

```
#include <string>
#include <memory>
#include <stdexcept>
#include "data_structures.h"
#include "dbconnimp.h"
```

Include dependency graph for dbconn.h:



10.8.1 Detailed Description

Interface to abstract database implementation base class.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.9 lib/database/table.cpp File Reference

Implementation of database table data structure.

```
#include <iostream>
#include <fstream>
#include <sstream>
#include <cassert>
#include "table.h"
#include "pgutils/pgutils.h"
```

Include dependency graph for table.cpp:



10.9.1 Detailed Description

Implementation of database table data structure.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.10 lib/database/table.h File Reference

Interface to database table data structure.

```
#include <vector>
#include <stdexcept>
#include "tablerow.h"
Include dependency graph for table.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class `gldb::TableException`
Base database connection exception class.
- class `gldb::TableNoSuchField`
No such field exception class.
- class `gldb::TableNoSuchRecord`
No such record exception class.
- class `gldb::TableMismatchedRecordLength`
Mismatched record length exception class.
- class `gldb::TableBadInputFile`
Could not connect to database exception class.
- class `gldb::TableCouldNotOpenInputFile`
Could not connect to database exception class.
- class `gldb::Table`
Database table class.

10.10.1 Detailed Description

Interface to database table data structure.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.11 lib/database/tablefield.cpp File Reference

Implementation of database table field class.

```
#include "tablefield.h"
```

Include dependency graph for tablefield.cpp:



Classes

- class `gldb::TableField`
Database table field class.

Functions

- `std::ostream & gldb::operator<< (std::ostream &out, const TableField &field)`
Overridden << operator for printing a field.

10.12.1 Detailed Description

Interface to database table field class.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.13 lib/database/ablerow.cpp File Reference

Implementation of database table row data structure.

```
#include <sstream>
#include "ablerow.h"
#include "pgutils/pgutils.h"
Include dependency graph for ablerow.cpp:
```



10.13.1 Detailed Description

Implementation of database table row data structure.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.14 lib/database/tablerow.h File Reference

Interface to database table row data structure.

```
#include <iostream>
#include <vector>
#include <string>
#include "tablefield.h"
Include dependency graph for tablerow.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gldb::TableRow](#)

Database table row class.

10.14.1 Detailed Description

Interface to database table row data structure.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.15 lib/database_imp/database_imp.h File Reference

Interface to database implementation factory function.

```
#include <memory>
#include "database/database.h"
Include dependency graph for database_imp.h:
```



This graph shows which files directly or indirectly include this file:



Functions

- `DBConnImp * gldb::get_connection` (const std::string &database, const std::string &hostname, const std::string &username, const std::string &password)

Creates and returns a pointer to a database implementation.

- `std::string gldb::get_database_type` ()

Returns the name of the compiled-in database type.

10.15.1 Detailed Description

Interface to database implementation factory function.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.16 lib/database_imp/dummy/dbconn_dummy_imp.cpp File Reference

Implementation of Dummy database connection implementation class.

```
#include <sstream>
#include "dbconn_dummy_imp.h"
Include dependency graph for dbconn_dummy_imp.cpp:
```



10.16.1 Detailed Description

Implementation of Dummy database connection implementation class.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.17 lib/database_imp/dummy/dbconn_dummy_imp.h File Reference

Interface to dummy database connection implementation class.

```
#include <string>
#include "database/database.h"
Include dependency graph for dbconn_dummy_imp.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gldb::DBConnDummy](#)

Dummy database implementation class.

10.17.1 Detailed Description

Interface to dummy database connection implementation class.

Author

Paul Griffiths

Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.18 lib/database_imp/mysql/dbconn_mysql_functions.cpp File Reference

Implementation of MySQL implementation factory function.

```
#include "../database_imp.h"
```

```
#include "dbconn_mysql_imp.h"
```

Include dependency graph for dbconn_mysql_functions.cpp:



10.18.1 Detailed Description

Implementation of MySQL implementation factory function.

Author

Paul Griffiths

Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.19 lib/database_imp/mysql/dbconn_mysql_imp.cpp File Reference

Implementation of MySQL database connection implementation class.

```
#include "dbconn_mysql_imp.h"
```

```
#include "dbconn_mysql_result.h"
```

Include dependency graph for dbconn_mysql_imp.cpp:

**Functions**

- static `TableRow get_field_names (MySQLResult &result)`
Gets field names from a MySQL result structure.
- static `TableRow get_row (MySQLResult &result, MYSQL_ROW row)`
Creates a TableRow from a MySQL result row.

10.19.1 Detailed Description

Implementation of MySQL database connection implementation class.


Paul Griffiths

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

```
#include <string>
#include "database/database.h"
#include <my_global.h>
#include <my_sys.h>
#include <mysql.h>
```

```
graph TD; Root["lib/database_imp/mysql/dbconn_mysql_imp.h"] --> DB["database/database.h"]; Root --> MG["my_global.h"]; Root --> MS["my_sys.h"]; Root --> MY["mysql.h"]; Root --> String["string"]; DB --> DBConn["dbconn.h"]; DBConn --> Memory["memory"]; DBConn --> DBConnImp["dbconnimp.h"]; DBConn --> DataStructures["data_structures.h"]; DBConnImp --> DataStructures; DataStructures --> Table["table.h"]; DataStructures --> TableField["tablefield.h"]; DataStructures --> TableRow["tablerow.h"]; Table --> StdExcept["stdexcept"]; Table --> Vector["vector"]; Table --> TableField; TableRow --> String; TableRow --> Iostream["iostream"]; TableField --> String; TableField --> Iostream;
```

This graph shows which files directly or indirectly include this file:



Classes

- class [gldb::DBConnMySQL](#)

MySQL database implementation class.

10.20.1 Detailed Description

Interface to MySQL database connection implementation class.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.21 lib/database_imp/mysql/dbconn_mysql_result.cpp File Reference

Implementation of MySQL result structure resource handle class.

```
#include <string>
#include "database/database.h"
#include "dbconn_mysql_result.h"
Include dependency graph for dbconn_mysql_result.cpp:
```



10.21.1 Detailed Description

Implementation of MySQL result structure resource handle class.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.22 lib/database_imp/mysql/dbconn_mysql_result.h File Reference


Interface to MySQL result structure resource handle class.

```
#include <my_global.h>
#include <my_sys.h>
#include <mysql.h>
```

Include dependency graph for dbconn_mysql_result.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [glb::MySQLResult](#)
MySQL result structure class.

10.22.1 Detailed Description

Interface to MySQL result structure resource handle class.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.23 lib/dbsql/dbsql.h File Reference


User interface to DBSQL module.

```
#include "dbsql_functions.h"  
#include "dbsqlstatements.h"
```

Include dependency graph for dbsql.h:



This graph shows which files directly or indirectly include this file:



10.23.1 Detailed Description

User interface to DBSQL module.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.24 lib/dbsql/dbsql_dummy.h File Reference


Interface to dummy SQL statement class.

```
#include "dbsqlstatements.h"
```

Include dependency graph for `dbsql_dummy.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [genleg::DBSQLDummy](#)
Dummy SQL statements class.

10.24.1 Detailed Description

Interface to dummy SQL statement class.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.25 lib/dbsql/dbsql_implementations.h File Reference

Aggregation header for DBSqlStatements implementations.

```
#include "dbsqlstatements.h"  
#include "dbsql_mysql.h"  
#include "dbsql_dummy.h"
```

Include dependency graph for dbsql_implementations.h:



10.25.1 Detailed Description

Aggregation header for DBSqlStatements implementations.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.26 lib/dbsql/dbsql_mysql.h File Reference


Interface to MySQL SQL statement class.

```
#include "dbsqlstatements.h"
```

Include dependency graph for dbsql_mysql.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [genleg::DBSQLMySQL](#)

MySQL SQL statements class.

10.26.1 Detailed Description

Interface to MySQL SQL statement class.

Author

Paul Griffiths

Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.27 lib/dbsql/dbsqlstatements.cpp File Reference

Implementation of SQL statement class.

```
#include <sstream>
```

```
#include "dbsqlstatements.h"
```

Include dependency graph for dbsqlstatements.cpp:



10.27.1 Detailed Description

Implementation of SQL statement class.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.28 lib/dbsql/dbsqlstatements.h File Reference

Implementation of SQL module standalone functions.

```
#include <string>
#include "gldb/gluser.h"
Include dependency graph for dbsqlstatements.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class `genleg::DBSQLStatements`

Functions

- static bool [boolstring_to_bool](#) (const std::string &bs)
Converts a string representation of a bool to a bool.
- **m_views** ({ "current_trial_balance", "check_total", "all_jes" })

10.29.1 Detailed Description

Implementation of General Ledger database class.

Author

Paul Griffiths

Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.29.2 Function Documentation

10.29.2.1 static bool boolstring_to_bool (const std::string & bs) [static]

Converts a string representation of a bool to a bool.

Parameters

<i>bs</i>	The bool string.
-----------	------------------

Returns

true if *bs* contains "1" or "TRUE", false if *bs* contains "0" or "FALSE".

Exceptions


<i>GLDBException</i>	if <i>bs</i> contains any other value.
----------------------	--

10.30 lib/gldb/gldatabase.h File Reference


Interface to General Ledger database class.

```
#include <vector>
#include <string>
#include "database/database.h"
#include "dbsql/dbsql.h"
#include "gluser.h"
```

Include dependency graph for `gldatabase.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [genleg::GLDatabase](#)
General ledger database class.

10.30.1 Detailed Description

Interface to General Ledger database class.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.31 lib/gldb/gldb.h File Reference


User interface to General Ledger database module.

```
#include "glexception.h"
#include "gldatabase.h"
#include "gluser.h"
```

Include dependency graph for gldb.h:



This graph shows which files directly or indirectly include this file:



10.31.1 Detailed Description

User interface to General Ledger database module.

Author

Paul Griffiths

Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>


10.32 lib/gldb/glexception.h File Reference

Interface to General Ledger base exception class.


```
#include <string>
```

```
#include <stdexcept>
```

Include dependency graph for `glexception.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [genleg::GLDBException](#)

Base general ledger database exception class.

10.32.1 Detailed Description

Interface to General Ledger base exception class.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.33 lib/gdb/gluser.cpp File Reference

Implementation of user class.

```
#include "gluser.h"
Include dependency graph for gluser.cpp:
```



10.33.1 Detailed Description

Implementation of user class.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.34 lib/gdb/gluser.h File Reference


Interface to user class.

```
#include <vector>
#include <string>
```

Include dependency graph for gluser.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [genleg::GLUser](#)
General ledger user class.

10.34.1 Detailed Description

Interface to user class.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.35 lib/gldb/gluser_pass.cpp File Reference

Implementation of password functions for user class.

```
#include <random>
#include <functional>
#include <stdexcept>
#include <unistd.h>
#include "gluser.h"
Include dependency graph for gluser_pass.cpp:
```



Macros

- `#define _XOPEN_SOURCE 600`

Functions

- static std::string `generate_salt ()`
Generates a random two-character salt for crypt()

10.35.1 Detailed Description

Implementation of password functions for user class.

Todo Implement a better form of password encryption. In particular, these functions are not re-entrant, and only use the first 8 characters of the password.

Author

Paul Griffiths

Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.35.2 Macro Definition Documentation

10.35.2.1 `#define _XOPEN_SOURCE 600`

UNIX feature test macro

10.35.3 Function Documentation

10.35.3.1 `static std::string generate_salt () [static]`

Generates a random two-character salt for crypt()

Returns


The two-character salt.

10.36 lib/pgutils/pgutils.h File Reference


Aggregate interface to general utility functions.

```
#include "stringhelp.h"
```

Include dependency graph for pgutils.h:



This graph shows which files directly or indirectly include this file:



10.36.1 Detailed Description

Aggregate interface to general utility functions.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.37 lib/pgutils/stringhelp.cpp File Reference

Implementation of string helper functions.

```
#include <algorithm>
#include <functional>
#include <cctype>
#include <locale>
#include <sstream>
#include "stringhelp.h"
```

Include dependency graph for stringhelp.cpp:



10.37.1 Detailed Description

Implementation of string helper functions.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.38 lib/pgutils/stringhelp.h File Reference


Interface to string helper functions.

```
#include <string>
#include <vector>
```

Include dependency graph for stringhelp.h:



This graph shows which files directly or indirectly include this file:



Functions

- `std::string & pgutils::trim_front (std::string &s)`
Trims leading whitespace from a string.
- `std::string & pgutils::trim_back (std::string &s)`
Trims trailing whitespace from a string.
- `std::string & pgutils::trim (std::string &s)`
Trims leading and trailing whitespace from a string.
- `std::vector< std::string > pgutils::split (const std::string &s, const char delim)`
Splits a delimited string into tokens.
- `std::vector< std::string > & pgutils::split (std::vector< std::string > &vec, const std::string &s, const char delim)`
Splits a delimited string into tokens.
- `bool pgutils::next_content_line (std::istream &ifs, std::string &s)`
Gets the next content line from a stream.
- `std::vector< std::string > & pgutils::content_lines (std::vector< std::string > &vec, std::istream &ifs)`
Populates a vector of content lines from a stream.
- `std::vector< std::vector< std::string > > & pgutils::split_lines (std::vector< std::vector< std::string > > &vec, std::istream &ifs, const char delim)`

Functions

- static void `set_configuration` (`Config` &config, int argc, char *argv[])
Sets program configuration options.
- static bool `check_help_and_version` (const `Config` &config)
Prints help or version messages if requested.
- static bool `check_db_parameters` (const `Config` &config)
Checks if database, hostname and username were provided.
- static void `print_usage_message` ()
Prints a program usage message.
- static void `print_version_message` ()
Prints a program version message.
- static void `print_help_message` ()
Prints a program help message.
- static std::string `login` (void)
Gets a password from the terminal.
- int `main` (int argc, char *argv[])
Main function.

Variables

- static const char * `programe` = "gl_db"
Static variable for program name.

10.39.1 Detailed Description

Main functionality for gl_db program.

Author

Paul Griffiths

Copyright


Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.40 progs/gl_report/gl_report_main.cpp File Reference

Main functionality for gl_report program.

```
#include <iostream>
#include "database/database.h"
#include "database_imp/database_imp.h"
#include "config/config.h"
```

Include dependency graph for `gl_report_main.cpp`:



Functions

- static void `set_configuration` (`genleg::Config` &config, int argc, char *argv[])
Sets program configuration options.
- static void `print_usage_message` ()
Prints a program usage message.
- static void `print_version_message` ()
Prints a program version message.
- static void `print_help_message` ()
Prints a program help message.
- static std::string `login` (void)
Gets a password from the terminal.
- int `main` (int argc, char *argv[])
Main function.

Variables

- static const char * `progrname` = "gl_report"
Static variable for program name.

10.40.1 Detailed Description

Main functionality for gl_report program.

Author

Paul Griffiths


Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

10.41 progs/gl_user/gl_user_main.cpp File Reference

Main functionality for gl_user program.

```
#include <iostream>
#include "gldb/gldb.h"
#include "database/database.h"
#include "config/config.h"
Include dependency graph for gl_user_main.cpp:
```



Functions

- static void [set_configuration](#) ([Config](#) &config, int argc, char *argv[])
Sets program configuration options.
- static bool [check_help_and_version](#) (const [Config](#) &config)
Prints help or version messages if requested.

- static bool `check_db_parameters` (const `Config` &config)
Checks if database, hostname and username were provided.
- `GLUser` `get_user` (`Config` &config, `GLDatabase` &gdb)
Returns a user from either an ID or a name.
- static void `show_user_details` (const `GLUser` &user)
Outputs details for a user.
- static void `enable_user` (`GLUser` &user, `Config` &config, `GLDatabase` &gdb)
Enables or disables a user.
- static void `set_user_password` (`GLUser` &user, `Config` &config, `GLDatabase` &gdb)
Sets a user's password.
- static void `check_user_password` (`GLUser` &user, `Config` &config)
Checks a user's password.
- static void `print_usage_message` ()
Prints a program usage message.
- static void `print_version_message` ()
Prints a program version message.
- static void `print_help_message` ()
Prints a program help message.
- static std::string `login` (void)
Gets a password from the terminal.
- int `main` (int argc, char *argv[])
Main function.

Variables

- static const char * `programe` = "gl_user"
Static variable for program name.

10.41.1 Detailed Description

Main functionality for gl_user program.

Author

Paul Griffiths

Copyright

Copyright 2014 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

Index

- ~Config
 - genleg::Config, [33](#)
- ~DBConnDummy
 - gldb::DBConnDummy, [47](#)
- ~DBConnImp
 - gldb::DBConnImp, [49](#)
- ~DBConnMySQL
 - gldb::DBConnMySQL, [52](#)
- ~DBSQLStatements
 - genleg::DBSQLStatements, [56](#)
- ~GLDatabase
 - genleg::GLDatabase, [60](#)
- ~GLUser
 - genleg::GLUser, [65](#)
- ~MySQLResult
 - gldb::MySQLResult, [69](#)
- ~Table
 - gldb::Table, [72](#)
- ~TableField
 - gldb::TableField, [82](#)
- ~TableRow
 - gldb::TableRow, [90](#)
- _XOPEN_SOURCE
 - config_getopt.cpp, [98](#)
 - gluser_pass.cpp, [138](#)
- add_cmdline_option
 - genleg::Config, [34](#)
- append_field
 - gldb::TableRow, [90](#), [91](#)
- append_record
 - gldb::Table, [73](#)
- backend
 - genleg::GLDatabase, [60](#)
- begin
 - gldb::TableRow, [91](#)
- boolstring_to_bool
 - gldatabase.cpp, [131](#)
- check_db_parameters
 - Database program., [25](#)
 - User administration program., [29](#)
- check_help_and_version
 - Database program., [25](#)
 - User administration program., [30](#)
- check_password
 - genleg::GLUser, [65](#)
- check_user_password
 - User administration program., [30](#)

- Config
 - genleg::Config, [33](#)
- config_getopt.cpp
 - _XOPEN_SOURCE, [98](#)
- ConfigBadConfigFile
 - genleg::ConfigBadConfigFile, [36](#)
- ConfigBadOption
 - genleg::ConfigBadOption, [37](#)
- ConfigCouldNotOpenFile
 - genleg::ConfigCouldNotOpenFile, [39](#)
- ConfigException
 - genleg::ConfigException, [40](#)
- ConfigOptionNotSet
 - genleg::ConfigOptionNotSet, [41](#)
- content_lines
 - General purpose utilities., [21](#)
- create_from_file
 - gldb::Table, [73](#)
- create_structure
 - genleg::GLDatabase, [60](#)
- create_table
 - genleg::DBSQLStatements, [56](#)
- create_user
 - genleg::GLDatabase, [61](#)
- create_view
 - genleg::DBSQLStatements, [56](#)
- DBConn
 - gldb::DBConn, [42](#)
- DBConnCouldNotConnect
 - gldb::DBConnCouldNotConnect, [44](#)
- DBConnCouldNotQuery
 - gldb::DBConnCouldNotQuery, [45](#)
- DBConnDummy
 - gldb::DBConnDummy, [47](#)
- DBConnException
 - gldb::DBConnException, [48](#)
- DBConnImp
 - gldb::DBConnImp, [49](#)
- DBConnMySQL
 - gldb::DBConnMySQL, [51](#), [52](#)
- DBSQLStatements
 - genleg::DBSQLStatements, [56](#)
- Database interaction module, [16](#)
 - get_connection, [17](#)
 - get_database_type, [17](#)
 - get_field_names, [17](#)
 - get_row, [17](#)
- Database program., [25](#)
 - check_db_parameters, [25](#)

- check_help_and_version, 25
 - login, 26
 - main, 26
 - set_configuration, 26
- destroy_structure
 - genleg::GLDatabase, 61
- drop_table
 - genleg::DBSQLStatements, 56
- drop_view
 - genleg::DBSQLStatements, 56
- enable_user
 - User administration program., 30
- enabled
 - genleg::GLUser, 66
- end
 - gldb::TableRow, 91, 92
- firstname
 - genleg::GLUser, 66
- GLDBException
 - genleg::GLDBException, 63
- GLDatabase
 - genleg::GLDatabase, 60
- GLUser
 - genleg::GLUser, 65
- General Ledger database module., 20
- General purpose utilities., 21
 - content_lines, 21
 - join, 21
 - next_content_line, 22
 - replace, 22
 - split, 22
 - split_lines, 23
 - trim, 23
 - trim_back, 23
 - trim_front, 23
- generate_salt
 - gluser_pass.cpp, 139
- genleg::Config, 33
 - ~Config, 33
 - add_cmdline_option, 34
 - Config, 33
 - is_set, 34
 - m_opts_set, 35
 - m_opts_supp, 35
 - populate_from_cmdline, 34
 - populate_from_file, 35
- genleg::ConfigBadConfigFile, 35
 - ConfigBadConfigFile, 36
- genleg::ConfigBadOption, 37
 - ConfigBadOption, 37
- genleg::ConfigCouldNotOpenFile, 38
 - ConfigCouldNotOpenFile, 39
- genleg::ConfigException, 39
 - ConfigException, 40
- genleg::ConfigOptionNotSet, 40
 - ConfigOptionNotSet, 41
- genleg::DBSQLDummy, 53
- genleg::DBSQLMySQL, 54
- genleg::DBSQLStatements, 55
 - ~DBSQLStatements, 56
 - create_table, 56
 - create_view, 56
 - DBSQLStatements, 56
 - drop_table, 56
 - drop_view, 56
 - get_perms, 57
 - grant, 57
 - revoke, 57
 - update_user, 58
 - user_by_id, 58
 - user_by_username, 58
- genleg::GLDBException, 63
 - GLDBException, 63
- genleg::GLDatabase, 58
 - ~GLDatabase, 60
 - backend, 60
 - create_structure, 60
 - create_user, 61
 - destroy_structure, 61
 - GLDatabase, 60
 - get_user_by_id, 61
 - get_user_by_username, 61
 - grant, 62
 - load_sample_data, 62
 - m_dbc, 62
 - m_sql, 63
 - m_tables, 63
 - m_views, 63
 - revoke, 62
 - update_user, 62
- genleg::GLUser, 64
 - ~GLUser, 65
 - check_password, 65
 - enabled, 66
 - firstname, 66
 - GLUser, 65
 - id, 66
 - lastname, 66
 - m_enabled, 68
 - m_firstname, 68
 - m_id, 68
 - m_lastname, 68
 - m_pass_hash, 68
 - m_pass_salt, 68
 - m_perms, 68
 - m_username, 68
 - pass_hash, 66
 - pass_salt, 66
 - permissions, 67
 - set_enabled, 67
 - set_firstname, 67
 - set_lastname, 67
 - set_password, 67
 - set_username, 67

- username, [68](#)
- get_connection
 - Database interaction module, [17](#)
- get_database_type
 - Database interaction module, [17](#)
- get_field
 - gldb::Table, [73](#)
- get_field_names
 - Database interaction module, [17](#)
- get_headers
 - gldb::Table, [74](#)
- get_perms
 - genleg::DBSQLStatements, [57](#)
- get_row
 - Database interaction module, [17](#)
- get_user
 - User administration program., [30](#)
- get_user_by_id
 - genleg::GLDatabase, [61](#)
- get_user_by_username
 - genleg::GLDatabase, [61](#)
- gldatabase.cpp
 - boolstring_to_bool, [131](#)
- gldb::DBConn, [41](#)
 - DBConn, [42](#)
 - m_imp, [43](#)
 - operator=, [42](#)
 - query, [42](#)
 - select, [43](#)
- gldb::DBConnCouldNotConnect, [43](#)
 - DBConnCouldNotConnect, [44](#)
- gldb::DBConnCouldNotQuery, [44](#)
 - DBConnCouldNotQuery, [45](#)
- gldb::DBConnDummy, [46](#)
 - ~DBConnDummy, [47](#)
 - DBConnDummy, [47](#)
 - operator=, [47](#)
 - query, [47](#)
 - select, [47](#)
- gldb::DBConnException, [48](#)
 - DBConnException, [48](#)
- gldb::DBConnImp, [49](#)
 - ~DBConnImp, [49](#)
 - DBConnImp, [49](#)
 - query, [50](#)
 - select, [50](#)
- gldb::DBConnMySQL, [50](#)
 - ~DBConnMySQL, [52](#)
 - DBConnMySQL, [51](#), [52](#)
 - m_conn, [53](#)
 - operator=, [52](#)
 - query, [52](#)
 - select, [52](#)
- gldb::MySQLResult, [69](#)
 - ~MySQLResult, [69](#)
 - m_num_fields, [70](#)
 - m_result, [70](#)
 - MySQLResult, [69](#)
- num_fields, [70](#)
- operator=, [70](#)
- result, [70](#)
- gldb::Table, [70](#)
 - ~Table, [72](#)
 - append_record, [73](#)
 - create_from_file, [73](#)
 - get_field, [73](#)
 - get_headers, [74](#)
 - insert_query, [74](#)
 - m_headers, [75](#)
 - m_quoted, [75](#)
 - m_records, [76](#)
 - num_fields, [74](#)
 - num_records, [74](#)
 - operator=, [74](#), [75](#)
 - set_quoted, [75](#)
 - Table, [72](#)
- gldb::TableBadInputFile, [76](#)
 - TableBadInputFile, [77](#)
- gldb::TableCouldNotOpenInputFile, [77](#)
 - TableCouldNotOpenInputFile, [78](#)
- gldb::TableException, [78](#)
 - TableException, [79](#)
- gldb::TableField, [79](#)
 - ~TableField, [82](#)
 - length, [82](#)
 - m_data, [84](#)
 - operator std::string, [82](#)
 - operator<<, [84](#)
 - operator+=, [82](#)
 - operator=, [82](#), [83](#)
 - TableField, [81](#)
- gldb::TableMismatchedRecordLength, [85](#)
 - TableMismatchedRecordLength, [85](#)
- gldb::TableNoSuchField, [86](#)
 - TableNoSuchField, [87](#)
- gldb::TableNoSuchRecord, [87](#)
 - TableNoSuchRecord, [88](#)
- gldb::TableRow, [88](#)
 - ~TableRow, [90](#)
 - append_field, [90](#), [91](#)
 - begin, [91](#)
 - end, [91](#), [92](#)
 - m_fields, [93](#)
 - operator=, [92](#)
 - print, [93](#)
 - record_string, [93](#)
 - size, [93](#)
 - TableRow, [89](#), [90](#)
- gluser_pass.cpp
 - _XOPEN_SOURCE, [138](#)
 - generate_salt, [139](#)
- grant
 - genleg::DBSQLStatements, [57](#)
 - genleg::GLDatabase, [62](#)
- id
 - genleg::GLUser, [66](#)

- insert_query
 - gldb::Table, 74
- is_set
 - genleg::Config, 34
- join
 - General purpose utilities., 21
- lastname
 - genleg::GLUser, 66
- length
 - gldb::TableField, 82
- lib/config/config.cpp, 95
- lib/config/config.h, 96
- lib/config/config_getopt.cpp, 97
- lib/database/data_structures.h, 98
- lib/database/database.h, 99
- lib/database/dbconn.cpp, 101
- lib/database/dbconn.h, 102
- lib/database/dbconnimp.h, 103
- lib/database/table.cpp, 105
- lib/database/table.h, 106
- lib/database/tablefield.cpp, 107
- lib/database/tablefield.h, 108
- lib/database/ablerow.cpp, 109
- lib/database/ablerow.h, 110
- lib/database_imp/database_imp.h, 112
- lib/database_imp/dummy/dbconn_dummy_imp.cpp, 114
- lib/database_imp/dummy/dbconn_dummy_imp.h, 115
- lib/database_imp/mysql/dbconn_mysql_functions.cpp, 117
- lib/database_imp/mysql/dbconn_mysql_imp.cpp, 118
- lib/database_imp/mysql/dbconn_mysql_imp.h, 119
- lib/database_imp/mysql/dbconn_mysql_result.cpp, 121
- lib/database_imp/mysql/dbconn_mysql_result.h, 122
- lib/dbsql/dbsql.h, 123
- lib/dbsql/dbsql_dummy.h, 124
- lib/dbsql/dbsql_implementations.h, 126
- lib/dbsql/dbsql_mysql.h, 127
- lib/dbsql/dbsqlstatements.cpp, 128
- lib/dbsql/dbsqlstatements.h, 129
- lib/gldb/gldatabase.cpp, 130
- lib/gldb/gldatabase.h, 131
- lib/gldb/gldb.h, 133
- lib/gldb/glexception.h, 134
- lib/gldb/gluser.cpp, 136
- lib/gldb/gluser.h, 136
- lib/gldb/gluser_pass.cpp, 137
- lib/pgutils/pgutils.h, 139
- lib/pgutils/stringhelp.cpp, 140
- lib/pgutils/stringhelp.h, 140
- load_sample_data
 - genleg::GLDatabase, 62
- login
 - Database program., 26
 - Reporting program., 27
 - User administration program., 30
- m_conn
 - gldb::DBConnMySQL, 53
- m_data
 - gldb::TableField, 84
- m_dbc
 - genleg::GLDatabase, 62
- m_enabled
 - genleg::GLUser, 68
- m_fields
 - gldb::TableRow, 93
- m_firstname
 - genleg::GLUser, 68
- m_headers
 - gldb::Table, 75
- m_id
 - genleg::GLUser, 68
- m_imp
 - gldb::DBConn, 43
- m_lastname
 - genleg::GLUser, 68
- m_num_fields
 - gldb::MySQLResult, 70
- m_opts_set
 - genleg::Config, 35
- m_opts_supp
 - genleg::Config, 35
- m_pass_hash
 - genleg::GLUser, 68
- m_pass_salt
 - genleg::GLUser, 68
- m_perms
 - genleg::GLUser, 68
- m_quoted
 - gldb::Table, 75
- m_records
 - gldb::Table, 76
- m_result
 - gldb::MySQLResult, 70
- m_sql
 - genleg::GLDatabase, 63
- m_tables
 - genleg::GLDatabase, 63
- m_username
 - genleg::GLUser, 68
- m_views
 - genleg::GLDatabase, 63
- main
 - Database program., 26
 - Reporting program., 27
 - User administration program., 31
- MySQLResult
 - gldb::MySQLResult, 69
- next_content_line
 - General purpose utilities., 22
- num_fields
 - gldb::MySQLResult, 70
 - gldb::Table, 74
- num_records
 - gldb::Table, 74

- operator std::string
 - gldb::TableField, [82](#)
- operator<<
 - gldb::TableField, [84](#)
- operator+=
 - gldb::TableField, [82](#)
- operator=
 - gldb::DBConn, [42](#)
 - gldb::DBConnDummy, [47](#)
 - gldb::DBConnMySQL, [52](#)
 - gldb::MySQLResult, [70](#)
 - gldb::Table, [74](#), [75](#)
 - gldb::TableField, [82](#), [83](#)
 - gldb::TableRow, [92](#)
- pass_hash
 - genleg::GLUser, [66](#)
- pass_salt
 - genleg::GLUser, [66](#)
- permissions
 - genleg::GLUser, [67](#)
- populate_from_cmdline
 - genleg::Config, [34](#)
- populate_from_file
 - genleg::Config, [35](#)
- print
 - gldb::TableRow, [93](#)
- Program configuration module, [15](#)
- progs/gl_db/gl_db_main.cpp, [142](#)
- progs/gl_report/gl_report_main.cpp, [143](#)
- progs/gl_user/gl_user_main.cpp, [145](#)
- query
 - gldb::DBConn, [42](#)
 - gldb::DBConnDummy, [47](#)
 - gldb::DBConnImp, [50](#)
 - gldb::DBConnMySQL, [52](#)
- record_string
 - gldb::TableRow, [93](#)
- replace
 - General purpose utilities., [22](#)
- Reporting program., [27](#)
 - login, [27](#)
 - main, [27](#)
 - set_configuration, [28](#)
- result
 - gldb::MySQLResult, [70](#)
- revoke
 - genleg::DBSQLStatements, [57](#)
 - genleg::GLDatabase, [62](#)
- SQL statements module, [19](#)
- select
 - gldb::DBConn, [43](#)
 - gldb::DBConnDummy, [47](#)
 - gldb::DBConnImp, [50](#)
 - gldb::DBConnMySQL, [52](#)
- set_configuration
 - Database program., [26](#)
 - Reporting program., [28](#)
 - User administration program., [31](#)
- set_enabled
 - genleg::GLUser, [67](#)
- set_firstname
 - genleg::GLUser, [67](#)
- set_lastname
 - genleg::GLUser, [67](#)
- set_password
 - genleg::GLUser, [67](#)
- set_quoted
 - gldb::Table, [75](#)
- set_user_password
 - User administration program., [31](#)
- set_username
 - genleg::GLUser, [67](#)
- show_user_details
 - User administration program., [31](#)
- size
 - gldb::TableRow, [93](#)
- split
 - General purpose utilities., [22](#)
- split_lines
 - General purpose utilities., [23](#)
- Table
 - gldb::Table, [72](#)
- TableBadInputFile
 - gldb::TableBadInputFile, [77](#)
- TableCouldNotOpenInputFile
 - gldb::TableCouldNotOpenInputFile, [78](#)
- TableException
 - gldb::TableException, [79](#)
- TableField
 - gldb::TableField, [81](#)
- TableMismatchedRecordLength
 - gldb::TableMismatchedRecordLength, [85](#)
- TableNoSuchField
 - gldb::TableNoSuchField, [87](#)
- TableNoSuchRecord
 - gldb::TableNoSuchRecord, [88](#)
- TableRow
 - gldb::TableRow, [89](#), [90](#)
- trim
 - General purpose utilities., [23](#)
- trim_back
 - General purpose utilities., [23](#)
- trim_front
 - General purpose utilities., [23](#)
- update_user
 - genleg::DBSQLStatements, [58](#)
 - genleg::GLDatabase, [62](#)
- User administration program., [29](#)
 - check_db_parameters, [29](#)
 - check_help_and_version, [30](#)
 - check_user_password, [30](#)
 - enable_user, [30](#)

- get_user, [30](#)
- login, [30](#)
- main, [31](#)
- set_configuration, [31](#)
- set_user_password, [31](#)
- show_user_details, [31](#)
- user_by_id
 - genleg::DBSQLStatements, [58](#)
- user_by_username
 - genleg::DBSQLStatements, [58](#)
- username
 - genleg::GLUser, [68](#)