

Minimum Transport Cost

There are N cities in Spring country. Between each pair of cities there may be one transportation track or none. Now there is some cargo that should be delivered from one city to another. The transportation fee consists of two parts:

1. the cost of the transportation on the path between these cities, and
2. a certain tax which will be charged whenever any cargo passing through one city, except for the source and the destination cities.

You must write a program to find the route which has the minimum cost.

Input

The first line of the input is an integer M , then a blank line followed by M datasets. There is a blank line between datasets. The data of path cost, city tax, source and destination cities are given in each dataset, which is of the form:

a_{11}	a_{12}	\dots	a_{1N}
a_{21}	a_{22}	\dots	a_{2N}
\dots	\dots	\ddots	\dots
a_{N1}	a_{N2}	\dots	a_{NN}
b_1	b_2	\dots	b_N
c	d		
e	f		
\dots	\dots		
g	h		

where a_{ij} is the transport cost from city i to city j , $a_{ij} = -1$ indicates there is no direct path between city i and city j . b_i represents the tax of passing through city i . And the cargo is to be delivered from city c to city d , city e to city f , ..., and city g to city h .

Output

For each dataset, you must output the sequence of cities passed by and the total cost, which is of the form:

From c to d :

Path: $c \rightarrow c_1 \rightarrow \dots \rightarrow c_k \rightarrow d$

Total cost : ...

...

From e to f :

Path: $e \rightarrow e_1 \rightarrow \dots \rightarrow e_k \rightarrow f$

Total cost : ...

Print a blank line between datasets,

Sample Input

1

```
0 3 22 -1 4
3 0 5 -1 -1
22 5 0 9 20
-1 -1 9 0 4
4 -1 20 4 0
5 17 8 3 1
1 3
3 5
2 4
```

Sample Output

From 1 to 3 :
Path: 1-->5-->4-->3
Total cost : 21

From 3 to 5 :
Path: 3-->4-->5
Total cost : 16

From 2 to 4 :
Path: 2-->1-->5-->4
Total cost : 17

Miguel A. Revilla
1999-01-11