Response to Reviewer 3

Enhancing Consent Policy Privacy in Blockchain-Based Healthcare Data Sharing

---

Working draft. Page and line references will be added after the revised manuscript reaches final pagination.

Comments 1: *The trust model around the Trusted Proof Service is a major limitation and should be discussed more critically. The paper explicitly assumes that the TPS preserves policy material and requester evidence, but the current evaluation even co-locates the TPS with the provider. This weakens the practical privacy claim, since the most sensitive information is moved off-chain rather than cryptographically protected from the service itself. The paper should more clearly distinguish what is protected from public-chain observers and what is merely trusted to the TPS.*

Response 1: We agree that this is the main architectural limitation, and the revision states it as such in the Problem, Discussion, and Conclusion sections. The distinction the reviewer asks for is now made in two places. The trust-model subsection separates authorization correctness, which the commitment and the on-chain verification enforce regardless of the TPS (and which the revised relation strengthens by binding the program length, the authorization context, and the issuer-signed claims), from policy confidentiality, which is not cryptographically enforced against the TPS and rests on the service following its workflow; it also names what a compromised or colluding TPS can do (expose policy and evidence, substitute unsigned evidence, refuse to prove) and notes that the provider-operated TPS of the evaluation concentrates that trust at the provider. A new threat/guarantee table then lists, for the public-chain observer, the requester, an honest-but-curious TPS, a compromised or colluding TPS, the provider-operated TPS, and a forged issuer, which of policy confidentiality, authorization correctness, liveness, and accountability is cryptographic, TPS-dependent, external, or not provided.

The claim is scoped accordingly: what the evaluation establishes is what a public-chain observer can infer from the artifacts a workflow-following TPS produces, and the abstract, Discussion, and Conclusion say that confidentiality against the service itself is a trust assumption, not a cryptographic property. The Discussion also names the mechanisms that would relocate that trust—collaborative-SNARK or attested proof generation so that no single party sees both policy and evidence, a holder-signed authorization context so that the service cannot reuse evidence it has seen, and accountable proof obligations so that refusals become attributable—and the Related Work section now relates this to self-sovereign-identity designs in which claim release is holder-controlled (Comment 5).

Changes in the manuscript. The trust distinction is stated explicitly in the system model, summarized in a new threat/guarantee matrix, interpreted as the principal architectural trade-off in the Discussion, and carried into the limitations and future directions of the Conclusion.

Location in the revised manuscript: Section "Problem and Threat Model," subsection "System and Trust Model," paragraphs on the provider-operated TPS.

> For implementation and evaluation simplicity, the current evaluation co-locates the TPS with the provider (a provider-operated TPS). This co-location concentrates trust at the provider side: a single party now holds both the policy and the requester

evidence, so a compromised provider-operated TPS could substitute inputs whose origin is not independently authenticated or withhold proof generation from legitimate requesters. Two guarantees must be distinguished here. Authorization correctness is primarily enforced by the commitment and on-chain proof verification: a proof that does not satisfy the committed policy relation is rejected, largely independently of how the TPS is instantiated. Policy confidentiality, in contrast, is not cryptographically enforced against the TPS itself; it rests entirely on the trust assumption stated above. Our evaluation therefore assumes a TPS that follows the prescribed workflow and isolates the remaining question: what a public-chain observer can infer from the resulting public artifacts. Weakening the TPS trust assumption itself is orthogonal and is the role of the reduced-trust instantiations above. Table 3 summarizes, for each party or failure mode, which of the four guarantees—policy confidentiality, authorization correctness, liveness, and accountability—is enforced cryptographically, which holds only under the TPS trust assumption, and which the prototype leaves to external functions or does not provide.

Location in the revised manuscript: Section "Problem and Threat Model," new Table 3, "What each guarantee of TPS-ZKPI rests on, per threat."

Table 3. What each guarantee of TPS-ZKPI rests on, per threat. C: cryptographic (commitment binding, proof soundness and zero knowledge, credential signature, on-chain checks); T: trust in the TPS following the prescribed workflow; E: external or lifecycle function; –: not provided by the prototype.

Threat	Policy confidentiality	Authorization correctness	Liveness	Accountability
Passive public-chain observer	C (proof, commitments) + empirical (gas padding)	C	n/a	C (recorded outcome)
Requester (untrusted)	C: sees only the public view	C: cannot forge a proof or reuse one in another context	n/a	C
Honest-but-curious TPS	T: TPS holds plaintext policy and evidence	C	T	–
Compromised or colluding TPS	–: policy and evidence exposed	C for committed relation; T for origin of unsigned evidence	–: may refuse to prove	–: refusal indistinguishable from denial
Provider-operated TPS (this evaluation)	T, concentrated at the provider	C	T	–
Forged or unauthorized issuer	n/a	C against forgery under the committed key; E for issuer legitimacy and revocation	n/a	E

Location in the revised manuscript: Section "Discussion," paragraphs on the TPS trust trade-off and reduced-trust directions.

The TPS trust assumption is the main architectural tradeoff. Moving confidentiality-sensitive proof generation to the TPS keeps policy-bound proving information away from requesters and public smart contracts while preserving on-chain verifiability, but it shifts part of the confidentiality burden to the service layer; the provider-operated TPS used here concentrates that burden at the provider rather than at an independent service (Section 4). This tradeoff leaves on-chain verifiability intact but does affect liveness and accountability: the TPS or provider can refuse to produce

> a proof, and such a refusal may be indistinguishable from a legitimate denial at the on-chain interface.
>
> Three directions follow. First, adding an explicit chain/contract domain and an authenticated submission channel would extend context binding beyond a single deployment and reduce front-running risk. Second, accountable proof obligations—for example, on-chain commitments to serve requests together with timeout-with-evidence mechanisms—would make proof refusals attributable. Third, the reduced-trust TPS instantiations of Section 4 (collaborative-SNARK or TEE-backed proving) would relax the trust concentration itself, including the attribute-origin limitation; realizing and evaluating them is left to future work.

Location in the revised manuscript: Section "Conclusion," limitations and future-directions paragraphs.

> The results hold for a metadata-only public-chain adversary and are empirical. Policy confidentiality against the TPS itself is not cryptographic but rests on the service following its workflow, and the evaluation's provider-operated TPS concentrates that trust at the provider. The supported policy class is an access-time checker for bounded Boolean policies over standardized terms: institutional or ethics approval, downstream purpose limitation, post-access duties, delegation, and credential revocation stay outside the proved statement. On-chain policy revocation and evolution govern future authorization decisions but do not retract data already released or enforce downstream cessation or deletion. Timing, ordering, mempool, and off-chain channels, adaptive probing, and correlations between outcomes and policy classes are not modeled, and the leakage criterion has a measurable false-positive rate on corpora that execute each policy once.
>
> Three directions follow. Reduced-trust proof generation—collaborative SNARKs or attested execution—would relax the trust concentration that the TPS introduces and, with a holder-signed authorization context, remove the service's ability to reuse valid evidence. A governed issuer registry with in-circuit membership and revocation witnesses would turn the credential path into an institutional guarantee. And extending the evaluation to active adversaries and to the timing and ordering channels excluded here would test whether transcript normalization remains sufficient once the observer is no longer passive.

Comments 2: *The current proof statement leaves important soundness gaps. The paper acknowledges that the program length is not bound into the policy commitment and that the proof is not bound to the requester, resource, or session context. These are not minor implementation details: they directly affect the correctness and replay-resistance of the authorization workflow. These issues should be fixed in the design and experimentally re-evaluated, rather than mainly left to future work.*

Response 2: Both gaps are closed in the revised design and implementation, and the evaluation was repeated on the revised system.

The policy commitment now covers the program length, $h = \mathsf{Poseidon}(\mathsf{H}_{\mathrm{pol}}(P_{\mathrm{enc}}) \parallel \ell \parallel r)$, and the same private ℓ drives both the commitment check and the interpreter, so an authorizing proof cannot rest on a shorter stack-consistent prefix. The proof statement now carries a public context digest $d_\chi = \mathsf{Poseidon}(id_{\mathrm{req}} \parallel id_{\mathrm{res}} \parallel \nu)$ that the circuit constrains and the access-control contract recomputes from the transaction parameters, so a captured proof cannot be paired

with a fresh nonce, another resource, or another requester within a deployment. The measured marginal costs (88 constraints for the length binding; 605 constraints, one public input, and about 56,000 gas for the context binding including the on-chain Poseidon recomputation) are given in the responses to Reviewer 1, Comments 1 and 2, which also describe the regression and end-to-end tests.

The re-evaluation is complete rather than partial. All of-record numbers in the revised manuscript come from a new capture of 1,077 policies and 1,773 Polygon Amoy executions under the frozen revised release (five-signal statement, length- and context-bound relation, credential-derived profile attributes), followed by a new un-padded ablation run of 1,119 executions on the same policy subset. The cost profile reflects the revised circuit (81,740 constraints) and the revised on-chain path, and the results sections report the outcome of the privacy attacks on the revised transcript, including two criterion failures that we report and trace to the padding's random draws rather than to the policy (Reviewer 1, Comments 5 and 6).

Changes in the manuscript. The Design section now defines both bindings as part of the proved relation. The Privacy Evaluation was regenerated from the revised implementation; the updated corpus description, headline results, and final cost profile are reproduced below, with the detailed PCH, PI, SPP, clustering, and ablation tables also replaced by the re-run results.

Location in the revised manuscript: Section "TPS-ZKPI Design," subsection "Commitment Binding and Proof Generation," policy-length binding.

> To bind each proof to a provider-defined hidden policy, the provider samples commitment randomness r uniformly from the scalar field and computes
>
> $$q = \mathsf{H}_{\mathrm{pol}}(P_{\mathrm{enc}}),$$
> $$h = \mathsf{Com}(P_{\mathrm{enc}}, \ell; r) = \mathsf{Poseidon}(q \parallel \ell \parallel r),$$
>
> where q is the Poseidon-based digest of the fixed-length encoded policy, ℓ is the private program length, r is the commitment randomness, and h is the policy commitment stored on-chain. The semantics of an encoded policy are determined by the pair (P_{enc}, ℓ), since ℓ identifies the active prefix of the padded token array. Accordingly, the circuit supplies the same private value ℓ to both the commitment verifier and the policy interpreter. Under the collision resistance of Poseidon, an accepting proof bound to h cannot substitute a different program length and therefore cannot evaluate an alternative stack-consistent prefix of P_{enc}.

Location in the revised manuscript: Section "TPS-ZKPI Design," subsection "Commitment Binding and Proof Generation," authorization-context binding.

> For an access request, let
>
> $$\chi = (id_{\mathrm{req}}, id_{\mathrm{res}}, \nu), \qquad d_\chi = \mathsf{Poseidon}(id_{\mathrm{req}} \parallel id_{\mathrm{res}} \parallel \nu),$$
>
> where ν is a fresh session nonce. The context tuple χ consists of private circuit inputs, while its digest d_χ is public. The current public-signal vector is
>
> $$(1, h, pp, d_\chi, \tau),$$
>
> where pp is a fixed-format commitment to the per-predicate parameters and τ is the request epoch used by the temporal checks. Although the three components of χ are not separate Groth16 public inputs, the ACM receives them as transaction

parameters in order to recompute d_χ; they are therefore visible in transaction calldata. The proof certifies the conjunction that $C(P_{\text{enc}}, \ell, (a, b)) = 1$, $h = \mathsf{Com}(P_{\text{enc}}, \ell; r)$, $d_\chi = \mathsf{Poseidon}(\chi)$, and the selected external-predicate witnesses satisfy their policy-bound verification relations. Before verifying π, the ACM checks that the resource is governed by the stated policy, that τ is current, that the nonce has not been used for the same requester–resource context, and that the digest recomputed from the transaction parameters equals the public signal d_χ. Thus, within one ACM deployment, a proof generated for one requester identifier, resource, and nonce cannot be accepted under a different tuple.

Location in the revised manuscript: Section "Privacy Evaluation," subsection "Dataset and corpus generation," opening paragraph.

We evaluate all three objectives on one policy corpus, so the supervised attacks and the clustering cross-check see the same transactions. The corpus holds **1077 distinct policies** run as **1773 on-chain executions** on *Polygon Amoy*, each execution being one commit transaction followed by one access transaction. The policies are produced by a deterministic generator with a fixed seed (`unified-decoupled-2026`). For reproducibility, this generator uses a deterministic test issuer to create the private profile-credential witnesses used by policies that exercise the credential predicate; this testing key does not model issuer governance or production key management.

Location in the revised manuscript: Section "Privacy Evaluation," updated Table 7, "Headline supervised results on the Polygon Amoy dataset."

Table 7. Headline supervised results on the Polygon Amoy dataset (30 policy-disjoint seeds; a task fails iff $\text{AUC}_{\text{mean}} > 0.55$ and at least 50% of seeds are significant).

Property	Hidden target	Headline supervised result
PCH	DUO terms and ICD-10 chapters	19 of 20 content-recovery tasks pass; AUC 0.464–0.570, significant seeds median 3%. ICD ch5 fails (AUC 0.667, 53%); its separability is carried entirely by the random pad target*
PI	Related policy-pair identity	3 gating tasks pass; AUC 0.509–0.549; significant seeds median 7%, max 10%
SPP	Structure, predicate, parameter, and nesting-depth buckets	20 of 21 pairwise contrasts pass; AUC 0.468–0.571, significant seeds median 7%. `nestingDepth` medium/deep fails (AUC 0.563, 53%); carried by the pad target*

* Rerunning the same protocol on the gas minus the logged pad target returns both tasks to PASS (the PCH and SPP subsections).

Location in the revised manuscript: Section "Privacy Evaluation," updated Table 15, "Single-point cost profile of the final RC1 configuration."

Table 15. Single-point cost profile of the final RC1 configuration at $\mathsf{DEPTH} = 64$. Gas, logs, calldata, and local prover timings are summarized over the 1,773 revised Polygon Amoy executions.

Metric	Value / source
Circuit size	81,740 R1CS constraints; 80,884 wires; $\mathsf{DEPTH} = 64$
Public interface	4 public inputs plus 1 output
Padded on-chain gas	Commit 304,167; access 1,057,283 mean gas
Event logs	Commit: 1 log / 180 bytes; access: 2 logs / 296 bytes
Calldata length	Commit 196 bytes; access 612 bytes (constant across policies)
Local witness time	763.6 ms mean
Local prove time	2,884.2 ms mean

Comments 3: *The policy language is still quite limited. The system focuses on fixed-length Boolean RPN programs, while many realistic healthcare consent policies involve temporal constraints, revocation, obligations, delegation, purpose limitation, institutional approval, and evolving consent. Some of these are treated as external predicate bits, but this moves complexity outside the proven statement. The paper should better explain what kinds of real consent policies can actually be supported end-to-end.*

Response 3: We agree that "external predicate bit" left the guarantee unclear, and the revision answers the question in two steps: the relation no longer accepts unconstrained predicate bits, and the Design section now states feature by feature what the prototype establishes at authorization time.

In the revised relation every predicate bit is derived in-circuit from a witness bound to committed parameters: ontology-scoped conditions (disease, study design, ancestry, geography, clinical term) are Merkle-membership proofs against a provider-committed whitelist root; user-, project-, and institution-specific restrictions are membership proofs of the holder pseudonym in provider-committed allowlists; and the profile-backed data-use terms are derived from the claims of an EdDSA-Poseidon credential that binds the policy commitment, the requester pseudonym, the resource, the claims, a validity interval, and a credential identifier. These profile-backed terms prove possession of signed claims at authorization time, not that subsequent use conforms to a declared purpose. The policy's own validity window is committed and checked against the public request epoch, which the contract requires to equal the current hour.

A new table in the Design section classifies each consent feature as decided in-circuit, decided on-chain by the access-control contract from public state, committed but not decided at request time, or not provided. It also states the compiler's composition limits and distinguishes institution-specific allowlists from institutional or ethics approval, which remains an out-of-circuit step. Policy revocation and resource rebinding govern future authorizations but cannot retract data already released or enforce downstream duties.

The Conclusion lists the unsupported features among its limitations. The Discussion proposes a governed issuer registry with in-circuit membership and non-revocation witnesses, together with holder-authorized presentation through a per-request signature. These extensions could preserve the Boolean interpreter and the fixed public-signal shape, but they would require a revised circuit and new proving and verification keys.

Changes in the manuscript. The supported policy class and its composition rules are now stated explicitly in the Design section and summarized feature by feature in a new table. The Discussion distinguishes implementable extensions from current guarantees, and the Conclusion lists the unsupported features and the prospective-only effect of policy withdrawal.

Location in the revised manuscript: Section "TPS-ZKPI Design," subsection "Policy Representation and Interpretation," paragraph "Scope of the supported policies."

> The policy class is deliberately restricted, and Table 4 states what the RC1 prototype establishes end-to-end. Unrestricted use (NRES) is supported only as a standalone policy; other supported terms may be combined by AND/OR in programs of at most 64 tokens, with each term appearing at most once and MOR/TS restricted to conjunctions. Categorical data-use terms, ontology-scoped conditions, requester allowlists, profile-backed terms, the policy validity window, and time-limited use are decided at authorization time, either inside the proved relation or by the ACM from public state; profile-backed terms establish possession of issuer-signed claims, not conformity of subsequent data use with a declared purpose. A publication moratorium is bound into the policy as an accepted obligation but cannot be decided at

request time, negation is rejected by the DUO compiler, and institutional or ethics approval, downstream purpose limitation, post-access duties, delegation, and credential revocation are left to external governance and the issuer lifecycle. On-chain policy revocation and resource rebinding affect future authorization decisions only; they do not retract data already released or enforce cessation or deletion after access. The prototype is therefore an access-time consent checker for bounded Boolean policies over standardized terms, not a general consent-language engine.

Location in the revised manuscript: Section "TPS-ZKPI Design," subsection "Policy Representation and Interpretation," new Table 4, "Consent-policy features and how far the RC1 prototype establishes them."

Table 4. Consent-policy features and how far the RC1 prototype establishes them. "In-circuit" means the condition is part of the proved relation; "on-chain" means the ACM enforces it from public state; "committed" means the value is bound into the policy but compliance is not decided at request time.

Consent feature	Status	What is established at authorization time
Unrestricted use (NRES)	In-circuit	Compiled as a standalone unconditional policy; it cannot be combined with another DUO term.
Categorical data-use terms combined with AND/OR (13 non-procedural DUO attributes, programs up to 64 tokens)	In-circuit	The committed program and its length are evaluated by the interpreter; each term may appear at most once.
Disease, study-design, ancestry, geography, and clinical-term scopes (DS, RS, POA, GS, CC)	In-circuit	Merkle membership of the requested code in a provider-committed whitelist whose root is bound in the parameter commitment.
User-, project-, and institution-specific restrictions (US, PS, IS)	In-circuit	Membership of the holder pseudonym in a provider-committed allowlist for the scope.
Profile-backed terms (GRU, HMB, NMDS, GSO, NPUNCU, NPOA, NPU, NCU)	In-circuit	EdDSA-Poseidon credential over policy commitment, pseudonym, resource, claims, validity interval, and identifier; the attributes are derived from the signed claims, but subsequent conformity with a declared purpose is not established.
Policy validity window	In-circuit + on-chain	The committed window is checked against the public request epoch, which the ACM requires to equal the current hour.
Time-limited use (TS)	On-chain	The committed duration starts a per-requester window on the first grant; later requests outside it are denied. TS may appear only conjunctively.
Publication moratorium (MOR)	Committed	The deadline is bound into the policy as an accepted obligation; publication conduct is not observable at request time. MOR may appear only conjunctively.
Negation	Not exposed	The interpreter evaluates NOT, but the DUO V3 compiler rejects it: membership witnesses prove inclusion only.
Prospective consent withdrawal and policy evolution	On-chain	A successor policy supersedes its predecessor, a policy can be revoked, and a resource can be rebound for future decisions; this does not retract data already released or enforce downstream cessation or deletion.
Institutional or ethics approval (IRB)	Not provided	Documentary approval and committee review remain an out-of-circuit authorization step.
Downstream purpose limitation, post-access duties (PUB, COL, RTN), delegation, credential revocation	Not provided	Carried by external governance, the data access agreement, and the issuer lifecycle, outside the proved statement.

Location in the revised manuscript: Section "Discussion," paragraphs on issuer governance and the proposed extension.

> A concrete deployment can close this gap without changing the Boolean interpreter. First, a governed issuer registry would publish schema-qualified issuer keys and their validity epochs; registration would validate a canonical, subgroup-safe public key and require proof of possession. Second, an issuer would sign a domain-separated credential containing a holder-key commitment, claim vector, authorization scope, validity interval, and unique credential identifier. Third, the circuit would verify both the credential signature and a Merkle proof that the issuer key is active in the registry, while continuing to derive policy attributes from the signed claims. The holder would retain its secret key and authorize each request by signing the context digest and request epoch; verifying this second signature inside the circuit would prevent a TPS that observes one credential presentation from generating proofs for fresh sessions. Finally, an epoch-specific sparse-Merkle or accumulator root would support a private non-revocation witness for the credential identifier. The registry and revocation roots can occupy fixed-format public or committed parameter slots, preserving the Boolean interpreter and the shape of the policy-independent public interface; integrating these checks would nevertheless require a revised circuit and new proving and verification keys.

Location in the revised manuscript: Section "Conclusion," third paragraph.

> The supported policy class is an access-time checker for bounded Boolean policies over standardized terms: institutional or ethics approval, downstream purpose limitation, post-access duties, delegation, and credential revocation stay outside the proved statement. On-chain policy revocation and evolution govern future authorization decisions but do not retract data already released or enforce downstream cessation or deletion.

Comments 4: *The privacy evaluation is too narrow. The adversary is mainly a passive metadata-only public-chain observer, and the effective leakage channel is reduced mostly to gas usage. This is useful, but it does not cover adaptive requester probing, repeated access attempts, timing/order leakage, off-chain TPS communication patterns, compromised TPS behaviour, or correlations between authorization outcomes and policy classes. The paper should either broaden the evaluation or tone down the privacy claims.*

Response 4: We chose to tone down the claims and to say precisely what the evaluation covers, while making the evaluation of the modeled channel more rigorous.

Toned-down claims. The abstract, Discussion, and Conclusion now describe the result as empirical resistance against the modeled public-chain metadata attacks, and the Discussion lists every exclusion the reviewer names—timing and ordering, mempool and broadcast behaviour, off-chain TPS communication, adaptive probing, repeated attempts, correlations between outcomes and policy classes (every request in the corpus is granted, so this correlation is not exercised), and compromised TPS behaviour—with the statement that the results should not be read as establishing general policy confidentiality against them. The threat model also states why the gas channel is wider than the verifier's arithmetic: the EVM prices calldata per byte, so any deterministic difference in how a public argument is encoded reaches the observer through gas even when calldata length is constant.

A more rigorous treatment of the modeled channel. The evaluation was re-run on the revised system and a new corpus. Two of the 45 supervised tasks now meet the failure criterion; we report them as failures and trace them, by subtracting the logged pad target from the access gas, to coincidences of the padding's own random draws with a label (Reviewer 1, Comments 5 and 6), and we quantify the criterion's false-positive rate with a null simulation. The re-run ablation shows what the un-padded transcript leaks and why: not the policy logic, which the fixed circuit already hides, but the byte pricing of the requester pseudonym, whose encoding width in our harness correlates with whether a policy activates the profile predicate. We report this because it is the kind of channel the reviewer's broader adversary would exploit, and because it shows that the evaluation does detect sub-kilogas deterministic channels when they exist.

We did not add adaptive or timing experiments in this revision. They require a different corpus design (repeated, adversarially chosen requests against the same policy, and control over block inclusion) and an adversary model with an active component; the Conclusion names them as the next step for the evaluation.

Changes in the manuscript. The revised Abstract names the evaluated adversary, the evaluation defines the observable channel and exclusions, and the Discussion and Conclusion state the empirical scope and unmodeled channels explicitly.

Location in the revised manuscript: Abstract.

> We evaluate TPS-ZKPI on Polygon Amoy against metadata-only public-chain adversaries with supervised and unsupervised inference attacks. Under a multi-seed leakage criterion, no attack recovers hidden policy information reproducibly above chance; a paired ablation attributes the gas-channel protection to the gas padding of transcript normalization, at an overhead of about 46% on access and 38% on commit gas.

Location in the revised manuscript: Section "Privacy Evaluation," subsection "Adversary and observables."

> Of these features, calldata length, proof size, and log counts/sizes are constant across policies by design; any policy-dependent signal can therefore only flow through the two gas measurements (`commitGasUsed`, `accessGasUsed`). The fixed circuit and the commitment-only interface make the non-gas features constant; randomized gas padding protects the gas channel that remains. That channel is wider than the verifier's arithmetic: because the EVM prices calldata per byte (four gas for a zero byte, sixteen otherwise), the gas of an access transaction also encodes the byte pattern of its public arguments, so any deterministic difference in how an argument is encoded reaches the observer through gas even when the calldata length is constant. The constant features remain in the attack pipeline but carry no variation to exploit. We do not model side channels such as block timing, transaction ordering, mempool or broadcast patterns, or off-chain TPS communication, nor the non-goals stated in the Problem and Threat Model section.

Location in the revised manuscript: Section "Discussion," opening and scope paragraphs.

> The evaluation supports a scoped claim: against the modeled public-chain metadata adversary, TPS-ZKPI provides empirical resistance rather than proven policy confidentiality. Of the 45 supervised tasks, 43 stay below the multi-seed leakage criterion, and unsupervised clustering shows no recoverable structure beyond one small,

permutation-significant nesting-depth ARI. The two tasks that meet the criterion—one ICD-10 chapter and the `nestingDepth medium/deep` contrast—are reported as failures, and both are carried by the random pad target rather than by the policy: subtracting the logged target from the access gas returns each to PASS, and replacing the gas features by policy-independent draws reproduces such failures in four of ten replicates. This is a property of the criterion on a corpus in which coverage-layer policies are executed once, so the thirty seeds resample the same random draws; we keep the criterion as stated and document the diagnostic, since lowering the significance threshold or raising the AUC threshold to absorb these cases would weaken it for genuine leaks. The gas-padding ablation attributes the gas-channel protection to randomized gas padding: without it the same attacks recover the policy family with AUCs up to 0.90. Content hiding itself rests on the commitment-only interface and the content-independent transcript normalization; padding is the defense-in-depth layer that absorbs whatever deterministic gas differences remain, of which the ablation exhibits one that does not come from the policy logic at all but from the byte encoding of a public transaction argument. Together with fixed-length policy representation, reusable interpretation, and commitment binding, these mechanisms limit the extent to which public-chain observers infer hidden policy content or structural properties from authorization transactions.

The scope of this claim is the adversary of Section 6.1: a passive observer of commitments, proofs, public parameters, calldata, events, and gas, on a corpus of generated policies. Timing and ordering of transactions, mempool and broadcast behaviour, off-chain communication with the TPS, adaptive requester probing, repeated access attempts, correlations between authorization outcomes and policy classes (every request in the corpus is granted), and compromised TPS behaviour are not modeled, and the results should not be read as establishing general policy confidentiality against them.

Location in the revised manuscript: Section "Conclusion," limitations and future-directions paragraphs.

The results hold for a metadata-only public-chain adversary and are empirical. Policy confidentiality against the TPS itself is not cryptographic but rests on the service following its workflow, and the evaluation's provider-operated TPS concentrates that trust at the provider. The supported policy class is an access-time checker for bounded Boolean policies over standardized terms: institutional or ethics approval, downstream purpose limitation, post-access duties, delegation, and credential revocation stay outside the proved statement. On-chain policy revocation and evolution govern future authorization decisions but do not retract data already released or enforce downstream cessation or deletion. Timing, ordering, mempool, and off-chain channels, adaptive probing, and correlations between outcomes and policy classes are not modeled, and the leakage criterion has a measurable false-positive rate on corpora that execute each policy once.

Three directions follow. Reduced-trust proof generation—collaborative SNARKs or attested execution—would relax the trust concentration that the TPS introduces and, with a holder-signed authorization context, remove the service's ability to reuse valid evidence. A governed issuer registry with in-circuit membership and revocation witnesses would turn the credential path into an institutional guarantee. And extending the evaluation to active adversaries and to the timing and ordering channels excluded here would test whether transcript normalization remains sufficient once the observer is no longer passive.

Comments 5: *The comparison with related work should be strengthened by considering recent blockchain-based access-control architectures that combine smart contracts, SSI-oriented trust models, and cryptographic mechanisms for controlling access to sensitive claims. In particular, the paper should better position TPS-ZKPI with respect to the issues discussed in DOI: 10.1016/j.bcra.2024.100196, especially regarding verifier authorization, smart-contract accountability, off-chain trust assumptions, and practical access-control workflows.*

Response 5: We thank the reviewer for the pointer. The Related Work section now contains a paragraph on self-sovereign-identity architectures that positions TPS-ZKPI against Buccafurri, De Angelis, and Nardone (Blockchain: Research and Applications, 2024) along the four dimensions named, together with recent zero-knowledge authentication work (Madine et al., 2025) and surveys of zero-knowledge proofs for blockchain privacy.

- *Verifier authorization.* In the CP-ABPRE design the holder's claims are readable only by verifiers that satisfy a holder-defined policy. In TPS-ZKPI the protected object is the provider's consent policy, not the requester's claim set: the claims are consumed as private witnesses of a proof whose statement is fixed and whose verifier is a public contract, so any observer may verify and verifier authorization is not a design question.
- *Smart-contract accountability.* There the contract meters the release of claims and keeps verifiers accountable; here the contract records the context-bound authorization outcome, and accountability attaches to that record rather than to claim release.
- *Off-chain trust.* An SSI verifier that decrypts a claim learns it; the TPS learns both policy and claims. This is why the Problem section treats the TPS as an explicit trust boundary and the new threat/guarantee table states what survives its compromise (Comment 1).
- *Access-control workflow.* The two designs sit on opposite sides of the same authorization relation. Combining them through holder-authorized presentation, including a per-request signature over the authorization context, would prevent a TPS that observes one credential presentation from reusing the evidence for fresh sessions.

Changes in the manuscript. The complete comparison paragraph and the added reference are reproduced below.

Location in the revised manuscript: Section "Related Work," new paragraph on self-sovereign-identity architectures.

> Self-sovereign-identity (SSI) architectures move authorization to verifiable claims held by the requester and shift the question to whom the holder may trust with those claims. Buccafurri et al. combine smart contracts with ciphertext-policy attribute-based proxy re-encryption so that a holder's claims can be read only by verifiers that satisfy a holder-defined policy, with the contract keeping verifiers accountable for the access they obtain; zero-knowledge presentations of credentials likewise let a patient authenticate anonymously against public or private chains, and surveys of zero-knowledge proofs for blockchain privacy catalogue this design space. TPS-ZKPI sits on the other side of the same authorization relation. In SSI designs the protected object is the requester's claim set and the policy that governs it is the holder's, whereas here the protected object is the provider's consent policy: the requester's claims are consumed as private witnesses of a proof whose statement is fixed and whose verifier is a public contract, so verifier authorization is not a design question (any observer may verify) and accountability is carried by the recorded, context-bound outcome rather than by a contract that meters the release of claims. The trust the two settings place off-chain also differs: an SSI verifier that decrypts

> a claim learns it, whereas the TPS learns both policy and claims, which is why Section 4 treats the TPS as an explicit trust boundary and Table 3 states what survives its compromise. Combining the two—holder-authorized presentation of the claims that TPS-ZKPI consumes as witnesses, including a per-request signature over the authorization context—would prevent a TPS that observes one presentation from reusing the evidence for fresh sessions, as discussed in Section 7.

Location in the revised manuscript: Reference list, new entry for Buccafurri et al. (2024).

> Buccafurri, F.; De Angelis, V.; Nardone, R. How can the holder trust the verifier? A CP-ABPRE-based solution to control the access to claims in a Self-Sovereign-Identity scenario. *Blockchain: Research and Applications* 2024, 5, 100196. `https://doi.org/10.1016/j.bcra.2024.100196`.

Comments 6: *The cost and scalability analysis needs more depth. The reported gas-padding overhead is substantial, around 38% for access and 40% for commit operations, and the evaluation is performed at a single circuit depth. The paper should evaluate how costs change with larger policy programs, richer predicates, more complex DUO/ICD conditions, and more realistic access workloads. Otherwise, it is difficult to judge whether the design is practical for real healthcare data-sharing platforms.*

Response 6: We added a cost-scaling analysis and restructured the cost discussion around the distinction that decides practicality: which costs are paid on-chain, and which off-chain.

Larger policy programs. A new table reports the prover-side cost of the revised circuit at program lengths 32, 64 (the deployed value), and 128 with the attribute and predicate counts fixed: R1CS constraints grow from 64,945 to 81,740 to 134,009, the proving key from 39 to 52 to 88 MB, and proving time from 0.38 to 0.49 to 0.73 s per proof on a laptop-class prover (witness generation 0.28–0.54 s). The verification side does not change: the statement keeps its five public signals at every length, so the verifier contract, its gas, and the padding band are the same.

Richer predicates and more complex DUO/ICD conditions. These enter through the predicate slots and their gadgets (Merkle membership for ontology scopes and allowlists, the credential verifier for profile-backed terms) rather than through the program length. Each additional slot adds its gadget's constraints to the prover and nothing to the on-chain cost, because predicate parameters are bound through the fixed-format parameter commitment rather than exposed as public inputs; a larger ICD or OBI whitelist changes only the Merkle root the provider commits, not the circuit or the gas. The revised corpus exercises this: whitelists range from 2 to 32 codes across five vocabularies, and the access gas of the un-padded ablation run varies by 276 gas across 1,119 executions.

Access workloads. The padding overhead is a fixed premium per transaction (about 330,000 gas on access and 85,000 on commit; 0.032 versus 0.022 POL per access at the evaluation's gas price), so it scales linearly with the number of authorizations and does not compound; the Discussion now states this together with how the band is calibrated per network (Reviewer 1, Comment 7). We did not run a throughput benchmark: the on-chain path is one Groth16 verification plus bookkeeping per authorization and is bounded by the chain, not by the design, while the off-chain path is embarrassingly parallel across TPS instances.

Changes in the manuscript. The Ablation subsection now reports the measured on-chain cost and separates it from prover-side scaling; the new scaling table gives the complete depth sweep; and the Discussion explains transaction-volume scaling and network calibration.

Location in the revised manuscript: Section "Privacy Evaluation," subsection "Ablation," paragraph "Cost."

> Padding is not free: over the subset it raises mean commit gas from 219,737 (B1) to 304,098 (B2), a 38.4% increase, and mean access gas from 723,462 to 1,056,674, a 46.1% increase. The padded access cost is set by the padding band, not by the policy: the TPS draws the target uniformly from 945,000–1,155,000 gas, and the base of that band is chosen above the bare access cost measured on the target network (748,000 gas on Amoy, whose pricing of the pairing precompiles is higher than the local EVM's) so that the whole band stays above real usage. At the 30 gwei tip used throughout, one padded access transaction costs about 0.032 POL and one commit about 0.009 POL; the overhead is therefore a fixed per-transaction premium of roughly 330,000 gas on access and 85,000 on commit, independent of transaction volume, and it does not grow with policy complexity, because neither the bare cost nor the band depends on the policy. Table 15 gives the single-point cost characterization of the final RC1 configuration at DEPTH = 64. The circuit compiles to 81,740 R1CS constraints; across the 1,773 Polygon Amoy executions, mean witness and proving times on the two-core capture host are 763.6 ms and 2,884.2 ms, respectively. Gas, logs, calldata lengths, and transaction objects are taken from the same executed dataset, whose transactions use the context-bound five-signal statement. Table 16 shows how the prover-side cost scales when the program length grows from DEPTH = 32 to 128 with N and M fixed: constraints, proving-key size, and proving time grow roughly linearly with DEPTH (from 65,000 to 134,000 constraints and from 0.38 to 0.73 s per proof on a laptop-class prover), while the statement keeps its five public signals, so the verifier contract, its gas, and the padding band are unchanged. Richer predicates would enter through M and the per-slot gadgets rather than through DEPTH; each additional slot adds its gadget's constraints to the prover and nothing to the on-chain cost, since predicate parameters are bound through the fixed-format parameter commitment rather than exposed as public inputs.

Location in the revised manuscript: Section "Privacy Evaluation," new Table 16, "Prover-side cost as the policy program length grows."

Table 16. Prover-side cost as the policy program length DEPTH grows, with $N = 13$, $M = 11$ and the public interface fixed. On-chain verification cost does not change: the statement keeps five public signals at every depth.

DEPTH	R1CS constraints	Proving key (MB)	Witness (ms)	Prove (ms)	Verify (ms)
32	64,945	38.7	282	382	11
64	81,740	52.2	343	494	10
128	134,009	87.5	542	730	11

Location in the revised manuscript: Section "Discussion," paragraph "The cost of padding."

> Within this scope, the residual cost is the randomized padding's gas overhead: on the ablation subset, about 46% on access gas and 38% on commit gas. Three observations bound its practical weight. First, the overhead is a fixed premium per transaction—roughly 330,000 gas on access and 85,000 on commit at the band used here—so it scales linearly with transaction volume and does not compound: at the 30 gwei tip of the evaluation, a padded access transaction costs about 0.032 POL against 0.022 POL unpadded. Second, neither the bare cost nor the band depends on the policy: the fixed circuit gives every proof the same verification work and the same

five public signals, and the prover-side cost of longer or richer policies (Table 16) is paid off-chain. Third, the band must be positioned above the bare cost on the target network, which differs between networks (the same verifier costs 243,000 gas on a local EVM and 372,000 on Amoy, whose pairing precompiles are priced higher); a deployment therefore calibrates the base target once per network, and the width of the band, ±10% here, is what determines how large a deterministic difference it can submerge. Padding cannot, of course, hide a difference larger than its band, and it does not address channels that are not gas.