



# APSTA-GE 2352

Statistical Computing: Lecture 11

Klint Kanopka

New York University

NYUGreyArtGallery

SEYER CENTER

WASHINGTON St



# Table of Contents

## 1. Statistical Computing - Week 11

### 1. Table of Contents

### 2. Announcements

## 2. Advanced Debugging

### 1. The tools we have so far

### 2. A more powerful debugging tool: `browser()`

## 3. The `apply()` Family

### 1. Side Effects

### 2. The `apply()` Family

### 3. Applying `apply()`

## 4. Wrap Up



# Check-In

- [Pollev.com/klintkanopka](https://Pollev.com/klintkanopka)

# Announcements

- PS6 is posted!
  - It's your 2nd to last pset
  - It's shorter than PS5
- Lab on Wednesday before Thanksgiving is cancelled
- After today:
  - 3 more lectures
  - 3 more labs
  - 2 more psets
- Reminder about next week's PRIISM seminar talk with my friend Charlie Rahal from Oxford!

# Advanced Debugging

The tools we have so far

# The tools we have so far

- Googling error messages

# The tools we have so far

- Googling error messages
- `print()` statements



# The tools we have so far

- Googling error messages
- `print()` statements
- `traceback()`

# The tools we have so far

- Googling error messages
- `print()` statements
- `traceback()`
- Any others?

What about generative AI?

# What about generative AI?

- I honestly don't know much about debugging code with tools like ChatGPT

# What about generative AI?

- I honestly don't know much about debugging code with tools like ChatGPT
- What's your experience been with using ChatGPT to help you debug or write code?

# What about generative AI?

- I honestly don't know much about debugging code with tools like ChatGPT
- What's your experience been with using ChatGPT to help you debug or write code?
- Are there other models/tools that you use?

# What about generative AI?

- I honestly don't know much about debugging code with tools like ChatGPT
- What's your experience been with using ChatGPT to help you debug or write code?
- Are there other models/tools that you use?
- What prompting strategies do you use?



# What about generative AI?

- I honestly don't know much about debugging code with tools like ChatGPT
- What's your experience been with using ChatGPT to help you debug or write code?
- Are there other models/tools that you use?
- What prompting strategies do you use?
- Do you feel like using generative AI to help with coding tasks increases your understanding?

# What about generative AI?

- I honestly don't know much about debugging code with tools like ChatGPT
- What's your experience been with using ChatGPT to help you debug or write code?
- Are there other models/tools that you use?
- What prompting strategies do you use?
- Do you feel like using generative AI to help with coding tasks increases your understanding?
- Any other notes?

# A more powerful debugging tool: `browser()`

- `browser()` lets you step into the code and execute it line by line while you monitor what is loaded in each environment and the values of intermediate objects
- You can further step into functions you encounter along the way
- How does it work?
  - You insert the `browser()` function call into some code you want to debug
  - From here, the right pane shows you the values and variables for the environment you're currently executing code in
  - You get a special prompt in the console, `Browse[1]>` to let you know you're doing browser stuff
  - All execution halts and the next line to be run appears above the prompt

# Using `browser()`

- First, you can use the `Browse[1]>` prompt like any other sort of console prompt and execute code from there
- Second, and more importantly, you get access to a bunch of new commands:
  1. `n` runs the **next** line of code (whatever is currently above the prompt)
  2. `s` is like next, but if the next line is a function, you'll **step into** it and run it interactively (line-by-line)
  3. `c` stops running code line-by-line and **continues** executing the current function you're currently in
  4. `Q` **quits** out of the browser

# Why and how to use `browser()` ?

- Essentially it's not too far off from inserting `print()` statements after every single line
- It allows you to see what changes after each line of code is run
- You can also insert code into a function to see if it fixes your problem
- A few other ways to use it:
  - Running `debug(FUN())` inserts `browser()` into the first line of `FUN()` , and so running `FUN()` will *always* open the browser. Stop this with `undebbug(FUN())`
  - `debugonce(FUN(args))` runs `FUN(args)` immediately opening a browser, but doesn't modify `FUN()`

# Why and how to use `browser()` ?

- Essentially it's not too far off from inserting `print()` statements after every single line
- It allows you to see what changes after each line of code is run
- You can also insert code into a function to see if it fixes your problem
- A few other ways to use it:
  - Running `debug(FUN())` inserts `browser()` into the first line of `FUN()` , and so running `FUN()` will *always* open the browser. Stop this with `undebbug(FUN())`
  - `debugonce(FUN(args))` runs `FUN(args)` immediately opening a browser, but doesn't modify `FUN()`
- **Next let's use `browser()` with the activity from lab yesterday**

# The `apply()` Family



# Side Effects

- If a function or operation modifies things outside its local environment, it has “side effects”
- These side effects can be hard to observe, but cause serious errors in analysis!
- Side effects most often occur when we are trying to hack together a solution to a problem
  - Functions that take and modify information from the global environment
  - Janky loops

# Avoiding Side Effects

- Writing things in functions is a good start!
  - Calls to functions generate new environments
  - New environments protect data in the global environment
- We can “hide loops”
  - The `apply()` family of functions does this really well
  - These nest the entire loop we want to carry out inside of a function call

# The `apply()` Family

- `apply()` takes a function and applies it to each element of a data object
- Whole bunch of different `apply()` functions
  - Different functions take different data objects as input
  - Different functions spit out different data objects
- Note that `apply()` functions aren't really any faster than loops!
  - They are not vectorized
  - They are, however, very easy to *parallelize*

# The main `apply()` functions

function	input	output	comment
<code>apply()</code>	matrix or array	vector or array or list	
<code>lapply()</code>	list or vector	list	
<code>sapply()</code>	list or vector	vector or matrix or list	simplify
<code>vapply()</code>	list or vector	vector or matrix or list	safer simplify
<code>tapply()</code>	data, categories	array or list	ragged
<code>mapply()</code>	lists and/or vectors	vector or matrix or list	multiple

Applying `apply()`

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1 # TODO
```

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1 Ns <- seq(from = 50, to = 1000, by = 50)
```



# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1 Ns <- seq(from = 50, to = 1000, by = 50)
2 M <- 1000
```

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1 Ns <- seq(from = 50, to = 1000, by = 50)
2 M <- 1000
3 means <- list(length = length(Ns))
```

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1 Ns <- seq(from = 50, to = 1000, by = 50)
2 M <- 1000
3 means <- list(length = length(Ns))
4
5 for (i in seq_along(Ns)) {
6
7 }
```

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1 Ns <- seq(from = 50, to = 1000, by = 50)
2 M <- 1000
3 means <- list(length = length(Ns))
4
5 for (i in seq_along(Ns)) {
6   for (j in 1:M) {
7
8   }
9 }
```

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1 Ns <- seq(from = 50, to = 1000, by = 50)
2 M <- 1000
3 means <- list(length = length(Ns))
4
5 for (i in seq_along(Ns)) {
6   means[[i]] <- vector(length = M)
7   for (j in 1:M) {
8
9   }
10 }
```

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1 Ns <- seq(from = 50, to = 1000, by = 50)
2 M <- 1000
3 means <- list(length = length(Ns))
4
5 for (i in seq_along(Ns)) {
6   means[[i]] <- vector(length = M)
7   for (j in 1:M) {
8     means[[i]][j] <- mean(rnorm(Ns[i]))
9   }
10 }
```

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1  Ns <- seq(from = 50, to = 1000, by = 50)
2  M <- 1000
3  means <- list(length = length(Ns))
4
5  for (i in seq_along(Ns)) {
6    means[[i]] <- vector(length = M)
7    for (j in 1:M) {
8      means[[i]][j] <- mean(rnorm(Ns[i]))
9    }
10 }
11
12 d_mean <- data.frame()
```



# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1  Ns <- seq(from = 50, to = 1000, by = 50)
2  M <- 1000
3  means <- list(length = length(Ns))
4
5  for (i in seq_along(Ns)) {
6    means[[i]] <- vector(length = M)
7    for (j in 1:M) {
8      means[[i]][j] <- mean(rnorm(Ns[i]))
9    }
10 }
11
12 d_mean <- data.frame(n = , mean = )
```

# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1  Ns <- seq(from = 50, to = 1000, by = 50)
2  M <- 1000
3  means <- list(length = length(Ns))
4
5  for (i in seq_along(Ns)) {
6    means[[i]] <- vector(length = M)
7    for (j in 1:M) {
8      means[[i]][j] <- mean(rnorm(Ns[i]))
9    }
10 }
11
12 d_mean <- data.frame(n = , mean = do.call(c, means))
```


# Uncertainty in mean estimates

- First we conduct a simulation study to observe how the uncertainty in estimating the mean of a normal distribution depends on the number of samples we draw from it

```
1  Ns <- seq(from = 50, to = 1000, by = 50)
2  M <- 1000
3  means <- list(length = length(Ns))
4
5  for (i in seq_along(Ns)) {
6    means[[i]] <- vector(length = M)
7    for (j in 1:M) {
8      means[[i]][j] <- mean(rnorm(Ns[i]))
9    }
10 }
11
12 d_mean <- data.frame(n = rep(Ns, each = M), mean = do.call(c, means))
```

# Visualizing uncertainty in mean estimates

```
1 ggplot(d_mean, aes(x = n,  
2                   y = mean,  
3                   group = n)) +  
4   geom_boxplot(alpha = 0.5,  
5               fill = okabeito_colors(3)) +  
6   theme_bw()
```



# Estimating uncertainty directly

- Next we visualize our estimates of the standard errors of these sampling distributions at each sample size

```
1 # TODO
```

# Estimating uncertainty directly

- Next we visualize our estimates of the standard errors of these sampling distributions at each sample size

```
1 sds <- vector(length = length(Ns))
```

# Estimating uncertainty directly

- Next we visualize our estimates of the standard errors of these sampling distributions at each sample size

```
1 sds <- vector(length = length(Ns))  
2  
3 for (i in seq_along(Ns)) {  
4  
5 }
```

# Estimating uncertainty directly

- Next we visualize our estimates of the standard errors of these sampling distributions at each sample size

```
1 sds <- vector(length = length(Ns))
2
3 for (i in seq_along(Ns)) {
4   sds[i] <- sd(means[[i]])
5 }
```



# Estimating uncertainty directly

- Next we visualize our estimates of the standard errors of these sampling distributions at each sample size

```
1 sds <- vector(length = length(Ns))
2
3 for (i in seq_along(Ns)) {
4   sds[i] <- sd(means[[i]])
5 }
6
7 d_sd <- data.frame()
```

# Estimating uncertainty directly

- Next we visualize our estimates of the standard errors of these sampling distributions at each sample size

```
1 sds <- vector(length = length(Ns))
2
3 for (i in seq_along(Ns)) {
4   sds[i] <- sd(means[[i]])
5 }
6
7 d_sd <- data.frame(n = , sd = )
```

# Estimating uncertainty directly

- Next we visualize our estimates of the standard errors of these sampling distributions at each sample size

```
1 sds <- vector(length = length(Ns))
2
3 for (i in seq_along(Ns)) {
4   sds[i] <- sd(means[[i]])
5 }
6
7 d_sd <- data.frame(n = , sd = sds)
```


# Estimating uncertainty directly

- Next we visualize our estimates of the standard errors of these sampling distributions at each sample size

```
1 sds <- vector(length = length(Ns))
2
3 for (i in seq_along(Ns)) {
4   sds[i] <- sd(means[[i]])
5 }
6
7 d_sd <- data.frame(n = Ns, sd = sds)
```

# Visualizing uncertainty estimates

```
1 ggplot(d_sd, aes(x = n, y = sd)) +  
2   geom_point(color = okabeito_colors(2)) +  
3   geom_line(color = okabeito_colors(2)) +  
4   theme_bw()
```



# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 # TODO: Construct the object to apply() over
4
5 # TODO: Construct the output
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function() {
4
5 }
6
7 # TODO: Construct the object to apply() over
8
9 # TODO: Construct the output
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function() {
4   return(m)
5 }
6
7 # TODO: Construct the object to apply() over
8
9 # TODO: Construct the output
```



# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   return(m)
6 }
7
8 # TODO: Construct the object to apply() over
9
10 # TODO: Construct the output
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 # TODO: Construct the output
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 n <- rep(Ns, each = M)
12
13 # TODO: Construct the output
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 n <- rep(Ns, each = M)
12
13 # TODO: Construct the output
14
15 d_mean_apply <- data.frame()
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 n <- rep(Ns, each = M)
12
13 # TODO: Construct the output
14
15 d_mean_apply <- data.frame(n = , mean = )
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 n <- rep(Ns, each = M)
12
13 # TODO: Construct the output
14
15 d_mean_apply <- data.frame(n = n, mean = )
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 n <- rep(Ns, each = M)
12
13 # TODO: Construct the output
14
15 d_mean_apply <- data.frame(n = n, mean = sapply())
```

# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 n <- rep(Ns, each = M)
12
13 # TODO: Construct the output
14
15 d_mean_apply <- data.frame(n = n, mean = sapply(X = , FUN = ))
```



# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 n <- rep(Ns, each = M)
12
13 # TODO: Construct the output
14
15 d_mean_apply <- data.frame(n = n, mean = sapply(X = , FUN = SimFun1))
```


# Uncertainty in mean estimates with `apply()`

- Now we redo the first simulation with something from the `apply()` family

```
1 # TODO: Write a simulation function
2
3 SimFun1 <- function(n_draws) {
4   draws <- rnorm(n_draws)
5   m <- mean(draws)
6   return(m)
7 }
8
9 # TODO: Construct the object to apply() over
10
11 n <- rep(Ns, each = M)
12
13 # TODO: Construct the output
14
15 d_mean_apply <- data.frame(n = n, mean = sapply(X = n, FUN = SimFun1))
```

# Visualizing uncertainty in mean estimates with `apply()`

```
1 ggplot(d_mean_apply, aes(x = n,  
2                           y = mean,  
3                           group = n)) +  
4   geom_boxplot(alpha = 0.5,  
5                 fill = okabeito_colors(3)) +  
6   theme_bw()
```



# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 # TODO: Construct the object to apply() over
4
5 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function() {
4
5 }
6
7 # TODO: Construct the object to apply() over
8
9 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function() {
4   return(sdev)
5 }
6
7 # TODO: Construct the object to apply() over
8
9 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function() {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   return(sdev)
8 }
9
10 # TODO: Construct the object to apply() over
11
12 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   return(sdev)
8 }
9
10 # TODO: Construct the object to apply() over
11
12 # TODO: Construct the output
```



# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = , MARGIN = , FUN = )
8   return(sdev)
9 }
10
11 # TODO: Construct the object to apply() over
12
13 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = , MARGIN = , FUN = mean)
8   return(sdev)
9 }
10
11 # TODO: Construct the object to apply() over
12
13 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = , FUN = mean)
8   return(sdev)
9 }
10
11 # TODO: Construct the object to apply() over
12
13 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   return(sdev)
9 }
10
11 # TODO: Construct the object to apply() over
12
13 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   sdev <- sd(means)
9   return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   sdev <- sd(means)
9   return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 sim_control_2 <- data.frame()
15
16 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   sdev <- sd(means)
9   return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 sim_control_2 <- data.frame(n_draws = , n_reps = )
15
16 # TODO: Construct the output
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   sdev <- sd(means)
9   return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 sim_control_2 <- data.frame(n_draws = Ns, n_reps = M)
15
16 # TODO: Construct the output
```



# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   sdev <- sd(means)
9   return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 sim_control_2 <- data.frame(n_draws = Ns, n_reps = M)
15
16 # TODO: Construct the output
17
18 sim_control_2$sdev <- mapply(FUN = , ...)
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   sdev <- sd(means)
9   return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 sim_control_2 <- data.frame(n_draws = Ns, n_reps = M)
15
16 # TODO: Construct the output
17
18 sim_control_2$sdev <- mapply(FUN = SimFun2, ...)
```

# Estimating uncertainty directly with `apply()`


```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   sdev <- sd(means)
9   return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 sim_control_2 <- data.frame(n_draws = Ns, n_reps = M)
15
16 # TODO: Construct the output
17
18 sim_control_2$sdev <- mapply(FUN = SimFun2,
19                             sim_control_2$n_draws,
20                             ...)
```

# Estimating uncertainty directly with `apply()`

```
1 # TODO: Write a simulation function
2
3 SimFun2 <- function(n_draws, n_reps) {
4   draws <- matrix(rnorm(n = n_draws * n_reps),
5                   nrow = n_draws,
6                   ncol = n_reps)
7   means <- apply(X = draws, MARGIN = 2, FUN = mean)
8   sdev <- sd(means)
9   return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 sim_control_2 <- data.frame(n_draws = Ns, n_reps = M)
15
16 # TODO: Construct the output
17
18 sim_control_2$sdev <- mapply(FUN = SimFun2,
19                             sim_control_2$n_draws,
20                             sim_control_2$n_reps)
```

# Visualizing uncertainty estimates with `apply()`

```
1  ggplot(sim_control_2, aes(x = n_draws,  
2                             y = sd)) +  
3    geom_point(color = okabeito_colors(2)) +  
4    geom_line(color = okabeito_colors(2)) +  
5    theme_bw()
```



# Extending to more distributions

```
1 # TODO: Write a simulation function
2
3 # TODO: Construct the object to apply() over
4
5 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun2 <- function(n_draws, n_reps) {
4    draws <- matrix(rnorm(n = n_draws * n_reps),
5                    nrow = n_draws,
6                    ncol = n_reps)
7    means <- apply(X = draws, MARGIN = 2, FUN = mean)
8    sdev <- sd(means)
9    return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps) {
4    draws <- matrix(rnorm(n = n_draws * n_reps),
5                     nrow = n_draws,
6                     ncol = n_reps)
7    means <- apply(X = draws, MARGIN = 2, FUN = mean)
8    sdev <- sd(means)
9    return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 # TODO: Construct the output
```



# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- matrix(rnorm(n = n_draws * n_reps),
5                     nrow = n_draws,
6                     ncol = n_reps)
7    means <- apply(X = draws, MARGIN = 2, FUN = mean)
8    sdev <- sd(means)
9    return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    # TODO: draw from distribution
5    # TODO: reshape into matrix
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    # TODO: draw from distribution
5    draws <- do.call()
6    # TODO: reshape into matrix
7    means <- apply(X = draws, MARGIN = 2, FUN = mean)
8    sdev <- sd(means)
9    return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    # TODO: draw from distribution
5    draws <- do.call(what = , args = )
6    # TODO: reshape into matrix
7    means <- apply(X = draws, MARGIN = 2, FUN = mean)
8    sdev <- sd(means)
9    return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    # TODO: draw from distribution
5    draws <- do.call(what = dist, args = )
6    # TODO: reshape into matrix
7    means <- apply(X = draws, MARGIN = 2, FUN = mean)
8    sdev <- sd(means)
9    return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    # TODO: draw from distribution
5    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
6    # TODO: reshape into matrix
7    means <- apply(X = draws, MARGIN = 2, FUN = mean)
8    sdev <- sd(means)
9    return(sdev)
10 }
11
12 # TODO: Construct the object to apply() over
13
14 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    # TODO: draw from distribution
5    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
6    # TODO: reshape into matrix
7    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
8    means <- apply(X = draws, MARGIN = 2, FUN = mean)
9    sdev <- sd(means)
10   return(sdev)
11 }
12
13 # TODO: Construct the object to apply() over
14
15 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 # TODO: Construct the output
```



# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 sim_control_3 <- data.frame()
14
15 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame()
15
16 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame(n_draws = ,
15                             n_reps = ,
16                             distribution = )
17
18 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame(n_draws = rep(Ns, times = length(distributions)),
15                             n_reps = ,
16                             distribution = )
17
18 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame(n_draws = rep(Ns, times = length(distributions)),
15                             n_reps = M,
16                             distribution = )
17
18 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame(n_draws = rep(Ns, times = length(distributions)),
15                             n_reps = M,
16                             distribution = rep(distributions, each = length(Ns)))
17
18 # TODO: Construct the output
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame(n_draws = rep(Ns, times = length(distributions)),
15                             n_reps = M,
16                             distribution = rep(distributions, each = length(Ns)))
17
18 # TODO: Construct the output
19
20 sim_control_3$sdev <- mapply(FUN = , ...)
```

# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame(n_draws = rep(Ns, times = length(distributions)),
15                             n_reps = M,
16                             distribution = rep(distributions, each = length(Ns)))
17
18 # TODO: Construct the output
19
20 sim_control_3$sdev <- mapply(FUN = SimFun3,
21                             ...)
```



# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame(n_draws = rep(Ns, times = length(distributions)),
15                             n_reps = M,
16                             distribution = rep(distributions, each = length(Ns)))
17
18 # TODO: Construct the output
19
20 sim_control_3$sdev <- mapply(FUN = SimFun3,
21                             sim_control_3$n_draws,
22                             ...)
```


# Extending to more distributions

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the object to apply() over
12
13 distributions <- c('rnorm', 'runif', 'rexp')
14 sim_control_3 <- data.frame(n_draws = rep(Ns, times = length(distributions)),
15                             n_reps = M,
16                             distribution = rep(distributions, each = length(Ns)))
17
18 # TODO: Construct the output
19
20 sim_control_3$sdev <- mapply(FUN = SimFun3,
21                             sim_control_3$n_draws,
22                             sim_control_3$n_reps,
23                             ...)
```



# Visualizing uncertainty across distributions

```
1  ggplot(sim_control_3,  
2      aes(x = n_draws,  
3          y = sd,  
4          color = distribution)) +  
5  geom_point() +  
6  geom_line() +  
7  scale_color_okabeito() +  
8  theme_bw()
```



# Constructing more complex data frame output

```
1 # TODO: Write a simulation function
2
3 # TODO: Construct the output
```

# Constructing more complex data frame output

```
1  # TODO: Write a simulation function
2
3  SimFun3 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    sdev <- sd(means)
8    return(sdev)
9  }
10
11 # TODO: Construct the output
```

# Constructing more complex data frame output

```
1  # TODO: Write a simulation function
2
3  SimFun4 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    out <- data.frame()
8    return(out)
9  }
10
11 # TODO: Construct the output
```

# Constructing more complex data frame output

```
1  # TODO: Write a simulation function
2
3  SimFun4 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    out <- data.frame(n = , dist = , mean = )
8    return(out)
9  }
10
11 # TODO: Construct the output
```



# Constructing more complex data frame output

```
1  # TODO: Write a simulation function
2
3  SimFun4 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    out <- data.frame(n = n_draws, dist = , mean = )
8    return(out)
9  }
10
11 # TODO: Construct the output
```

# Constructing more complex data frame output

```
1  # TODO: Write a simulation function
2
3  SimFun4 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    means <- apply(X = draws, MARGIN = 2, FUN = mean)
7    out <- data.frame(n = n_draws, dist = dist, mean = )
8    return(out)
9  }
10
11 # TODO: Construct the output
```

# Constructing more complex data frame output

```
1 # TODO: Write a simulation function
2
3 SimFun4 <- function(n_draws, n_reps, dist) {
4   draws <- do.call(what = dist, args = list(n = n_draws * n_reps))
5   draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6   means <- apply(X = draws, MARGIN = 2, FUN = mean)
7   out <- data.frame(n = n_draws, dist = dist, mean = means)
8   return(out)
9 }
10
11 # TODO: Construct the output
```

# Constructing more complex data frame output

```
1 # TODO: Write a simulation function
2
3 SimFun4 <- function(n_draws, n_reps, dist) {
4   draws <- do.call(dist, args = list(n = n_draws * n_reps))
5   draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6   out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7   return(out)
8 }
9
10 # TODO: Construct the output
```

# Constructing more complex data frame output

```
1 # TODO: Write a simulation function
2
3 SimFun4 <- function(n_draws, n_reps, dist) {
4   draws <- do.call(dist, args = list(n = n_draws * n_reps))
5   draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6   out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7   return(out)
8 }
9
10 # TODO: Construct the output
11
12 out <- maply(FUN = , ...)
```

# Constructing more complex data frame output

```
1  # TODO: Write a simulation function
2
3  SimFun4 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7    return(out)
8  }
9
10 # TODO: Construct the output
11
12 out <- mapply(
13   FUN = SimFun4,
14   ...
15 )
```

# Constructing more complex data frame output

```
1  # TODO: Write a simulation function
2
3  SimFun4 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7    return(out)
8  }
9
10 # TODO: Construct the output
11
12 out <- mapply(
13   FUN = SimFun4,
14   sim_control_3$n_draws,
15   ...
16 )
```

# Constructing more complex data frame output

```
1 # TODO: Write a simulation function
2
3 SimFun4 <- function(n_draws, n_reps, dist) {
4   draws <- do.call(dist, args = list(n = n_draws * n_reps))
5   draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6   out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7   return(out)
8 }
9
10 # TODO: Construct the output
11
12 out <- mapply(
13   FUN = SimFun4,
14   sim_control_3$n_draws,
15   sim_control_3$n_reps,
16   ...
17 )
```



# Constructing more complex data frame output

```
1 # TODO: Write a simulation function
2
3 SimFun4 <- function(n_draws, n_reps, dist) {
4   draws <- do.call(dist, args = list(n = n_draws * n_reps))
5   draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6   out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7   return(out)
8 }
9
10 # TODO: Construct the output
11
12 out <- mapply(
13   FUN = SimFun4,
14   sim_control_3$n_draws,
15   sim_control_3$n_reps,
16   sim_control_3$distribution
17 )
```

# Constructing more complex data frame output


```
1  # TODO: Write a simulation function
2
3  SimFun4 <- function(n_draws, n_reps, dist) {
4    draws <- do.call(dist, args = list(n = n_draws * n_reps))
5    draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6    out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7    return(out)
8  }
9
10 # TODO: Construct the output
11
12 out <- mapply(
13   FUN = SimFun4,
14   sim_control_3$n_draws,
15   sim_control_3$n_reps,
16   sim_control_3$distribution,
17   SIMPLIFY = FALSE
18 )
```

# Constructing more complex data frame output

```
1 # TODO: Write a simulation function
2
3 SimFun4 <- function(n_draws, n_reps, dist) {
4   draws <- do.call(dist, args = list(n = n_draws * n_reps))
5   draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6   out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7   return(out)
8 }
9
10 # TODO: Construct the output
11
12 out <- mapply(
13   FUN = SimFun4,
14   sim_control_3$n_draws,
15   sim_control_3$n_reps,
16   sim_control_3$distribution,
17   SIMPLIFY = FALSE
18 )
19
20 d_sim_4 <- do.call('rbind', out)
```

# Constructing more complex data frame output

```
1 # TODO: Write a simulation function
2
3 SimFun4 <- function(n_draws, n_reps, dist) {
4   draws <- do.call(dist, args = list(n = n_draws * n_reps))
5   draws <- matrix(draws, nrow = n_draws, ncol = n_reps)
6   out <- data.frame(n = n_draws, dist = dist, mean = apply(X = draws, MARGIN = 2, FUN = mean))
7   return(out)
8 }
9
10 # TODO: Construct the output
11
12 out <- mapply(FUN = SimFun4,
13               sim_control_3$n_draws,
14               sim_control_3$n_reps,
15               sim_control_3$distribution,
16               SIMPLIFY = FALSE)
17
18 d_sim_4 <- do.call('rbind', out)
19
20 ggplot(d_sim_4, aes(x = n, y = mean, group = n, fill = dist)) +
21   geom_boxplot(alpha = 0.5) +
22   facet_grid(. ~ dist) +
23   scale_fill_okabeito() +
24   theme_bw()
```



Wrap Up

# Recap

- Debugging is challenging, but we have four (five?) main tools:
  - Googling error messages
  - `print()` statements
  - `traceback()`
  - `browser()`
  - Maybe ChatGPT if you like it?
- The `apply()` family of functions allows you to hide loops
  - Not more efficient, but *safer* than loops
  - Encourages functionalization of code
  - Makes code easier to read

# Final Thoughts

- [PollEv.com/klintkanopka](https://pollev.com/klintkanopka)