



# H610S BMC 3.84.07 Release Notes

## HCI

Michael Wallis, amitha  
October 05, 2020

This PDF was generated from [https://docs.netapp.com/us-en/hci/docs/rn\\_H610S\\_BMC\\_3.84.07.html](https://docs.netapp.com/us-en/hci/docs/rn_H610S_BMC_3.84.07.html) on October 28, 2020. Always check docs.netapp.com for the latest.

# Table of Contents

H610S BMC 3.84.07 Release Notes .....	1
What's New .....	1
New Features .....	1
Resolved issues .....	1
Known issues .....	2
Upgrading BMC firmware on H610S nodes .....	2

# H610S BMC 3.84.07 Release Notes

The downloadable BMC update contains BMC feature enhancements and bug fixes for NetApp H610S nodes.

## What's New

H610S BMC 3.84.07 contains various bug fixes and new features. This release brings to the field critical updated BMC firmware ahead of subsequent Element software and storage firmware bundle releases, which will also include this updated BMC firmware for H610S nodes.

This firmware package is supported on Element versions 11.8, 12.0, and 12.2. You can upgrade the H610S BMC firmware directly out-of-band, and upgrade instructions can be found in [Upgrading BMC firmware on H610S nodes](#).

## New Features

The following are the new features and changes included in this release:

- Enabled INITRD support
- Updated SSL help message about X.509 certificates
- Disabled TLS 1.0 and 1.1 support
- Added Redfish remote media support
- Added the H5Viewer RKVM feature
- Added Remote syslog support

## Resolved issues

The following are issues that have been resolved in this release:

Issue	Description
N/A	The debug user sysadmin can log in using SSH after resetting the BMC.
N/A	When you use the console to ping the BMC IP address, the BMC does not respond.
N/A	During an AC power cycle stress test, the access permissions of the SOLSSH config file are lost.
CSESF-116	During an AC power cycle stress test, "PROCHOT" CPU thermal warnings appear in the BMC logs.

Issue	Description
CSESF-121	The create and update service account API takes longer than expected.
CSD-3321 / CSESF-129	The H610S BMC can hang and become inaccessible with the error "BMC Self Test Failed".
CSESF-197	The BMC web UI inventory API returns the wrong memory serial number format.

## Known issues

There are no known issues in this release.

## Upgrading BMC firmware on H610S nodes

Perform the following steps to upgrade the BMC firmware version on your H610S nodes. The procedure can take approximately 30 minutes to complete.

### *What you'll need*

- You have checked for alerts by clicking **Reporting** > **Alerts** in the NetApp Element software web UI to ensure that there are no errors.
- You have downloaded the BMC update package.
- You have ensured that the BMC and the computer you are using to perform the update are located on the same network.
- You have contacted NetApp Support for assistance with the BMC upgrade.

### *Steps*

1. Log in to the BMC console using your web browser: [https://<BMC\\_IP>/#login](https://<BMC_IP>/#login), where <BMC\_IP> is the IP address of the BMC.
2. Click **Maintenance**.
3. Click **Preserve Configuration**.
4. Do the following:
  - a. Disable the **Check All** checkbox.
  - b. Enable the **IPMI** checkbox.
  - c. Enable the **Network** checkbox.
  - d. Enable the **Authentication** checkbox.
    - The **IPMI** setting is used to preserve existing user accounts.
    - The **Network** setting is used to preserve the DHCP assigned BMC IP address.

- The **Authentication** setting is used to preserve custom accounts configured for BMC login.

5. Click **Save**.
6. Click **Firmware Update**.
7. Disable the **Preserve all Configuration** checkbox.



Ensure that you have disabled the **Preserve all Configuration** checkbox.

8. On the computer you are using to perform the update, extract the contents of the BMC update package.
9. In the BMC web UI, under the **Select Firmware Image** section of the **Firmware Update** page, click **Choose File**.
10. Browse to the `rom.ima_enc` file within the extracted package contents and select it.
11. Click **Start firmware update** and click **OK** when the prompt appears asking if you want to continue.
12. Click **OK** when a prompt appears indicating that a firmware reset is happening.
13. After several minutes, use a new browser tab to log in to the BMC web UI.
14. On the BMC dashboard, go to **Device Information** > **More info**.
15. Confirm that the **Firmware Revision** is **3.84.07**.
16. Perform this procedure for the remaining H610S storage nodes in your cluster.

## Find more Information

- [NetApp HCI Documentation Center](#)
- [NetApp HCI Resources Page](#)

## Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.