
Some basic graph definitions¹

David Barber

University College London

These slides accompany the book Bayesian Reasoning and Machine Learning. The book and demos can be downloaded from www.cs.ucl.ac.uk/staff/D.Barber/brml. Feedback and corrections are also available on the site. Feel free to adapt these slides for your own purposes, but please include a link the above website.

Graphs



Definition


A graph consists of nodes (vertices) and undirected or directed links (edges) between nodes.

Path

A path from X_i to X_j is a sequence of connected nodes starting at X_i and ending at X_j .

Directed Graphs

All the edges are directed:



DAG

Directed Acyclic Graph: Graph in which by following the direction of the arrows a node will never be visited more than once.

Parents and Children:


 X_i is a parent of X_j if there is a link from X_i to X_j . X_i is a child of X_j if there is a link from X_i to X_i .

Ancestors and Descendants:

The ancestors of a node X_i are the nodes with a directed path ending at X_i . The descendants of X_i are the nodes with a directed path beginning at X_i .

Undirected Graph

All the edges are undirected:



Clique

A clique is a fully connected subset of nodes. (X_1,X_2,X_4) forms a (non-maximal) clique.


Maximal Clique

Clique which is not a subset of a larger clique. (X_1,X_2,X_3,X_4) and (X_2,X_3,X_5) are both maximal cliques.

Connectivity


Connected graph

There is a path between every pair of vertices:



Connected components

In a non-connected graph, the connected components are the connected-subgraphs:




 (X_1, X_2, X_4) and (X_3, X_5) are the two connected components.



Connectedness

Singly-connected

There is only one path from any node \boldsymbol{a} to another other node \boldsymbol{b}



Multiply-connected

A graph is multiply-connected if it is not singly-connected:

