## https://github.com/klyuev1/php-tasks/blob/main/24/index.php

```
mindex.php ×
                     <?php
                          $host = 'localhost';
go
                          $password =
                          $db_name = 'test';
$ \
                         $link = mysqli connect($host, $user, $password, $db name);
                          $sel1_query = "SELECT * FROM workers WHERE id = 3";
$sel2_query = "SELECT * FROM workers WHERE salary > 400";
                          $or_and_1_query = "SELECT * FROM workers WHERE age = 27 or salary = 1000";
$or_and_2_query = "SELECT * FROM workers WHERE age = 27 or salary != 400";
                         $insert = "INSERT INTO workers (name, age, salary) VALUES ('KMPMAA', 26, 300)";
$insert_query = mysqli_query($link, $insert) or die(mysqli_error($link));
$insert_query_test = "SELECT * FROM workers WHERE name = 'KMPMAA' and age = 26";
                          $delete = "DELETE FROM `workers` WHERE id = 7";
                          $delete query = mysqli query($link, $delete) or die(mysqli error($link));
                          Supdate2 = "UPDATE workers SET age=35 WHERE id=4";
Supdate3 = "UPDATE workers SET salary=700 WHERE salary=500";
Supdate4 = "UPDATE workers SET age=23 WHERE id > 2 and id <= 5";
Supdate5 = "UPDATE workers SET name = 'KeHA', salary = 900 WHERE name = 'BacA'";
                          $arr = [$sel1_query, $sel2_query, $or_and_1_query, $or_and_2_query, $insert_query_test, $update1, $update2, $update3, $update4, $update5];
                                each($arr as $query){
    $result = mysqli_query($link, $query) or die(mysqli_error($link));
    for ($data = []; $row = mysqli_fetch_assoc($result); $data[] = $row);
× ⊗0∆0 ₩0
```



