

# Class Notes 5

- Python
- JavaScript
- Java



## Question 1

Given an  $m \times n$  matrix, return true if the matrix is Toeplitz. Otherwise, return false. A matrix is Toeplitz if every diagonal from top-left to bottom-right has the same elements.

1	2	3	4
5	1	2	3
9	5	1	2

Example 1:

Input: matrix = [[1,2,3,4],[5,1,2,3],[9,5,1,2]]

Output: true

Explanation:

In the above grid, the diagonals are:

"[9]", "[5, 5]", "[1, 1, 1]", "[2, 2, 2]", "[3, 3]", "[4]".

In each diagonal all elements are the same, so the answer is True.

Solution:

### Intuition and Algorithm

For each diagonal with elements in order  $a_1, a_2, a_3, \dots, a_k$ , we can check  $a_1 = a_2, a_2 = a_3, \dots, a_{k-1} = a_k$ . The matrix is *Toeplitz* if and only if all of these conditions are true for all (top-left to bottom-right) diagonals.

Every element belongs to some diagonal, and it's previous element (if it exists) is it's top-left neighbor. Thus, for the square  $(r, c)$ , we only need to check

$r == 0$  OR  $c == 0$  OR  $matrix[r-1][c-1] == matrix[r][c]$ .

Time Complexity:  $O(M \cdot N)$ , as defined in the problem statement.

Space Complexity:  $O(1)$ .

```
class Solution {
    public boolean isToeplitzMatrix(int[][] matrix) {
        for (int r = 0; r < matrix.length; ++r)
            for (int c = 0; c < matrix[0].length; ++c)
                if (r > 0 && c > 0 && matrix[r-1][c-1] != matrix[r][c])
                    return false;
        return true;
    }
}
```




## Question 2

Given a 2D integer array matrix, return *the transpose* of matrix.

The *transpose* of a matrix is the matrix flipped over its main diagonal, switching the matrix's row and column indices.

2	4	-1
-10	5	11
18	-7	6



2	-10	18
4	5	-7
-1	11	6

Example 1:

Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]


Output:

[[1,4,7],[2,5,8],[3,6,9]]

Solution:

Intuition

Observe how the cells move in groups when we rotate the image.



We can iterate over each group of four cells and rotate them.

Complexity Analysis

Let  $M$  be the number of cells in the matrix.

Time complexity:  $O(M)$ , as each cell is getting read once and written once.

Space complexity:  $O(1)$  because we do not use any other additional data structures.

```
class Solution {
    public int[][] transpose(int[][] A) {
        int R = A.length, C = A[0].length;
        int[][] ans = new int[C][R];
        for (int r = 0; r < R; ++r)
            for (int c = 0; c < C; ++c) {
                ans[c][r] = A[r][c];
            }
        return ans;
    }
}
```




## Question 3

You are given an  $n \times n$  2D matrix representing an image, rotate the image by 90 degrees (clockwise).

You have to rotate the image in-place, which means you have to modify the input 2D matrix directly. DO NOT allocate another 2D matrix and do the rotation.

Example 1:

1	2	3
4	5	6
7	8	9



7	4	1
8	5	2
9	6	3

Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]

Output: [[7,4,1],[8,5,2],[9,6,3]]

Solution:

Intuition and Algorithm

The transpose of a matrix  $A$  with dimensions  $R \times C$  is a matrix *ans* with dimensions  $C \times R$  for which  $ans[c][r] = A[r][c]$ .

We initialize a new matrix *ans* representing the answer. Then, we'll copy each entry of the matrix as appropriate.

Complexity Analysis

Time Complexity:  $O(R \cdot C)$ , where  $R$  and  $C$  are the number of rows and columns in the given matrix  $A$ .

Space Complexity:  $O(R \cdot C)$ , the space used by the answer.

```
class Solution {
    public void rotate(int[][] matrix) {
        int n = matrix.length;
        for (int i = 0; i < (n + 1) / 2; i++) {
            for (int j = 0; j < n / 2; j++) {
                int temp = matrix[n - 1 - j][i];
                matrix[n - 1 - j][i] = matrix[n - 1 - i][n - j - 1];
                matrix[n - 1 - i][n - j - 1] = matrix[j][n - 1 - i];
                matrix[j][n - 1 - i] = matrix[i][j];
                matrix[i][j] = temp;
            }
        }
    }
}
```



## Question 4

Given a non-empty array of non-negative integers nums, the *degree* of this array is defined as the maximum frequency of any one of its elements.

Your task is to find the smallest possible length of a (contiguous) subarray of nums, that has the same degree as nums.

Example 1:

Input: nums = [1,2,2,3,1]

Output: 2

Explanation:

The input array has a degree of 2 because both elements 1 and 2 appear twice.

Of the subarrays that have the same degree:

[1, 2, 2, 3, 1], [1, 2, 2, 3], [2, 2, 3, 1], [1, 2, 2], [2, 2, 3], [2, 2]

The shortest length is 2. So return 2.

Complexity Analysis

- Time Complexity:  $O(m \cdot n)$
- Space Complexity:  $O(1)$

Solution:

```
class Solution {
    public int maximumWealth(int[][] accounts) {
        // Initialize the maximum wealth seen so far to 0 (the minimum wealth)
        int maxWealthSoFar = 0;

        // Iterate over accounts
        for (int[] account : accounts) {
            // For each account, initialize the sum to 0
            int currCustomerWealth = 0;
            // Add the money in each bank
            for (int money : account) {
                currCustomerWealth += money;
            }
            // Update the maximum wealth seen so far if the current wealth is g
            // If it is less than the current sum
            maxWealthSoFar = Math.max(maxWealthSoFar, currCustomerWealth);
        }

        // Return the maximum wealth
        return maxWealthSoFar;
    }
}
```