Online Examination Report

Date:	28.07.2014
Attempts:	1
Examinee:	Atwoki Kaija, Albert
Date of birth:	
Subject:	070-Operational procedures
Result:	0 %
Time used:	00:00:20 (HH:MM:SS)

Attachments

1. List of result by question
2. List of result by topic
3. Detailed question result report

Attachment 1: List of result by question

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
1	1	71.	OPERATIONAL PROCEDURES	0,00	1,00
2	179	71.	OPERATIONAL PROCEDURES	0,00	1,00
3	190	71.	OPERATIONAL PROCEDURES	0,00	1,00
4	56	71.1.1	ICAO Annex 6	0,00	1,00
5	149	71.1.1.3	General	0,00	1,00
6	61	71.1.2.1	Civil Aviation Regulations	0,00	1,00
7	76	71.1.2.6	Civil Aviation Regulations	0,00	1,00
8	24	71.1.2.6	Civil Aviation Regulations	0,00	1,00
9	29	71.1.3.3	MNPS Airspace	0,00	1,00
10	10	71.1.3.3	MNPS Airspace	0,00	1,00
11	82	71.1.3.3	MNPS Airspace	0,00	1,00
12	92	71.2.1	Operations Manual	0,00	1,00
13	109	71.2.1.1	Operating procedures	0,00	1,00
14	107	71.2.1.1	Operating procedures	0,00	1,00
15	160	71.2.1.1	Operating procedures	0,00	1,00
16	171	71.2.1.1	Operating procedures	0,00	1,00
17	34	71.2.1.1	Operating procedures	0,00	1,00
18	136	71.2.1.1	Operating procedures	0,00	1,00
19	84	71.2.1.1	Operating procedures	0,00	1,00
20	138	71.2.1.1	Operating procedures	0,00	1,00
21	148	71.2.2	Icing conditions	0,00	1,00
22	114	71.2.2.1	On ground de-/anti-icing	0,00	1,00
23	124	71.2.2.1	On ground de-/anti-icing	0,00	1,00
24	144	71.2.4.2	Influence of the flight procedure	0,00	1,00
25	119	71.2.5	Fire/smoke	0,00	1,00
26	102	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
27	37	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
28	117	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
29	131	71.2.5.6	Types of extinguishers	0,00	1,00
30	87	71.2.5.6	Types of extinguishers	0,00	1,00
31	141	71.2.5.6	Types of extinguishers	0,00	1,00
32	62	71.2.7	Wind shear and microburst	0,00	1,00
33	11	71.2.7	Wind shear and microburst	0,00	1,00
34	51	71.2.8	Wake turbulence	0,00	1,00
35	12	71.2.8.1	Cause	0,00	1,00
36	15	71.2.8.1	Cause	0,00	1,00
37	33	71.2.11.2	Requirements	0,00	1,00
38	164	71.2.12	Transport of dangerous goods	0,00	1,00
39	9	71.2.12	Transport of dangerous goods	0,00	1,00
40	154	71.2.13	Contaminated runways	0,00	1,00
			Total:0%	**0,00**	**40,00**

Attachment 2: List of result by topic

Licence

Date: 28.07.2014

Examinee: Atwoki Kaija, Albert

Location: Uganda Civil Aviation Authority

Your Result: 0,00 from 40,00 Points (0,00 %)

Topics	Ammount of Questions	Points achieved	Maximum Points	Percent
71. OPERATIONAL PROCEDURES	40	0,00	40,00	0,00
71.1. GENERAL REQUIREMENTS	8	0,00	8,00	0,00
71.2. SPECIAL OPERATIONAL PROCEDURES	29	0,00	29,00	0,00
Total	**40**	**0,00**	**40,00**	**0,00**

1

According to civil aviation regulations and assuming the following circumstances:

- for a Category A aeroplane
- an aerodrome equipped with runway edge lighting and centre line lighting and multiple RVR information
- an acceptable alternate aerodrome is available, the minimum RVR / Visibility required for take-off is:

- ☐ **150 m.**
- ☐ **250 m.**
- ☐ **300 m.**
- ☐ **200 m.**

ID:	1(LTS:226049, LTM:1)	Max. Points	1,00
Syllabus reference:	71. OPERATIONAL PROCEDURES	Points	0,00

2

What aural and visual indications should be observed over an ILS middle marker?

- ☐ **Continuous dashes at the rate of two per second.**
- ☐ **Continuous dots at the rate of six per second.**
- ☐ **Alternate dots and dashes at the rate of two per second.**

ID:	179(LTS:226028, LTM:211)	Max. Points	1,00
Syllabus reference:	71. OPERATIONAL PROCEDURES	Points	0,00

3

What effect would a light crosswind of approximately 7 knots have on vortex behavior?

- ☐ **The upwind vortex would tend to remain over the runway.**
- ☐ **The downwind vortex would tend to remain over the runway.**
- ☐ **The light crosswind would rapidly dissipate vortex strength.**

ID:	190(LTS:226039, LTM:222)	Max. Points	1,00
Syllabus reference:	71. OPERATIONAL PROCEDURES	Points	0,00

4

Among the EAC states, the CAA-OPS of Aircraft is based on :

- ☐ **The air transport rules**
- ☐ **The Civil Aviation Requirements (CAA)**
- ☐ **ICAO Annex 6**
- ☐ **A CAA guideline**

ID: 56(LTS:226166, LTM:60)
Syllabus reference: 71.1.1 ICAO Annex 6

Max. Points 1,00
Points 0,00

5

Which one of the following sets of conditions is most likely to attract birds to an aerodrome ?

- ☐ **mowing and maintaining the grass long**
- ☐ **a refuse tip in close proximity**
- ☐ **the extraction of minerals such as sand and gravel**
- ☐ **a modern sewage tip in close proximity**

ID: 149(LTS:226163, LTM:178)
Syllabus reference: 71.1.1.3 General

Max. Points 1,00
Points 0,00

6

AOC regulations applies to:

- ☐ **aeroplanes proceeding from EAC states or flying over them.**
- ☐ **the operation by an EAC state member of any civil aeroplane.**
- ☐ **the operation by an EAC state member of any civil commercial transport aeroplane.**
- ☐ **aeroplanes used by police, customs and defence departments.**

ID:	61(LTS:226202, LTM:65)	Max. Points	1,00
Syllabus reference:	71.1.2.1 Civil Aviation Regulations	Points	0,00

7

According to civil aviation regulations, an aeroplane whose maximum approved passenger seating configuration is 10 seats must be equipped with:

- ☐ **three hand fire-extinguishers in the passenger compartment.**
- ☐ **one hand fire-extinguisher on the flight deck and two hand fire-extinguishers in the passenger compartment.**
- ☐ **one hand fire-extinguisher on the flight deck and one hand fire-extinguisher in the passenger compartment.**
- ☐ **two hand fire-extinguishers on the flight deck and two hand fire-extinguishers in the passenger compartment.**

ID:	76(LTS:226153, LTM:80)	Max. Points	1,00
Syllabus reference:	71.1.2.6 Civil Aviation Regulations	Points	0,00

8

In accordance with civil aviation regulations, for aeroplanes intended to be operated at pressure altitude of 39000 ft, the total number of oxygen dispensing units and outlets shall exceed:

- ☐ **the number of passengers by at least 10%.**
- ☐ **the number of seats by at least 10%.**
- ☐ **the number of passengers.**
- ☐ **the number of seats.**

ID:	24(LTS:226156, LTM:25)	Max. Points	1,00
Syllabus reference:	71.1.2.6 Civil Aviation Regulations	Points	0,00

9

In airspace where MNPS is applicable, the minimum vertical separation between FL 290 and FL 410 is:

- ☐ **500 ft**
- ☐ **1 500 ft**
- ☐ **2000ft**
- ☐ **1 000 ft**

ID:	29(LTS:226065, LTM:31)	Max. Points	1,00
Syllabus reference:	71.1.3.3 MNPS Airspace	Points	0,00

10

Aircraft may operate in MNPS airspace along a number of special routes, if the aircraft is equipped with at least:

- ☐ two Inertial Navigation Systems (INS).
- ☐ three Inertial Navigation System (INS).
- ☐ one Long Range Navigation System (LNRS).
- ☐ two independent Long Range Navigation Systems (LRNS).

ID:	10(LTS:226063, LTM:10)	Max. Points	1,00
Syllabus reference:	71.1.3.3 MNPS Airspace	Points	0,00

11

An aircraft operating within MNPS Airspace is unable to continue flight in accordance with its air traffic control clearance, but is able to maintain its assigned level, and due to a total loss of communications capability, cannot obtain a revised clearance from ATC. The aircraft should offset from the assigned route by 15 NM and climb or descent 500 ft, if:

- ☐ **above FL410**
- ☐ **at FL410**
- ☐ **below FL410**
- ☐ **at FL430**

ID:	82(LTS:226073, LTM:87)	Max. Points	1,00
Syllabus reference:	71.1.3.3 MNPS Airspace	Points	0,00

12

The minimum equipment list of a public transport airplane is to be found in the :

- ☐ **operation manual.**
- ☐ **flight manual.**
- ☐ **flight record.**
- ☐ **JAR OPS.**

ID:	92(LTS:226132, LTM:102)	Max. Points	1,00
Syllabus reference:	71.2.1 Operations Manual	Points	0,00

13

After a landing, with overweight and overspeed conditions, the tyres and brakes are extremely hot. The fireguards should approach the landing gear tyres:

- ☐ **only from front or rear side.**
- ☐ **only from left or right side.**
- ☐ **under no circumstances.**
- ☐ **from any side.**

ID:	109(LTS:226096, LTM:129)	Max. Points	1,00
Syllabus reference:	71.2.1.1 Operating procedures	Points	0,00

14

For aircraft certified , cockpit voice recorder must keep the conversations and sound alarms recorded during the last :

- ☐ **flight.**
- ☐ **25 hours of operation.**
- ☐ **30 minutes of operation.**
- ☐ **48 hours of operation.**

ID:	107(LTS:226098, LTM:127)	Max. Points	1,00
Syllabus reference:	71.2.1.1 Operating procedures	Points	0,00

15

During an explosive decompression at flight level 370 (FL 370), your first action will be :

- ☐ **to set the transponder to 7700**
- ☐ **to warn the ATC**
- ☐ **to put on the oxygen mask**
- ☐ **to comfort your passengers**

ID:	160(LTS:226126, LTM:191)	Max. Points	1,00
Syllabus reference:	71.2.1.1 Operating procedures	Points	0,00

16

Life preservers required for overwater operations are stored

- ☐ **within easy reach of each passenger.**
- ☐ **within easy reach of each seated occupant.**
- ☐ **under each occupant seat.**

ID: 171(LTS:226122, LTM:202)
Syllabus reference: 71.2.1.1 Operating procedures

Max. Points 1,00
Points 0,00

17

Flight crew members on the flight deck shall keep their safety belt fastened:

- ☐ **only during take off and landing.**
- ☐ **while at their station.**
- ☐ **from take off to landing.**
- ☐ **only during take off and landing and whenever necessary by the commander in the interest of safety.**

ID: 34(LTS:226093, LTM:36)
Syllabus reference: 71.2.1.1 Operating procedures

Max. Points 1,00
Points 0,00

18

Following an explosive decompression, the maximum altitude without oxygen at which flying efficiency is not impaired is :

- ☐ **2500 ft**
- ☐ **25000 ft**
- ☐ **8000 ft**
- ☐ **14000 ft**

ID:	136(LTS:226105, LTM:164)	Max. Points	1,00
Syllabus reference:	71.2.1.1 Operating procedures	Points	0,00

19

The Minimum Equipment List (MEL) shall be established by:

- ☐ **the manufacturer and approved by the Authority.**
- ☐ **the Civil Aviation Authority of all the European States.**
- ☐ **the operator and approved by the Authority.**
- ☐ **the respective Authority of the operator.**

ID:	84(LTS:226102, LTM:89)	Max. Points	1,00
Syllabus reference:	71.2.1.1 Operating procedures	Points	0,00

20

On overwater flights, an operator shall not operate an aeroplane at a distance away from land, which is suitable for making an emergency landing greater than that corresponding to :

- ☐ **300 NM or 90 minutes at cruising speed.**
- ☐ **100 NM or 30 minutes at cruising speed.**
- ☐ **400 NM or 120 minutes at cruising speed.**
- ☐ **200 NM or 45 minutes at cruising speed.**

ID:	138(LTS:226107, LTM:166)	Max. Points	1,00
Syllabus reference:	71.2.1.1 Operating procedures	Points	0,00

21

The greatest possibility of ice buildup, while flying under icing conditions, occurs on :

- ☐ **The upper and lower wingsurfaces.**
- ☐ **Only the pitot and static probes.**
- ☐ **The upper and lower rudder surfaces.**
- ☐ **The aircraft front areas.**

ID:	148(LTS:226060, LTM:177)	Max. Points	1,00
Syllabus reference:	71.2.2 Icing conditions	Points	0,00

22

The anti-icing fluid protecting film can wear off and reduce considerably the protection time:

- ☐ **when the temperature of the airplane skin is close to 0 °C.**
- ☐ **when the outside temperature is close to 0 °C.**
- ☐ **during strong winds or as a result of the other aircraft engines jet wash.**
- ☐ **when the airplane is into the wind.**

ID:	114(LTS:226208, LTM:134)	Max. Points	1,00
Syllabus reference:	71.2.2.1 On ground de-/anti-icing	Points	0,00

23

If after anti-icing has been completed a pre-departure inspection reveals evidence of freezing, the correct action is to :

- ☐ **complete departure as soon as possible to reduce the possibility of further freezing**
- ☐ **complete departure provided that the recommended anti-icing holdover (protection) time for the prevailing conditons and type of fluid used has not been exceeded**
- ☐ **switch on all the aeroplane anti-icing and de-icing systems and leave on until clear of icing conditions when airborne**
- ☐ **carry out a further de-icing process**

ID:	124(LTS:226210, LTM:150)	Max. Points	1,00
Syllabus reference:	71.2.2.1 On ground de-/anti-icing	Points	0,00

24

As regards the detection of bird strike hazard, the pilot's means of information and prevention are:
1 - ATIS.
2 - NOTAMs.
3- BIRDTAMs.
4 - Weather radar.,

- ☐ **1,2,3,4,5**
- ☐ **2,5**
- ☐ **1,3,4**
- ☐ **1,2,5**

ID:	144(LTS:226190, LTM:172)	Max. Points	1,00
Syllabus reference:	71.2.4.2 Influence of the flight procedure	Points	0,00

25

The "NO SMOKING" sign must be illuminated :

- ☐ when oxygen is being supplied in the cabin.
- ☐ in each cabin section if oxygen is being carried.
- ☐ during take off and landing.
- ☐ during climb and descent.

ID:	119(LTS:226084, LTM:140)	Max. Points	1,00
Syllabus reference:	71.2.5 Fire/smoke	Points	0,00

26

If smoke appears in the air conditioning, the first action to take is to :

- ☐ **Begin an emergency descent.**
- ☐ **Determine which system is causing the smoke.**
- ☐ **Put on the mask and goggles.**
- ☐ **Cut off all air conditioning units.**

ID: 102(LTS:226186, LTM:118)
Syllabus reference: 71.2.5.3 Fire in the cabin, cockpit, cargo comp

Max. Points 1,00
Points 0,00

27

Beneath fire extinguishers the following equipment for fire fighting is on board:

- ☐ **crash axes or crowbars.**
- ☐ **a hydraulic winch and a big box of tools.**
- ☐ **a big bunch of fire extinguishing blankets.**
- ☐ **water and all type of beverage.**

ID:	37(LTS:226182, LTM:39)	Max. Points	1,00
Syllabus reference:	71.2.5.3 Fire in the cabin, cockpit, cargo comp	Points	0,00

28

To extinguish a fire in the cockpit, you use:
1. a water fire-extinguisher
2. a powder or chemical fire-extinguisher
3. a halon fire-extinguisher
4. a CO2 fire-extinguisher

- ☐ **1, 2, 3, 4**
- ☐ **2, 3, 4**
- ☐ **1, 2**
- ☐ **3, 4**

29

You will use a halon extinguisher for a fire of:
1 - solids (fabric, plastic, ...)
2 - liquids (alcohol, gasoline, ...)
3 - gas
4 - metals (aluminium, magnesium, ...)
The combination regrouping all the correct statements

- ☐ **1,2,3,4**
- ☐ **1,2,4**
- ☐ **1,2,3**
- ☐ **2,3,4**

ID:	131(LTS:226079, LTM:159)	Max. Points	1,00
Syllabus reference:	71.2.5.6 Types of extinguishers	Points	0,00

30

CO_2 type extinguishers are fit to fight:
1 - class A fires
2 - class B fires
3 - electrical source fires
4 - special fires: metals, gas, chemical product
Which of the following combinations contains all the correct statements:

- ☐ **1 - 3 - 4**
- ☐ **1 - 2 - 4**
- ☐ **2 - 3 - 4**
- ☐ **1 - 2 - 3**

ID:	87(LTS:226077, LTM:95)	Max. Points	1,00
Syllabus reference:	71.2.5.6 Types of extinguishers	Points	0,00

31

A fire occurs in a wheel and immediate action is required to extinguish it. The safest extinguishant to use is :

- ☐ **water**
- ☐ **foam**
- ☐ **CO_2 (carbon dioxide)**
- ☐ **dry powder**

ID: 141(LTS:226080, LTM:169)
Syllabus reference: 71.2.5.6 Types of extinguishers

Max. Points 1,00
Points 0,00

32

In final approach, you encounter a strong rear wind gust or strong down wind which forces you to go around. You
1- maintain the same aircraft configuration (gear and flaps)
2- reduce the drags (gear and flaps)
3- gradually increase the attitude up to triggering of stick shaker
4- avoid excessive attitude change The combination of correct statements is :

- ☐ **1,4**
- ☐ **2,4**
- ☐ **1,3**
- ☐ **2,3**

ID:	62(LTS:226089, LTM:66)	Max. Points	1,00
Syllabus reference:	71.2.7 Wind shear and microburst	Points	0,00

33

One of the main characteristics of windshear is that it :

- ☐ **can occur at any altitude in both the vertical and horizontal planes**
- ☐ **can occur at any altitude and only in the horizontal plane**
- ☐ **occurs only at a low altitude (2000 ft) and never in the horizontal plane**
- ☐ **occurs only at a low altitude (2000 ft) and never in the vertical plane**

ID:	11(LTS:226088, LTM:11)	Max. Points	1,00
Syllabus reference:	71.2.7 Wind shear and microburst	Points	0,00

34

According with DOC 4444 (ICAO), a wake turbulence radar separation minima of 9,3 Km (5,0 NM) shall be applied when a :

- ☐ **LIGHT aircraft is crossing behind a MEDIUM aircraft, at the same altitude or less than 300 m (1 000.ft)**
- ☐ **MEDIUM aircraft is crossing behind a MEDIUM aircraft, at the same altitude or less than 300 n (1 000 ft)**
- ☐ **HEAVY aircraft is crossing behind a HEAVY aircraft, at the same altitude or less than 300 m (1 000 ft)**
- ☐ **LIGHT aircraft is crossing behind a HEAVY aircraft, at the same altitude or less than 300 m (1 000 ft)**

ID:	51(LTS:226148, LTM:53)	Max. Points	1,00
Syllabus reference:	71.2.8 Wake turbulence	Points	0,00

35

The wake turbulence caused by an aircraft is mainly the result of:

1. An aerodynamic effect (wing tip vortices).
2. The engines action (propellers rotation or engine gas exhausts).
3. The importance of the drag devices (size of the landing gear, of the flaps, etc.).

The combination regrouping all the correct statements is:

- ☐ **1.**
- ☐ **2 and 3.**
- ☐ **1, 2 and 3.**
- ☐ **3.**

ID:	12(LTS:226144, LTM:12)	Max. Points	1,00
Syllabus reference:	71.2.8.1 Cause	Points	0,00

36

Aeroplane wake turbulence during take off starts when:

- ☐ **the take off roll commences.**
- ☐ **out of ground effect.**
- ☐ **slats and flaps are extended only.**
- ☐ **the nose wheel lifts off the runway.**

ID:	15(LTS:226145, LTM:15)	Max. Points	1,00
Syllabus reference:	71.2.8.1 Cause	Points	0,00

37

According to Civil aviation authority, if a fuel jettisoning system is required, it must be capable of jettisoning enough fuel within:

- ☐ **30 minutes**
- ☐ **60 minutes**
- ☐ **45 minutes**
- ☐ **15 minutes**

ID:	33(LTS:226180, LTM:35)	Max. Points	1,00
Syllabus reference:	71.2.11.2 Requirements	Points	0,00

38

In compliance with the civil aviation regulations in order to carry dangerous goods on board a public transport airplane, they must be accompanied with a :

- ☐ **specialized handling employee.**
- ☐ **transport document for dangerous goods.**
- ☐ **representative of the company owning the materials.**
- ☐ **system to warn the crew in case of a leak or of an abnormal**

ID:	164(LTS:226142, LTM:195)	Max. Points	1,00
Syllabus reference:	71.2.12 Transport of dangerous goods	Points	0,00

39

The authorization for the transport of hazardous materials is specified on the:

- ☐ **insurance certificate.**
- ☐ **registration certificate.**
- ☐ **airworthiness certificate.**
- ☐ **air carrier certificate.**

ID:	9(LTS:226139, LTM:9)	Max. Points	1,00
Syllabus reference:	71.2.12 Transport of dangerous goods	Points	0,00

40

Acording to the civil aviation regulations a runway is considered damp when:

- ☐ **it is covered with a film of water of less than 3 mm.**
- ☐ **its surface is not dry, and when surface moisture does not give it a shiny appearance.**
- ☐ **it is covered with a film of water of less than 1 mm.**
- ☐ **surface moisture gives it a shiny appearance.**

ID:	154(LTS:226055, LTM:183)	Max. Points	1,00
Syllabus reference:	71.2.13 Contaminated runways	Points	0,00