
Online Examination Report

Date:	23.07.2014
Attempts:	1
Examinee:	Ojule, Benjamin
Date of birth:	
Subject:	070-Operational procedures
Result:	42,5 %
Time used:	00:01:00 (HH:MM:SS)

Attachments

1. List of result by question
2. List of result by topic
3. Detailed question result report

Attachment 1: List of result by question

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
1	176		71. OPERATIONAL PROCEDURES	0,00	1,00
2	180		71. OPERATIONAL PROCEDURES	0,00	1,00
3	190		71. OPERATIONAL PROCEDURES	0,00	1,00
4	184		71. OPERATIONAL PROCEDURES	0,00	1,00
5	186		71. OPERATIONAL PROCEDURES	0,00	1,00
6	174		71. OPERATIONAL PROCEDURES	1,00	1,00
7	118	71.1.1.3	General	0,00	1,00
8	24	71.1.2.6	Civil Aviation Regulations	1,00	1,00
9	77	71.1.3	Long-range flights	0,00	1,00
10	40	71.1.3.3	MNPS Airspace	0,00	1,00
11	52	71.1.3.3	MNPS Airspace	1,00	1,00
12	53	71.1.3.3	MNPS Airspace	0,00	1,00
13	172	71.2	SPECIAL OPERATIONAL PROCEDURES	0,00	1,00
14	42	71.2.1	Operations Manual	1,00	1,00
15	92	71.2.1	Operations Manual	1,00	1,00
16	107	71.2.1.1	Operating procedures	1,00	1,00
17	28	71.2.1.1	Operating procedures	0,00	1,00
18	138	71.2.1.1	Operating procedures	0,00	1,00
19	150	71.2.1.1	Operating procedures	1,00	1,00
20	34	71.2.1.1	Operating procedures	0,00	1,00
21	163	71.2.2.1	On ground de-/anti-icing	0,00	1,00
22	114	71.2.2.1	On ground de-/anti-icing	1,00	1,00
23	117	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
24	47	71.2.5.3	Fire in the cabin, cockpit, cargo comp	1,00	1,00
25	89	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
26	131	71.2.5.6	Types of extinguishers	0,00	1,00
27	98	71.2.5.6	Types of extinguishers	0,00	1,00
28	11	71.2.7	Wind shear and microburst	1,00	1,00

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
29	166	71.2.8	Wake turbulence	0,00	1,00
30	162	71.2.8	Wake turbulence	0,00	1,00
31	51	71.2.8	Wake turbulence	1,00	1,00
32	12	71.2.8.1	Cause	1,00	1,00
33	38	71.2.8.2	List of relevant parameters	0,00	1,00
34	55	71.2.9.2	Use of SSR	0,00	1,00
35	159	71.2.9.4	Bomb on board	1,00	1,00
36	165	71.2.12	Transport of dangerous goods	1,00	1,00
37	9	71.2.12	Transport of dangerous goods	1,00	1,00
38	54	71.2.12.1	ICAO Annex 18	0,00	1,00
39	105	71.2.13	Contaminated runways	1,00	1,00
40	65	71.2.13.4	Procedures	1,00	1,00
Total:42%				17,00	40,00

Attachment 2: List of result by topic

Licence

Date: 23.07.2014

Examinee: Ojule, Benjamin

Location: Uganda Civil Aviation Authority

Your Result: 17,00 from 40,00 Points (42,50 %)

Topics	Ammount of Questions	Points achieved	Maximum Points	Percent
71. OPERATIONAL PROCEDURES	40	17,00	40,00	42,50
71.1. GENERAL REQUIREMENTS	6	2,00	6,00	33,33
71.2. SPECIAL OPERATIONAL PROCEDURES	28	14,00	28,00	50,00
Total	40	17,00	40,00	42,50

1

What minimum aircraft equipment is required for operation within Class C airspace?

☐ Two-way communications.

☒ Transponder and DME.

☐ Two-way communications and transponder.

2

What aural and visual indications should be observed over an ILS outer marker?

- ☐ Alternate dots and dashes at the rate of two per second.
- ☐ Continuous dashes at the rate of two per second.
- ☒ Continuous dots at the rate of six per second.

3

What effect would a light crosswind of approximately 7 knots have on vortex behavior?

- ☐ The downwind vortex would tend to remain over the runway.
- ☐ The upwind vortex would tend to remain over the runway.
- ☒ The light crosswind would rapidly dissipate vortex strength.

4

When diverting to an alternate airport because of an emergency, pilots should

- ☒ **rely upon radio as the primary method of navigation.**
- ☐ **apply rule-of-thumb computations, estimates, and other appropriate shortcuts to divert to the new course as soon as possible.**
- ☐ **complete all plotting, measuring, and computations involved before diverting.**

5

Which is a necessary condition for the occurrence of a low-level temperature inversion wind shear?

- ☐ The temperature differential between the cold and warm layers must be at least 10 degrees C.
- ☒ A wind direction difference of at least 30 degrees C between the wind near the surface and the wind just above the inversion.
- ☐ A calm or light wind near the surface and a relatively strong wind just above the inversion.

6

Which incident would require that the nearest Flight Control Center field office be notified immediately?

- ☒ In-flight fire.
- ☐ Fire of the primary aircraft while in a hangar which results in damage to other property of more than \$25,000.
- ☐ Ground fire resulting in fire equipment dispatch.

7

90 % of bird strikes occur :

- ☒ **above 1 000 m**
- ☐ **between 500 and 1 000 m**
- ☐ **under 500 m**
- ☐ **between 500 and 1 500 m**

8

In accordance with civil aviation regulations, for aeroplanes intended to be operated at pressure altitude of 39000 ft, the total number of oxygen dispensing units and outlets shall exceed:

- ☐ the number of passengers.
- ☐ the number of seats.
- ☒ the number of seats by at least 10%.
- ☐ the number of passengers by at least 10%.

9

A jet-powered aircraft, flying above the optimum altitude will have :

- ☐ increased manoeuvring limits
- ☒ reduced range
- ☐ increased Mach number stability
- ☒ increased flight envelope

10

Air traffic services may require an aircraft to report position when flying east-west, south of 70°N between 5°W and 65°W, every:

☐ 20° of longitude.

☒ 5° of longitude.

☐ 10° of longitude.

☐ 15° of longitude.

11

In the event of communication failure in an Minimum Navigation Performance Specification(MNPS) airspace, the pilot must:

- ☐ change the flight level in accordance with predetermined instructions.
- ☒ continue the flight in compliance with the last oceanic clearance received and acknowledged.
- ☐ join one of the so-called "special" routes.
- ☐ return to the flight plan route if it is different from the last oceanic clearance received and acknowledged.

12

In Minimum Navigation Performance Specification (MNPS) airspace, the speed reference for turbo-jet aircraft is the:

- ☒ **ground speed.**
- ☐ **indicated airspeed.**
- ☐ **Mach number.**
- ☐ **true airspeed.**

13

An airplane operated by a supplemental air carrier flying over uninhabited terrain must carry which emergency equipment?

- ☒ **Survival kit for each passenger.**
- ☐ **Colored smoke flares and a signal mirror.**
- ☐ **Suitable pyrotechnic signaling devices.**

14

During a flight, the chief steward informs the crew that a passenger is using a portable device suspected to disturb the aircraft electronic systems. The captain:

- ☒ must not authorize any person to use such a device on board.
- ☐ authorizes its use during the whole flight phase.
- ☐ may authorize the use of this device, as an exception.
- ☐ authorizes its use except during take-off and landing phases.

15

The minimum equipment list of a public transport airplane is to be found in the :

☐ flight record.

☐ JAR OPS.

☐ flight manual.

☒ operation manual.

16

For aircraft certified , cockpit voice recorder must keep the conversations and sound alarms recorded during the last :

- ☐ 25 hours of operation.
- ☐ 48 hours of operation.
- ☐ flight.
- ☒ 30 minutes of operation.

17

An aircraft is flying in heavy rain. To carry out a safe approach, it is necessary to :

- ☐ carry out an approach with flaps up, in order to avoid exposing too much lifting surface to the rain
- ☒ reduce the approach speed, because the runway may be very slippery on landing
- ☐ maintain the normal approach speed up to landing
- ☐ increase its approach speed, because the rain affects the lift by deteriorating the boundary layer

18

On overwater flights, an operator shall not operate an aeroplane at a distance away from land, which is suitable for making an emergency landing greater than that corresponding to :

- ☐ 400 NM or 120 minutes at cruising speed.
- ☐ 200 NM or 45 minutes at cruising speed.
- ☐ 100 NM or 30 minutes at cruising speed.
- ☒ 300 NM or 90 minutes at cruising speed.

19

Supplemental oxygen is used to :

- ☒ provide people on board with oxygen during a cabin depressurisation
- ☐ protect a crew who fights a fire
- ☐ assist a passenger with breathing disorders
- ☐ provide with oxygen passengers who might require it, following a cabin depressurisation

20

Flight crew members on the flight deck shall keep their safety belt fastened:

- ☐ while at their station.
- ☒ only during take off and landing and whenever necessary by the commander in the interest of safety.
- ☐ only during take off and landing.
- ☐ from take off to landing.

21

An aircraft having undergone an anti-icing procedure must be anti-icing fluid free at the latest when :

- ☐ releasing the brakes in order to take-off.
- ☒ leaving the icing zone.
- ☐ it is rotating (before taking-off).
- ☐ it is implementing its own anti-icing devices.

22

The anti-icing fluid protecting film can wear off and reduce considerably the protection time:

- ☐ when the outside temperature is close to 0 °C.
- ☐ when the airplane is into the wind.
- ☐ when the temperature of the airplane skin is close to 0 °C.
- ☒ during strong winds or as a result of the other aircraft engines jet wash.

23

To extinguish a fire in the cockpit, you use:

- 1. a water fire-extinguisher*
- 2. a powder or chemical fire-extinguisher*
- 3. a halon fire-extinguisher*
- 4. a CO2 fire-extinguisher*

☒ 1, 2, 3, 4

☐ 2, 3, 4

☐ 3, 4

☐ 1, 2

24

According to AOC of EAC regulations, at least one of the following hand fire extinguishers must be conveniently located on the flight deck:

- ☐ a water fire-extinguisher.
- ☐ a foam fire-extinguisher.
- ☐ a powder fire-extinguisher.
- ☒ a halon fire-extinguisher or equivalent.

25

In case of a fire due to the heating of the brakes, you fight the fire using:

- 1. a dry powder fire extinguisher*
 - 2. a water spray atomizer*
 - 3. a water fire-extinguisher*
 - 4. a CO2 fire-extinguisher to the maximum*
- The combination regrouping all the correct statements is:*

☐ 3, 4

☐ 1, 2

☒ 2, 3, 4

☐ 1, 4

26

You will use a halon extinguisher for a fire of:

1 - solids (fabric, plastic, ...)

2 - liquids (alcohol, gasoline, ...)

3 - gas

4 - metals (aluminium, magnesium, ...)

The combination regrouping all the correct statements

☐ 1,2,3

☐ 1,2,3,4

☐ 1,2,4

☒ 2,3,4

27

A CO2 fire extinguisher can be used for:

- 1. a paper fire*
- 2. a hydrocarbon fire*
- 3. a fabric fire*
- 4. an electrical fire*
- 5. a wood fire*

The combination regrouping all the correct statements

☐ 2, 3, 4

☐ 1, 2, 3, 4, 5

☐ 2, 4, 5

☒ 1, 3, 5

28

One of the main characteristics of windshear is that it :

- ☐ can occur at any altitude and only in the horizontal plane
- ☐ occurs only at a low altitude (2000 ft) and never in the vertical plane
- ☒ can occur at any altitude in both the vertical and horizontal planes
- ☐ occurs only at a low altitude (2000 ft) and never in the horizontal plane

29

When taking-off after a widebody aircraft which has just landed, you should take-off :

- ☐ at the point where the aircraft's wheels have touched down and on the wind side of the runway .
- ☐ beyond the point where the aircraft's wheels have touched down.
- ☒ in front of the point where the aircraft's wheels have touched down.
- ☐ at the point where the aircraft's wheels have touched the ground and on the underwind side of the runway .

30

The greatest wake turbulence occurs when the generating aircraft is :

- ☐ Small, light, at maximum speed in full flaps configuration
- ☐ Small, light, at low speed in clean configuration
- ☒ Large, heavy, at maximum speed in full flaps configuration
- ☐ Large, heavy, at low speed in clean configuration

31

According with DOC 4444 (ICAO), a wake turbulence radar separation minima of 9,3 Km (5,0 NM) shall be applied when a :

- ☐ MEDIUM aircraft is crossing behind a MEDIUM aircraft, at the same altitude or less than 300 n (1 000 ft)
- ☐ LIGHT aircraft is crossing behind a HEAVY aircraft, at the same altitude or less than 300 m (1 000 ft)
- ☒ LIGHT aircraft is crossing behind a MEDIUM aircraft, at the same altitude or less than 300 m (1 000.ft)
- ☐ HEAVY aircraft is crossing behind a HEAVY aircraft, at the same altitude or less than 300 m (1 000 ft)

32

The wake turbulence caused by an aircraft is mainly the result of:

1. An aerodynamic effect (wing tip vortices).
2. The engines action (propellers rotation or engine gas exhausts).
3. The importance of the drag devices (size of the landing gear, of the flaps, etc.).

The combination regrouping all the correct statements is:

☐ 1, 2 and 3.

☒ 1.

☐ 2 and 3.

☐ 3.

33

The greatest wake turbulence occurs when the generating aircraft is:

- ☒ **Large, heavy, at maximum speed in full flaps configuration**
- ☐ **Small, light, at maximum speed in full flaps configuration**
- ☐ **Small, light, at low speed in clean configuration**
- ☐ **Large, heavy, at low speed in clean configuration**

34

What is the transponder code to be used by the commander of an aircraft that is subject to unlawful interference?

☐ A 7500

☒ A 7700

☐ A 7800

☐ A 7600

35

In case of a serious threat based on the presence of a bomb on board a pressurized aircraft and disregarding any fuel considerations:

- ☐ you carry out an emergency descent to reach the safety altitude.
- ☐ you climb to the maximum flight level which does not need the use of pressurization.
- ☒ you descend to the flight level corresponding to the indicated cabin altitude or the safety altitude if higher and take preventive steps by putting yourself in a landing approach configuration.
- ☐ you go down to the level corresponding to the indicated cabin altitude and keep the airplane in a clean configuration until the final approach.

36

Who makes sure that the air transportation of an item of dangerous goods is not prohibited?

- ☐ It is not specified.
- ☐ The captain, always using the list of prohibited aircraft items.
- ☒ The shipper when completing the shipper's declaration for dangerous goods.
- ☐ The operator.

37

The authorization for the transport of hazardous materials is specified on the:

☐ airworthiness certificate.

☐ insurance certificate.

☐ registration certificate.

☒ air carrier certificate.

38

The content of the dangerous goods transport document is specified in the:

- ☒ Air Transport Permit.
- ☐ OPS documentation.
- ☐ Technical Instructions.
- ☐ Flight Manual.

39

A runway covered with 4 mm thick water, is said to be:

☐ flooded.

☐ contaminated.

☒ damp.

☐ wet.

40

For an airplane with a tyre pressure of 14 bars, there is a risk of dynamic hydroplaning as soon as the :

1- water height is equal to the depth of the tyre grooves.

2- speed is greater than 123 kt.

3- water height is equal to the half of the depth of the tyre grooves.

4- speed is greater than 95 kt. The combination regrouping all the correct statements is:

☐ 1 and 4.

☐ 2 and 3.

☐ 3 and 4.

☒ 1 and 2.

