
Online Examination Report

Date:	03.09.2014
Attempts:	1
Examinee:	Jackson, Bwayo
Date of birth:	1/20/1989
Subject:	070-Operational procedures
Result:	60 %
Time used:	00:30:00 (HH:MM:SS)

Attachments

1. List of result by question
2. List of result by topic
3. Detailed question result report

Attachment 1: List of result by question

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
1	184	71. OPERATIONAL PROCEDURES		1,00	1,00
2	186	71. OPERATIONAL PROCEDURES		1,00	1,00
3	185	71. OPERATIONAL PROCEDURES		0,00	1,00
4	190	71. OPERATIONAL PROCEDURES		0,00	1,00
5	191	71. OPERATIONAL PROCEDURES		1,00	1,00
6	56	71.1.1 ICAO Annex 6		1,00	1,00
7	59	71.1.1.1 Definitions		0,00	1,00
8	19	71.1.1.3 General		0,00	1,00
9	118	71.1.1.3 General		1,00	1,00
10	39	71.1.2 Civil Aviation Regulations		1,00	1,00
11	31	71.1.2.3 Civil Aviation Regulations		1,00	1,00
12	76	71.1.2.6 Civil Aviation Regulations		1,00	1,00
13	170	71.2 SPECIAL OPERATIONAL PROCEDURES		1,00	1,00
14	21	71.2.1 Operations Manual		1,00	1,00
15	150	71.2.1.1 Operating procedures		1,00	1,00
16	123	71.2.1.1 Operating procedures		0,00	1,00
17	20	71.2.1.1 Operating procedures		1,00	1,00
18	145	71.2.1.1 Operating procedures		1,00	1,00
19	112	71.2.1.1 Operating procedures		1,00	1,00
20	121	71.2.1.1 Operating procedures		0,00	1,00
21	28	71.2.1.1 Operating procedures		0,00	1,00
22	139	71.2.1.1 Operating procedures		0,00	1,00
23	84	71.2.1.1 Operating procedures		1,00	1,00
24	85	71.2.1.1 Operating procedures		0,00	1,00
25	135	71.2.1.1 Operating procedures		1,00	1,00
26	140	71.2.2.1 On ground de-/anti-icing		1,00	1,00
27	115	71.2.2.1 On ground de-/anti-icing		0,00	1,00
28	144	71.2.4.2 Influence of the flight procedure		0,00	1,00

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
29	50	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
30	87	71.2.5.6	Types of extinguishers	1,00	1,00
31	6	71.2.7	Wind shear and microburst	1,00	1,00
32	11	71.2.7	Wind shear and microburst	1,00	1,00
33	62	71.2.7	Wind shear and microburst	0,00	1,00
34	162	71.2.8	Wake turbulence	0,00	1,00
35	166	71.2.8	Wake turbulence	0,00	1,00
36	17	71.2.9.1	ICAO Annex 17	0,00	1,00
37	55	71.2.9.2	Use of SSR	1,00	1,00
38	58	71.2.9.4	Bomb on board	1,00	1,00
39	111	71.2.12	Transport of dangerous goods	1,00	1,00
40	97	71.2.12.1	ICAO Annex 18	1,00	1,00
Total:60%				24,00	40,00

Attachment 2: List of result by topic

Licence

Date: 03.09.2014

Examinee: Jackson, Bwayo

Location: Uganda Civil Aviation Authority

Your Result: 24,00 from 40,00 Points (60,00 %)

Topics	Ammount of Questions	Points achieved	Maximum Points	Percent
71. OPERATIONAL PROCEDURES	40	24,00	40,00	60,00
71.1. GENERAL REQUIREMENTS	7	5,00	7,00	71,43
71.2. SPECIAL OPERATIONAL PROCEDURES	28	16,00	28,00	57,14
Total	40	24,00	40,00	60,00

1

When diverting to an alternate airport because of an emergency, pilots should

- ☐ complete all plotting, measuring, and computations involved before diverting.
- ☐ rely upon radio as the primary method of navigation.
- ☒ apply rule-of-thumb computations, estimates, and other appropriate shortcuts to divert to the new course as soon as possible.

2

Which is a necessary condition for the occurrence of a low-level temperature inversion wind shear?

- ☐ The temperature differential between the cold and warm layers must be at least 10 degrees C.
- ☐ A wind direction difference of at least 30 degrees C between the wind near the surface and the wind just above the inversion.
- ☒ A calm or light wind near the surface and a relatively strong wind just above the inversion.

3

How does the wake turbulence vortex circulate around each wingtip?

- ☐ Inward, upward, and counterclockwise.
- ☐ Outward, upward, and around each tip.
- ☒ Inward, upward, and around each tip.

4

What effect would a light crosswind of approximately 7 knots have on vortex behavior?

- ☐ The upwind vortex would tend to remain over the runway.
- ☐ The downwind vortex would tend to remain over the runway.
- ☒ The light crosswind would rapidly dissipate vortex strength.

5

When landing behind a large jet aircraft, at which point on the runway should you plan to land?

- ☐ If any crosswind, land on the windward side of the runway and prior to the jet's touchdown point.
- ☒ Beyond the jet's touchdown point.
- ☐ At least 1,000 feet beyond the jet's touchdown point.

6

Among the EAC states, the CAA-OPS of Aircraft is based on :

- ☐ The air transport rules
- ☐ The Civil Aviation Requirements (CAA)
- ☒ ICAO Annex 6
- ☐ A CAA guideline

7

According to Annex 6, 'RNP type' is defined as a containment value expressed as a distance in ... (i) ... from the intended position within which flights would be for at least ... (ii) ... of the total flying time.

☐ (i) nautical miles
(ii) 90%

☐ (i) kilometers
(ii) 90%

☐ (i) kilometers
(ii) 95%

☒ (i) nautical miles
(ii) 95%

Candidate: Bwayo Jackson
Date of birth: 1989-01-20

Subject: 070-Operational procedures
Date: 2014-09-03



8

During a night flight, an observer located in the cockpit, seeing an aircraft coming from front right on approximate opposite parallel track, will first see the:

☒ red light

☐ red and white flashing light

☐ green light

☐ white light

9

90 % of bird strikes occur :

☐ between 500 and 1 000 m

☒ under 500 m

☐ above 1 000 m

☐ between 500 and 1 500 m

Candidate: Bwayo Jackson
Date of birth: 1989-01-20

Subject: 070-Operational procedures
Date: 2014-09-03

10

An operator must ensure that, for the duration of each flight, be kept on the ground a copy of the :

- ☒ operation flight plan.
- ☐ flight plan processing.
- ☐ ATC (Air Traffic Control) flight plan.
- ☐ flight route sheet.

11

According to Annex 6, what is the definition of an Air Operator Certificate?

- ☒ A certificate authorising an operator to carry out specified commercial air transport operations.
- ☐ A certificate the crew will present to immigration officers, stating that all passengers on board fulfil the visa requirements needed.
- ☐ A certificate automatically authorising an operator to carry out domestic air services in any ICAO contracting State.
- ☐ A certificate needed to carry out specified commercial international air transport operations, but not for domestic commercial flights.

12

According to civil aviation regulations, an aeroplane whose maximum approved passenger seating configuration is 10 seats must be equipped with:

- ☐ three hand fire-extinguishers in the passenger compartment.
- ☐ one hand fire-extinguisher on the flight deck and two hand fire-extinguishers in the passenger compartment.
- ☒ one hand fire-extinguisher on the flight deck and one hand fire-extinguisher in the passenger compartment.
- ☐ two hand fire-extinguishers on the flight deck and two hand fire-extinguishers in the passenger compartment.

13

When a supplemental air carrier is operating over an uninhabited area, how many appropriately equipped survival kits are required aboard the aircraft?

- ☐ One for each passenger seat.
- ☒ One for each occupant of the aircraft.
- ☐ One for each passenger, plus 10 percent.

14

You are the captain of a commercial airplane and you notice, after take-off, a flock of birds which may present a bird strike hazard, you must:

- ☒ immediately inform the appropriate ground station.
- ☐ inform the appropriate ground station within a reasonable period of time.
- ☐ draft a bird strike hazard report upon arrival and within at most 48 hours.
- ☐ inform the other aircraft by radio.

15

Supplemental oxygen is used to :

- ☐ protect a crew who fights a fire
- ☐ assist a passenger with breathing disorders
- ☒ provide people on board with oxygen during a cabin depressurisation
- ☐ provide with oxygen passengers who might require it, following a cabin depressurisation

16

The Civil Aviation Regulations establishes that, a co-pilot is not assigned to operate at the flight controls during take-off and landing unless :

- ☐ he has carried out at least three flights as pilot-in-command or as a co-pilot at the controls of the type to be used, in the preceding 90 days.
- ☒ he has carried out as pilot-in-command or as co-pilot at least three take-off and three landings in an aeroplane or an approved flight simulator of the type used, in the preceding 90 days.
- ☐ he has operated as pilot-in-command or as co-pilot at the controls during take-off and landing of the type to be used in the preceding 90 days.
- ☐ he has carried out as-pilot-in-command or as co-pilot at lest three take-off and three landings in an aeroplane or an approved flight simulator of the type used, in the preceding 30 days

17

According to civil aviation regulations in East Africa, the Minimum Equipment List of an aircraft is found in the:

☒ operations manual.

☐ flight manual.

☐ flight record.

☐ CAA OPS.

Candidate: Bwayo Jackson
Date of birth: 1989-01-20

Subject: 070-Operational procedures
Date: 2014-09-03

18

During a night flight, an observer located in the cockpit, seeing an aircraft coming from the front left, will first see the :

- ☒ green steady light
- ☐ white steady light
- ☐ red steady light
- ☐ green flashing light

Candidate: Bwayo Jackson
Date of birth: 1989-01-20

Subject: 070-Operational procedures
Date: 2014-09-03



19

A life jacket is mandatory for any passenger on board an aircraft flying away from the shore by more than :

☐ 200 NM

☐ 400 NM

☐ 100 NM

☒ 50 NM

20

A category III A is an approach which may be carried out with a runway visual range of at least :

☒ 250 m

☐ 100 m

☐ 200 m

☐ 50 m

21

An aircraft is flying in heavy rain. To carry out a safe approach, it is necessary to :

- ☒ carry out an approach with flaps up, in order to avoid exposing too much lifting surface to the rain
- ☐ reduce the approach speed, because the runway may be very slippery on landing
- ☐ increase its approach speed, because the rain affects the lift by deteriorating the boundary layer
- ☐ maintain the normal approach speed up to landing

Candidate: Bwayo Jackson
Date of birth: 1989-01-20

Subject: 070-Operational procedures
Date: 2014-09-03



22

A category B aircraft can carry out an indirect approach followed by a visual maneuver only if the horizontal visibility is higher than or equal to:

☐ 2400 m

☐ 3600 m

☒ 1500 m

☐ 1600 m

23

The Minimum Equipment List (MEL) shall be established by:

- ☐ the manufacturer and approved by the Authority.
- ☐ the Civil Aviation Authority of all the European States.
- ☒ the operator and approved by the Authority.
- ☐ the respective Authority of the operator.

24

The Master Minimum Equipment List (M MEL), if this exists, is established by:

- ☒ the manufacturer of the aircraft, but need not to be accepted by the authority
- ☐ the operator of the aircraft, and accepted by the authority
- ☐ the manufacturer of the aircraft, and accepted by the authority
- ☐ the operator of the aircraft, and accepted by the manufacturer

25

Selecting an alternate aerodrome the runway of this facility must be sufficiently long to allow a full stop landing from 50 ft above the threshold (jet type aircraft, dry runway) within:

☒ 60% of the landing distance available.

☐ 80% of the landing distance available.

☐ 50% of the landing distance available.

☐ 70% of the landing distance available.

26

An aircraft having undergone an anti-icing procedure and having exceeded the protection time of the anti-icing fluid:

- ☒ must undergo a de-icing procedure before a new application of anti-icing fluid for take-off.
- ☐ must only undergo a new anti-icing procedure for take-off.
- ☐ must only undergo a de-icing procedure for take-off.
- ☐ need not to undergo a new anti-icing procedure for take-off.

27

During an aircraft de-icing/anti-icing procedure:

- ☐ the anti-icing fluid is applied without heating and the de-icing fluid is applied hot.
- ☐ the anti-icing and de-icing fluids are applied cold.
- ☒ the de-icing fluid is applied without heating and the anti-icing fluid is applied hot.
- ☐ the anti-icing and de-icing fluids are applied hot.

28

As regards the detection of bird strike hazard, the pilot's means of information and prevention are:

1 - ATIS.

2 - NOTAMs.

3- BIRDTAMs.

4 - Weather radar.,

☐ 1,2,3,4,5

☐ 2,5

☒ 1,3,4

☐ 1,2,5

29

An aircraft having undertaken an anti-icing procedure and having exceeded the holdover time of the anti-icing fluid:

- ☐ must undertake a de-icing procedure before a new application of anti-icing fluid before take-off.
- ☐ does not require a new anti-icing procedure before take-off.
- ☐ must only undertake a de-icing procedure before take-off.
- ☒ must only undertake a new anti-icing procedure before take-off.

30

CO2 type extinguishers are fit to fight:

1 - class A fires

2 - class B fires

3 - electrical source fires

4 - special fires: metals, gas, chemical product

Which of the following combinations contains all the correct statements:

☐ 1 - 3 - 4

☐ 1 - 2 - 4

☐ 2 - 3 - 4

☒ 1 - 2 - 3

31

Which one of the following magnitudes will be the first to change its value when penetrating a windshear ?

- ☐ Vertical speed.
- ☒ Indicated airspeed.
- ☐ Pitch angle.
- ☐ Groundspeed.

32

One of the main characteristics of windshear is that it :

- ☒ can occur at any altitude in both the vertical and horizontal planes
- ☐ can occur at any altitude and only in the horizontal plane
- ☐ occurs only at a low altitude (2000 ft) and never in the horizontal plane
- ☐ occurs only at a low altitude (2000 ft) and never in the vertical plane

33

In final approach, you encounter a strong rear wind gust or strong down wind which forces you to go around. You

1- maintain the same aircraft configuration (gear and flaps)

2- reduce the drags (gear and flaps)

3- gradually increase the attitude up to triggering of stick shaker

4- avoid excessive attitude change The combination of correct statements is :

☒ 1,4

☐ 2,4

☐ 1,3

☐ 2,3

34

The greatest wake turbulence occurs when the generating aircraft is :

- ☐ Large, heavy, at low speed in clean configuration
- ☒ Large, heavy, at maximum speed in full flaps configuration
- ☐ Small, light, at maximum speed in full flaps configuration
- ☐ Small, light, at low speed in clean configuration

35

When taking-off after a widebody aircraft which has just landed, you should take-off :

- ☐ at the point where the aircraft's wheels have touched down and on the wind side of the runway .
- ☐ beyond the point where the aircraft's wheels have touched down.
- ☐ at the point where the aircraft's wheels have touched the ground and on the underwind side of the runway .
- ☒ in front of the point where the aircraft's wheels have touched down.

36

According to ICAO Annex 17, following an unlawful interference, who shall take adequate measures for the safety of passengers and crew of an aircraft, until their journey can be continued?

- ☐ The responsible Civil Aviation Authority
- ☐ The aircraft's operator.
- ☐ The contracting State where the aircraft is located.
- ☒ The commander of the aircraft.

Candidate: Bwayo Jackson
Date of birth: 1989-01-20

Subject: 070-Operational procedures
Date: 2014-09-03



37

What is the transponder code to be used by the commander of an aircraft that is subject to unlawful interference?

☐ A 7600

☐ A 7800

☒ A 7500

☐ A 7700

38

In case of a serious threat based on the presence of a bomb on board a pressurized aircraft and disregarding any fuel considerations:

- ☐ you climb to the maximum flight level which does not need the use of pressurization.
- ☐ you carry out an emergency descent to reach the safety altitude.
- ☒ you descend to the flight level corresponding to the indicated cabin altitude or the safety altitude if higher and take preventive steps by putting yourself in a landing approach configuration.
- ☐ you go down to the level corresponding to the indicated cabin altitude and keep the aircraft in a clean configuration until the final approach.

39

ICAO (International Civil Aviation Organization) Appendix 18 is a document dealing with

- ☐ the technical operational use of aircraft
- ☐ the air transport of live animals
- ☒ the safety of the air transport of dangerous goods
- ☐ the noise pollution of aircraft

40

In addition to the languages required by the State of Origin, what language should be set for the markings related to dangerous goods :

☐ Spanish

☐ English, French or Spanish

☐ French

☒ English