
Online Examination Report

Date:	20.08.2014
Attempts:	1
Examinee:	Okirol, Samuel
Date of birth:	
Subject:	070-Operational procedures
Result:	50 %
Time used:	00:01:00 (HH:MM:SS)

Attachments

1. List of result by questions
2. List of result by topic
3. Detailed question result report

Attachment 1: List of result by questions

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
1	199	71. OPERATIONAL PROCEDURES		0,00	1,00
2	187	71. OPERATIONAL PROCEDURES		1,00	1,00
3	183	71. OPERATIONAL PROCEDURES		0,00	1,00
4	189	71. OPERATIONAL PROCEDURES		0,00	1,00
5	186	71. OPERATIONAL PROCEDURES		0,00	1,00
6	59	71.1.1.1 Definitions		1,00	1,00
7	31	71.1.2.3 Civil Aviation Regulations		1,00	1,00
8	22	71.1.2.6 Civil Aviation Regulations		0,00	1,00
9	49	71.1.3.3 MNPS Airspace		0,00	1,00
10	52	71.1.3.3 MNPS Airspace		1,00	1,00
11	120	71.1.3.3 MNPS Airspace		0,00	1,00
12	42	71.2.1 Operations Manual		1,00	1,00
13	126	71.2.1 Operations Manual		1,00	1,00
14	153	71.2.1 Operations Manual		0,00	1,00
15	160	71.2.1.1 Operating procedures		1,00	1,00
16	139	71.2.1.1 Operating procedures		0,00	1,00
17	132	71.2.1.1 Operating procedures		1,00	1,00
18	147	71.2.1.1 Operating procedures		0,00	1,00
19	112	71.2.1.1 Operating procedures		1,00	1,00
20	123	71.2.1.1 Operating procedures		0,00	1,00
21	85	71.2.1.1 Operating procedures		0,00	1,00
22	110	71.2.1.1 Operating procedures		1,00	1,00
23	107	71.2.1.1 Operating procedures		0,00	1,00
24	104	71.2.1.1 Operating procedures		0,00	1,00
25	150	71.2.1.1 Operating procedures		1,00	1,00
26	128	71.2.1.1 Operating procedures		1,00	1,00
27	148	71.2.2 Icing conditions		1,00	1,00
28	3	71.2.2 Icing conditions		0,00	1,00

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
29	115	71.2.2.1	On ground de-/anti-icing	0,00	1,00
30	163	71.2.2.1	On ground de-/anti-icing	1,00	1,00
31	144	71.2.4.2	Influence of the flight procedure	1,00	1,00
32	36	71.2.5.3	Fire in the cabin, cockpit, cargo comp	1,00	1,00
33	166	71.2.8	Wake turbulence	0,00	1,00
34	162	71.2.8	Wake turbulence	1,00	1,00
35	83	71.2.9.1	ICAO Annex 17	0,00	1,00
36	58	71.2.9.4	Bomb on board	1,00	1,00
37	8	71.2.12	Transport of dangerous goods	1,00	1,00
38	54	71.2.12.1	ICAO Annex 18	1,00	1,00
39	154	71.2.13	Contaminated runways	0,00	1,00
40	142	71.2.13	Contaminated runways	0,00	1,00
Total:50%				20,00	40,00

Attachment 2: List of result by topic

Licence

Date: 20.08.2014

Examinee: Okirol, Samuel

Location: Uganda Civil Aviation Authority

Your Result: 20,00 from 40,00 Points (50,00 %)

Topics	Ammount of Questions	Points achieved	Maximum Points	Percent
71. OPERATIONAL PROCEDURES	40	20,00	40,00	50,00
71.1. GENERAL REQUIREMENTS	6	3,00	6,00	50,00
71.2. SPECIAL OPERATIONAL PROCEDURES	29	16,00	29,00	55,17
Total	40	20,00	40,00	50,00

1

While being vectored, if crossing the ILS final approach course becomes imminent and an approach clearance has not been issued, what action should be taken by the pilot?

- ☒ Turn inbound and execute the missed approach procedure at the outer marker if approach clearance has not been received.
- ☐ Maintain the last assigned heading and query ATC.
- ☐ Turn outbound on the final approach course, execute a procedure turn, and inform ATC.

2

To operate an aircraft under IFR, a flight plan must have been filed and an ATC clearance received prior to

- ☐ entering weather conditions in any airspace.
- ☐ controlling the aircraft solely by use of instruments.
- ☒ entering controlled airspace.

3

The lowest ILS Category II minimums are

- ☐ DH 100 feet and RVR 1,200 feet.
- ☐ DH 150 feet and RVR 1,500 feet.
- ☒ DH 50 feet and RVR 1,200 feet.

4

Wake turbulence is near maximum behind a jet transport just after takeoff because

- ☒ the engines are at maximum thrust output at slow airspeed.
- ☐ of the high angle of attack and high gross weight.
- ☐ the gear and flap configuration increases the turbulence to maximum.

5

Which is a necessary condition for the occurrence of a low-level temperature inversion wind shear?

- ☒ **The temperature differential between the cold and warm layers must be at least 10 degrees C.**
- ☐ **A wind direction difference of at least 30 degrees C between the wind near the surface and the wind just above the inversion.**
- ☐ **A calm or light wind near the surface and a relatively strong wind just above the inversion.**

6

According to Annex 6, 'RNP type' is defined as a containment value expressed as a distance in ... (i) ... from the intended position within which flights would be for at least ... (ii) ... of the total flying time.

☐ (i) nautical miles
(ii) 90%

☐ (i) kilometers
(ii) 90%

☒ (i) nautical miles
(ii) 95%

☐ (i) kilometers
(ii) 95%

7

According to Annex 6, what is the definition of an Air Operator Certificate?

- ☐ A certificate automatically authorising an operator to carry out domestic air services in any ICAO contracting State.
- ☒ A certificate authorising an operator to carry out specified commercial air transport operations.
- ☐ A certificate the crew will present to immigration officers, stating that all passengers on board fulfil the visa requirements needed.
- ☐ A certificate needed to carry out specified commercial international air transport operations, but not for domestic commercial flights.

8

In accordance with civil aviation regulations, an aeroplane whose maximum approved passenger seating configuration is greater than 600 seats must be equipped with at least:

- ☒ 9 hand fire-extinguishers conveniently located in the passenger compartment.
- ☐ 6 hand fire-extinguishers conveniently located in the passenger compartment.
- ☐ 8 hand fire-extinguishers conveniently located in the passenger compartment.
- ☐ 7 hand fire-extinguishers conveniently located in the passenger compartment.

9

The minimum navigation equipment required for an aircraft flying without restriction in MNPS airspace can be at the very least :

- ☐ Three inertial navigation units.
- ☒ Two inertial navigation units.
- ☐ One inertial navigation unit.
- ☒ Two inertial navigation units and a DECCA.

10

In the event of communication failure in an Minimum Navigation Performance Specification(MNPS) airspace, the pilot must:

- ☐ change the flight level in accordance with predetermined instructions.
- ☒ continue the flight in compliance with the last oceanic clearance received and acknowledged.
- ☐ join one of the so-called "special" routes.
- ☐ return to the flight plan route if it is different from the last oceanic clearance received and acknowledged.

11

During a flight to destination in the northern hemisphere, planned in MNPS (Minimum Navigation Performance Specification) airspace, you expect to cross the 30°W meridian at 00H30 UTC ; you will then normally be ;

- ☐ within the organized daytime flight track system
- ☐ in a random space
- ☒ out of the organized flight track system
- ☒ within the organized night-time flight track system

12

During a flight, the chief steward informs the crew that a passenger is using a portable device suspected to disturb the aircraft electronic systems. The captain:

- ☒ must not authorize any person to use such a device on board.
- ☐ authorizes its use during the whole flight phase.
- ☐ may authorize the use of this device, as an exception.
- ☐ authorizes its use except during take-off and landing phases.

13

The Master Minimum Equipment List (MMEL) defines the equipment on which certain in-flight failures can be allowed and the conditions under which this allowance can be accepted. This MMEL is drawn up by :

- ☒ the manufacturer and approved by the certification authority
- ☐ the operator and approved by the certification authority
- ☐ the operator and is specified in the operation manual
- ☐ the operator from a main list drawn up by the manufacturer

14

A piece of equipment on your public transport airplane fails while taxiing to the holding point. The reference document you use in the first place to decide on the procedure to follow is:

☒ the minimum equipment list.

☐ the flight record.

☐ the operation manual

☐ the CAA OPS.

15

During an explosive decompression at flight level 370 (FL 370), your first action will be :

- ☒ to put on the oxygen mask
- ☐ to comfort your passengers
- ☐ to warn the ATC
- ☐ to set the transponder to 7700

16

A category B aircraft can carry out an indirect approach followed by a visual maneuver only if the horizontal visibility is higher than or equal to:

☐ 3600 m

☐ 1600 m

☐ 2400 m

☒ 1500 m

17

When establishing an instrument approach procedure, 5 aircraft categories according to their speed at the threshold (Vat) are established. This speed is equal to the stalling speed in the landing configuration at the maximum certified landing weight multiplied by a factor of:

☒ 1.3

☐ 1.5

☐ 1.15

☐ 1.45

18

An airline operator shall make sure that if the aircraft planned for the flight is a performance class B aeroplane, it will be able, throughout its flight route or its alternate route scheduled from this initial route, to reach a climb rate of at least :

- ☒ 300 ft/min with one engine inoperative and all the others operating at maximum continuous power.
- ☐ 300ft/min with all engines operating at maximum continuous power.
- ☐ 500 ft/min with one engine inoperative and all the others operating at maximum continuous power.
- ☐ 500 ft/min with all engines operating at maximum cruise power.

19

A life jacket is mandatory for any passenger on board an aircraft flying away from the shore by more than :

☐ 100 NM

☒ 50 NM

☐ 400 NM

☐ 200 NM

20

The Civil Aviation Regulations establishes that, a co-pilot is not assigned to operate at the flight controls during take-off and landing unless :

- ☐ he has carried out at least three flights as pilot-in-command or as a co-pilot at the controls of the type to be used, in the preceding 90 days.
- ☒ he has carried out as pilot-in-command or as co-pilot at least three take-off and three landings in an aeroplane or an approved flight simulator of the type used, in the preceding 90 days.
- ☐ he has carried out as-pilot-in-command or as co-pilot at least three take-off and three landings in an aeroplane or an approved flight simulator of the type used, in the preceding 30 days
- ☐ he has operated as pilot-in-command or as co-pilot at the controls during take-off and landing of the type to be used in the preceding 90 days.

21

The Master Minimum Equipment List (M MEL), if this exists, is established by:

- ☐ the operator of the aircraft, and accepted by the authority
- ☒ the operator of the aircraft, and accepted by the manufacturer
- ☐ the manufacturer of the aircraft, but need not to be accepted by the authority
- ☐ the manufacturer of the aircraft, and accepted by the authority

22

Following an emergency landing which will need an evacuation from the aircraft?
1 - remain on the runway,
2 - clear the runway using the first available taxiway,
3 - keep one engine or the APU running in order to maintain the electrical power supply on,
4 - turn off all systems.

☐ 2,4.

☐ 1,3.

☐ 2,3.

☒ 1,4.

23

For aircraft certified , cockpit voice recorder must keep the conversations and sound alarms recorded during the last :

- ☒ 25 hours of operation.
- ☐ 48 hours of operation.
- ☐ flight.
- ☐ 30 minutes of operation.

24

The information to consider for a standard straight-in approach is :

1 - the horizontal visibility

2 - the ceiling

3 - the minimum descending altitude (MDA)

4 - the decision altitude (DA) Which of the following combinations contains all of the

☐ 1 - 4

☒ 1 - 2 - 4

☐ 1 - 3

☐ 1 - 2 - 3

25

Supplemental oxygen is used to :

- ☒ provide people on board with oxygen during a cabin depressurisation
- ☐ protect a crew who fights a fire
- ☐ assist a passenger with breathing disorders
- ☐ provide with oxygen passengers who might require it, following a cabin depressurisation

26

In the absence of wind and without the astronomic precession effect, an aircraft would, at a constant gyro heading, follow a :

☐ spherical flight segment

☐ straight map line

☐ rhumb line

☒ great circle line

27

The greatest possibility of ice buildup, while flying under icing conditions, occurs on :

- ☐ The upper and lower wingsurfaces.
- ☐ Only the pitot and static probes.
- ☒ The aircraft front areas.
- ☐ The upper and lower rudder surfaces.

Candidate: Samuel Okirol
Date of birth: --
Subject: 070-Operational procedures
Date: 2014-08-20

28

The maximum validity of a SNOWTAM is :

☐ 12 hours

☐ 24 hours

☐ 3 hours

☒ 6 hours

29

During an aircraft de-icing/anti-icing procedure:

- ☐ the de-icing fluid is applied without heating and the anti-icing fluid is applied hot.
- ☐ the anti-icing fluid is applied without heating and the de-icing fluid is applied hot.
- ☒ the anti-icing and de-icing fluids are applied cold.
- ☐ the anti-icing and de-icing fluids are applied hot.

30

An aircraft having undergone an anti-icing procedure must be anti-icing fluid free at the latest when :

- ☐ releasing the brakes in order to take-off.
- ☐ leaving the icing zone.
- ☒ it is rotating (before taking-off).
- ☐ it is implementing its own anti-icing devices.

31

As regards the detection of bird strike hazard, the pilot's means of information and prevention are:

1 - ATIS.

2 - NOTAMs.

3- BIRDTAMs.

4 - Weather radar.,

☐ 1,2,3,4,5

☐ 2,5

☒ 1,2,5

☐ 1,3,4

32

In the absence of wind and without the astronomic precession effect, an aircraft would, at a constant gyro heading, follow a:

- ☐ spherical flight segment
- ☐ rhumb line
- ☒ great circle line
- ☐ straight map line

33

When taking-off after a widebody aircraft which has just landed, you should take-off :

- ☒ at the point where the aircraft's wheels have touched down and on the wind side of the runway .
- ☐ beyond the point where the aircraft's wheels have touched down.
- ☐ in front of the point where the aircraft's wheels have touched down.
- ☐ at the point where the aircraft's wheels have touched the ground and on the underwind side of the runway .

34

The greatest wake turbulence occurs when the generating aircraft is :

- ☐ Small, light, at maximum speed in full flaps configuration
- ☐ Small, light, at low speed in clean configuration
- ☐ Large, heavy, at maximum speed in full flaps configuration
- ☒ Large, heavy, at low speed in clean configuration

35

In addition to informing each State, whose citizens are known to be on board an aircraft, the State of the country in which an aircraft has landed after an act of unlawful interference must immediately notify the :

- ☐ State of Registry of the aircraft and the State of the operator only
- ☒ State of Registry of the aircraft and the CAA
- ☐ State of Registry of the aircraft, the State of the operator and ICAO
- ☐ State of the operator, the CAA. and ICAO

36

In case of a serious threat based on the presence of a bomb on board a pressurized aircraft and disregarding any fuel considerations:

- ☐ you carry out an emergency descent to reach the safety altitude.
- ☐ you go down to the level corresponding to the indicated cabin altitude and keep the aircraft in a clean configuration until the final approach.
- ☐ you climb to the maximum flight level which does not need the use of pressurization.
- ☒ you descend to the flight level corresponding to the indicated cabin altitude or the safety altitude if higher and take preventive steps by putting yourself in a landing approach configuration.

37

In the hazardous materials transportation act, the freight compliance with the regulatory arrangements is the responsibility of the :

☐ aerodrome manager.

☐ captain.

☒ sender.

☐ station manager.

38

The content of the dangerous goods transport document is specified in the:

- ☐ Air Transport Permit.
- ☐ OPS documentation.
- ☒ Technical Instructions.
- ☐ Flight Manual.

39

According to the civil aviation regulations a runway is considered damp when:

- ☐ it is covered with a film of water of less than 3 mm.
- ☒ its surface is not dry, and when surface moisture does not give it a shiny appearance.
- ☐ surface moisture gives it a shiny appearance.
- ☒ it is covered with a film of water of less than 1 mm.

40

For an airplane with a tyre pressure of 12 bars, there is a risk of dynamic hydroplaning as soon as the :

1- water height is equal to the depth of the tyre grooves.

2- speed is greater than 114 kt.

3- water height is equal to the half of the depth of the tyre grooves.

4- speed is greater than 83 kt.

The combination regrouping all the correct statements is :

☐ 1 and 2.

☒ 1 and 4.

☐ 3 and 4.

☐ 2 and 3.