
Online Examination Report

Date:	21.07.2014
Attempts:	1
Examinee:	Ariho, William
Date of birth:	4/22/1989
Subject:	070-Operational Procedures
Result:	34,99 %
Time used:	00:00:12 (HH:MM:SS)

Attachments

1. List of result by question
2. List of result by topic
3. Detailed question result report

Attachment 1: List of result by question

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
1	186	71. OPERATIONAL PROCEDURES		0,00	1,00
2	180	71. OPERATIONAL PROCEDURES		1,00	1,00
3	175	71. OPERATIONAL PROCEDURES		0,00	1,00
4	191	71. OPERATIONAL PROCEDURES		0,00	1,00
5	184	71. OPERATIONAL PROCEDURES		0,00	1,00
6	174	71. OPERATIONAL PROCEDURES		1,00	1,00
7	56	71.1.1 ICAO Annex 6		0,00	1,00
8	19	71.1.1.3 General		1,00	1,00
9	149	71.1.1.3 General		0,00	1,00
10	167	71.1.3.2 Transoceanic and polar flight		1,00	1,00
11	100	71.2.1 Operations Manual		1,00	1,00
12	34	71.2.1.1 Operating procedures		0,00	1,00
13	112	71.2.1.1 Operating procedures		0,00	1,00
14	107	71.2.1.1 Operating procedures		0,00	1,00
15	3	71.2.2 Icing conditions		0,00	1,00
16	115	71.2.2.1 On ground de-/anti-icing		0,00	1,00
17	143	71.2.2.1 On ground de-/anti-icing		1,00	1,00
18	140	71.2.2.1 On ground de-/anti-icing		1,00	1,00
19	119	71.2.5 Fire/smoke		0,00	1,00
20	117	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
21	89	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
22	102	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
23	37	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
24	5	71.2.5.6 Types of extinguishers		1,00	1,00
25	141	71.2.5.6 Types of extinguishers		0,00	1,00
26	131	71.2.5.6 Types of extinguishers		1,00	1,00
27	16	71.2.5.6 Types of extinguishers		1,00	1,00
28	87	71.2.5.6 Types of extinguishers		0,00	1,00

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
29	62	71.2.7	Wind shear and microburst	0,00	1,00
30	78	71.2.7.1	Effects and recognition	0,00	1,00
31	86	71.2.7.1	Effects and recognition	1,00	1,00
32	162	71.2.8	Wake turbulence	0,00	1,00
33	166	71.2.8	Wake turbulence	1,00	1,00
34	12	71.2.8.1	Cause	1,00	1,00
35	15	71.2.8.1	Cause	0,00	1,00
36	38	71.2.8.2	List of relevant parameters	0,00	1,00
37	79	71.2.9	Security (unlawful events)	0,00	1,00
38	55	71.2.9.2	Use of SSR	0,00	1,00
39	111	71.2.12	Transport of dangerous goods	0,00	1,00
40	97	71.2.12.1	ICAO Annex 18	1,00	1,00
Total:35%				14,00	40,00

Attachment 2: List of result by topic

Licence

Date: 16.07.2014

Examinee: Ariho, William

Location: Uganda Civil Aviation Authority

Your Result: 14,00 from 40,00 Points (35,00 %)

Topics	Ammount of Questions	Points achieved	Maximum Points	Percent
71. OPERATIONAL PROCEDURES	40	14,00	40,00	35,00
71.1. GENERAL REQUIREMENTS	4	2,00	4,00	50,00
71.2. SPECIAL OPERATIONAL PROCEDURES	30	10,00	30,00	33,33
Total	40	14,00	40,00	35,00

1

Which is a necessary condition for the occurrence of a low-level temperature inversion wind shear?

- ☒ The temperature differential between the cold and warm layers must be at least 10 degrees C.
- ☐ A wind direction difference of at least 30 degrees C between the wind near the surface and the wind just above the inversion.
- ☐ A calm or light wind near the surface and a relatively strong wind just above the inversion.

Candidate: William Ariho
Date of birth: 1989-04-22

Subject: 070-Operational Procedures
Date: 2014-07-16



2

What aural and visual indications should be observed over an ILS outer marker?

☐ Alternate dots and dashes at the rate of two per second.

☒ Continuous dashes at the rate of two per second.

☐ Continuous dots at the rate of six per second.

Candidate: William Ariho
Date of birth: 1989-04-22

Subject: 070-Operational Procedures
Date: 2014-07-16



3

(Refer to Figure 126.) Which altitude (box 1) is applicable to the vertical extent of the inner and outer circles (now called surface and shelf areas)?

☐ 4,000 feet above airport.

☐ 3,000 feet above airport.

☒ 3,000 feet AGL.

See Attachments:

1. atp_126.jpg

Figure 126

(Attachment
No.1)

4

When landing behind a large jet aircraft, at which point on the runway should you plan to land?

- ☐ If any crosswind, land on the windward side of the runway and prior to the jet's touchdown point.
- ☐ Beyond the jet's touchdown point.
- ☒ At least 1,000 feet beyond the jet's touchdown point.

5

When diverting to an alternate airport because of an emergency, pilots should

- ☐ rely upon radio as the primary method of navigation.
- ☐ apply rule-of-thumb computations, estimates, and other appropriate shortcuts to divert to the new course as soon as possible.
- ☒ complete all plotting, measuring, and computations involved before diverting.

6

Which incident would require that the nearest Flight Control Center field office be notified immediately?

- ☒ **In-flight fire.**
- ☐ **Fire of the primary aircraft while in a hangar which results in damage to other property of more than \$25,000.**
- ☐ **Ground fire resulting in fire equipment dispatch.**

Candidate: William Ariho
Date of birth: 1989-04-22

Subject: 070-Operational Procedures
Date: 2014-07-16

7

Among the EAC states, the CAA-OPS of Aircraft is based on :

- ☒ ICAO Annex 6
- ☐ A CAA guideline
- ☒ The Civil Aviation Requirements (CAA)
- ☐ The air transport rules

8

During a night flight, an observer located in the cockpit, seeing an aircraft coming from front right on approximate opposite parallel track, will first see the:

☒ green light

☐ white light

☐ red and white flashing light

☐ red light

9

Which one of the following sets of conditions is most likely to attract birds to an aerodrome ?

- ☒ a refuse tip in close proximity
- ☐ a modern sewage tip in close proximity
- ☒ mowing and maintaining the grass long
- ☐ the extraction of minerals such as sand and gravel

10

What emergency equipment is required for extended overwater operations?

- ☐ A pyrotechnic signaling device for each life preserver.
- ☒ A life jacket equipped with a survivor locator light, for each person on the airplane.
- ☐ A portable survival emergency locator transmitter for each liferaft.

11

Information concerning evacuation procedures can be found in the :

☐ flight manual.

☒ operation manual.

☐ operational flight plan.

☐ journey logbook.

12

Flight crew members on the flight deck shall keep their safety belt fastened:

- ☐ while at their station.
- ☒ only during take off and landing and whenever necessary by the commander in the interest of safety.
- ☐ only during take off and landing.
- ☐ from take off to landing.

Candidate: William Ariho
Date of birth: 1989-04-22

Subject: 070-Operational Procedures
Date: 2014-07-16



13

A life jacket is mandatory for any passenger on board an aircraft flying away from the shore by more than :

☒ 100 NM

☐ 50 NM

☐ 400 NM

☐ 200 NM

14

For aircraft certified , cockpit voice recorder must keep the conversations and sound alarms recorded during the last :

☐ 25 hours of operation.

☐ 48 hours of operation.

☒ flight.

☐ 30 minutes of operation.

Candidate: William Ariho
Date of birth: 1989-04-22

Subject: 070-Operational Procedures
Date: 2014-07-16

15

The maximum validity of a SNOWTAM is :

☒ 12 hours

☐ 24 hours

☐ 3 hours

☐ 6 hours

16

During an aircraft de-icing/anti-icing procedure:

- ☐ the de-icing fluid is applied without heating and the anti-icing fluid is applied hot.
- ☐ the anti-icing fluid is applied without heating and the de-icing fluid is applied hot.
- ☐ the anti-icing and de-icing fluids are applied cold.
- ☒ the anti-icing and de-icing fluids are applied hot.

17

For a given ambient temperature and type of de-icing fluid used, in which one of the following types of weather condition will the holdover (protection) time be shortest ?

☒ Freezing rain

☐ Freezing fog

☐ Frost

☐ Steady snow

18

An aircraft having undergone an anti-icing procedure and having exceeded the protection time of the anti-icing fluid:

- ☐ must only undergo a de-icing procedure for take-off.
- ☐ need not to undergo a new anti-icing procedure for take-off.
- ☐ must only undergo a new anti-icing procedure for take-off.
- ☒ must undergo a de-icing procedure before a new application of anti-icing fluid for take-off.

19

The "NO SMOKING" sign must be illuminated :

- ☒ during take off and landing.
- ☐ when oxygen is being supplied in the cabin.
- ☐ in each cabin section if oxygen is being carried.
- ☐ during climb and descent.

20

To extinguish a fire in the cockpit, you use:

- 1. a water fire-extinguisher*
- 2. a powder or chemical fire-extinguisher*
- 3. a halon fire-extinguisher*
- 4. a CO2 fire-extinguisher*

☐ 1, 2, 3, 4

☒ 2, 3, 4

☐ 3, 4

☐ 1, 2

21

In case of a fire due to the heating of the brakes, you fight the fire using:

1. a dry powder fire extinguisher

2. a water spray atomizer

3. a water fire-extinguisher

4. a CO2 fire-extinguisher to the maximum

The combination regrouping all the correct statements is:

☐ 3, 4

☐ 1, 2

☐ 2, 3, 4

☒ 1, 4

22

If smoke appears in the air conditioning, the first action to take is to :

- ☐ Put on the mask and goggles.
- ☒ Cut off all air conditioning units.
- ☐ Determine which system is causing the smoke.
- ☐ Begin an emergency descent.

23

Beneath fire extinguishers the following equipment for fire fighting is on board:

- ☒ a big bunch of fire extinguishing blankets.
- ☐ water and all type of beverage.
- ☐ a hydraulic winch and a big box of tools.
- ☐ crash axes or crowbars.

24

You will use a powder fire-extinguisher for:

- 1. a paper fire**
- 2. a plastic fire**
- 3. a hydrocarbon fire**
- 4. an electrical fire**

The combination regrouping all the correct statements is:

☐ **1, 2, 3**

☐ **1, 4**

☐ **2, 3**

☒ **1, 2, 3, 4**

25

A fire occurs in a wheel and immediate action is required to extinguish it. The safest extinguishant to use is :

☐ water

☐ foam

☒ dry powder

☒ CO2 (carbon dioxide)

26

You will use a halon extinguisher for a fire of:

1 - solids (fabric, plastic, ...)

2 - liquids (alcohol, gasoline, ...)

3 - gas

4 - metals (aluminium, magnesium, ...)

The combination regrouping all the correct statements

☒ 1,2,3

☐ 1,2,3,4

☐ 1,2,4

☐ 2,3,4

27

You will use a CO2 fire-extinguisher for :

- 1. a paper fire*
- 2. a plastic fire*
- 3. a hydrocarbon fire*
- 4. an electrical fire*

The combination regrouping all the correct statements is:

☐ 3,4

☐ 2,3

☒ 1,2,3,4

☐ 1,2,3

28

CO2 type extinguishers are fit to fight:

1 - class A fires

2 - class B fires

3 - electrical source fires

4 - special fires: metals, gas, chemical product

Which of the following combinations contains all the correct statements:

☐ 2 - 3 - 4

☐ 1 - 2 - 3

☒ 1 - 2 - 4

☐ 1 - 3 - 4

29

In final approach, you encounter a strong rear wind gust or strong down wind which forces you to go around. You

1- maintain the same aircraft configuration (gear and flaps)

2- reduce the drags (gear and flaps)

3- gradually increase the attitude up to triggering of stick shaker

4- avoid excessive attitude change The combination of correct statements is :

☐ 1,3

☒ 1,4

☐ 2,4

☐ 2,3

30

During a manual approach, the aeroplane is subjected to windshear with an increasing tail wind. In the absence of a pilot action, the aeroplane:

- 1- flies above the intended approach path
- 2- flies below the intended approach path
- 3- has an increasing true airspeed
- 4- has a decreasing true airspeed

The combination of correct statements is:

☐ 1, 4.

☐ 2, 4.

☒ 1, 3.

☐ 2, 3.

31

Wind shear is:

- ☐ a variation only in horizontal wind velocity over a short distance.
- ☐ a variation in vertical or horizontal wind velocity and / or wind direction over a large distance.
- ☐ a variation only in vertical wind velocity over a short distance.
- ☒ a large variation in vertical or horizontal wind velocity and / or wind direction over a short distance.

32

The greatest wake turbulence occurs when the generating aircraft is :

- ☐ Small, light, at maximum speed in full flaps configuration
- ☐ Small, light, at low speed in clean configuration
- ☒ Large, heavy, at maximum speed in full flaps configuration
- ☐ Large, heavy, at low speed in clean configuration

33

When taking-off after a widebody aircraft which has just landed, you should take-off :

- ☐ at the point where the aircraft's wheels have touched down and on the wind side of the runway .
- ☒ beyond the point where the aircraft's wheels have touched down.
- ☐ in front of the point where the aircraft's wheels have touched down.
- ☐ at the point where the aircraft's wheels have touched the ground and on the underwind side of the runway .

34

The wake turbulence caused by an aircraft is mainly the result of:

1. An aerodynamic effect (wing tip vortices).
2. The engines action (propellers rotation or engine gas exhausts).
3. The importance of the drag devices (size of the landing gear, of the flaps, etc.).

The combination regrouping all the correct statements is:

☐ 1, 2 and 3.

☒ 1.

☐ 2 and 3.

☐ 3.

35

Aeroplane wake turbulence during take off starts when:

- ☒ the take off roll commences.
- ☐ out of ground effect.
- ☐ the nose wheel lifts off the runway.
- ☐ slats and flaps are extended only.

36

The greatest wake turbulence occurs when the generating aircraft is:

- ☒ Large, heavy, at maximum speed in full flaps configuration
- ☐ Small, light, at maximum speed in full flaps configuration
- ☐ Small, light, at low speed in clean configuration
- ☐ Large, heavy, at low speed in clean configuration

Candidate: William Ariho
Date of birth: 1989-04-22

Subject: 070-Operational Procedures
Date: 2014-07-16



37

What transponder code should be used to provide recognition of an aircraft which is being subjected to unlawful interference :

☐ code 7600

☒ code 7700

☐ code 7500

☐ code 2000

Candidate: William Ariho
Date of birth: 1989-04-22

Subject: 070-Operational Procedures
Date: 2014-07-16



38

What is the transponder code to be used by the commander of an aircraft that is subject to unlawful interference?

☐ A 7500

☒ A 7700

☐ A 7800

☐ A 7600

39

ICAO (International Civil Aviation Organization) Appendix 18 is a document dealing with

- ☒ the technical operational use of aircraft
- ☐ the air transport of live animals
- ☐ the noise pollution of aircraft
- ☐ the safety of the air transport of dangerous goods

40

In addition to the languages required by the State of Origin, what language should be set for the markings related to dangerous goods :

☐ French

☒ English

☐ English, French or Spanish

☐ Spanish


Attachment No. 1

Questions 3

Figure 126

atp_126.jpg

Class C Airspace



Services upon establishing two-way radio communication and radar contact:

Sequencing Arrivals

IFR/VFR Standard Separation

IFR/VFR Traffic Advisories and Conflict Resolution

VFR/VFR Traffic Advisories

IFR: Instrument Flight Rules
VFR: Visual Flight Rules

Figure 126. Class C Airspace © ASA