
Online Examination Report

Date:	21.07.2014
Attempts:	1
Examinee:	Asaba, Joshua
Date of birth:	2/24/1990
Subject:	070-Operational Procedures
Result:	30 %
Time used:	00:00:12 (HH:MM:SS)

Attachments

1. List of result by question
2. List of result by topic
3. Detailed question result report

Attachment 1: List of result by question

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
1	175	71. OPERATIONAL PROCEDURES		0,00	1,00
2	174	71. OPERATIONAL PROCEDURES		1,00	1,00
3	184	71. OPERATIONAL PROCEDURES		0,00	1,00
4	186	71. OPERATIONAL PROCEDURES		1,00	1,00
5	180	71. OPERATIONAL PROCEDURES		0,00	1,00
6	191	71. OPERATIONAL PROCEDURES		0,00	1,00
7	56	71.1.1 ICAO Annex 6		0,00	1,00
8	118	71.1.1.3 General		0,00	1,00
9	149	71.1.1.3 General		0,00	1,00
10	167	71.1.3.2 Transoceanic and polar flight		1,00	1,00
11	100	71.2.1 Operations Manual		1,00	1,00
12	34	71.2.1.1 Operating procedures		0,00	1,00
13	112	71.2.1.1 Operating procedures		0,00	1,00
14	3	71.2.2 Icing conditions		0,00	1,00
15	148	71.2.2 Icing conditions		0,00	1,00
16	114	71.2.2.1 On ground de-/anti-icing		1,00	1,00
17	140	71.2.2.1 On ground de-/anti-icing		0,00	1,00
18	115	71.2.2.1 On ground de-/anti-icing		0,00	1,00
19	144	71.2.4.2 Influence of the flight procedure		0,00	1,00
20	119	71.2.5 Fire/smoke		0,00	1,00
21	117	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
22	102	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
23	37	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
24	89	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
25	98	71.2.5.6 Types of extinguishers		0,00	1,00
26	5	71.2.5.6 Types of extinguishers		0,00	1,00
27	141	71.2.5.6 Types of extinguishers		1,00	1,00
28	131	71.2.5.6 Types of extinguishers		0,00	1,00

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
29	87	71.2.5.6	Types of extinguishers	0,00	1,00
30	166	71.2.8	Wake turbulence	1,00	1,00
31	162	71.2.8	Wake turbulence	0,00	1,00
32	12	71.2.8.1	Cause	1,00	1,00
33	15	71.2.8.1	Cause	0,00	1,00
34	38	71.2.8.2	List of relevant parameters	0,00	1,00
35	79	71.2.9	Security (unlawful events)	1,00	1,00
36	55	71.2.9.2	Use of SSR	1,00	1,00
37	111	71.2.12	Transport of dangerous goods	1,00	1,00
38	97	71.2.12.1	ICAO Annex 18	1,00	1,00
39	154	71.2.13	Contaminated runways	0,00	1,00
40	67	71.2.13.4	Procedures	0,00	1,00
Total:30%				12,00	40,00

Attachment 2: List of result by topic

Licence

Date: 16.07.2014

Examinee: Asaba, Joshua

Location: Uganda Civil Aviation Authority

Your Result: 12,00 from 40,00 Points (30,00 %)

Topics	Ammount of Questions	Points achieved	Maximum Points	Percent
71. OPERATIONAL PROCEDURES	40	12,00	40,00	30,00
71.1. GENERAL REQUIREMENTS	4	1,00	4,00	25,00
71.2. SPECIAL OPERATIONAL PROCEDURES	30	9,00	30,00	30,00
Total	40	12,00	40,00	30,00

1

(Refer to Figure 126.) Which altitude (box 1) is applicable to the vertical extent of the inner and outer circles (now called surface and shelf areas)?

☒ **3,000 feet above airport.**

☐ **3,000 feet AGL.**

☐ **4,000 feet above airport.**

See Attachments:

1. atp_126.jpg

Figure 126

(Attachment
No.1)

2

Which incident would require that the nearest Flight Control Center field office be notified immediately?

- ☒ **In-flight fire.**
- ☐ **Fire of the primary aircraft while in a hangar which results in damage to other property of more than \$25,000.**
- ☐ **Ground fire resulting in fire equipment dispatch.**

3

When diverting to an alternate airport because of an emergency, pilots should

- ☐ rely upon radio as the primary method of navigation.
- ☐ apply rule-of-thumb computations, estimates, and other appropriate shortcuts to divert to the new course as soon as possible.
- ☒ complete all plotting, measuring, and computations involved before diverting.

4

Which is a necessary condition for the occurrence of a low-level temperature inversion wind shear?

- ☒ **A calm or light wind near the surface and a relatively strong wind just above the inversion.**
- ☐ **A wind direction difference of at least 30 degrees C between the wind near the surface and the wind just above the inversion.**
- ☐ **The temperature differential between the cold and warm layers must be at least 10 degrees C.**

Candidate: Joshua Asaba
Date of birth: 1990-02-24

Subject: 070-Operational Procedures
Date: 2014-07-16

5

What aural and visual indications should be observed over an ILS outer marker?

- ☐ Continuous dashes at the rate of two per second.
- ☐ Continuous dots at the rate of six per second.
- ☒ Alternate dots and dashes at the rate of two per second.

6

When landing behind a large jet aircraft, at which point on the runway should you plan to land?

- ☒ **At least 1,000 feet beyond the jet's touchdown point.**
- ☐ **Beyond the jet's touchdown point.**
- ☐ **If any crosswind, land on the windward side of the runway and prior to the jet's touchdown point.**

Candidate: Joshua Asaba
Date of birth: 1990-02-24

Subject: 070-Operational Procedures
Date: 2014-07-16

7

Among the EAC states, the CAA-OPS of Aircraft is based on :

- ☐ A CAA guideline
- ☐ The air transport rules
- ☐ ICAO Annex 6
- ☒ The Civil Aviation Requirements (CAA)

8

90 % of bird strikes occur :

- ☒ under 500 m
- ☐ between 500 and 1 500 m
- ☐ between 500 and 1 000 m
- ☒ above 1 000 m

9

Which one of the following sets of conditions is most likely to attract birds to an aerodrome ?

- ☒ a refuse tip in close proximity
- ☐ a modern sewage tip in close proximity
- ☒ the extraction of minerals such as sand and gravel
- ☐ mowing and maintaining the grass long

10

What emergency equipment is required for extended overwater operations?

- ☒ A life jacket equipped with a survivor locator light, for each person on the airplane.
- ☐ A pyrotechnic signaling device for each life preserver.
- ☐ A portable survival emergency locator transmitter for each liferaft.

11

Information concerning evacuation procedures can be found in the :

- ☒ operation manual.
- ☐ journey logbook.
- ☐ flight manual.
- ☐ operational flight plan.

12

Flight crew members on the flight deck shall keep their safety belt fastened:

- ☐ while at their station.
- ☒ only during take off and landing and whenever necessary by the commander in the interest of safety.
- ☐ from take off to landing.
- ☐ only during take off and landing.

Candidate: Joshua Asaba
Date of birth: 1990-02-24

Subject: 070-Operational Procedures
Date: 2014-07-16

13

A life jacket is mandatory for any passenger on board an aircraft flying away from the shore by more than :

☐ 50 NM

☐ 200 NM

☐ 100 NM

☒ 400 NM

Candidate: Joshua Asaba
Date of birth: 1990-02-24

Subject: 070-Operational Procedures
Date: 2014-07-16



14

The maximum validity of a SNOWTAM is :

☐ 24 hours

☒ 6 hours

☐ 12 hours

☐ 3 hours

15

The greatest possibility of ice buildup, while flying under icing conditions, occurs on :

- ☒ The aircraft front areas.
- ☐ The upper and lower rudder surfaces.
- ☒ Only the pitot and static probes.
- ☐ The upper and lower wingsurfaces.

16

The anti-icing fluid protecting film can wear off and reduce considerably the protection time:

- ☐ when the outside temperature is close to 0 °C.
- ☐ when the airplane is into the wind.
- ☒ during strong winds or as a result of the other aircraft engines jet wash.
- ☐ when the temperature of the airplane skin is close to 0 °C.

17

An aircraft having undergone an anti-icing procedure and having exceeded the protection time of the anti-icing fluid:

- ☐ need not to undergo a new anti-icing procedure for take-off.
- ☐ must undergo a de-icing procedure before a new application of anti-icing fluid for take-off.
- ☒ must only undergo a de-icing procedure for take-off.
- ☐ must only undergo a new anti-icing procedure for take-off.

18

During an aircraft de-icing/anti-icing procedure:

- ☐ the anti-icing and de-icing fluids are applied cold.
- ☐ the anti-icing and de-icing fluids are applied hot.
- ☒ the anti-icing fluid is applied without heating and the de-icing fluid is applied hot.
- ☒ the de-icing fluid is applied without heating and the anti-icing fluid is applied hot.

Candidate: Joshua Asaba
Date of birth: 1990-02-24

Subject: 070-Operational Procedures
Date: 2014-07-16



19

As regards the detection of bird strike hazard, the pilot's means of information and prevention are:

1 - ATIS.

2 - NOTAMs.

3- BIRDTAMs.

4 - Weather radar.,

☐ 1,2,5

☒ 1,3,4

☐ 2,5

☐ 1,2,3,4,5

20

The "NO SMOKING" sign must be illuminated :

- ☒ in each cabin section if oxygen is being carried.
- ☐ during climb and descent.
- ☐ when oxygen is being supplied in the cabin.
- ☐ during take off and landing.

21

To extinguish a fire in the cockpit, you use:

- 1. a water fire-extinguisher*
- 2. a powder or chemical fire-extinguisher*
- 3. a halon fire-extinguisher*
- 4. a CO2 fire-extinguisher*

☐ 3, 4

☐ 1, 2

☒ 2, 3, 4

☐ 1, 2, 3, 4

22

If smoke appears in the air conditioning, the first action to take is to :

- ☒ Cut off all air conditioning units.
- ☐ Begin an emergency descent.
- ☐ Put on the mask and goggles.
- ☐ Determine which system is causing the smoke.

23

Beneath fire extinguishers the following equipment for fire fighting is on board:

- ☒ a hydraulic winch and a big box of tools.
- ☐ a big bunch of fire extinguishing blankets.
- ☐ water and all type of beverage.
- ☐ crash axes or crowbars.

24

In case of a fire due to the heating of the brakes, you fight the fire using:

1. a dry powder fire extinguisher

2. a water spray atomizer

3. a water fire-extinguisher

4. a CO2 fire-extinguisher to the maximum

The combination regrouping all the correct statements is:

☐ 2, 3, 4

☐ 3, 4

☐ 1, 2

☒ 1, 4

25

A CO2 fire extinguisher can be used for:

- 1. a paper fire*
- 2. a hydrocarbon fire*
- 3. a fabric fire*
- 4. an electrical fire*
- 5. a wood fire*

The combination regrouping all the correct statements

☐ 2, 3, 4

☐ 1, 2, 3, 4, 5

☒ 1, 3, 5

☐ 2, 4, 5

26

You will use a powder fire-extinguisher for:

- 1. a paper fire**
- 2. a plastic fire**
- 3. a hydrocarbon fire**
- 4. an electrical fire**

The combination regrouping all the correct statements is:

☒ **1, 2, 3**

☐ **1, 4**

☐ **1, 2, 3, 4**

☐ **2, 3**

27

A fire occurs in a wheel and immediate action is required to extinguish it. The safest extinguishant to use is :

☒ dry powder

☐ CO2 (carbon dioxide)

☐ foam

☐ water

28

You will use a halon extinguisher for a fire of:

1 - solids (fabric, plastic, ...)

2 - liquids (alcohol, gasoline, ...)

3 - gas

4 - metals (aluminium, magnesium, ...)

The combination regrouping all the correct statements

☐ 1,2,4

☒ 2,3,4

☐ 1,2,3,4

☐ 1,2,3

29

CO2 type extinguishers are fit to fight:

1 - class A fires

2 - class B fires

3 - electrical source fires

4 - special fires: metals, gas, chemical product

Which of the following combinations contains all the correct statements:

☐ 1 - 2 - 4

☐ 2 - 3 - 4

☐ 1 - 2 - 3

☒ 1 - 3 - 4

30

When taking-off after a widebody aircraft which has just landed, you should take-off :

- ☐ in front of the point where the aircraft's wheels have touched down.
- ☐ at the point where the aircraft's wheels have touched the ground and on the underwind side of the runway .
- ☒ beyond the point where the aircraft's wheels have touched down.
- ☐ at the point where the aircraft's wheels have touched down and on the wind side of the runway .

31

The greatest wake turbulence occurs when the generating aircraft is :

- ☐ Small, light, at low speed in clean configuration
- ☒ Large, heavy, at low speed in clean configuration
- ☐ Small, light, at maximum speed in full flaps configuration
- ☒ Large, heavy, at maximum speed in full flaps configuration

32

The wake turbulence caused by an aircraft is mainly the result of:

1. An aerodynamic effect (wing tip vortices).
2. The engines action (propellers rotation or engine gas exhausts).
3. The importance of the drag devices (size of the landing gear, of the flaps, etc.).

The combination regrouping all the correct statements is:

☐ 2 and 3.

☐ 3.

☒ 1.

☐ 1, 2 and 3.

33

Aeroplane wake turbulence during take off starts when:

- ☐ the nose wheel lifts off the runway.
- ☐ slats and flaps are extended only.
- ☐ out of ground effect.
- ☒ the take off roll commences.

34

The greatest wake turbulence occurs when the generating aircraft is:

- ☒ Large, heavy, at maximum speed in full flaps configuration
- ☐ Small, light, at maximum speed in full flaps configuration
- ☐ Large, heavy, at low speed in clean configuration
- ☐ Small, light, at low speed in clean configuration

Candidate: Joshua Asaba
Date of birth: 1990-02-24

Subject: 070-Operational Procedures
Date: 2014-07-16

35

What transponder code should be used to provide recognition of an aircraft which is being subjected to unlawful interference :

☒ **code 7500**

☐ **code 2000**

☐ **code 7700**

☐ **code 7600**

Candidate: Joshua Asaba
Date of birth: 1990-02-24

Subject: 070-Operational Procedures
Date: 2014-07-16



36

What is the transponder code to be used by the commander of an aircraft that is subject to unlawful interference?

☐ A 7800

☒ A 7500

☐ A 7700

☐ A 7600

37

ICAO (International Civil Aviation Organization) Appendix 18 is a document dealing with

:

- ☐ the noise pollution of aircraft
- ☒ the safety of the air transport of dangerous goods
- ☐ the air transport of live animals
- ☐ the technical operational use of aircraft

38

In addition to the languages required by the State of Origin, what language should be set for the markings related to dangerous goods :

☒ English

☐ Spanish

☐ French

☐ English, French or Spanish

39

According to the civil aviation regulations a runway is considered damp when:

- ☐ surface moisture gives it a shiny appearance.
- ☐ it is covered with a film of water of less than 1 mm.
- ☐ its surface is not dry, and when surface moisture does not give it a shiny appearance.
- ☒ it is covered with a film of water of less than 3 mm.

40

In case of landing on a flooded runway and in heavy rain:

1. you increase your approach speed,
2. you land firmly in order to obtain a firm contact of the wheels with the runway and immediately land your nose gear,
3. you decrease your approach speed,
4. you use systematically all the lift dumper devices,
5. you land as smoothly as possible,
6. you brake energetically.

The combination regrouping all the correct statements is:

☒ 1, 4, 5, 6

☐ 1, 2, 4

☐ 2, 3, 4

☐ 3, 5


Attachment No. 1

Questions 1

Figure 126

atp_126.jpg

Class C Airspace



Services upon establishing two-way radio communication and radar contact:

Sequencing Arrivals

IFR/VFR Standard Separation

IFR/VFR Traffic Advisories and Conflict Resolution

VFR/VFR Traffic Advisories

IFR: Instrument Flight Rules
VFR: Visual Flight Rules

Figure 126. Class C Airspace © ASA