
Online Examination Report

Date:	02.08.2014
Attempts:	1
Examinee:	Okeng, Japheth
Date of birth:	
Subject:	070-Operational procedures
Result:	0 %
Time used:	00:00:08 (HH:MM:SS)

Attachments

1. List of result by question
2. List of result by topic
3. Detailed question result report

Attachment 1: List of result by question

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
1	176	71. OPERATIONAL PROCEDURES		0,00	1,00
2	185	71. OPERATIONAL PROCEDURES		0,00	1,00
3	184	71. OPERATIONAL PROCEDURES		0,00	1,00
4	200	71. OPERATIONAL PROCEDURES		0,00	1,00
5	59	71.1.1.1 Definitions		0,00	1,00
6	19	71.1.1.3 General		0,00	1,00
7	39	71.1.2 Civil Aviation Regulations		0,00	1,00
8	173	71.1.2 Civil Aviation Regulations		0,00	1,00
9	61	71.1.2.1 Civil Aviation Regulations		0,00	1,00
10	31	71.1.2.3 Civil Aviation Regulations		0,00	1,00
11	76	71.1.2.6 Civil Aviation Regulations		0,00	1,00
12	167	71.1.3.2 Transoceanic and polar flight		0,00	1,00
13	29	71.1.3.3 MNPS Airspace		0,00	1,00
14	82	71.1.3.3 MNPS Airspace		0,00	1,00
15	126	71.2.1 Operations Manual		0,00	1,00
16	100	71.2.1 Operations Manual		0,00	1,00
17	90	71.2.1 Operations Manual		0,00	1,00
18	42	71.2.1 Operations Manual		0,00	1,00
19	150	71.2.1.1 Operating procedures		0,00	1,00
20	20	71.2.1.1 Operating procedures		0,00	1,00
21	145	71.2.1.1 Operating procedures		0,00	1,00
22	28	71.2.1.1 Operating procedures		0,00	1,00
23	84	71.2.1.1 Operating procedures		0,00	1,00
24	140	71.2.2.1 On ground de-/anti-icing		0,00	1,00
25	163	71.2.2.1 On ground de-/anti-icing		0,00	1,00
26	119	71.2.5 Fire/smoke		0,00	1,00
27	89	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00
28	117	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
29	37	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
30	50	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
31	11	71.2.7	Wind shear and microburst	0,00	1,00
32	15	71.2.8.1	Cause	0,00	1,00
33	12	71.2.8.1	Cause	0,00	1,00
34	38	71.2.8.2	List of relevant parameters	0,00	1,00
35	79	71.2.9	Security (unlawful events)	0,00	1,00
36	58	71.2.9.4	Bomb on board	0,00	1,00
37	159	71.2.9.4	Bomb on board	0,00	1,00
38	33	71.2.11.2	Requirements	0,00	1,00
39	142	71.2.13	Contaminated runways	0,00	1,00
40	18	71.2.13.1	Kinds of contamination	0,00	1,00
Total:0%				0,00	40,00

Attachment 2: List of result by topic

Licence

Date: 02.08.2014

Examinee: Okeng, Japheth

Location: Uganda Civil Aviation Authority

Your Result: 0,00 from 40,00 Points (0,00 %)

Topics	Ammount of Questions	Points achieved	Maximum Points	Percent
71. OPERATIONAL PROCEDURES	40	0,00	40,00	0,00
71.1. GENERAL REQUIREMENTS	10	0,00	10,00	0,00
71.2. SPECIAL OPERATIONAL PROCEDURES	26	0,00	26,00	0,00
Total	40	0,00	40,00	0,00

1

What minimum aircraft equipment is required for operation within Class C airspace?

- ☐ Two-way communications.
- ☐ Transponder and DME.
- ☒ Two-way communications and transponder.

2

How does the wake turbulence vortex circulate around each wingtip?

- ☐ Inward, upward, and counterclockwise.
- ☒ Outward, upward, and around each tip.
- ☐ Inward, upward, and around each tip.

3

When diverting to an alternate airport because of an emergency, pilots should

- ☐ complete all plotting, measuring, and computations involved before diverting.
- ☐ rely upon radio as the primary method of navigation.
- ☒ apply rule-of-thumb computations, estimates, and other appropriate shortcuts to divert to the new course as soon as possible.

4

If during a VFR practice instrument approach, Radar Approach Control assigns an altitude or heading that will cause you to enter the clouds, what action should be taken?

- ☒ **Avoid the clouds and inform ATC that altitude/heading will not permit VFR.**
- ☐ **Enter the clouds, since ATC authorization for practice approaches is considered an IFR clearance.**
- ☐ **Abandon the approach.**

5

According to Annex 6, 'RNP type' is defined as a containment value expressed as a distance in ... (i) ... from the intended position within which flights would be for at least ... (ii) ... of the total flying time.

☐ (i) nautical miles
(ii) 90%

☐ (i) kilometers
(ii) 90%

☐ (i) kilometers
(ii) 95%

☒ (i) nautical miles
(ii) 95%

6

During a night flight, an observer located in the cockpit, seeing an aircraft coming from front right on approximate opposite parallel track, will first see the:

- ☐ red light
- ☐ red and white flashing light
- ☒ green light
- ☐ white light

7

An operator must ensure that, for the duration of each flight, be kept on the ground a copy of the :

- ☒ operation flight plan.
- ☐ flight plan processing.
- ☐ ATC (Air Traffic Control) flight plan.
- ☐ flight route sheet.

8

An airplane operated by a commercial operator flying over uninhabited terrain must carry which emergency equipment?

- ☐ A signal mirror and colored smoke flares.
- ☒ An approved survival-type emergency locator transmitter.
- ☐ Survival kit for each passenger.

9

AOC regulations applies to:

- ☐ aeroplanes proceeding from EAC states or flying over them.
- ☐ the operation by an EAC state member of any civil aeroplane.
- ☒ the operation by an EAC state member of any civil commercial transport aeroplane.
- ☐ aeroplanes used by police, customs and defence departments.

10

According to Annex 6, what is the definition of an Air Operator Certificate?

- ☒ A certificate authorising an operator to carry out specified commercial air transport operations.
- ☐ A certificate the crew will present to immigration officers, stating that all passengers on board fulfil the visa requirements needed.
- ☐ A certificate automatically authorising an operator to carry out domestic air services in any ICAO contracting State.
- ☐ A certificate needed to carry out specified commercial international air transport operations, but not for domestic commercial flights.

11

According to civil aviation regulations, an aeroplane whose maximum approved passenger seating configuration is 10 seats must be equipped with:

- ☐ three hand fire-extinguishers in the passenger compartment.
- ☐ one hand fire-extinguisher on the flight deck and two hand fire-extinguishers in the passenger compartment.
- ☒ one hand fire-extinguisher on the flight deck and one hand fire-extinguisher in the passenger compartment.
- ☐ two hand fire-extinguishers on the flight deck and two hand fire-extinguishers in the passenger compartment.

12

What emergency equipment is required for extended overwater operations?

- ☐ A portable survival emergency locator transmitter for each liferaft.
- ☒ A life jacket equipped with a survivor locator light, for each person on the airplane.
- ☐ A pyrotechnic signaling device for each life preserver.

13

In airspace where MNPS is applicable, the minimum vertical separation between FL 290 and FL 410 is:

- ☐ 500 ft
- ☐ 1 500 ft
- ☐ 2000ft
- ☒ 1 000 ft

14

An aircraft operating within MNPS Airspace is unable to continue flight in accordance with its air traffic control clearance, but is able to maintain its assigned level, and due to a total loss of communications capability, cannot obtain a revised clearance from ATC. The aircraft should offset from the assigned route by 15 NM and climb or descent 500 ft, if:

☐ above FL410

☐ at FL410

☒ below FL410

☐ at FL430

15

The Master Minimum Equipment List (M MEL) defines the equipment on which certain in-flight failures can be allowed and the conditions under which this allowance can be accepted. This M MEL is drawn up by :

- ☐ the operator and is specified in the operation manual
- ☒ the manufacturer and approved by the certification authority
- ☐ the operator from a main list drawn up by the manufacturer
- ☐ the operator and approved by the certification authority

16

Information concerning evacuation procedures can be found in the :

- ☐ journey logbook.
- ☐ operational flight plan.
- ☐ flight manual.
- ☒ operation manual.

17

The observations and studies conducted on the behavior of birds on the ground, ahead of an aircraft taking off and having reached an average speed of 135 kt, show that birds fly away :

- ☐ as soon as they hear the engines noise
- ☐ about ten seconds beforehand
- ☒ about two seconds beforehand
- ☐ from the beginning of the takeoff roll

18

During a flight, the chief steward informs the crew that a passenger is using a portable device suspected to disturb the aircraft electronic systems. The captain:

- ☒ must not authorize any person to use such a device on board.
- ☐ authorizes its use during the whole flight phase.
- ☐ authorizes its use except during take-off and landing phases.
- ☐ may authorize the use of this device, as an exception.

19

Supplemental oxygen is used to :

- ☐ protect a crew who fights a fire
- ☐ assist a passenger with breathing disorders
- ☒ provide people on board with oxygen during a cabin depressurisation
- ☐ provide with oxygen passengers who might require it, following a cabin depressurisation

20

According to civil aviation regulations in East Africa, the Minimum Equipment List of an aircraft is found in the:

☒ operations manual.

☐ flight manual.

☐ flight record.

☐ CAA OPS.

21

During a night flight, an observer located in the cockpit, seeing an aircraft coming from the front left, will first see the :

- ☒ green steady light
- ☐ white steady light
- ☐ red steady light
- ☐ green flashing light

22

An aircraft is flying in heavy rain. To carry out a safe approach, it is necessary to :

- ☐ carry out an approach with flaps up, in order to avoid exposing too much lifting surface to the rain
- ☐ reduce the approach speed, because the runway may be very slippery on landing
- ☒ increase its approach speed, because the rain affects the lift by deteriorating the boundary layer
- ☐ maintain the normal approach speed up to landing

23

The Minimum Equipment List (MEL) shall be established by:

- ☐ the manufacturer and approved by the Authority.
- ☐ the Civil Aviation Authority of all the European States.
- ☒ the operator and approved by the Authority.
- ☐ the respective Authority of the operator.

24

An aircraft having undergone an anti-icing procedure and having exceeded the protection time of the anti-icing fluid:

- ☒ must undergo a de-icing procedure before a new application of anti-icing fluid for take-off.
- ☐ must only undergo a new anti-icing procedure for take-off.
- ☐ must only undergo a de-icing procedure for take-off.
- ☐ need not to undergo a new anti-icing procedure for take-off.

25

An aircraft having undergone an anti-icing procedure must be anti-icing fluid free at the latest when :

- ☐ it is implementing its own anti-icing devices.
- ☒ it is rotating (before taking-off).
- ☐ releasing the brakes in order to take-off.
- ☐ leaving the icing zone.

26

The "NO SMOKING" sign must be illuminated :

- ☒ when oxygen is being supplied in the cabin.
- ☐ in each cabin section if oxygen is being carried.
- ☐ during take off and landing.
- ☐ during climb and descent.

27

In case of a fire due to the heating of the brakes, you fight the fire using:

1. a dry powder fire extinguisher

2. a water spray atomizer

3. a water fire-extinguisher

4. a CO2 fire-extinguisher to the maximum

The combination regrouping all the correct statements is:

☐ 1, 4

☐ 2, 3, 4

☐ 3, 4

☒ 1, 2

28

To extinguish a fire in the cockpit, you use:

- 1. a water fire-extinguisher*
- 2. a powder or chemical fire-extinguisher*
- 3. a halon fire-extinguisher*
- 4. a CO2 fire-extinguisher*

☐ 1, 2, 3, 4

☐ 2, 3, 4

☐ 1, 2

☒ 3, 4

29

Beneath fire extinguishers the following equipment for fire fighting is on board:

- ☒ crash axes or crowbars.
- ☐ a hydraulic winch and a big box of tools.
- ☐ a big bunch of fire extinguishing blankets.
- ☐ water and all type of beverage.

30

An aircraft having undertaken an anti-icing procedure and having exceeded the holdover time of the anti-icing fluid:

- ☒ **must undertake a de-icing procedure before a new application of anti-icing fluid before take-off.**
- ☐ **does not require a new anti-icing procedure before take-off.**
- ☐ **must only undertake a de-icing procedure before take-off.**
- ☐ **must only undertake a new anti-icing procedure before take-off.**

31

One of the main characteristics of windshear is that it :

- ☒ can occur at any altitude in both the vertical and horizontal planes
- ☐ can occur at any altitude and only in the horizontal plane
- ☐ occurs only at a low altitude (2000 ft) and never in the horizontal plane
- ☐ occurs only at a low altitude (2000 ft) and never in the vertical plane

32

Aeroplane wake turbulence during take off starts when:

- ☐ the take off roll commences.
- ☐ out of ground effect.
- ☐ slats and flaps are extended only.
- ☒ the nose wheel lifts off the runway.

33

The wake turbulence caused by an aircraft is mainly the result of:

1. An aerodynamic effect (wing tip vortices).
2. The engines action (propellers rotation or engine gas exhausts).
3. The importance of the drag devices (size of the landing gear, of the flaps, etc.).

The combination regrouping all the correct statements is:

☒ 1.

☐ 2 and 3.

☐ 1, 2 and 3.

☐ 3.

34

The greatest wake turbulence occurs when the generating aircraft is:

- ☐ Small, light, at low speed in clean configuration
- ☐ Large, heavy, at maximum speed in full flaps configuration
- ☒ Large, heavy, at low speed in clean configuration
- ☐ Small, light, at maximum speed in full flaps configuration

35

What transponder code should be used to provide recognition of an aircraft which is being subjected to unlawful interference :

☐ code 7700

☒ code 7500

☐ code 7600

☐ code 2000

36

In case of a serious threat based on the presence of a bomb on board a pressurized aircraft and disregarding any fuel considerations:

- ☐ you climb to the maximum flight level which does not need the use of pressurization.
- ☐ you carry out an emergency descent to reach the safety altitude.
- ☒ you descend to the flight level corresponding to the indicated cabin altitude or the safety altitude if higher and take preventive steps by putting yourself in a landing approach configuration.
- ☐ you go down to the level corresponding to the indicated cabin altitude and keep the aircraft in a clean configuration until the final approach.

37

In case of a serious threat based on the presence of a bomb on board a pressurized aircraft and disregarding any fuel considerations:

- ☐ you climb to the maximum flight level which does not need the use of pressurization.
- ☒ you descend to the flight level corresponding to the indicated cabin altitude or the safety altitude if higher and take preventive steps by putting yourself in a landing approach configuration.
- ☐ you carry out an emergency descent to reach the safety altitude.
- ☐ you go down to the level corresponding to the indicated cabin altitude and keep the airplane in a clean configuration until the final approach.

38

According to Civil aviation authority, if a fuel jettisoning system is required, it must be capable of jettisoning enough fuel within:

☐ 30 minutes

☐ 60 minutes

☐ 45 minutes

☒ 15 minutes

39

For an airplane with a tyre pressure of 12 bars, there is a risk of dynamic hydroplaning as soon as the :

1- water height is equal to the depth of the tyre grooves.

2- speed is greater than 114 kt.

3- water height is equal to the half of the depth of the tyre grooves.

4- speed is greater than 83 kt.

The combination regrouping all the correct statements is :

☐ 1 and 4.

☐ 3 and 4.

☒ 1 and 2.

☐ 2 and 3.

40

In the civil aviation regulation, a runway is considered wet when:

1. it is covered with a quantity of water or loose or slushy snow less than or equal to the equivalent of 3 mm of water.
2. the amount of surface moisture is sufficient to modify its colour but does not give it a shiny appearance.
3. the amount of surface moisture is sufficient to make it reflective, but does not create large stagnant sheets of water.
4. it bears stagnant sheets of water.

The combination regrouping all the correct statements is:

☐ 4

☒ 1, 3

☐ 1, 2

☐ 1, 2, 3