

Online Examination Report

Date:	28.07.2014
Attempts:	1
Examinee:	Eguny 2, Robert
Date of birth:	5/8/1991
Subject:	070-Operational procedures
Result:	0 %
Time used:	00:00:13 (HH:MM:SS)

Attachments

1. List of result by question
2. List of result by topic
3. Detailed question result report

Attachment 1: List of result by question

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
1	185	71. OPERATIONAL PROCEDURES		0,00	1,00
2	191	71. OPERATIONAL PROCEDURES		0,00	1,00
3	25	71.1.1 ICAO Annex 6		0,00	1,00
4	56	71.1.1 ICAO Annex 6		0,00	1,00
5	59	71.1.1.1 Definitions		0,00	1,00
6	118	71.1.1.3 General		0,00	1,00
7	173	71.1.2 Civil Aviation Regulations		0,00	1,00
8	39	71.1.2 Civil Aviation Regulations		0,00	1,00
9	61	71.1.2.1 Civil Aviation Regulations		0,00	1,00
10	31	71.1.2.3 Civil Aviation Regulations		0,00	1,00
11	69	71.1.2.5 Civil Aviation Regulations		0,00	1,00
12	24	71.1.2.6 Civil Aviation Regulations		0,00	1,00
13	22	71.1.2.6 Civil Aviation Regulations		0,00	1,00
14	52	71.1.3.3 MNPS Airspace		0,00	1,00
15	53	71.1.3.3 MNPS Airspace		0,00	1,00
16	29	71.1.3.3 MNPS Airspace		0,00	1,00
17	139	71.2.1.1 Operating procedures		0,00	1,00
18	145	71.2.1.1 Operating procedures		0,00	1,00
19	135	71.2.1.1 Operating procedures		0,00	1,00
20	150	71.2.1.1 Operating procedures		0,00	1,00
21	85	71.2.1.1 Operating procedures		0,00	1,00
22	160	71.2.1.1 Operating procedures		0,00	1,00
23	34	71.2.1.1 Operating procedures		0,00	1,00
24	3	71.2.2 Icing conditions		0,00	1,00
25	114	71.2.2.1 On ground de-/anti-icing		0,00	1,00
26	140	71.2.2.1 On ground de-/anti-icing		0,00	1,00
27	119	71.2.5 Fire/smoke		0,00	1,00
28	102	71.2.5.3 Fire in the cabin, cockpit, cargo comp		0,00	1,00

CQB Number	Internal Number	Syllabus reference	Chapter	Points	Max. Points
29	89	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
30	50	71.2.5.3	Fire in the cabin, cockpit, cargo comp	0,00	1,00
31	16	71.2.5.6	Types of extinguishers	0,00	1,00
32	134	71.2.5.6	Types of extinguishers	0,00	1,00
33	5	71.2.5.6	Types of extinguishers	0,00	1,00
34	12	71.2.8.1	Cause	0,00	1,00
35	38	71.2.8.2	List of relevant parameters	0,00	1,00
36	108	71.2.9	Security (unlawful events)	0,00	1,00
37	165	71.2.12	Transport of dangerous goods	0,00	1,00
38	146	71.2.12	Transport of dangerous goods	0,00	1,00
39	154	71.2.13	Contaminated runways	0,00	1,00
40	142	71.2.13	Contaminated runways	0,00	1,00
Total:0%				0,00	40,00

Attachment 2: List of result by topic

Licence

Date: 28.07.2014

Examinee: Eguny 2, Robert

Location: Uganda Civil Aviation Authority

Your Result: 0,00 from 40,00 Points (0,00 %)

Topics	Ammount of Questions	Points achieved	Maximum Points	Percent
71. OPERATIONAL PROCEDURES	40	0,00	40,00	0,00
71.1. GENERAL REQUIREMENTS	14	0,00	14,00	0,00
71.2. SPECIAL OPERATIONAL PROCEDURES	24	0,00	24,00	0,00
Total	40	0,00	40,00	0,00

1

How does the wake turbulence vortex circulate around each wingtip?

- ☐ Inward, upward, and counterclockwise.
- ☐ Inward, upward, and around each tip.
- ☒ Outward, upward, and around each tip.

2

When landing behind a large jet aircraft, at which point on the runway should you plan to land?

- ☐ At least 1,000 feet beyond the jet's touchdown point.
- ☒ Beyond the jet's touchdown point.
- ☐ If any crosswind, land on the windward side of the runway and prior to the jet's touchdown point.

3

The master minimum equipment list (M MEL) is established by:

- ☐ the manufacturer of the aircraft, but need not to be accepted by the authority
- ☒ the manufacturer of the aircraft, and accepted by the authority
- ☐ the operator of the aircraft, and accepted by the authority
- ☐ the operator of the aircraft, and accepted by the manufacturer

4

Among the EAC states, the CAA-OPS of Aircraft is based on :

- ☐ A CAA guideline
- ☐ The air transport rules
- ☒ ICAO Annex 6
- ☐ The Civil Aviation Requirements (CAA)

5

According to Annex 6, 'RNP type' is defined as a containment value expressed as a distance in ... (i) ... from the intended position within which flights would be for at least ... (ii) ... of the total flying time.

- ☒ (i) nautical miles
(ii) 95%
- ☐ (i) kilometers
(ii) 95%
- ☐ (i) kilometers
(ii) 90%
- ☐ (i) nautical miles
(ii) 90%

6

90 % of bird strikes occur :

- ☒ under 500 m
- ☐ between 500 and 1 500 m
- ☐ between 500 and 1 000 m
- ☐ above 1 000 m

7

An airplane operated by a commercial operator flying over uninhabited terrain must carry which emergency equipment?

- ☒ An approved survival-type emergency locator transmitter.
- ☐ Survival kit for each passenger.
- ☐ A signal mirror and colored smoke flares.

8

An operator must ensure that, for the duration of each flight, be kept on the ground a copy of the :

- ☐ flight route sheet.
- ☐ ATC (Air Traffic Control) flight plan.
- ☐ flight plan processing.
- ☒ operation flight plan.

9

AOC regulations applies to:

- ☐ the operation by an EAC state member of any civil aeroplane.
- ☒ the operation by an EAC state member of any civil commercial transport aeroplane.
- ☐ aeroplanes used by police, customs and defence departments.
- ☐ aeroplanes proceeding from EAC states or flying over them.

10

According to Annex 6, what is the definition of an Air Operator Certificate?

- ☐ A certificate the crew will present to immigration officers, stating that all passengers on board fulfil the visa requirements needed.
- ☐ A certificate needed to carry out specified commercial international air transport operations, but not for domestic commercial flights.
- ☒ A certificate authorising an operator to carry out specified commercial air transport operations.
- ☐ A certificate automatically authorising an operator to carry out domestic air services in any ICAO contracting State.

11

In accordance to the EAC states' Civil aviation regulations (Aerodrome Operating Minima), for a Category III B approach, the RVR shall not be less than:

☐ 150 m

☐ 50 m

☒ 75 m

☐ 100 m

12

In accordance with civil aviation regulations, for aeroplanes intended to be operated at pressure altitude of 39000 ft, the total number of oxygen dispensing units and outlets shall exceed:

- ☐ the number of seats.
- ☐ the number of passengers by at least 10%.
- ☐ the number of passengers.
- ☒ the number of seats by at least 10%.

13

In accordance with civil aviation regulations, an aeroplane whose maximum approved passenger seating configuration is greater than 600 seats must be equipped with at least:

- ☒ 8 hand fire-extinguishers conveniently located in the passenger compartment.
- ☐ 7 hand fire-extinguishers conveniently located in the passenger compartment.
- ☐ 6 hand fire-extinguishers conveniently located in the passenger compartment.
- ☐ 9 hand fire-extinguishers conveniently located in the passenger compartment.

14

In the event of communication failure in an Minimum Navigation Performance Specification(MNPS) airspace, the pilot must:

- ☐ join one of the so-called "special" routes.
- ☐ return to the flight plan route if it is different from the last oceanic clearance received and acknowledged.
- ☒ continue the flight in compliance with the last oceanic clearance received and acknowledged.
- ☐ change the flight level in accordance with predetermined instructions.

15

In Minimum Navigation Performance Specification (MNPS) airspace, the speed reference for turbo-jet aircraft is the:

- ☒ Mach number.
- ☐ true airspeed.
- ☐ indicated airspeed.
- ☐ ground speed.

16

In airspace where MNPS is applicable, the minimum vertical separation between FL 290 and FL 410 is:

☒ 1 000 ft

☐ 2000ft

☐ 1 500 ft

☐ 500 ft

17

A category B aircraft can carry out an indirect approach followed by a visual maneuver only if the horizontal visibility is higher than or equal to:

☐ 3600 m

☒ 1600 m

☐ 1500 m

☐ 2400 m

18

During a night flight, an observer located in the cockpit, seeing an aircraft coming from the front left, will first see the :

- ☐ green flashing light
- ☐ red steady light
- ☐ white steady light
- ☒ green steady light

19

Selecting an alternate aerodrome the runway of this facility must be sufficiently long to allow a full stop landing from 50 ft above the threshold (jet type aircraft, dry runway) within:

- ☐ 80% of the landing distance available.
- ☐ 70% of the landing distance available.
- ☒ 60% of the landing distance available.
- ☐ 50% of the landing distance available.

20

Supplemental oxygen is used to :

- ☐ assist a passenger with breathing disorders
- ☐ provide with oxygen passengers who might require it, following a cabin depressurisation
- ☐ protect a crew who fights a fire
- ☒ provide people on board with oxygen during a cabin depressurisation

21

The Master Minimum Equipment List (M MEL), if this exists, is established by:

- ☐ the operator of the aircraft, and accepted by the authority
- ☐ the operator of the aircraft, and accepted by the manufacturer
- ☒ the manufacturer of the aircraft, and accepted by the authority
- ☐ the manufacturer of the aircraft, but need not to be accepted by the authority

22

During an explosive decompression at flight level 370 (FL 370), your first action will be :

- ☐ to comfort your passengers
- ☐ to set the transponder to 7700
- ☒ to put on the oxygen mask
- ☐ to warn the ATC

23

Flight crew members on the flight deck shall keep their safety belt fastened:

- ☐ while at their station.
- ☐ only during take off and landing and whenever necessary by the commander in the interest of safety.
- ☐ from take off to landing.
- ☒ only during take off and landing.

24

The maximum validity of a SNOWTAM is :

☒ 24 hours

☐ 6 hours

☐ 12 hours

☐ 3 hours

25

The anti-icing fluid protecting film can wear off and reduce considerably the protection time:

- ☐ when the outside temperature is close to 0 °C.
- ☐ when the airplane is into the wind.
- ☒ during strong winds or as a result of the other aircraft engines jet wash.
- ☐ when the temperature of the airplane skin is close to 0 °C.

26

An aircraft having undergone an anti-icing procedure and having exceeded the protection time of the anti-icing fluid:

- ☐ need not to undergo a new anti-icing procedure for take-off.
- ☒ must undergo a de-icing procedure before a new application of anti-icing fluid for take-off.
- ☐ must only undergo a de-icing procedure for take-off.
- ☐ must only undergo a new anti-icing procedure for take-off.

27

The "NO SMOKING" sign must be illuminated :

- ☐ in each cabin section if oxygen is being carried.
- ☐ during climb and descent.
- ☒ when oxygen is being supplied in the cabin.
- ☐ during take off and landing.

28

If smoke appears in the air conditioning, the first action to take is to :

- ☐ Cut off all air conditioning units.
- ☐ Begin an emergency descent.
- ☒ Put on the mask and goggles.
- ☐ Determine which system is causing the smoke.

29

In case of a fire due to the heating of the brakes, you fight the fire using:

1. a dry powder fire extinguisher

2. a water spray atomizer

3. a water fire-extinguisher

4. a CO2 fire-extinguisher to the maximum

The combination regrouping all the correct statements is:

☐ 2, 3, 4

☐ 3, 4

☒ 1, 2

☐ 1, 4

30

An aircraft having undertaken an anti-icing procedure and having exceeded the holdover time of the anti-icing fluid:

- ☐ does not require a new anti-icing procedure before take-off.
- ☐ must only undertake a new anti-icing procedure before take-off.
- ☒ must undertake a de-icing procedure before a new application of anti-icing fluid before take-off.
- ☐ must only undertake a de-icing procedure before take-off.

31

You will use a CO2 fire-extinguisher for :

- 1. a paper fire*
- 2. a plastic fire*
- 3. a hydrocarbon fire*
- 4. an electrical fire*

The combination regrouping all the correct statements is:

☒ 1,2,3,4

☐ 3,4

☐ 2,3

☐ 1,2,3

32

The fire extinguisher types which may be used on class B fires are:

- 1 - H₂O,
- 2 - CO₂,
- 3 - dry-chemical,
- 4 - halogen

☐ 2

☒ 2 - 3 - 4

☐ 3 - 4

☐ 1 - 2 - 3 - 4,

33

You will use a powder fire-extinguisher for:

- 1. a paper fire**
- 2. a plastic fire**
- 3. a hydrocarbon fire**
- 4. an electrical fire**

The combination regrouping all the correct statements is:

☐ **1, 2, 3**

☐ **1, 4**

☒ **1, 2, 3, 4**

☐ **2, 3**

34

The wake turbulence caused by an aircraft is mainly the result of:

1. An aerodynamic effect (wing tip vortices).
2. The engines action (propellers rotation or engine gas exhausts).
3. The importance of the drag devices (size of the landing gear, of the flaps, etc.).

The combination regrouping all the correct statements is:

☐ 2 and 3.

☐ 3.

☒ 1.

☐ 1, 2 and 3.

35

The greatest wake turbulence occurs when the generating aircraft is:

- ☐ Large, heavy, at maximum speed in full flaps configuration
- ☐ Small, light, at maximum speed in full flaps configuration
- ☒ Large, heavy, at low speed in clean configuration
- ☐ Small, light, at low speed in clean configuration

36

The flight deck door should be capable of being :

- ☐ directly locked from outside the compartment
- ☐ remotely locked from either inside or outside the compartment
- ☒ locked from within the compartment
- ☐ remotely locked by cabin crew operation from outside the compartment

37

Who makes sure that the air transportation of an item of dangerous goods is not prohibited?

- ☐ It is not specified.
- ☐ The captain, always using the list of prohibited aircraft items.
- ☐ The operator.
- ☒ The shipper when completing the shipper's declaration for dangerous goods.

38

The dangerous goods transport document, if required, shall be drawn up by :

- ☒ the shipper.
- ☐ the captain.
- ☐ the operator.
- ☐ the handling agent.

39

According to the civil aviation regulations a runway is considered damp when:

- ☐ surface moisture gives it a shiny appearance.
- ☐ it is covered with a film of water of less than 1 mm.
- ☒ its surface is not dry, and when surface moisture does not give it a shiny appearance.
- ☐ it is covered with a film of water of less than 3 mm.

40

For an airplane with a tyre pressure of 12 bars, there is a risk of dynamic hydroplaning as soon as the :

1- water height is equal to the depth of the tyre grooves.

2- speed is greater than 114 kt.

3- water height is equal to the half of the depth of the tyre grooves.

4- speed is greater than 83 kt.

The combination regrouping all the correct statements is :

☐ 3 and 4.

☐ 2 and 3.

☐ 1 and 4.

☒ 1 and 2.