

0001. A braking action given by ATS of 0.25 and below is ;

- a) Medium.
- b) Good.
- c) Medium/poor.
- d) Poor.

Answer ;

d) Poor.

0002. A checklist of AIP supplements currently in force shall be issued at intervals of ;

- a) not more than three months.
- b) not more than one month.
- c) not more than 2 months.
- d) not more than 28 days.

Answer ;

b) not more than one month.

0003. A checklist of NOTAM currently in force shall be issued at the AFTN at intervals of ;

- a) not more than 28 days.
- b) not more than 15 days.
- c) not more than one month.
- d) not more than 10 days.

Answer ;

c) not more than one month.

0004. A circling approach is ;

- a) a flight manoeuvre to be performed only under radar vectoring.
- b) a visual manoeuvre to be conducted only in IMC.
- c) a contact flight manoeuvre.
- d) a visual flight manoeuvre keeping the runway in sight.

Answer ;

d) a visual flight manoeuvre keeping the runway in sight.

0005. A Control Zone shall extend laterally to at least ;

- a) 10 miles from the centre of the aerodrome or aerodromes concerned in the direction from which approaches may be made.
- b) 20 miles from the centre of the aerodrome or aerodromes concerned in the direction from which approaches may be made.
- c) 15 miles from the centre of the aerodrome or aerodromes concerned in the direction from which approaches may be made.
- d) 5 nautical miles from the centre of the aerodrome or aerodromes concerned in the direction from which approaches may be made.

Answer ;

d) 5 nautical miles from the centre of the aerodrome or aerodromes concerned in the direction from which approaches may be made.

0006. A controlled airspace extending upwards from a specified limit above the earth is ;

- a) Control zone.
- b) Flight Information Region.
- c) Advisory airspace.
- d) Control area.

Answer ;

d) Control area.

0007. A controlled airspace extending upwards from the surface of the earth to a specified upper limit is ;

- a) Air traffic zone.
- b) Advisory airspace.
- c) Control area.
- d) Control zone.

Answer ;

d) Control zone.

0008. A controlled flight is requested to inform the appropriate ATC unit whenever the average True Air Speed at cruising level varies or is expected to vary from that given in the flight plan by plus or minus ;

- a) 5%.
- b) 2%.
- c) 3%.
- d) 10 %.

Answer ;

- a) 5%.
-

0009. A double white cross displayed horizontally in the signal area means ;

- a) the aerodrome is being used by gliders and that glider flights are being performed.
- b) need special precautions while approaching for landing.
- c) an area unit for the movement of aircraft.
- d) special precautions must be observed due to bad state of the taxiways.

Answer ;

- a) the aerodrome is being used by gliders and that glider flights are being performed.
-

0010. A flashing red light from control tower during an approach to land means ;

- a) continue circling and wait for further instructions.
- b) the airport is unsafe , do not land.
- c) the airport is temporarily closed , continue circling.
- d) give way to other aircraft in emergency.

Answer ;

- b) the airport is unsafe , do not land.
-

0011. A lower limit of a Control Area shall be established at a height above the ground level or water of not less than ;

- a) 500 metres.
- b) 300 metres.
- c) 200 metres.
- d) 150 metres.

Answer ;

- c) 200 metres.
-

0012. A minimum radar separation shall be provided until aircraft are established inbound on the ILS localizer course and/or MLS final approach track. This minimum is , when independent parallel approaches are being conducted ;

- a) 2.0 NM.
- b) 1.0 NM.
- c) 5.0 NM.
- d) 3.0 NM.

Answer ;

- d) 3.0 NM.
-

0013. A minimum vertical separation shall be provided until aircraft are established inbound on the ILS localizer course and/or MLS final approach track. This minimum is , when independent parallel approaches are being conducted ;

- a) 200 m (660 ft).
- b) 150 m (500 ft).
- c) 100 m (330 ft).
- d) 300 m (1000 ft).

Answer ;

- d) 300 m (1000 ft).
-

0014. A notice containing information concerning flight safety , air navigation , technical , administration or legislative matters and originated at the AIS of a state is called ;

- a) Aeronautical Information Circular (AIC).
- b) NOTAM.
- c) AIRAC.
- d) Aeronautical Information Publication (AIP).

Answer ;

- a) Aeronautical Information Circular (AIC).
-

0015. A notice providing information on Rules of the Air , Air Traffic Services and Air Navigation Procedures and distributed in advance of its effective date is ;

- a) A NOTAM RAC.
- b) An ATS NOTAM.
- c) An Advisory NOTAM.
- d) An AIRAC.

Answer ;

- d) An AIRAC.

0016. A radio communications , “Distress” differs from “Urgency” because in the first case ;

- a) there is a serious and imminent danger requiring immediate assistance.
- b) the aeroplane will not be able to reach a suitable aerodrome.
- c) the aeroplane has suffered damages which impair its fitness to fly.
- d) the aeroplane or a passenger's safety require the flight immediately interrupted.

Answer ;

- a) there is a serious and imminent danger requiring immediate assistance.

0017. A red flare addressed to a flying aircraft means ;

- a) Not with standing any previous instructions , do not land for the time being.
- b) Dangerous airfield. Do not land.
- c) Come back and land.
- d) Give way to another aircraft and hold the circuit.

Answer ;

- a) Not with standing any previous instructions , do not land for the time being.

0018. A “RNAV” distance based separation minimum may be used at the time the level is crossed , provided that each aircraft reports its distance to or from the same “on track” way-point. This minimum is ;

- a) 20 NM.
- b) 50 NM.
- c) 80 NM.
- d) 60 NM.

Answer ;

- c) 80 NM.

0019. A separation minimum shall be applied between a light or MEDIUM aircraft and a HEAVY aircraft and between a LIGHT aircraft and a MEDIUM aircraft when the heavier aircraft is making a low or missed approach and the lighter aircraft is landing on the same runway in the opposite direction or on a parallel opposite direction runway separated by ;

- a) less than 730 m.
- b) 760 m.
- c) less than 760 m.
- d) 730 m.

Answer ;

- c) less than 760 m

0020. A separation minimum shall be applied between a light or MEDIUM aircraft and a HEAVY aircraft and between a LIGHT aircraft and a MEDIUM aircraft when the heavier aircraft is making a low or missed approach and the lighter aircraft is utilizing an opposite direction runway for take off , this minimum is ;

- a) 1 minute.
- b) 2 minutes.
- c) 5 minutes.
- d) 3 minutes.

Answer ;

- b) 2 minutes.

0021. A signalman will ask the pilot to apply parking brakes by the following signals ;

- a) Arms down , palms facing inwards , moving arms from extended position inwards.
- b) Crossing arms extended above his head.
- c) Horizontally moving his hands , fingers extended, palms toward ground.
- d) Raise arm and hand , with fingers extended , horizontally in front of body , then clench fist.

Answer ;

- d) Raise arm and hand , with fingers extended , horizontally in front of body , then clench fist.
-

0022. A so called "Visual Approach" can be performed ;
- a) during IFR flights , if there is permanent sight on the movement area and the underlying ground.
 - b) during IFR flights , if the cloud base is 1000 ft more than the appropriate DA or MDA for that procedure.
 - c) as in above , but in addition there should be a visibility of 5.5 km or more.
 - d) during IFR and VFR flights in VMC.

Answer ;

- a) during IFR flights , if there is permanent sight on the movement area and the underlying ground.
-

0023. A Special Air Report comprises a number of sections. In section I the pilot fills in ;
- a) a position report , including aircraft identification , height , position and time.
 - b) flight identification and weather noted.
 - c) weather noted.
 - d) urgent messages.

Answer ;

- a) a position report , including aircraft identification , height , position and time.
-

0024. A State shall provide assistance to an aircraft subjected to an act of unlawful seizure. This assistance includes ;
- a) provision of navigation aids , air traffic services , permission to land and refuelling.
 - b) provision of navigation aids , air traffic services and permission to land.
 - c) only permission to land.
 - d) provision of navigation aids , air traffic services , permission to land and catering for passengers.

Answer ;

- b) provision of navigation aids , air traffic services and permission to land.
-

0025. A State shall take adequate measures for the safety of passengers and crew of an aircraft which is subjected to an act of unlawful interference ;
- a) until their journey can be continued.
 - b) if is requested by an individual passenger.
 - c) and arrange for them to return to their country of origin.
 - d) during a period of investigation.

Answer ;

- a) until their journey can be continued.
-

0026. A strayed aircraft is ;
- a) an aircraft which has deviated significantly from its intended track or which reports that it is lost.
 - b) only that aircraft which reports that it is lost.
 - c) only that aircraft which has deviated significantly its intended track.
 - d) an aircraft in a given area but whose identity has not been established.

Answer ;

- a) an aircraft which has deviated significantly from its intended track or which reports that it is lost.
-

0027. A VFR flight constitutes essential traffic to other VFR flights , when operating in controlled airspace classified as ;
- a) B.
 - b) B , C and D.
 - c) B and C.
 - d) B , C , D and E.

Answer ;

- a) B.
-

0028. A VFR flight when flying inside an ATS airspace classified as B has to maintain the following minima of flight visibility and distance from clouds ;
- a) 8 km below 3050 m (10.000 ft) AMSL , 1500 m horizontal and 300 m vertical from clouds.
 - b) 5 km below 3050 m (10.000 ft) AMSL and clear of clouds.
 - c) 5 km below 3050 m (10.000 ft) AMSL , 1500 m horizontal and 300 m vertical from clouds.
 - d) 5 km visibility , 1500 m horizontal and 300 m vertical from clouds.

Answer ;

- c) 5 km below 3050 m (10.000 ft) AMSL , 1500 m horizontal and 300 m vertical from clouds.
-

0029. A VFR flight when flying inside an ATS airspace classified as C has to maintain the following minima of flight visibility and distance from clouds ;
- a) 8 km at or above 3050 m (10.000 ft) AMSL , 1500 m horizontal and 300 m vertical from clouds.
 - b) 8 km at or above 3050 m (10.000 ft) AMSL , and clear of clouds.
 - c) 5 NM at or above 3050 m (10.000 ft) AMSL , 1500 m horizontal and 300 m vertical from clouds.
 - d) 5km at or above 3050 m (10.000 ft) AMSL ,1500 m horizontal and 300 m vertical from clouds.

Answer ;

- a) 8 km at or above 3050 m (10.000 ft) AMSL , 1500 m horizontal and 300 m vertical from clouds.

0030. Abbreviations (Doc 8168)
In Pans-Ops , the abbreviation DER stands for ;
- a) Distance error in routing.
 - b) Direct entry route.
 - c) Displaced end of runway.
 - d) **Departure end of runway.**

Answer ;
d) **Departure end of runway.**

0031. Abbreviations (Doc 8168)
What does the abbreviation OIS mean ?
- a) Obstacle in surface.
 - b) Obstacle identification slope.
 - c) **Obstacle identification surface.**
 - d) Obstruction in surface.

Answer ;
c) **Obstacle identification surface.**

0032. Accident , incident notification and reporting
After landing , while taxiing towards the apron , the landing gear of your aircraft sinks into a hole. Nobody gets injured , but the aircraft sustains structural damage. This obliges the crew to delay the departure.
- a) This is an incident and the pilot-in-command must report it to the airport authority within the next 48 hours.
 - b) Since there is no person injured and the flight is terminated , a damage report has to be made out with the services of the aerodrome in charge of the runway and taxiways for the insurance company.
 - c) This is an irregularity in the operation. The crew must inform the operator of the aerodrome and establish a report.
 - d) **This is an accident and the crew must follow the procedure relevant to this case.**

Answer ;
d) **This is an accident and the crew must follow the procedure relevant to this case.**

0033. Accident investigation
Who is responsible for the initiation of an accident investigation ?
- a) The aircraft manufacturer.
 - b) The Operators of the same aircraft type.
 - c) **The Authority of the State in which the accident took place.**
 - d) The State of design and manufacturer.

Answer ;
c) **The Authority of the State in which the accident took place.**

0034. Accident investigation - objective
The sole objective of the investigation of an accident or incident shall be the ;
- a) prevention of accidents or incidents and establish the liability.
 - b) prevention of accidents or incidents and to provide legal evidence for subsequent court cases.
 - c) **prevention of accidents or incidents.**
 - d) prevention of accidents or incidents and provide the manufacturer with investigation data for the improvement of the design.

Answer ;
c) **prevention of accidents or incidents.**

0035. According to Annex 7 , the registration mark shall be letters , numbers or a combination of letters and numbers and shall be that assigned by ;
- a) the International Civil Aviation Organisation.
 - b) the International Telecommunication Union.
 - c) **the state of registry or common mark registering authority.**
 - d) the state of registry only.

Answer ;
c) **the state of registry or common mark registering authority.**

0036. According to ICAO Annex 8 , a certificate of airworthiness shall be renewed or shall remain valid subject to the ;
- a) laws of the State in which is operated.
 - b) laws of the State of registry and operation.
 - c) **laws of the State of registry.**
 - d) requirements laid down by ICAO.

Answer ;
c) **laws of the State of registry.**

-
- 0037.** According to international agreements wind direction shall be adjusted to the local variation and given in degrees magnetic ;
- a) when the local variation exceeds 10° East or 10° West.
 - b) in upper wind forecast for areas north of lat 60° North or 60° South.
 - c) before landing and take-off.
 - d) when an aircraft on the request by a meteorological watch office (MWO) or at specified points transmits a PIREP.

Answer ;

- c) before landing and take-off.
-

- 0038.** According to JAR-FCL , a professional flight crew licence issued by a non JAA State may be rendered valid for use on aircraft registered in a JAA Member State ;

- a) at the discretion of the Authority of that Member State concerned for a period not exceeding one year , provided that the basic licence remains valid.
- b) at the discretion of the Authority of the Member State concerned for a period not exceeding the period validity of basic licence.
- c) at the discretion of the Authority of that Member State concerned for a period not exceeding one year.
- d) at the discretion of the Authority of that Member State concerned for a period not exceeding one year , provided that the basic licence remains valid.

Answer ;

- d) at the discretion of the Authority of that Member State concerned for a period not exceeding one year , provided that the basic licence remains valid.
-

- 0039.** According to JAR-FCL , an applicant for a CPL (A) who has satisfactorily followed and completed an integrated flying training course shall have completed as a pilot of aeroplanes having a certificate of airworthiness issued or accepted by a JAA Member State at least ;

- a) 150 hours of flight time.
- b) 200 hours of flight time plus 10 hours of instrument ground time.
- c) 150 hours of flight time plus 10 hours of instrument ground time.
- d) 200 hours of flight time.

Answer ;

- a) 150 hours of flight time.
-

- 0040.** According to JAR-FCL , an applicant for an IR(A) shall hold a PPL (A) including a night qualification or CPL(A) and shall have completed at least 50 hours ;

- a) instructional flight time as student-pilot-in-command of aeroplanes.
- b) cross country flight time as pilot of aeroplanes or helicopters of which at least 10 hours shall be in aeroplanes.
- c) instructional flight time as student-pilot-in-command of aeroplanes or helicopters of which at least 10 hours shall be in aeroplanes.
- d) cross country flight time as pilot-in-command in aeroplanes or helicopters of which at least 10 hours shall be in aeroplanes.

Answer ;

- d) cross country flight time as pilot-in-command in aeroplanes or helicopters of which at least 10 hours shall be in aeroplanes.
-

- 0041.** According to JAR-FCL , an applicant for ATPL (A) shall have completed as a pilot of aeroplane at least 1.500 hours of flight time , including ;

- a) 500 hours in multi-pilot operations on aeroplanes type certificated in accordance with JAR/FAR 25 or JAR/FAR 23.
- b) 500 hours in multi-pilot operations on aeroplanes type certificated in accordance with JAR/FAR 25 or JAR/FAR 23 , of which up to 150 hours may be as flight engineer.
- c) 500 hours in multi-pilot operations on aeroplanes type certificated in accordance with JAR/FAR 25 or JAR/FAR 23 , as pilot-in-command.
- d) 500 hours in multi-pilot operations on aeroplanes type certificated in accordance with JAR/FAR 25 or JAR/FAR 23 , including 200 hours of night flight as pilot-in-command or as co-pilot.

Answer ;

- a) 500 hours in multi-pilot operations on aeroplanes type certificated in accordance with JAR/FAR 25 or JAR/FAR 23.
-

0042. According to JAR-FCL , an applicant for ATPL(A) shall have demonstrated the ability to perform as pilot-in-command , the procedures and manoeuvres of an aeroplane type certificated for ;

- a) operations by pilots under training.
- b) the carriage of passengers at night.
- c) a minimum crew of two pilots under IFR.
- d) a minimum crew of two pilots plus a flight engineer.

Answer ;

- c) a minimum crew of two pilots under IFR.
-

0043. According to JAR-FCL , an examiner's authorisation is valid for ;

- a) the period of validity of the class/type rating.
- b) not more than two years.
- c) not more than three years.
- d) the period of validity of the medical certificate.

Answer ;

- c) not more than three years.
-

0044. According to JAR-FCL , an instrument rating is valid for ;

- a) indefinitely.
- b) the period of validity of the licence.
- c) one year.
- d) two years.

Answer ;

- c) one year.
-

0045. According to JAR-FCL , class rating shall be established for single pilots aeroplanes not requiring a type rating , including ;

- a) all self-sustaining gliders.
- b) all types of single-pilot , single-engine aeroplanes fitted with a turbojet engine.
- c) any other type of aeroplane if considered necessary.
- d) microlights having fixed wings and moveable aerodynamic control surfaces acting in all three dimensions.

Answer ;

- a) all self-sustaining gliders.
-

0046. According to JAR-FCL , Class 2 medical certificate for private pilots will be valid for ;

- a) 24 months until age of 40 , 12 months until age of 60 and 6 months thereafter.
- b) 24 months until age of 40 , 12 months thereafter.
- c) 60 months until age of 40 , 24 months until age of 50 , 12 months until age of 65 and 6 months thereafter.
- d) 60 months until age of 30 , 24 months until age of 40 , 12 months thereafter.

Answer ;

- c) 60 months until age of 30 , 24 months until age of 50 , 12 months until age of 65 and 6 months thereafter.
-

0047. According to JAR-FCL , establishment of separate type rating for aeroplanes will be assessed on the basis of three criteria. One of these three criteria is that the aeroplane has ;

- a) handling characteristics that require additional flying or simulator training.
- b) handling characteristics that require the use of more than one crew member.
- c) a certificate of airworthiness issued by the manufacturer.
- d) a certificate of airworthiness issued by a non-member state.

Answer ;

- a) handling characteristics that require additional flying or simulator training.
-

0048. According to JAR-FCL , licence holders do not exercise the privileges of their licences , related ratings or authorisations at any time when they are aware of any decrease in their medical fitness which might render them unable to safely exercise those privileges. They shall without undue delay seek the advice of the authority or AME when becoming aware of hospital or clinic admissions for ;

- a) more than one week.
- b) more than 12 hours.
- c) more than 12 days.
- d) any period.

Answer ;

- b) more than 12 hours.
-

0049. According to JAR-FCL , medical certificates classes are ;

- a) 1 and 2.
- b) class 1 only.
- c) 1 , 2 and 3.
- d) 1 , 2 , 3 and 4.

Answer ;

- a) 1 and 2.

0050. According to JAR-FCL , single pilot single-engine class ratings are valid for ;

- a) one year.
- b) two years up to age 40 years then one year thereafter.
- c) five years after licence issue.
- d) two years.

Answer ;

- d) two years.

0051. According to JAR-FCL , successful completion of multi-crew co-operation (MCC) training shall be required to ;

- a) obtain a professional pilot licence.
- b) revalidate any rating or licence.
- c) obtain the first class rating on multi-engine aeroplanes.
- d) obtain the first type rating on multi-pilot aeroplanes.

Answer ;

- d) obtain the first type rating on multi-pilot aeroplanes.

0052. According to JAR-FCL , the aeroplane instructor categories recognised are ;

- a) FE(A)/TRE(A)/CRE(A)/IRE(A) and SFI authorisation.
- b) FI(A) and IRI(A).
- c) FI(A)/TRI(A)/CRE(A)/IRE(A) and SFI authorisation.
- d) FI(A)/TRI(A)/CRI(A)/IRI(A) ratings , SFI and MCCI authorisation.

Answer ;

- d) FI(A)/TRI(A)/CRI(A)/IRI(A) ratings , SFI and MCCI authorisation.

0053. According to JAR-FCL , the privileges of a newly qualified Flight Instructor are restricted to carrying out instruction under the supervision of a FI(A) , approved for this purpose. The restrictions may be removed from the rating ;

- a) on the recommendation of the supervising FI(A) after the holder of the restricted FI(A) rating has completed a competency test.
- b) on the recommendation of the supervising FI(A) after the holder of the restricted FI(A) rating has completed at least 100 hours flight instruction and , in addition , has supervised at least 25 student solo flights.
- c) on the recommendation of the supervising FI(A) after the holder of the restricted FI(A) rating has supervised at least 100 solo flights.
- d) on the recommendation of the supervising FI(A) after the holder of the restricted FI(A) rating has supervised at least 100 solo flights and completed a competency test.

Answer ;

- b) on the recommendation of the supervising FI(A) after the holder of the restricted FI(A) rating has completed at least 100 hours flight instruction and , in addition , has supervised at least 25 student solo flights.

0054. According to JAR-FCL , the privileges of the holder of an unrestricted FI(A) rating are to conduct flight instruction for the issue of a CPL(A) ;

- a) provided that the FI(A) has completed not less than 15 hours on the relevant type in the preceding 12 months.
- b) provided that the FI(A) has completed 200 hours of flight instruction.
- c) provided that the FI(A) has completed at least 500 hours of flight time as a pilot of aeroplanes including at least 200 hours of flight instruction.
- d) without restriction.

Answer ;

- c) provided that the FI(A) has completed at least 500 hours of flight time as a pilot of aeroplanes including at least 200 hours of flight instruction.

0055. According to JAR-FCL , the validity of type ratings and multi-engine class ratings will be one year from the date ;

- a) of the last medical certificate.
- b) of issue.
- c) of the skill test.
- d) the application is received by the Authority.

Answer ;

- b) of issue.

0056. According to the “Aerodrome Reference Code” , the “Code Letter E” shall identify an aircraft wing span of ;

- a) 36 m up to but not including 52 m.
- b) 24 m up to but not including 36 m.
- c) 52 m up to but not including 65 m.
- d) 15 m up to but not including 24 m.

Answer ;

- c) 52 m up to but not including 65 m.
-

0057. According with the “Aerodrome Reference Code” the “Code number 4” shall identify an aircraft reference field length of ;

- a) 1200 m.
- b) 1800 m and over.
- c) 1500 m.
- d) 1600 m.

Answer ;

- b) 1800 m and over.
-

0058. Aerodrome Control Service - Priority for landing

If an aircraft enters the traffic circuit without proper authorisation ;

- a) it shall only be permitted to land after having received proper authorisation from the aerodrome authority.
- b) it shall be permitted to land if its actions indicate that it so desires.
- c) it shall not be permitted to land.
- d) it shall not be permitted to land unless it becomes evident that the aircraft is in a state of emergency.

Answer ;

- b) it shall be permitted to land if its actions indicate that it so desires.
-

0059. Aerodrome - General

A defined rectangular area on the ground at the end of the take-off run available , prepared as a suitable area in which an aircraft can be stopped in the case of an abandoned take-off , is called ;

- a) Runway end safety area.
- b) Stopway.
- c) Clearway.
- d) Obstacle free zone (OFZ).

Answer ;

- b) Stopway.
-

0060. Aerodrome Identification Beacon

The light shown by an “Aerodrome Identification Beacon” of a land aerodrome shall be flashing , giving the aerodrome identification by Morse Code. The colour of this light is ;

- a) Blue.
- b) White.
- c) Yellow.
- d) Green.

Answer ;

- d) Green.
-

0061. Aerodrome traffic is ;

- a) All traffic in the aerodrome circuit.
- b) All traffic on the manoeuvring area and flying in the vicinity of an aerodrome.
- c) All traffic on the movement area and flying in the vicinity of an aerodrome.
- d) All traffic on the manoeuvring area.

Answer ;

- b) All traffic on the manoeuvring area and flying in the vicinity of an aerodrome.
-

0062. Aerodromes signs should be in the following configuration ;

- a) mandatory instruction signs , black background with red inscriptions.
- b) mandatory instruction signs , red background with black inscriptions.
- c) information signs , yellow or black background with black or yellow inscriptions.
- d) information signs , orange background with black inscriptions.

Answer ;

- c) information signs , yellow or black background with black or yellow inscriptions.
-

0063. Aeronautical Ground Lights on and in the vicinity of aerodromes may be turned off , provided that they can be brought back into operation before the expected arrival of an aircraft in at least ;

- a) 30 minutes.
- b) one hour.
- c) 5 minutes.
- d) 15 minutes.

Answer ;

d) 15 minutes.

0064. Aeronautical Information Service

Name the acronym signifying the system aimed at advance notification based on common effective dates , of circumstances that necessitate significant changes in operating practices.

- a) NOTAM RAC
- b) ATS NOTAM
- c) AIRAC
- d) Advisory NOTAM

Answer ;

c) AIRAC

0065. AIP

SIGMET information can be found in which part of the AIP ?

- a) MET
- b) GEN
- c) AD
- d) ENR

Answer ;

b) GEN

0066. AIP

Which part contains a brief description of areas and/or routes for which meteorological service is provided ?

- a) METEO
- b) AD
- c) GEN
- d) ENR

Answer ;

c) GEN

0067. AIP

Which part of the AIP contains a brief description of the service(s) responsible for search and rescue ?

- a) ENR
- b) AD
- c) SAR
- d) GEN

Answer ;

d) GEN

0068. AIP

Which part of the AIP contains a list with “Location Indicators” ?

- a) ENR
- b) AD
- c) LOC
- d) GEN

Answer ;

d) GEN

0069. AIP

Which part of the AIP contains information about holding , approach and departure procedures ?

- a) ENR
- b) MAP
- c) AD
- d) GEN

Answer ;

a) ENR

0070. AIP

Which part of the AIP contains information relating to existing prohibited , restricted and danger areas ?

- a) ENR
- b) The AIP does not contain this information
- c) GEN
- d) AD

Answer ;

- a) ENR
-

0071. AIP

Which part of the AIP gives detailed information about refuelling facilities and the fuel grades available ?

- a) AD
- b) FAL
- c) GEN
- d) ENR

Answer ;

- a) AD
-

0072. Air traffic control service is provided for the purpose of ;

- a) preventing collisions between aircraft , between aircraft and obstacles on the manoeuvring area and expediting and maintaining an orderly flow of air traffic.
- b) applying separation between aircraft and expediting and maintaining an orderly flow of air traffic.
- c) preventing collisions between controlled air traffic and expediting and maintaining an orderly flow of air traffic.
- d) avoiding collisions between all aircraft and maintaining an orderly flow of air traffic.

Answer ;

- a) preventing collisions between aircraft , between aircraft and obstacles on the manoeuvring area and expediting and maintaining an orderly flow of air traffic.
-

0073. Air Traffic Service unit means: ;

- a) Air Traffic Control units , Flight Information Centres or Air Services reporting offices.
- b) Air Traffic Control units and Flight Information Centres.
- c) Flight Information Centres and Air Services reporting offices.
- d) Air Traffic Control units and Air Services reporting offices.

Answer ;

- a) Air Traffic Control units , Flight Information Centres or Air Services reporting offices.
-

0074. Air traffic services unit clocks and other time recording devices shall be checked as necessary to ensure correct time to within plus or minus ;

- a) 10 seconds of UTC at all times.
- b) 15 seconds of UTC at all times.
- c) 1 minute of UTC at all times.
- d) 30 seconds of UTC at all times.

Answer ;

- d) 30 seconds of UTC at all times.
-

0075. Aircraft "A" with an ATC clearance is flying in VMC conditions within a control area. Aircraft "B" with no ATC clearance is approaching at approximately the same altitude and on a converging course. Which has the right of way ?

- a) Aircraft "A" regardless of the direction which "B" is approaching.
- b) Aircraft "B" if "A" is on its left.
- c) Aircraft "B" regardless of the direction "A" is approaching.
- d) Aircraft "A" if "B" is on its right.

Answer ;

- b) Aircraft "B" if "A" is on its left.
-

0076. Aircraft flying along the same track may be separated by DME-distances from the same DME and it is confirmed that the aircraft have passed each other. Specify the shortest difference in DME-distance to make it possible for one aircraft to climb or descend ;

- a) 15 NM.
- b) 20 NM.
- c) 12 NM.
- d) 10 NM.

Answer ;

- d) 10 NM.
-

- 0077.** Aircraft wishing to conduct IFR flight within advisory airspace , but not electing to use the air traffic advisory service ;
- a) shall nevertheless submit a flight plan but changes made thereto are not necessary to be notified.
 - b) may file a flight plan under pilot's discretion.
 - c) need to file a flight plan.
 - d) shall nevertheless submit a flight plan and notify changes made thereto to the ATS unit providing that service.

Answer ;

- d) shall nevertheless submit a flight plan and notify changes made thereto to the ATS unit providing that service.

0078. Airspace Classification - Services

During a "Visual Approach" in Controlled Airspace Class C ;

- a) ATC will provide separation with other traffic.
- b) ATC will provide separation with arriving but not with departing traffic.
- c) ATC will provide separation between flights under IFR , pilots are responsible for separation between flights under VFR.
- d) Pilots are responsible for separation with arriving and departing aircraft.

Answer ;

- a) ATC will provide separation with other traffic.

0079. Alert phase is defined as follows ;

- a) An emergency event in which an aircraft and its occupants are considered to be threatened by a danger.
- b) A situation where an apprehension exists as to the safety of an aircraft and its occupants.
- c) A situation related to an aircraft which reports that the fuel on board is exhausted.
- d) A situation related to an aircraft and its occupants are considered to be in a state of emergency.

Answer ;

- b) A situation where an apprehension exists as to the safety of an aircraft and its occupants.

0080. Altimeter setting (change during climb)

On flights in accordance with IFR , the change of the altimeter setting from QNH to Standard shall be made at the ;

- a) transition level.
- b) level specified by ATC.
- c) transition layer.
- d) transition altitude.

Answer ;

- d) transition altitude.

0081. Altimeter setting procedures – Definitions

The Transition Level ;

- a) shall be the highest available flight level below the transition altitude that has been established.
- b) is published for the aerodrome in the Section ENR of the AIP.
- c) shall be the lowest flight level available for use above the transition altitude.
- d) is calculated and declared for an approach by the Pilot-in command.

Answer ;

- c) shall be the lowest flight level available for use above the transition altitude.

0082. Altimeter setting procedures - Transition Altitude

The transition altitude of an aerodrome shall be as low as possible but normally not less than ;

- a) 1500 ft.
- b) 2500 ft.
- c) 3000 ft.
- d) 1000 ft.

Answer ;

- c) 3000 ft.

0083. Altimeter setting procedures - Transition Altitude/Level

In the vicinity of an aerodrome of intended landing or used for take-off , the vertical position of aircraft shall be expressed in term of ;

- a) altitude above mean sea level at or below the transition altitude.
- b) flight level at or below the transition level.
- c) altitude above mean sea level at or above the transition altitude.
- d) flight level at or below the transition altitude.

Answer ;

- a) altitude above mean sea level at or below the transition altitude.

0084. Altimeter setting procedures - Transition Layer

Unless instructed otherwise by an air traffic controller , when passing through the transition layer , a pilot shall report the vertical position of the aircraft as ;

- a) either altitude or flight level in climb.
- b) altitude in climb.
- c) flight level in a descent.
- d) altitude in a descent.

Answer ;

- d) altitude in a descent.
-

0085. Altimeter setting procedures - Transition Layer

When flying through the transition layer the vertical position of the aircraft should be expressed as ;

- a) either altitude or flight level during climb.
- b) flight level during descent.
- c) altitude during climb.
- d) altitude during descent.

Answer ;

- d) altitude during descent.
-

0086. Altimeter setting procedures - Transition Level

The transition level ;

- a) is calculated by the Pilot-in command.
- b) will be passed to aircraft by ATS units.
- c) is published and updated in the NOTAM.
- d) is published on the approach and landing chart for each aerodrome.

Answer ;

- b) will be passed to aircraft by ATS units.
-

0087. Altimeter setting procedures - Transition Level

The vertical position of an aircraft at or above the transition level with altimeter setting 1013.2 hPa has to be reported ;

- a) as Altitude.
- b) as Height.
- c) according to pilot's choice.
- d) as Flight Level.

Answer ;

- d) as Flight Level.
-

0088. Altimeter setting procedures - Transition Level

With altimeter setting of 1013.2 hPa , the vertical position of an aircraft at or above the transition level has to be reported ;

- a) as Altitude.
- b) as Height.
- c) according to pilot's choice.
- d) as Flight Level.

Answer ;

- d) as Flight Level.
-

0089. An air traffic control unit ;

- a) may ask an aircraft to temporarily change its call sign for safety reasons when there is a risk of confusion between two or more similar call signs.
- b) may require to change the call sign for safety reasons when there is a risk of confusion between two or more similar call signs providing the aircraft is on a repetitive flight plan.
- c) may not ask an aircraft to change its call sign after accepting the flight plan.
- d) must not ask an aircraft to change its call sign.

Answer ;

- a) may ask an aircraft to temporarily change its call sign for safety reasons when there is a risk of confusion between two or more similar call signs.
-

0090. An AIRAC is ;

- a) a package which consists of the following elements ; AIP , supplements to the AIP , NOTAM , AIC , checklists and summaries.
- b) a publication issued by or with the authority of a state containing aeronautical information of a lasting character essential to air navigation.
- c) a notice distributed by means of telecommunication containing information concerning the establishment , condition or change in any aeronautical facility service , procedure or hazard , the timely knowledge of which is essential to personnel concerned with flight operations.
- d) an Acronym for a system aimed at advance notification based on common effective dates , of circumstances necessitating significant changes in operating procedures.

Answer ;

- d) an Acronym for a system aimed at advance notification based on common effective dates , of circumstances necessitating significant changes in operating procedures.

0091. An aircraft in climb or descent is considered to have crossed a level when the SSR mode C derived level information indicates that it has passed this level in the required direction by ;

- a) more than 300 ft.
- b) +/- 300 ft.
- c) 300 ft.
- d) more than 200 ft.

Answer ;

- a) more than 300 ft.

0092. An aircraft intercepted by another aircraft shall immediately attempt to establish radio communication with the intercepting aircraft on the following frequencies ;

- a) 243 MHz – 125.5 MHz.
- b) 121.5 MHz – 282.8 MHz.
- c) 121.5 MHz – 125.5 MHz.
- d) 121.5 MHz – 243 MHz.

Answer ;

- d) 121.5 MHz – 243 MHz.

0093. An aircraft is considered to be maintaining its assigned level as long as the SSR mode C derived level information indicated that it is within ;

- a) +/- 500 ft of the assigned level.
- b) +/- 200 ft of the assigned level.
- c) +/- 300 ft of the assigned level.
- d) +/- 250 ft of the assigned level.

Answer ;

- c) +/- 300 ft of the assigned level.

0094. An aircraft is considered to overtake another if it approaches the other aircraft from the rear on a line forming an angle of less than ;

- a) 70 degrees with the plane of symmetry of the latter.
- b) 50 degrees with the plane of symmetry of the latter.
- c) 80 degrees with the plane of symmetry of the latter.
- d) 60 degrees with the plane of symmetry of the latter.

Answer ;

- a) 70 degrees with the plane of symmetry of the latter.

0095. An aircraft is flying under Instrument Flight Rules in an area where the visibility is unlimited and the sky is clear (free of clouds) , when it totally loses radio communications. The procedure to be followed is ;

- a) adopt a VFR flight level and continue flight onto destination.
- b) descend to En-route Minimum Safe Altitude and join closest airfield open to IFR operations.
- c) continue flight onto destination , complying with last received clearances then with filed flight plan.
- d) land on the closest appropriate aerodrome , then advise Air Traffic Services of landing.

Answer ;

- d) land on the closest appropriate aerodrome , then advise Air Traffic Services of landing.
-

0096. An aircraft is maintaining FL 150 within airspace class C. Another aircraft below at FL 140 is receiving a clearance to descend to FL 70. It is severe turbulence in the area. When is the earliest that a clearance to descend to FL 140 or below can be expected ?

- a) When the other aircraft has reported that it has left FL 120.
- b) When the other aircraft has reported that it has left FL 140.
- c) When the other aircraft has reported that it has reached FL 70.
- d) When the other aircraft has reported that it has descended through FL 130.

Answer ;

- d) When the other aircraft has reported that it has descended through FL 130.

0097. An aircraft making a radar approach should be advised to consider executing a missed approach , if the position or identification of the aircraft is in doubt during any portion of the final approach or if the aircraft is not visible on the radar display for significant interval during the last ;

- a) 2 NM.
- b) 3 NM.
- c) 4 NM.
- d) 1 NM.

Answer ;

- a) 2 NM.

0098. An aircraft making a radar approach should be directed to consider executing a missed approach if the aircraft is not visible on the radar display for any significant interval during the ;

- a) last 5 NM of the approach.
- b) last 3 NM of the approach.
- c) last 2 NM of the approach.
- d) last 4 NM of the approach.

Answer ;

- c) last 2 NM of the approach.

0099. An aircraft making a radar approach should be directed to execute a missed approach if no clearance to land has been received from the non-radar controller by the time the aircraft reaches a distance of ;

- a) 5 NM from the touchdown.
- b) 2 NM from the touchdown.
- c) 4 NM from the touchdown.
- d) 1.5 NM from the touchdown.

Answer ;

- b) 2 NM from the touchdown.

0100. An aircraft manoeuvring in an airport's circuit receives a series of red flashes from the control tower. This signifies that the aircraft must ;

- a) give way to another aircraft.
- b) return to land and that clearance to land will be communicated in due course.
- c) not land for the moment regardless of previous instructions.
- d) not land because the airport is not available for landing.

Answer ;

- d) not land because the airport is not available for landing.

0101. An aircraft shall display , if so equipped , an anti-collision light ;

- a) while taxiing , but not when it is being towed.
- b) outside the daylight-period in flight , but not on the ground when it is being towed.
- c) on the ground when the engines are running.
- d) outside the daylight-period at engine-start. During the daylight-period this is not applicable.

Answer ;

- c) on the ground when the engines are running.
-

0102. An aircraft which is being subjected to unlawful interference (hijacked) and is forced to divert from the cleared track or cruising level without being able to communicate with ATS shall try to ;

- a) declare an emergency.
- b) continue at an altitude that differs from the semicircular rule with 1000 feet when above FL 290 and 500 feet when lower than FL 290.
- c) fly the emergency triangle.
- d) as soon as possible commence emergency descent in order to minimise the difference between cabin pressure and outside pressure.

Answer ;

- b) continue at an altitude that differs from the semicircular rule with 1000 feet when above FL 290 and 500 feet when lower than FL 290.

0103. An airline is planning a flight that will require a Technical landing in a neighbouring state. Which freedom of the Air will be exercised ?

- a) 2nd freedom.
- b) 3rd freedom.
- c) 1st freedom.
- d) 4th freedom.

Answer ;

- a) 2nd freedom.

0104. An applicant for a commercial pilot licence-aeroplane shall have completed in aeroplanes not less than ;

- a) 200 hours of flight time or 150 hours if completed during a course of approved training as a pilot of aeroplanes.
- b) 150 hours of flight time and 100 hours as pilot in command.
- c) 200 hours of flight time and 70 hours as pilot in command.
- d) 200 hours of flight time and 80 hours as pilot in command.

Answer ;

- a) 200 hours of flight time or 150 hours if completed during a course of approved training as a pilot of aeroplanes.

0105. An applicant for a commercial pilot licence-aeroplane shall have completed in aeroplanes not less than ;

- a) 15 hours of cross country flight time as pilot-in-command including a cross country flight not less than 540 km (300 NM).
- b) 20 hours of cross country flight time as pilot-in-command including a cross country flight not less than 540 km (300 NM).
- c) 10 hours of cross country flight time as pilot-in-command including a cross country flight not less than 540 km (300 NM).
- d) 25 hours of cross country flight time as pilot-in-command including a cross country flight not less than 540 km (300 NM).

Answer ;

- b) 20 hours of cross country flight time as pilot-in-command including a cross country flight not less than 540 km (300 NM).

0106. An applicant for a commercial pilot licence-aeroplane shall have completed not less than hours of cross country flight time as pilot in command including a cross country flight totalling not less than km (..... NM) , in the course of which full stop landings at two different aerodromes shall be made. The hours and distance referred are ;

- a) 10 hours and 270 km (150 NM)
- b) 15 hours and 540 km (300 NM)
- c) 20 hours and 270 km (150 NM)
- d) 20 hours and 540 km (300 NM)

Answer ;

- d) 20 hours and 540 km (300 NM)

0107. An applicant for a commercial pilot licence shall have completed in aeroplanes not less than ;

- a) 20 hours of instrument instruction time of which not more than 5 hours may be instrument ground time.
- b) 10 hours of instrument instruction time of which not more than 5 hours may be instrument ground time.
- c) 15 hours of instrument time of which not more than 5 hours as pilot in command.
- d) 20 hours of instrument instruction time of which not more than 10 hours may be instrument ground time.

Answer ;

- b) 10 hours of instrument instruction time of which not more than 5 hours may be instrument ground time.

0108. An applicant for a commercial pilot licence shall hold ;

- a) a current class I medical assessment.
- b) a current class III medical assessment.
- c) a current class II medical assessment.
- d) a current class medical assessment as prescribed by the state issuing the licence.

Answer ;

- a) a current class I medical assessment.

0109. An applicant for an Airline Transport Pilot Licence aeroplane shall have completed in aeroplanes not less than hours , either as pilot in command or made up by not less than hours as pilot-in-command and the additional flight time as co-pilot performing , under the supervision of the pilot-in-command the duties and functions of pilot in command provided that the method of supervision employed is acceptable to the licensing authority. The stated above hours are respectively ;

- a) 200 hours and 75 hours
- b) 250 hours and 100 hours
- c) 200 hours and 100 hours
- d) 150 hours and 75 hours

Answer ;

- b) 250 hours and 100 hours

0110. An applicant for an Airline Transport Pilot Licence shall have completed in aeroplanes not less than ;

- a) 150 hours of instrument time , of which not more than 75 hours of instrument ground time.
- b) 75 hours of instrument time , of which not more than 30 hours may be instrument ground time.
- c) 100 hours of instrument time , of which not more than 30 hours of instrument ground time
- d) 75 hours of instrument time , of which not more than 20 hours of instrument ground time.

Answer ;

- b) 75 hours of instrument time , of which not more than 30 hours may be instrument ground time.

0111. An applicant for an Airline Transport Pilot Licence shall have completed in aeroplanes not less than ;

- a) 100 hours of night flight only as pilot in command.
- b) 75 hours of night time only as pilot in command.
- c) 75 hours of night flight as pilot in command or as co-pilot.
- d) 100 hours of night flight as pilot in command or as co-pilot.

Answer ;

- d) 100 hours of night flight as pilot in command or as co-pilot.

0112. An applicant holding a private or commercial pilot licence aeroplane for the issue of an instrument rating , shall have completed hours of cross-country flight time as pilot-in-command of aircraft in categories acceptable to the licensing Authority , of which not less than hours shall be in aeroplanes. The said hours , are respectively ;

- a) 40 hours and 15 hours
- b) 50 hours and 10 hours
- c) 40 hours and 10 hours
- d) 50 hours and 15 hours

Answer ;

- b) 50 hours and 10 hours

0113. An approaching aircraft may descent below the MSA if ;

- a) the aircraft gets radar vectors.
- b) the pilot is following the published approach procedure.
- c) the pilot has the field and the underlying terrain in sight and will keep it in sight.
- d) all mentioned answers are correct.

Answer ;

- d) all mentioned answers are correct.

0114. An ATS airspace where IFR and VFR are permitted and receive flight information service if requested , is classified as ;

- a) Airspace G.
- b) Airspace F.
- c) Airspace C.
- d) Airspace E.

Answer ;

- a) Airspace G.
-

0115. An ATS airspace where IFR and VFR are permitted IFR flights are subject to Air Traffic Control Service and are separated from other IFR flights. All flights receive traffic information as far as is practical , is classified as ;

- a) Airspace A.
- b) Airspace B.
- c) [Airspace E.](#)
- d) Airspace D.

Answer ;

- c) [Airspace E.](#)

0116. An ATS airspace where IFR and VFR flights are permitted , all flights are subject to air traffic control service and are separated from each other is classified as ;

- a) Airspace C.
- b) [Airspace B.](#)
- c) Airspace D.
- d) Airspace E.

Answer ;

- b) [Airspace B.](#)

0117. An ATS airspace where IFR and VFR flights are permitted , all flights are subject to air traffic control service and IFR flights are separated from other IFR flights and from VFR flights , VFR flights are separated from IFR flights and receive traffic information in respect of other VFR flights , is classified as ;

- a) Airspace E.
- b) [Airspace C.](#)
- c) Airspace D.
- d) Airspace B.

Answer ;

- b) [Airspace C.](#)

0118. An ATS airspace where IFR and VFR flights are permitted , all participating IFR flights receive an air traffic advisory service and all flights receive flight information service if requested , is classified ;

- a) Airspace D.
- b) Airspace G.
- c) Airspace E.
- d) [Airspace F.](#)

Answer ;

- d) [Airspace F.](#)

0119. An ATS airspace where IFR and VFR flights are permitted and all flights are subject to air traffic control service. IFR flights are separated from other IFR flights and receive traffic information in respect of VFR flights. VFR flights receive traffic information in respect of all other flights , is classified as ;

- a) Airspace A.
- b) [Airspace D.](#)
- c) Airspace E.
- d) Airspace B.

Answer ;

- b) [Airspace D.](#)

0120. An information issued by a meteorological watch office concerning the occurrence or expected occurrence of specified en-route weather phenomena which may affect the safety of low-level aircraft operations and which was not already included in the forecast issued for low level flights in the flight information region concerned or subarea thereof is ;

- a) a SIGMET information.
- b) a NOTAM.
- c) [an AIRMET information.](#)
- d) an En-Route Meteo Report.

Answer ;

- c) [an AIRMET information.](#)

0121. An integrated aeronautical information package consists of the following elements ;

- a) AIP , supplements to AIP , NOTAM and PIB , AIC and checklist summaries.
- b) AIP , including amendment service , supplements to AIP , NOTAM , AIC , AIRAC.
- c) AIP , including amendment service , supplements to AIP , NOTAM , AIC and checklist summaries.
- d) [AIP , including amendment service , supplements to AIP , NOTAM and pre-flight information bulletin \(PIB \) , AIC , checklists and summaries.](#)

Answer ;

- d) [AIP , including amendment service , supplements to AIP , NOTAM and pre-flight information bulletin \(PIB \) , AIC , checklists and summaries.](#)

0122. Annex 2 - Light signals for aerodrome traffic

A series of green flashes from aerodrome control directed towards an aircraft on ground means ;

- a) Stand by , clearance for take off will be given in short time.
- b) Cleared to taxi.
- c) Accelerate taxi speed.
- d) Slow down taxi speed , but continue.

Answer ;

- b) Cleared to taxi.
-

0123. Annex 2 - Light signals for aerodrome traffic

A series of green flashes from aerodrome control directed towards an aircraft in flight means ;

- a) Expedite and make a short approach and land as soon as possible.
- b) Return for landing , clearance to land and will be given in due course.
- c) Cleared to land.
- d) Continue circling and give way to other aircraft.

Answer ;

- b) Return for landing , clearance to land and will be given in due course.
-

0124. Annex 12 - Search and Rescue - Signals at night

The pilot of an aircraft , observing a luminous signal requesting help , will indicate to the persons in difficulty that he has received the ground signals by ;

- a) fly over the group of people in difficulty as low as possible.
- b) switching his landing lights on and off twice or , if the aeroplane is not so equipped , his navigation lights twice.
- c) make at least one complete turn over the group of people in difficulty.
- d) transmit , by luminous Morse signal , a series of the letter "R" using his navigational lights.

Answer ;

- b) switching his landing lights on and off twice or , if the aeroplane is not so equipped , his navigation lights twice.
-

0125. Annex 17 - Security

Each Contracting State shall ensure that the appropriate authority arranges for the supporting resources and facilities required by the aviation security services to be available ;

- a) on a common basis for all airports within the State.
- b) at each airport serving international civil aviation.
- c) for administrative staff of each airport within that State.
- d) for every airline operating in that State.

Answer ;

- b) at each airport serving international civil aviation.
-

0126. Anti collision lights

Aircraft equipped with red anticollision lights may display them ;

- a) outside the daylight-period in flight , but not on the ground when being towed.
- b) outside the daylight-period at engine start. During the daylight-period this procedure is not applicable.
- c) on the ground when the engines are running.
- d) while taxiing , but not when being towed.

Answer ;

- c) on the ground when the engines are running.
-

0127. Any person who suffers damage on the surface shall , upon proof only that damage was caused by an aircraft in flight or by any person or thing falling therefore will be entitled to compensation as provided by ;

- a) the Rome Convention.
- b) the Warsaw Convention.
- c) the Chicago Convention.
- d) the Montreal Convention.

Answer ;

- a) the Rome Convention.
-

0128. Approach Control Service

An Expected Approach Time/EAT will be transmitted by the most expeditious means to the aircraft when it is expected that it has to hold ;

- a) for 20 minutes or more.
- b) for 30 minutes or more.**
- c) for 10 minutes or more.
- d) for 15 minutes or more.

Answer ;

- b) for 30 minutes or more.**
-

0129. Approach Procedures - Arrival and approach segments

In an instrument approach procedure , the segment in which alignment and descent for landing are made is called ;

- a) Arrival segment.
- b) Initial approach segment.
- c) Final approach segment.**
- d) Intermediate approach segment.

Answer ;

- c) Final approach segment.**
-

0130. Approach Procedures - Arrival and approach Segments

The minimum obstacle clearance in the primary area of the initial approach segment for an instrument approach procedure is at least ;

- a) 150 m (492 ft).
- b) 300 m (984 ft).**
- c) 450 m (1476 ft).
- d) 600 m (1968 ft).

Answer ;

- b) 300 m (984 ft).**
-

0131. Approach Procedures - Arrival and Approach Segments - Intermediate approach segment

What is the minimum obstacle clearance requirement at the end of the primary area of the intermediate approach segment in an instrument approach procedure ?

- a) 150 m (492 ft) reducing to 0 m.
- b) 450 m (1476 ft) reducing to 150 m (492 ft).
- c) 300 m (984 ft) reducing to 0 m.
- d) 300 m (984 ft) reducing to 150 m (492 ft).**

Answer ;

- d) 300 m (984 ft) reducing to 150 m (492 ft).**
-

0132. Approach Procedures - Circling

A circling approach is ;

- a) a visual flight manoeuvre that may be carried out as long as visual ground contact can be maintained.
- b) a visual flight manoeuvre to be performed when radar vectoring is available.
- c) a visual manoeuvre to be conducted only in IMC.
- d) a visual flight manoeuvre keeping the runway environment in sight while at MDA/H.**

Answer ;

- d) a visual flight manoeuvre keeping the runway environment in sight while at MDA/H.**
-

0133. Approach Procedures - Circling

It is permissible to eliminate from consideration a particular sector where a prominent obstacle exists in the visual manoeuvring (circling) area outside the final approach and missed approach area. When this option is exercised , the published procedure ;

- a) permits circling only in VMC.
- b) recommends not to perform circling within the total sector in which the obstacle exists.
- c) prohibits circling within the total sector in which the obstacle exists.**
- d) prohibits the circling approach to the affected runway.

Answer ;

- c) prohibits circling within the total sector in which the obstacle exists.**
-

0134. Approach Procedures - Circling

The term used to describe the visual phase of flight after completing an instrument approach , to bring an aircraft into position for landing on a runway which is not suitably located for straight-in approach , is ;

- a) Visual approach.
- b) Visual manoeuvring (circling).
- c) Contact approach.
- d) Aerodrome traffic pattern.

Answer ;

- b) Visual manoeuvring (circling).
-

0135. Approach procedures - Circling

The visual contact with the runway is lost on the down-wind leg , while circling to land following an instrument approach. You have to initiate a go-around ;

- a) if you have other visual cues of the aerodrome environment , continue with visual ground contact.
- b) turn towards the runway , maintain altitude and request ATC instructions.
- c) make a turn of 90 degrees towards the runway and try to regain visual contact.
- d) make an initial climbing turn towards the runway and initiate the missed approach.

Answer ;

- d) make an initial climbing turn towards the runway and initiate the missed approach.
-

0136. Approach procedures - Final approach segment

In a precision approach (ILS) , generally glide path interception occurs at heights above runway elevation from ;

- a) 300 m (984 ft) to 900 m (2955 ft).
- b) 150 m (492 ft) to 900 m (2955 ft).
- c) 150 m (492 ft) to 300 m (984 ft).
- d) 300 m (984 ft) to 600 m (1968 ft).

Answer ;

- a) 300 m (984 ft) to 900 m (2955 ft).
-

0137. Approach procedures - Final approach segment

In a precision approach (ILS) , the final approach segment begins at the ;

- a) FAP.
- b) FAF.
- c) IF.
- d) MAP.

Answer ;

- a) FAP.
-

0138. Approach procedures - Final approach segment - Precision approach - ILS

The ILS obstacle clearance surfaces assume that the pilot does not normally deviate from the centreline more than ;

- a) a quarter of a scale deflection after being established on the track.
- b) half a scale deflection after being established on the track.
- c) one full scale deflection after being established on the track.
- d) one and a half of a scale deflection after being established on the track.

Answer ;

- b) half a scale deflection after being established on the track.
-

0139. Approach procedures - Instrument Approach Area

The primary area of an instrument approach segment is ;

- a) the most critical part of the segment where the minimum altitude should be kept very carefully.
- b) a defined area symmetrically disposed about the nominal flight track in which the Minimum Obstacle Clearance is provided.
- c) the outside part of the segment where the obstacle clearance increases from zero ft to the appropriate minimum.
- d) the first part of the segment.

Answer ;

- b) a defined area symmetrically disposed about the nominal flight track in which the Minimum Obstacle Clearance is provided.
-

0140. Approach procedures - MDH / OCH

For a non-precision or circling approach , the Minimum Descent Height (MDH) cannot be lower than ;

- a) 400 ft.
- b) 200 ft.
- c) the Obstacle Clearance Height (OCH).
- d) 350 ft.

Answer ;

- c) the Obstacle Clearance Height (OCH).
-

0141. Approach procedures - Minimum Sector Altitudes / MSA

Minimum Sector Altitudes are established for each aerodrome. The MSA provides an obstacle clearance of at least 300 m (984 ft) within a circle , associated with the homing facility for the approach procedure of that aerodrome. How many NM is the radius of this circle ?

- a) 10 NM
- b) 25 NM
- c) 5 NM
- d) 20 NM

Answer ;

- b) 25 NM
-

0142. Approach procedures - Missed approach climb

Normally the missed approach procedures are based on a nominal missed approach climb gradient of ;

- a) 2%.
- b) 5%.
- c) 3.3%.
- d) 2.5%.

Answer ;

- d) 2.5%.
-

0143. Approach procedures - Missed approach - Phases

A complete missed approach procedure consists of the following phases ;

- a) Arrival , Intermediate and Final.
- b) Initial , Intermediate and Final.
- c) Initial and Final.
- d) Arrival , Initial , Intermediate and Final.

Answer ;

- b) Initial , Intermediate and Final.
-

0144. Approach procedures - Non-precision - straight-in

A so-called “straight-in-approach” is considered to be acceptable for a non-precision approach , if the angle between the final approach track and the runway centreline is ;

- a) 20° or less.
- b) 40° or less.
- c) 10° or less.
- d) 30° or less.

Answer ;

- d) 30° or less.
-

0145. Approach segments

In an instrument approach procedure , the segment in which alignment and descent for landing are made is called ;

- a) Final approach segment.
- b) Initial approach segment.
- c) Arrival segment.
- d) Intermediate approach segment.

Answer ;

- a) Final approach segment.
-

0146. Area Control Centres issue clearances for the purpose of ;

- a) achieving separation between IFR flights.
- b) providing flight Information Service.
- c) providing advisory service.
- d) achieving separation between controlled flights.

Answer ;

- d) achieving separation between controlled flights.
-

0147. Arrival and Approach segments - General

What are the names of all separate segments that can be part of an instrument approach procedure ?

- a) Initial , intermediate , final.
- b) Descend , holding arrival , initial , intermediate , final , missed approach.
- c) Arrival , holding , initial , intermediate , final , missed approach.
- d) Arrival , initial , intermediate , final , missed approach.

Answer ;

- d) Arrival , initial , intermediate , final , missed approach.

0148. “ASDA” (Acceleration Stop Distance Available) is ;

- a) the length of the take-off run available plus the length of the clearway.
- b) the length of the runway plus the length of stopway available (if stopway provided).
- c) the length of the take-off run available plus the length of stopway (if stopway provided).
- d) the length of the take-off run available plus the length of stopway and clearway (if provided) .

Answer ;

- c) the length of the take-off run available plus the length of stopway (if stopway provided).

0149. At night an aircraft observes a luminous signal requesting help. To indicate that he has received these ground signals , the pilot must ;

- a) switch his landing lights on and off twice or , if he is not so equipped , his navigation lights twice.
- b) fly over the group of people in difficulty as low as possible.
- c) make at least one complete turn over the group of people in difficulty.
- d) transmit , by luminous Morse signal , a series of the letter “R” using his navigational lights.

Answer ;

- a) switch his landing lights on and off twice or , if he is not so equipped , his navigation lights twice.

0150. At the commencement of final approach , if the controller possesses wind information in the form of components , significant changes in the mean surface wind direction and speed shall be transmitted to aircraft. The mean cross-wind component significant change is ;

- a) 8 KT.
- b) 5 KT.
- c) 10 KT.
- d) 3 KT.

Answer ;

- b) 5 KT.

0151. At the commencement of final approach , if the controller possesses wind information in the form of components , significant changes in the mean surface wind direction and speed shall be transmitted to aircraft. The mean head-wind component significant change is ;

- a) 5 KT.
- b) 8 KT.
- c) 4 KT.
- d) 10 KT.

Answer ;

- d) 10 KT.

0152. At the commencement of final approach , if the controller possesses wind information in the form of components , significant changes in the mean surface wind direction and speed shall be transmitted to aircraft. The mean tail-wind component significant change is ;

- a) 2 KT.
- b) 3 KT.
- c) 4 KT.
- d) 5 KT.

Answer ;

- a) 2 KT.

0153. ATIS broadcast ;

- a) shall not be transmitted on the voice channel of an ILS.
- b) shall not be transmitted on the voice of a VOR.
- c) shall be transmitted on the voice channel of an ILS , on a discrete VHF frequency or on the voice channel of a VOR.
- d) Shall only be transmitted on a discrete VHF frequency.

Answer ;

- a) shall not be transmitted on the voice channel of an ILS.

- 0154.** ATIS broadcast messages containing departure and arrival information should include cloud cover , when the clouds are ;
- a) cumulonimbus.
 - b) below 1500 m (5000 ft) or below the highest minimum sector altitude , whichever is the greater.
 - c) below 900 m (3000 ft) or below the highest minimum sector altitude , whichever is the greater.
 - d) below 2000 m (600 ft) or below the highest minimum sector altitude , whichever is the greater.

Answer ;

- b) below 1500 m (5000 ft) or below the highest minimum sector altitude , whichever is the greater.
-

- 0155.** ATS airspace's where IFR and VFR flights are permitted , all flights are subject to air traffic control service and are separated from each other is classified as ;

- a) Class A.
- b) Class B.
- c) Class E.
- d) Class D.

Answer ;

- b) Class B.
-

- 0156.** Authority

The final authority as to the disposition of the aircraft has the ;

- a) ATC controller whenever the aircraft is flying in controlled airspace.
- b) Pilot-in-command.
- c) Aircraft owner.
- d) Operator.

Answer ;

- b) Pilot-in-command.
-

- 0157.** Avoidance of collisions

The highest priority for landing has ;

- a) an aircraft that is compelled to land (Emergency landing).
- b) an aircraft on a diplomatic flight (Head of state).
- c) an Air Ambulance carrying a very sick person needing immediate medical attention.
- d) a military aircraft.

Answer ;

- a) an aircraft that is compelled to land (Emergency landing).
-

- 0158.** “Cabotage” refers to ;

- a) domestic air services.
- b) a flight above territorial waters.
- c) a national air carrier.
- d) crop spraying.

Answer ;

- a) domestic air services.
-

- 0159.** Change from IFR to VFR will always take place ;

- a) on the initiative of the aircraft commander.
- b) as instructed by an air traffic control unit.
- c) at the clearance limit, irrespective of the weather conditions.
- d) when the aircraft is leaving controlled airspace during VMC.

Answer ;

- a) on the initiative of the aircraft commander.
-

- 0160.** Changing of flight rules from IFR to VFR is possible ;

- a) only when leaving controlled airspace.
- b) if instructed by ATC so long as VMC is forecasted during the next 60 minutes.
- c) if the commander so requests.
- d) if instructed by ATC so long as VMC is forecasted during the next 30 minutes.

Answer ;

- c) if the commander so requests.
-

0161. Characteristics of T-VASIS

Each wing bar has ;

- a) 4 lights.
- b) 3 lights.
- c) 5 lights.
- d) 2 lights.

Answer ;

- a) 4 lights.
-

0162. Chicago Convention - Obligation to inform

Contracting States have the obligation to inform ICAO about ;

- a) changes in the national regulations.
- b) new licenses and ratings for flight crew and ground personnel and any suspended validity of such licenses.
- c) differences or non-compliance with standards in any of the Annexes to the convention.
- d) the pricing policy and agreements or passenger tickets and freight in international air transport.

Answer ;

- c) differences or non-compliance with standards in any of the Annexes to the convention.
-

0163. Circling approach

One of the conditions to descent below the MDA on a circling approach is ;

- a) the landing runway and an alternative landing possibility (runway) are in sight.
- b) the Ceiling is 1500 ft or higher.
- c) the horizontal Visibility is at least 5 NM and the Ceiling is 1500 ft or higher.
- d) the required visual references have been established and can be maintained.

Answer ;

- d) the required visual references have been established and can be maintained.
-

0164. Classification of Airspace

Above 3050 m (10.000 ft) AMSL , the VMC minima for VFR flights in all classes of airspace are ;

- a) Visibility : 8 km , Distance from clouds : 1500 m horizontal , 1000 ft vertical.
- b) No minima defined , VFR flights are not permitted.
- c) Visibility : 8 km , clear of clouds.
- d) Visibility : 5 km , Distance from clouds : 1500 m horizontal , 1000 ft vertical.

Answer ;

- a) Visibility : 8 km , Distance from clouds : 1500 m horizontal , 1000 ft vertical.
-

0165. Clearance for descent

An aircraft flying under IFR , maintaining FL 150 has requested clearance for descent. Another aircraft flying below , maintaining FL 140 receives the clearance ; “Descend to FL 70 , report passing FL 100”. The earliest moment the pilot of the aircraft at the higher level can expect to receive a clearance to descend to FL 140 or below is , when the pilot of the aircraft at the lower level has reported ;

- a) that he has passed through FL 100.
- b) that he has descended through FL 130.
- c) that he has reached FL 70.
- d) that he has left FL 140.

Answer ;

- d) that he has left FL 140.
-

0166. Clearance on Final Approach

A pilot may expect to receive the clearance to land or any alternative clearance before the aircraft reaches a distance of ;

- a) 3 NM from touchdown.
- b) 2 NM from touchdown.
- c) 5 NM from touchdown.
- d) 4 NM from touchdown.

Answer ;

- b) 2 NM from touchdown.
-

0167. Clearance to land or any alternative clearance received from the non-radar controller should normally be passed to the aircraft before it reaches a distance of ;

- a) 3 NM from touchdown.
- b) 5 NM from touchdown.
- c) 4 NM from touchdown.
- d) 2 NM from touchdown.

Answer ;

- d) 2 NM from touchdown.
-

- 0168.** Clearances will be issued by an ATC unit for the purpose of ;
- a) achieving separation between controlled flights.
 - b) providing flight Information Service.
 - c) providing alerting services.
 - d) providing advisory services.

Answer ;

- a) achieving separation between controlled flights.
-

- 0169.** “Clearway” is defined rectangular area established to ;
- a) permit the aircraft to stop if it fails the take-off.
 - b) protect aircraft during take-off or landing operations.
 - c) reduce the risk of damage to aircraft running off a runway.
 - d) permit aircraft to make a portion of its initial climb to a specific height.

Answer ;

- d) permit aircraft to make a portion of its initial climb to a specific height.
-

- 0170.** “Code letter D” shall be chosen to identify a taxiway used by aircraft having an outer main gear wheel span of less than 9 m. The taxiway width shall be ;
- a) 23 m.
 - b) 18 m.
 - c) 25 m.
 - d) 15 m.

Answer ;

- b) 18 m.
-

- 0171.** Communication Failure

After experiencing a communication failure on a flight accordance with IFR , the aircraft shall comply with the communication failure procedures. When flying in VMC , the aircraft shall ;

- a) continue on to destination , complying with last received and confirmed clearances or with filed flight plan.
- b) continue to fly in VMC , land at the nearest suitable aerodrome and report its arrival by most expeditious means to the appropriate ATS unit.
- c) adopt a VFR flight level and continue according to VFR to the flight plan destination.
- d) descend to Minimum Safe Altitude/Level , continue to the nearest aerodrome with instrument approach procedure.

Answer ;

- b) continue to fly in VMC , land at the nearest suitable aerodrome and report its arrival by most expeditious means to the appropriate ATS unit.
-

- 0172.** Communication Failure - Flight Procedures

You are on a flight in accordance with IFR in IMC , exactly on the current flight plan route. At 18:36 UTC you receive and acknowledge the following instruction from the radar controller ; “Turn immediately , fly heading 050° until further advised”. At 18:37 UTC you discover a communication failure. Two way radio communication cannot be established again.

- a) You continue on Heading 050 for 15 minutes.
- b) You continue on Heading 050.
- c) You continue on Heading 050 for 30 minutes.
- d) You have to return to your current flight plan route.

Answer ;

- d) You have to return to your current flight plan route.
-

- 0173.** Concerning to RNP (Required Navigation Performance) types , the indication RNP 4 , represents a navigation accuracy of ;

- a) plus or minus 4 NM on a 90 per cent containment basis.
- b) plus or minus 4 miles on a 90 per cent containment basis.
- c) plus or minus 4 NM on a 98 per cent containment basis.
- d) plus or minus 4 NM on a 95 per cent containment basis.

Answer ;

- d) plus or minus 4 NM on a 95 per cent containment basis.
-

- 0174.** Control Area (CTA) is defined as follows ;

- a) A controlled airspace extending upwards from a specified limit above the earth.
- b) A controlled airspace extending upwards from a height of 1000 feet above the earth.
- c) A controlled airspace extending upwards from the surface of the earth to a specified limit.
- d) A controlled airspace extending upwards from a height of 900 feet above the earth.

Answer ;

- a) A controlled airspace extending upwards from a specified limit above the earth.
-

- 0175.** Cruising level IFR during cruise within controlled airspace shall be given as flight level (FL) ;
- a) above the transition altitude when applicable.
 - b) if the obstacle clearance is more than 2000 feet.
 - c) only in airspace class A.
 - d) when QNH is higher than the standard pressure 1013 hPa.

Answer ;

- a) above the transition altitude when applicable.
-

0176. Definitions

The movement area of an airfield , the adjacent terrain and buildings or portions thereof with controlled access are called ;

- a) Security program.
- b) Manoeuvring area.
- c) Airside.
- d) Terminal.

Answer ;

- c) Airside.
-

0177. Definitions

What is ;

A manoeuvre in which a turn is made away from a designated track followed by a turn in the opposite direction to permit the aircraft to intercept and proceed along the reciprocal of the designated track.

- a) Race track
- b) Procedure turn
- c) Reversal track
- d) Base turn

Answer ;

- b) Procedure turn
-

0178. Definitions - Aerodrome

A defined rectangular area , selected or prepared as a suitable area over which an aeroplane may make a portion of its initial climb to a specific height is called ;

- a) Runway end safety area (RESA).
- b) Stopway.
- c) Take-off run available (TORA).
- d) Clearway.

Answer ;

- d) Clearway.
-

0179. Definitions - Aerodrome

Non-precision approach runways and precision approach runways CAT I , II and III are defined as ;

- a) Non-instrument runways.
- b) Instrument runways.
- c) Movement area.
- d) Parallel runways.

Answer ;

- b) Instrument runways.
-

0180. Definitions - (ICAO Doc 8168)

What is ;

A turn executed by the aircraft during the initial approach between the end of the outbound track and the beginning of the intermediate or final approach track. The tracks are not reciprocal.

- a) Base turn
- b) Procedure turn
- c) Reversal procedure
- d) Race track

Answer ;

- a) Base turn
-

0181. Definitions - Visual Approach

A so called "Visual Approach" can be performed ;

- a) during IFR and VFR approaches in VMC.
- b) during IFR approaches , if the cloud base is 1000 ft higher than the appropriate DA or MDA for that procedure , and the visibility is at least 5.5 km.
- c) during IFR approaches if the cloud base is 1000 ft higher than the appropriate DA or MDA for that procedure.
- d) when either part or all of an instrument approach procedure is not completed and the approach is executed in visual reference to terrain.

Answer ;

- d) when either part or all of an instrument approach procedure is not completed and the approach is executed in visual reference to terrain.

0182. Departure procedure - Design

The main factor/s that dictate/s in general the design of an instrument departure procedure is/are ;

- a) ATC availability and requirements.
- b) airspace restrictions applicable and in force.
- c) availability of navigation aids.
- d) the terrain surrounding the aerodrome.

Answer ;

- d) the terrain surrounding the aerodrome.

0183. Dependent parallel approaches may be conducted to parallel runways provided that the missed approach track for one approach diverges by ;

- a) at least 15° (degrees) from the missed approach track of the adjacent approach.
- b) at least 30° (degrees) from the missed approach track of the adjacent approach.
- c) at least 45° (degrees) from the missed approach track of the adjacent approach.
- d) at least 25° (degrees) from the missed approach track of the adjacent approach.

Answer ;

- b) at least 30° (degrees) from the missed approach track of the adjacent approach.

0184. Deviation from Flight Plan

Pilots of controlled flights are requested to inform the appropriate ATS whenever the average TAS at cruising level between reporting points varies or is expected to vary from the TAS given in the flight plan by ;

- a) 2%.
- b) 3%.
- c) 4%.
- d) 5%.

Answer ;

- d) 5%.

0185. During an arrival procedure under an IFR flight plan in VMC conditions , traffic avoidance is the responsibility of ;

- a) the approach controller.
- b) the radar controller.
- c) the pilot in command.
- d) the airport controller.

Answer ;

- c) the pilot in command.

0186. During an IFR flight in VMC in controlled airspace you experience a two-way radio communication failure. You will ;

- a) land at the nearest suitable aerodrome and inform ATC.
- b) descend to the flight level submitted for that portion of flight.
- c) land at the nearest suitable aerodrome maintaining VMC and inform ATC.
- d) select A7600 and continue according current flight plan to destination.

Answer ;

- c) land at the nearest suitable aerodrome maintaining VMC and inform ATC.

0187. During radar-control , a "radar-controller" shall issue a missed-approach instruction , in case the "tower-controller" has not issued a "landing-clearance" at the moment the aircraft is ;

- a) 2 NM from touch-down.
- b) 4 NM from touch-down.
- c) 3 NM from touch-down.
- d) 1 NM from touch-down.

Answer ;

- a) 2 NM from touch-down.

0188. Each contracting state shall provide an Aeronautical Information Service (AIS) in its territory and for areas in which the state is responsible for the Air Traffic Services outside its territory , and this shall include the preparation and origination of ;

- a) AIP , NOTAMs , Circular and AIRAC.
- b) Integrated Aeronautical Information Package.
- c) Only NOTAMs and Circulars.
- d) Only AIP and NOTAMs.

Answer ;

- b) Integrated Aeronautical Information Package.

0189. Each member state should designate an appropriate authority with its administration to be responsible for the development implementation and maintenance of a national aviation security programme. This programme should apply ;

- a) to all international civil air transport including aircraft engaged solely in the carriage of cargo and yet to domestic flights at the discretion of each member state.
- b) only to passengers and aircrew in international civil transport flights.
- c) only to passengers and aircrew in international civil transport flights and domestic flights.
- d) only to all international civil transport including aircraft engaged solely in the carriage of cargo.

Answer ;

- a) to all international civil air transport including aircraft engaged solely in the carriage of cargo and yet to domestic flights at the discretion of each member state.

0190. Each State of ICAO Annex 17 shall ensure the establishment of a security programme ;

- a) at each airport.
- b) only for administrative staff of airport.
- c) for every airline operating in the State.
- d) that is common for all airports within State.

Answer ;

- a) at each airport.

0191. Except in some special cases the establishment of change-over points should be limited to route segments of ;

- a) 100 NM or more.
- b) 60 NM or more.
- c) 50 NM or more.
- d) 75 NM or more.

Answer ;

- b) 60 NM or more.

0192. Except otherwise established by the appropriate ATS authority a Surveillance Radar Approach (SRA) shall be terminated at a distance from the touchdown of ;

- a) 2 NM.
- b) 3 NM.
- c) 5 NM.
- d) 4 NM.

Answer ;

- a) 2 NM.

0193. Except when a clearance is obtained from an ATC unit , a VFR flight cannot enter or leave a control zone when ceiling is less than ;

- a) 1000 feet or visibility is less than 8 km.
- b) 1000 feet or visibility is less than 5 km.
- c) 1500 feet or visibility is less than 5 km.
- d) 2000 feet or visibility is less than 5 km.

Answer ;

- c) 1500 feet or visibility is less than 5 km.

0194. Except when prescribed in procedures or made possible by agreements , aircraft under radar-control shall not be vectored closer to the boundary of controlled airspace than ;

- a) 2.5 NM.
- b) 3 NM.
- c) 5 NM.
- d) 1.5 NM.

Answer ;

- a) 2.5 NM.

0195. Expedited Approach Time / EAT

A pilot receives an EAT as soon as practicable , when an expected approach delay is ;

- a) 20 minutes.
- b) 10 minutes or more.**
- c) 10 minutes.
- d) 15 minutes or more.

Answer ;

- b) 10 minutes or more.**
-

0196. Final approach segment

During a precision approach (ILS) , glide path interception occurs normally at heights above runway elevation between ;

- a) 300 m (984 ft) to 900 m (2955 ft).**
- b) 300 m (984 ft) to 600 m (1968 ft).
- c) 150 m (492 ft) to 300 m (984 ft).
- d) 150 m (492 ft) to 900 m (2955 ft).

Answer ;

- a) 300 m (984 ft) to 900 m (2955 ft).**
-

0197. Flight Information Region (FIR) is an airspace within which the following services are provided ;

- a) Flight Information Service , Alerting Service and Advisory Service.
- b) Flight Information Service only.
- c) Flight Information Service and Alerting Service.**
- d) Flight Information Service and Advisory Service.

Answer ;

- c) Flight Information Service and Alerting Service.**
-

0198. Flight information service provided to flights shall include the provision of information concerning collision hazards to aircraft operating in airspace classes ;

- a) A to E (inclusive).
- b) F and G.
- c) C to G (inclusive).**
- d) A to G (inclusive).

Answer ;

- c) C to G (inclusive).**
-

0199. Flight Information Service shall be provided to aircraft in order to avoid collision hazards when operating in airspace classes ;

- a) F only.
- b) A , B , C , D , E , F and G.
- c) F and G only.
- d) C , D , E , F and G.**

Answer ;

- d) C , D , E , F and G.**
-

0200. Flight Plan

For flights in accordance with IFR within advisory airspace a flight plan ;

- a) shall be submitted. There is no obligation to report changes.
- b) shall be submitted. Changes to the flight plan have to be reported.**
- c) may be submitted at the pilots discretion. In case a flight plan is submitted all changes shall be reported as soon as practicable to the appropriate ATS unit.
- d) does not have to be submitted.

Answer ;

- b) shall be submitted. Changes to the flight plan have to be reported.**
-

0201. Flight Plan - Inadvertent track changes

In the event that a controlled flight inadvertently deviates from its track given in the current flight plan , action should be taken in order to ;

- a) maintain VMC , wait for instructions from the appropriate ATS unit.
- b) adjust the heading of aircraft to regain track as soon as practicable.**
- c) notify the appropriate ATS unit immediately notifying the new track and to comply with instructions from ATS.
- d) climb or descent by 500 ft , inform the appropriate ATS unit.

Answer ;

- b) adjust the heading of aircraft to regain track as soon as practicable.**
-

0202. For an IFR flight to an airport equipped with nav aids , the estimated time of arrival is the estimated time at which the aircraft ;

- a) will arrive overhead the initial approach fix.
- b) will leave the initial approach fix to start the final approach.
- c) will land.
- d) will stop on the parking area.

Answer ;

- a) will arrive overhead the initial approach fix.

0203. For commercial pilot licence aeroplane the applicant shall have completed in aeroplanes not less than if the privileges of the licence are to be exercised at night ;

- a) 5 hours of night flight time including 5 take-offs and 5 landings either as pilot in command or as co-pilot.
- b) 5 hours of night flight time including 5 take-offs and 5 landings as pilot in command.
- c) 5 hours of night flight time including 3 take-offs and 3 landings as pilot in command.
- d) 5 hours of night flight time including 3 take-offs and 5 landings as pilot in command.

Answer ;

- b) 5 hours of night flight time including 5 take-offs and 5 landings as pilot in command.

0204. For controlled traffic that shall be separated in the vicinity of an airport , separation minima may be reduced ;

- a) only if the air traffic controller has the involved aircraft in sight.
- b) if the commander of the involved aircraft so requests.
- c) at the discretion of the air traffic controller.
- d) when the commander in the following aircraft has the preceding aircraft in sight and is able to maintain own separation.

Answer ;

- d) when the commander in the following aircraft has the preceding aircraft in sight and is able to maintain own separation.

0205. For the transport of potentially disruptive passengers some supplementary safeguards are to be observed such as ;

- a) the boarding will be at the pilot in command discretion.
- b) boarding prior to all passengers.
- c) boarding after to all other passengers.
- d) the boarding has to be done at the state discretion.

Answer ;

- b) boarding prior to all passengers.

0206. General provisions - amended clearance

If an ATC clearance is not suitable to the pilot-in-command of an aircraft ;

- a) the PIC may request an amended clearance from the ATC. Amended clearances will only be given when VMC prevails.
- b) the PIC has to accept the ATC clearance. The clearance is based on the flight plan filed with ATC.
- c) the PIC may request and , if practicable , obtain an amended clearance.
- d) the PIC may propose another clearance. ATC has to amend the clearance in accordance with the pilots request.

Answer ;

- c) the PIC may request and , if practicable , obtain an amended clearance.

0207. General provisions - change from IFR to VFR

A change from instrument flight rules (IFR) to visual flight rules (VFR) is only acceptable , when VFR is permitted in that air space and when ;

- a) the PIC has requested and obtained an ATC CLR for the change and has filed a special VFR flight plan.
- b) the position of the change has been noted on the ATC flight plan. The cancellation of the IFR flight will then be made automatically by ATC.
- c) the change is initiated by the PIC with a message containing the specific expression “cancelling my IFR flight”.
- d) ATC invites the PIC to change from IFR to VFR.

Answer ;

- c) the change is initiated by the PIC with a message containing the specific expression “cancelling my IFR flight”.

0208. General provisions - handling an ATC-flight plan in case of a delay

In the event of a delay for an uncontrolled flight for which a flight plan has been submitted , the flight plan should be amended or a new flight plan submitted and the old one cancelled , when the delay is exceeding the original ;

- a) estimated departure time by 30 minutes.
- b) estimated off-block time by 30 minutes.
- c) **estimated off-block time by 60 minutes.**
- d) estimated departure time by 60 minutes.

Answer ;

- c) estimated off-block time by 60 minutes.**

0209. General provisions - handling an ATC-flight plan in case of a delay

In the event of a delay of a controlled flight , the submitted flight plan should be amended or cancelled and a new flight plan submitted when the delay is in excess of ;

- a) **30 minutes of the estimated time off blocks.**
- b) 30 minutes of the estimated time of departure.
- c) 60 minutes of the estimated time off blocks.
- d) 60 minutes of the estimated time of departure.

Answer ;

- a) 30 minutes of the estimated time off blocks.**

0210. General provisions - Responsibility for terrain clearance

Who is in general responsible for an ATC clearance to be safe in respect to terrain clearance ?

- a) The aircraft operator.
- b) **The pilot-in-command.**
- c) The ATS reporting office accepting the flight plan.
- d) The ATC.

Answer ;

- b) The pilot-in-command.**

0211. General provisions for ATS - Content of voice position reports (according Doc4444)

A complete position report transmitted by radiotelephony shall contain the following elements of information in the order listed ;

- a) **1) Aircraft identification , 2) position , 3) time , 4) flight level or altitude , 5) next position and time over , 6) ensuing significant point.**
- b) 1) Aircraft identification , 2) position , 3) flight level or altitude , 4) time , 5) next position and time over , 6) ensuing significant point.
- c) 1) Aircraft identification , 2) position , 3) time , 4) true air speed , 5) flight level or altitude , 6) next position and time over.
- d) 1) Aircraft identification , 2) position , 3) time , 4) flight level or altitude , 5) next position , 6) time over.

Answer ;

- a) 1) Aircraft identification , 2) position , 3) time , 4) flight level or altitude , 5) next position and time over , 6) ensuing significant point.**

0212. General provisions for ATS - Obstacle clearance

When does Air Traffic Control Services have the responsibility to prevent collisions with terrain ?

- a) ATS never prevent collisions with terrain.
- b) **When a flight in accordance with IFR is vectored by radar.**
- c) ATS only provides prevention when an aircraft is flying IFR in IMC.
- d) Always when ATS are provided.

Answer ;

- b) When a flight in accordance with IFR is vectored by radar.**

0213. Given ;

AGL = above ground level

AMSL = above mean sea level

FL = flight level

Within uncontrolled airspace , the first usable level in IFR must provide a 500 ft margin above the following two levels ;

- a) **3000 ft AMSL or 1000 ft AGL.**
- b) FL30 or 100 ft AGL.
- c) FL30 or 1500 ft AGL.
- d) 3000 ft AMSL or 1500 ft AGL.

Answer ;

- a) 3000 ft AMSL or 1000 ft AGL.**

0214. High intensity obstacle lights should be ;

- a) fixed red.
- b) flashing white.
- c) fixed orange.
- d) flashing red.

Answer ;

- b) flashing white.
-

0215. Holding procedures

If for any reasons a pilot is unable to conform to the procedures for normal conditions laid down for any particular holding pattern , he should ;

- a) follow the radio communication failure procedure.
- b) advise ATC as early as possible.
- c) execute a non-standard holding pattern in accordance with the performance of his aeroplane.
- d) remain within the protected area , but may deviate from the prescribed holding.

Answer ;

- b) advise ATC as early as possible.
-

0216. Holding Procedures - Buffer Area

How far beyond the boundary of the holding area extends the buffer area ?

- a) 5 NM.
- b) 3 NM.
- c) 5 km.
- d) 3 km.

Answer ;

- a) 5 NM.
-

0217. Holding procedures - Entry

Related to the three entry sectors in a holding pattern , there is a zone of flexibility on either side of the sectors boundaries of ;

- a) 15°.
- b) 5°.
- c) 10°.
- d) 20°.

Answer ;

- b) 5°.
-

0218. Holding procedures - Entry

You have received instructions to hold over a radio fix. The published procedure is ; All turns to the right , 1 minute outbound , inbound Magnetic Track 052°. You are approaching the fix on Magnetic Track 232°. Select the appropriate entry procedure ;

- a) parallel or direct.
- b) either offset or parallel.
- c) offset only.
- d) direct only.

Answer ;

- b) either offset or parallel.
-

0219. Holding procedures - Offset Entry

Above 14.000 ft in still air , the outbound time on a 30° offset track is limited to ;

- a) 2 minutes.
- b) 1 minute.
- c) 1 minute 30 seconds.
- d) 3 minutes.

Answer ;

- c) 1 minute 30 seconds.
-

0220. Holding procedures - Outbound time

The outbound time in a holding pattern above 14.000 ft in still air conditions is ;

- a) 2 minutes 30 seconds.
- b) 2 minutes.
- c) 1 minute.
- d) 1 minute 30 seconds.

Answer ;

- d) 1 minute 30 seconds.
-

0221. Holding procedures - Outbound time

The outbound time in a holding pattern at 14.000 ft or below in still air conditions is ;

- a) 1 minute.
- b) 30 seconds.
- c) 2 minutes.
- d) 1,5 minutes.

Answer ;

- a) 1 minute.
-

0222. Horizontal separation - Independent parallel approaches

A minimum radar separation shall be provided until aircraft are established inbound on the ILS localizer course and/or MLS final approach track. This minimum is , when independent parallel approaches are being conducted ;

- a) 1.0 NM.
- b) 2.0 NM.
- c) 3.0 NM.
- d) 5.0 NM.

Answer ;

- c) 3.0 NM.
-

0223. Horizontal separation - Independent parallel approaches

Such approaches may be conducted to parallel runways provided that , the missed approach track for one approach diverges from the missed approach track of the adjacent approach by at least ;

- a) 30° (degrees).
- b) 25° (degrees).
- c) 45° (degrees).
- d) 20° (degrees).

Answer ;

- a) 30° (degrees).
-

0224. How many red lights must a pilot see , whose aircraft , in final approach , is following a normal glide path defined by a PAPI ?

- a) None.
- b) 3.
- c) 1.
- d) 2.

Answer ;

- d) 2.
-

0225. ICAO Annex 1

When a Contracting State renders valid a licence issued in accordance with Annex 1 by another Contracting State , the validity of the authorisation ;

- a) shall not extend beyond the period of validity of the licence.
- b) depends on the regulations of the contracting state which renders valid the licence.
- c) shall not extend beyond one year for ATPL and CPL.
- d) is only considered for PPL.

Answer ;

- a) shall not extend beyond the period of validity of the licence.
-

0226. ICAO Annex 1 - JAR FCL1 - Cross Country flight time requirements for the ATPL.

As part of the total flight time requirement of 1500 hours , the applicant for an Airline Transport Pilot Licence aeroplane shall have completed not less than 200 hours of cross-country flight time on aeroplanes. How much of this shall be pilot-in-command time or co-pilot time under the supervision of the pilot in command , performing the duties and functions of a pilot in command , provided that the method of supervision employed is acceptable to the licensing authority ?

- a) 75 hours.
- b) 10 hours.
- c) 100 hours.
- d) 50 hours.

Answer ;

- c) 100 hours.
-

0227. ICAO Annex 2 - Definitions

Who is charged with the safe conduct of a flight ?

- a) The pilot-in-command.
- b) The aircraft owner.
- c) The ATC controller whenever the aircraft is flying in controlled airspace.
- d) The airline operator.

Answer ;

- a) The pilot-in-command.
-

0228. ICAO Annex 7 - Nationality and registration

The registration mark shall be letters , numbers or a combination of letters and numbers and shall be that assigned by the ;

- a) Ministry of Transport and the Ministry of Defense in the state of registry.
- b) the International Telecommunication Union.
- c) the International Civil Aviation Organisation.
- d) the state of registry or common mark registering authority.

Answer ;

- d) the state of registry or common mark registering authority.
-

0229. ICAO Annex 7 - Nationality and registration

When letters are used for the registration mark , combinations shall not be used which might be confused with the ;

- a) letters used for ICAO identification documents.
- b) five letter combinations used in the international code of signals.
- c) four letter combinations beginning with Q.
- d) three letters combinations used in the international code of signals.

Answer ;

- b) five letter combinations used in the international code of signals.
-

0230. ICAO Annex 12 - Search and Rescue

The procedure for the pilot-in-command of an aircraft to be followed in case of intercepting a distress transmission is ;

- a) record the position of the transmission , proceed according to the flight plan , complete the SAR report form at the next airport , indicating where you can be reached in order to supply further information.
- b) hold at the position where the distress signal and/or message is received , co-ordinate the SAR operation by using the appropriate VHF and/or HF frequencies until released by a SAR unit.
- c) record the position of the craft in distress if given , if possible take a bearing of the transmission , inform the appropriate RCC or ASS and , while awaiting instructions , proceed at your discretion towards the position given in the transmission.
- d) record the position of the craft in distress , take a bearing of transmission , inform the appropriate RCC or ATS using the appropriate VHF and/or HF frequencies , proceed on the most expeditious way towards the position given in transmission.

Answer ;

- c) record the position of the craft in distress if given , if possible take a bearing of the transmission , inform the appropriate RCC or ASS and , while awaiting instructions , proceed at your discretion towards the position given in the transmission.
-

0231. ICAO Annex 13 - Accident/Incident notification and reporting

The aircraft has made a complete stop on the apron. When leaving the aircraft , one of the passengers walks into the trailing edge of the wing and gets seriously injured.

- a) This is an incident. The pilot-in-command must report it to the airport authority within the next 48 hours.
- b) This is a matter of passenger insurance as the flight is terminated and the aeroplane doors are open. The airport operator or the company in charge of the handling shall establish a report for the insurance company.
- c) This is an irregularity in the handling. The handling agent must inform his insurance company.
- d) This is an accident. The crew must follow the procedure relevant for this case.

Answer ;

- d) This is an accident. The crew must follow the procedure relevant for this case.
-

0232. ICAO Annex 13 - Notification and reporting

During the climb-out phase of a flight the pilot-in-command becomes incapacitated. The co-pilot takes over control of the aircraft and decides that he will return for landing. What action has to be taken after landing ?

- a) This is an irregularity in the operation. The operator must inform the Authority by writing and Irregularity Report.
- b) This is an irregularity. The pilot-in-command or the Operator must deposit a report on behalf of the involved airport Authority within the following 48 hours.
- c) This is a serious incident. The crew must follow the procedure relevant to an incident.
- d) This is an accident. The crew must follow the procedure relevant to an accident.

Answer ;

- c) This is a serious incident. The crew must follow the procedure relevant to an incident.

0233. ICAO Annex 14 - Visual aids for navigation - Lights

Runway edge lights shall consist of at least ;

- a) flashing lights showing variable yellow.
- b) flashing lights showing variable green.
- c) fixed lights showing steady green.
- d) fixed lights showing variable white.

Answer ;

- d) fixed lights showing variable white.
-

0234. ICAO Annex 14 - Visual aids for navigation - Lights - Displaced Threshold

When a threshold is displaced , what colour shall the lights have in approach direction between the beginning of the runway and the displaced threshold ?

- a) flashing red , intermittent with flashing white.
- b) white.
- c) red.
- d) blue , this portion of the runway is considered as taxiway.

Answer ;

- c) red.
-

0235. ICAO Annex 14 - Visual aids for navigation - Runway End Lights

The colour of fixed , unidirectional Runway End Lights is ;

- a) white.
- b) red.
- c) yellow.
- d) green.

Answer ;

- b) red.
-

0236. If a licence holder is unable to perform the flight crew functions appropriate to that licence due to illness , the authority must be informed ;

- a) if still not fit to fly when his/her current medical certificate expires.
- b) after 21 days of consecutive "illness".
- c) after one calendar month of consecutive illness.
- d) as soon as possible if the illness is expected to last more than 21 days.

Answer ;

- b) after 21 days of consecutive "illness".
-

0237. If a pilot is carrying out single pilot commercial passenger transport operations how does the validity of his class 1 medical change on his 40th birthday ?

- a) from 12 months to 3 months.
- b) from 36 months to 24 months.
- c) from 24 months to 12 months.
- d) from 12 months to 6 months.

Answer ;

- d) from 12 months to 6 months.
-

0238. If an arriving aircraft is making a straight in approach a departing aircraft may take off in any direction ;

- a) until ten minutes before the arriving aircraft is estimated to be over the instrument runway.
- b) until five minutes before the arriving aircraft is estimated to be over the instrument runway.
- c) until two minutes before the arriving aircraft is estimated to be over the instrument runway.
- d) until three minutes before the arriving aircraft is estimated to be over the instrument runway.

Answer ;

- b) until five minutes before the arriving aircraft is estimated to be over the instrument runway.
-

0239. If an international commercial air service is operated with a single pilot aircraft , what is the maximum age of the pilot ?

- a) 65
- b) 60
- c) 69
- d) 59

Answer ;

- d) 59
-

0240. If no ICAO identifier has been attributed to an alternate airport (box 16) of a flight plan form ;
- a) write XXXX in box 16 and indicate in box 18 (additional information) ALTN/ followed by the name of the airport.
 - b) write XXXX in box 16 and indicate in box 18 (additional information) DEGT/ followed by the name of the airport.
 - c) write ZZZZ in box 16 and indicate in box 18 (additional information) DEGT/ followed by the name of the airport.
 - d) write ZZZZ in box 16 and indicate in box 18 (additional information) ALTN/ followed by the name of the airport.

Answer ;

- d) write ZZZZ in box 16 and indicate in box 18 (additional information) ALTN/ followed by the name of the airport.

0241. If radio communication is established during an interception but communications in a common language is not possible , which phrase should be pronounced by the intercepting aircraft to request the intercepted aircraft to descend for landing ?

- a) Descend
- b) Descend for landing
- c) You land
- d) Let down

Answer ;

- a) Descend

0242. If radio contact with the intercepting aircraft is established but communication on a common language is not possible , which phrase should be pronounced by the intercepted aircraft to communicate that he is unable to comply with the instructions received ?

- a) CAN NOT
- b) UNABLE TO COMPLY
- c) CAN NOT COMPLY
- d) NOT POSSIBLE

Answer ;

- a) CAN NOT

0243. If the crew on an arriving aircraft approaching a controlled aerodrome will report “field in sight” , a clearance for “visual approach” may be given under certain conditions ;

- a) the meteorological visibility must not be less than 8 km.
- b) continued approach will be according to VFR.
- c) the air traffic controller will provide separation to other controlled traffic.
- d) the approach must be passing the FAF.

Answer ;

- c) the air traffic controller will provide separation to other controlled traffic.

0244. IFR cruising levels within controlled airspace shall be given as flight level (FL) ;

- a) when the QNH is higher than the standard pressure 1013 hPa.
- b) only in airspace class A.
- c) if the obstacle clearance is more than 2000 feet.
- d) above the transition altitude when applicable.

Answer ;

- d) above the transition altitude when applicable.

0245. In a precision approach Category I lighting system , the centre line and crossbar lights shall be ;

- a) fixed lights showing variable white.
- b) fixed lights showing variable green.
- c) flashing lights showing variable green.
- d) flashing lights showing variable white.

Answer ;

- a) fixed lights showing variable white.

0246. In a precision approach Category I lighting system , the single , two and three light sources on the centre line have a length of ;

- a) 150 m.
- b) 250 m.
- c) 200 m.
- d) 300 m.

Answer ;

- d) 300 m.

0247. In case of parallel runways , each runway designation number shall be supplemented ;
- a) by a letter for 2 parallel runways.
 - b) by a number like “0” and “01” for 2 parallel runways.
 - c) by a letter - for example 3 parallel runways “L” and “R” and the central has no letter.
 - d) by a letter - for example 2 parallel runways “L” and “R” - for 3 “L” , “C” and “R”.

Answer ;

- d) by a letter - for example 2 parallel runways “L” and “R” - for 3 “L” , “C” and “R”.

0248. In certain circumstances a medical examination may be deferred at the discretion of the licensing authority , provided that such deferment shall only be made as an exception and shall not exceed ;

- a) a single period of six months in the case of a flight crew member of an aircraft engaged in commercial operations.
- b) two consecutive periods each of three months in the case of a flight crew member of an aircraft engaged in non commercial operations.
- c) a single period of six months in the case of a flight crew member of an aircraft engaged in non commercial operations.
- d) in the case of a private pilot , a single period of 12 months.

Answer ;

- c) a single period of six months in the case of a flight crew member of an aircraft engaged in non commercial operations.

0249. In order to avoid confusion , the identification numbers given to each prohibited area , restricted area and danger area shall not be re-used for a period of ;

- a) at least 6 months after cancellation of the area to which they refer.
- b) at least 2 months after cancellation of the area to which they refer.
- c) at least one year after cancellation of the area to which they refer.
- d) at least 3 months after cancellation of the area to which they refer.

Answer ;

- c) at least one year after cancellation of the area to which they refer.

0250. In order to meet the wake turbulence criteria , what minimum separation should be applied when a Medium aircraft is taking off behind a Heavy aircraft and both are using the same runway ?

- a) 4 minutes
- b) 1 minute
- c) 3 minutes
- d) 2 minutes

Answer ;

- d) 2 minutes

0251. In order to meet wake turbulence criteria , for arriving aircraft and using timed approaches , what minima shall be applied to aircraft landing behind a Heavy or a Medium aircraft ?

- a) Light aircraft behind Medium aircraft - 4 minutes.
- b) Medium aircraft behind Heavy aircraft - 2 minutes.
- c) Medium aircraft behind Heavy aircraft - 3 minutes.
- d) Medium aircraft other Medium aircraft - 2 minutes.

Answer ;

- b) Medium aircraft behind Heavy aircraft - 2 minutes.

0252. In the “Aerodrome Reference Code” the code element 2 shall identify ;

- a) the length of the aircraft fuselage.
- b) the width of the aircraft wing.
- c) Only the aircraft wing span.
- d) the aircraft wing span and the outer main gear wheel span.

Answer ;

- d) the aircraft wing span and the outer main gear wheel span.

0253. In the case of parallel runways , each runway designation number shall be supplemented ;

- a) by a letter - for example 3 parallel runways “L” and “R” and the central has no letter.
- b) by a number like “0” and “01” for 2 parallel runways.
- c) by a letter for 2 parallel runways.
- d) by a letter - for example 2 parallel runways “L” and “R” - for 3 “L” , “C” and “R”.

Answer ;

- d) by a letter - for example 2 parallel runways “L” and “R” - for 3 “L” , “C” and “R”.

- 0254.** In the event of being hijacked in an area where regional procedures have not been established the pilot should ;
- a) fly a standard racetrack pattern at the next reporting point on track and await ATC instructions.
 - b) fly a left-hand racetrack pattern at the next reporting point on track and await ATC instructions.
 - c) fly a right-hand orbit and await ATC instructions.
 - d) proceed at a level which differs from the cruising levels normally used for IFR flight in the area by 300 m (1000 ft) above FL290 in non-RVSM airspace or 150 m (500 ft) above FL290 in RVSM airspace or below FL290.

Answer ;

- d) proceed at a level which differs from the cruising levels normally used for IFR flight in the area by 300 m (1000 ft) above FL290 in non-RVSM airspace or 150 m (500 ft) above FL290 in RVSM airspace or below FL290.

-
- 0255.** In the event that a controlled flight inadvertently deviates from its current flight plan , the appropriate ATS unit has to be informed ;

- a) it is a deviation from the track.
- b) the estimated time is in error by more than 10 minutes.
- c) the TAS varies by plus or minus 5% of the TAS notified in the flight plan.
- d) of an emergency.

Answer ;

- c) the TAS varies by plus or minus 5% of the TAS notified in the flight plan.

-
- 0256.** In the “PAPI” system the pilot during an approach will see the two units nearest the runway as red and the two units farthest from the runway as white when ;

- a) only on the approach slope.
- b) below the approach slope.
- c) above the approach slope.
- d) on or close to the approach slope.

Answer ;

- d) on or close to the approach slope.

-
- 0257.** In the “VASIS” , how many light units are in each wing bar ?

- a) 4.
- b) 3.
- c) 5.
- d) 2.

Answer ;

- a) 4.

-
- 0258.** In which section of AIP are contained information elements relating to prohibited , restricted and dangerous areas ?

- a) ENR
- b) AGA
- c) GEN
- d) MAP

Answer ;

- a) ENR

-
- 0259.** Inadvertent changes from a Flight Plan
The appropriate ATS unit has to be informed ;

- a) about any track deviation.
- b) about any deviation in TAS.
- c) if the time estimate for the next reporting point is found to be in error in excess of more than ten minutes from that notified to ATS.
- d) if the average TAS at cruising level varies or is expected to vary by $\pm 5\%$ from that given in the flight plan.

Answer ;

- d) if the average TAS at cruising level varies or is expected to vary by $\pm 5\%$ from that given in the flight plan.
-

- 0260.** Independent parallel approaches may be conducted to parallel runways provided that ;
- a) the missed approach track for one approach diverges by at least 25° (degrees) from the missed approach track of the adjacent approach.
 - b) the missed approach track for one approach diverges by at least 45° (degrees) from the missed approach track of the adjacent approach.
 - c) the missed approach track for one approach diverges by at least 30° (degrees) from the missed approach track of the adjacent approach.
 - d) the missed approach track for one approach diverges by at least 20° (degrees) from the missed approach track of the adjacent approach.

Answer ;

- c) the missed approach track for one approach diverges by at least 30° (degrees) from the missed approach track of the adjacent approach.
-

- 0261.** Independent parallel approaches may be conducted to parallel runways provided that a no transgression zone / NTZ is established equidistant between the extended runway centre lines ;

- a) 610 m.
- b) 500 m.
- c) 600 m.
- d) 710 m.

Answer ;

- a) 610 m.
-

- 0262.** Independent parallel approaches may be conducted to parallel runways provided that a no transgression zone (NTZ) of at least ;

- a) 500 m is established between extended runway centre lines and as is depicted on the radar display.
- b) 610 m is established between extended runway centre lines and as is depicted on the radar display.
- c) 600 m is established between extended runway centre lines and as is depicted on the radar display.
- d) 710 m is established between extended runway centre lines and as is depicted on the radar display.

Answer ;

- b) 610 m is established between extended runway centre lines and as is depicted on the radar display.
-

- 0263.** Information on holding , approach and departure procedures. Which part of the AIP contains this information ?

- a) GEN
- b) ENR
- c) MAP
- d) AD

Answer ;

- b) ENR
-

- 0264.** Instrument Departure Procedures - Obstacle Clearance

The minimum obstacle clearance at the departure end of runway equals ;

- a) 35 ft.
- b) 0 ft.
- c) 0.8 % gradient.
- d) 3.3 % gradient.

Answer ;

- b) 0 ft.
-

- 0265.** Instrument Departure Procedure - Wind correction

Flying an Instrument Departure Procedure pilots are expected to ;

- a) request a clearance from ATC with regards to a wind correction to be applied.
- b) ignore the wind and proceed on a heading equal to the track.
- c) request from ATC an adequate heading to cater for wind direction and strength.
- d) correct the track for known wind to remain within the protected airspace.

Answer ;

- d) correct the track for known wind to remain within the protected airspace.
-

- 0266.** “Instrument runways” are the following runways intended for the operation of aircraft using instrument approach procedures ;

- a) Instrument approach runways , precision approach runways category I , II and III.
- b) Precision approach runways in general.
- c) Precision approach runways category I , II and III.
- d) Non precision approach runways , precision approach runways category I , II and III.

Answer ;

- d) Non precision approach runways , precision approach runways category I , II and III.
-

0267. Interception

An aircraft equipped with SSR transponder which is intercepted by another aircraft shall immediately , unless otherwise instructed by the appropriate air traffic service unit , select Mode A ;

- a) Code 7000.
- b) Code 7700.
- c) Code 7600.
- d) Code 7500.

Answer ;

- b) Code 7700.

0268. Interception

An aircraft which is intercepted by another aircraft shall immediately attempt to establish radio-communication with the intercepting aircraft or with the appropriate intercept control unit , by making a general call on the frequency ;

- a) 121.5 MHz. If no contact has been established , and if practicable , repeat this call on the frequency 125.5 MHz.
- b) 121.5 MHz. If no contact has been established , and if practicable , repeat this call on the frequency 243 MHz.
- c) 243 MHz. If no contact has been established , and if practicable , repeat this call on the frequency 125.5 MHz.
- d) 121.5 MHz. If no contact has been established , and if practicable , repeat this call on the frequency 282.8 MHz.

Answer ;

- b) 121.5 MHz. If no contact has been established , and if practicable , repeat this call on the frequency 243 MHz.

0269. Interception

If any instructions received by radio from any sources conflict with those given by the intercepting aircraft by visual signals , the intercepted aircraft shall ;

- a) select transponder mode A , squawk 7600 , fly holding patterns until having received instructions from the appropriate ATS unit.
- b) ignore the signals of the intercepting aircraft and request instructions from the appropriate ATS unit.
- c) ignore the signals of the intercepting aircraft and continue in accordance with the last clearance received and confirmed by the appropriate ATS unit.
- d) follow the instructions of the intercepting aircraft and request immediate clarification.

Answer ;

- d) follow the instructions of the intercepting aircraft and request immediate clarification.

0270. Interception

If radio contact is established during interception but communication in a common language is not possible , attempts shall be made to convey instructions and essential information by using standard phrases and pronunciations , transmitting each phrase twice . The standard phrase with the meaning “descend for landing” for use by INTERCEPTING aircraft is ;

- a) YOU LAND.
- b) DESCEND FOR LAND.
- c) LET DOWN.
- d) DESCEND.

Answer ;

- d) DESCEND.

0271. Interception , DAY or NIGHT

Which manoeuvre will be executed by an intercepting aircraft if the pilot of this aircraft wants to communicate to the intercepted aircraft “YOU MAY PROCEED” ?

- a) Rocking aircraft and flashing navigational lights at regular intervals.
- b) Circling the intercepted aircraft in a counter-clockwise pattern for aeroplanes , in a clockwise pattern for helicopter.
- c) Rocking aircraft twice in front of the intercepting aircraft , after acknowledgement by intercepted aircraft a slow level turn (normally to the left).
- d) An abrupt break-away manoeuvre from the intercepted aircraft consisting of a climbing turn of 90 degrees or more without crossing the line of flight of the intercepted aircraft.

Answer ;

- d) An abrupt break-away manoeuvre from the intercepted aircraft consisting of a climbing turn of 90 degrees or more without crossing the line of flight of the intercepted aircraft.

0272. JAR FCL 1

In accordance with JAR FCL 1 the credit for MPA co-pilot time is ;

- a) 100% of the co-pilot flight time towards the total flight time required for a higher grade of pilot licence.
- b) 50% of the co-pilot flight time towards the total flight time required for a higher grade of pilot licence.
- c) 75% of the co-pilot flight time towards the total flight time required for a higher grade of pilot licence.
- d) 100 hours of the flying time required for a higher grade of pilot licence.

Answer ;

- a) 100% of the co-pilot flight time towards the total flight time required for a higher grade of pilot licence.
-

0273. JAR-FCL 1

Instructor categories are ;

- a) FI(A) , TRI(A) , CRI(A) , IRI(A) ratings , SFI and MCCI authorisation.
- b) FI(A) and IRI(A) ratings.
- c) FI(A) , TRI(A) , CRE(A) , IRE(A) ratings and SFI authorisation.
- d) FE(A) , TRE(A) , CRE(A) , IRE(A) ratings and SFI authorisation.

Answer ;

- a) FI(A) , TRI(A) , CRI(A) , IRI(A) ratings , SFI and MCCI authorisation.
-

0274. JAR-FCL 1 , Minimum flight experience requirements for the IR

The applicant for an IR(A) shall hold a PPL(A) including a night qualification or a CPL(A) and shall have completed at least;

- a) 50 hours instructional flight time as student-pilot-in-command of aeroplanes.
- b) 50 hours cross country flight time as pilot-in-command in aeroplanes or helicopters of which at least 10 hours shall be in aeroplanes.
- c) 50 hours instructional flight time as student-pilot-in-command of aeroplanes or helicopters of which at least 10 hours shall be in aeroplanes.
- d) 50 hours cross country flight time as pilot of aeroplanes of which at least 10 hours shall be in aeroplanes.

Answer ;

- b) 50 hours cross country flight time as pilot-in-command in aeroplanes or helicopters of which at least 10 hours shall be in aeroplanes.
-

0275. JAR-FCL 3 , Information of the Authority in case of illness

The holder of a pilot's licence shall inform the Authority of any illness , which involves the incapacity to undertake licence related functions for a certain number of days. The number of days is ;

- a) 90.
- b) 60.
- c) 21.
- d) 30.

Answer ;

- c) 21.
-

0276. Lights on and in the vicinity of aerodromes may be turned off , provided that they can be again brought into operation ;

- a) at least 15 minutes before the expected arrival of an aircraft.
- b) at least 30 minutes before the expected arrival of an aircraft.
- c) at least one hour before the expected arrival of an aircraft.
- d) at least 5 minutes before the expected arrival of an aircraft.

Answer ;

- c) at least one hour before the expected arrival of an aircraft.
-

0277. Light signals

A red flare addressed to an aircraft in flight means ;

- a) Return for approach , clearance to land to be expected on final.
- b) Aerodrome unsafe , do not land.
- c) Slow down speed to minimum , give way to other aircraft in the circuit and continue circling.
- d) Not with standing any previous instructions , do not land for the time being.

Answer ;

- d) Not with standing any previous instructions , do not land for the time being.
-

0278. Light signals for aerodrome traffic

A series of red flashes from aerodrome control directed towards an aircraft on ground means ;

- a) Give way to other aircraft taxiing.
- b) Taxi clear of landing area in use.
- c) Stop and taxi back , you are on the wrong taxiway.
- d) Slow down taxi speed.

Answer ;

- b) Taxi clear of landing area in use.
-

0279. Longitudinal separation

The longitudinal separation minimum for 2 aircraft when both are utilizing the same “on track” DME station is ;

- a) 10 NM.
- b) 5 NM.
- c) 20 NM.
- d) 15 NM.

Answer ;

- c) 20 NM.
-

0280. Longitudinal separation minima based on distance using DME for aircraft at the same cruising level and track , provided that each aircraft utilises “on track” DME stations and separation is checked by obtaining simultaneous DME readings , is ;

- a) 40 NM.
- b) 25 NM.
- c) 20 NM.
- d) 10 NM.

Answer ;

- c) 20 NM.
-

0281. Longitudinal separation minima based on time

The minimum longitudinal separation between two aircraft flying on the same track , the preceeding one maintaining a true airspeed of 37 km (20 kt) faster than the succeeding aircraft , departed from the same aerodrome or having reported exactly over the same significant point , is ;

- a) 5 minutes.
- b) 10 minutes.
- c) 2 minutes.
- d) 3 minutes.

Answer ;

- a) 5 minutes .
-

0282. Longitudinal separation minima based on time for aircraft at the same cruising level when navigation aids permit frequent determination of position and speed provided that the preceding aircraft is maintaining a true air speed of 20 kt or more faster than the succeeding aircraft will be ;

- a) 2 minutes.
- b) 5 minutes.
- c) 3 minutes.
- d) 10 minutes.

Answer ;

- b) 5 minutes.
-

0283. Longitudinal separation minima based on time for aircraft at the same cruising level when navigation aids permit frequent determination of position and speed provided that the preceding aircraft is maintaining a true air speed of 40 kt or more faster than the succeeding aircraft will be ;

- a) 2 minutes.
- b) 3 minutes.
- c) 10 minutes.
- d) 5 minutes.

Answer ;

- b) 3 minutes.
-

0284. Longitudinal separation minima based on time for aircraft at the same cruising level when navigation aids permit frequent determination of position and speed will be ;

- a) 10 minutes.
- b) 3 minutes.
- c) 5 minutes.
- d) 15 minutes.

Answer ;

- a) 10 minutes.
-

0285. Low intensity obstacle lights on fixed objects shall be ;

- a) flashing red.
- b) fixed orange.
- c) flashing yellow.
- d) fixed red.

Answer ;

- d) fixed red.
-

0286. Low intensity obstacle lights on mobile objects shall be ;

- a) flashing red or preferably yellow.
- b) fixed red or preferably orange.
- c) fixed red or preferably blue.
- d) flashing blue.

Answer ;

- a) flashing red or preferably yellow.
-

0287. Lower Limit of Controlled Airspace

The lower limit of a Control area/CTA shall be established not less than ;

- a) 1000 ft AGL.
- b) 3000 ft AGL.
- c) 700 ft AGL.
- d) 1500 ft AGL.

Answer ;

- c) 700 ft AGL.
-

0288. Mandatory instruction signs

Information signs other than location signs shall consist of ;

- a) black background with red inscriptions.
- b) black inscriptions on yellow background.
- c) orange background with black inscriptions.
- d) yellow inscriptions on black background.

Answer ;

- b) black inscriptions on yellow background.
-

0289. Member states should introduce specific security measures for the air transport of the following groups of potentially disruptive passengers defined below ;

- a) Deportees and persons in lawful custody only.
- b) Deportees , inadmissible persons and persons in lawful custody.
- c) Deportees and inadmissible persons only.
- d) None of the answers is correct.

Answer ;

- b) Deportees , inadmissible persons and persons in lawful custody.
-

0290. Minimum and maximum age for ATPL holders

According to ICAO Annex 1 , the minimum/maximum age for the holder of an ATPL is ;

- a) 16 and 60 years.
- b) 17 and 59 years.
- c) 21 and 59 years.
- d) 18 and 60 years.

Answer ;

- c) 21 and 59 years.
-

0291. Minimum level IFR

Over high terrain or mountainous areas , where no minimum flight altitude has been established , flights in accordance with IFR shall be flown at a level which is at least ;

- a) 1000 ft above the highest obstacle located within 10 NM of the estimated position of the aircraft.
- b) 2000 ft above the highest obstacle located within 8 km of the estimated position of the aircraft.
- c) 2000 ft above the highest obstacle located within 10 NM of the estimated position of the aircraft.
- d) 1000 ft above the highest obstacle located within 8 km of the estimated position of the aircraft.

Answer ;

- b) 2000 ft above the highest obstacle located within 8 km of the estimated position of the aircraft.
-

0292. Minimum level IFR

When not flying over high terrain or mountainous areas and where no minimum flight altitude has been established , flights in accordance with IFR shall be flown at a level which is at least ;

- a) 2000 ft above the highest obstacle located within 10 NM of the estimated position of the aircraft.
- b) 1000 ft above the highest obstacle located within 8 km of the estimated position of the aircraft.
- c) 1000 ft above the highest obstacle located within 10 NM of the estimated position of the aircraft.
- d) 2000 ft above the highest obstacle located within 8 km of the estimated position of the aircraft.

Answer ;

- b) 1000 ft above the highest obstacle located within 8 km of the estimated position of the aircraft.
-

0293. Minimum Radar Separation on final approach

The minimum radar separation provided between aircraft established on the same localizer course shall be ; (plus additional longitudinal separation as required for wake turbulence)

- a) 2.5 NM.
- b) 2 NM.
- c) 5 NM.
- d) 3 NM.

Answer ;

a) 2.5 NM

0294. Non Radar Wake Turbulence separation minima for departing aircraft.

The minimum separation that shall be applied between a LIGHT or MEDIUM aircraft taking off behind a HEAVY aircraft and both are using the same runway is ;

- a) 1 minute.
- b) 2 minutes.
- c) 3 minutes.
- d) 4 minutes.

Answer ;

b) 2 minutes.

0295. Normal vectors to an ILS final give a 30° intercept. What is the maximum intercept angle according to ICAO Doc 4444 ?

- a) 50°.
- b) 40°.
- c) 45°.
- d) 30°.

Answer ;

c) 45°

0296. OCA

An OCA is referenced to: ;

- a) the Aerodrome Reference Point.
- b) an Aerodrome Elevation.
- c) Mean Sea Level.
- d) the relevant Runway Threshold.

Answer ;

c) Mean Sea Level.

0297. On aerodromes aircraft taxiing on the manoeuvring area of an aerodrome shall give way to ;

- a) other converging aircraft.
- b) aircraft taking off or about to take off.
- c) all vehicles moving on the apron except the “follow me” vehicle.
- d) other vehicles and pedestrians.

Answer ;

b) aircraft taking off or about to take off.

0298. One minute separation may be used between departing aircraft if they are to fly on tracks diverging by at least ;

- a) 30° immediately after take-off.
- b) 25° immediately after take-off.
- c) 45° immediately after take-off.
- d) 15° immediately after take-off.

Answer ;

c) 45° immediately after take-off.

0299. One of the functions ensured by a radar control unit for the provision of approach control service is ;

- a) to conduct surveillance radar approaches.
- b) to apply a reduced vertical separation of 500 feet between IFR flights and VFR flights.
- c) to provide instructions in order to reduce separations minima, if accepted by the pilots.
- d) to apply a horizontal separation less than 5 NM.

Answer ;

a) to conduct surveillance radar approaches.

- 0300.** One of the functions ensured by a radar control unit for the provision of approach control service is ;
- a) to provide instructions to reduce the separation minima.
 - b) to apply a reduced vertical separation of 500 feet between IFR and VFR flights.
 - c) to apply a horizontal separation less than 5 NM.
 - d) to conduct precision radar approach (PAR).

Answer ;

- d) to conduct precision radar approach (PAR).
-

- 0301.** One of the main objectives of ICAO is to ;
- a) approve new international airlines.
 - b) approve the ticket prices set by international airline companies.
 - c) develop principles and technique for international aviation.
 - d) approve new international airlines with jet aircraft.

Answer ;

- c) develop principles and technique for international aviation.
-

- 0302.** Operationally significant changes to the AIP shall be published in accordance with ;
- a) AIRAC procedures and identified by the acronym AIRAC.
 - b) NOTAM procedures and identified by acronym NOTAM followed by a number.
 - c) AIP supplements and shall be clearly identified.
 - d) AIC procedures and identified by the acronym AIC followed by a number.

Answer ;

- a) AIRAC procedures and identified by the acronym AIRAC.
-

- 0303.** Procedures related to communication failure - IFR in VMC
Which procedure do you follow after having experienced a two way communication failure during a flight in accordance with IFR in VMC ?

- a) Maintain the assigned level and route and land at the nearest aerodrome where VMC conditions prevail.
- b) Continue to fly in VMC and return to the aerodrome of departure.
- c) Continue to fly in VMC , land at the nearest suitable aerodrome , report the arrival by the most expeditious means to the appropriate Air Traffic Control unit.
- d) Continue the flight at the assigned level and route , carry out level changes as indicated in the filed ATC flight plan , start the approach to the flight plan destination at the planned ETA.

Answer ;

- c) Continue to fly in VMC , land at the nearest suitable aerodrome , report the arrival by the most expeditious means to the appropriate Air Traffic Control unit.
-

- 0304.** Radar controlled aircraft on intermediate or final approach may be requested to make minor speed adjustments by ATC. These adjustments shall never be more than ;

- a) 25 knots at any stage.
- b) 20 knots and not within 4 NM of threshold.
- c) 15 knots at any stage.
- d) 10 knots and not within 5 NM of threshold.

Answer ;

- b) 20 knots and not within 4 NM of threshold.
-

- 0305.** Radar identification of a departing aircraft can be achieved if a radar blip is observed within a certain distance from the end of the runway. Identification has to be achieved within ;

- a) 1 NM.
- b) 5 NM.
- c) 3 NM.
- d) 2 NM.

Answer ;

- a) 1 NM.
-

- 0306.** Radar Services - Precision Surveillance Radar

At what distance from the end of the runway may a pilot expect that his aircraft can be identified on departure when ATC is equipped with and using PSR ?

- a) 5 NM
- b) 1 NM
- c) 2 NM
- d) 3 NM

Answer ;

- b) 1 NM
-

0307. Radar Services - Radar Separation Minima

When radar capabilities at a given location so permit , the minimum radar separation of 5 NM may be reduced , but shall not be less than ;

- a) 2.0 NM.
- b) 1.5 NM.
- c) 3.0 NM.
- d) 5.0 NM.

Answer ;

- c) 3.0 NM.

0308. Regarding Aerodrome Flight Information Service (AFIS) ;

- a) its only purpose is to relay ATC information to the aircraft in flight or on the ground.
- b) its purpose is to supply ATC services but it is not a state organisation.
- c) it has the same privileges and prerogatives as an ATC organisation but its activity is neither continuous nor regular.
- d) it can only supply limited services to the users and under no circumstances may it supply ATC services.

Answer ;

- d) it can only supply limited services to the users and under no circumstances may it supply ATC services.

0309. Registration mark

Some letter combinations shall not be used in registration marks. Which of the following combinations might be confused with an urgent or distress signal ?

- a) III
- b) XXX
- c) DDD
- d) RCC

Answer ;

- b) XXX

0310. Repetitive flight plans (RPLs) shall not be used for flights operated regularly on the same day(s) of consecutive weeks and ;

- a) on at least ten occasions or every day over a period of at least ten consecutive days.
- b) on at least ten occasions or every day over a period of at least 20 consecutive days.
- c) on at least 20 occasions.
- d) on at least 20 days consecutively.

Answer ;

- a) on at least ten occasions or every day over a period of at least ten consecutive days.

0311. Required Navigation Performance (RNP) shall be prescribed ;

- a) by regional air navigation agreements.
- b) by states but not on the basis of regional air agreements.
- c) by ICAO on the basis of regional air navigation agreements.
- d) by states on the basis of regional air navigation agreements.

Answer ;

- d) by states on the basis of regional air navigation agreements.

0312. Right of way - Avoidance of collisions

When two aircraft are approaching head-on or approximately so and there is a danger of collision , each shall ;

- a) alter its heading to the left.
- b) alter its heading to the right.
- c) turn , climb or descent as appropriate in order to avoid.
- d) switch on all available lights in order to warn the other traffic.

Answer ;

- b) alter its heading to the right.

0313. Right of way - Converging

Two aircraft are approaching each other in a controlled airspace class D in VMC at approximately the same level on converging courses. Aircraft "A" is flying under IFR , Aircraft "B" is flying under VFR. Who has the right of way ?

- a) Aircraft "B" regardless of the direction from which "A" is approaching.
- b) Aircraft "A" regardless of the direction from which "B" is approaching.
- c) Aircraft "A" , providing it has "B" on its right.
- d) Aircraft "B" , providing it has "A" on its right.

Answer ;

- d) Aircraft "B" , providing it has "A" on its right.

0314. Runway edge lights excepted in the case of a displaced threshold shall be ;

- a) fixed lights showing variable white or yellow.
- b) flashing white.
- c) fixed lights showing variable white.
- d) fixed lights , white or yellow colour.

Answer ;

- a) fixed lights showing variable white or yellow
-

0315. Runway end lights shall be ;

- a) fixed unidirectional lights showing white in the direction of the runway.
- b) fixed lights showing variable white.
- c) fixed unidirectional lights showing red in the direction of the runway.
- d) fixed lights showing variable red.

Answer ;

- c) fixed unidirectional lights showing red in the direction of the runway.
-

0316. Runway-lead-in lighting should consist ;

- a) of group of at least three white lights flashing in sequence towards the runway.
- b) of an arbitrary amount of green lights.
- c) always of a straight row of lights towards the runway.
- d) of flashing lights only.

Answer ;

- a) of group of at least three white lights flashing in sequence towards the runway.
-

0317. Runway threshold identification lights , when provided , should be ;

- a) flashing white.
- b) flashing green.
- c) fixed green.
- d) fixed white.

Answer ;

- a) flashing white.
-

0318. Runway threshold lights shall be ;

- a) fixed unidirectional lights showing white in the direction of approach to the runway.
- b) fixed unidirectional lights showing green in the direction of approach to the runway.
- c) fixed lights green colours.
- d) fixed lights showing green or white colours.

Answer ;

- b) fixed unidirectional lights showing green in the direction of approach to the runway.
-

0319. Search and Rescue

The colour of droppable containers and streamers for food and water is ;

- a) red.
- b) blue.
- c) yellow.
- d) black.

Answer ;

- b) blue.
-

0320. Search and Rescue

The colour of droppable containers and streamers for medical supply and first aid equipment is ;

- a) black.
- b) red.
- c) blue.
- d) yellow.

Answer ;

- b) red.
-

0321. Search and Rescue

The unit responsible for promoting efficient organisation of search and rescue service is the ;

- a) Flight Information Centre.
- b) Alerting Centre.
- c) Area Control Centre.
- d) Rescue Co-ordination Centre.

Answer ;

- d) Rescue Co-ordination Centre.

0322. Search and Rescue - Organisation

The unit responsible for promoting efficient organisation of search and rescue service in each SAR region is the ;

- a) Flight Information Centre.
- b) Alerting Centre.
- c) Rescue Co-ordination Centre.
- d) Area Control Centre.

Answer ;

c) Rescue Co-ordination Centre.

0323. Search and Rescue signals

The ground - air visual code for "REQUIRE ASSISTANCE" is ;

- a) V.
- b) Y.
- c) N.
- d) X.

Answer ;

a) V.

0324. Search and Rescue signals

The ground - air visual code for "REQUIRE MEDICAL ASSISTANCE" is ;

- a) X.
- b) V.
- c) N.
- d) Y.

Answer ;

a) X.

0325. Search and Rescue signals

The ground - air visual signal code for use by survivors on ground to indicate "AFIRMATIVE" is ;

- a) X.
- b) Y.
- c) V.
- d) N.

Answer ;

b) Y.

0326. Search and Rescue signals

The ground - air visual signal code for use by survivors on ground to indicate "NEGATIVE" is ;

- a) V.
- b) N.
- c) X.
- d) Y.

Answer ;

b) N.

0327. Search and Rescue signals - Droppable containers

Containers or packages containing survival equipment for dropping should have the general nature of the content indicated by a colour code. The colour for blankets and protective clothing is ;

- a) red.
- b) yellow.
- c) black.
- d) blue.

Answer ;

b) yellow.

0328. Search and Rescue signals - Droppable containers

Containers or packages containing survival equipment for dropping should have the general nature of the content indicated by a colour code. The colour of droppable containers and streamers for food and water is ;

- a) blue.
- b) black.
- c) yellow.
- d) red.

Answer ;

a) blue.

0329. Search and Rescue signals - Droppable containers

Containers or packages containing survival equipment for dropping should have the general nature of the content indicated by a colour code. The colour of droppable containers and streamers for medical supply is ;

- a) black.
- b) yellow.
- c) red.
- d) blue.

Answer ;

- c) red.

0330. Select the acronym corresponding to the following definition ; a special NOTAM series notifying , by means of a specific format , an important change for the aircraft operations , due to a volcano activity , a volcano eruption or a volcanic ash cloud ;

- a) GVATAM
- b) VULTAM
- c) ASHTAM
- d) NAVTAM

Answer ;

- c) ASHTAM

0331. Separation - VMC and own separation

The “Clearance to fly maintaining own separation while in visual meteorological conditions” may be given by the appropriate ATS authority. This has to be requested by the pilot of a controlled flight and has to be agreed by the pilot of the other aircraft. The conditions are ;

- a) Airspace Class C , VMC , hours of daylight.
- b) Airspace Class B , C , D and E , VMC.
- c) Airspace Class D and E , VMC , hours of daylight.
- d) Airspace Class C , D , VMC.

Answer ;

- c) Airspace Class D and E , VMC , hours of daylight.

0332. Separation in the vicinity of aerodromes - Timed approaches

A “Timed Approach Procedure” may be utilized as necessary in order to expedite the approaches of a number of arriving aircraft. This will be obtained by requesting aircraft to ;

- a) notify the time when passing a specified point.
- b) pass a specified point inbound at the previously notified time.
- c) keep distance and time equal between aircraft in the approach.
- d) maintain a specified airspeed during the approach procedure.

Answer ;

- b) pass a specified point inbound at the previously notified time.

0333. Separation methods and minima - Essential traffic

A VFR flight constitutes essential traffic to other VFR flights , when operating in controlled airspace classified as ;

- a) B and C.
- b) B , C , D and E.
- c) B , C and D.
- d) B.

Answer ;

- d) B.

0334. Separation methods and minima - Essential traffic information

Essential traffic is ;

- a) Controlled Traffic separated from other controlled traffic with the prescribed separation minima.
- b) Uncontrolled IFR flights separated from uncontrolled VFR flights within advisory airspace.
- c) Controlled Traffic not separated from another controlled traffic with the prescribed separation minima.
- d) Controlled IFR flights separated from uncontrolled flights within advisory airspace.

Answer ;

- c) Controlled Traffic not separated from another controlled traffic with the prescribed separation minima.

0335. Separation methods and minima - General

What are the controlled traffic separation methods applied by ATC ?

- a) Vertical and horizontal separation.
- b) Time separation and track separation.
- c) Composite separation.
- d) Vertical , horizontal and angular separation.

Answer ;

- a) Vertical and horizontal separation.

0336. Separation methods and minima - Vertical separation

Above flight level FL 290 the Vertical Separation Minimum (VSM) between aircraft flying in the same direction is ;

- a) 4000 feet.
- b) 3000 feet.
- c) 1500 feet.
- d) 2000 feet.

Answer ;

- a) 4000 feet.
-

0337. Separation methods and minima - Vertical separation

Above flight level FL 290 the Vertical Separation Minimum (VSM) shall be ;

- a) 4000 feet.
- b) 3000 feet.
- c) 1500 feet.
- d) 2000 feet.

Answer ;

- d) 2000 feet.
-

0338. Separation methods and minima - Vertical separation

The Vertical Separation Minimum (VSM) for flights in accordance with IFR within controlled airspace above FL 290 is ;

- a) 4000 feet (1200 m).
- b) 2000 feet (600 m).
- c) 1000 feet (300 m).
- d) 500 feet (150 m).

Answer ;

- b) 2000 feet (600 m).
-

0339. Separation methods and minima - Vertical separation

The Vertical Separation Minimum (VSM) for flights in accordance with IFR within controlled airspace below FL 290 is ;

- a) 2000 feet (600 m).
- b) 2500 feet (750 m).
- c) 1000 feet (300 m).
- d) 500 feet (150 m).

Answer ;

- c) 1000 feet (300 m).
-

0340. Signal from a signalman to an aircraft

A signalman requests the pilot engage brakes with the following signal ;

- a) Raise arm and hand , with fingers extended , horizontally in front of body , then clench fist.
- b) Horizontally moving his hands , fingers extended , palms towards ground.
- c) Crossing arms extended above his head.
- d) Arms down , palms facing inwards , moving arms from extended position inwards.

Answer ;

- a) Raise arm and hand , with fingers extended , horizontally in front of body , then clench fist.
-

0341. Special VFR flights may the authorised to operate locally within a control zone when the ground visibility is not less than 1500 metres , even when the aircraft is not equipped with a functioning radio receiver within class ;

- a) C , D and E airspace.
- b) E airspace.
- c) D and E airspace.
- d) D airspace.

Answer ;

- b) E airspace.
-

0342. SSR - Special codes

ATC has assigned you the transponder code 5320. In case of loosing two way radio communication , you have to squawk ;

- a) Mode A Code 7700.
- b) Mode A Code 5320.
- c) Mode A Code 7500.
- d) Mode A Code 7600.

Answer ;

- d) Mode A Code 7600.
-

0343. SSR - Transponder
Pilots shall not SQUAK IDENT unless they ;
- a) operate within controlled airspace.
 - b) are requested by ATC.
 - c) operate a transponder with Mode C.
 - d) operate outside controlled airspace.

Answer ;

- b) are requested by ATC.
-

0344. SSR - Transponder
When acknowledging mode/code setting instructions , pilots shall ;
- a) read back the mode and code to be set.
 - b) read back the code to be set and SQUAK IDENT.
 - c) use the word ROGER.
 - d) use the word WILCO.

Answer ;

- a) read back the mode and code to be set.
-

0345. SSR - Transponder
When an aircraft carries a serviceable transponder , the pilot shall operate the transponder ;
- a) at all times during flight , regardless of whether the aircraft is within or outside airspace where SSR is used for ATS purposes.
 - b) only when the aircraft is flying within airspace where SSR is used for ATS purposes.
 - c) only when the aircraft is flying within controlled airspace.
 - d) only when directed by ATC.

Answer ;

- a) at all times during flight , regardless of whether the aircraft is within or outside airspace where SSR is used for ATS purposes.
-

0346. SSR - Transponder
When an aircraft is subjected to unlawful interference , the pilot-in-command shall indicate the situation by setting the transponder to Mode A , Code ;
- a) 7700.
 - b) 7600.
 - c) 7000.
 - d) 7500.

Answer ;

- d) 7500.
-

0347. SSR - Transponder
When the aircraft carries serviceable Mode C transponder , the pilot shall continuously operate this mode ;
- a) regardless of ATC instructions.
 - b) unless otherwise directed by ATC.
 - c) only when the aircraft is flying within controlled airspace.
 - d) only when directed by ATC.

Answer ;

- b) unless otherwise directed by ATC.
-

0348. Standard Instrument Departure Procedures - Straight Departures
A straight departure is one in which the initial departure track does not deviate from the alignment of the extended runway centre line by more than ;
- a) 30°.
 - b) 15°.
 - c) 45°.
 - d) 12.5°.

Answer ;

- b) 15°.
-

0349. Subject to conditions specified by the appropriate ATS authority , a radar controller may request radar-controlled aircraft to adjust their speed when established on intermediate and final approach. This speed adjustment should not be more than ;
- a) +/- 15 kt.
 - b) +/- 20 kt.
 - c) +/- 10 kt.
 - d) +/- 8 kt.

Answer ;

- b) +/- 20 kt.

0350. Taxiway centre line lights other than an exit taxiway shall be ;

- a) **fixed lights showing green.**
- b) fixed lights showing white.
- c) fixed lights showing blue.
- d) fixed lights showing yellow.

Answer ;

- a) **fixed lights showing green.**
-

0351. Taxiway edge lights shall be ;

- a) flashing showing blue.
- b) fixed showing yellow.
- c) fixed showing green.
- d) **fixed showing blue.**

Answer ;

- d) **fixed showing blue.**
-

0352. Temporary changes of “long duration” and information of “short duration” with extensive text and/or graphics are published as AIP supplements. It is considered a long duration ;

- a) six months or longer.
- b) **three months or longer.**
- c) one year or longer.
- d) two months or longer.

Answer ;

- b) **three months or longer.**
-

0353. The abbreviation PAPI stands for ;

- a) Precision Approach Power Index.
- b) **Precision Approach Path Indicator.**
- c) Precision Approach Power Indicator.
- d) Precision Approach Path Index.

Answer ;

- b) **Precision Approach Path Indicator.**
-

0354. The aerodrome category for rescue and fire fighting is based on ;

- a) **the over-all length of the longest aeroplane normally using the aerodrome and its maximum fuselage width.**
- b) the over-all length of the longest aeroplane normally using the aerodrome and its maximum fuselage weight.
- c) the over-all length of the longest aeroplane.
- d) the longest aeroplane maximum width only

Answer ;

- a) **the over-all length of the longest aeroplane normally using the aerodrome and its maximum fuselage width.**
-

0355. The “Aerodrome Reference Code” is a code composed of two elements which are related to the aeroplane performance characteristics and dimensions. These elements are a combination of a number and a letter as in the example under listed ;

- a) 4F.
- b) 5E.
- c) **2B.**
- d) 6D.

Answer ;

- c) **2B.**
-

0356. The age of an applicant for a commercial pilot licence shall not be less than ;

- a) 17 years of age.
- b) 16 years of age.
- c) **18 years of age.**
- d) 21 years of age.

Answer ;

- c) **18 years of age.**
-

0357. The air traffic control unit has reported “radar contact” , what does that mean to the pilot ?

- a) **The radar identity of the aircraft has been established.**
- b) The aircraft is subject to positive control.
- c) The pilot does not have to follow up the position of the aircraft.
- d) Position reports may be omitted.

Answer ;

- a) **The radar identity of the aircraft has been established.**

0358. The aircraft commander , when he has reasonable grounds to believe that a person has committed or is about to commit , on board the aircraft , an offence against penal law ;

- a) may require the assistance of passengers to restrain such person.
- b) may request such person to disembark.
- c) may not require or authorise the assistance of other crew members.
- d) may deliver such person to the competent authorities.

Answer ;

- d) may deliver such person to the competent authorities.
-

0359. The Alerting Service is provided by ;

- a) the Area Control Centres.
- b) the ATC unit responsible for the aircraft at that moment , when it is provided with 121.5 MHz.
- c) the ATS unit responsible for the aircraft at that moment.
- d) only by ATC units.

Answer ;

- c) the ATS unit responsible for the aircraft at that moment.
-

0360. The applicant for an Airline Transport Pilot Licence shall have completed in aeroplanes not less than hours of cross-country flight time , of which not less than hours shall be as pilot-in command or co-pilot performing , under the supervision of the pilot in command , the duties and functions of a pilot in command , provided that the method of supervision employed is acceptable to the licensing authority. The state above hours are respectively ;

- a) 200 hours and 75 hours
- b) 250 hours and 10 hours
- c) 200 hours and 100 hours
- d) 150 hours and 75 hours

Answer ;

- c) 200 hours and 100 hours
-

0361. The applicant to exercise the functions of an Instrumental Flight Rating in aeroplanes shall prove , according to Annex I , PERSONNEL LICENSING , his/her capability to pilot such aircraft only by instrumental rules and an engine

- a) multi-engine / inoperative or simulated inoperative.
- b) amphibious / inactive or simulated inactive.
- c) land / inactive.
- d) single-engine / inactive.

Answer ;

- a) multi-engine / inoperative or simulated inoperative.
-

0362. The ASHTAM provides information on the status of activity of a volcano when a change in its activity is , or is expected to be of operational significance. This information is provided using the volcano level of colour code. When volcanic eruption in progress or volcano dangerous , eruption likely , with ash plume/cloud is reported above FL 250 or is expected to rise above FL 250 , the level of alert colour code is ;

- a) YELLOW.
- b) GREEN.
- c) RED.
- d) ORANGE.

Answer ;

- c) RED.
-

0363. The ATIS broadcast message should , whenever practicable , not exceed ;

- a) 3 minutes.
- b) 30 seconds.
- c) 2 minutes.
- d) 1 minute.

Answer ;

- b) 30 seconds.
-

0364. The closure of a runway for a year , because of maintenance , will be published ;

- a) only in AIP.
- b) in NOTAM and AIP , inclusive Supplement.
- c) NOTAM , AIP and MAL.
- d) only in NOTAM.

Answer ;

- b) in NOTAM and AIP , inclusive Supplement.
-

0365. The colour identification of the contents of droppable containers and packages containing survival equipment should take the form of coloured streamers according to the following code ;

- a) Blue for medical supplies and first aid equipment.
- b) Red for food and water.
- c) Black for food and water.
- d) Yellow for blankets and protective clothing.

Answer ;

- d) Yellow for blankets and protective clothing.

0366. The Convention defining the duties of the parties relating to the carriage of passengers , baggage and cargo and the liability of the carriers and extent of compensation for damage is the ;

- a) Convention for the unification of certain rules for international carriage by air , Montreal 1999.
- b) Convention on Jurisdiction and the Enforcement of Judgements in Civil and Commercial Air Transport , Brussels 1968.
- c) Convention on Offences and Certain Other Acts Committed on Board Aircraft , Tokyo 1963.
- d) United Nations Conference on the Law and Treaties , Vienna 1969.

Answer ;

- a) Convention for the unification of certain rules for international carriage by air , Montreal 1999.

0367. The Convention of Rome 1933/1952 for the Unification of certain Rules Relating to Damage caused by Aircraft was established in order to define the liability in case of damage ;

- a) to third parties on the surface.
- b) to other aircraft in case of midair collision.
- c) to other aircraft while operating on ground.
- d) caused by Dangerous Goods that have been carried by an aircraft.

Answer ;

- a) to third parties on the surface.

0368. The convention on offences and certain acts committed on board aircraft , is ;

- a) the convention of Chicago.
- b) the convention of Rome.
- c) the convention of Tokyo.
- d) the convention of Paris.

Answer ;

- c) the convention of Tokyo.

0369. The convention signed by the states and moved by a desire to ensure adequate compensation for persons who suffer damage caused on the surface by foreign aircraft is ;

- a) the Paris Convention.
- b) the Rome Convention.
- c) the Warsaw Convention.
- d) the Tokyo Convention.

Answer ;

- b) the Rome Convention.

0370. The convention which deals with offences against penal law , is ;

- a) the convention of Tokyo.
- b) the convention of Warsaw.
- c) the convention of Madrid.
- d) the convention of Rome.

Answer ;

- a) the convention of Tokyo.

0371. The criterion which shall be used to determine that a specific level is occupied by an aircraft shall be , (except that appropriate ATS authorities may specify a smaller criterion) ;

- a) +/- 200 ft.
- b) +/- 150 ft.
- c) +/- 250 ft.
- d) +/- 300 ft.

Answer ;

- d) +/- 300 ft.

0372. The documents for entry and departure of aircraft ;
- a) are accepted in hand-written block lettering in ink.
 - b) has to be typewritten.
 - c) are accepted at the contracting state discretion.
 - d) has to be typewritten or produced by electronic data processing techniques.

Answer ;

- a) are accepted in hand-written block lettering in ink.
-

0373. The duration of the period of currency of a medical assessment shall begin on the date ;

- a) the licence is issued or renewed.
- b) the medical assessment is issued.
- c) the licence is delivered to the pilot.
- d) the licence is issued or validated.

Answer ;

- b) the medical assessment is issued.
-

0374. The EAT has to be transmitted to the pilot as soon as possible , in case the expected delay is ;

- a) 15 minutes or more.
- b) 10 minutes.
- c) 20 minutes.
- d) 5 minutes or more.

Answer ;

- b) 10 minutes.
-

0375. The “estimated total time” in block 16 of a VFR flight plan is the estimated time ;

- a) required by the aircraft from the moment it moves by its own power until it stops at the end of the flight (block time).
- b) required by the aircraft from take-off to arrive overhead the destination airport.
- c) required by the aircraft from brake release at take-off until landing.
- d) of endurance at cruising power taking into account pressure and temperature on that day.

Answer ;

- b) required by the aircraft from take-off to arrive overhead the destination airport.
-

0376. The first freedom of the air is ;

- a) the opportunity to operate a commercial flight with passengers on board between two states.
- b) the right to board passengers from the state where the aircraft is registered and to fly to an other state.
- c) the right to overfly another State without landing.
- d) the right to land for a technical stop.

Answer ;

- c) the right to overfly another State without landing.
-

0377. The following minimum radar separation shall be provided between aircraft on the same localizer with additional longitudinal separation as required for wake turbulence ;

- a) 3 NM.
- b) 5 NM.
- c) 2 NM.
- d) 2.5 NM.

Answer ;

- a) 3 NM.
-

0378. The height of the marks on the fuselage (or equivalent structure) and on the vertical tail surfaces of heavier than air aircraft shall be ;

- a) at least between 20 centimetres and 40 centimetres.
- b) at least 20 centimetres.
- c) at least 40 centimetres.
- d) at least 30 centimetres.

Answer ;

- d) at least 30 centimetres.
-

0379. The height of the marks under the wings of heavier than air aircraft shall be ;

- a) at least 75 centimetres.
- b) at least 50 centimetres.
- c) at least 60 centimetres.
- d) at least between 40 centimetres and 50 centimetres.

Answer ;

- b) at least 50 centimetres.

0380. The holder of a pilot licence should inform the Authority of any illness which they are suffering which involves incapacity to undertake those functions to which the licence relates throughout a period of a certain number of days or more. The number of days is ;

- a) 21.
- b) 30.
- c) 60.
- d) 90.

Answer ;

- a) 21.

0381. The holder of a pilot licence when acting as co-pilot of an aircraft required to be operated with a co-pilot , shall be entitled to be credit with not more than ;

- a) 50 % of the co-pilot flight time towards the total flight time required for a higher grade of pilot licence.
- b) 60 % of the co-pilot flight time towards , the total flight time required for a higher grade of a pilot licence.
- c) 40 % of the co-pilot flight time towards , the total flight time required for a higher grade of a pilot licence.
- d) 100 hours of flying time required for a higher grade of a pilot licence.

Answer ;

- a) 50 % of the co-pilot flight time towards the total flight time required for a higher grade of pilot licence.

0382. The holder of a pilot licence when acting as co-pilot performing under the supervision of the pilot in command the functions and duties of a pilot in command shall be entitled to be credit ;

- a) in full with his flight but not more than 300 hours towards the total time required for a higher grade of pilot licence.
- b) 50% of his flight time towards the total time required for higher grade of pilot licence.
- c) the flight time towards the total time required for higher grade of pilot licence in accordance with the requirements of the licensing authority.
- d) in full with his flight time towards the total time required for higher grade of pilot licence.

Answer ;

- d) in full with his flight time towards the total time required for higher grade of pilot licence.

0383. The ICAO Annex 17 comprise rules in order to establish security measures for passengers ;

- a) and baggage.
- b) checked baggage , cargo and other goods , access control and airport design.
- c) cabin baggage , checked baggage , cargo and other goods , access control and airport design.
- d) checked baggage , cargo and other goods.

Answer ;

- c) cabin baggage , checked baggage , cargo and other goods , access control and airport design.

0384. The ICAO annex which deals with entry and departure of cargo and other articles on international flights is ;

- a) Annex 8.
- b) Annex 16.
- c) Annex 9.
- d) Annex 15.

Answer ;

- c) Annex 9.

0385. The ICAO annex which deals with entry and departure of persons and their baggage in international flights is ;

- a) Annex 6.
- b) Annex 15.
- c) Annex 9.
- d) Annex 8.

Answer ;

- c) Annex 9.

0386. The identification of each prohibited , restricted and danger area shall be composed by ;

- a) the nationality letters for location indicators assigned to the state or territory , followed the letters P , R and D and figures.
- b) the letters P (Prohibited) , R (Restricted) and D (Dangerous) for the area concerned and figures.
- c) the letters P (Prohibited) , R (Restricted) and D (Dangerous) followed by figures.
- d) the nationality letters for the location indicators assigned to the state , followed by P , R and D.

Answer ;

- a) the nationality letters for location indicators assigned to the state or territory , followed the letters P , R and D and figures.

0387. The International Civil Aviation Convention Annex containing standards and recommended practices for Personnel Licensing is ;

- a) [Annex 1.](#)
- b) Annex 12.
- c) Annex 11.
- d) Annex 2.

Answer ;

- a) [Annex 1.](#)

0388. The International Civil Aviation Organisation (ICAO) establishes ;

- a) aeronautical standards adopted by all states.
- b) proposals for aeronautical regulations in the form of 18 annexes.
- c) standards and recommended practices applied without exception by all states , signatory to the Chicago Convention.
- d) [standards and recommended international practices for contracting member states.](#)

Answer ;

- d) [standards and recommended international practices for contracting member states.](#)

0389. The International Civil Aviation Organisation (ICAO) was established by the international convention of ;

- a) [Chicago.](#)
- b) Montreal.
- c) Warsaw.
- d) the Hague.

Answer ;

- a) [Chicago.](#)

0390. The international convention defining rules relative to the responsibilities of international air carriers for the carriage of passengers , baggage and freight is the ;

- a) [Warsaw Convention.](#)
- b) Tokyo Convention.
- c) Hague Convention.
- d) Montreal Convention.

Answer ;

- a) [Warsaw Convention.](#)

0391. The letter “L” is written in the wake turbulence box of a flight plan form when the maximum certified take-off weight of an aircraft is less than or equal to ;

- a) 14.000 kg.
- b) 20.000 kg.
- c) [7.000 kg.](#)
- d) 5.700 kg for aeroplanes and 2.700 kg for helicopters.

Answer ;

- c) [7.000 kg.](#)

0392. The licensing authority shall determine whether experience as pilot under instruction in a synthetic flight trainer which it has approved , is acceptable as part of the total flight time of 1500 hours. Credit for such experience shall be limited to a maximum of ;

- a) 100 hours of which not more than 20 hours shall have been acquired in a basic instrument flight trainer.
- b) [100 hours , of which not more than 25 hours shall have been acquired in a flight procedure trainer or basic instrument flight trainer.](#)
- c) 100 hours of which not more than 15 hours shall have been acquired in a flight procedure trainer or basic instrument flight trainer.
- d) 75 hours of which not more than 20 hours shall have been acquired in a flight procedure trainer or basic instrument flight trainer.

Answer ;

- b) [100 hours , of which not more than 25 hours shall have been acquired in a flight procedure trainer or basic instrument flight trainer.](#)

0393. The light shown by an “Aerodrome Identification Beacon” at a land aerodrome shall be ;

- a) white and green colour identification given by Morse Code.
- b) [green colour identification given by Morse Code.](#)
- c) blue colour identification given by Morse Code.
- d) white colour identification given by Morse Code.

Answer ;

- b) [green colour identification given by Morse Code.](#)
-

0394. The loading limitations shall include ;

- a) all limiting mass , mass distributions and centres of gravity.
- b) all limiting mass and centres of gravity.
- c) all limiting mass , centres of gravity position , mass distributions and floor loading.
- d) all limiting mass , centres of gravity position and floor loading.

Answer ;

- c) all limiting mass , centres of gravity position , mass distributions and floor loading.
-

0395. The longitudinal separation minima based on distance using DME , and each aircraft “on track” uses DME stations , is ;

- a) 20 NM when the leading aircraft maintains a true airspeed of 20 kt or more faster than the succeeding aircraft.
- b) 5 NM.
- c) 20 NM.
- d) 10 NM.

Answer ;

- c) 20 NM.
-

0396. The longitudinal separation minima based on DME , and each aircraft “on track” uses DME stations , is ;

- a) 20 NM provided that the leading aircraft maintains a true airspeed of 10 kt or more faster than the succeeding aircraft.
- b) 10 NM provided that the leading aircraft maintains a true airspeed of 20 kt or more faster than the succeeding aircraft.
- c) 10 NM provided that the leading aircraft maintains a true airspeed of 10 kt or more faster than the succeeding aircraft.
- d) 10 NM provided that the leading aircraft maintains a true airspeed of 40 kt or more faster than the succeeding aircraft.

Answer ;

- b) 10 NM provided that the leading aircraft maintains a true airspeed of 20 kt or more faster than the succeeding aircraft.
-

0397. The longitudinal separation minima based on time between aircraft at same cruising level where navigation aids permit frequent determination of position and speed and the preceding aircraft is maintaining a true airspeed of 20 kt or more faster than the succeeding aircraft , is ;

- a) 5 minutes.
- b) 10 minutes.
- c) 3 minutes.
- d) 15 minutes.

Answer ;

- a) 5 minutes.
-

0398. The longitudinal separation minima based on time between aircraft at same cruising level where navigation aids permit frequent determination of position and speed and the preceding aircraft is maintaining a true airspeed of 40 kt or more faster than the succeeding aircraft , is ;

- a) 5 minutes.
- b) 6 minutes.
- c) 10 minutes.
- d) 3 minutes.

Answer ;

- d) 3 minutes.
-

0399. The longitudinal separation minima based on time between aircraft at same cruising level where navigation aids permit frequent determination of position and speed , is ;

- a) 3 minutes.
- b) 15 minutes.
- c) 10 minutes.
- d) 5 minutes.

Answer ;

- c) 10 minutes.
-

0400. The longitudinal separation minima between aircraft departed from the same aerodrome and following the same track , and the preceding aircraft is maintaining a true airspeed of 20 kt or more faster than the succeeding aircraft , is ;

- a) 2 minutes.
- b) 5 minutes.
- c) 3 minutes.
- d) 10 minutes.

Answer ;

- b) 5 minutes.

0401. The longitudinal separation minima between aircraft departed from the same aerodrome and following the same track , and the preceding aircraft is maintaining a true airspeed of 40 kt or more faster than the succeeding aircraft , is ;

- a) 3 minutes.
- b) 5 minutes.
- c) 10 minutes.
- d) 8 minutes.

Answer ;

- a) 3 minutes.

0402. The minimum age for obtaining a PPL is ;

- a) 17 years.
- b) 16 years.
- c) 21 years.
- d) 18 years.

Answer ;

- a) 17 years.

0403. The minimum radar separation to be provided to aircraft established on the localizer course shall be ;

- a) 5.0 NM between aircraft on the same localizer course.
- b) 3.0 NM between aircraft on the same localizer course.
- c) 2.0 NM between aircraft on the same localizer course.
- d) 3.0 NM between aircraft on adjacent localizer course.

Answer ;

- b) 3.0 NM between aircraft on the same localizer course.

0404. The movement area of an airfield , the adjacent lands and buildings or the parts of them with controlled access is called ;

- a) Terminal.
- b) Manoeuvring area.
- c) Aeronautical part.
- d) Security program.

Answer ;

- c) Aeronautical part.

0405. The national civil aviation security programme shall be established by ;

- a) ECAC.
- b) each contracting state.
- c) ICAO.
- d) ICAO and other organisations including the contracting state concerned.

Answer ;

- b) each contracting state.

0406. The objectives of ICAO was ratified by the ;

- a) Geneva convention 1936.
- b) Warsaw convention 1929.
- c) Chicago convention 1944.
- d) Geneva convention 1948.

Answer ;

- c) Chicago convention 1944.

0407. The obligation of a carrier to transport any person away from the territory of a Contracting State shall terminate from the moment such person has been definitely admitted in other Contracting State of destination.

- a) The obligation is for the Contracting State of the operator.
- b) The obligation of the operator terminates as soon as the person leaves the aeroplane.
- c) The stated above is correct.
- d) The operator has no obligation.

Answer ;

- c) The stated above is correct.

0408. The “PAPI” shall consist of ;

- a) two wing bars of 4 sharp transition multi-lamp or paired units equally spaced.
- b) a wing bar of 4 sharp transition multi-lamp or paired units equally spaced.**
- c) two wing bars of 6 sharp transition multi-lamp or paired units equally spaced.
- d) a wing bar of 2 sharp transition multi-lamp equally spaced.

Answer ;

- b) a wing bar of 4 sharp transition multi-lamp or paired units equally spaced.**
-

0409. The phases related to an aircraft in emergency or believed in emergency are: ;

- a) uncertainty phase , urgency phase , distress phase.
- b) uncertainty phase , alert phase , distress phase.**
- c) uncertainty phase , distress phase , urgency phase.
- d) uncertainty phase , alert phase , distress phase and urgency phase.

Answer ;

- b) uncertainty phase , alert phase , distress phase.**
-

0410. The pilot in command of an aircraft ;

- 1. must comply immediately to all instructions received from ATC.
- 2. is responsible only if he is the “pilot flying”.
- 3. may deviate from air regulations for safety reasons.
- 4. may be exempt from air regulations in order to comply to an ATC instruction.
- 5. may ask for the modification of an unsatisfactory clearance.

Which of the following combinations contains all of the correct statements ?

- a) 3 , 4 , 5.
- b) 3 , 5.**
- c) 2 , 3 , 5.
- d) 1 , 4.

Answer ;

- b) 3 , 5.**
-

0411. The planned cruising speed for the first leg or all of the cruising portion of the flight must be entered in the speed box of a flight plan form. This speed is the ;

- a) true air speed (TAS).**
- b) indicated air speed (IAS).
- c) estimated ground speed (G/S).
- d) true air speed at 65% power.

Answer ;

- a) true air speed (TAS).**
-

0412. The prescribed re-examination of a licence holder operating in an area distant from designated medical examination facilities may be deferred at the discretion of the licence authority , provided that such deferment shall only be made as an exception and shall not exceed ;

- a) a single period of three month in the case of a flight crew member of an aircraft engaged in commercial operations.
- b) a single period of six month in the case of a flight crew member of an aircraft engaged in non-commercial operations.**
- c) two consecutive periods each of six month in the case of a flight crew member of an aircraft engaged in non-commercial operations.
- d) two consecutive periods each of three month in the case a flight crew member of an aircraft engaged in non-commercial operations.

Answer ;

- b) a single period of six month in the case of a flight crew member of an aircraft engaged in non-commercial operations.**
-

0413. The primary duty provided by a radar unit is ;

- a) to assist aircraft due to failure of airborne equipment.
- b) to assist aircraft where navigation appears unsatisfactory.
- c) to assist aircraft on the location storms.
- d) to provide radar separation.**

Answer ;

- d) to provide radar separation.**
-

0414. The privileges of the holder of a commercial pilot licence-aeroplane shall be ;
- a) none of the answers are correct.
 - b) to act as pilot in command in any aeroplane engaged in commercial air transportation.
 - c) to act as pilot-in command in any aeroplane engaged in operations other than commercial air transportation.
 - d) to act as pilot in command in any aeroplane certificate for single pilot operation other than in commercial air transportation.

Answer ;

- c) to act as pilot-in command in any aeroplane engaged in operations other than commercial air transportation.

0415. The proficiency check of a pilot took place the 15th of April. The validity of the previous proficiency check was the 30th of June. The period of the new proficiency check can be and can't exceed ;

- a) 15th of October the same year.
- b) 30th of October the same year.
- c) 30th of April the following year.
- d) 31th of December the same year.

Answer ;

- d) 31th of December the same year.

0416. The radar controller shall not request the pilot to adjust the speed where the aircraft has passed ;

- a) 3 NM from the threshold on final approach.
- b) 5 NM from the threshold on final approach.
- c) 2 NM from the threshold on final approach.
- d) 4 NM from the threshold on final approach.

Answer ;

- d) 4 NM from the threshold on final approach.

0417. The radar separation minimum may be reduced but not below ;

- a) 1.5 NM.
- b) 2.0 NM.
- c) 3.0 NM.
- d) 5.0 NM.

Answer ;

- c) 3.0 NM.

0418. The Rome Convention and later amendments deals with ;

- a) regulation of transportation of dangerous goods.
- b) offences and certain other acts committed on board aircraft.
- c) damage caused by any aircraft to third parties on the surface.
- d) damage caused by foreign aircraft to third parties on the surface.

Answer ;

- d) damage caused by foreign aircraft to third parties on the surface.

0419. The runway edge lights shall be ;

- a) blue.
- b) white.
- c) green.
- d) red.

Answer ;

- b) white.

0420. The second freedom of the air is the ;

- a) right to "cabotage" traffic , (trans-border traffic).
- b) right to overfly without landing.
- c) right to operate a commercial passenger flight with passengers on board between two states.
- d) right to land for a technical stop.

Answer ;

- d) right to land for a technical stop.

0421. The separation method whereby the vertical and horizontal separation may be reduced till a maximum of half the standard criteria is called ;

- a) Composite separation.
- b) Reduced separation.
- c) Combined separation.
- d) Essential separation.

Answer ;

- a) Composite separation.

0422. The SIGMET service is in the AIP , in the following part ;

- a) AGA
- b) GEN
- c) ENR
- d) MET

Answer ;

b) GEN

0423. The speed limitation for both IFR flights and VFR flights inside ATS airspace classified as B , when flying below 3050 m (10000 ft) AMSL , is ;

- a) 260 KT IAS.
- b) 250 KT TAS.
- c) not applicable.
- d) 250 KT IAS.

Answer ;

c) not applicable.

0424. The speed limitation for IFR flights inside ATS airspace classified as C , when flying below 3050 m (10000 ft) AMSL , is ;

- a) 240 KT IAS.
- b) not applicable.
- c) 250 KT IAS.
- d) 250 KT TAS.

Answer ;

b) not applicable.

0425. The speed limitation for IFR flights inside ATS airspace classified as E , when flying below 3050 m (10000 ft) AMSL , is ;

- a) 250 KT TAS.
- b) 260 KT IAS.
- c) 250 KT IAS.
- d) not applicable.

Answer ;

c) 250 KT IAS.

0426. The speed limitation for VFR flights inside ATS airspace classified as C , when flying below 3050 m (10000 ft) AMSL , is ;

- a) 250 KT TAS.
- b) 240 KT IAS.
- c) not applicable.
- d) 250 KT IAS.

Answer ;

d) 250 KT IAS.

0427. The “Standards” contained in the Annexes to the Chicago convention are to be considered ;

- a) binding for the member states that have not notified ICAO about a national difference.
- b) binding for all member states.
- c) advice and guidance for the aviation legislation within the member states.
- d) binding for all air line companies with international traffic.

Answer ;

a) binding for the member states that have not notified ICAO about a national difference.

0428. The state of design shall ensure that , there exists a continuing structural integrity program to ensure the airworthiness of the aeroplane , which includes specific information concerning corrosion prevention and control , in respect of aeroplanes ;

- a) over 5.700 kg maximum certificate take-off mass.
- b) up to 5.700 kg maximum certificate take-off mass.
- c) over 5.700 kg maximum certificate take-off and landing mass.
- d) up to 5.700 kg maximum certificate take-off and landing mass.

Answer ;

a) over 5.700 kg maximum certificate take-off mass.

0429. The STOPWAY is a defined rectangular area on the ground at the end of take-off run available prepared as a suitable area where ;

- a) a landing aircraft can be stopped if overcoming the end of runway.
- b) a landing aircraft can be stopped only in emergency.
- c) an aircraft taking-off or landing can be stopped.
- d) an aircraft can be stopped in the case of an abandoned take-off.

Answer ;

- d) an aircraft can be stopped in the case of an abandoned take-off.

0430. The surveillance radar approach shall be terminated at a distance of 2 NM from the touchdown except when as determined by the appropriate ATS authority , the accuracy of the radar equipment permits to be continued to a prescribed point less than 2 NM from the touchdown. In this case distance and level information shall be given at each ;

- a) half NM.
- b) half mile.
- c) 1.5 NM.
- d) 1 NM.

Answer ;

- a) half NM.

0431. The system notifying in advance the circumstances requiring important changes in the methods of operation , based on common effective dates , is identified by the acronym ;

- a) IFPS.
- b) EATCHIP.
- c) NOTAM.
- d) AIRAC.

Answer ;

- d) AIRAC.

0432. The temporary , long-term modification (3 months or more) and the short-term extensive or graphical information are published as follows ;

- a) Trigger NOTAM
- b) NOTAM
- c) AIP Amendments
- d) AIP Supplements

Answer ;

- d) AIP Supplements

0433. The tolerance value used to determine that mode C derived level information displayed to the controller is accurate shall be ;

- a) +/- 500 ft.
- b) +/- 200 ft.
- c) +/- 250 ft.
- d) +/- 300 ft.

Answer ;

- d) +/- 300 ft.

0434. The transfer of an aircraft from one ATC unit to another is done ;

- a) by agreement with the receiving unit.
- b) through a central control unit.
- c) automatically at the control zone boundary.
- d) with the pilot's consent.

Answer ;

- a) by agreement with the receiving unit.

0435. The units providing Air Traffic Services are ;

- a) Area Control Centre - Approach Control Office and Aerodrome Control Tower.
- b) Area Control Centre - Flight Information Region - Approach Control Office and Tower.
- c) Area Control Centre - Flight Information Centre - Approach Control Office - Aerodrome Control Tower and Air Traffic Services reporting office.
- d) Area Control Centre - Advisory Centre - Flight Information Centre - Approach Control Office and Tower.

Answer ;

- c) Area Control Centre - Flight Information Centre - Approach Control Office - Aerodrome Control Tower and Air Traffic Services reporting office.
-

0436. The validity of the instrument-rating aeroplane - IR(A) is ;

- a) 6 months.
- b) 5 years.
- c) 1 year.
- d) 2 years.

Answer ;

- c) 1 year.

0437. The VMC minima for a VFR flight inside an ATS airspace classified as B , is ;

- a) 8 km visibility when at or above 3050 m (10.000 ft) AMSL and clear of clouds.
- b) 5 NM visibility when below 3050 m (10.000 ft) AMSL , 1500 m horizontal and 300 m vertical from cloud.
- c) 5 NM visibility below 3050 m (10.000 ft) AMSL , clear of clouds.
- d) 8 km visibility when at or above 3050 m (10.000 ft) AMSL , and 1500 m horizontal and 300 m vertical from clouds.

Answer ;

- d) 8 km visibility when at or above 3050 m (10.000 ft) AMSL , and 1500 m horizontal and 300 m vertical from clouds.

0438. The VMC minima for an airspace classified as “B” above 10.000 feet MSL are ;

- a) 1 nautical mile horizontally and 1000 feet vertically from clouds , 8 km visibility.
- b) 1500 metres horizontally , 1000 feet vertically from clouds , 8 km visibility.
- c) 1 mile horizontally and 1000 feet vertically from clouds , 5 km visibility.
- d) clear of clouds , 8 km visibility.

Answer ;

- b) 1500 metres horizontally , 1000 feet vertically from clouds , 8 km visibility.

0439. The VMC minima for an airspace classified as “G” above 10.000 feet MSL are ;

- a) 1 nautical mile horizontally and 1000 feet vertically from clouds , 5 km visibility.
- b) 1500 m horizontally , 1000 feet vertically from clouds , 8 km visibility.
- c) 1 nautical mile horizontally and 1000 feet vertically from clouds , 8 km visibility.
- d) 1500 m horizontally and 1000 feet vertically from clouds , 5 km visibility.

Answer ;

- b) 1500 m horizontally , 1000 feet vertically from clouds , 8 km visibility.

0440. The Warsaw convention and later amendments deals with ;

- a) the regulation of transportation of dangerous goods.
- b) limitation of the operator’s liability for damage caused to passengers and goods transported.
- c) operator’s licence for international scheduled aviation.
- d) the security system at airports.

Answer ;

- b) limitation of the operator’s liability for damage caused to passengers and goods transported.

0441. The white dumb-bell with black perpendicular bar indicates that ;

- a) this aerodrome is using parallel runways.
- b) taxiing need not be confined to the taxiways.
- c) glider flying is performed outside the landing area.
- d) landing , take-off and taxiing is allowed on runway and/or taxiway only.

Answer ;

- b) taxiing need not be confined to the taxiways.

0442. To be able to execute a public transport flight , the minimum and maximum age (with ATPL) is ;

- a) 18 and 60 years.
- b) 17 and 59 years.
- c) 21 and 59 years.
- d) 16 and 60 years.

Answer ;

- c) 21 and 59 years.

0443. To perform a VFR flight in airspace classification E ;

- a) a clearance and/or two-way radio communication is required.
- b) a clearance and two-way radio communication is required.
- c) a clearance is required.
- d) two way radio communication is not required.

Answer ;

- d) two way radio communication is not required.

0444. "TODA" take-off distance available is ;

- a) the length of the take-off run available plus the length of clearway available (if provided).
- b) the length of the runway available plus the length of clearway available (if provided).
- c) the length of the take-off run available plus the length of the stop way.
- d) the length of the take-off run available plus the length of the stop way and clearway (if provided).

Answer ;

- a) the length of the take-off run available plus the length of clearway available (if provided).

0445. Two minutes separation may be used between departing aircraft if they are to fly on the same track , when ;

- a) the preceding aircraft is 10 kt or more faster than the following aircraft.
- b) the preceding aircraft is 30 kt or more faster than the following aircraft.
- c) the preceding aircraft is 20 kt or more faster than the following aircraft.
- d) the preceding aircraft is 40 kt or more faster than the following aircraft.

Answer ;

- d) the preceding aircraft is 40 kt or more faster than the following aircraft.

0446. Type ratings shall be established ;

- a) all the answers are correct.
- b) only aircraft certificated for operation with a minimum crew of at least two pilots.
- c) for any type of aircraft whenever considered necessary by the authority.
- d) only for aircraft certificated for operation with a minimum crew of at least two pilots and each type of helicopter.

Answer ;

- c) for any type of aircraft whenever considered necessary by the authority.

0447. Unaccompanied baggage carried by air shall be cleared under the procedure applicable to ;

- a) accompanied baggage or under another simplified customs procedure distinct from that normally applicable to other cargo.
- b) cargo but is free from any kind of declaration forms.
- c) cargo and is covered by a traffic document.
- d) cargo but clearance documents provided by airlines shall be completed by the passenger prior to shipment.

Answer ;

- a) accompanied baggage or under another simplified customs procedure distinct from that normally applicable to other cargo.

0448. Unlawful interference (Hijacking) in non RVSM airspace

If an aircraft is being subjected to unlawful interference (hijacked) in non RVSM airspace and the pilot is forced to divert from the cleared track or cruising level without being able to communicate with ATS , he shall try to ;

- a) proceed at a level which differs from the cruising level normally used for IFR flights in that area by 1000 ft if the aircraft is operated above FL290 or 500 ft if the aircraft is operated below FL290.
- b) slow the speed of the aircraft down to minimum , squawk A7700 and declare emergency on 121.5 MHz.
- c) commence as soon as possible an emergency descent in order to minimise the difference between cabin pressure and outside pressure.
- d) fly the emergency triangle and try to establish radiotelephony contact with the interference coordinator of the appropriate ATS unit on 121.5 MHz.

Answer ;

- a) proceed at a level which differs from the cruising level normally used for IFR flights in that area by 1000 ft if the aircraft is operated above FL290 or 500 ft if the aircraft is operated below FL290.

0449. Unless otherwise prescribed by the appropriate ATS authority , the horizontal radar separation minimum shall be ;

- a) 5.0 NM.
- b) 3.5 NM.
- c) 3.0 NM.
- d) 10.0 NM.

Answer ;

- a) 5.0 NM.

0450. Unless otherwise prescribed by the appropriate ATS authority , the radar controller should notify the non-radar controller when an aircraft making a radar approach is approximately ;

- a) 8 NM.
- b) 6 NM.
- c) 10 NM.
- d) 5 NM.

Answer ;

- a) 8 NM.

0451. Unless otherwise prescribed , what is the rule regarding level to be maintained by an aircraft flying IFR outside controlled airspace ?

- a) 2000 feet above the highest obstacle within 8 nautical miles of course.
- b) 1000 feet above the highest obstacle within 8 kilometres of the estimated position of the aircraft.
- c) 2000 feet above the highest obstacle within 8 kilometres of course.
- d) 1000 feet above the highest obstacle within 8 nautical miles of course.

Answer ;

- b) 1000 feet above the highest obstacle within 8 kilometres of the estimated position of the aircraft.

0452. Urgency signals

The crew of an aircraft uses the following signal in order to give notice of difficulties , which compel it to land without requiring immediate assistance ;

- a) Switching on and off three times the navigation lights.
- b) Switching on and off of the landing lights in a sequence consisting of the letter group SOS.
- c) Switching on and off three times the landing lights.
- d) The repeated switching on and off of the landing lights.

Answer ;

- d) The repeated switching on and off of the landing lights.

0453. Use of Radar in the Approach Service - Vectoring to final approach track

When an aircraft is vectored by radar to the localizer course , the angle between the interception course and the localizer course is normally 30 degrees. In accordance with Doc 4444 this angle shall not be greater than ;

- a) 40°.
- b) 35°.
- c) 50°.
- d) 45°.

Answer ;

- d) 45°.

0454. Visual aids for denoting obstacles

Low intensity obstacle lights on vehicles other than those associated with emergency or security shall be ;

- a) flashing yellow.
- b) fixed red.
- c) flashing blue.
- d) fixed blue.

Answer ;

- a) flashing yellow.

0455. Visual aids for navigation

Runway-lead-in lighting shall consist ;

- a) always of a straight row of lights towards the runway.
- b) of an arbitrary amount of green lights.
- c) of groups of at least three white lights , flashing in sequence towards the runway.
- d) of a group of at least 5 flashing yellow lights.

Answer ;

- c) of groups of at least three white lights , flashing in sequence towards the runway.

0456. Visual aids for navigation - Approach lights

The centre line and crossbar lights of a precision approach Category I lighting system shall be fixed lights , showing variable intensity of the following colour ;

- a) blue.
- b) green.
- c) white.
- d) yellow.

Answer ;

- c) white.

0457. Visual aids for navigation - Lights

Runway threshold identification lights are ;

- a) flashing white lights.
- b) flashing green lights.
- c) fixed white lights.
- d) steady yellow lights.

Answer ;

- a) flashing white lights.

0458. Visual aids for navigation - Lights

The colour of the fixed , unidirectional Runway End Lights shall be ;

- a) green.
- b) white.
- c) red.
- d) yellow.

Answer ;

c) red.

0459. Visual aids for navigation - Lights

Which is the principal composition of a precision approach Category I lighting system ?

- a) A row of lights on the extended centre line of the runway , extending over a distance of 420 m from the runway threshold and a crossbar at a distance of 250 m from the runway threshold.
- b) A row of lights on the extended centre line of the runway , extending over a distance of 600 m from the runway threshold and a crossbar at a distance of 450 m from the runway threshold.
- c) A row of lights on the extended centre line of the runway , extending over a distance of 900 m from the runway threshold and a crossbar at a distance of 300 m from the runway threshold.
- d) A PAPI or T-VASIS system.

Answer ;

c) A row of lights on the extended centre line of the runway , extending over a distance of 900 m from the runway threshold and a crossbar at a distance of 300 m from the runway threshold.

0460. Visual aids for navigation - Lights - PAPI

How does a pilot see the PAPI wing bar lights , when the position of the aircraft is far above the approach slope ?

- a) All the four units are steady white.
- b) The unit nearest to and the unit farthest from the runway are steady white , the two in the centre are flashing white.
- c) All the four units are flashing white.
- d) The unit nearest to and the unit farthest from the runway are white , the two others are red.

Answer ;

a) All the four units are steady white.

0461. Visual aids for navigation - Markings

On an aerodrome equipped with parallel runways, the designation number of each runway shall be supplemented as follows ;

- a) In case of two parallel runways by the letter “L” and “R” in the sequence from left to right.
- b) In case of three parallel runways by adding “L” to the designation of the runway farthest to the left , adding one “R” to the central runway and adding two “R” to the designation of the runway farthest to the right.
- c) In case of three parallel runways by the letter “L” and “R” for the outer runways and no letter supplement for the central runway.
- d) In case of two parallel runways by adding “10” to the left runway designation and by subtracting “10” from the right runway designation.

Answer ;

a) In case of two parallel runways by the letter “L” and “R” in the sequence from left to right.

0462. Visual aids for navigation - Runway threshold Lights

The colour of the fixed , unidirectional runway threshold and wing bar lights shall be ;

- a) yellow.
- b) flashing white.
- c) white.
- d) green.

Answer ;

d) green.

0463. Visual ground signals

A double white cross displayed horizontally in the signal area indicates that ;

- a) this area is unfit for the movement of aircraft.
- b) special precautions is needed while approaching for landing on the runway in use.
- c) the aerodrome is being used by gliders and that glider flights are being performed.
- d) special precautions must be observed due to the state of the taxiways.

Answer ;

c) the aerodrome is being used by gliders and that glider flights are being performed.

0464. Visual ground signals

A horizontal white dumb-bell with a black bar placed perpendicular to the shaft across each circular portion placed in the signal area indicates that ;

- a) aircraft are required to land and take-off on runways only , but other manoeuvres need to be confined to runways or taxiways.
- b) the aerodrome is being used by gliders and that glider flights are being performed on a parallel runway.
- c) a parallel runway system is used at this aerodrome.
- d) aircraft are required to land and take-off on runways and all other manoeuvres need to be confined to runways or taxiways.

Answer ;

- a) aircraft are required to land and take-off on runways only , but other manoeuvres need to be confined to runways or taxiways.

0465. Visual ground signals

A right-hand arrow of conspicuous colour indicates ;

- a) the position of the Aerodrome Reference Point / ARP.
- b) that turns are to be made to the right before landing and after take-off.
- c) that turns in the aerodrome circuit have to be made to the left , but gliders have to make the turns to the right.
- d) that 180 degree turns on the runway for backtrack have to be made to the right.

Answer ;

- b) that turns are to be made to the right before landing and after take-off.

0466. Visual Flight Rules

Above an altitude of 10.000 ft , flights operating within airspace Class “G” in accordance with VFR shall observe the following weather minima ;

- a) a distance from cloud : 1 Nautical Mile (NM) horizontally , 1000 ft vertically , flight visibility : 8 km.
- b) a distance from cloud : 1 Nautical Mile (NM) horizontally , 1000 ft vertically , flight visibility : 5 km.
- c) a distance from cloud : 1500 m horizontally , 1000 ft vertically , flight visibility : 5 km.
- d) a distance from cloud : 1500 m horizontally , 1000 ft vertically , flight visibility : 8 km.

Answer ;

- d) a distance from cloud : 1500 m horizontally , 1000 ft vertically , flight visibility : 8 km.

0467. Visual Flight Rules

An aircraft operating in accordance with VFR , above the sea at altitudes between 4500 ft and 9000 ft AMSL , outside controlled airspace shall maintain at least ;

- a) a distance from cloud of 600 m horizontally and 1000 ft vertically and a flight visibility of 5 km.
- b) a distance from cloud of 1500 m horizontally and 1000 ft vertically and a flight visibility of 8 km.
- c) a distance from cloud of 1000 m horizontally and 1000 ft vertically and a flight visibility of 5 km.
- d) a distance from cloud of 1500 m horizontally and 1000 ft vertically and a flight visibility of 5 km.

Answer ;

- d) a distance from cloud of 1500 m horizontally and 1000 ft vertically and a flight visibility of 5 km.

0468. Visual Flight Rules

Except when a clearance is obtained from an ATC unit , VFR flights shall not take-off or land at an aerodrome within a CTR or enter the aerodrome traffic zone or traffic pattern when the ;

- a) ceiling is less than 1000 ft or the ground visibility is less than 8 km.
- b) ceiling is less than 1500 ft or the ground visibility is less than 5 km.
- c) ceiling is less than 1000 ft or the ground visibility is less than 5 km.
- d) ceiling is less than 2000 ft or the ground visibility is less than 5 km.

Answer ;

- b) ceiling is less than 1500 ft or the ground visibility is less than 5 km.

0469. Visual signals

In flight the pilot of an aircraft observes a series of projectiles discharged from the ground at intervals of 10 seconds , each showing , on bursting , red and green lights or stars. The meaning of this signal is ;

- a) the aerodrome nearby you have chosen for landing is unsafe , do not attempt to land. Proceed to your alternate.
- b) give way to other aircraft and continue circling.
- c) notwithstanding any previous instructions , stay in the circuit , do not land for the time being.
- d) the unauthorised aircraft is flying in or about to enter a restricted , prohibited or danger area and the aircraft is to take such remedial action as may be necessary.

Answer ;

- d) the unauthorised aircraft is flying in or about to enter a restricted , prohibited or danger area and the aircraft is to take such remedial action as may be necessary.

- 0470.** VMC minima for VFR flights in Class B airspace , above 3050 m (10000 ft) AMSL , are ;
- a) 5 km visibility , 1500 m horizontal and 1000 ft vertical distance from clouds.
 - b) 8 km visibility , 1500 m horizontal and 1000 ft vertical distance from clouds.**
 - c) 8 km visibility , and clear of clouds.
 - d) No minima , VFR flights are not permitted.

Answer ;

- c) 8 km visibility , 1500 m horizontal and 1000 ft vertical distance from clouds.**
-

- 0471.** Wake turbulence - Separation between departing aircraft
The minimum separation to be applied between a LIGHT or MEDIUM aircraft taking off behind a HEAVY aircraft or a LIGHT aircraft taking off behind a MEDIUM aircraft using the same runway is ;
- a) 3 minutes.
 - b) 2 minutes.**
 - c) 1 minute.
 - d) 5 minutes.

Answer ;

- b) 2 minutes.**
-

- 0472.** What is a “barrette” ?
- a) a frangible structure on which approach lights are fixed.
 - b) three or more ground lights closely spaced together to appear as a bar of lights.**
 - c) a CAT II or III holding position.
 - d) a high obstacle near the runway and/or taxiway.

Answer ;

- b) three or more ground lights closely spaced together to appear as a bar of lights.**
-

- 0473.** What is meant when departure control instruct you to “resume own navigation” after you have been vectored to an airway ?
- a) You are still in radar contact , but must make position reports.
 - b) Advisories will no longer be issued by ATC.
 - c) You should maintain that airway by use of your navigation equipment.**
 - d) Radar Service is terminated.

Answer ;

- c) You should maintain that airway by use of your navigation equipment.**
-

- 0474.** What is the length of an approach lighting system of a precision-approach runway CAT II ?
- a) 300 m
 - b) 150 m
 - c) 600 m
 - d) 900 m**

Answer ;

- d) 900 m**
-

- 0475.** What is the maximum speed adjustment that a pilot should be requested to make when under radar control and established on intermediate and final approach ?
- a) ± 10 KT
 - b) ± 15 KT
 - c) ± 20 KT**
 - d) ± 25 KT

Answer ;

- c) ± 20 KT**
-

- 0476.** What is the minimum vertical separation between aircraft flying IFR below flight level 290 ?
- a) 1500 feet
 - b) 500 feet
 - c) 1000 feet**
 - d) 2000 feet

Answer ;

- c) 1000 feet**
-

0477. What is the minimum wake turbulence separation criteria when a Light aircraft is taking off behind a Medium aircraft and both are using the same runway ?

- a) 5 minutes
- b) 1 minute
- c) 2 minutes
- d) 3 minutes

Answer ;

- c) 2 minutes

0478. What is the shortest distance in a sequence for landing between a “Heavy” aircraft preceding a “Light” aircraft ?

- a) 2 km
- b) 10 km
- c) 3 NM
- d) 6 NM

Answer ;

- d) 6 NM

0479. What is the speed limit (IAS) in airspace class E ?

- a) 250 kt for IFR and VFR up to FL 100.
- b) 250 kt only for VFR up to FL 195.
- c) 250 kt only for IFR up to FL 100.
- d) 250 kt VFR and IFR , all levels.

Answer ;

- a) 250 kt for IFR and VFR up to FL 100.

0480. When a contracting state renders valid a licence issued by another contracting state the validity of the authorisation ;

- a) shall not extend beyond the period of validity of the licence other than for use in private flights.
- b) shall not extend more than 15 days from the date of the licence.
- c) shall not extend beyond the period of validity of the licence.
- d) the Contracting state rendering a licence valid may extend the date of the validity at its own discretion.

Answer ;

- c) shall not extend beyond the period of validity of the licence.

0481. When a controlled flight inadvertently deviates from its current flight plan , ATC has to be informed in case ;

- a) it is a deviation from the track.
- b) the TAS varies by plus or minus 5% of the TAS notified in the flight plan.
- c) the estimated time is in error by more than 10 minutes.
- d) of an emergency.

Answer ;

- b) the TAS varies by plus or minus 5% of the TAS notified in the flight plan.

0482. When a fixed-distance marking has to be provided this marking shall commence at ;

- a) 450 m from threshold.
- b) 150 m from threshold.
- c) 600 m from threshold.
- d) 300 m from threshold.

Answer ;

- d) 300 m from threshold.

0483. When a member state allows police officers , security staff , bodyguards or other agents of foreign states to carry weapons in their territory for the protection of aircraft in flight , permission for the carriage of weapons should be conditional upon ;

- a) notification of the pilot in command of a decision to permit a weapon to be carried on board his aircraft only.
- b) agreement between the state of embarkation and the state of destination.
- c) agreement between the state of embarkation and the airport of arrival.
- d) prior notification by the state of embarkation to the foreign state in which the weapons will be carried on the airport of arrival and notification of the pilot in command of a decision to permit a weapon to be carried on board his aircraft.

Answer ;

- d) Prior notification by the state of embarkation to the foreign state in which the weapons will be carried on the airport of arrival and notification of the pilot in command of a decision to permit a weapon to be carried on board his aircraft.

0484. When a person is found inadmissible and is returned to the operator for transport away from the territory of the state , the operator ;

- a) shall not be preclude from recovering from such person any transportation costs arising from his(her) inadmissibility.
- b) is not responsible for the person inadmissible for entry in the receiving state.
- c) and the state of the operator are both responsible for the person inadmissible.
- d) shall not recover from such person any transportation costs arising from his(her) inadmissibility.

Answer ;

- a) shall not be preclude from recovering from such person any transportation costs arising from his(her) inadmissibility.

0485. When a RADAR operator says the following to an aircraft ; “fly heading 030” , the pilot must fly heading ;

- a) 030° true , in still air conditions (thereby flying the true track).
- b) 030° true.
- c) 030° magnetic.
- d) 030° magnetic in still air conditions (thereby flying the magnetic track).

Answer ;

- c) 030° magnetic.

0486. When an aircraft has sustained damage , the aircraft shall be allowed to resume its flight , if ;

- a) the state of design and the state of manufacture inform the state of registry that the aircraft is still airworthy.
- b) the state of registry , the state of design and the state of manufacture consider that the aircraft is still airworthy.
- c) the state of registry considers that the damage sustained is of a nature such that the aircraft is still airworthy.
- d) the state of manufacture informs the state of registry that the damage sustained is of a nature such that the aircraft is still airworthy.

Answer ;

- c) the state of registry considers that the damage sustained is of a nature such that the aircraft is still airworthy.

0487. When an aircraft is experiencing difficulties , triggering of the alert phase is the responsibility of ;

- a) air traffic control and flight information centres.
- b) search and rescue co-ordination centres.
- c) control centres only.
- d) air traffic co-ordination centres.

Answer ;

- a) air traffic control and flight information centres.

0488. When an aircraft subjected to an unlawful interference has landed it shall notify by the most expeditious means of the State of registry of the aircraft and the State of the operator of the landing and shall similarly transmit all other relevant information to the ;

- a) two aforementioned States , each State whose citizens suffered fatalities or injuries , each State whose citizens are known to be on board the aircraft and the ICAO.
- b) two aforementioned States , each State whose citizens suffered fatalities or injuries , each State whose citizens were detained as hostages , each State whose citizens are known to be on board the aircraft and the ICAO.
- c) two aforementioned States , each State whose citizens suffered fatalities or injuries on board the aircraft and the ICAO.
- d) two aforementioned States and the ICAO.

Answer ;

- b) two aforementioned States , each State whose citizens suffered fatalities or injuries , each State whose citizens were detained as hostages , each State whose citizens are known to be on board the aircraft and the ICAO.

0489. When an aircraft will pass through the level of another aircraft on the same track , the following minimum longitudinal separation shall be provided ;

- a) 5 minutes at the time the level is crossed.
- b) 20 minutes at the time the level is crossed.
- c) 15 minutes at the time the level is crossed.
- d) 10 minutes at the time the level is crossed.

Answer ;

- c) 15 minutes at the time the level is crossed.
-

0490. When are ATIS broadcasts updated ?

- a) Only when the ceiling and/or visibility changes by a reportable value.
- b) Upon receipt of any official weather , regardless of content change or reported values.
- c) Every 30 minutes if weather conditions are below those for VFR , otherwise hourly.
- d) Only when weather conditions change enough to require a change in the active runway or instrument approach in use.

Answer ;

- b) Upon receipt of any official weather , regardless of content change or reported values.

0491. When conducting a surveillance radar approach , the radar controller shall terminate the surveillance radar approach , except as determined by the appropriate ATS authority , at a distance of ;

- a) 1 NM from touchdown.
- b) 3 NM from touchdown.
- c) 2.5 NM from touchdown.
- d) 2 NM from touchdown.

Answer ;

- d) 2 NM from touchdown.

0492. When independent parallel approaches are being conducted and vectoring to intercept the ILS localizer course or MLS final approach track , the final vector shall be such as to enable the aircraft to intercept the ILS localizer course or MLS final approach track at an angle not greater than ;

- a) 30 degrees.
- b) 15 degrees.
- c) 20 degrees.
- d) 25 degrees.

Answer ;

- a) 30 degrees.

0493. When independent parallel approaches are being conducted to parallel runways and vectoring to intercept the ILS localizer course or MLS final approach track , the vector shall be such as to enable the aircraft to be established on the ILS localizer course or MLS final approach track in level flight for ;

- a) at least 2.5 NM prior to intercepting the ILS glide path or specified MLS elevation angle.
- b) at least 2.0 NM prior to intercepting the ILS glide path or specified MLS elevation angle.
- c) at least 1.5 NM prior to intercepting the ILS glide path or specified MLS elevation angle.
- d) at least 3.0 NM prior to intercepting the ILS glide path or specified MLS elevation angle.

Answer ;

- b) at least 2.0 NM prior to intercepting the ILS glide path or specified MLS elevation angle.

0494. When it becomes apparent that an aircraft is in difficulty , the decision to initiate the alert phases is the responsibility of the ;

- a) flight information or control organisations.
- b) search and rescue co-ordination centres.
- c) operational air traffic control centres.
- d) air traffic co-ordination services.

Answer ;

- c) operational air traffic control centres.

0495. When letters are used for registration mark combinations shall not be used which might be confused with urgent signals for example ;

- a) LLL.
- b) RCC.
- c) FFF.
- d) TTT.

Answer ;

- d) TTT.

0496. When letters are used for registration mark combinations shall not be used which might be confused with urgent signals for example ;

- a) DDD.
- b) LLL.
- c) RCC.
- d) PAN.

Answer ;

- d) PAN.

0497. When letters are used for the registration mark combinations shall not be used which might be confused with the ;
- a) three letters combinations used in the international code of signals.
 - b) four letter combinations beginning with Q.
 - c) five letter combinations used in the international code of signals.
 - d) letters used for ICAO identification documents.

Answer ;

- c) five letter combinations used in the international code of signals.
-

0498. When letters are used for the registration mark combinations shall not be used which might be confused with urgent or distress signals for example ;

- a) DDD.
- b) LLL.
- c) XXX.
- d) RCC.

Answer ;

- c) XXX.
-

0499. When mixing or contact does take place between passengers subjected to security control and other persons not subjected to such control after the security screening points at airports serving international civil aviation have been passed ;

- a) only the passengers cabin baggage are to be re screened.
- b) the passengers concerned and their cabin baggage shall be rescreened before boarding an aircraft.
- c) the persons not subjected to security control shall be identified.
- d) only the passengers are to be re screened.

Answer ;

- b) the passengers concerned and their cabin baggage shall be rescreened before boarding an aircraft.
-

0500. When on a RNP 1 route is indicated A342 Z , means that all turns shall be made within the allowable RNP tolerance of a tangential arc between the straight leg segments with a radius of ;

- a) 25 NM on the route between 30° and 90° at and below FL190.
- b) 15 NM on the route between 30° and 90° at and above FL 200.
- c) 22.5 NM on the route between 30° and 90° at and above FL 250.
- d) 15 NM on the route between 30° and 90° at and below FL 190.

Answer ;

- d) 15 NM on the route between 30° and 90° at and below FL 190.
-

0501. When on a RNP 1 route is indicated B235 Y , means that all turns shall be made within the allowable RNP tolerance of a tangential arc between the straight leg segments defined with a radius of ;

- a) 22.5 NM between 30° and 90° at and above FL260.
- b) 20 NM on the route between 30° and 90° at and above FL200.
- c) 22.5 NM between 30° and 90° at and above FL200.
- d) 25.0 NM on the route between 30° and 90° at and above FL 250.

Answer ;

- c) 22.5 NM between 30° and 90° at and above FL200.
-

0502. When radar identification of aircraft has been achieved , the radar controller shall ;

- a) inform the aircraft only if radar identification has been achieved without availability of SSR.
- b) inform the aircraft only if communication's load permits it.
- c) not advise the aircraft before issuing instructions.
- d) inform the aircraft prior to issue any instructions or advice based on the use of radar.

Answer ;

- d) inform the aircraft prior to issue any instructions or advice based on the use of radar.
-

0503. When "Secondary Radar" is used , an aircraft may be identified by one of the following procedures ;

- a) To request pilot to set transponder on position "OFF".
- b) To request pilot to set transponder on position "ON".
- c) To request pilot to switch from "ON" to "STBY".
- d) Observation of compliance with an instruction to operate transponder from "ON" to "STBY" and back to "ON".

Answer ;

- d) Observation of compliance with an instruction to operate transponder from "ON" to "STBY" and back to "ON".
-

0504. When surveillance radar approaches are to be continued to the threshold of the runway transmission should not be interrupted for intervals of more than five seconds while the aircraft is within a distance of ;

- a) 1.5 NM from the touchdown.
- b) 2 NM from the touchdown.
- c) 4 NM from the touchdown.
- d) 3 NM from the touchdown.

Answer ;

- c) 4 NM from the touchdown.

0505. When the holders of aircraft transport pilot licences aeroplane and helicopter have passed their 40th birthday the medical examination shall be reduced from ;

- a) 24 months to 12 months.
- b) 12 months to 3 months.
- c) none of the answers are correct.
- d) 12 months to 6 months.

Answer ;

- d) 12 months to 6 months.

0506. When the Mach number technique (MNT) is being applied , and the preceding aircraft shall maintain a mach number equal to or greater than the following aircraft a RNAV distance based separation minimum may be used on the same direction tracks in lieu of 10 minutes longitudinal separation minimum. The distance is ;

- a) 70 NM.
- b) 100 NM.
- c) 80 NM.
- d) 60 NM.

Answer ;

- c) 80 NM.

0507. When the transponder appears to be unserviceable prior to departure and restore is impossible , than ;

- a) you must indicate the failure in the flight plan , after which the ATC will endeavour to provide for continuation of the flight.
- b) you are not allowed to commence the flight.
- c) the flight can only continue in the most direct manner.
- d) departure to the nearest suitable airport where repair can be effected is allowed.

Answer ;

- d) departure to the nearest suitable airport where repair can be effected is allowed.

0508. When vectoring an aircraft to intercept the localizer course , the final vector furnished shall be such as to enable the aircraft to intercept the localizer course at an angle not greater than ;

- a) 20 degrees.
- b) 25 degrees.
- c) 15 degrees.
- d) 30 degrees.

Answer ;

- d) 30 degrees.

0509. Whenever ATIS is provided , the broadcast information shall be updated ;

- a) at least every half an hour independently of any significant change.
- b) immediately a significant change occurs.
- c) as prescribed by the meteorological office.
- d) as prescribed by the state.

Answer ;

- b) immediately a significant change occurs.

0510. Whenever ATIS is provided , the preparation and dissemination of the ATIS message shall be the responsibility of ;

- a) the air traffic services.
- b) the unit as prescribed the states.
- c) the meteorological office serving the aerodrome(s).
- d) both air traffic services and the meteorological office.

Answer ;

- a) the air traffic services.

0511. Whenever unlawful interference with an aircraft is suspected , and where automatic distinct display of SSR Mode A code 7500 and code 7700 is not provided , the radar controller shall attempt to verify this suspicion by ;

- a) setting the SSR decoder to mode A 7700 then to standby and thereafter to code 7500.
- b) setting the SSR decoder to mode A code 7500 and thereafter to code 7700.
- c) setting the SSR decoder to mode A code 7000 and thereafter to code 7500.
- d) setting the SSR decoder to mode A 7500 then to standby and thereafter to code 7700.

Answer ;

- b) setting the SSR decoder to mode A code 7500 and thereafter to code 7700.

0512. Where a “Secondary Surveillance Radar” (SSR) is not available , radar identification may be achieved by one of the following procedures ;

- a) to instruct the pilot to execute one or more changes of 10°.
- b) to instruct the pilot to execute one or more changes of 20° or more.
- c) to instruct the pilot to execute one or more changes of 30° or more.
- d) to instruct the pilot to execute one or more changes of 45°.

Answer ;

- c) to instruct the pilot to execute one or more changes of 30° or more.

0513. Where an upper flight information region (UIR) is established , the procedures applicable there in ;

- a) have to be as agreed at the regional air navigation meetings.
- b) have to be as indicated by ICAO council.
- c) need not to be identical with those applicable in the underlying flight information region.
- d) has to be the same as the underlying flight information region.

Answer ;

- c) need not to be identical with those applicable in the underlying flight information region.

0514. Where State has not established minimum IFR altitudes , the minimum height of an aircraft above the highest obstacle over high terrain , or in mountainous areas shall be for an IFR flight ;

- a) at least 1000 feet within 8 km of the estimated position.
- b) at least 1000 feet within 5 km of the estimated position.
- c) at least 2000 feet within 8 km of the estimated position.
- d) at least 2000 feet within 5 km of the estimated position.

Answer ;

- c) at least 2000 feet within 8 km of the estimated position.

0515. Which action shall be taken by an aircraft in the traffic pattern of an aerodrome , experiencing radio failure to indicate difficulties which compel it to land without requiring immediate assistance ?

- a) Switching on and off four times the landing lights.
- b) Switching on and off four times the navigation lights.
- c) Switching on and off three times the landing lights.
- d) The repeated switching on and off of the landing lights.

Answer ;

- d) The repeated switching on and off of the landing lights.

0516. Which body of ICAO finalises the Standard and Recommended Practices (SARPS) for submission for adoption ?

- a) The Air Navigation Commission.
- b) The Assembly.
- c) The Council.
- d) The Regional Air Navigation meeting.

Answer ;

- a) The Air Navigation Commission.

0517. Which “code letter” shall be chosen to identify a taxiway to be used by an aircraft having a wheel base of 15 m ?

- a) Code letter “E”.
- b) Code letter “B”.
- c) Code letter “C”.
- d) Code letter “D”.

Answer ;

- c) Code letter “C”.

0518. Which code shall be used on Mode “A” to provide recognition of an aircraft subjected to unlawful interference ?

- a) Code 2000.
- b) Code 7600.
- c) Code 7700.
- d) Code 7500.

Answer ;

- d) Code 7500.
-

0519. Which code shall be used on Mode “A” to provide recognition of an emergency aircraft ?

- a) Code 7500.
- b) Code 7000.
- c) Code 7700.
- d) Code 7600.

Answer ;

- c) Code 7700.
-

0520. Which condition is requested so that an aerodrome may be considered controlled ?

- a) The aerodrome shall be located within a controlled airspace.
- b) The aerodrome shall be located within a Control Zone.
- c) The aerodrome shall be located within a Control Zone (CTR) and provided with a Control Tower.
- d) The aerodrome shall be provided with a Control Tower.

Answer ;

- d) The aerodrome shall be provided with a Control Tower.
-

0521. Which does ATC Term “Radar contact” signify ?

- a) Your aircraft has been identified on the radar display and radar flight instructions will be provided until radar identification is terminated.
- b) Your aircraft has been identified and you will receive separation from all aircraft while in contact with this radar facility.
- c) You will be given traffic advisories until advised that the service has been terminated or that radar contact has been lost.
- d) ATC is receiving your transponder and will furnish vectors and traffic advisories until you are advised that contact has been lost.

Answer ;

- a) Your aircraft has been identified on the radar display and radar flight instructions will be provided until radar identification is terminated.
-

0522. Which freedom of the air will be exercised by an airline planning a flight that will require a technical stop in a neighbouring State ?

- a) 4th freedom
- b) 3th freedom
- c) 1th freedom
- d) 2th freedom

Answer ;

- d) 2th freedom
-

0523. Which information is not included in Instrument Approach Charts (IAC) in the AIP ?

- a) OCA or OCH.
- b) Obstacles penetrating the obstacle free area in the final approach sector.
- c) Any addition to minima when the aerodrome is used as alternate.
- d) DME-frequencies.

Answer ;

- c) Any addition to minima when the aerodrome is used as alternate.
-

0524. Which of the following actions shall be taken in case of a controlled flight deviates from the track ?

- a) Notify ATC of the new track immediately and comply with instructions.
- b) If VMC , maintain this condition , waiting for the ATC instructions.
- c) Inform the ATC unit immediately.
- d) Adjust the heading of aircraft to regain track as soon as practicable.

Answer ;

- d) Adjust the heading of aircraft to regain track as soon as practicable.
-

0525. Which of the following alternatives describes the complete CAT 1 (Calvert) type of approach light system ?

- a) 3 crossbars , centre line with 3 , 2 or 1 lamp per light unit.
- b) 5 crossbars , centre line with 3 , 2 and 1 lamp per light unit.**
- c) 4 crossbars , centre line with 3 or 2 lamps per light unit.
- d) 3 crossbars , centre line with 3 or 2 lamps per light unit.

Answer ;

- b) 5 crossbars , centre line with 3 , 2 and 1 lamp per light unit.**
-

0526. Which of the following Annexes to the Chicago convention contains international standards and recommended practices for air traffic services (ATS) ?

- a) Annex 14
- b) Annex 11**
- c) Annex 17
- d) Annex 6

Answer ;

- b) Annex 11**
-

0527. Which of the following Annexes to the Chicago convention contains minimum specifications for a crew licence to have international validity ?

- a) Annex 1**
- b) Annex 3
- c) Annex 2
- d) Annex 4

Answer ;

- a) Annex 1**
-

0528. Which of the following Annexes to the Chicago convention contains minimum specifications for the design of aerodromes ?

- a) Annex 14**
- b) Annex 6
- c) Annex 11
- d) Annex 10

Answer ;

- a) Annex 14**
-

0529. Which of the following correctly lists special purpose codes that are to be used in conjunction with Secondary Surveillance Radar (SSR) ?

- a) Distress 7700 , Hijacking 7500 , Communication failure 7600.**
- b) Distress 7500 , Hijacking 7700 , Communication failure 7600.
- c) Distress 7700 , Hijacking 7600 , Communication failure 7500.
- d) Distress 7600 , Hijacking 7500 , Communication failure 7700.

Answer ;

- a) Distress 7700 , Hijacking 7500 , Communication failure 7600.**
-

0530. Which of the following is obligating for members of ICAO ?

- a) ICAO must be informed about differences from the standards in any of the Annexes to the convention.**
- b) ICAO must be informed about new flight crew licenses and any suspended validity of such licenses.
- c) ICAO must be informed about changes in the national regulations.
- d) ICAO shall approve the pricing of tickets on international airline connections.

Answer ;

- a) ICAO must be informed about differences from the standards in any of the Annexes to the convention.**
-

0531. Which of the following statements regarding aerodrome control service is correct ?

- a) An aircraft entering the traffic circuit without permission of ATC , will be cleared to land if this is desirable.**
- b) Suspension of VFR operations can not be initiated by the aerodrome controller.
- c) The aerodrome control service is a service provided for the purpose of preventing collisions between aircraft on the movement area.
- d) ATC permission is required for entering the apron with a vehicle.

Answer ;

- a) An aircraft entering the traffic circuit without permission of ATC , will be cleared to land if this is desirable.**
-

0532. Which of the following statements regarding Alerting service is correct ?
- a) Alerting Service and Flight Information Service are often provided by the same ATS unit.
 - b) The distress phase is established when an aircraft is known or believed to be the subject of unlawful interference.
 - c) Aircraft in the vicinity of an aircraft known or believed to be the subject of unlawful interference, shall be informed about this.
 - d) The Alert phase is established when no communication has been received from an aircraft within a period of thirty minutes after the time a communication should have been received.

Answer ;

- a) Alerting Service and Flight Information Service are often provided by the same ATS unit.
-

0533. Which provisions on a VFR-flight in Class E airspace are CORRECT ?
- a) Service provided : Traffic Information as far as practical , ATC Clearance not required.
 - b) Service provided : Air Traffic Control Service , ATC Clearance required.
 - c) Service provided : Air Traffic Control Service , ATC Clearance not required.
 - d) Service provided : Traffic Information as far as practical , ATC Clearance required.

Answer ;

- a) Service provided : Traffic Information as far as practical , ATC Clearance not required.
-

0534. Which statement is correct ?
- a) The upper limit of a CTR shall be established at a height of at least 3000 ft AMSL.
 - b) The lower limit of a TMA shall be established at a height of at least 700 ft AGL.
 - c) The lower limit of an UIR may coincide with an IFR cruising level.
 - d) The lower limit of a CTA shall be established at a height of at least 1500 ft AGL.

Answer ;

- b) The lower limit of a TMA shall be established at a height of at least 700 ft AGL.
-

0535. Which statement is correct ?
During a “Visual Approach” in Controlled Airspace (Class C) ;
- a) the pilot to apply separation with other traffic.
 - b) ATC will apply separation with other traffic.
 - c) ATC will apply separation with other arriving traffic.
 - d) ATC will apply separation only with other IFR-traffic.

Answer ;

- b) ATC will apply separation with other traffic.
-

0536. Which statement regarding approach control service is correct ?
- a) If it is anticipated that an aircraft has to hold for 30 minutes or more , an Expected Approach Time will be transmitted by the most expeditious means to the aircraft.
 - b) An approach sequence shall be established according to the sequence of initial radio contact between aircraft and approach control.
 - c) During a visual approach an aircraft is maintaining its own separation.
 - d) Approach control have to advise the aircraft operators about substantial delays in departure in any event when they are expected to exceed 45 minutes.

Answer ;

- a) If it is anticipated that an aircraft has to hold for 30 minutes or more , an Expected Approach Time will be transmitted by the most expeditious means to the aircraft.
-

0537. While on IFR flight , a pilot has an emergency which causes a deviation from an ATC clearance. What action must be taken ?

- a) Squawk 7700.
- b) Request an amended clearance or cancel the IFR flight plan.
- c) Submit a detailed report to ATC within 24 hours.
- d) The appropriate ATC unit shall be notified of the action taken as soon as circumstances permit.

Answer ;

- d) The appropriate ATC unit shall be notified of the action taken as soon as circumstances permit.
-

0538. While taxiing an aircraft receives from the airport controller the following light signal ; a series of green flashes. This signal means that the aircraft ;

- a) must return to its point of departure.
- b) must stop.
- c) is cleared for take-off.
- d) may continue to taxi towards the take-off area.

Answer ;

- d) may continue to taxi towards the take-off area.

0539. While taxiing an aircraft receives the following light signal from the control tower ; series of red flashes. This signal means that the aircraft ;

- a) may continue to taxi to the take-off area.
- b) must return to its point of departure.
- c) must vacate the landing area in use.
- d) must stop.

Answer ;

- c)** must vacate the landing area in use.
-

0540. Whilst flying in an aerodrome's traffic circuit , an aircraft receives a series of green flashes from the tower. The aircraft ;

- a) is cleared to land.
- b) must give way to another aircraft.
- c) must come back to land and the landing clearance will be sent in due time.
- d) must land immediately and clear the landing area.

Answer ;

- c)** must come back to land and the landing clearance will be sent in due time.
-

0541. Who is responsible , under Annex 13 of the Chicago convention for the initiation of an accident investigation ?

- a) The law enforcement authorities of the state in which the aircraft is registered.
- b) The aircraft manufacturer.
- c) Operators of the same aircraft type.
- d) The government of the state in which the accident took place.

Answer ;

- d)** The government of the state in which the accident took place.
-

0542. Within the Annex to the ICAO convention that specifies dimensions of aerodromes is a specific dimension given for the approach light system for CAT 1 ILS. What should be the length of this approach light system ?

- a) 900 metres
- b) 1000 metres
- c) 420 metres
- d) 1200 metres

Answer ;

- a)** 900 metres
-

0543. Within the Annex to the ICAO convention that specifies dimensions of aerodromes are codes for different runways. Which is the minimum width of a runway with runway code 4 ?

- a) 40 metres
- b) 35 metres
- c) 45 metres
- d) 50 metres

Answer ;

- c)** 45 metres
-

0544. You may act as a flight instructor to carry out flight instruction for the issue of a PPL ;

- a) with an ATPL.
- b) with a theoretical CPL examination plus flight instructor rating.
- c) with a CPL.
- d) with a PPL plus flight instructor rating.

Answer ;

- b)** with a theoretical CPL examination plus flight instructor rating.
-

0545. You may act as a flight instructor to carry out flight instruction for the issue of a PPL ;

- a) with a CPL.
- b) with a PPL plus flight instructor rating.
- c) with a valid licence plus flight instructor rating.
- d) with a PPL plus CPL theory.

Answer ;

- c)** with a valid licence plus flight instructor rating.
-

0546. You receive an IFR enroute clearance stating ; Clearance expires at 0920. What does it mean ?

- a) If not airborne until 0920 , a new clearance has to be issued.
- b) After 0920 return to the ramp and file a new flight plan.
- c) Do not take off before 0920.
- d) The take off clearance is expected at 0920.

Answer ;

- a) If not airborne until 0920 , a new clearance has to be issued.
-